

evox PLATFORM INCLUDED | Ex INCLUDED

300M SERIES

IE2-IE3

Modular planetary gearboxes

Bonfiglioli

Chapter	Description	Page
GENERAL INFORMATION		**2**
1	Symbols and units of measure	2
2	Introduction	4
3	Allowed temperature limits	4
4	Specifications	5
5	Versions	6
6	Output torque	8
7	Power	9
8	Efficiency	10
9	Reduction ratio	10
10	Angular speed	10
11	Service factor	10
12	Service factor requested by application	11
13	Life factor	11
14	Product selection	12
15	Installation	30
16	Lubrication	32
17	Storage	35
18	Supply conditions	35
SERIES 300M MODULAR PLANETARY GEARBOXES		**36**
19	300M Gearbox designation	36
20	3/V_M Gearbox designation	38
21	3/A Gearbox designation	40
22	Motor designation	42
23	Additional Options	43
24	Mounting position	45
25	Rating charts	49
26	Dimensions	262
CUSTOMER'S SHAFT		**472**
TORQUE ARM		**475**
TORQUE ARM KIT FOR FP VERSIONS		**475**

Chapter	Description	Page
NEGATIVE MULTIDISC BRAKE AND HYDRAULIC MOTORS		**476**
H1	Symbols and units of measure	476
H2	Negative multidisc brake	476
H3	Inputs for hydraulic motors	477
H4	Hydraulic motors	487
H5	Technical features	487
H6	Designation	488
H7	Displacement selection	489
H8	Checking	489
H9	Technical data MG motors	490
H10	Dimensions MG motors	492
H11	Technical databrakes for MG motors	493
H12	Installation	493
PLANETARYM GEARBOX SERIES 300M ATEX CONFIGURATION		**496**
A1	Scope of document	496
A2	Introduction to the atex directives	496
A3	Use, installation and maintenance	498
A4	Peculiarities of 300M series gear units compliant with directive Atex	498
A5	Ordering numbers	506
A6	Declaration of conformity	508
ELECTRIC MOTORS		**510**
M1	Symbols and units of measurement	510
M2	Introduction	511
M3	General characteristics	513
M4	Motor designation	515
M5	Variants and options	519
M6	Mechanical features	521
M7	Electrical characteristics	526
M8	Asynchronous brake motors	538
M9	DC BRAKE MOTORS TYPE BXN-BX-BE-BN_FD AND MXN-MX-ME-M_FD	539
M10	AC BRAKE MOTORS TYPE BXN-BX-BE-BN_FA AND MXN-MX-ME-M_FA	545
M11	Brake release systems	549
M12	Options	551
M13	Tables of motors correlation	565
M14	Motor rating charts BXN-MXN	568
M15	Motors dimensions BXN-MXN	570
M16	Motor rating charts BX-MX	574
M17	Motors dimensions BX-MX	581
M18	Motor rating charts BE-ME	589
M19	Motors dimensions BE-ME	603
M20	Motor rating charts BN-M	607
M21	Motors dimensions BN-M	624

Revisions

Refer to page 632 for the catalogue revision index. Visit www.bonfiglioli.com to search for catalogues with up-to-date revisions.

1 SYMBOLS AND UNITS OF MEASURE

Symbols	Units of Measure	Description
$A_{c\ 1,2}$	[N]	Calculated thrust load
$A_{n\ 1,2}$	[N]	Rated thrust load
A_{r2}	[N]	Thrust load at gearbox output shaft
F_h	–	Lifetime factor for gearbox calculation
$F_{h\ 1,2}$	–	Lifetime factor for bearing calculation
$f_{n\ 1,2}$	–	Speed factor referred to input and output shaft loading
f_L	–	Lifetime factor
f_m	–	Increase factor
$f_{h\ 1,2}$	–	Load corrective factor on shafts
f_S	–	Service factor
f_S'	–	Service factor required by the application
f_t	–	Thermal factor
f_v	–	Speed factor
h	[h]	Lifetime in hours
i	–	Reduction ratio
K_a	–	Axial load duty factor
K_r	–	Radial load factor
l	–	Intermittence factor
M_2	[Nm]	Torque delivered to output shaft
M_{c2}	[Nm]	Calculated torque at gearbox output
M_{2REF}	[Nm]	Reference torque
M_{n2}	[Nm]	Gearbox rated output torque
M_{2max}	[Nm]	Gearbox max. output torque
Mb	[Nm]	Rated brake torque
$M_{r\ 1,2}$	[Nm]	Required torque at gearbox
$n_{1,2}$	[min^{-1}]	Angular speed
p	[bar]	Hydraulic oil pressure
P_1	[kW]	Max transmissible power at gearbox input
P_1'	[kW]	Transmitted power at gearbox input
P_2	[kW]	Transmitted power at gearbox output
P_n	[kW]	Motor rated power
P_{r1}	[kW]	Required input power
P_{r2}	[kW]	Output power at n_2 max
P_{r2}'	[kW]	Output power at n_2 min
P_S	[kW]	Excess power
P_T	[kW]	Gearbox thermal capacity
Q	[l/min]	Hydraulic flow rate
$R_{c\ 1,2}$	[N]	Calculated radial load
$R_{n1\ 1,2}$	[N]	Rated radial load at shaft mid-point
$R_{x\ 1,2}$	[N]	Rated radial load at gearbox re-calculated with respect to different load application points
t_a	[°C]	Ambient temperature
t_S	[°C]	Surface temperature
t_o	[°C]	Oil temperature
V	[cm^3]	Hydraulic motor displacement
V_c	[cm^3]	(Theoretical) Hydraulic motor displacement
X	[mm]	Load application distance from shaft shoulder
η_d	–	Dynamic efficiency
Z	–	Frequency of starts

$_1$ value applies to input shaft

$_2$ value applies to output shaft

	Symbol referring to weight of gearboxes.
	Columns marked with this symbol indicate the reference page showing dimensions.
	This symbol identifies reference page number.
	DANGER - WARNING This symbol indicates situations of danger, which if ignored, may result in serious injury to the operator.
	IMPORTANT This symbol indicates important technical information.
	Apply to equipment complying with “ATEX” Directive
	These symbols identify the mounting positions of accessories.
	These symbols identify the position of gearbox input (black-filled areas).

	The number associated with the wrench symbol indicates the tightening torque for friction coupling screws.
	Negative multidisc brake.
	Hydraulic motor connection.
	Cover for standard input flanging.
	Inline units.
	Right angle units.
	Worm-planetary combined design.
	Bevel helical-planetary combined design.

2 INTRODUCTION

This catalogue presents BONFIGLIOLI RIDUTTORI's range of Series 300M modular planetary gearboxes.
The range has been expanded and integrated with new sizes, technical improvements and enhanced modularity right through to the larger sizes. This feature signifies greater flexibility in internal production to ensure quick availability of products in the sizes and types requested either directly from the company or from the many affiliates belonging to the BONFIGLIOLI sales network in various countries around the world.

The gearboxes are tested in conformity with the following standards:

ISO 6336 : 2006 - method B for gears
ISO 281 for bearings
DIN 743 : 2012 for shafts

Symbols	Description / Condition	Value (*)	
		Synthetic Oil	Mineral Oil
t_a	Ambient temperature		
$t_{au\ min}$	Minimum operating ambient temperature	**-30°C**	**-10°C**
$t_{au\ Max}$	Maximum operating ambient temperature	**+50°C**	**+40°C**
$t_{as\ min}$	Minimum storage ambient temperature	**-40°C**	**-10°C**
$t_{as\ Max}$	Maximum storage ambient temperature	**+50°C**	**+50°C**
t_s	Surface temperature		
$t_{s\ min}$	Minimum gearbox surface temperature starting with partial load (#)	**-25°C**	**-10°C**
$t_{sc\ min}$	Minimum gearbox surface temperature starting with full load	**-10°C**	**-5°C**
$t_{s\ Max}$	Maximum casing surface temperature during continuous operation (measured next to the gearbox input)	**+100°C**	**+100°C** (@)
t_o	Oil temperature		
$t_{o\ Max}$	Maximum oil temperature during continuous operation	**+95°C**	**+95°C** (@)

(*) = Refer to the table "Selection of the optimal oil viscosity" for further information about minimum and maximum values of different oil viscosity and for using hydraulic circuits. For values of t_a < -20°C and t_s, t_o > 80 °C, choose (as permitted in the product configuration stage) the sealing type of the most suitable material to the type of application. If needed contact Bonfiglioli Technical Service.

(@) = Continuous operation it is not advised if t_s and t_o range is 80°C to 95 °C.

(#) = For full load start-up it is recommended to ramp-up and provide for greater absorption of the motor. If needed, contact Bonfiglioli Technical Service.

3 ALLOWED TEMPERATURE LIMITS

4 SPECIFICATIONS

The 300M series consist of a range of multi-purpose planetary gearboxes that can be operated by either hydraulic or electric motors. Basic features are:

- 20 frame sizes of modular design
- output torque up to 1.286.700 Nm
- transmissible power up to 1050 kW
- ratios from 3,4:1 to 5234:1
- versions:
  - in-line with 1 to 4 reductions
  - right angle (spiral bevel gear set into first stage) with 2 to 4 reductions
- combinations with:
  - worm gear units
  - bevel-helical gear units
- flange, foot and shaft mounting arrangements
- slow output shafts: keyed, splined male, splined hollow, shrink disk mounted
- input adaptors for:
  - IEC-normalised electric motors
  - integral motor for in-line units up to size 307 and for units combined with bevel helical and worm gears
  - hydraulic motors by major manufacturers and according to SAE J744C
- parallel input shafts
- gearmotors with:
  - electric motors IEC
  - hydraulic orbital motors by BONFIGLIOLI TRASMITAL MG
- negative hydraulic parking brakes for operation by hydraulic motors
- output shaft accessories:
  - flanges
  - pinions
  - splined bars
  - shrink discs

More design features:

- high ratio of transmissible torque to overall dimensions
- high overhung and axial load capacity due to heavy duty tapered roller bearings featured on H and P versions
- high efficiency
- inner parts are coupled through splined connections rather than keys
- planetary gears mounted onto self-centering carriers to ensure the most even load distribution among planetary gears
- housing made of spheroidal cast iron.

(A 1)

Configuration	Power	Torque	Ratios	Efficiency	Noise level
	$0.25 \le P_n$ [kW] ≤ 55	$M_{2REF} \le 1286700$ Nm	$3.4 \le i \le 2916$	High	Medium
	$0.25 \le P_n$ [kW] ≤ 55	$M_{2REF} \le 656000$ Nm	$7 \le i \le 953$	High	Medium
	$0.12 \le P_n$ [kW] ≤ 22	$M_{2REF} \le 656000$ Nm	$370 \le i \le 5234$	Medium	Low
	$0.12 \le P_n$ [kW] ≤ 22	$M_{2REF} \le 15680$ Nm	$18.7 \le i \le 731$	High	Low

5 VERSIONS

A INPUT

B REDUCTIONS

A

1 Orbital hydraulic motor MG with/without brake
2 Hydraulic motor
3 Hydraulic motor setting
4 Cover
5 Negative brake
6 Compact electric motor
7 IEC electric motor
8 Electric motor setting
9 Electric motor connection with integrated fan
10 Input shaft
11 Solid input shaft with fan

B

12 Right-angle reduction stage
13 Single planetary reduction stage
14 Two or more planetary reduction stages
15 Planetary reduction combined with wormgear unit
16 Planetary reduction stage combined with helical bevel gear unit



C

17 **MC/MZ** - Keyed or splined solid shaft output
18 **HC/HZ** - Keyed or splined heavy duty solid output shaft
19 **PC/PZ** - Output with support bracket and keyed or splined solid shaft
20 **FZ** - Splined hollow output shaft
21 **FP** - Hollow output shaft for shrink disc
22 **HC** - Parallel solid output shaft
23 **HZ** - Splined solid output shaft
24 **FZ** - Splined hollow output shaft
25 **FP** - Hollow output shaft for shrink disc
26 **PC** - Foot mount
27 **VK** - Reinforced output with parallel shaft for stirrers and mixers
28 **FDK** - Hollow shaft with double keyway
29 **FZP** - Hollow splined shaft with axial blockage device

D

30 **W0A** - Flange
31 **P_** - Pinion
32 **M0A** - Sleeve coupling
33 End plate
34 **B0A** - Splined bar
35 **G0A** - Shrink disc

C OUTPUT



D FITTINGS



GENERAL INFORMATION

The following paragraphs contain information on essential elements for selection and correct use of gearmotors.

(A 2)



6 OUTPUT TORQUE

6.1 Reference torque M_{2REF} [Nm]

It is the significant value for the size. It is equivalent to the maximum value of nominal torque M_{n2} for a life factor n_2 x h = 10000 (referred to single stage configuration L1).

6.2 Rated output torque M_{n2} [Nm]

It is the output torque which the gearbox can transmit with steady load under working condition specified in the calculation method.

6.3 Maximun torque M_{2max} [Nm]

It is the output torque that the gearbox can withstand under static or almost static conditions. It is generally meant as a momentary peak load or starting-up torque under load.
The values in the tables are valid only in versions with output splined shaft (accessories excluded).

6.4 Required torque M_{r2} [Nm]

The torque drawn by the application. It must always be equal to or less than rated output torque M_{n2} for the gearbox under study.

7 POWER

7.1 Input rated power P_{n1} [kW]

P_{n1} is the maximum power that can be safely applied to the gearbox when the same is operated:
- at a n_1 drive speed
- yielding a theoretical lifetime of 10000 hours
- service factor f_s=1

$$P_1' \times fs \leq P_1 \quad (1)$$

Check that the formula here below is always satisfied:

7.2 Output power P_2 [kW]

This value is the net power delivered to the output shaft.
It can be calculated through the following formulas:

$$P2 = P1 \times \eta d \quad (2)$$

$$P_2 = \frac{M_{r2} \times n_2}{9550} \quad (3)$$

Efficiency values are listed in table (A3).

7.3 Thermal power P_T [kW]

This parameter is linked to the gearbox thermal limit (see par. 14.5).

8 EFFICIENCY

8.1 Dynamic efficiency η_d

$$\eta_d = \frac{P_2}{P_1} \quad (4)$$

The parameter is defined as the relationship of the net power delivered to the output shaft P_2 to the power applied to the input shaft P_1:

(A 3)

No. of reductions	Configuration		
	Planetary	Combined with worm gear unit	Combined with right-angle unit
1	0.97	—	—
2	0.94	0.73	—
3	0.91	0.70	0.91
4	0.88	—	—

Indicative values for the efficiency are listed in the chart here after.

9 REDUCTION RATIO i

$$i = \frac{n_1}{n_2} \quad (5)$$

It is defined as the relationship of the speed the input shaft is driven at and the speed delivered at the output shaft of a gearbox.

10 ANGULAR SPEED

10.1 Input speed n_1 [min $^{-1}$]

The speed the gearbox is driven at.
The value is coincident with the motor speed if this is directly connected to the gearbox.
Input speed should never exceed the n_{1max} value listed in the gearbox rating chart.

$$n_2 = \frac{n_1}{i} \quad (6)$$

10,2 Output speed n_2 [min^{-1}]

It is calculated from drive speed n_1 and gear ratio **i**, as per the following equation:

11 SERVICE FACTOR f_S

$$f_S = \frac{P_{n1}}{P_1} \quad (7)$$

This is the relationship of the gear unit rated power to the power of the electric motor actually driving the unit.

12 SERVICE FACTOR REQUESTED BY APPLICATION f_S'

(A 4)

Service factor f_S' required depending on the application						
Type of load	Number of starts/hour z	Total operating hours (h)				
		≤ 5000	10000	15000	25000	50000
		Daily operating hours (h)				
		h < 4	4 < h < 8	8 < h < 12	12 < h < 16	16 < h < 24
Uniform load	Z < 10	0.90	1.00	1.15	1.30	1.60
	10 < Z < 30	0.95	1.15	1.30	1.50	1.80
	30 < Z < 100	1.00	1.25	1.45	1.60	2.00
Moderate shock load	Z < 10	1.00	1.25	1.45	1.60	2.00
	10 < Z < 30	1.10	1.40	1.60	1.80	2.20
	30 < Z < 100	1.20	1.50	1.70	2.00	2.40
Heavy shock load	Z < 10	1.20	1.50	1.70	2.00	2.40
	10 < Z < 30	1.30	1.60	1.80	2.10	2.60
	30 < Z < 100	1.40	1.75	2.00	2.30	2.80

It's a coefficient that represents the severity of the application. This factor takes into account, although approximately, the type of load the gearbox operates with, the specific duty cycle as well as the operating daily hours.
The table (A4) is of reference when determining the appropriate service factor for the application.

$$F_{h1} = (n_1 \times h) \quad (8)$$

$$F_{h2} = (n_2 \times h) \quad (9)$$

13 LIFE FACTOR F_{h1}, F_{h2}

Factor resulting by multiplying angular speed at input (n_1) or output (n_2) by actual operating working hours h, break times excluded.

Life factor is directly proportional to gearbox rpms during the whole duty time

14 PRODUCT SELECTION

Bonfiglioli Forever Forward	TECHNICAL DATA REQUIRED FOR THE SELECTION OF 300M	Nr:	
		Date:	
		Rev_	Date:

		A)	***GENERAL DATA***							
#	1		Company / Customer							
#	2		Contact							
#	3		Branch / Distributor							
#	4		Order quantity							
	5		Delivery time							
		B_1)	***ELECTRIC MOTOR***			*B_2)*	***HYDRAULIC MOTOR***			
	6		Motor Type							
#	7	P_{n1}	Rated motor Power		[kW]	V	Displacement		[cm³]	
#	8	P_{r1}	Motor power demand		[kW]	Δp	Max drop of pressure		[bar]	
	9	n_1	Input speed		[min-1]	Q	Max oil flow rate		[l/min]	
	10		Pole number							
	11		Motor mounting: B3 - B5 - B14							
		C_1)	***PLANETARY GEARBOX***			*C_2)*	***ATEX CONDITION [GROUP II] -2014/34/EU***			
#	12		Gearbox configuration							
#	13	i	Gear ratio			Category: [**2**=standard / **3**=special]				
#	14	n_2	Output speed		[min-1]	Atmosphere: [**G**=gas / **D**=dust]				
#	15	M_{r2}	Output torque demand		[Nm]	Zone: [**1 - 21** / **2 - 22**]				
#	16	M_{p2}	Peak torque demand		[Nm]	Temperature Class [T4 / 135 °C]				
#	17	f_S	Service factor demand							
	18		Rotation of the output shaft [frontal view]:		**CW**		**CCW**			
#	19	L_{10H}	Bearings lifetime		[h]					
#	20		Gears lifetime		[h]					
	21	SF_{min}	Safety for tooth root stress		standard reference (ISO preferred)					
	22	SH_{min}	Safety for flank pressure		standard reference (ISO preferred)					
		D)	***ADDITIONAL LOADS***							
	23	R_{c2}	Radial load on output shaft		[N]					
	24	x_2	Load application distance from shaft shoulder		[mm]					
	26	R_{c1}	Radial load on input shaft		[N]					
	27	x_1	Load application distance from shaft shoulder		[mm]					
	29	A_{n2}	Thrust load on output shaft (+ / -)		[N]					
	30	A_{n1}	Thrust load on input shaft (+ / -)		[N]					
		E)	***APPLICATION***							
#	31		Type of application							
	32		Duty cycle	Time phase %	Time phase hours	Gearbox output torque [Nm]	Gearbox output speed [min-1]			
				,,,,	,,,,					
				,,,,	,,,,					
				,,,,	,,,,					
				,,,,	,,,,					
				,,,,	,,,,					
	33		Notes about Duty Cycle:							
			Duty type	**S1**	**S2**	**S3**	**S4-S8**			
	34	v_A	Ambient air velocity		[m/s]	≤ 0.5	> 0.5 ≤ 1.4	> 1.4		
#	35	t_a	Ambient temperature range		[°C]					
	36		Altitude a.s.l.		[m]					
	37		Rating according FEM class	T-	L-	M-				
		F)	***OPTIONS OR ADDITIONAL REQUESTS***							
	38		Lubrication							
	39		Supplementary cooling systems							
	40		Paint coating							
	41		To specific requests for testing							
		G)	***NOTES***							
	42		Notes and additional Customer requirements:							
#	43		**PRJ number if present for Special Gearbox**							

Mandatory for the selection

The form, duly filled in, can be forwarded to our Technical Service which will assist the Customer in selecting the most suitable drive for the specific application.

14,1 PRODUCT SELECTION GUIDE



NOTE:
The selection criteria and specifications reported in this catalogue are not valid for every and each application, including those where the gearbox operates as a safety device preventing injury to persons or damage to objects, as is the case with hoisting equipment.
For these applications, the gearbox should be selected according to specific criteria and in compliance with the applicable safety regulations. Should this be the case we recommend that you seek advice from BONFIGLIOLI Technical Service.

For the selection of gear units in Atex configuration, see also the specific chapter on page 486.

14,2 METHOD A (Gearbox selection by power)

Based on application type, it should be defined :
a) Required service factor $\mathbf{f_S'}$ (see tab A4);

b) Required drive power:

$$P_{r1} = \frac{M_{r2} \times n_2}{9550 \times \eta_d} \quad (10)$$

Table (A3) lists the indicative values of efficiency ηd for the different types of gearboxes.

c) After required power $\mathbf{P_{r1}}$ and output speed $\mathbf{n_2}$ are known, locate the gearmotor rating charts and select the one relevant to normalized power $\mathbf{P_n}$ equal to or greater than $\mathbf{P_{r1}}$:

$$P_n \geq P_{r1} \quad (11)$$

Unless otherwise specified, power $\mathbf{P_n}$ listed in the motor rating chart refers to continuous duty S1. For motors operating in conditions other than S1, determine type of duty according to CEI 2-3/IEC 60034-1 standards.
Note that for duty cycles from S2 to S8 and motor frame sizes up to 132 included, power may be upgraded over that specified for continuous duty. In this event, the condition to be verified is the following:

$$P_n = \frac{P_{r1}}{f_m} \quad (12)$$

The adjusting factor $\mathbf{f_m}$ can be obtained from table (A5).

(A 5)

	DUTY						
	S2			**S3***			**S4-S8**
	Cycle duration			Cyclic duration factor			Please contact us
	10	**30**	**60**	**25%**	**40%**	**60%**	
f_m	1.35	1.15	1.05	1.25	1.15	1.1	

* Cycle time must be equal to or less than 10 minutes. Should this not be the case contact our Technical Service for assistance.

Cyclic duration rate is the relationship of operating time under load $\mathbf{t_r}$ to total cycle time ($\mathbf{t_f}$ + $\mathbf{t_r}$) where $\mathbf{t_f}$ is time at rest, expressed as a percentage.

Cyclic duration rate:

$$I = \frac{t_r}{t_f + t_r} \times 100 \quad (13)$$

For the output speed $\mathbf{n_2}$, or closest to, select the gearmotor that yields a service factor $\mathbf{f_S}$ meeting the following condition:

$$f_S \geq f_S' \quad (14)$$

In case of **FP** configuration, please see Verification paragraph (chapter 14.5 - item g) .

14,3 METHOD B (Gearbox selection by Torque requested by application)

Based on application type, it should be defined :
a) Required service factor $\mathbf{f_S'}$ (see tab A4);

b) Determine calculated torque according to required output torque $\mathbf{M_{r2}}$ as follows:

$$M_{c2} = M_{r2} \times f_S' \quad (15)$$

c) Determine gear ratio from required output speed $\mathbf{n_2}$ and drive speed $\mathbf{n_1}$:

$$i = \frac{n_1}{n_2} \quad (16)$$

d) Once $\mathbf{M_{c2}}$ and **i** are determined, locate the gearbox rating chart for the drive speed $\mathbf{n_1}$ and select a gearbox featuring the ratio i nearest to calculated ratio that also satisfies the condition:

$$M_{n2} \geq M_{c2} \quad (17)$$

If a IEC-normalised motor is to be fitted onto the gearbox, check availability of the applicable adapter.

In case of **FP** configuration, please see Verification paragraph (chapter 14.5 - item g) .

14,4 METHOD C (Gearbox selection by number of working cycles)

a) Determine the following according to the required application:
- Required service factor $\mathbf{f_S'}$ (see tab. A4)
- required gearbox working life h
- required drive unit (hydraulic, electric or others).

b) Define the calculated torque with the required output torque M_{r2}:

$$M_{c2} = M_{r2} \times f_S' \quad (18)$$

c) Calculate the life factor with required working life h and output speed n_2.:

$$Fh_2 = (n_2 \times h) \quad (19)$$

d) Calculate the required reduction ratio:

$$i = \frac{n_1}{n_2} \quad (20)$$

e) Select gearbox size which, having a reduction ratio close to the calculated value, which satisties the following

$$M_{c2} \leq M_{n2} \quad (21)$$

$$Fh_2 \leq (n_2 \times h) \quad (22)$$

where M_{n2} and Fh_2 are indicated in the tables on technical features for each gearbox size.

In case of applications in which the required torque M_{r2} and speed n_2 vary within a wide range, best selection could be an equivalent required torque given by:

$$M_{r2} = \sqrt[4]{\frac{(n_2 \times h)_A \times M_A^4 + (n_2 \times h)_B \times M_B^4 + (n_2 \times h)_C \times M_C^4 + ...}{(n_2 \times h)_A + (n_2 \times h)_B + (n_2 \times h)_C + ...}} \quad (23)$$

referred to:

(A 6)



and calculating the life factor Fh with:

$$Fh_{calc} = (n_2 \times h)_A + (n_2 \times h)_B + (n_2 \times h)_C + ... \quad (24)$$

Then follow the same procedure as specified in d) and e).

In case of **FP** configuration, please see Verification paragraph (chapter 14.5 - item g) .

14,5 VERIFICATION

After selecting the drive units, please check the following:

a) Thermal power

The thermal power P_T is the maximum power that the gearbox can transmit mechanically, under continuous operation, without the internal temperature rising to a value that could damage the gearbox components.

Base thermal capacities values P_{TB} are listed in section C and calculated under the following operating conditions:
- Input speed 1500 min^{-1} (some exceptions)
- Ambient temperature 20°C
- Foot base with splined or solid keyed shaft
- Horizontal mounting position (A, B, E, F, G, I, J, M)
- Installation in large area (air speed > 1.4 m/s)
- Continuous duty
- Max. installation altitude 1000 m
- Oil ISO VG 320

They are valid for a specific size and gearbox ratio.

Please refer to Bonfiglioli Technical Service:
- For L1 gearbox configuration
- For R2 gearbox configuration, size > 307

Otherwise, for a specific configuration, the total thermal power P_T can be calculated using the following formula:

$$P_T = P_{TB} \times f_{out} \times f_{Tamb} \times f_{speed} \times f_{pos} \times f_{input\ V} \times f_{air} \times f_{id} \times f_{nb} \quad (25)$$

Where:
P_T = overall thermal power
P_{TB} = Base thermal power
f_{out} = factor depends on output version
f_{Tamb} = factor for ambient temperature 40°C
f_{speed} = factor for specific input speed (1800, 1200, 1000 min^{-1})
f_{pos} = factor for vertical mounting position (T, O, Q, V)
$f_{input\ V}$ = factor for solid input shaft if present (apply only for size ≥ 309)
f_{air} = factor for installation in confined space (air speed ≤ 1.4 m/s)
f_{id} = factor for intermittent duty
f_{nb} = factor for negative multidisc brake (if present)

The specific factors are listed in the tables below.

The total thermal power obtained from this calculation must be greater than the P_{r1} (required input power).

$$P_T \geq P_{r1} \quad (26)$$

For specific configuration or application data different from the standard, please refer to Bonfiglioli Technical Service.

(A 7)

(L)	f_{out}				
300	**L2**		**L3**		**L4**
	i ≤ 20.1	i > 20.1			
FZ/FP/HC/ HZ/MC/MZ/ FDK	0.68	0.75	0.75		0.91
PZ/PC	1.00	1.00	1.00		1.00
301	**L2**		**L3**		**L4**
	i ≤ 20.1	i > 20.1	i ≤ 116	i > 116	
FZ/FP/HC/ HZ/MC/MZ/ FDK	0.65	0.70	0.78	0.80	0.97
PZ/PC	1.00		1.00		1.00
303	**L2**		**L3**		**L4**
FZ/FP/HC/ HZ/MC/MZ/ FDK	0.82		0.84		0.81
PZ/PC	1.00		—		
304	**L2**		**L3**		**L4**
FZ/FP/HC/ HZ/MC/MZ/ FDK	0.83		0.83		0.79
PZ/PC	1.00		1.00		1.00
305	**L2**		**L3**		**L4**
FZ/FP/HC/ HZ/MC/MZ/ FDK	0.80		0.80		0.78
PZ/PC	1.00		1.00		1.00
306	**L2**		**L3**		**L4**
	i ≤ 26.4	i > 26.4			
FZ/FP/HC/ HZ/MC/MZ/ FDK	0.70	0.75	0.72		0.75
PZ/PC	1.00	1.00	1.00		1.00
307	**L2**		**L3**		**L4**
	i ≤ 28.0	i > 28.0			
FZ/FP/HC/ HZ/MC/MZ/ FDK	0.77	0.81	0.80		0.81
PZ/PC	1.00	1.00	1.00		1.00
309	**L2**		**L3**		**L4**
	i ≤ 17.4 (i = 12.3)* (i = 14.7)*	i > 17.4			
FZ/FP/HC/ HZ/MC/MZ/ FDK	0.37	0.50	0.52		0.55
PZ/PC	1.00	1.00	1.00		1.00
310M	**L2**		**L3**		**L4**
	i ≤ 21.8 (i = 14.7)*	i > 21.8			
FZ/FP/HC/ HZ/FDK	0.40	0.50	0.59		0.61
PZ/PC	1.00	1.00	1.00		1.00
311M	**L2**		**L3**		**L4**
	i ≤ 21.5	i > 21.5			
FZ/FP/HC/ HZ/FZP	0.40	0.42	0.50		0.60
PZ/PC	1.00	1.00	1.00		1.00

(L)	f_{out}					
313M	**L2**		**L3**		**L4**	
			i ≤ 92.4	i > 92.4		
FZ/FP/HC/ HZ/FZP	*		0.43	0.55	0.60	
PZ/PC	1.00		1.00		1.00	
314M	**L2**		**L3**		**L4**	
			i ≤ 73.9	i > 73.9		
FP/HC/HZ/ FZP	*		0.45	0.50	0.65	
FZ	*		0.30	0.44	0.52	
PZ/PC	1.00		1.00		1.00	
315M	**L2**		**L3**		**L4**	
	i ≤ 22.3	i > 22.3 n_1 ≤1200 rpm				
FP/HC/HZ/ FZP	*	0.47	0.46		0.50	
FZ	*	0.38	0.37		0.40	
PZ/PC	1.00	1.00	1.00		1.00	
316M	**L2**		**L3**		**L4**	
			i ≤ 114	i > 114		
FZ/FP/HC/ HZ/FZP	*		0.45	0.50	0.60	
PZ/PC	1.00		1.00		1.00	
317M	**L2**		**L3**		**L4**	
	i ≥ 22.1 n_1 = 900 rpm		i ≤ 69.3	i > 69.3		
FZ/FP/HC/ HZ/FZP	*		*	0.60	0.65	
PZ/PC	1.00		1.00	1.00	1.00	
318M	**L2**		**L3**		**L4**	
	n_1 = 500 rpm		i ≤ 98.2	i > 98.2		
FZ/FP/HC/ HZ/FZP	0.55		*	0.50	0.57	
PZ/PC	1.00		1.00	1.00	1.00	
319	**L2**		**L3**		**L4**	
	n_1 = 500 rpm		i = 84.8, 100, 126	i = 109 i > 126		
FZ/FP/HC/ HZ/FZP	0.60		*	0.55	0.64	
PZ/PC	1.00		1.00	1.00	1.00	
321	—		**L3**		**L4**	
			i ≤ 98.2	i > 98.2	i ≤ 308	i > 308
FZ/FP/HC/ HZ/FZP	—		0.51	0.60	0.50	0.56
PZ/PC	—		1.00	1.00	1.00	1.00
323	—		**L3**		**L4**	
FZ/FP/FZP	—		1.00		1.00	
325	—		**L3**		**L4**	
FZ/FP/FZP	—		1.00		1.00	

* BONFIGLIOLI TECHNICAL SERVICE

(A 8)

(R)	f_{out}		
300	**R2**	**R3**	**R4**
FZ/FP/HC/HZ/ MC/MZ/FDK	0.85	0.90	0.92
PZ/PC	1.00	1.00	1.00
301	**R2**	**R3**	**R4**
FZ/FP/HC/HZ/ MC/MZ/FDK	0.80	0.83	0.87
PZ/PC	1.00	1.00	1.00
303	**R2**	**R3**	**R4**
FZ/FP/HC/HZ/ MC/MZ/FDK	0.88	0.91	0.95
PZ/PC	1.00	1.00	1.00
304	**R2**	**R3**	**R4**
FZ/FP/HC/HZ/ MC/MZ/FDK	0.88	0.91	0.95
PZ/PC	1.00	1.00	1.00
305	**R2**	**R3**	**R4**
FZ/FP/HC/HZ/ MC/MZ/FDK	0.86	0.93	0.97
PZ/PC	1.00	1.00	1.00
306	**R2**	**R3**	**R4**
FZ/FP/HC/HZ/ MC/MZ/FDK	0.88	0.90	0.90
PZ/PC	1.00	1.00	1.00
307	—	**R3**	**R4**
FZ/FP/HC/HZ/ MC/MZ/FDK	—	0.78	0.81
PZ/PC	—	1.00	1.00
309	—	**R3**	**R4**
FZ/FP/HC/HZ/ MC/MZ/FDK	—	0.53	0.58
PZ/PC	—	1.00	1.00
310M	—	**R3**	**R4**
FZ/FP/HC/HZ/ FDK	—	0.55	0.60
PZ/PC	—	1.00	1.00
311M	—	**R3**	**R4**
FZ/FP/HC/HZ/ FZP	—	0.45	0.55
PZ/PC	—	1.00	1.00

(R)	f_{out}		
313M	—	**R3**	**R4**
FZ/FP/HC/HZ/ FZP	—	0.45	0.60
PZ/PC	—	1.00	1.00
314M	—	**R3**	**R4**
FZ/FP/HC/HZ/ FZP	—	*	0.60
PZ/PC	—	1.00	1.00
315M		**R3**	**R4**
FZ/FP/HC/HZ/ FZP	—	*	0.50
PZ/PC	—	1.00	1.00
316M	—	**R3**	**R4**
FZ/FP/HC/HZ/ FZP	—	*	0.55
PZ/PC	—	1.00	1.00
317M	—	**R3**	**R4**
FZ/FP/HC/HZ/ FZP	—	*	0.65
PZ/PC	—	1.00	1.00
318M		—	**R4**
FZ/FP/HC/HZ/ FZP	—	—	*
PZ/PC	—	—	1.00
319	—	—	**R4**
FZ/FP/HC/HZ/ FZP	—	—	0.60
PZ/PC	—	—	1.00
321	—	—	**R4**
FZ/FP/HC/HZ/ FZP	—	—	0.58
PZ/PC	—	—	1.00

* BONFIGLIOLI TECHNICAL SERVICE

(A 9)

(L)	f_{Tamb}				
300	L2		L3		L4
	i ≤ 20.1	i > 20.1	i ≤ 116	i > 116	
	0.64	0.72	0.66	0.72	0.75
301	L2		L3		L4
	i ≤ 20.1	i > 20.1	i ≤ 116	i > 116	
	0.64	0.75	0.68	0.75	0.75
303	L2		L3		L4
	i ≤ 12.5	i > 12.5			
	0.58	0.68	0.65		0.75
304	L2		L3		L4
	i ≤ 22.7	i > 22.7	i ≤ 90.2	i > 90.2	
	0.63	0.69	0.66	0.70	0.75
305	L2		L3		L4
	i ≤ 26.4	i > 26.4	i ≤ 125	i > 125	
	0.63	0.66	0.65	0.70	0.75
306	L2		L3		L4
	i ≤ 26.4	i > 26.4			
	0.60	0.70	0.70		0.75
307	L2		L3		L4
	i ≤ 28.0 (i = 12.3)* (i = 14.7)*	i > 28.0			
	0.65	0.68	0.70		0.75
309	L2		L3		L4
	i ≤ 17.4 (i = 12.3)* (i = 14.7)*	i > 17.4			
	0.6	0.65	0.73		0.75
310M	L2		L3		L4
	i ≤ 21.8 (i = 14.7)*	i > 21.8			
	0.60	0.65	0.72		0.75

(L)	f_{Tamb}				
311M	L2		L3		L4
	i ≤ 21.5	i > 21.5	i ≤ 89.3	i > 89.3	
	*	0.60	0.63	0.72	0.75
313M	L2		L3		L4
	i ≥ 21.8		i ≤ 92.4	i > 92.4	
	0.47		0.65	0.70	0.75
314M	L2		L3		L4
	i ≥ 22.3		i ≤ 73.9	i > 73.9	
	0.58		0.65	0.72	0.75
315M	L2		L3		L4
	i ≤ 22.3	i > 22.3	i ≤ 108	i > 108	
	*	0.47	0.64	0.71	0.75
316M	L2		L3		L4
	i ≤ 21.8	i > 21.8	i ≤ 114	i > 114	
	*	0.60	0.62	0.65	0.75
317M	L2		L3		L4
	i ≥ 22.1 n_1 = 1000 rpm		i ≤ 69.3	i > 69.3	
	0.50		0.50	0.65	0.75
318M	L2		L3		L4
	n_1 = 500 rpm		i ≤ 98.2	i > 98.2	
	0.60		0.60	0.60	0.60
319	L2		L3		L4
	n_1 = 500 rpm		i ≤ 126	i > 126	
	0.55		0.60	0.65	0.65
321	—		L3		L4
	—		0.6		0.70
323	—		L3		L4
	—		0.6		0.65
323	—		L3		L4
	—		0.6		0.65

* BONFIGLIOLI TECHNICAL SERVICE

(A 10)

(R)	f_{Tamb}		
300	R2	R3	R4
	0.65	0.70	0.70
301	R2	R3	R4
	0.65	0.70	0.70
303	R2	R3	R4
	0.62	0.66	0.70
304	R2	R3	R4
	0.60	0.65	0.67
305	R2	R3	R4
	0.63	0.65	0.68
306	R2	R3	R4
	0.63	0.68	0.70
307	—	R3	R4
	—	0.65	0.69
309	—	R3	R4
	—	0.67	0.70
310M	—	R3	R4
	—	0.65	0.68
311M	—	R3	R4
	—	0.60	0.70

(R)	f_{Tamb}		
313M	—	R3	R4
	—	0.63	0.70
314M	—	R3	R4
	—	0.55	0.60
315M	—	R3	R4
	—	0.65	0.70
316M	—	R3	R4
	—	0.60	0.65
317M	—	R3	R4
	—	0.60	0.65
318M	—	—	R4
	—	—	0.60
319	—	—	R4
	—	—	0.60
321	—	—	R4
	—	—	0.60

* BONFIGLIOLI TECHNICAL SERVICE

(A 11)

(L)	f_{speed}			
300	**L2**		**L3**	**L4**
	i ≤ 20.1	i > 20.1		
n_1 = 1800 rpm	0.80	0.95	0.95	0.95
n_1 = 1200 rpm	1.10	1.03	1.02	1.02
n_1 = 1000 rpm	1.30	1.05	1.05	1.05
301	**L2**		**L3**	**L4**
	i ≤ 20.1	i > 20.1		
n_1 = 1800 rpm	0.80	0.95	0.95	0.95
n_1 = 1200 rpm	1.12	1.03	1.02	1.02
n_1 = 1000 rpm	1.30	1.10	1.10	1.10
303	**L2**		**L3**	**L4**
	i ≤ 20.8	i > 20.8		
n_1 = 1800 rpm	0.80	0.95	0.95	0.95
n_1 = 1200 rpm	1.03	1.02	1.02	1.02
n_1 = 1000 rpm	1.05	1.10	1.05	1.05
304	**L2**		**L3**	**L4**
	i ≤ 22.7	i > 22.7		
n_1 = 1800 rpm	0.96	0.98	0.91	0.91
n_1 = 1200 rpm	1.05	1.03	1.04	1.04
n_1 = 1000 rpm	1.10	1.06	1.05	1.05
305	**L2**		**L3**	**L4**
	i ≤ 26.4	i > 26.4		
n_1 = 1800 rpm	0.90	0.93	0.90	0.90
n_1 = 1200 rpm	1.03	1.02	1.02	1.02
n_1 = 1000 rpm	1.06	1.04	1.04	1.04
306	**L2**		**L3**	**L4**
	i ≤ 26.4	i > 26.4		
n_1 = 1800 rpm	0.85	0.95	0.95	0.95
n_1 = 1200 rpm	1.03	1.02	1.02	1.02
n_1 = 1000 rpm	1.12	1.04	1.04	1.04
307	**L2**		**L3**	**L4**
	i ≤ 28.0	i > 28.0		
n_1 = 1800 rpm	0.87	0.92	0.97	0.97
n_1 = 1200 rpm	1.10	1.03	1.02	1.02
n_1 = 1000 rpm	1.18	1.06	1.05	1.05
309	**L2**		**L3**	**L4**
	i ≤ 25.4	i > 25.4		
n_1 = 1800 rpm	*	0.88	0.95	0.95
n_1 = 1200 rpm	1.10	1.06	1.02	1.02
n_1 = 1000 rpm	1.22	1.10	1.05	1.05
310M	**L2**		**L3**	**L4**
	i ≤ 25.4	i > 25.4		
n_1 = 1800 rpm	*	*	0.95	0.95
n_1 = 1200 rpm	1.20	1.15	1.02	1.02
n_1 = 1000 rpm	1.50	1.20	1.05	1.05
311M	**L2**		**L3**	**L4**
	i ≤ 21.5	i > 21.5		
n_1 = 1800 rpm	*	*	0.90	0.90
n_1 = 1200 rpm	1.10	1.15	1.05	1.05
n_1 = 1000 rpm	1.50	1.26	1.10	1.10
313M	**L2**		**L3**	**L4**
	i ≥ 21.8			
n_1 = 1800 rpm	*		0.60	0.60
n_1 = 1200 rpm	1.20		1.05	1.05
n_1 = 1000 rpm	1.50		1.10	1.10
314M	**L2**		**L3**	**L4**
	i ≥ 22.3			
n_1 = 1800 rpm	*		*	*
n_1 = 1200 rpm	1.20		1.05	1.05
n_1 = 1000 rpm	1.45		1.10	1.10

(L)	f_{speed}				
315M	**L2**		**L3**		**L4**
	i ≤ 22.3	i > 22.3			
n_1 = 1800 rpm	*	*	*		0.90
n_1 = 1200 rpm	1.50	1.16	1.15		1.07
n_1 = 1000 rpm	1.70	1.30	1.25		1.10
316M	**L2**		**L3**		**L4**
	i ≤ 21.8	i > 21.8	i ≤ 114	i > 114	
n_1 = 1800 rpm	*	*	*	*	0.90
n_1 = 1200 rpm	*	1.15	1.2	1.15	1.05
n_1 = 1000 rpm	*	1.45	1.30	1.20	1.07
317M	**L2**		**L3**		**L4**
			i ≤ 69.3	i > 69.3	
n_1 = 1800 rpm	*		*	*	0.90
n_1 = 1200 rpm	*		1.2	1.05	1.05
n_1 = 1000 rpm	1.00		1.25	1.20	1.20
318M	**L2**		**L3**		**L4**
			i ≤ 98.2	i > 98.2	
n_1 = 1800 rpm	*		*	*	*
n_1 = 1200 rpm	*		1.30	1.15	1.10
n_1 = 1000 rpm	*		1.50	1.20	1.20
319	**L2**		**L3**		**L4**
			i ≤ 126	i > 126	
n_1 = 1800 rpm	*		*	*	*
n_1 = 1200 rpm	*		1.25	1.15	1.10
n_1 = 1000 rpm	*		1.30	1.20	1.15
321	—		**L3**		**L4**
			i ≤ 126	i > 126	
n_1 = 1800 rpm	—		*	*	*
n_1 = 1200 rpm	—		*	*	1.05
n_1 = 1000 rpm	—		1.00	1.00	1.10
323	—		**L3**		**L4**
n_1 = 1800 rpm	—		*	*	*
n_1 = 1200 rpm	—		*	*	1.03
n_1 = 1000 rpm	—		*	*	1.05
325	—		**L3**		**L4**
n_1 = 1800 rpm	—		*	*	*
n_1 = 1200 rpm	—		*	*	1.03
n_1 = 1000 rpm	—		*	*	1.05

* BONFIGLIOLI TECHNICAL SERVICE

(A 12)

(R)	f_{speed}		
300	**R2**	**R3**	**R4**
n_1 = 1800 rpm	0.95	0.97	0.97
n_1 = 1200 rpm	1.05	1.04	1.04
n_1 = 1000 rpm	1.15	1.05	1.05
301	**R2**	**R3**	**R4**
n_1 = 1800 rpm	0.88	0.90	0.90
n_1 = 1200 rpm	1.05	1.03	1.03
n_1 = 1000 rpm	1.15	1.05	1.05
303	**R2**	**R3**	**R4**
n_1 = 1800 rpm	0.90	0.93	0.93
n_1 = 1200 rpm	1.05	1.03	1.03
n_1 = 1000 rpm	1.10	1.05	1.05
304	**R2**	**R3**	**R4**
n_1 = 1800 rpm	0.90	0.93	0.93
n_1 = 1200 rpm	1.05	1.03	1.03
n_1 = 1000 rpm	1.08	1.05	1.05
305	**R2**	**R3**	**R4**
n_1 = 1800 rpm	0.90	0.93	0.93
n_1 = 1200 rpm	1.05	1.03	1.03
n_1 = 1000 rpm	1.12	1.05	1.05
306	**R2**	**R3**	**R4**
n_1 = 1800 rpm	0.85	0.88	0.88
n_1 = 1200 rpm	1.05	1.03	1.03
n_1 = 1000 rpm	1.08	1.05	1.05
307	—	**R3**	**R4**
n_1 = 1800 rpm	—	0.90	0.94
n1 = 1200 rpm	—	1.03	1.02
n_1 = 1000 rpm	—	1.06	1.05
309	—	**R3**	**R4**
n_1 = 1800 rpm	—	0.80	0.85
n_1 = 1200 rpm	—	1.03	1.02
n_1 = 1000 rpm	—	1.06	1.05
310M	—	**R3**	**R4**
n_1 = 1800 rpm	—	0.90	0.93
n_1 = 1200 rpm	—	1.03	1.02
n_1 = 1000 rpm	—	1.08	1.04
311M	—	**R3**	**R4**
n_1 = 1800 rpm	—	0.80	0.85
n_1 = 1200 rpm	—	1.07	1.05
n_1 = 1000 rpm	—	1.12	1.10

(R)	f_{speed}		
313M	—	**R3**	**R4**
n_1 = 1800 rpm	—	0.80	0.85
n_1 = 1200 rpm	—	1.08	1.05
n_1 = 1000 rpm	—	1.12	1.08
314M	—	**R3**	**R4**
n_1 = 1800 rpm	—	*	0.90
n_1 = 1200 rpm	—	1.15	1.10
n_1 = 1000 rpm	—	1.25	1.18
315M	—	**R3**	**R4**
n_1 = 1800 rpm	—	*	0.80
n_1 = 1200 rpm	—	1.10	1.08
n_1 = 1000 rpm	—	1.25	1.15
316M	—	**R3**	**R4**
n_1 = 1800 rpm	—	*	0.80
n_1 = 1200 rpm	—	1.15	1.10
n_1 = 1000 rpm	—	1.25	1.15
317M	—	**R3**	**R4**
n_1 = 1800 rpm	—	*	0.75
n_1 = 1200 rpm	—	1.20	1.10
n_1 = 1000 rpm	—	1.25	1.15
318M	—	—	**R4**
n_1 = 1800 rpm	—	—	*
n_1 = 1200 rpm	—	—	1.08
n_1 = 1000 rpm	—	—	1.15
319	—	—	**R4**
n_1 = 1800 rpm	—	—	*
n_1 = 1200 rpm	—	—	1.05
n_1 = 1000 rpm	—	—	1.15
321	—	—	**R4**
n_1 = 1800 rpm	—	—	*
n_1 = 1200 rpm	—	—	1.05
n_1 = 1000 rpm	—	—	1.15

* BONFIGLIOLI TECHNICAL SERVICE

(A 13)

(L)	f_{pos}			
300	L2		L3	L4
	i ≤ 20.1	i > 20.1		
	0.65	0.85	0.88	0.88
301	L2		L3	L4
	i ≤ 20.1	i > 20.1		
	0.70	0.90	0.88	0.88
303	L2		L3	L4
	0.83		0.90	0.90
304	L2		L3	L4
	i ≤ 22.7	i > 22.7		
	0.80	0.85	0.85	0.85
305	L2		L3	L4
	i ≤ 26.4	i > 26.4		
	0.80	0.85	0.85	0.85
306	L2		L3	L4
	i ≤ 26.4	i > 26.4		
	0.80	0.85	0.85	0.85
307	L2		L3	L4
	i ≤ 28.0	i > 28.0		
	0.80	0.85	0.85	0.85
309	L2		L3	L4
	i ≤ 25.4	i > 25.4		
	0.40	0.75	0.85	0.85
310M	L2		L3	L4
	i ≤ 25.4	i > 25.4		
	*	0.70	0.85	0.85
311M	L2		L3	L4
	i ≤ 21.5	i > 21.5		
	*	0.40	0.80	
313M	L2		L3	L4
	0.40		0.75	0.75
314M	L2		L3	L4
	*		0.80	0.80

(L)	f_{pos}			
315M	L2	L3		L4
		i ≤ 108	i > 108	
	*	0.50	0.75	0.75
316M	L2	L3		L4
		i ≤ 114	i > 114	
	*	*	0.65	0.70
317M	L2	L3		L4
		i ≤ 69.3	i > 69.3	
	*	0.50	0.55	0.75
318M	L2	L3		L4
		i ≤ 98.2	i > 98.2	
	0.70	*	*	0.70
319	L2	L3		L4
	i ≥ 26	i ≤ 126	i > 126	
	0.90	*	0.70	0.75
321	—	L3		L4	
		i ≤ 98.2	i > 98.2	i ≤ 308	i > 308
	—	*	0.70	0.50	0.80
323	—	L3		L4	
		i ≤ 120	i > 120	i ≤ 500	i > 500
	—	0.86	0.93	*	0.75
325	—	L3		L4	
		i ≤ 120	i > 120	i ≤ 500	i > 500
	—	0.86	0.93	*	0.75

* BONFIGLIOLI TECHNICAL SERVICE

(A 14)

(R)	f_{pos}		
300	R2	R3	R4
	0.87	0.90	0.90
301	R2	R3	R4
	0.86	0.90	0.90
303	R2	R3	R4
	0.90	0.92	0.92
304	R2	R3	R4
	0.88	0.92	0.92
305	R2	R3	R4
	0.86	0.90	0.90
306	R2	R3	R4
	0.88	0.92	0.92
307	—	R3	R4
	—	0.85	0.92
309	—	R3	R4
	—	0.84	0.92
310M	—	R3	R4
	—	0.90	0.93
311M	—	R3	R4
	—	0.65	0.70

(R)	f_{pos}		
313M	—	R3	R4
	—	0.75	0.80
314M	—	R3	R4
	—	*	0.70
315M	—	R3	R4
	—	*	0.75
316M	—	R3	R4
	—	*	0.90
317M	—	R3	R4
	—	*	0.90
318M	—	—	R4
	—	—	0.70
319	—	—	R4
	—	—	0.70
321	—	—	R4
	—	—	0.70

* BONFIGLIOLI TECHNICAL SERVICE

(A 15)

(L)	f_{air} < 1.4 m/s		
300	L2	L3	L4
	0.50	0.75	0.75
301	L2	L3	L4
	0.60	0.70	0.70
303	L2	L3	L4
	0.55	0.60	0.60
304	L2	L3	L4
	0.66	0.70	0.70
305	L2	L3	L4
	0.60	0.63	0.63
306	L2	L3	L4
	0.55	0.65	0.65
307	L2	L3	L4
	0.50	0.60	0.60
309	L2	L3	L4
	*	0.6	0.6
310M	L2	L3	L4
	0.50	0.65	0.65
311M	L2	L3	L4
	0.50	0.60	0.60
313M	L2	L3	L4
	*	0.50	0.50
314M	L2	L3	L4
	*	0.60	0.60
315M	L2	L3	L4
	*	0.55	0.55
316M	L2	L3	L4
	*	0.55	0.55

(L)	f_{air} < 1.4 m/s				
317M	L2	L3		L4	
		i ≤ 69.3	i > 69.3		
	*	0.50	0.55	0.60	
318M	L2	L3		L4	
		i ≤ 98.2	i > 98.2		
	0.55	*	0.45	0.60	
319	L2	L3		L4	
		i ≤ 126	i > 126		
	0.60	0.45	0.60	0.60	
321	—	L3		L4	
		i ≤ 98.2	i > 98.2	i ≤ 308	i > 308
	—	*	0.60	0.60	0.70
323	—	L3		L4	
	—	0.70		0.60	
325	—	L3		L4	
	—	0.70		0.60	

* BONFIGLIOLI TECHNICAL SERVICE

(A 16)

(R)	f_{air} < 1.4 m/s		
300	R2	R3	R4
	0.70	0.75	0.75
301	R2	R3	R4
	0.60	0.65	0.65
303	R2	R3	R4
	0.65	0.65	0.65
304	R2	R3	R4
	0.55	0.60	0.60
305	R2	R3	R4
	0.60	0.65	0.65
306	R2	R3	R4
	0.60	0.65	0.65
307	—	R3	R4
	—	0.62	0.66
309	—	R3	R4
	—	0.60	0.65
310M	—	R3	R4
	—	0.60	0.65
311M	—	R3	R4
	—	0.55	0.60

(R)	f_{air} < 1.4 m/s		
313M	—	R3	R4
	—	0.55	0.60
314M	—	R3	R4
	—	0.55	0.65
315M	—	R3	R4
	—	*	0.60
316M	—	R3	R4
	—	*	0.60
317M	—	R3	R4
	—	*	0.65
318M	—	—	R4
	—	—	*
319	—	—	R4
	—	—	*
321	—	—	R4
	—	—	*

* BONFIGLIOLI TECHNICAL SERVICE

(A 17)

(L)	$f_{input\ V}$			
309	L2		L3	L4
	0.92		0.95	0.95
310M	L2		L3	L4
	0.60		0.90	0.90
311M	L2		L3	L4
	i ≤ 21.5	i > 21.5		
	*	0.76	0.95	0.95
313M	L2		L3	L4
	i ≥ 21.5			
	0.40		0.90	0.90
314M	L2		L3	L4
	i ≥ 22.3			
	0.45		0.85	0.85
315M	L2		L3	L4
	i ≤ 22.3	i > 22.3		
	0.50	0.54	0.85	0.85

* BONFIGLIOLI TECHNICAL SERVICE

(L)	$f_{input\ V}$			
316M	L2	L3		L4
		i ≤ 114	i > 114	
	*	0.6	0.45	0.45
317M	L2	L3		L4
		i ≤ 69.3	i > 69.3	
	1.00	0.65	0.70	0.75
318M	L2	L3		L4
		i ≤ 98.2	i > 98.2	
	1.00	*	0.80	0.80
319	L2	L3		L4
		i ≤ 126	i > 126	
	1.00	0.85	0.90	0.90
321	—	L3		L4
	—	1.00		0.85
323	—	L3		L4
	—	1.00		1.00
325	—	L3		L4
	—	1.00		1.00

(A 18)

(R)	$f_{input\ V}$	
309	R3	R4
	0.94	0.97
310M	R3	R4
	0.90	0.95
311M	R3	R4
	0.90	0.95
313M	R3	R4
	0.90	0.93
314M	R3	R4
	0.70	0.75

* BONFIGLIOLI TECHNICAL SERVICE

(R)	$f_{input\ V}$	
315M	R3	R4
	0.60	0.70
316M	R3	R4
	0.70	0.80
317M	R3	R4
	0.75	0.85
318M	—	R4
	—	0.90
319	—	R4
	—	0.90
321	—	R4
	—	0.90

(A 19)

	cycling duration factor [%] based 60 min running (running on load [min]/60*100)				
	100	80	60	40	20
f_{id}	1.0	1.1	1.4	1.7	2

(A 20)

	L1 only for ⟨Ex⟩	L2	L3-L4	R2	R3-R4
f_{nb}	0.8	0.9	1	0.8	0.9

b) Auxiliary thermal devices

If $P_T < P_{r1}$, gearboxes are avalible with auxiliary thermal devices (FV, PFAN, CRX).

Supplementary cooling systems are made up of an air-oil heat exchanger, a motor pump, a fi lter for warm oil and an electric system that incorporates an overload cutout for electric motors.
A special feature of these cooling systems is their low noise.



Technical data

(A 21)

		CR1	CR2	CR3
Power absorbtion	[kW]	0.55	0.75	1.1
Pumpflow	[l/min]	13	22	34
Air flow	[m3/h]	850	1500	200
Noise level at 1 mt.	[dB(A)]	68	70	75
Weight	[kg]	24	36	58

Calculate excess power P_s using this formula:

$$P_s = (1 - \eta_d) \times (P_{r1} - P_T) \quad (27)$$

Select thermal device according the following chart.



Electric motor connection with integrated fan - PF



	L1	L2	L3	L4	R2	R3	R4
300	PF1*	PF1*	PF1*	PF1*	PF1*	PF1*	PF1*
301	PF1*	PF1*	PF1*	PF1*	PF1*	PF1*	PF1*
303	PF1*	PF1	PF1	PF1	PF1*	PF1*	PF1*
304	PF1*	PF1	PF1	PF1	PF1*	PF1*	PF1*
305	PF1*	PF1	PF1	PF1	PF1*	PF1*	PF1*
306	PF1	PF1	PF1	PF1	PF1*	PF1*	PF1*
307	PF2*	PF1	PF1	PF1	PF1*	PF1*	PF1*
309	PF2*	PF1*	PF1	PF1	PF1*	PF1*	PF1*
310M	PF2*	PF1*	PF1	PF1	PF1*	PF1*	PF1*
311M	PF2	PF2	PF1	PF1	PF1*	PF1*	PF1*
313M	—	PF2	PF1	PF1	PF1*	PF1*	PF1*
314M	—	PF2	PF1	PF1	—	PF1*	PF1*
315M	—	PF2	PF2	PF1	—	PF1*	PF1*
316M	—	PF2	PF2	PF1	—	PF1*	PF1*
317M	—	—	PF2	PF1	—	PF1*	PF1*
318M	—	—	PF2	PF2	—	—	PF1*
319	—	—	PF2	PF2	—	—	PF1*
321	—	—	—	PF2	—	—	PF1*
323	—	—	—	PF2	—	—	—
325	—	—	—	PF2	—	—	—

* For R execution and For T, V mounting position

BONFIGLIOLI TECHNICAL SERVICE

Solid input shaft with fan - FV



Check that the cooling system you have selected will fit the gearbox (see table A22).
If this is not the case, contact our sales organization.

(A 22)

Gearbox	L1	L2	L3	L4	R2	R3	R4
306	CR1	CR1	—	—	—	—	—
307	CR1	CR1	—	—	CR1	—	—
309	CR1	CR1	CR1	—	CR1	—	—
310M	CR2	CR1	CR1	—	—	CR1	—
311M	CR2	CR1	CR1	—	CR1	CR1	—
313M	CR2	CR1	CR1	—	CR1	CR1	—
314M	CR3	CR2	CR1	—	—	CR1	—
315M	CR3	CR2	CR1	—	—	CR1	—
316M	CR3	CR2	CR1	—	—	CR1	—
317M	CR3	CR2	CR2	CR1	—	—	—
318M	CR3	CR2	CR2	CR1	—	—	—
319	CR3	CR2	CR2	CR1	—	—	—
321	CR3	CR2	CR2	CR2	—	—	—

Dimensions







(A 23)

	A	B	C	D	E	F	G	H
CR1	410	395	193	370	250	400	200	1/2" Gas
CR2	450	405	203	470	250	500	200	3/4" Gas
CR3	495	455	225	520	290	550	240	3/4" Gas

c) Maximum torque

Make sure that neither the momentary peak torque nor the starting torque under load ever exceed the $\mathbf{M_{2max}}$ value that the gearbox is rated for (see figure A2).

d) Radial loads

Examine the application and establish:
- overhung load applying to input and/or output shaft through the following formula:

$$R_{c1-2} = \frac{2000 \times M_{r1-2} \times K_r}{d} \quad (28)$$

R_{c1-2} = overhung load [N]
1 = for input shaft
2 = for output shaft
M_{r1-2} = Torque at the shaft [Nm]
d = P.C.D [mm] of transmission element (sprocket, gear, pulley, etc.)
K_r =1 chain transmission
K_r =1.25 gear transmission
K_r =1.5-2.5 V-belt transmission

- Define the trust load position X onto shaft. Check this value with the chart indicating the load R_{x1-2} bearable by the gearbox. Check that the following is satisfied:

$$R_{c1-2} \leq Rx_{1-2} \times fh_{1-2} \quad (29)$$

where fh_{1-2} are the radial and thrust load corrective factor depending on the required life factor Fh_1 and Fh_2 (refers to radial and thrust loads in the "Dimensions" chapter).

e) Thrust loads
Check the thrust load, when exerted onto the output shaft, as specified for the radial load.
The following should be satisfied:

$$\pm A_{c2} \leq \pm A_{n2} \times fh_2 \qquad (30)$$

(A 24)



where fh_2 are the radial and thrust load corrective factor depending on the required life factor Fh_2 (refers to radial and thrust loads in the "Dimensions" chapter).

When a thrust load is combined with an axial load contact our Sales Dept. for a proper checking procedure.

f) VK output
Determine:
- Radial load $\mathbf{R_{c2}}$
- Thrust load $\mathbf{A_{c2}}$
- Offset x of load $\mathbf{R_{c2}}$

Look up the diagram relevant to the gearbox under study and identify permitted radial load **Rx2** corresponding to distance X and the ratio **An2/Rn2** nearest to value **Ac2/Rc2**.
Make sure the following equation is verified:

$$R_{x2} \geq R_{c2} \qquad (31)$$

Values in the diagram refer to:
- n_2 = 10 rpm
- 10000 hrs theoretical lifetime

For different output speed $\mathbf{n_2}$, or lifetime expectancy, consider:
- a speed factor $\mathbf{f_{n2}}$ as per table (A25):

(A 25)

n_2	1	2.5	5	10	15	25	50	100
f_{n2}	2.0	1.51	1.23	1.00	0.88	0.76	0.62	0.50

- a lifetime factor $\mathbf{f_L}$ according to table (A26).

(A 26)

Lifetime	2500 h	5000 h	10000 h	15000 h	25000 h	50000 h	100000 h	100
f_L	0.66	0.81	1.00	1.13	1.32	1.62	2.00	0.50

This condition must be verified:

$$R_{x2} \times f_{n2} \geq R_{c2} \times f_L \quad (32)$$

g) FP output (FDK and FZP when and if available)
On shaft-mounted installations, gearmotors produce a reaction force due to fixing position and motor weight and/or external loads from other connection elements.

These forces combination is added to normal load condition and will influence :
• berings life
• output shaft resistance
• flange tightening condition

In the event that there is an additional load (like a large size electric motor) and /or a single stage gearbox (with particular attention to sizes from 300 to 307), it' recommended to contact our Technical Service.
For the specific reaction loads due to fixing position, in the dimensional section for each size are reported the minimum lenght for torque reaction arms (single or double) that can reach the rated performances.

14,6 HOW TO SELECT THE MOTOR

14.6.1 Electric motor (see section M in this catalogue)

a) n_2 and dynamic efficiency η_d are known, calculate input power based on torque M_{r2} as follows

$$P_{r1} = \frac{M_{r2} \times n_2}{9550 \times \eta_d} \ [kW] \quad (33)$$

Table (A3) reports the values of efficiency ηd related to the different reduction stages of the gearboxes of series 300M.

b) Look up the motor selection charts and select a size with such rated power to satisfy this condition:

$$P_{r1} \leq P_n \quad (34)$$

4-pole motors and over should be preferred.

Unless otherwise specified, power P_n of motors indicated in the catalogue refers to continuous duty S1. For motors used in conditions other than S1, the type of duty required by reference to CEI 2-3/IEC 34-1 Standards must be mentioned.
For duties from S2 to S8 in particular and for motor frame 132 or smaller, extra power can be obtained with respect to continuous duty power, consequently the following condition must be satisfied:

$$\frac{P_{r1}}{f_m} \leq P_n \quad (35)$$

The increased power factor f_m can be obtained from table (A5).

For duties other than S1 with considerable number of starts per hour, factor Z must be considered (it is ascertained by using the information in the motors chapter). Factor Z defines the maximum number of starts for the application under consideration.

14.6.2 Hydraulic motor (see section H in this catalogue)

Determine hydraulic motor type according to the application, choosing from the options given in guidance table (A27).

(A 27)

Duty	Light		Medium		Heavy	
Pressure p [bar]	<175		175 - 200		200 - 450	
Motor design	orbital	gear motor 	radial piston	axial piston 	cam motor 	axial piston 
Speed	medium ≤ 700	high ≤ 3000	medium ≤ 500	high ≤ 4000	low ≤ 200	medium ≤ 4000
ηmh	0.80	0.85	0.95	0.93	0.93	0.93
ηv	0.90	0.87	0.95	0.95	0.95	0.95

Based on the specifications of gearbox input:

- input torque M_{r1} [Nm]
- input speed n_1 [min^{-1}]

and on allowed pressure p [bar] for the hydraulic circuit, calculate the displacement of the hydraulic motor by formula:

$$V_c = \frac{20 \times \pi \times M_{r1}}{p \times \eta mh} \ [cm^3] \qquad (36)$$

Where ηmh is the hydraulic mechanical efficiency of the motor (tab. A27).

Select a motor size with displacement V that satisfies the following condition:

$$V_c \leq V \qquad (37)$$

Calculate the flow required for the hydraulic motor

$$Q_1 = \frac{V \times n_1}{\eta_v \times 1000} \ [l/min] \qquad (38)$$

where η_v is volumetric efficiency.
For hydraulic orbital motors by BONFIGLIOLI TRASMITAL, please see section H in this catalogue. For other types of hydraulic motors, see the relevant technical literature.

15 INSTALLATION

Observing a few rules for correct installation is essential to the reliable and proper operation of the gearbox.
The rules set out here are intended as a preliminary guide to selecting gearbox.
For effective and proper installation, follow the instructions given in the Installation, use and maintenance manual available from our Sales network.
Following is a brief outline of installation rules:

a) Fastening:
– Place the gearbox on a surface providing adequate rigidity. Mating surfaces should be machined and flat.

– This applies especially to flange-mounted gearboxes with splined hollow output shafts (refer to the Installation, Operation and Maintenance Manual available on www.bonfiglioli.com).

– In applications that involve high radial loads at the output end, flange mounting is recommended for some gearboxes as this mounting pattern benefits from the double pilot diameters provided on these gearboxes (refer to the Installation, Operation and Maintenance Manual available on www.bonfiglioli.com).

– Make sure the gearbox is suitable for the required mounting position.

– Use bolts specified in Use and Maintenance Manual (available on www.bonfiglioli.com) and tighten the bolts to the rated values specified in the relevant charts.

b) Connections
– When fitting transmission elements onto the gearbox do not tap them with hammers or similar tools. To slide these parts in, use the service screws and tappings provided at the shaft ends.
Be sure to clean off any grease or rust preventative from the shafts before fitting any parts.

(A 28)



– Direction of rotation
Before wiring the motor please note the input/output shaft arrangement, as described in the diagram here after:

RA/RO: For the monodirectional applications or for the applications requiring a sense of rotation prevailing on that opposite to it, the selection of "**RA/RO**" option ensures the declared performance.
For applications not requiring a prevailing sense of rotation with respect to each other, the performances are guaranteed regardless of the selected "**RA/RO**" option.

c) Paint coating

– Use paint compatible with the primer applied to the gearbox, see "Supply conditions".
Prior to painting, tape the seal rings installed on the shafts. Contact with the solvent may damage the seals with subsequent oil leakage.

d) Lubrication

– Prior to commissioning, fill the gearbox with the recommended type and quantity of oil (refer to the Installation, Operation and Maintenance Manual available on www.bonfiglioli.com). The level is to be checked through the appropriate plug, or sight glass, each gearbox is provided with, and located according to the mounting position originally specified.

NOTE: Combined gearboxes feature separate lubrication for planetary stages and for worm gears (series 3/V_M) or bevel helical units (series 3/A). The operations described above are not to be performed with life-lubed gearboxes, that are factory filled with synthetic oil.

16 LUBRICATION

Refer to the User's Manual available at www.bonfiglioli.com for indications about checking the oil level and its replacement.
Do not mix mineral oils with synthetic oils and/or different brands.
However, oil level should be checked at regular intervals and topped up as required.
Check monthly if unit operates under intermittent duty, more frequently if duty is continuous.

16.1 Selection of the optimal oil viscosity (data relating to Shell Oils)



* = It is recommended to ramp-up and to provide for greater absorption of the motor.
If needed and in the event of impulse loads, contact Bonfiglioli Technical Service.

16.2 Lubrication for 300M series gearboxes

All gearboxes are oil-bath lubricated. For applications calling for gearboxes with a vertically positioned axis, in which oil coverage during operation would not be sufficient to ensure correct lubrication of upper bearings, suitable life lubrication systems are used.

Prior to starting-up, fill the gearbox with the appropriate quantity of oil.
Gearboxes are generally provided with oil fill, level and drain plugs. As such, the mounting position needs always to be specified when ordering the gearbox.
For the reference charts of oil plugs placement and quantity of lubricant, refer to the Installation, Operation and Maintenance Manual (available on www.bonfiglioli.com).

– Note: For applications with non-routine operating conditions, consult factory with complete information.

– Unless otherwise specified, gear units are supplied unlubricated. Primary gear units belonging to 3/V_M and 3/A combinations instead may be supplied factory filled with long-life synthetic lubricant, depending on their frame size, as indicated in the Use and Maintenance Manual (available at www.bonfiglioli.com).

– It is possible, for all gear unit sizes, to request supply in the following oil types, selectable according to the specifications defined in the table.

LUBRICATION	TYPE	DESIGNATION	PRODUTTORE
LH	Polyglycol (PAG)	OMALA S4 WE 150	Shell
LM	Polyglycol (PAG)	OMALA S4 WE 320	

NOTE - The lubrication option is applicable to all configurations except those with hydraulic inputs.

– The oil capacities listed for the various types of unit are indicative only. Fill the gearbox up to the level plug, located as per the mounting position specified when ordering to ensure the gearbox is properly filled.

– Should transmitted power exceed the thermal capacity of the unit a supplementary cooling unit must be provided (see: Auxiliary thermal devices).

NOTE - Combined gearboxes and gearmotors feature separate lubrication for planetary stages and for worm gearboxes (3/V_M) or helical bevel units (3/A).

16.3 Brakes lubrification

The hydraulically operated multidisc brakes are lubricated by the same oil as the gearbox.

17 STORAGE

Observe the following instructions to ensure correct storage of delivered products:

a) Do not store outdoors, in areas exposed to weather or with excessive humidity.

b) Always place boards, wood, or other material between the products and the floor.
The gearbox should not have direct contact with the floor.

c) For storage periods of over 60 days, all machined surfaces such as flanges, shafts and couplings must be protected with a suitable anti-oxidation product.

d) In the cases of long-term storage defined in the order phase with the optional choice of SLM or SLP (see specific chapter for cases and times), the appropriate technical requirements are given in the User Manual available on www.bonfiglioli.com. To guarantee times, conditions and extensions, contact the Bonfiglioli Assistance Center available on the company website.

18 SUPPLY CONDITIONS

Gearboxes are supplied as follows:

a) arranged for installation in the mounting position specified in the purchase order;

b) Unlubricated. Inner parts are protected by a film of the oil used for testing purpose;

c) when no specific protection class is requested, the surfaces of gearboxes are protected to at least corrosivity class C2 (UNI EN ISO 12944-2), realized with a grey antioxidant water-based primer Ral 7042. Mating surface are not coated .

d) tested to factory specifications;

e) suitably packed;

f) complete with mounting hardware for IEC electric or hydrauilc motors;

g) gearboxes lubricated “for life” are factory filled with oil.

19 300M GEARBOX DESIGNATION

3 11M L 2 16.7 HZ

OUTPUT VERSION



MZ: Splined male shaft



HZ: Heavy duty splined male shaft



PZ: Foot base with splined shaft



FZ / FZB: Hollow splined shaft



FP: Hollow shaft for shrink disc



FDK: Hollow shaft with double keyway



MC: Solid keyed shaft



HC: Heavy duty solid keyed shaft



PC: Foot base with solid keyed shaft



VK: Reinforced output with heavy duty keyed shaft for stirrers and mixer



FZP: Hollow splined shaft with axial blockage device (recommended for shaft mounted installation)

Reduction ratio

Fill in the value of the transm. ratio (including point and decimals) reported in the selection charts

Es. : 1/5.33 = 5.33 1/44.6 = 44.6 1/131 = 131

No. OF REDUCTIONS

1, 2, 3, 4

DESIGN

L = Linear



R = Right angle



GEARBOX SIZE

00 = 300	262	**05** = 305	306	**10M** = 310M	354	**15M** = 315M	402	**19** = 319	444
01 = 301	272	**06** = 306	318	**11M** = 311M	366	**16M** = 316M	414	**21** = 321	454
03 = 303	282	**07** = 307	330	**13M** = 313M	378	**17M** = 317M	424	**23** = 323	464
04 = 304	294	**09** = 309	342	**14M** = 314M	390	**18M** = 318M	434	**25** = 325	468

SERIES

6A S5EC A A W0A ... ...

OPTIONS

GASKET
STANDARD = NBR
PV = Fluoro elastomer
(⛔ hydraulic inputs 📞 BONFIGLIOLI TECHNICAL SERVICE)

LUBRICATION
LM (SHELL OMALA S4 WE 320)
LH (SHELL OMALA S4 WE 150)
(⛔ Hydraulic inputs 📞 BONFIGLIOLI TECHNICAL SERVICE)

SURFACE PROTECTION
C2 (default)**, C3, C4** — 43

CERTIFICATES
AC, CC — 45

PAINTING
RAL7042 (default)**, RAL5010, RAL9005, RAL9006, RAL9010** — 43

ONLY FOR RIGHT ANGLE DESIGN
preferential input direction of rotation

RA = left
RO = right

32

SUPPLEMENTARY COOLING SYSTEM
CR1, CR2, CR3 — 26

OUTPUT FITTINGS



P... = Pinions



B0A = Splined bar

M0A = Sleeve coupling

G0A = Shrink disc



W0A = Flange

MOTOR FLANGE ORIENTATION — 477

MOUNTING POSITION — 45

INPUT

Without motor adaptor

V9AA	V9AC	V9AE	V9AG	V9AL
V9AB	V9AD	V9AF	V9AH	



Input keyed shaft

	V01A	V01B	V05B	V06B	V07A	V07B	V10B	V11B	V15B
diam.	Ø24	Ø38	Ø48	Ø60	Ø60	Ø80	Ø80	Ø80	Ø120



Solid input shaft with fan

	FV05B	FV06B	FV07A	FV07B	FV10B	FV11B
diam.	Ø48	Ø60	Ø60	Ø80	Ø80	Ø80



Electric motor connection
P+IEC (P71...P250)

Electric motor connection with integrated fan

PF160	PF180	PF200	PF225	PF250

* For version R and for mounting positions T and V 📞 BONFIGLIOLI TECHNICAL SERVICE



Integrated gearmotor with in-built compact electric motor (available up to size 307)

S2, S3, S4



Hydraulic motor adapter with European standard flange
For motors with U.S.-type flange
(⛔ PV-LM-LH option 📞 BONFIGLIOLI TECHNICAL SERVICE)

S5AP, COAA, HOBA, ... — 478

Hydraulic motor MG
(⛔ PV option 📞 BONFIGLIOLI TECHNICAL SERVICE) — 487

ONLY WITH HYDRAULIC MOTOR ADAPTOR



Standard negative multidisc brake

6 = Type : **4, 5, 6**
A = Braking torque : **A, B, C, ...** — 477

Negative multidisc brake for MG hydraulic motor
SF = Without brake — 493



20 3/V_M GEARBOX DESIGNATION

3/V 10M L 3 1617 PC

OUTPUT VERSION



MZ: Splined male shaft



MC: Solid keyed shaft



HZ: Heavy duty splined male shaft



HC: Heavy duty solid keyed shaft



PZ: Foot base with splined shaft



PC: Foot base with solid keyed shaft



FZ / FZB: Hollow splined shaft



FZP: Hollow splined shaft with axial blockage device (recommended for shaft mounted installation)



FP: Hollow shaft for shrink disc



FDK: Hollow shaft with double keyway

REDUCTION RATIO

Fill in the value of the transm. ratio reported in the selection charts
Es. : 1/773 = 773

No. OF REDUCTIONS

3, 4

DESIGN

L = Combined 300M unit,
2 or 3 planetary stages + worm gear units



GEARBOX SIZE

00 = 3/V 00	266	**05** = 3/V 05	310	**10M** = 3/V 10M	358	**15M** = 3/V 15M	406	**19** = 3/V 19	448
01 = 3/V 01	276	**06** = 3/V 06	322	**11M** = 3/V 11M	370	**16M** = 3/V 16M	418	**21** = 3/V 21	458
03 = 3/V 03	286	**07** = 3/V 07	334	**13M** = 3/V 13M	382	**17M** = 3/V 17M	428		
04 = 3/V 04	298	**09** = 3/V 09	346	**14M** = 3/V 14M	394	**18M** = 3/V 18M	438		

SERIES

Combined 300M gearboxes / Worm gear units

P80 B5 AF W0A ...

OPTIONS

GASKET
STANDARD = NBR
PV = Fluoro elastomer

SURFACE PROTECTION
C2 (default)**, C3, C4**
43

PAINTING
RAL7042 (default)**, RAL5010, RAL9005, RAL9006, RAL9010**
43

CERTIFICATES
AC, CC
45

OUTPUT FITTINGS



P... = Pinions | **B0A =** Splined bar | **M0A =** Sleeve coupling | **G0A =** Shrink disc | **W0A =** Flange

MOUNTING POSITION
47

DESIGN
B5, B14

ENTRATA



Electric motor connection **P+IEC** (P63...P180)

Input keyed shaft **HS**



Integrated gearmotor with in-built compact electric motor **S1, S2, S3**



21 3/A GEARBOX DESIGNATION

3/A 06 L 2 69.9 PC

OUTPUT VERSION



MZ: Splined male shaft



MC: Solid keyed shaft



HZ: Heavy duty splined male shaft



HC: Heavy duty solid keyed shaft



PZ: Foot base with splined shaft



PC: Foot base with solid keyed shaft



FZ / FZB: Hollow splined shaft



FP: Hollow shaft for shrink disc



FDK: Hollow shaft with double keyway

REDUCTION RATIO
Fill in the value of the transm. ratio reported in the selection charts
Es. : 1/19.4 = 19.4 1/175 = 175

No. OF REDUCTIONS
2

DESIGN
L = Combined 300 unit,
1 planetary stages + A helical bevel units



GEARBOX SIZE

00 = 3/A 00 (300+A10)	267	**05 =** 3/A 05 (305+A41)	311
01 = 3/A 01 (301+A20)	277	**06 =** 3/A 06 (306+A50)	323
03 = 3/A 03 (303+A30)	287	**07 =** 3/A 07 (307+A60)	335
04 = 3/A 04 (304+A41)	299		

SERIES
Combined 300 gearboxes / A series helical bevel gear units

S4 EF W0A ...

OPTIONS

GASKET
STANDARD = NBR
PV = Fluoro elastomer

SURFACE PROTECTION
C2 (default)**, C3, C4**
43

PAINTING
RAL7042 (default)**, RAL5010, RAL9005, RAL9006, RAL9010**
43

CERTIFICATES
AC, CC
45

OUTPUT FITTINGS



P... = Pinions | **B0A =** Splined bar | **M0A =** Sleeve coupling | **G0A =** Shrink disc | **W0A =** Flange

MOUNTING POSITION
47

INPUT



Integrated gearmotor with in-built compact electric motor **S2, S3, S4**





Electric motor connection **P+IEC** (P63...P180)



Input keyed shaft **HS**



22 MOTOR DESIGNATION

MOTOR | BRAKE

M 1LA 4 230/400-50 IP54 CLF ... **W** | **FD** 7.5 R SB 220 SA ...

OPTIONS

BRAKE SUPPLY

RECTIFIER TYPE
NB, SB, NBR, SBR

BRAKE HAND RELEASE
R, RM

BRAKE TORQUE

BRAKE TYPE
FD (d.c. brake)
FA (a.c. brake)

TERMINAL BOX POSITION
W (default)**, N, E, S**

MOTOR MOUNTING
— (compact motor)
B5 (IEC - motor)

INSULATION CLASS
CL F standard
CL H option

DEGREE OF PROTECTION
IP55 standard (IP54 - brake motor)

VOLTAGE - FREQUENCY

POLE NUMBER
4, 6, 2/4, 2/6, 2/8, 2/12

MOTOR SIZE
1SD - 5LA (compact motor)
63A - 250M (IEC motor)

MOTOR TYPE
MX-MXN = compact 3-phase, class IE3
BX-BXN = IEC 3-phase, class IE3
ME = compact 3-phase, class IE2
BE = IEC 3-phase, class IE2
M = compact 3-phase, class IE1
BN = IEC 3-phase, class IE1



23 ADDITIONAL OPTIONS

23.1 SURFACE PROTECTION

When no specific protection class is requested, the surfaces of gearboxes are protected to at least corrosivity class C2 (UNI EN ISO 12944-2). For improved resistance to atmospheric corrosion, gearboxes can be delivered with C3 and C4 surface protection, obtained by painting the complete gearbox.

SURFACE PROTECTION	Typical environments	Maximum surface temperature	Corrosivity class according to UNI EN ISO 12944-2
C3	Urban and industrial environments with up to 100% relative humidity (medium air pollution)	120°C	C3
C4	Industrial areas, coastal areas, chemical plant, with up to 100% relative humidity (high air pollution)	120°C	C4

Gearboxes with optional protection to class C3 or C4 are available in a choice of colours.
If no specific colour is requested (see the “PAINTING” option) gearboxes are finished in RAL 7042.
Gearboxes can also be supplied with surface protection for corrosivity class C5 according to UNI EN ISO 12944-2. Contact our Technical Service for further details.

23.2 PAINTING

Gearboxes with optional protection to class C3 or C4 are available in the colours listed in the following table.

PAINTING	Farbe	RAL number
RAL7042*	Traffik Grey A	7042
RAL5010	Gentian Blue	5010
RAL9005	Jet Black	9005
RAL9006	White Aluminium	9006
RAL9010	Pure White	9010
RAL7035	Light Grey	7035
RAL7001	Silver Grey	7001
RAL5015	Sky Blue	5015
RAL7037	Dusty Grey	7037
RAL5024	Pastel Blue	5024

* Gearboxes are supplied in this standard colour if no other colour is specified.

NOTE – “PAINTING” options can only be specified in conjunction with “SURFACE PROTECTION” options.

23.3 LONG TERM STOCK

In presence of the Long Term Stock option the configured product is supplied without the standard lubricant oil but with an anticorrosive protective liquid to grant the integrity and full functionality of the gear unit in those cases where the unit will not be installed immediately but it has to be stocked for a long period of time (installation later than 6 months from delivery).
The warranty conditions are valid 12 months from commissioning (with commissioning within 24 months from delivery) or 24 months from delivery without commissioning.
After 2 years of stock, the unit with the Long Term Stock option needs to be checked by Bonfiglioli assistance center. In case of a product that is not properly preserved, an offer by Bonfiglioli will be issued for a complete restore.
With the recovery activity successfully concluded, the warranty conditions restart from the 12 months of commissioning (with commissioning within 24 months from restore date) or 24 months from restore date

Applicability of the Long Term Stock option:

Gearbox size	Applicability of Long Term Stock option
300 ... 321	**SLM, SLP**

The Long Term Stock option can be requested in 2 versions:

- SLM Long Term Stock_Mineral Oil: option having anti-corrosive protective oil compatible with all mineral-based oil lubricants listed in the "Installation, operation and maintenance" Bonfiglioli manual.
- SLP Long Term Stock_Polyglycol Oil: option having anti-corrosive protective oil compatible with all polyglycol-based oil lubricants listed in the "Installation, operation and maintenance" Bonfiglioli manual.

Note: only one version can be selected. SLM and SLP can't coexist.

When configuring a gear unit or gearmotor with the Long Term Stock option, it is necessary to know the type of lubricating oil that will be used by the customer during the operating period (mineral or polyglycol oil).
Before commissioning a Bonfiglioli product with this option, make sure that the lubricating oil filling activity takes place through the specific filling plug determined by the mounting position indicated on the plate.
With regards to gear units with lifetime lubrication (see table below), the quantity of lubricating oil to top up is not indicated in the relevant "installation, use and maintenance" Bonfiglioli manual. In this case, if the Long Term Stock option is active, it is therefore necessary to contact the Bonfiglioli assistance center to receive this information.

Gearbox size	Lubricant charge quantity
300 ... 321	

23.4 CERTIFICATES

AC - Certificate of compliance
The document certifies the compliance of the product with the purchase order and the construction in conformity with the applicable procedures of the Bonfiglioli Quality System.

CC - Inspection certificate
The document entails checking on order compliance, the visual inspection of external conditions and of mating dimensions. Checking on main functional parameters in unloaded conditions is also performed along with oil seal proofing, both in static and in running conditions. Units inspected are sampled within the shipping batch and marked individually.

23.5 TACONITE SEALS

Taconite seals are recommended for environments characterised by the presence of abrasive dust or powders. Taconite seals incorporate a combination of sealing rings, labyrinths and a grease chamber. This option is available for **FP** and **FZ** version from size 314M to 325.
For detailed information please contact our Technical Service.

24 MOUNTING POSITION

The product designation is only complete when the mounting position is also specified. Please refer to table (A27) for in-line gear units and to (A28) for right angle drives.
Applicable to gear units of sizes 323-325 in O/T mounting position BONFIGLIOLI TECHNICAL SERVICE

24.1 In-line units

(A 27)



24.2 Right angle units

(A 28)

B0 - B1 - B2 - B3



I0 - I1 - I2 - I3



J0 - J1 - J2 - J3



M0 - M1 - M2 - M3



P0 - P1 - P2 - P3



R0 - R1 - R2 - R3



U0 - U1 - U2 - U3



W0 - W1 - W2 - W3



24.3 3/V_M Series

(A 29)

AA - AE - AF - AD



EA - EE - EF - ED



TA - TE - TF - TD



VA - VE - VF - VD



OA - OE - OF - OD



QA - QE - QF - QD



FA - FE - FF - FD



24.4 3/A Series

(A 30)

AA - AE - AF - AD



EA - EE - EF - ED



TA - TE - TF - TD



VA - VE - VF - VD



OA - OE - OF - OD



QA - QE - QF - QD



FA - FE - FF - FD



25 RATING CHARTS

A GEARMOTOR SELECTION BY POWER

B GEARBOX SELECTION BY APPLICATION TORQUE

C GEARBOX SELECTION BY NUMBER OF WORKING CYCLES









25.1 300M L - 300M R GEARMOTOR RATING CHARTS

Reading the rating chart.



1	Rating of electric motor connected to the gearbox
2	Gearbox output speed
3	Rated torque to the output shaft based on: - specified service factor - 10000 h theoretical lifetime
4	Service factor
5	Gear ratio
6	Frame size of the in-line gear unit
7	Frame size of the right-angle gear unit. NOTE: letters (B) (C) near size indication identify different angle reduction dimensions. See dimensions pages.
8	IEC motor size and pole number
9	Integral motor frame size and pole number
10	Permitted overhung loading on output shaft, based on: - service factor f_S=1 - 10000 h theoretical lifetime - speed of output n_2 For forces not applied at shaft middlepoint, see diagrams provided in the specific gearbox overall dimensioning pages



Index with reference to the size page.
Gearmotor sizes refer to combinations with BONFIGLIOLI-manufactured motors

A

300 L		262
300 R		264
301L		272
301R		274
303 L		282
303 R		284
303 VK		292
304 L		294
304 R		296
304 VK		304
305 L		306
305 R		308
305 VK		316
306 L		318
306 R		320
306 VK		328

307 L		330
307 R		332
307 VK		340
309 L		342
309 R		344
309 VK		352
310M L		354
310M R		356
310M VK		364
311M L		366
311M R		368
311M VK		376
313M L		378
313M R		380
313M VK		388
314M L		390
314M R		392
314M VK		400

315M L		402
315M R		404
315M VK		412
316M L		414
316M R		416
317M L		424
317M R		426
318M L		434
318M R		436
319 L		444
319 R		446
321 L		454
321 R		456
323 L		464
325 L		468



The selection of motors takes into account the requirements of Regulation 2009/125/CE (see section M of this catalogue). When the motor rated power is below 0,12kW, **BN/M** motors can be provided. Starting from 1st July 2021 the regulation 2009/125/CE will apply also to motors equipped with brake, and 8 poles motors.

A

P_1 = 0.25 kW

n_2	M_2	S	i							Rn_2 [N]				
min^{-1}	Nm					IE1	IE2	IE1	IE2	MC	MZ	HC/PC	HZ/PZ	FZ
0.47	4470	1.6	2916	**306L4**	—	**BN71A4**	**BE71A4**	—	—	35000	39900	79800	92100	35000
0.57	3710	3.0	2423	**307L4**	—	**BN71A4**	**BE71A4**	—	—	40900	51100	92100	121100	45000
0.59	3580	2.0	2337	**306L4**	—	**BN71A4**	**BE71A4**	—	—	33900	38700	77300	89300	35000
0.62	3440	1.1	2243	**305L4**	—	**BN71A4**	**BE71A4**	—	—	28300	32400	54600	64700	24000
0.67	3180	2.2	2074	**306L4**	—	**BN71A4**	**BE71A4**	—	—	33300	38000	76000	87800	35000
0.69	3050	0.9	1991	**303L4**	—	**BN71A4**	**BE71A4**	—	—	27800	31800	53700	63700	24000
0.69	3050	1.2	1991	**304L4**	—	**BN71A4**	**BE71A4**	—	—	27800	31800	53700	63700	24000
0.69	3050	1.8	1991	**305L4**	—	**BN71A4**	**BE71A4**	—	—	27800	31800	53700	63700	24000
0.74	2840	1.7	1854	**305L4**	—	**BN71A4**	**BE71A4**	—	—	27600	31500	53200	63000	24000
0.76	2780	1.1	1815	**304L4**	—	**BN71A4**	**BE71A4**	—	—	27500	31400	53000	62800	24000
0.87	2430	0.9	1586	**303L4**	—	**BN71A4**	**BE71A4**	—	—	27000	30800	52000	61600	24000
0.87	2430	1.6	1586	**304L4**	—	**BN71A4**	**BE71A4**	—	—	27000	30800	52000	61600	24000
0.87	2430	2.0	1586	**305L4**	—	**BN71A4**	**BE71A4**	—	—	27000	30800	52000	61600	24000
1.0	2100	1.2	1370	**303L4**	—	**BN71A4**	**BE71A4**	—	—	26400	30200	50900	60300	23900
1.0	2060	1.8	1344	**304L4**	—	**BN71A4**	**BE71A4**	—	—	26300	30100	50800	60200	23800
1.0	2100	2.2	1370	**305L4**	—	**BN71A4**	**BE71A4**	—	—	26400	30200	50900	60300	23900
1.1	1950	1.2	1275	**301L4**	—	**BN71A4**	**BE71A4**	—	—	8090	8090	26800	29200	7790
1.1	1960	1.4	1278	**303L4**	—	**BN71A4**	**BE71A4**	—	—	26100	29900	50400	59700	23400
1.1	1950	2.0	1271	**304L4**	—	**BN71A4**	**BE71A4**	—	—	26100	29900	50400	59700	23400
1.1	1960	2.8	1278	**305L4**	—	**BN71A4**	**BE71A4**	—	—	26100	29900	50400	59700	23400
1.2	1700	1.0	1108	**301L4**	—	**BN71A4**	**BE71A4**	—	—	7930	7930	26200	28700	7440
1.2	1780	1.6	1164	**304L4**	—	**BN71A4**	**BE71A4**	—	—	25800	29500	49700	59000	22700
1.3	1680	1.4	1098	**303L4**	—	**BN71A4**	**BE71A4**	—	—	25600	29200	49300	58500	22200
1.3	1680	2.7	1098	**305L4**	—	**BN71A4**	**BE71A4**	—	—	25600	29200	49300	58500	22200
1.4	1560	1.5	1022	**301L4**	—	**BN71A4**	**BE71A4**	—	—	7840	7840	25900	28300	7240
1.4	1560	1.8	1018	**303L4**	—	**BN71A4**	**BE71A4**	—	—	25300	28900	48800	57800	21700
1.4	1560	2.5	1018	**304L4**	—	**BN71A4**	**BE71A4**	—	—	25300	28900	48800	57800	21700
1.5	1440	1.6	942	**301L4**	—	**BN71A4**	**BE71A4**	—	—	7750	7750	25600	28000	7040
1.5	1370	1.6	896	**303L4**	—	**BN71A4**	**BE71A4**	—	—	24800	28400	47900	56800	20800
1.7	1250	0.9	819	**300L4**	—	**BN71A4**	**BE71A4**	—	—	7590	7590	25100	29200	6720
1.7	1250	1.8	819	**301L4**	—	**BN71A4**	**BE71A4**	—	—	7590	7590	25100	27400	6720
1.7	1250	2.2	816	**303L4**	—	**BN71A4**	**BE71A4**	—	—	24500	28000	47300	56000	20100
1.7	1220	1.5	797	—	**303R4**	**BN71A4**	**BE71A4**	—	—	24400	27900	47100	55900	20000
1.7	1260	1.8	824	—	**303R4**	**BN71A4**	**BE71A4**	—	—	24500	28100	47300	56100	20200
1.7	1220	2.9	797	—	**305R4**	**BN71A4**	**BE71A4**	—	—	24400	27900	47100	55900	20000
1.8	1160	1.0	755	**300L4**	—	**BN71A4**	**BE71A4**	—	—	7500	7500	24800	28900	6540
1.8	1160	1.9	755	**301L4**	—	**BN71A4**	**BE71A4**	—	—	7500	7500	24800	27100	6540
1.8	1170	1.3	766	—	**301R4**	**BN71A4**	**BE71A4**	—	—	7520	7520	24900	27200	6580
1.9	1100	2.0	718	**303L4**	—	**BN71A4**	**BE71A4**	—	—	24100	27500	46400	55000	19300
2.0	1080	2.5	702	**304L4**	—	**BN71A4**	**BE71A4**	—	—	24000	27400	46300	54800	19200
2.0	1070	2.5	699	—	**304R4**	**BN71A4**	**BE71A4**	—	—	24000	27400	46300	54800	19100
2.1	990	2.3	649	**303L4**	—	**BN71A4**	**BE71A4**	—	—	23700	27100	45800	54200	18700
2.1	1010	2.1	659	—	**303R4**	**BN71A4**	**BE71A4**	—	—	23800	27200	45900	54400	18800
2.2	940	1.2	616	**300L4**	—	**BN71A4**	**BE71A4**	—	—	7290	7290	24100	28000	6110
2.2	940	2.3	616	**301L4**	—	**BN71A4**	**BE71A4**	—	—	7290	7290	24100	26400	6110
2.3	940	1.6	613	—	**301R4**	**BN71A4**	**BE71A4**	—	—	7290	7290	24100	26300	6100
2.4	870	2.8	567	—	**303R4**	**BN71A4**	**BE71A4**	—	—	23300	26600	44900	53200	17800
2.5	850	1.3	558	**300L4**	—	**BN71A4**	**BE71A4**	—	—	7190	7190	23800	27600	5920



P_1 = 0.25 kW

n_2	M_2	S	i			IE1	IE2	IE1	IE2	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
2.5	850	2.5	558	**301L4**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	7190	7190	23800	26000	5920
2.5	860	3.0	560	**—**	**304R4**	**BN71A4**	**BE71A4**	**—**	**—**	23200	26500	44800	53100	17800
2.6	810	2.6	528	**—**	**303R4**	**BN71A4**	**BE71A4**	**—**	**—**	23000	26300	44400	52700	17400
2.8	760	1.4	494	**300L4**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	7060	7060	23400	27200	5680
2.8	750	1.0	491	**—**	**300R4**	**BN71A4**	**BE71A4**	**—**	**—**	7060	7060	23300	27100	5670
2.8	760	2.8	494	**301L4**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	7060	7060	23400	25500	5680
2.8	750	1.9	491	**—**	**301R4**	**BN71A4**	**BE71A4**	**—**	**—**	7060	7060	23300	25500	5670
3.0	690	1.5	453	**—**	**300R4**	**BN71A4**	**BE71A4**	**—**	**—**	6980	6980	23100	26800	5520
3.0	690	2.8	453	**—**	**301R4**	**BN71A4**	**BE71A4**	**—**	**—**	6980	6980	23100	25200	5520
3.1	680	1.5	447	**300L4**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	6960	6960	23000	26800	5490
3.4	620	1.1	403	**300L4**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	6860	6860	22700	26400	5310
3.4	620	2.2	403	**301L4**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	6860	6860	22700	24800	5310
3.5	600	1.1	394	**—**	**300R4**	**BN71A4**	**BE71A4**	**—**	**—**	6840	6840	22600	26300	5270
3.5	600	2.3	394	**—**	**301R4**	**BN71A4**	**BE71A4**	**—**	**—**	6840	6840	22600	24700	5270
3.5	610	2.8	389	**303L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	22100	25200	42500	50400	15700
3.7	590	1.2	374	**300L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	6790	6790	22500	26100	5180
3.7	590	2.3	374	**301L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	6790	6790	22500	24500	5180
3.8	560	1.8	363	**—**	**300R4**	**BN71A4**	**BE71A4**	**—**	**—**	6760	6760	22400	26000	5130
4.2	510	1.9	330	**300L4**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	6670	6670	22100	25600	4970
4.6	470	1.4	299	**300L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	6570	6570	21700	25300	4810
4.6	470	2.8	299	**301L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	6570	6570	21700	23800	4810
4.7	450	2.2	291	**—**	**300R4**	**BN71A4**	**BE71A4**	**—**	**—**	6550	6550	21700	25200	4760
5.1	410	2.3	268	**—**	**300R4**	**BN71A4**	**BE71A4**	**—**	**—**	6500	6500	21500	25000	4630
5.8	380	1.7	240	**300L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	6500	6500	21500	25000	4460
5.8	360	1.8	237	**—**	**300R4**	**BN71A4**	**BE71A4**	**—**	**—**	6500	6500	21500	25000	4450
6.2	350	2.6	221	**300L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	6500	6500	21500	25000	4340
6.4	330	2.8	215	**—**	**300R4**	**BN71A4**	**BE71A4**	**—**	**—**	6500	6500	21500	25000	4300
7.2	300	2.1	192	**300L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	6500	6500	21500	25000	4150
9.6	220	3.0	143	**—**	**300R4**	**BN71A4**	**BE71A4**	**—**	**—**	6500	6500	21500	25000	3760
10.4	210	2.6	133	**—**	**300R3**	**BN71A4**	**BE71A4**	**—**	**—**	6420	6420	21300	24700	3670

P_1 = 0.37 kW

n_2	M_2	S	i			IE1	IE2	IE1	IE2	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
0.47	6710	1.0	2916	**306L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	35000	40000	79900	92200	35000
0.57	5580	2.0	2423	**307L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	41000	51200	92200	121200	45000
0.59	5380	1.3	2337	**306L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	34000	38700	77400	89400	35000
0.66	4770	1.5	2074	**306L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	33400	38100	76100	87900	35000
0.69	4580	1.2	1991	**305L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	27900	31900	53800	63700	24000
0.74	4270	1.1	1854	**305L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	27600	31500	53200	63100	24000
0.74	4240	2.4	1843	**306L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	32800	37400	74800	86400	35000
0.86	3650	1.1	1586	**304L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	27000	30800	52000	61700	24000
0.86	3650	1.3	1586	**305L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	27000	30800	52000	61700	24000
0.86	3680	2.3	1597	**306L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	32200	36700	73300	84600	35000
0.93	3390	3.0	1475	**306L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	31800	36200	72500	83700	35000
1.0	3090	1.2	1344	**304L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	26400	30100	50800	60200	23800
1.0	3150	1.5	1370	**305L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	26400	30200	51000	60400	24000
1.1	2940	1.0	1278	**303L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	26200	29900	50500	59800	23500
1.1	2930	1.3	1271	**304L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	26100	29900	50400	59800	23400
1.1	2940	1.9	1278	**305L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	26200	29900	50500	59800	23500
1.1	2940	2.9	1279	**306L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	31200	35500	71000	82000	34200
1.2	2530	0.9	1098	**303L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	25600	29300	49400	58500	22300
1.2	2680	1.1	1164	**304L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	25800	29500	49800	59000	22700
1.2	2530	1.8	1098	**305L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	25600	29300	49400	58500	22300
1.3	2350	1.0	1022	**301L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	7840	7840	25900	28400	7250
1.3	2340	1.2	1018	**303L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	25300	29000	48900	57900	21700
1.3	2340	1.7	1018	**304L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	25300	29000	48900	57900	21700
1.3	2340	2.3	1018	**305L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	25300	29000	48900	57900	21700
1.5	2170	1.1	942	**301L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	7750	7750	25600	28000	7060
1.5	2060	1.1	896	**303L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	24900	28400	48000	56900	20800
1.5	2060	2.1	896	**305L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	24900	28400	48000	56900	20800



P_1 = 0.37 kW

n_2	M_2	S	i			IE1	IE2	IE1	IE2	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
1.7	1880	1.2	819	**301L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	7600	7600	25100	27500	6740
1.7	1880	1.5	816	**303L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	24500	28000	47300	56100	20200
1.7	1830	1.0	797	**—**	**303R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	24500	28000	47200	55900	20000
1.7	1900	1.2	824	**—**	**303R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	24600	28100	47400	56200	20300
1.7	1880	2.0	816	**304L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	24500	28000	47300	56100	20200
1.7	1880	2.9	816	**305L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	24500	28000	47300	56100	20200
1.7	1830	1.9	797	**—**	**305R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	24500	28000	47200	55900	20000
1.7	1900	2.3	824	**—**	**305R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	24600	28100	47400	56200	20300
1.8	1740	1.3	755	**301L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	7510	7510	24800	27200	6560
1.9	1650	1.3	718	**303L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	24100	27500	46500	55100	19400
1.9	1650	2.5	718	**305L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	24100	27500	46500	55100	19400
2.0	1620	1.7	702	**304L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	24000	27500	46300	54900	19200
2.0	1610	1.7	699	**—**	**304R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	24000	27400	46300	54900	19200
2.1	1490	1.6	649	**303L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	23800	27100	45800	54300	18700
2.1	1520	1.4	659	**—**	**303R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	23800	27200	45900	54400	18800
2.1	1490	2.4	649	**304L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	23800	27100	45800	54300	18700
2.1	1520	2.7	659	**—**	**305R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	23800	27200	45900	54400	18800
2.2	1420	1.5	616	**301L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	7300	7300	24100	26400	6130
2.2	1410	1.1	613	**—**	**301R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	7290	7290	24100	26400	6120
2.4	1300	1.9	567	**—**	**303R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	23300	26600	44900	53300	17900
2.4	1290	2.0	560	**—**	**304R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	23300	26600	44800	53200	17800
2.5	1280	1.7	558	**301L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	7190	7190	23800	26000	5930
2.5	1280	2.2	556	**303L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	23200	26600	44800	53100	17800
2.5	1280	2.9	556	**304L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	23200	26600	44800	53100	17800
2.6	1220	1.7	528	**—**	**303R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	23100	26400	44500	52700	17500
2.8	1140	0.9	494	**300L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	7070	7070	23400	27200	5690
2.8	1140	1.8	494	**301L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	7070	7070	23400	25600	5690
2.8	1130	1.3	491	**—**	**301R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	7070	7070	23400	25500	5680
2.8	1130	2.4	492	**303L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	22800	26100	44000	52200	17100
3.0	1040	1.0	453	**—**	**300R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6980	6980	23100	26900	5530
3.0	1040	1.9	453	**—**	**301R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6980	6980	23100	25300	5530
3.0	1040	2.2	452	**—**	**303R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	22600	25800	43500	51600	16600
3.1	1030	1.0	447	**300L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6970	6970	23100	26800	5510
3.1	1030	2.0	447	**301L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6970	6970	23100	25200	5510
3.1	1030	2.7	446	**303L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	22500	25700	43400	51500	16500
3.2	1010	2.5	426	**304L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	22400	25600	43100	51100	16300
3.3	950	2.5	413	**303L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	22300	25500	42900	50900	16100
3.3	950	2.6	414	**—**	**304R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	22300	25500	43000	50900	16100
3.4	930	1.5	403	**301L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6870	6870	22700	24800	5320
3.4	950	2.1	402	**303L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	22200	25300	42800	50700	15900
3.5	910	1.5	394	**—**	**301R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6850	6850	22600	24700	5280
3.5	920	1.8	389	**303L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	22100	25200	42600	50500	15800
3.5	900	2.2	390	**—**	**303R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	22100	25200	42600	50500	15800
3.7	890	1.5	374	**301L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6800	6800	22500	24600	5190
3.8	840	1.2	363	**—**	**300R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6770	6770	22400	26000	5140
3.8	840	2.4	363	**—**	**301R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6770	6770	22400	24500	5140
3.8	840	2.8	364	**—**	**303R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	21900	25000	42200	50000	15400
4.1	760	1.3	330	**300L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6680	6680	22100	25700	4980
4.1	760	2.6	330	**301L4**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6680	6680	22100	24100	4980
4.1	770	3.0	336	**—**	**303R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	21600	24700	41700	49400	15000
4.3	760	2.5	321	**303L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	21500	24600	41400	49100	14800
4.4	720	2.6	313	**—**	**303R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	21400	24500	41300	48900	14700
4.6	710	0.9	299	**300L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6580	6580	21800	25300	4820
4.6	710	1.9	299	**301L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6580	6580	21800	23800	4820
4.7	670	1.4	291	**—**	**300R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6560	6560	21700	25200	4770
4.7	670	2.9	291	**—**	**301R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6560	6560	21700	23700	4770
5.1	620	1.5	268	**—**	**300R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	25000	4650
5.7	570	1.1	240	**300L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	25000	4470
5.7	570	2.3	240	**301L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	23500	4470
5.8	550	1.2	237	**—**	**300R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	25000	4460
5.8	550	2.4	237	**—**	**301R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	23500	4460
6.2	520	1.8	221	**300L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	25000	4350
6.4	490	1.9	215	**—**	**300R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	25000	4310
7.1	460	1.4	192	**300L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	25000	4160
7.1	460	2.9	192	**301L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	23500	4160



P_1 = 0.37 kW

n_2	M_2	S	i			IE1	IE2	IE1	IE2	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
7.7	420	2.1	177	**300L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	25000	4040
7.8	400	2.2	175	**—**	**300R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	25000	4030
8.6	370	2.4	159	**—**	**300R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	25000	3900
9.6	330	2.0	143	**—**	**300R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	25000	3770
9.7	340	2.6	142	**300L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	25000	3760
10.3	320	1.7	133	**—**	**300R3**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6430	6430	21300	24800	3680
10.5	310	2.8	131	**300L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6400	6400	21200	24700	3660
10.6	300	2.9	130	**—**	**300R4**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6380	6380	21100	24600	3650
11.8	270	2.4	116	**300L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6150	6150	20400	23800	3510
12.9	250	2.6	106	**—**	**300R3**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	5980	5980	19900	23200	3410

P_1 = 0.55 kW

n_2	M_2	S	i			IE1	IE2	IE1	IE2	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
0.55	8490	2.8	2523	**310ML4**	**—**	**BN80A4**	**BE80A4**	**—**	**—**	—	—	106900	135500	65000
0.57	8150	1.3	2423	**307L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	40900	51100	92000	121000	45000
0.57	8150	2.1	2423	**309L4**	**—**	**BN80A4**	**BE80A4**	**—**	**—**	—	—	94000	121000	36000
0.67	6980	1.0	2074	**306L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	33300	38000	76000	87700	35000
0.68	6870	2.1	2041	**307L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	39900	49900	89700	118100	45000
0.69	6740	2.5	2003	**309L4**	**—**	**BN80A4**	**BE80A4**	**—**	**—**	—	—	91500	117700	36000
0.75	6200	1.6	1843	**306L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	32800	37300	74700	86200	35000
0.79	5950	2.6	1767	**307L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	39100	48800	87900	115700	45000
0.81	5800	2.9	1723	**309L4**	**—**	**BN80A4**	**BE80A4**	**—**	**—**	—	—	89500	115200	36000
0.87	5370	1.6	1597	**306L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	32100	36600	73200	84500	35000
0.87	5350	2.8	1591	**307L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	38500	48100	86600	113900	45000
0.94	4960	2.0	1475	**306L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	31700	36200	72300	83500	35000
1.0	4610	1.0	1370	**305L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	26400	30100	50900	60300	23900
1.1	4280	0.9	1271	**304L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	26100	29800	50300	59600	23300
1.1	4300	1.3	1278	**305L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	26100	29800	50400	59700	23300
1.1	4300	2.0	1279	**306L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	31100	35400	70900	81800	34000
1.1	4290	2.9	1274	**307L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	37300	46600	83900	110400	43700
1.3	3690	1.2	1098	**305L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	25600	29200	49300	58400	22200
1.3	3680	2.1	1095	**306L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	30400	34700	69300	80000	32300
1.4	3430	1.1	1018	**304L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	25300	28900	48800	57800	21600
1.4	3430	1.6	1018	**305L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	25300	28900	48800	57800	21600
1.4	3410	2.8	1015	**306L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	30100	34300	68600	79200	31500
1.6	3020	1.4	896	**305L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	24800	28400	47900	56700	20700
1.6	2950	2.6	877	**306L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	29500	33600	67200	77500	30000
1.7	2750	1.0	816	**303L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	24500	28000	47200	56000	20100
1.7	2750	1.4	816	**304L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	24500	28000	47200	56000	20100
1.7	2750	2.0	816	**305L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	24500	28000	47200	56000	20100
1.7	2680	1.3	797	**—**	**305R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	24400	27900	47100	55800	19900
1.7	2770	1.5	824	**—**	**305R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	24500	28000	47300	56100	20200
1.7	2720	2.8	809	**306L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	29100	33200	66400	76600	29200
1.7	2790	2.3	830	**—**	**306R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	29200	33300	66600	76900	29500
1.9	2420	0.9	718	**303L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	24000	27500	46400	55000	19300
1.9	2420	1.7	718	**305L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	24000	27500	46400	55000	19300
2.0	2360	1.1	702	**304L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	24000	27400	46200	54800	19100
2.0	2350	1.1	699	**—**	**304R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	24000	27400	46200	54800	19100
2.1	2180	1.1	649	**303L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23700	27100	45700	54200	18600
2.1	2220	1.0	659	**—**	**303R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23800	27100	45800	54300	18700
2.1	2180	1.6	649	**304L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23700	27100	45700	54200	18600
2.1	2180	2.1	649	**305L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23700	27100	45700	54200	18600
2.1	2220	1.9	659	**—**	**305R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23800	27100	45800	54300	18700
2.1	2240	2.7	665	**—**	**306R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	28300	32300	64600	74500	27400
2.3	2070	1.0	616	**301L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	7280	7280	24100	26300	6100
2.5	1880	1.1	558	**301L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	7180	7180	23700	26000	5900
2.5	1870	1.5	556	**303L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23200	26500	44700	53000	17700
2.5	1910	1.3	567	**—**	**303R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23200	26600	44800	53100	17800
2.5	1870	2.0	556	**304L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23200	26500	44700	53000	17700
2.5	1880	1.4	560	**—**	**304R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23200	26500	44800	53000	17700



P_1 = 0.55 kW

n_2	M_2	S	i			IE1	IE2	IE1	IE2	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
2.5	1870	2.9	556	**305L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23200	26500	44700	53000	17700
2.5	1910	2.6	567	**—**	**305R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23200	26600	44800	53100	17800
2.6	1780	1.2	528	**—**	**303R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23000	26300	44400	52600	17400
2.6	1780	2.2	528	**—**	**305R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23000	26300	44400	52600	17400
2.8	1660	1.3	494	**301L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	7060	7060	23300	25500	5670
2.8	1660	1.6	492	**303L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22800	26000	43900	52100	17000
2.8	1660	2.3	492	**304L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22800	26000	43900	52100	17000
3.1	1500	1.4	447	**301L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6960	6960	23000	25100	5480
3.1	1520	1.3	453	**—**	**301R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6970	6970	23100	25200	5510
3.1	1500	1.9	446	**303L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22500	25700	43300	51300	16400
3.1	1520	1.5	452	**—**	**303R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22500	25700	43400	51400	16500
3.1	1500	2.5	446	**304L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22500	25700	43300	51300	16400
3.1	1520	2.4	452	**—**	**304R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22500	25700	43400	51400	16500
3.3	1480	1.7	426	**304L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22300	25500	43000	51000	16200
3.4	1360	1.0	403	**301L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6850	6850	22700	24800	5300
3.4	1390	1.7	413	**303L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22200	25400	42900	50800	16000
3.4	1390	2.2	413	**304L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22200	25400	42900	50800	16000
3.4	1390	1.8	414	**—**	**304R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22200	25400	42900	50800	16000
3.5	1320	1.0	394	**—**	**301R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6830	6830	22600	24700	5250
3.5	1390	1.4	402	**303L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22100	25300	42700	50600	15900
3.5	1390	2.7	402	**305L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22100	25300	42700	50600	15900
3.6	1350	1.3	389	**303L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22000	25200	42500	50400	15700
3.6	1310	1.5	390	**—**	**303R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22000	25200	42500	50400	15700
3.6	1350	2.4	389	**305L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22000	25200	42500	50400	15700
3.6	1310	2.9	390	**—**	**305R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22000	25200	42500	50400	15700
3.7	1300	1.1	374	**301L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6780	6780	22400	24500	5160
3.8	1220	1.6	363	**—**	**301R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6750	6750	22300	24400	5110
3.8	1220	1.9	364	**—**	**303R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21800	24900	42100	49900	15400
3.8	1220	2.4	364	**—**	**304R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21800	24900	42100	49900	15400
4.1	1130	2.0	336	**—**	**303R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21600	24700	41600	49300	14900
4.1	1180	2.1	341	**304L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21600	24700	41700	49400	15000
4.1	1140	2.1	338	**—**	**304R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21600	24700	41600	49300	15000
4.2	1110	1.8	330	**301L4**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6660	6660	22000	24100	4960
4.3	1110	1.7	321	**303L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21400	24500	41300	49000	14700
4.4	1050	1.8	313	**—**	**303R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21400	24400	41200	48800	14600
4.6	1040	1.3	299	**301L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6570	6570	21700	23700	4790
4.8	980	1.0	291	**—**	**300R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6540	6540	21600	25200	4750
4.8	980	2.0	291	**—**	**301R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6540	6540	21600	23700	4750
4.8	980	2.7	290	**—**	**303R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21100	24100	40700	48300	14200
5.0	960	2.3	276	**303L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21000	24000	40500	48000	14000
5.1	950	2.5	273	**304L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21000	24000	40500	48000	14000
5.2	900	1.0	268	**—**	**300R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	25000	4620
5.2	900	2.1	268	**—**	**301R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	23500	4620
5.4	890	2.1	258	**303L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21000	24000	40500	48000	13700
5.4	860	2.1	255	**—**	**303R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21000	24000	40500	48000	13600
5.8	830	1.6	240	**301L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	23500	4450
5.9	800	1.6	237	**—**	**301R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	23500	4440
6.0	780	2.4	231	**—**	**303R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21000	24000	40500	48000	13200
6.3	770	1.2	221	**300L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	25000	4330
6.3	770	2.3	221	**301L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	23500	4330
6.3	760	2.9	220	**303L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21000	24000	40500	48000	13000
6.5	720	1.3	215	**—**	**300R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	25000	4290
6.5	720	2.5	215	**—**	**301R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	23500	4290
7.2	670	1.0	192	**300L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	25000	4140
7.2	670	2.0	192	**301L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	23500	4140
7.3	660	2.8	190	**303L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21000	24000	40500	48000	12400
7.8	610	1.4	177	**300L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	25000	4030
7.8	610	2.9	177	**301L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	23500	4030
7.9	590	1.5	175	**—**	**300R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	25000	4010
8.8	530	1.6	159	**—**	**300R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	25000	3880
9.7	480	1.3	143	**—**	**300R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	25000	3750
9.7	480	2.7	143	**—**	**301R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	23500	3750
9.8	490	1.8	142	**300L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	25000	3740
10.5	460	1.2	133	**—**	**300R3**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6400	6400	21200	24700	3660
10.5	460	2.5	133	**—**	**301R3**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6400	6400	21200	23200	3660



P_1 = 0.55 kW

n_2	M_2	S	i			IE1	IE2	IE1	IE2	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
10.6	450	1.9	131	**300L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6370	6370	21100	24600	3640
10.7	440	2.0	130	**—**	**300R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6350	6350	21100	24500	3630
12.0	400	1.6	116	**300L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6120	6120	20400	23700	3490
13.1	370	1.8	106	**—**	**300R3**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	5950	5950	19800	23100	3400
13.1	360	2.4	106	**—**	**300R4**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	5940	5940	19800	23000	3390
13.3	360	2.4	105	**300L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	5920	5920	19800	23000	3380
16.2	300	2.9	85.6	**300L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	5530	5530	18600	21600	3160
16.3	300	2.2	85.2	**—**	**300R3**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	5520	5520	18600	21600	3150
19.9	240	2.7	69.9	**300L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	5170	5170	17500	20300	2950
20.4	240	2.7	68.2	**—**	**300R3**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	5130	5130	17400	20200	2930
21.5	230	2.4	64.8	**300L2**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	5040	5040	17100	19900	2880

P_1 = 0.75 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
0.57	11200	2.1	2523	**310ML4**	**—**	**BE80B4**	**BX80B4**	**—**	**—**	—	—	106500	135000	65000
0.59	10700	1.0	2423	**307L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	40700	50900	91600	120500	45000
0.59	10700	1.6	2423	**309L4**	**—**	**BE80B4**	**BX80B4**	**—**	**—**	—	—	93600	120500	36000
0.70	9040	1.6	2041	**307L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	39700	49700	89400	117600	45000
0.71	8860	1.9	2003	**309L4**	**—**	**BE80B4**	**BX80B4**	**—**	**—**	—	—	91100	117300	36000
0.71	8950	2.7	2022	**310ML4**	**—**	**BE80B4**	**BX80B4**	**—**	**—**	—	—	103100	130800	65000
0.78	8160	1.2	1843	**306L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	32600	37200	74400	85900	35000
0.81	7820	2.0	1767	**307L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	38900	48600	87600	115200	45000
0.83	7630	2.2	1723	**309L4**	**—**	**BE80B4**	**BX80B4**	**—**	**—**	—	—	89200	114800	36000
0.89	7100	2.4	1605	**309L4**	**—**	**BE80B4**	**BX80B4**	**—**	**—**	—	—	88300	113600	36000
0.90	7070	1.2	1597	**306L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	32000	36400	72900	84100	35000
0.90	7040	2.1	1591	**307L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	38300	47900	86200	113500	45000
0.97	6530	1.5	1475	**306L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	31600	36000	72000	83200	35000
1.0	6230	2.5	1408	**307L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	37700	47100	84800	111500	44800
1.0	6110	2.8	1380	**309L4**	**—**	**BE80B4**	**BX80B4**	**—**	**—**	—	—	86400	111200	35600
1.1	5660	1.0	1278	**305L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	26000	29700	50200	59400	23100
1.1	5660	1.5	1279	**306L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	31000	35300	70600	81500	33700
1.1	5640	2.2	1274	**307L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	37100	46400	83600	109900	43300
1.1	5690	2.9	1286	**309L4**	**—**	**BE80B4**	**BX80B4**	**—**	**—**	—	—	85500	110100	34700
1.2	5120	2.8	1157	**307L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	36600	45800	82400	108400	41900
1.3	4860	0.9	1098	**305L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	25400	29100	49100	58200	22000
1.3	4840	1.6	1095	**306L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	30300	34500	69000	79700	32000
1.4	4510	1.2	1018	**305L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	25200	28800	48600	57500	21400
1.4	4490	2.1	1015	**306L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	30000	34200	68300	78900	31200
1.6	3970	1.1	896	**305L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	24700	28300	47700	56500	20500
1.6	3880	2.0	877	**306L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	29300	33400	66900	77200	29700
1.7	3650	1.2	824	**—**	**305R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	24400	27900	47100	55800	20000
1.7	3680	1.7	830	**—**	**306R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	29100	33200	66400	76600	29200
1.8	3610	1.1	816	**304L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	24400	27900	47000	55800	19900
1.8	3610	1.5	816	**305L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	24400	27900	47000	55800	19900
1.8	3530	1.0	797	**—**	**305R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	24300	27800	46900	55600	19800
1.8	3580	2.2	809	**306L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	29000	33100	66100	76300	28900
2.0	3180	1.3	718	**305L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	24000	27400	46200	54700	19100
2.1	2940	2.1	665	**—**	**306R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	28200	32200	64300	74200	27100
2.2	2870	1.2	649	**304L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	23600	27000	45500	54000	18400
2.2	2870	1.6	649	**305L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	23600	27000	45500	54000	18400
2.2	2920	1.4	659	**—**	**305R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	23700	27000	45600	54100	18500
2.5	2510	1.0	567	**—**	**303R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	23200	26500	44700	52900	17600
2.5	2510	2.0	567	**—**	**305R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	23200	26500	44700	52900	17600
2.6	2460	1.1	556	**303L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	23100	26400	44500	52800	17500
2.6	2460	1.5	556	**304L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	23100	26400	44500	52800	17500
2.6	2480	1.0	560	**—**	**304R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	23100	26400	44600	52800	17600
2.6	2460	2.2	556	**305L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	23100	26400	44500	52800	17500
2.7	2340	1.7	528	**—**	**305R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22900	26200	44200	52400	17200
2.9	2190	1.0	494	**301L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	7030	7030	23200	25400	5610
2.9	2180	1.2	492	**303L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22700	25900	43800	51900	16800



P_1 = 0.75 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
2.9	2180	1.7	492	**304L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22700	25900	43800	51900	16800
2.9	2180	2.5	492	**305L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22700	25900	43800	51900	16800
3.2	1980	1.0	447	**301L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6930	6930	22900	25000	5430
3.2	2010	1.0	453	**—**	**301R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6940	6940	23000	25100	5450
3.2	1970	1.4	446	**303L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22400	25600	43100	51100	16300
3.2	2000	1.1	452	**—**	**303R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22400	25600	43200	51200	16300
3.2	1970	1.9	446	**304L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22400	25600	43100	51100	16300
3.2	2000	1.8	452	**—**	**304R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22400	25600	43200	51200	16300
3.2	1970	2.8	446	**305L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22400	25600	43100	51100	16300
3.2	2000	2.4	452	**—**	**305R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22400	25600	43200	51200	16300
3.4	1940	1.3	426	**304L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22200	25400	42900	50800	16000
3.5	1830	1.3	413	**303L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22100	25300	42700	50600	15900
3.5	1830	1.7	413	**304L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22100	25300	42700	50600	15900
3.5	1830	1.4	414	**—**	**304R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22100	25300	42700	50600	15900
3.5	1830	2.6	413	**305L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22100	25300	42700	50600	15900
3.6	1830	1.1	402	**303L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22000	25200	42500	50400	15700
3.6	1830	2.1	402	**305L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22000	25200	42500	50400	15700
3.7	1770	1.0	389	**303L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21900	25100	42300	50200	15500
3.7	1730	1.1	390	**—**	**303R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22000	25100	42300	50200	15600
3.7	1770	1.8	389	**305L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21900	25100	42300	50200	15500
3.7	1730	2.2	390	**—**	**305R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22000	25100	42300	50200	15600
3.9	1610	1.2	363	**—**	**301R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6730	6730	22200	24300	5070
3.9	1610	1.4	364	**—**	**303R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21700	24800	41900	49700	15200
3.9	1610	1.8	364	**—**	**304R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21700	24800	41900	49700	15200
3.9	1610	2.9	364	**—**	**305R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21700	24800	41900	49700	15200
4.2	1560	1.6	341	**304L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21500	24600	41500	49200	14900
4.2	1490	1.6	338	**—**	**304R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21500	24600	41500	49100	14800
4.3	1460	1.3	330	**301L4**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6640	6640	21900	24000	4910
4.3	1490	1.5	336	**—**	**303R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21500	24600	41400	49100	14800
4.4	1470	1.3	321	**303L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21400	24400	41200	48800	14600
4.4	1470	2.5	321	**305L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21400	24400	41200	48800	14600
4.6	1380	1.4	313	**—**	**303R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21300	24300	41000	48600	14500
4.6	1380	2.6	313	**—**	**305R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21300	24300	41000	48600	14500
4.7	1360	2.6	307	**—**	**304R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21200	24200	40900	48500	14400
4.8	1360	1.0	299	**301L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6540	6540	21600	23700	4750
4.9	1290	1.5	291	**—**	**301R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6520	6520	21600	23600	4700
4.9	1280	2.1	290	**—**	**303R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40600	48100	14100
4.9	1280	2.9	290	**—**	**304R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40600	48100	14100
5.2	1260	1.8	276	**303L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40500	48000	13900
5.2	1250	1.9	273	**304L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40500	48000	13800
5.3	1190	1.6	268	**—**	**301R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6500	6500	21500	23500	4580
5.6	1180	1.6	258	**303L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40500	48000	13600
5.6	1130	1.6	255	**—**	**303R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40500	48000	13500
6.0	1090	1.2	240	**301L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6500	6500	21500	23500	4410
6.0	1050	1.2	237	**—**	**301R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6500	6500	21500	23500	4400
6.2	1020	1.8	231	**—**	**303R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40500	48000	13100
6.5	1010	0.9	221	**300L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6500	6500	21500	25000	4290
6.5	1010	1.8	221	**301L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6500	6500	21500	23500	4290
6.5	1010	2.2	220	**303L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40500	48000	12900
6.7	950	1.0	215	**—**	**300R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6500	6500	21500	25000	4250
6.7	950	1.9	215	**—**	**301R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6500	6500	21500	23500	4250
6.7	950	2.9	214	**—**	**303R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40500	48000	12700
7.1	920	2.6	202	**304L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40500	48000	12500
7.4	880	1.5	192	**301L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6500	6500	21500	23500	4100
7.5	870	2.1	190	**303L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40500	48000	12300
7.7	820	2.8	185	**—**	**303R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40500	48000	12100
8.1	810	1.1	177	**300L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6500	6500	21500	25000	3990
8.1	780	1.1	175	**—**	**300R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6500	6500	21500	25000	3980
8.1	810	2.2	177	**301L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6500	6500	21500	23500	3990
8.1	780	2.3	175	**—**	**301R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6500	6500	21500	23500	3980
8.1	810	2.7	178	**303L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40500	48000	12000
8.7	750	3.0	164	**303L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40500	48000	11700
9.0	700	1.2	159	**—**	**300R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6500	6500	21500	25000	3850
9.0	700	2.5	159	**—**	**301R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6500	6500	21500	23500	3850
9.4	700	2.6	152	**303L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40500	48000	11400



P_1 = 0.75 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
10.0	630	1.0	143	—	**300R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6500	6500	21500	25000	3720
10.0	630	2.1	143	—	**301R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6500	6500	21500	23500	3720
10.1	650	1.3	142	**300L3**	—	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6480	6480	21500	24900	3700
10.1	650	2.7	142	**301L3**	—	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6480	6480	21500	23400	3700
10.8	610	0.9	133	—	**300R3**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6340	6340	21000	24500	3620
10.8	610	1.9	133	—	**301R3**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6340	6340	21000	23000	3620
10.9	600	1.4	131	**300L3**	—	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6310	6310	20900	24300	3610
10.9	600	2.9	131	**301L3**	—	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6310	6310	20900	22900	3610
11.0	570	1.5	130	—	**300R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6290	6290	20900	24300	3590
11.0	570	3.0	130	—	**301R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6290	6290	20900	22800	3590
12.3	530	1.2	116	**300L3**	—	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6060	6060	20200	23500	3460
12.3	530	2.5	116	**301L3**	—	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6060	6060	20200	22100	3460
13.4	490	1.3	106	—	**300R3**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	5890	5890	19700	22900	3370
13.4	490	2.7	106	—	**301R3**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	5890	5890	19700	21500	3370
13.5	470	1.8	106	—	**300R4**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	5880	5880	19600	22800	3360
13.6	480	1.8	105	**300L3**	—	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	5860	5860	19600	22800	3350
16.7	390	2.2	85.6	**300L3**	—	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	5480	5480	18400	21400	3130
16.8	390	1.7	85.2	—	**300R3**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	5470	5470	18400	21400	3120
18.2	360	2.4	78.7	—	**300R3**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	5330	5330	18000	20900	3040
18.5	350	2.4	77.5	**300L3**	—	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	5300	5300	17900	20800	3030
20.5	320	2.0	69.9	**300L3**	—	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	5120	5120	17300	20200	2920
21.0	310	2.1	68.2	—	**300R3**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	5080	5080	17200	20000	2900
22.1	300	1.8	64.8	**300L2**	—	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	4990	4990	17000	19700	2850
22.6	290	2.9	63.2	**300L3**	—	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	4950	4950	16800	19600	2830
22.7	290	3.0	62.9	—	**300R3**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	4940	4940	16800	19500	2820
27.5	240	2.7	51.9	**300L2**	—	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	4640	4640	15900	18400	2650

P_1 = 1.1 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
0.57	16500	1.4	2523	**310ML4**	—	**BE90S4**	**BX90S4**	—	—	—	—	106500	135000	65000
0.59	15900	1.1	2423	**309L4**	—	**BE90S4**	**BX90S4**	—	—	—	—	93600	120500	36000
0.65	14300	2.8	2187	**313ML4**	—	**BE90S4**	**BX90S4**	—	—	—	—	189900	222500	80000
0.68	13700	2.7	2096	**311ML4**	—	**BE90S4**	**BX90S4**	—	—	—	—	130300	132900	65000
0.70	13400	1.1	2041	**307L4**	—	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	39700	49700	89400	117600	45000
0.71	13100	1.3	2003	**309L4**	—	**BE90S4**	**BX90S4**	—	—	—	—	91100	117300	36000
0.71	13200	1.8	2022	**310ML4**	—	**BE90S4**	**BX90S4**	—	—	—	—	103100	130800	65000
0.80	11800	2.0	1794	**310ML4**	—	**BE90S4**	**BX90S4**	—	—	—	—	101400	128600	65000
0.81	11600	1.4	1767	**307L4**	—	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	38900	48600	87600	115200	45000
0.83	11300	1.5	1723	**309L4**	—	**BE90S4**	**BX90S4**	—	—	—	—	89200	114800	36000
0.86	11000	2.2	1672	**310ML4**	—	**BE90S4**	**BX90S4**	—	—	—	—	100400	127300	65000
0.89	10500	1.6	1605	**309L4**	—	**BE90S4**	**BX90S4**	—	—	—	—	88300	113600	36000
0.90	10400	1.4	1591	**307L4**	—	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	38300	47900	86200	113500	45000
0.97	9660	1.0	1475	**306L4**	—	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	31600	36000	72000	83200	35000
0.99	9420	2.5	1438	**310ML4**	—	**BE90S4**	**BX90S4**	—	—	—	—	98200	124600	65000
1.0	9230	1.7	1408	**307L4**	—	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	37700	47100	84800	111500	44800
1.0	9040	1.9	1380	**309L4**	—	**BE90S4**	**BX90S4**	—	—	—	—	86400	111200	35600
1.1	8380	1.0	1279	**306L4**	—	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	31000	35300	70600	81500	33700
1.1	8350	1.5	1274	**307L4**	—	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	37100	46400	83600	109900	43300
1.1	8420	2.0	1286	**309L4**	—	**BE90S4**	**BX90S4**	—	—	—	—	85500	110100	34700
1.2	7580	1.9	1157	**307L4**	—	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	36600	45800	82400	108400	41900
1.2	7530	2.2	1149	**309L4**	—	**BE90S4**	**BX90S4**	—	—	—	—	84200	108300	33500
1.3	7170	1.1	1095	**306L4**	—	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	30300	34500	69000	79700	32000
1.4	6650	1.4	1015	**306L4**	—	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	30000	34200	68300	78900	31200
1.4	6550	2.1	999	**307L4**	—	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	35900	44800	80700	106200	39900
1.4	6550	2.8	999	**309L4**	—	**BE90S4**	**BX90S4**	—	—	—	—	82500	106200	31900
1.6	5750	1.3	877	**306L4**	—	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	29300	33400	66900	77200	29700
1.6	5940	2.6	906	**307L4**	—	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	35400	44200	79600	104700	38700
1.7	5440	1.2	830	—	**306R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	29100	33200	66400	76600	29200
1.8	5350	1.0	816	**305L4**	—	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	24400	27900	47000	55800	19900
1.8	5300	1.5	809	**306L4**	—	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	29000	33100	66100	76300	28900



P_1 = 1.1 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
1.8	5240	2.6	801	**307L4**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	34800	43400	78200	102900	37100
2.0	4580	2.1	700	**306L4**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	28400	32400	64800	74800	27600
2.1	4360	1.4	665	**—**	**306R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	28200	32200	64300	74200	27100
2.1	4520	2.2	690	**—**	**307R4**	**BE90S4**	**BX90S4**	**—**	**—**	34000	42500	76500	100700	35300
2.2	4250	1.1	649	**305L4**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	23600	27000	45500	54000	18400
2.2	4320	0.9	659	**—**	**305R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	23700	27000	45600	54100	18500
2.3	4160	2.3	636	**306L4**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	28000	31900	63900	73800	26700
2.4	3860	2.4	589	**306L4**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	27700	31600	63200	73000	26000
2.4	3870	2.2	590	**—**	**306R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	27700	31600	63200	73000	26100
2.5	3710	1.3	567	**—**	**305R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	23200	26500	44700	52900	17600
2.6	3640	1.0	556	**304L4**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	23100	26400	44500	52800	17500
2.6	3640	1.5	556	**305L4**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	23100	26400	44500	52800	17500
2.6	3600	2.0	550	**—**	**306R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	27400	31300	62600	72200	25500
2.7	3460	1.1	528	**—**	**305R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22900	26200	44200	52400	17200
2.8	3340	2.8	509	**306L4**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	27100	30900	61900	71500	24800
2.9	3220	1.2	492	**304L4**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22700	25900	43800	51900	16800
2.9	3220	1.7	492	**305L4**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22700	25900	43800	51900	16800
2.9	3200	2.8	488	**—**	**306R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	27000	30800	61500	71000	24500
2.9	3210	2.9	490	**—**	**307R4**	**BE90S4**	**BX90S4**	**—**	**—**	32400	40500	72900	95900	31500
3.1	2980	2.4	455	**—**	**306R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	26700	30500	60900	70300	23900
3.2	2920	1.0	446	**303L4**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22400	25600	43100	51100	16300
3.2	2920	1.3	446	**304L4**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22400	25600	43100	51100	16300
3.2	2960	1.2	452	**—**	**304R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22400	25600	43200	51200	16300
3.2	2920	1.9	446	**305L4**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22400	25600	43100	51100	16300
3.2	2960	1.6	452	**—**	**305R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22400	25600	43200	51200	16300
3.5	2710	1.1	413	**304L4**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22100	25300	42700	50600	15900
3.5	2710	0.9	414	**—**	**304R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22100	25300	42700	50600	15900
3.5	2710	1.8	413	**305L4**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22100	25300	42700	50600	15900
3.5	2740	2.1	405	**306L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	26300	30000	59900	69200	23000
3.6	2710	1.4	402	**305L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22000	25200	42500	50400	15700
3.7	2630	1.2	389	**305L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21900	25100	42300	50200	15500
3.7	2560	1.5	390	**—**	**305R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22000	25100	42300	50200	15600
3.7	2560	2.7	391	**306L4**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	26100	29800	59600	68800	22700
3.7	2550	3.0	389	**—**	**306R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	26100	29800	59600	68800	22700
3.9	2380	1.0	364	**—**	**303R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21700	24800	41900	49700	15200
3.9	2380	1.2	364	**—**	**304R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21700	24800	41900	49700	15200
3.9	2380	2.0	364	**—**	**305R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21700	24800	41900	49700	15200
4.2	2300	1.1	341	**304L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21500	24600	41500	49200	14900
4.2	2210	1.1	338	**—**	**304R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21500	24600	41500	49100	14800
4.3	2200	1.0	336	**—**	**303R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21500	24600	41400	49100	14800
4.3	2200	2.1	336	**—**	**305R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21500	24600	41400	49100	14800
4.4	2170	1.7	321	**305L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21400	24400	41200	48800	14600
4.4	2190	2.5	325	**306L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	25500	29000	58000	67000	21300
4.6	2050	0.9	313	**—**	**303R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21300	24300	41000	48600	14500
4.6	2050	1.8	313	**—**	**305R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21300	24300	41000	48600	14500
4.7	2010	1.7	307	**—**	**304R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21200	24200	40900	48500	14400
4.9	1910	1.0	291	**—**	**301R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	6520	6520	21600	23600	4700
4.9	1900	1.4	290	**—**	**303R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40600	48100	14100
4.9	1900	1.9	290	**—**	**304R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40600	48100	14100
4.9	1900	2.8	290	**—**	**305R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40600	48100	14100
5.0	1950	2.8	288	**306L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	25000	28500	57100	65900	20500
5.2	1870	1.2	276	**303L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	13900
5.2	1840	1.3	273	**304L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	13800
5.2	1870	2.4	276	**305L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	13900
5.3	1760	1.1	268	**—**	**301R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	6500	6500	21500	23500	4580
5.3	1750	2.1	267	**—**	**304R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	13700
5.6	1740	1.1	258	**303L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	13600
5.6	1670	1.1	255	**—**	**303R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	13500
5.6	1740	2.1	258	**305L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	13600
5.6	1670	2.2	255	**—**	**305R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	13500
6.2	1510	1.2	231	**—**	**303R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	13100
6.2	1510	2.4	231	**—**	**305R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	13100
6.3	1480	2.3	227	**—**	**304R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	13000
6.5	1490	1.2	221	**301L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	6500	6500	21500	23500	4290
6.5	1490	1.5	220	**303L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	12900



P_1 = 1.1 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N]				
min^{-1}	Nm									MC	MZ	HC/PC	HZ/PZ	FZ
6.5	1490	2.4	220	**304L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	12900
6.7	1410	1.3	215	**—**	**301R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	6500	6500	21500	23500	4250
6.7	1400	2.0	214	**—**	**303R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	12700
6.7	1400	2.6	214	**—**	**304R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	12700
7.1	1360	1.8	202	**304L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	12500
7.4	1300	1.0	192	**301L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	6500	6500	21500	23500	4100
7.5	1290	1.4	190	**303L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	12300
7.5	1290	2.8	190	**305L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	12300
7.7	1210	1.9	185	**—**	**303R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	12100
7.7	1210	2.9	185	**—**	**304R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	12100
8.1	1200	1.5	177	**301L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	6500	6500	21500	23500	3990
8.1	1150	1.5	175	**—**	**301R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	6500	6500	21500	23500	3980
8.1	1200	1.8	178	**303L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	12000
8.1	1200	2.4	178	**304L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	12000
8.7	1110	2.0	164	**303L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	11700
8.7	1110	2.1	165	**304L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	11700
9.0	1040	1.7	159	**—**	**301R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	6500	6500	21500	23500	3850
9.0	1040	2.6	158	**—**	**303R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	11500
9.4	1030	1.8	152	**303L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	11400
9.7	970	2.4	148	**—**	**303R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	11300
10.0	940	1.4	143	**—**	**301R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	6500	6500	21500	23500	3720
10.1	960	1.8	142	**301L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	6480	6480	21500	23400	3700
10.1	960	2.7	141	**303L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	20900	23900	40400	47800	11100
10.8	900	1.3	133	**—**	**301R3**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	6340	6340	21000	23000	3620
10.9	880	1.0	131	**300L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	6310	6310	20900	24300	3610
10.9	880	1.9	131	**301L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	6310	6310	20900	22900	3610
11.0	850	1.0	130	**—**	**300R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	6290	6290	20900	24300	3590
11.0	850	2.0	130	**—**	**301R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	6290	6290	20900	22800	3590
11.5	840	2.2	124	**303L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	20100	22900	38800	46000	10600
11.8	820	2.9	121	**—**	**304R3**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	19900	22700	38500	45700	10500
12.3	780	1.7	116	**301L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	6060	6060	20200	22100	3460
12.5	770	2.4	114	**—**	**303R3**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	19500	22300	37900	44900	10300
12.7	760	2.4	113	**303L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	19400	22200	37700	44700	10300
13.4	720	0.9	106	**—**	**300R3**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5890	5890	19700	22900	3370
13.4	720	1.8	106	**—**	**301R3**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5890	5890	19700	21500	3370
13.5	690	1.2	106	**—**	**300R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5880	5880	19600	22800	3360
13.5	690	2.5	106	**—**	**301R4**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5880	5880	19600	21500	3360
13.6	710	1.2	105	**300L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5860	5860	19600	22800	3350
13.6	710	2.4	105	**301L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5860	5860	19600	21400	3350
15.6	620	2.9	91.5	**—**	**303R3**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	18100	20700	35400	42000	9600
16.7	580	1.5	85.6	**300L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5480	5480	18400	21400	3130
16.7	580	2.9	85.6	**301L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5480	5480	18400	20100	3130
16.8	580	1.1	85.2	**—**	**300R3**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5470	5470	18400	21400	3120
16.8	580	2.3	85.2	**—**	**301R3**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5470	5470	18400	20100	3120
18.2	530	1.6	78.7	**—**	**300R3**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5330	5330	18000	20900	3040
18.2	530	3.0	78.7	**—**	**301R3**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5330	5330	18000	19600	3040
18.5	520	1.6	77.5	**300L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5300	5300	17900	20800	3030
20.5	470	1.4	69.9	**300L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5120	5120	17300	20200	2920
20.5	470	2.8	69.9	**301L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5120	5120	17300	19000	2920
21.0	460	1.4	68.2	**—**	**300R3**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5080	5080	17200	20000	2900
21.0	460	2.8	68.2	**—**	**301R3**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5080	5080	17200	18800	2900
22.1	450	1.2	64.8	**300L2**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	4990	4990	17000	19700	2850
22.1	450	2.5	64.8	**301L2**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	4990	4990	17000	18500	2850
22.6	430	2.0	63.2	**300L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	4950	4950	16800	19600	2830
22.7	420	2.0	62.9	**—**	**300R3**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	4940	4940	16800	19500	2820
27.5	360	1.8	51.9	**300L2**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	4640	4640	15900	18400	2650
27.7	350	2.4	51.6	**300L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	4630	4630	15800	18400	2640
28.4	340	2.5	50.4	**—**	**300R3**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	4590	4590	15700	18300	2620
34	290	2.2	41.5	**300L2**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	4300	4300	14800	17300	2460
35	280	2.3	41.2	**—**	**300R3**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	4290	4290	14800	17200	2450
43	230	2.8	33.3	**300L2**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	4000	4000	13900	16100	2280
78	130	2.9	18.5	**—**	**300R2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	3280	3280	11600	13500	1880



P_1 = 1.5 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
0.57	22300	1.1	2523	**310ML4**	**—**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	106500	135000	65000
0.65	19400	2.1	2187	**313ML4**	**—**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	189900	222500	80000
0.68	18600	2.0	2096	**311ML4**	**—**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	130300	132900	65000
0.71	17700	1.0	2003	**309L4**	**—**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	91100	117300	36000
0.71	17900	1.3	2022	**310ML4**	**—**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	103100	130800	65000
0.80	15900	1.5	1794	**310ML4**	**—**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	101400	128600	65000
0.81	15600	1.0	1767	**307L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	38900	48600	87600	115200	45000
0.81	15600	2.6	1766	**311ML4**	**—**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	127100	129700	65000
0.83	15300	1.1	1723	**309L4**	**—**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	89200	114800	36000
0.85	14900	2.5	1680	**311ML4**	**—**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	126200	128800	65000
0.86	14800	1.6	1672	**310ML4**	**—**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	100400	127300	65000
0.89	14200	1.2	1605	**309L4**	**—**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	88300	113600	36000
0.90	14100	1.1	1591	**307L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	38300	47900	86200	113500	45000
0.99	12700	1.9	1438	**310ML4**	**—**	**BE90LA4**	**BX90LA4**	**—**	**—**	0	0	98200	124600	65000
1.0	12500	1.3	1408	**307L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	37700	47100	84800	111500	44800
1.0	12200	1.4	1380	**309L4**	**—**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	86400	111200	35600
1.1	11300	1.1	1274	**307L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	37100	46400	83600	109900	43300
1.1	11400	1.5	1286	**309L4**	**—**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	85500	110100	34700
1.1	11100	2.2	1259	**310ML4**	**—**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	96400	122200	62300
1.2	10200	1.4	1157	**307L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	36600	45800	82400	108400	41900
1.2	10200	1.6	1149	**309L4**	**—**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	84200	108300	33500
1.2	10300	2.8	1164	**310ML4**	**—**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	95300	120900	60700
1.4	8990	1.1	1015	**306L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	30000	34200	68300	78900	31200
1.4	8850	1.6	999	**307L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	35900	44800	80700	106200	39900
1.4	8850	2.1	999	**309L4**	**—**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	82500	106200	31900
1.6	7760	1.0	877	**306L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	29300	33400	66900	77200	29700
1.6	8020	1.9	906	**307L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	35400	44200	79600	104700	38700
1.6	8020	2.2	906	**309L4**	**—**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	81400	104700	30900
1.6	7950	2.8	898	**—**	**310MR4**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	91900	116500	55700
1.8	7160	1.1	809	**306L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	29000	33100	66100	76300	28900
1.8	7090	1.9	801	**307L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	34800	43400	78200	102900	37100
1.8	7090	2.6	801	**309L4**	**—**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	79900	102900	29700
2.0	6190	1.5	700	**306L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	28400	32400	64800	74800	27600
2.0	6390	2.4	722	**307L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	34200	42800	77100	101400	35800
2.1	5890	1.0	665	**—**	**306R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	28200	32200	64300	74200	27100
2.1	6110	1.6	690	**—**	**307R4**	**BE90LA4**	**BX90LA4**	**—**	**—**	34000	42500	76500	100700	35300
2.1	6110	2.4	690	**—**	**309R4**	**BE90LA4**	**BX90LA4**	**—**	**—**	—	—	78200	100700	28200
2.2	5790	2.2	654	**307L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	33800	42200	76000	99900	34700
2.3	5630	1.7	636	**306L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	28000	31900	63900	73800	26700
2.4	5220	1.8	589	**306L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	27700	31600	63200	73000	26000
2.4	5230	1.6	590	**—**	**306R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	27700	31600	63200	73000	26100
2.5	5020	1.0	567	**—**	**305R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	23200	26500	44700	52900	17600
2.5	5120	2.9	579	**307L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	33200	41500	74600	98200	33300
2.5	5150	2.5	581	**—**	**307R4**	**BE90LA4**	**BX90LA4**	**—**	**—**	33200	41500	74700	98300	33300
2.6	4920	1.1	556	**305L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	23100	26400	44500	52800	17500
2.6	4870	1.5	550	**—**	**306R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	27400	31300	62600	72200	25500
2.8	4510	2.1	509	**306L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	27100	30900	61900	71500	24800
2.9	4360	1.2	492	**305L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	22700	25900	43800	51900	16800
2.9	4320	2.1	488	**—**	**306R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	27000	30800	61500	71000	24500
2.9	4340	2.2	490	**—**	**307R4**	**BE90LA4**	**BX90LA4**	**—**	**—**	32400	40500	72900	95900	31500
3.1	4020	1.8	455	**—**	**306R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	26700	30500	60900	70300	23900
3.1	4120	3.0	465	**307L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	32200	40200	72400	95200	30900
3.2	3950	0.9	446	**304L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	22400	25600	43100	51100	16300
3.2	4000	0.9	452	**—**	**304R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	22400	25600	43200	51200	16300
3.2	3950	1.4	446	**305L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	22400	25600	43100	51100	16300
3.2	4000	1.2	452	**—**	**305R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	22400	25600	43200	51200	16300
3.2	3930	2.5	444	**306L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	26600	30400	60700	70100	23700
3.4	3720	2.4	420	**—**	**306R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	26400	30100	60200	69500	23300
3.5	3660	1.3	413	**305L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	22100	25300	42700	50600	15900
3.5	3700	1.5	405	**306L3**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	26300	30000	59900	69200	23000
3.6	3670	1.0	402	**305L3**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	22000	25200	42500	50400	15700
3.7	3450	1.1	390	**—**	**305R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	22000	25100	42300	50200	15600
3.7	3460	2.0	391	**306L4**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	26100	29800	59600	68800	22700
3.7	3440	2.2	389	**—**	**306R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	26100	29800	59600	68800	22700
3.9	3220	0.9	364	**—**	**304R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21700	24800	41900	49700	15200



P_1 = 1.5 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N]				
min^{-1}	Nm									MC	MZ	HC/PC	HZ/PZ	FZ
3.9	3220	1.4	364	—	**305R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21700	24800	41900	49700	15200
4.3	2970	1.5	336	—	**305R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21500	24600	41400	49100	14800
4.3	3070	2.9	336	**307L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	30700	38400	69100	90900	27800
4.4	2930	1.2	321	**305L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21400	24400	41200	48800	14600
4.4	2960	1.9	325	**306L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	25500	29000	58000	67000	21300
4.6	2770	1.3	313	—	**305R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21300	24300	41000	48600	14500
4.6	2760	2.8	312	—	**306R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	25300	28900	57700	66600	21100
4.7	2710	1.3	307	—	**304R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21200	24200	40900	48500	14400
4.9	2570	1.0	290	—	**303R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40600	48100	14100
4.9	2570	1.4	290	—	**304R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40600	48100	14100
4.9	2570	2.1	290	—	**305R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40600	48100	14100
5.0	2630	2.1	288	**306L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	25000	28500	57100	65900	20500
5.2	2490	1.0	273	**304L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	13800
5.2	2520	1.8	276	**305L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	13900
5.3	2370	1.6	267	—	**304R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	13700
5.3	2450	2.2	268	**306L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	25000	28500	57000	65800	20000
5.6	2350	1.5	258	**305L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	13600
5.6	2260	1.6	255	—	**305R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	13500
6.2	2050	1.8	231	—	**305R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	13100
6.3	2010	1.7	227	—	**304R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	13000
6.5	2010	1.1	220	**303L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	12900
6.5	2010	1.8	220	**304L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	12900
6.5	2010	2.4	220	**305L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	12900
6.7	1900	1.0	215	—	**301R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	6500	6500	21500	23500	4250
6.7	1900	1.4	214	—	**303R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	12700
6.7	1900	1.9	214	—	**304R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	12700
6.7	1900	2.8	214	—	**305R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	12700
7.1	1840	1.3	202	**304L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	12500
7.5	1740	1.1	190	**303L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	12300
7.5	1740	2.1	190	**305L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	12300
7.7	1640	1.4	185	—	**303R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	12100
7.7	1640	2.1	185	—	**304R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	12100
7.7	1640	2.7	185	—	**305R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	12100
8.1	1620	1.1	177	**301L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	6500	6500	21500	23500	3990
8.1	1550	1.1	175	—	**301R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	6500	6500	21500	23500	3980
8.1	1620	1.4	178	**303L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	12000
8.1	1620	1.8	178	**304L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	12000
8.1	1620	2.7	178	**305L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	12000
8.7	1490	1.5	164	**303L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	11700
8.7	1500	1.6	165	**304L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	11700
8.7	1490	3.0	164	**305L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	11700
9.0	1410	1.2	159	—	**301R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	6500	6500	21500	23500	3850
9.0	1400	1.9	158	—	**303R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	11500
9.0	1400	2.5	158	—	**304R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	11500
9.4	1390	1.3	152	**303L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	11400
9.4	1390	2.6	152	**305L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	11400
9.6	1360	2.5	150	**304L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	11300
9.7	1310	1.8	148	—	**303R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	11300
9.7	1310	2.6	148	—	**304R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	11300
10.0	1270	1.0	143	—	**301R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	6500	6500	21500	23500	3720
10.1	1300	1.3	142	**301L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	6480	6480	21500	23400	3700
10.1	1290	2.0	141	**303L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	20900	23900	40400	47800	11100
10.1	1290	2.7	141	**304L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	20900	23900	40400	47800	11100
10.8	1210	0.9	133	—	**301R3**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	6340	6340	21000	23000	3620
10.9	1190	1.4	131	**301L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	6310	6310	20900	22900	3610
11.0	1150	1.5	130	—	**301R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	6290	6290	20900	22800	3590
11.0	1190	3.0	130	**304L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	20400	23300	39400	46700	10800
11.1	1140	2.3	129	—	**303R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	20300	23200	39300	46600	10800
11.5	1140	1.6	124	**303L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	20100	22900	38800	46000	10600
11.8	1110	2.2	121	—	**304R3**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	19900	22700	38500	45700	10500
12.3	1060	1.2	116	**301L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	6060	6060	20200	22100	3460
12.5	1040	1.7	114	—	**303R3**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	19500	22300	37900	44900	10300
12.7	1030	1.8	113	**303L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	19400	22200	37700	44700	10300
13.4	970	1.3	106	—	**301R3**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	5890	5890	19700	21500	3370
13.5	940	0.9	106	—	**300R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	5880	5880	19600	22800	3360



A

P_1 = 1.5 kW

n_2	M_2	S	i							Rn_2 [N]				
min^{-1}	Nm					IE2	IE3	IE2	IE3	MC	MZ	HC/PC	HZ/PZ	FZ
13.5	940	1.8	106	—	**301R4**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	5880	5880	19600	21500	3360
13.6	960	1.8	105	**301L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	5860	5860	19600	21400	3350
13.7	950	2.7	105	**303L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	18900	21600	36900	43700	10000
14.7	890	2.7	97.0	—	**304R3**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	18500	21100	36000	42700	9790
15.6	840	2.2	91.5	—	**303R3**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	18100	20700	35400	42000	9600
15.9	820	2.7	90.2	**303L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	18000	20600	35300	41800	9550
16.7	780	1.1	85.6	**300L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	5480	5480	18400	21400	3130
16.7	780	2.2	85.6	**301L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	5480	5480	18400	20100	3130
16.8	780	1.7	85.2	—	**301R3**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	5470	5470	18400	20100	3120
18.2	720	1.2	78.7	—	**300R3**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	5330	5330	18000	20900	3040
18.2	720	2.2	78.7	—	**301R3**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	5330	5330	18000	19600	3040
18.5	710	1.2	77.5	**300L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	5300	5300	17900	20800	3030
18.5	710	2.4	77.5	**301L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	5300	5300	17900	19600	3030
19.5	670	2.7	73.3	—	**303R3**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	16800	19200	33100	39300	8920
20.5	640	1.0	69.9	**300L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	5120	5120	17300	20200	2920
20.5	640	2.0	69.9	**301L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	5120	5120	17300	19000	2920
21.0	620	1.0	68.2	—	**300R3**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	5080	5080	17200	20000	2900
21.0	620	2.1	68.2	—	**301R3**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	5080	5080	17200	18800	2900
22.1	610	0.9	64.8	**300L2**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4990	4990	17000	19700	2850
22.1	610	1.9	64.8	**301L2**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4990	4990	17000	18500	2850
22.6	580	1.5	63.2	**300L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4950	4950	16800	19600	2830
22.6	580	2.9	63.2	**301L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4950	4950	16800	18400	2830
22.7	570	1.5	62.9	—	**300R3**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4940	4940	16800	19500	2820
22.7	570	2.9	62.9	—	**301R3**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4940	4940	16800	18400	2820
27.5	490	1.3	51.9	**300L2**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4640	4640	15900	18400	2650
27.5	490	2.7	51.9	**301L2**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4640	4640	15900	17300	2650
27.7	470	1.8	51.6	**300L3**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4630	4630	15800	18400	2640
28.4	460	1.8	50.4	—	**300R3**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4590	4590	15700	18300	2620
34	390	1.7	41.5	**300L2**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4300	4300	14800	17300	2460
35	380	1.7	41.2	—	**300R3**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4290	4290	14800	17200	2450
37	360	2.3	38.4	**300L2**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4190	4190	14500	16800	2390
38	340	2.5	37.3	—	**300R3**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4150	4150	14400	16700	2370
43	310	2.1	33.3	**300L2**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4000	4000	13900	16100	2280
47	290	2.9	30.7	**300L2**	—	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	3890	3890	13600	15800	2220
78	170	2.1	18.5	—	**300R2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	3280	3280	11600	13500	1880

P_1 = 2.2 kW

n_2	M_2	S	i							Rn_2 [N]				
min^{-1}	Nm					IE2	IE3	IE2	IE3	MC	MZ	HC/PC	HZ/PZ	FZ
0.65	28500	1.4	2187	**313ML4**	—	**BE100LA4**	**BX100LA4**	—	—	—	—	189900	222500	80000
0.68	27300	1.3	2096	**311ML4**	—	**BE100LA4**	**BX100LA4**	—	—	—	—	130300	132900	65000
0.71	26300	0.9	2022	**310ML4**	—	**BE100LA4**	**BX100LA4**	—	—	—	—	103100	130800	65000
0.79	23600	2.4	1817	**313ML4**	—	**BE100LA4**	**BX100LA4**	—	—	—	—	184900	216700	80000
0.80	23400	1.0	1794	**310ML4**	—	**BE100LA4**	**BX100LA4**	—	—	—	—	101400	128600	65000
0.81	23000	1.8	1766	**311ML4**	—	**BE100LA4**	**BX100LA4**	—	—	—	—	127100	129700	65000
0.85	21900	1.7	1680	**311ML4**	—	**BE100LA4**	**BX100LA4**	—	—	—	—	126200	128800	65000
0.86	21800	1.1	1672	**310ML4**	—	**BE100LA4**	**BX100LA4**	—	—	—	—	100400	127300	65000
0.95	19500	2.9	1502	**313ML4**	—	**BE100LA4**	**BX100LA4**	—	—	—	—	180000	210900	80000
0.99	18700	1.3	1438	**310ML4**	—	**BE100LA4**	**BX100LA4**	—	—	—	—	98200	124600	65000
1.0	18000	0.9	1380	**309L4**	—	**BE100LA4**	**BX100LA4**	—	—	—	—	86400	111200	35600
1.0	18400	2.2	1415	**311ML4**	—	**BE100LA4**	**BX100LA4**	—	—	—	—	123200	125700	64800
1.0	18100	2.8	1394	**313ML4**	—	**BE100LA4**	**BX100LA4**	—	—	—	—	178100	208700	79300
1.1	16700	1.0	1286	**309L4**	—	**BE100LA4**	**BX100LA4**	—	—	—	—	85500	110100	34700
1.1	16400	1.5	1259	**310ML4**	—	**BE100LA4**	**BX100LA4**	—	—	—	—	96400	122200	62300
1.2	15100	1.0	1157	**307L4**	—	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	36600	45800	82400	108400	41900
1.2	15000	1.1	1149	**309L4**	—	**BE100LA4**	**BX100LA4**	—	—	—	—	84200	108300	33500
1.2	15200	1.9	1164	**310ML4**	—	**BE100LA4**	**BX100LA4**	—	—	—	—	95300	120900	60700
1.2	16000	2.9	1230	**311ML4**	—	**BE100LA4**	**BX100LA4**	—	—	—	—	120700	123200	61800
1.4	13000	1.1	999	**307L4**	—	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	35900	44800	80700	106200	39900
1.4	13000	1.4	999	**309L4**	—	**BE100LA4**	**BX100LA4**	—	—	—	—	82500	106200	31900
1.4	13000	2.2	1002	**310ML4**	—	**BE100LA4**	**BX100LA4**	—	—	—	—	93300	118300	57700



P_1 = 2.2 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
1.5	12700	2.5	974	**310ML4**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	92900	117800	57200
1.6	11800	1.3	906	**307L4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	35400	44200	79600	104700	38700
1.6	11800	1.5	906	**309L4**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	81400	104700	30900
1.6	11700	1.9	898	**—**	**310MR4**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	91900	116500	55700
1.8	10400	1.3	801	**307L4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	34800	43400	78200	102900	37100
1.8	10400	1.7	801	**309L4**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	79900	102900	29700
1.8	10400	2.6	798	**310ML4**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	90300	114500	53500
1.9	9850	2.5	757	**—**	**310MR4**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	89600	113600	52600
2.0	9100	1.0	700	**306L4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	28400	32400	64800	74800	27600
2.0	9400	1.6	722	**307L4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	34200	42800	77100	101400	35800
2.0	9400	2.3	722	**309L4**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	78800	101400	28700
2.0	9440	2.8	726	**310ML4**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	89100	113000	51800
2.1	8980	1.1	690	**—**	**307R4**	**BE100LA4**	**BX100LA4**	**—**	**—**	34000	42500	76500	100700	35300
2.1	8980	1.7	690	**—**	**309R4**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	78200	100700	28200
2.2	8500	1.5	654	**307L4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	33800	42200	76000	99900	34700
2.2	8500	2.1	654	**309L4**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	77600	99900	27700
2.2	8310	2.5	639	**—**	**310MR4**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	87500	110900	49700
2.3	8270	1.1	636	**306L4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	28000	31900	63900	73800	26700
2.4	7670	1.2	589	**306L4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	27700	31600	63200	73000	26000
2.4	7680	1.1	590	**—**	**306R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	27700	31600	63200	73000	26100
2.4	7670	2.5	590	**—**	**310MR4**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	86500	109700	48400
2.5	7530	2.0	579	**307L4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	33200	41500	74600	98200	33300
2.5	7560	1.7	581	**—**	**307R4**	**BE100LA4**	**BX100LA4**	**—**	**—**	33200	41500	74700	98300	33300
2.5	7530	2.8	579	**309L4**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	76300	98200	26600
2.5	7560	2.1	581	**—**	**309R4**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	76400	98300	26700
2.6	7160	1.0	550	**—**	**306R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	27400	31300	62600	72200	25500
2.8	6630	1.4	509	**306L4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	27100	30900	61900	71500	24800
2.8	6630	2.1	509	**307L4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	32600	40700	73300	96400	31900
2.8	6630	2.2	509	**309L4**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	74900	96400	25500
2.9	6350	1.4	488	**—**	**306R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	27000	30800	61500	71000	24500
2.9	6380	1.5	490	**—**	**307R4**	**BE100LA4**	**BX100LA4**	**—**	**—**	32400	40500	72900	95900	31500
2.9	6380	2.2	490	**—**	**309R4**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	74500	95900	25200
3.1	5920	1.2	455	**—**	**306R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	26700	30500	60900	70300	23900
3.1	6050	2.0	465	**307L4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	32200	40200	72400	95200	30900
3.1	5950	2.3	457	**—**	**309R4**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	73800	94900	24600
3.2	5800	0.9	446	**305L4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	22400	25600	43100	51100	16300
3.2	5780	1.7	444	**306L4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	26600	30400	60700	70100	23700
3.2	5890	2.3	453	**—**	**307R4**	**BE100LA4**	**BX100LA4**	**—**	**—**	32000	40000	72100	94800	30700
3.4	5460	1.6	420	**—**	**306R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	26400	30100	60200	69500	23300
3.5	5430	1.0	405	**306L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	26300	30000	59900	69200	23000
3.5	5280	2.3	406	**307L4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	31500	39400	71000	93300	29600
3.5	5380	2.2	413	**—**	**307R4**	**BE100LA4**	**BX100LA4**	**—**	**—**	31600	39500	71100	93600	29800
3.7	5090	1.4	391	**306L4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	26100	29800	59600	68800	22700
3.7	5060	1.5	389	**—**	**306R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	26100	29800	59600	68800	22700
3.8	4870	2.9	374	**—**	**309R4**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	71700	92300	23000
3.9	4740	1.0	364	**—**	**305R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21700	24800	41900	49700	15200
3.9	4720	2.6	363	**—**	**307R4**	**BE100LA4**	**BX100LA4**	**—**	**—**	31000	38800	69800	91900	28500
4.3	4370	1.1	336	**—**	**305R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21500	24600	41400	49100	14800
4.3	4510	2.0	336	**307L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	30700	38400	69100	90900	27800
4.3	4310	2.7	331	**—**	**307R4**	**BE100LA4**	**BX100LA4**	**—**	**—**	30600	38300	68900	90700	27600
4.3	4510	2.9	336	**309L3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	70600	90900	22200
4.4	4350	1.3	325	**306L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	25500	29000	58000	67000	21300
4.6	4060	1.9	312	**—**	**306R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	25300	28900	57700	66600	21100
4.9	3770	1.0	290	**—**	**304R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40600	48100	14100
4.9	3770	1.4	290	**—**	**305R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40600	48100	14100
4.9	3760	2.2	289	**—**	**306R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	25000	28500	57100	65900	20500
5.0	3860	1.4	288	**306L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	25000	28500	57100	65900	20500
5.0	3800	3.0	284	**307L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	30000	37500	67500	88800	26200
5.2	3710	1.2	276	**305L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	13900
5.3	3480	1.1	267	**—**	**304R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	13700
5.3	3600	1.5	268	**306L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	25000	28500	57000	65800	20000
5.6	3460	1.0	258	**305L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	13600
5.6	3320	1.1	255	**—**	**305R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	13500
5.8	3240	2.5	249	**—**	**306R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	25000	28500	57000	65800	19500
6.0	3190	2.6	238	**306L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	25000	28500	57000	65800	19300



P_1 = 2.2 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N]				
min^{-1}	Nm									MC	MZ	HC/PC	HZ/PZ	FZ
6.0	3210	2.7	239	**307L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	30000	37500	67500	88800	24800
6.2	3010	1.2	231	**—**	**305R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	13100
6.2	3000	2.5	230	**—**	**306R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	25000	28500	57000	65800	19000
6.3	2950	1.2	227	**—**	**304R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	13000
6.4	2980	2.2	222	**306L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	25000	28500	57000	65800	18800
6.5	2960	1.2	220	**304L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	12900
6.5	2960	1.6	220	**305L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	12900
6.7	2790	1.0	214	**—**	**303R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	12700
6.7	2790	1.3	214	**—**	**304R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	12700
6.7	2790	1.9	214	**—**	**305R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	12700
7.0	2750	3.0	205	**306L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	25000	28500	57000	65800	18300
7.5	2550	1.4	190	**305L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	12300
7.5	2550	2.6	190	**306L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	25000	28500	57000	65800	17900
7.7	2410	1.0	185	**—**	**303R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	12100
7.7	2410	1.4	185	**—**	**304R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	12100
7.7	2410	1.9	185	**—**	**305R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	12100
8.1	2380	0.9	178	**303L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	12000
8.1	2380	1.2	178	**304L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	12000
8.1	2380	1.9	178	**305L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	12000
8.7	2200	1.0	164	**303L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	11700
8.7	2210	1.1	165	**304L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	11700
8.7	2200	2.0	164	**305L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	11700
9.0	2060	1.3	158	**—**	**303R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	11500
9.0	2060	1.7	158	**—**	**304R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	11500
9.0	2060	2.6	158	**—**	**305R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	11500
9.4	2050	1.8	152	**305L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	11400
9.6	2010	1.7	150	**304L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	11300
9.7	1930	1.2	148	**—**	**303R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	11300
9.7	1930	1.8	148	**—**	**304R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	11300
9.7	1930	2.3	148	**—**	**305R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	21000	24000	40500	48000	11300
9.9	1930	2.8	144	**—**	**306R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	25000	28500	57000	65800	16300
10.1	1900	0.9	142	**301L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	6480	6480	21500	23400	3700
10.1	1900	1.4	141	**303L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	20900	23900	40400	47800	11100
10.1	1900	1.9	141	**304L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	20900	23900	40400	47800	11100
10.1	1900	2.8	141	**305L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	20900	23900	40400	47800	11100
10.9	1760	1.0	131	**301L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	6310	6310	20900	22900	3610
11.0	1690	1.0	130	**—**	**301R4**	**BE100LA4**	**BX100LA4**	**—**	**—**	6290	6290	20900	22800	3590
11.0	1750	2.0	130	**304L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	20400	23300	39400	46700	10800
11.1	1680	1.6	129	**—**	**303R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	20300	23200	39300	46600	10800
11.1	1680	2.1	129	**—**	**304R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	20300	23200	39300	46600	10800
11.5	1670	1.1	124	**303L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	20100	22900	38800	46000	10600
11.5	1670	2.2	124	**305L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	20100	22900	38800	46000	10600
11.8	1630	1.5	121	**—**	**304R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	19900	22700	38500	45700	10500
12.5	1530	1.2	114	**—**	**303R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	19500	22300	37900	44900	10300
12.5	1530	2.3	114	**—**	**305R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	19500	22300	37900	44900	10300
12.7	1510	1.2	113	**303L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	19400	22200	37700	44700	10300
12.7	1510	2.4	113	**305L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	19400	22200	37700	44700	10300
12.9	1480	2.3	111	**304L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	19300	22000	37500	44400	10200
13.1	1420	2.4	109	**—**	**304R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	19200	22000	37400	44300	10200
13.4	1430	0.9	106	**—**	**301R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	5890	5890	19700	21500	3370
13.5	1380	1.2	106	**—**	**301R4**	**BE100LA4**	**BX100LA4**	**—**	**—**	5880	5880	19600	21500	3360
13.6	1410	1.2	105	**301L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	5860	5860	19600	21400	3350
13.7	1400	1.8	105	**303L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	18900	21600	36900	43700	10000
13.7	1400	2.5	105	**304L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	18900	21600	36900	43700	10000
14.7	1300	1.8	97.0	**—**	**304R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	18500	21100	36000	42700	9790
15.6	1230	1.5	91.5	**—**	**303R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	18100	20700	35400	42000	9600
15.6	1230	2.9	91.5	**—**	**305R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	18100	20700	35400	42000	9600
15.9	1210	1.9	90.2	**303L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	18000	20600	35300	41800	9550
15.9	1210	2.8	90.2	**304L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	18000	20600	35300	41800	9550
16.0	1160	2.9	89.4	**—**	**304R4**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	18000	20500	35200	41700	9520
16.7	1150	1.5	85.6	**301L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	5480	5480	18400	20100	3130
16.8	1140	1.1	85.2	**—**	**301R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	5470	5470	18400	20100	3120
18.2	1060	1.5	78.7	**—**	**301R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	5330	5330	18000	19600	3040
18.2	1060	2.1	78.7	**—**	**303R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	17200	19700	33900	40100	9130
18.2	1060	2.7	78.7	**—**	**304R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	17200	19700	33900	40100	9130



P_1 = 2.2 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
18.5	1040	1.6	77.5	**301L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	5300	5300	17900	19600	3030
18.5	1040	2.4	77.2	**303L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	17100	19500	33700	39900	9070
19.5	980	1.9	73.3	**—**	**303R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	16800	19200	33100	39300	8920
19.8	970	2.3	72.3	**303L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	16700	19100	33000	39100	8870
20.5	940	1.4	69.9	**301L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	5120	5120	17300	19000	2920
21.0	920	1.4	68.2	**—**	**301R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	5080	5080	17200	18800	2900
22.1	900	1.3	64.8	**301L2**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	4990	4990	17000	18500	2850
22.6	850	1.0	63.2	**300L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	4950	4950	16800	19600	2830
22.6	850	1.9	63.2	**301L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	4950	4950	16800	18400	2830
22.7	840	1.0	62.9	**—**	**300R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	4940	4940	16800	19500	2820
22.7	840	2.0	62.9	**—**	**301R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	4940	4940	16800	18400	2820
22.7	850	3.0	63.1	**303L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	16000	18300	31700	37500	8480
22.7	850	2.6	63.1	**—**	**303R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	16000	18300	31700	37500	8480
24.2	820	2.9	59.1	**304L2**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	15600	17900	31100	36800	8300
25.6	770	2.4	55.8	**303L2**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	15300	17500	30500	36200	8140
26.4	730	2.5	54.2	**—**	**303R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	15200	17400	30300	35900	8060
27.5	720	0.9	51.9	**300L2**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	4640	4640	15900	18400	2650
27.5	720	1.8	51.9	**301L2**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	4640	4640	15900	17300	2650
27.7	690	1.2	51.6	**300L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	4630	4630	15800	18400	2640
27.7	690	2.4	51.6	**301L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	4630	4630	15800	17300	2640
28.4	680	1.3	50.4	**—**	**300R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	4590	4590	15700	18300	2620
28.4	680	2.4	50.4	**—**	**301R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	4590	4590	15700	17200	2620
32	620	2.9	44.6	**303L2**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	14200	16300	28600	33800	7560
34	570	1.1	41.5	**300L2**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	4300	4300	14800	17300	2460
34	570	2.3	41.5	**301L2**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	4300	4300	14800	16200	2460
35	550	1.2	41.2	**—**	**300R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	4290	4290	14800	17200	2450
35	550	2.4	41.2	**—**	**301R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	4290	4290	14800	16200	2450
37	530	1.6	38.4	**300L2**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	4190	4190	14500	16800	2390
37	530	2.9	38.4	**301L2**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	4190	4190	14500	15800	2390
38	500	1.7	37.3	**—**	**300R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	4150	4150	14400	16700	2370
43	460	1.4	33.3	**300L2**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	4000	4000	13900	16100	2280
43	460	2.8	33.3	**301L2**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	4000	4000	13900	15200	2280
47	420	2.0	30.7	**300L2**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	3890	3890	13600	15800	2220
47	410	2.1	30.4	**—**	**300R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	3880	3880	13500	15700	2220
58	340	2.4	24.6	**300L2**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	3610	3610	12700	14700	2070
58	330	2.2	24.8	**—**	**300R3**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	3630	3630	12700	14800	2070
58	340	2.5	24.8	**—**	**303R2**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	11700	13400	23900	28400	6210
71	280	2.3	20.1	**300L2**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	3380	3380	11900	13900	1930
78	260	1.4	18.5	**—**	**300R2**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	3280	3280	11600	13500	1880
78	260	2.9	18.5	**—**	**301R2**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	3280	3280	11600	12700	1880
97	200	2.5	14.8	**—**	**300R2**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	3050	3050	10900	12600	1740
159	130	2.5	9.00	**300L1**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	2590	2590	9380	10900	1480

P_1 = 3 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
0.65	38700	1.0	2187	**313ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	190100	222700	80000
0.68	37100	1.0	2096	**311ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	130400	133100	65000
0.78	32200	1.8	1817	**313ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	185100	216900	80000
0.80	31300	1.3	1766	**311ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	127200	129800	65000
0.85	29700	1.2	1680	**311ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	126300	128900	65000
0.95	26600	2.1	1502	**313ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	180100	211100	80000
0.99	25500	0.9	1438	**310ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	98300	124700	65000
1.0	25100	1.6	1415	**311ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	123300	125800	64900
1.0	24700	2.1	1394	**313ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	178200	208900	79500
1.1	22300	1.1	1259	**310ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	96500	122300	62400
1.1	22400	2.5	1266	**313ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	175800	206000	77000
1.2	20600	1.4	1164	**310ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	95400	121000	60800
1.2	21800	2.1	1230	**311ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	120800	123300	62000
1.3	18700	2.4	1058	**311ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	118300	120700	58900



P_1 = 3 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
1.3	19800	2.5	1117	**313ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	172700	202400	73800
1.4	17700	1.0	999	**309L4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	82600	106300	32000
1.4	17700	1.6	1002	**310ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	93400	118400	57900
1.4	17500	2.6	986	**311ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	117100	119500	57600
1.5	17200	1.9	974	**310ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	93000	117900	57300
1.6	16000	1.0	906	**307L4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	35400	44300	79700	104800	38700
1.6	16000	1.1	906	**309L4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	81400	104800	31000
1.6	15900	1.4	898	**—**	**310MR4**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	91900	116600	55800
1.8	14200	0.9	801	**307L4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	34800	43500	78300	103000	37200
1.8	14200	1.3	801	**309L4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	80000	103000	29700
1.8	14100	1.9	798	**310ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	90400	114600	53600
1.8	13800	2.6	778	**—**	**313MR4**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	164000	192200	65500
1.9	13400	1.9	757	**—**	**310MR4**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	89700	113800	52700
1.9	13200	2.5	746	**—**	**311MR4**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	112500	114800	52500
2.0	12800	1.2	722	**307L4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	34300	42800	77100	101500	35900
2.0	12800	1.7	722	**309L4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	78800	101500	28700
2.0	12900	2.1	726	**310ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	89200	113100	52000
2.1	12200	1.2	690	**—**	**309R4**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	78300	100800	28300
2.2	11600	1.1	654	**307L4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	33800	42200	76000	100000	34700
2.2	11600	1.6	654	**309L4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	77700	100000	27800
2.2	11300	2.3	637	**310ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	87500	111000	49700
2.2	11300	1.8	639	**—**	**310MR4**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	87600	111000	49800
2.4	10300	1.2	581	**—**	**307R4**	**BE100LB4**	**BX100LB4**	**—**	**—**	33200	41500	74800	98400	33400
2.4	10300	1.5	581	**—**	**309R4**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	76400	98400	26700
2.4	10400	2.5	590	**310ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	86600	109800	48500
2.4	10400	1.9	590	**—**	**310MR4**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	86600	109800	48500
2.5	10200	1.5	579	**307L4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	33200	41500	74700	98300	33400
2.5	10200	2.1	579	**309L4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	76400	98300	26700
2.7	9160	2.8	517	**—**	**310MR4**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	85000	107700	46400
2.8	9020	1.0	509	**306L4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	27200	31000	62000	71500	24900
2.8	9020	1.6	509	**307L4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	32600	40800	73400	96500	32000
2.8	9020	1.6	509	**309L4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	75000	96500	25600
2.8	8980	2.8	507	**310ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	84700	107400	46100
2.9	8640	1.1	488	**—**	**306R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	27000	30800	61600	71100	24500
2.9	8680	1.1	490	**—**	**307R4**	**BE100LB4**	**BX100LB4**	**—**	**—**	32400	40500	73000	96000	31600
2.9	8680	1.6	490	**—**	**309R4**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	74600	96000	25300
3.1	8230	1.5	465	**307L4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	32200	40200	72400	95300	31000
3.1	8020	1.7	453	**—**	**307R4**	**BE100LB4**	**BX100LB4**	**—**	**—**	32100	40100	72200	94900	30700
3.1	8230	2.2	465	**309L4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	74000	95300	24800
3.1	8090	1.7	457	**—**	**309R4**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	73800	95000	24700
3.1	8040	2.4	454	**—**	**310MR4**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	83400	105800	44500
3.2	7870	1.3	444	**306L4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	26700	30400	60800	70100	23800
3.4	7430	1.2	420	**—**	**306R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	26400	30100	60300	69600	23300
3.4	7320	1.6	413	**—**	**307R4**	**BE100LB4**	**BX100LB4**	**—**	**—**	31700	39600	71200	93700	29800
3.4	7320	2.5	413	**—**	**309R4**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	72800	93700	23900
3.5	7180	1.7	406	**307L4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	31600	39500	71000	93400	29600
3.5	7180	2.5	406	**309L4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	72600	93400	23700
3.6	6920	1.0	391	**306L4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	26200	29800	59700	68900	22800
3.6	6930	2.7	392	**310ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	81700	103500	42300
3.7	6890	1.1	389	**—**	**306R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	26100	29800	59600	68800	22700
3.8	6630	2.2	374	**—**	**309R4**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	71800	92400	23100
3.9	6420	1.9	363	**—**	**307R4**	**BE100LB4**	**BX100LB4**	**—**	**—**	31100	38800	69900	92000	28600
4.1	6180	2.4	349	**307L4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	30900	38600	69500	91500	28200
4.2	6140	1.5	336	**307L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	30700	38400	69200	91000	27800
4.2	6140	2.2	336	**309L3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	70700	91000	22300
4.3	5860	2.0	331	**—**	**307R4**	**BE100LB4**	**BX100LB4**	**—**	**—**	30700	38300	69000	90800	27700
4.3	5860	3.0	331	**—**	**309R4**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	70500	90800	22200
4.4	5920	0.9	325	**306L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25500	29000	58100	67100	21400
4.6	5520	1.4	312	**—**	**306R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25300	28900	57800	66700	21100
4.7	5310	2.6	300	**—**	**307R4**	**BE100LB4**	**BX100LB4**	**—**	**—**	30200	37800	68000	89500	26800
4.9	5130	1.0	290	**—**	**305R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21100	24100	40600	48100	14100



P_1 = 3 kW

n_2	M_2	S	i							Rn_2 [N]				
min^{-1}	Nm					IE2	IE3	IE2	IE3	MC	MZ	HC/PC	HZ/PZ	FZ
4.9	5260	1.0	288	**306L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25100	28600	57100	65900	20600
4.9	5120	1.6	289	**—**	**306R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25100	28600	57100	66000	20600
5.0	5170	2.2	284	**307L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	30000	37500	67500	88800	26300
5.0	5040	2.2	284	**—**	**307R4**	**BE100LB4**	**BX100LB4**	**—**	**—**	30000	37500	67500	88800	26300
5.3	4900	1.1	268	**306L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25000	28500	57000	65800	20100
5.7	4400	1.9	249	**—**	**306R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25000	28500	57000	65800	19600
5.9	4370	2.0	239	**307L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	30000	37500	67500	88800	24900
5.9	4370	3.0	239	**309L3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	69000	88800	19900
6.0	4350	1.9	238	**306L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25000	28500	57000	65800	19300
6.1	4110	2.7	232	**—**	**307R4**	**BE100LB4**	**BX100LB4**	**—**	**—**	30000	37500	67500	88800	24600
6.2	4080	1.9	230	**—**	**306R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25000	28500	57000	65800	19100
6.4	4020	1.2	220	**305L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	12900
6.4	4050	1.6	222	**306L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25000	28500	57000	65800	18800
6.6	3790	1.0	214	**—**	**304R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	12800
6.6	3790	1.4	214	**—**	**305R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	12800
6.6	3780	2.6	214	**—**	**306R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25000	28500	57000	65800	18600
6.9	3740	2.2	205	**306L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25000	28500	57000	65800	18400
7.5	3470	1.0	190	**305L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	12300
7.5	3460	1.9	190	**306L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25000	28500	57000	65800	17900
7.7	3270	1.1	185	**—**	**304R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	12200
7.7	3270	1.4	185	**—**	**305R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	12200
7.8	3200	2.9	181	**—**	**306R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25000	28500	57000	65800	17600
8.0	3240	1.4	178	**305L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	12000
8.5	2970	2.5	168	**—**	**306R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25000	28500	57000	65800	17200
8.7	2990	1.5	164	**305L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	11700
9.0	2800	1.0	158	**—**	**303R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	11600
9.0	2800	1.3	158	**—**	**304R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	11600
9.0	2800	1.9	158	**—**	**305R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	11600
9.3	2780	1.3	152	**305L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	11400
9.3	2770	2.7	152	**306L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25000	28500	57000	65800	16600
9.5	2730	1.3	150	**304L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	11300
9.6	2620	1.3	148	**—**	**304R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	11300
9.6	2620	1.7	148	**—**	**305R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	11300
9.9	2630	2.1	144	**—**	**306R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25000	28500	57000	65800	16300
10.0	2580	1.0	141	**303L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	47900	11100
10.0	2580	1.4	141	**304L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	47900	11100
10.0	2580	2.0	141	**305L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	47900	11100
10.9	2380	1.5	130	**304L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	20400	23300	39500	46800	10800
11.0	2290	1.2	129	**—**	**303R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	20400	23300	39400	46700	10800
11.0	2290	1.5	129	**—**	**304R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	20400	23300	39400	46700	10800
11.0	2290	2.3	129	**—**	**305R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	20400	23300	39400	46700	10800
11.4	2270	1.6	124	**305L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	20100	23000	38900	46100	10700
11.7	2210	1.1	121	**—**	**304R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	19900	22800	38600	45800	10600
11.9	2180	3.0	119	**—**	**306R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	23600	26900	54100	62400	15300
12.4	2090	1.7	114	**—**	**305R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	19500	22300	38000	45000	10400
12.6	2060	1.7	113	**305L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	19400	22200	37800	44800	10300
12.9	2020	1.7	111	**304L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	19300	22100	37600	44500	10200
13.0	1940	1.7	109	**—**	**304R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	19300	22000	37500	44400	10200
13.4	1870	0.9	106	**—**	**301R4**	**BE100LB4**	**BX100LB4**	**—**	**—**	5890	5890	19700	21500	3370
13.6	1910	1.4	105	**303L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	19000	21700	36900	43800	10100
13.6	1910	1.8	105	**304L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	19000	21700	36900	43800	10100
13.6	1910	2.7	105	**305L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	19000	21700	36900	43800	10100
14.6	1770	1.3	97.0	**—**	**304R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	18500	21100	36100	42800	9810
15.5	1670	1.1	91.5	**—**	**303R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	18100	20700	35500	42100	9620
15.5	1670	2.1	91.5	**—**	**305R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	18100	20700	35500	42100	9620
15.7	1650	1.4	90.2	**303L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	18100	20600	35300	41900	9580
15.7	1650	2.0	90.2	**304L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	18100	20600	35300	41900	9580
15.7	1650	2.6	90.2	**305L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	18100	20600	35300	41900	9580
15.9	1580	2.1	89.4	**—**	**304R4**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	18000	20600	35200	41800	9550
16.6	1560	1.1	85.6	**301L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	5490	5490	18500	20200	3140
18.0	1440	1.5	78.7	**—**	**303R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	17300	19700	33900	40200	9150

A



P_1 = 3 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N]				
min^{-1}	Nm									MC	MZ	HC/PC	HZ/PZ	FZ
18.0	1440	2.0	78.7	—	**304R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	17300	19700	33900	40200	9150
18.1	1440	1.1	78.7	—	**301R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	5340	5340	18000	19700	3050
18.3	1410	1.2	77.5	**301L3**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	5310	5310	17900	19600	3030
18.4	1410	1.8	77.2	**303L3**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	17100	19600	33700	40000	9090
18.4	1410	2.5	77.2	**304L3**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	17100	19600	33700	40000	9090
19.4	1340	1.4	73.3	—	**303R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	16800	19300	33200	39400	8940
19.4	1340	2.7	73.3	—	**305R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	16800	19300	33200	39400	8940
19.6	1320	1.7	72.3	**303L3**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	16800	19200	33100	39200	8890
19.6	1320	2.5	72.3	**304L3**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	16800	19200	33100	39200	8890
20.3	1280	1.0	69.9	**301L3**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	5130	5130	17400	19000	2930
20.8	1250	1.0	68.2	—	**301R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	5090	5090	17300	18900	2910
21.9	1220	0.9	64.8	**301L2**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	5000	5000	17000	18600	2860
22.5	1150	1.4	63.2	**301L3**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	4960	4960	16900	18400	2840
22.5	1150	2.2	63.1	**303L3**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	16000	18300	31700	37600	8500
22.5	1150	1.9	63.1	—	**303R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	16000	18300	31700	37600	8500
22.5	1150	2.5	63.1	—	**304R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	16000	18300	31700	37600	8500
22.6	1150	1.4	62.9	—	**301R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	4960	4960	16800	18400	2830
24.0	1110	2.1	59.1	**304L2**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	15700	17900	31100	36900	8320
25.4	1050	1.7	55.8	**303L2**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	15400	17600	30600	36300	8160
26.2	990	1.8	54.2	—	**303R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	15200	17400	30300	36000	8080
26.6	970	2.2	53.4	**303L3**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	15200	17300	30200	35800	8040
27.3	980	1.3	51.9	**301L2**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	4650	4650	15900	17400	2660
27.5	940	1.7	51.6	**301L3**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	4640	4640	15900	17300	2650
28.2	920	0.9	50.4	—	**300R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	4600	4600	15800	18300	2630
28.2	920	1.8	50.4	—	**301R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	4600	4600	15800	17200	2630
28.3	920	2.6	50.3	—	**303R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	14900	17000	29700	35200	7880
30	850	2.5	46.6	—	**303R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	14500	16600	29000	34400	7680
30	890	2.7	47.3	**304L2**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	14600	16600	29100	34500	7720
32	840	2.2	44.6	**303L2**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	14300	16300	28600	33900	7570
33	780	2.7	42.6	—	**303R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	14100	16100	28200	33400	7460
34	780	1.7	41.5	**301L2**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	4310	4310	14900	16300	2460
35	750	1.7	41.2	—	**301R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	4300	4300	14800	16200	2460
37	720	1.2	38.4	**300L2**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	4200	4200	14500	16900	2400
37	720	2.1	38.4	**301L2**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	4200	4200	14500	15900	2400
37	720	3.0	38.4	**303L2**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	13600	15500	27400	32400	7200
38	680	1.2	37.3	—	**300R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	4160	4160	14400	16700	2380
38	680	2.4	37.3	—	**301R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	4160	4160	14400	15700	2380
40	670	2.7	35.8	**303L2**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	13300	15200	26800	31700	7040
43	630	1.0	33.3	**300L2**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	4010	4010	13900	16200	2290
43	630	2.1	33.3	**301L2**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	4010	4010	13900	15200	2290
46	580	1.5	30.7	**300L2**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	3900	3900	13600	15800	2230
46	580	2.7	30.7	**301L2**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	3900	3900	13600	14800	2230
47	560	1.5	30.4	—	**300R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	3890	3890	13500	15700	2220
47	560	2.9	30.4	—	**301R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	3890	3890	13500	14800	2220
57	450	1.6	24.8	—	**300R3**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	3630	3630	12700	14800	2080
57	470	1.8	24.8	—	**303R2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	11700	13400	24000	28400	6220
58	460	1.8	24.6	**300L2**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	3620	3620	12700	14800	2070
71	380	1.7	20.1	**300L2**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	3390	3390	12000	13900	1930
77	350	1.1	18.5	—	**300R2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	3290	3290	11700	13600	1880
77	350	2.1	18.5	—	**301R2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	3290	3290	11700	12700	1880
78	340	2.2	18.2	**300L2**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	3280	3280	11600	13500	1870
96	280	2.6	14.8	**300L2**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	3060	3060	10900	12700	1750
96	280	1.8	14.8	—	**300R2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	3060	3060	10900	12700	1750
120	220	2.7	11.8	—	**300R2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	2840	2840	10200	11900	1620
158	170	1.8	9.00	**300L1**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	2590	2590	9400	10900	1480
197	140	3.0	7.20	**300L1**	—	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	2410	2410	8790	10200	1370



P_1 = 4 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
0.79	43400	1.3	1817	**313ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	184700	216500	80000
0.82	42200	1.0	1766	**311ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	127000	129600	65000
0.86	40200	0.9	1680	**311ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	126100	128700	65000
0.96	35900	1.6	1502	**313ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	179800	210700	80000
1.0	33800	1.2	1415	**311ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	123000	125500	64600
1.0	33300	1.5	1394	**313ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	177900	208400	79100
1.1	30300	1.8	1266	**313ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	175400	205600	76600
1.2	27800	1.0	1164	**310ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	95200	120700	60600
1.2	29400	1.6	1230	**311ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	120600	123100	61700
1.3	26700	1.9	1117	**313ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	172300	201900	73500
1.4	23900	1.2	1002	**310ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	93200	118200	57600
1.4	25300	1.8	1058	**311ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	118000	120400	58700
1.4	24200	2.2	1014	**313ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	170000	199200	71200
1.5	23300	1.4	974	**310ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	92800	117700	57100
1.5	23600	1.9	986	**311ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	116800	119200	57300
1.6	21500	1.0	898	**—**	**310MR4**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	91800	116300	55500
1.6	21300	2.5	889	**313ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	166800	195500	68100
1.7	19700	2.2	825	**311ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	113900	116200	54000
1.8	19100	0.9	801	**309L4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	79900	102800	29600
1.8	19100	1.4	798	**310ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	90200	114400	53400
1.8	18900	2.6	790	**313ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	164000	192200	65500
1.9	18100	1.4	757	**—**	**310MR4**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	89500	113500	52500
1.9	17800	1.8	746	**—**	**311MR4**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	112300	114600	52200
1.9	18600	1.9	778	**—**	**313MR4**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	163700	191800	65200
2.0	17300	1.2	722	**309L4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	78700	101300	28600
2.0	17300	1.5	726	**310ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	89000	112900	51700
2.1	16500	0.9	690	**—**	**309R4**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	78200	100600	28200
2.2	15600	1.2	654	**309L4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	77600	99800	27700
2.3	15200	1.7	637	**310ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	87400	110800	49500
2.3	15300	1.4	639	**—**	**310MR4**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	87400	110800	49600
2.3	15000	2.8	627	**311ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	109500	111700	49300
2.3	15000	2.7	629	**—**	**311MR4**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	109600	111800	49300
2.4	14100	1.8	590	**310ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	86400	109600	48300
2.4	14100	1.4	590	**—**	**310MR4**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	86400	109600	48300
2.5	13800	1.1	579	**307L4**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	33100	41400	74600	98100	33200
2.5	13900	0.9	581	**—**	**307R4**	**BE112M4**	**BX112M4**	**—**	**—**	33200	41500	74600	98200	33300
2.5	13800	1.5	579	**309L4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	0	0	76200	98100	26600
2.5	13900	1.1	581	**—**	**309R4**	**BE112M4**	**BX112M4**	**—**	**—**	0	0	76300	98200	26600
2.8	12200	1.2	509	**307L4**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	32500	40700	73200	96300	31800
2.8	12200	1.2	509	**309L4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	74900	96300	25500
2.8	12100	2.1	507	**310ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	84600	107200	45900
2.8	12400	2.0	517	**—**	**310MR4**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	84800	107500	46200
2.9	11700	1.2	490	**—**	**309R4**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	74500	95800	25100
2.9	11700	2.7	490	**—**	**311MR4**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	105700	107900	45400
3.1	11100	1.1	465	**307L4**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	32100	40200	72300	95100	30900
3.1	11100	1.7	465	**309L4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	73900	95100	24700
3.2	10600	0.9	444	**306L4**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	26600	30300	60600	70000	23600
3.2	10800	1.2	453	**—**	**307R4**	**BE112M4**	**BX112M4**	**—**	**—**	32000	40000	72000	94700	30600
3.2	10900	1.3	457	**—**	**309R4**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	73700	94900	24600
3.2	10800	2.7	453	**310ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	83200	105500	44200
3.2	10900	1.8	454	**—**	**310MR4**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	83200	105500	44200
3.5	9880	1.2	413	**—**	**307R4**	**BE112M4**	**BX112M4**	**—**	**—**	31600	39500	71100	93500	29700
3.5	9880	1.8	413	**—**	**309R4**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	72700	93500	23700
3.6	9690	1.2	406	**307L4**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	31500	39400	70900	93200	29500
3.6	9690	1.9	406	**309L4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	72500	93200	23600
3.7	9360	2.0	392	**310ML4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	81500	103300	42100
3.8	8950	1.6	374	**—**	**309R4**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	71600	92200	23000
3.8	9150	2.6	383	**—**	**310MR4**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	81200	103000	41800
4.0	8670	1.4	363	**—**	**307R4**	**BE112M4**	**BX112M4**	**—**	**—**	31000	38800	69800	91800	28400
4.1	8340	1.8	349	**307L4**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	30800	38500	69400	91300	28100
4.1	8340	2.5	349	**309L4**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	70900	91300	22400
4.3	8290	1.1	336	**307L3**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	30700	38300	69000	90800	27700
4.3	7920	1.5	331	**—**	**307R4**	**BE112M4**	**BX112M4**	**—**	**—**	30600	38300	68900	90600	27600
4.3	8290	1.6	336	**309L3**	**—**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	70600	90800	22200
4.3	7920	2.2	331	**—**	**309R4**	**BE112M4**	**BX112M4**	**—**	**—**	—	—	70400	90600	22100
4.6	7450	1.0	312	**—**	**306R4**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	25300	28800	57600	66500	21000
4.8	7170	2.0	300	**—**	**307R4**	**BE112M4**	**BX112M4**	**—**	**—**	30200	37700	67900	89300	26700
5.0	6910	1.2	289	**—**	**306R4**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	25000	28500	57000	65800	20500

A



P_1 = 4 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
5.1	6990	1.6	284	**307L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	30000	37500	67500	88800	26200
5.1	6800	1.7	284	—	**307R4**	**BE112M4**	**BX112M4**	—	—	30000	37500	67500	88800	26200
5.1	6990	2.3	284	**309L3**	—	**BE112M4**	**BX112M4**	—	—	—	—	69000	88800	20900
5.1	6800	2.5	284	—	**309R4**	**BE112M4**	**BX112M4**	—	—	—	—	69000	88800	21000
5.6	6170	2.4	258	—	**307R4**	**BE112M4**	**BX112M4**	—	—	30000	37500	67500	88800	25400
5.6	6170	2.8	258	—	**309R4**	**BE112M4**	**BX112M4**	—	—	—	—	69000	88800	20300
5.8	5940	1.4	249	—	**306R4**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	25000	28500	57000	65800	19500
6.0	5870	1.4	238	**306L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	25000	28500	57000	65800	19200
6.0	5900	1.5	239	**307L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	30000	37500	67500	88800	24700
6.0	5900	2.2	239	**309L3**	—	**BE112M4**	**BX112M4**	—	—	—	—	69000	88800	19800
6.2	5550	2.0	232	—	**307R4**	**BE112M4**	**BX112M4**	—	—	30000	37500	67500	88800	24500
6.3	5500	1.4	230	—	**306R4**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	25000	28500	57000	65800	19000
6.5	5460	1.2	222	**306L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	25000	28500	57000	65800	18800
6.5	5440	2.3	221	**307L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	30000	37500	67500	88800	24100
6.5	5490	2.4	223	**309L3**	—	**BE112M4**	**BX112M4**	—	—	—	—	69000	88800	19300
6.7	5120	1.1	214	—	**305R4**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	21000	24000	40500	48000	12700
6.7	5110	1.9	214	—	**306R4**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	25000	28500	57000	65800	18500
7.0	5050	1.6	205	**306L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	25000	28500	57000	65800	18300
7.0	4920	2.9	206	—	**307R4**	**BE112M4**	**BX112M4**	—	—	30000	37500	67500	88800	23500
7.1	4970	2.2	202	**307L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	30000	37500	67500	88800	23400
7.6	4680	1.4	190	**306L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	25000	28500	57000	65800	17800
7.8	4420	1.0	185	—	**305R4**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	21000	24000	40500	48000	12100
8.0	4330	2.2	181	—	**306R4**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	25000	28500	57000	65800	17500
8.1	4370	1.0	178	**305L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	21000	24000	40500	48000	11900
8.1	4360	2.8	177	**307L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	30000	37500	67500	88800	22400
8.6	4010	1.9	168	—	**306R4**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	25000	28500	57000	65800	17100
8.7	3950	2.8	165	—	**307R4**	**BE112M4**	**BX112M4**	—	—	30000	37500	67500	88800	21900
8.8	4030	1.1	164	**305L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	21000	24000	40500	48000	11600
8.9	3980	2.7	162	**307L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	30000	37500	67500	88800	21700
9.1	3780	0.9	158	—	**304R4**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	21000	24000	40500	48000	11500
9.1	3780	1.4	158	—	**305R4**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	21000	24000	40500	48000	11500
9.1	3770	2.6	158	—	**306R4**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	25000	28500	57000	65800	16800
9.4	3760	1.0	152	**305L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	21000	24000	40500	48000	11400
9.5	3750	2.0	152	**306L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	25000	28500	57000	65800	16500
9.6	3680	0.9	150	**304L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	21000	24000	40500	48000	11300
9.7	3540	1.0	148	—	**304R4**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	21000	24000	40500	48000	11200
9.7	3540	1.3	148	—	**305R4**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	21000	24000	40500	48000	11200
10.0	3550	1.5	144	—	**306R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	25000	28500	57000	65800	16300
10.2	3490	1.0	141	**304L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	20900	23900	40300	47700	11100
10.2	3490	1.5	141	**305L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	20900	23900	40300	47700	11100
10.2	3470	2.3	141	**306L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	24800	28300	56600	65400	16100
11.0	3210	1.1	130	**304L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	20300	23200	39300	46600	10800
11.1	3090	1.1	129	—	**304R4**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	20300	23200	39200	46500	10700
11.1	3090	1.7	129	—	**305R4**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	20300	23200	39200	46500	10700
11.6	3070	1.2	124	**305L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	20000	22900	38800	45900	10600
11.9	2990	2.6	121	**306L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	23600	26900	54100	62500	15300
12.0	2950	2.9	120	—	**307R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	28200	35300	63900	84000	19600
12.1	2940	2.2	119	—	**306R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	23500	26800	53900	62200	15300
12.6	2820	1.3	114	—	**305R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	19400	22200	37800	44800	10300
12.8	2780	1.3	113	**305L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	19400	22100	37600	44600	10300
12.8	2770	2.7	112	**306L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	23000	26200	52900	61100	15000
13.0	2720	1.2	111	**304L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	19200	22000	37400	44300	10200
13.2	2620	1.3	109	—	**304R4**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	19200	21900	37300	44200	10200
13.8	2580	1.0	105	**303L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	18900	21600	36800	43600	10000
13.8	2580	1.4	105	**304L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	18900	21600	36800	43600	10000
13.8	2580	2.0	105	**305L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	18900	21600	36800	43600	10000
14.6	2430	2.7	98.5	—	**306R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	22000	25100	50900	58700	14300
14.8	2390	1.0	97.0	—	**304R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	18400	21000	36000	42600	9770
15.7	2260	1.6	91.5	—	**305R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	18100	20600	35400	41900	9580
16.0	2220	1.0	90.2	**303L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	18000	20500	35200	41700	9530
16.0	2220	1.5	90.2	**304L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	18000	20500	35200	41700	9530
16.0	2220	1.9	90.2	**305L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	18000	20500	35200	41700	9530
16.1	2140	1.6	89.4	—	**304R4**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	17900	20500	35100	41600	9500
18.3	1940	1.1	78.7	—	**303R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	17200	19600	33800	40000	9110
18.3	1940	1.5	78.7	—	**304R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	17200	19600	33800	40000	9110
18.3	1940	2.2	78.7	—	**305R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	17200	19600	33800	40000	9110
18.6	1900	1.3	77.2	**303L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	17100	19500	33600	39800	9050
18.6	1900	1.8	77.2	**304L3**	—	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	17100	19500	33600	39800	9050



P_1 = 4 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
18.6	1900	2.5	77.2	**305L3**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	17100	19500	33600	39800	9050
19.6	1810	1.0	73.3	**—**	**303R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	16800	19200	33100	39200	8900
19.6	1810	2.0	73.3	**—**	**305R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	16800	19200	33100	39200	8900
19.9	1780	1.3	72.3	**303L3**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	16700	19100	32900	39000	8850
19.9	1780	1.9	72.3	**304L3**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	16700	19100	32900	39000	8850
19.9	1780	2.3	72.3	**305L3**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	16700	19100	32900	39000	8850
22.8	1560	1.1	63.2	**301L3**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	4940	4940	16800	18400	2820
22.8	1550	1.6	63.1	**303L3**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	15900	18200	31600	37500	8460
22.8	1550	1.4	63.1	**—**	**303R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	15900	18200	31600	37500	8460
22.8	1550	2.2	63.1	**304L3**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	15900	18200	31600	37500	8460
22.8	1550	1.8	63.1	**—**	**304R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	15900	18200	31600	37500	8460
22.8	1550	2.8	63.1	**—**	**305R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	15900	18200	31600	37500	8460
22.9	1550	1.1	62.9	**—**	**301R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	4930	4930	16800	18300	2820
24.3	1500	1.6	59.1	**304L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	15600	17800	31000	36800	8280
25.8	1420	1.3	55.8	**303L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	15300	17500	30500	36100	8120
25.8	1420	2.5	55.8	**305L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	15300	17500	30500	36100	8120
26.6	1340	1.4	54.2	**—**	**303R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	15200	17300	30200	35800	8040
26.6	1340	2.7	54.2	**—**	**305R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	15200	17300	30200	35800	8040
27.0	1320	1.7	53.4	**303L3**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	15100	17200	30100	35600	8000
27.0	1320	2.5	53.4	**304L3**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	15100	17200	30100	35600	8000
27.7	1320	1.0	51.9	**301L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	4630	4630	15800	17300	2640
27.9	1270	1.3	51.6	**301L3**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	4620	4620	15800	17300	2640
28.6	1240	1.3	50.4	**—**	**301R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	4580	4580	15700	17200	2620
28.6	1240	1.9	50.3	**—**	**303R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	14800	16900	29500	35000	7840
28.6	1240	2.8	50.3	**—**	**304R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	14800	16900	29500	35000	7840
30	1200	2.0	47.3	**304L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	14500	16600	29000	34400	7690
31	1150	1.9	46.6	**—**	**303R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	14400	16500	28900	34200	7650
31	1150	2.5	46.6	**—**	**304R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	14400	16500	28900	34200	7650
32	1130	1.6	44.6	**303L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	14200	16200	28500	33800	7540
33	1070	3.0	43.6	**304L3**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	14100	16100	28300	33500	7480
34	1050	2.0	42.6	**—**	**303R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	14000	16000	28100	33300	7420
35	1060	1.2	41.5	**301L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	4290	4290	14800	16200	2450
35	1010	1.3	41.2	**—**	**301R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	4280	4280	14800	16100	2450
38	970	1.6	38.4	**301L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	4180	4180	14500	15800	2390
38	980	2.2	38.4	**303L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	13500	15400	27200	32300	7170
38	980	2.9	38.4	**304L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	13500	15400	27200	32300	7170
39	920	0.9	37.3	**—**	**300R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	4140	4140	14300	16700	2370
39	920	1.7	37.3	**—**	**301R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	4140	4140	14300	15700	2370
39	920	2.6	37.1	**—**	**303R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	13400	15300	27000	32000	7090
40	910	2.0	35.8	**303L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	13200	15100	26700	31600	7000
43	850	1.5	33.3	**301L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3990	3990	13900	15100	2280
46	780	2.7	31.5	**—**	**303R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	12600	14500	25700	30400	6710
47	780	1.1	30.7	**300L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3880	3880	13500	15700	2220
47	750	1.1	30.4	**—**	**300R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3870	3870	13500	15700	2210
47	780	2.0	30.7	**301L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3880	3880	13500	14800	2220
47	750	2.1	30.4	**—**	**301R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3870	3870	13500	14700	2210
47	780	2.7	30.8	**303L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	12600	14300	25500	30200	6660
54	670	2.7	26.4	**303L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	11900	13600	24400	28900	6330
58	610	1.2	24.8	**—**	**300R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3620	3620	12700	14800	2070
58	610	2.3	24.8	**—**	**301R3**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3620	3620	12700	13900	2070
58	630	1.4	24.8	**—**	**303R2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	11700	13300	23900	28300	6200
59	620	1.3	24.6	**300L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3610	3610	12700	14700	2060
59	620	2.4	24.6	**301L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3610	3610	12700	13800	2060
72	510	1.3	20.1	**300L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3370	3370	11900	13800	1930
72	510	2.5	20.1	**301L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3370	3370	11900	13000	1930
78	470	1.6	18.5	**—**	**301R2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3280	3280	11600	12700	1870
79	460	1.6	18.2	**300L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3260	3260	11600	13400	1860
79	460	3.0	18.2	**301L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3260	3260	11600	12600	1860
97	380	1.9	14.8	**300L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3050	3050	10900	12600	1740
98	370	1.4	14.8	**—**	**300R2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3040	3040	10900	12600	1740
98	370	2.5	14.8	**—**	**301R2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3040	3040	10900	11900	1740
119	310	2.3	12.1	**300L2**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	2850	2850	10200	11900	1630
122	300	2.0	11.8	**—**	**300R2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	2830	2830	10200	11800	1610
160	240	1.4	9.00	**300L1**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	2580	2580	9360	10900	1470
160	240	2.7	9.00	**301L1**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	2580	2580	9360	10200	1470
165	220	2.8	8.74	**—**	**300R2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	2550	2550	9280	10800	1460
200	190	2.2	7.20	**300L1**	**—**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	2390	2390	8750	10200	1370



P_1 = 5.5 kW

n_2	M_2	S	i							Rn_2 [N]				
min^{-1}	Nm					IE2	IE3	IE2	IE3	MC	MZ	HC/PC	HZ/PZ	FZ
0.77	60300	2.5	1893	**317ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	410500	436100	150000
0.80	57900	1.0	1817	**313ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	184400	216100	80000
0.81	57300	1.1	1796	**314ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	171100	205200	90000
0.81	57500	1.4	1805	**315ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	171200	205400	90000
0.94	49500	2.5	1553	**316ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	256500	287700	150000
0.97	47900	1.2	1502	**313ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	179400	210300	80000
0.98	47300	1.3	1485	**314ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	166500	199700	90000
0.98	47600	1.7	1492	**315ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	166600	199800	90000
1.0	45100	0.9	1415	**311ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	122800	125300	64300
1.0	44400	1.1	1394	**313ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	177500	208000	78800
1.1	40700	1.8	1277	**314ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	163000	195500	86100
1.1	40900	2.2	1284	**315ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	163100	195600	86200
1.1	41700	2.9	1308	**316ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	250300	280700	144600
1.2	39200	1.2	1230	**311ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	120400	122800	61400
1.2	40300	1.4	1266	**313ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	175100	205200	76300
1.2	39400	3.0	1237	**316ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	248300	278500	142000
1.3	35600	1.4	1117	**313ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	172000	201600	73200
1.3	35000	2.0	1099	**314ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	159500	191300	81900
1.3	35200	2.5	1104	**315ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	159600	191400	82000
1.4	33700	1.3	1058	**311ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	117800	120200	58400
1.4	32300	1.7	1014	**313ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	169600	198800	70800
1.4	33100	2.3	1038	**314ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	158200	189700	80300
1.4	33200	3.0	1043	**315ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	158300	189900	80400
1.5	31000	1.0	974	**310ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	92600	117500	56800
1.5	31400	1.4	986	**311ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	116600	119000	57000
1.6	28300	1.8	889	**313ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	166500	195100	67800
1.6	29500	2.4	926	**314ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	155700	186700	77300
1.6	29700	3.0	930	**315ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	155800	186800	77500
1.6	29000	2.5	909	**—**	**315MR4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	155300	186200	76900
1.7	27300	2.7	858	**314ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	154000	184600	75400
1.8	25400	1.1	798	**310ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	90000	114200	53100
1.8	26300	1.7	825	**311ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	113700	116000	53700
1.8	25200	2.0	790	**313ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	163700	191800	65200
1.9	24100	1.0	757	**—**	**310MR4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	89400	113300	52200
1.9	24800	1.4	778	**—**	**313MR4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	163300	191400	64900
2.0	23000	0.9	722	**309L4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	78500	101100	28500
2.0	23100	1.2	726	**310ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	88800	112600	51500
2.0	23800	1.4	746	**—**	**311MR4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	112100	114300	52000
2.1	22200	2.3	695	**313ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	160700	188300	62500
2.3	20300	1.3	637	**310ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	87200	110500	49300
2.3	20400	1.0	639	**—**	**310MR4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	87200	110600	49300
2.3	20000	2.1	627	**311ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	109300	111500	49000
2.3	20000	2.1	629	**—**	**311MR4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	109300	111600	49100
2.3	20200	2.4	633	**313ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	158600	185800	60500
2.3	20600	2.4	647	**—**	**313MR4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	159100	186400	61000
2.4	19600	2.8	614	**—**	**314MR4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	146800	176000	67400
2.5	18400	1.2	579	**309L4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	76100	97900	26400
2.5	18800	1.4	590	**310ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	86200	109300	48000
2.5	18800	1.0	590	**—**	**310MR4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	86200	109300	48000
2.6	18100	2.3	568	**311ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	107800	110000	47400
2.7	17000	2.8	535	**—**	**313MR4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	154800	181400	57200
2.8	16500	1.5	517	**—**	**310MR4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	84600	107300	46000
2.8	16600	2.4	520	**—**	**311MR4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	106400	108600	46100
2.8	16400	2.9	514	**313ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	153900	180400	56500
2.9	16200	1.5	507	**310ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	84400	107000	45700
2.9	16300	2.8	512	**311ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	106200	108400	45800
3.0	15600	2.1	490	**—**	**311MR4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	105500	107700	45200
3.1	14800	1.2	465	**309L4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	73700	94900	24600
3.2	14400	0.9	453	**—**	**307R4**	**BE132S4**	**BX132SB4**	**—**	**—**	31900	39900	71900	94500	30500
3.2	14600	1.0	457	**—**	**309R4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	73600	94700	24400
3.2	14400	2.0	453	**310ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	83100	105300	44000
3.2	14500	1.3	454	**—**	**310MR4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	83100	105300	44000
3.3	14000	2.8	438	**—**	**311MR4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	103800	106000	43500
3.5	13200	0.9	413	**—**	**307R4**	**BE132S4**	**BX132SB4**	**—**	**—**	31500	39400	70900	93300	29500
3.5	13200	1.4	413	**—**	**309R4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	72500	93300	23600
3.5	13200	3.0	413	**—**	**311MR4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	103000	105100	42700



P_1 = 5.5 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N]				
min^{-1}	Nm									MC	MZ	HC/PC	HZ/PZ	FZ
3.6	12900	0.9	406	**307L4**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	31400	39300	70700	93100	29400
3.6	12900	1.4	406	**309L4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	72300	93100	23500
3.7	12500	1.5	392	**310ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	81300	103100	41900
3.8	12200	2.0	383	**—**	**310MR4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	81100	102800	41600
3.9	11900	1.2	374	**—**	**309R4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	71500	92000	22900
4.0	11600	1.1	363	**—**	**307R4**	**BE132S4**	**BX132SB4**	**—**	**—**	30900	38700	69600	91600	28300
4.2	11100	1.3	349	**307L4**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	30800	38500	69200	91100	27900
4.2	11100	1.9	349	**309L4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	70800	91100	22300
4.2	11500	1.6	350	**310ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	80100	101500	40400
4.2	11000	2.7	347	**—**	**310MR4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	79900	101400	40200
4.3	11100	1.2	336	**309L3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	70400	90600	22100
4.4	10600	1.1	331	**—**	**307R4**	**BE132S4**	**BX132SB4**	**—**	**—**	30500	38200	68700	90400	27400
4.4	10600	1.6	331	**—**	**309R4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	70300	90400	22000
4.8	9720	2.4	305	**—**	**310MR4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	78500	99500	38600
4.9	9560	1.5	300	**—**	**307R4**	**BE132S4**	**BX132SB4**	**—**	**—**	30100	37600	67800	89100	26600
4.9	9700	2.3	295	**310ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	78100	99100	38200
5.0	9570	2.9	291	**311ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	98000	100000	38000
5.1	9210	0.9	289	**—**	**306R4**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	25000	28500	57000	65800	20400
5.1	9310	1.2	284	**307L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	30000	37500	67500	88800	26100
5.1	9070	1.2	284	**—**	**307R4**	**BE132S4**	**BX132SB4**	**—**	**—**	30000	37500	67500	88800	26100
5.1	9310	1.7	284	**309L3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	69000	88800	20800
5.1	9070	1.9	284	**—**	**309R4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	69000	88800	20900
5.7	8220	1.8	258	**—**	**307R4**	**BE132S4**	**BX132SB4**	**—**	**—**	30000	37500	67500	88800	25300
5.7	8220	2.1	258	**—**	**309R4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	69000	88800	20200
5.7	8230	2.7	258	**—**	**310MR4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	78000	98900	36500
5.9	7920	1.0	249	**—**	**306R4**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	25000	28500	57000	65800	19400
5.9	8190	2.2	249	**310ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	78000	98900	36100
6.1	7820	1.0	238	**306L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	25000	28500	57000	65800	19100
6.1	7860	1.1	239	**307L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	30000	37500	67500	88800	24600
6.1	7860	1.7	239	**309L3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	69000	88800	19700
6.3	7340	1.0	230	**—**	**306R4**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	25000	28500	57000	65800	18900
6.3	7400	1.5	232	**—**	**307R4**	**BE132S4**	**BX132SB4**	**—**	**—**	30000	37500	67500	88800	24400
6.3	7400	2.3	232	**—**	**309R4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	69000	88800	19500
6.3	7560	2.6	230	**310ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	78000	98900	35100
6.6	7260	1.8	221	**307L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	30000	37500	67500	88800	24000
6.6	7320	1.8	223	**309L3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	69000	88800	19200
6.8	6810	1.4	214	**—**	**306R4**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	25000	28500	57000	65800	18400
7.1	6730	1.2	205	**306L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	25000	28500	57000	65800	18200
7.1	6550	2.2	206	**—**	**307R4**	**BE132S4**	**BX132SB4**	**—**	**—**	30000	37500	67500	88800	23400
7.2	6620	1.7	202	**307L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	30000	37500	67500	88800	23300
7.2	6620	2.5	202	**309L3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	69000	88800	18600
7.7	6230	1.0	190	**306L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	25000	28500	57000	65800	17700
7.7	6080	2.3	191	**—**	**307R4**	**BE132S4**	**BX132SB4**	**—**	**—**	30000	37500	67500	88800	22800
7.7	6080	2.8	191	**—**	**309R4**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	69000	88800	18300
8.0	6000	2.4	183	**309L3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	69000	88800	18000
8.1	5770	1.6	181	**—**	**306R4**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	25000	28500	57000	65800	17500
8.2	5820	2.1	177	**307L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	30000	37500	67500	88800	22300
8.7	5350	1.4	168	**—**	**306R4**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	25000	28500	57000	65800	17000
8.8	5260	2.1	165	**—**	**307R4**	**BE132S4**	**BX132SB4**	**—**	**—**	30000	37500	67500	88800	21800
9.0	5310	2.0	162	**307L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	30000	37500	67500	88800	21600
9.2	5050	1.1	158	**—**	**305R4**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	21000	24000	40500	48000	11400
9.2	5030	1.9	158	**—**	**306R4**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	25000	28500	57000	65800	16700
9.6	4990	1.5	152	**306L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	25000	28500	57000	65800	16500
9.6	4840	2.8	152	**—**	**307R4**	**BE132S4**	**BX132SB4**	**—**	**—**	30000	37500	67500	88800	21200
9.9	4720	1.0	148	**—**	**305R4**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	21000	24000	40500	48000	11200
10.0	4810	2.8	146	**307L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	30000	37500	67500	88800	20900
10.1	4740	1.2	144	**—**	**306R3**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	24900	28400	56800	65500	16200
10.3	4650	1.1	141	**305L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	20800	23700	40100	47500	11000
10.4	4630	1.7	141	**306L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	24700	28200	56400	65100	16100
10.5	4560	2.4	139	**307L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	29500	36900	66500	87500	20500
11.3	4120	1.3	129	**—**	**305R4**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	20200	23000	39000	46300	10700
12.0	3980	2.0	121	**306L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	23500	26800	53900	62200	15300
12.2	3930	2.2	120	**—**	**307R3**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	28100	35100	63600	83700	19600
12.3	3920	1.7	119	**—**	**306R3**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	23400	26600	53600	61900	15200
12.8	3760	1.0	114	**—**	**305R3**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	19400	22100	37600	44600	10300



P_1 = 5.5 kW

n_2	M_2	S	i							Rn_2 [N]				
min^{-1}	Nm					IE2	IE3	IE2	IE3	MC	MZ	HC/PC	HZ/PZ	FZ
12.9	3720	2.8	113	**307L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	27600	34500	62600	82300	19200
13.0	3700	1.0	113	**305L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	19300	22000	37500	44400	10200
13.0	3690	2.0	112	**306L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	22900	26100	52700	60800	14900
13.2	3630	0.9	111	**304L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	19100	21900	37300	44200	10200
13.3	3490	1.0	109	**—**	**304R4**	**BE132S4**	**BX132SB4**	**—**	**—**	19100	21800	37200	44000	10100
14.0	3430	1.0	105	**304L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	18800	21500	36600	43400	9970
14.0	3430	1.5	105	**305L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	18800	21500	36600	43400	9970
14.0	3420	2.6	104	**306L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	22300	25500	51500	59500	14500
14.7	3250	2.6	99.0	**—**	**307R3**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	26400	32900	60100	79000	18300
14.8	3240	2.0	98.5	**—**	**306R3**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	21900	25000	50700	58500	14200
16.0	3010	1.2	91.5	**—**	**305R3**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	18000	20500	35200	41700	9530
16.2	2960	1.1	90.2	**304L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	17900	20400	35100	41500	9490
16.2	2960	1.4	90.2	**305L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	17900	20400	35100	41500	9490
16.3	2850	1.2	89.4	**—**	**304R4**	**BE132S4**	**BX132SB4**	**—**	**—**	17800	20400	35000	41400	9460
16.5	2900	3.0	88.3	**306L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	21100	24100	49000	56600	13700
17.2	2780	2.7	84.7	**—**	**306R3**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	20900	23800	48400	55900	13600
17.8	2690	2.6	81.9	**306L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	20600	23500	47900	55300	13400
18.5	2590	1.1	78.7	**—**	**304R3**	**BE132S4**	**BX132SB4**	**—**	**—**	17100	19500	33600	39900	9070
18.5	2590	1.7	78.7	**—**	**305R3**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	17100	19500	33600	39900	9070
18.9	2540	1.0	77.2	**303L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	17000	19400	33500	39700	9010
18.9	2540	1.4	77.2	**304L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	17000	19400	33500	39700	9010
18.9	2540	1.9	77.2	**305L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	17000	19400	33500	39700	9010
19.9	2410	1.5	73.3	**—**	**305R3**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	16700	19100	32900	39000	8850
20.1	2460	2.2	72.5	**306L2**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	19800	22600	46200	53300	12900
20.2	2370	0.9	72.3	**303L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	16600	19000	32800	38900	8810
20.2	2370	1.4	72.3	**304L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	16600	19000	32800	38900	8810
20.2	2370	1.8	72.3	**305L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	16600	19000	32800	38900	8810
23.1	2070	1.0	63.1	**—**	**303R3**	**BE132S4**	**BX132SB4**	**—**	**—**	15900	18100	31500	37300	8420
23.1	2070	1.4	63.1	**—**	**304R3**	**BE132S4**	**BX132SB4**	**—**	**—**	15900	18100	31500	37300	8420
23.1	2070	2.1	63.1	**—**	**305R3**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	15900	18100	31500	37300	8420
23.2	2070	1.2	63.1	**303L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	15900	18100	31500	37300	8420
23.2	2070	1.7	63.1	**304L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	15900	18100	31500	37300	8420
23.2	2070	2.3	63.1	**305L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	15900	18100	31500	37300	8420
24.7	2000	1.2	59.1	**304L2**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	15500	17800	30900	36600	8240
26.0	1910	2.7	56.3	**306L2**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	18200	20700	42800	49400	11800
26.2	1890	1.0	55.8	**303L2**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	15200	17400	30300	36000	8080
26.2	1890	1.9	55.8	**305L2**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	15200	17400	30300	36000	8080
26.9	1780	1.0	54.2	**—**	**303R3**	**BE132S4**	**BX132SB4**	**—**	**—**	15100	17200	30100	35700	8010
26.9	1780	2.0	54.2	**—**	**305R3**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	15100	17200	30100	35700	8010
27.3	1750	1.2	53.4	**303L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	15000	17200	30000	35500	7970
27.3	1750	1.8	53.4	**304L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	15000	17200	30000	35500	7970
27.3	1750	2.3	53.4	**305L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	15000	17200	30000	35500	7970
28.3	1700	1.0	51.6	**301L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	4600	4600	15700	17200	2630
29.0	1660	1.0	50.4	**—**	**301R3**	**BE132S4**	**BX132SB4**	**—**	**—**	4560	4560	15600	17100	2610
29.0	1650	1.4	50.3	**—**	**303R3**	**BE132S4**	**BX132SB4**	**—**	**—**	14700	16800	29400	34900	7810
29.0	1650	2.1	50.3	**—**	**304R3**	**BE132S4**	**BX132SB4**	**—**	**—**	14700	16800	29400	34900	7810
29.0	1650	2.7	50.3	**—**	**305R3**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	14700	16800	29400	34900	7810
31	1530	1.4	46.6	**—**	**303R3**	**BE132S4**	**BX132SB4**	**—**	**—**	14400	16400	28800	34100	7610
31	1600	1.5	47.3	**304L2**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	14400	16500	28900	34200	7650
31	1530	1.9	46.6	**—**	**304R3**	**BE132S4**	**BX132SB4**	**—**	**—**	14400	16400	28800	34100	7610
31	1530	2.8	46.6	**—**	**305R3**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	14400	16400	28800	34100	7610
33	1510	1.2	44.6	**303L2**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	14100	16200	28400	33600	7500
33	1430	2.2	43.6	**304L3**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	14000	16000	28200	33400	7450
33	1510	2.4	44.6	**305L2**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	14100	16200	28400	33600	7500
34	1400	1.5	42.6	**—**	**303R3**	**BE132S4**	**BX132SB4**	**—**	**—**	13900	15900	28000	33200	7390
34	1400	2.3	42.6	**—**	**304R3**	**BE132S4**	**BX132SB4**	**—**	**—**	13900	15900	28000	33200	7390
34	1400	2.7	42.6	**—**	**305R3**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	13900	15900	28000	33200	7390
35	1410	0.9	41.5	**301L2**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	4280	4280	14700	16100	2440
35	1350	1.0	41.2	**—**	**301R3**	**BE132S4**	**BX132SB4**	**—**	**—**	4260	4260	14700	16100	2430
38	1300	1.2	38.4	**301L2**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	4160	4160	14400	15700	2380
38	1300	1.7	38.4	**303L2**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	13500	15400	27100	32200	7140
38	1300	2.2	38.4	**304L2**	**—**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	13500	15400	27100	32200	7140
39	1220	1.3	37.3	**—**	**301R3**	**BE132S4**	**BX132SB4**	**—**	**—**	4120	4120	14300	15600	2360
39	1220	2.0	37.1	**—**	**303R3**	**BE132S4**	**BX132SB4**	**—**	**—**	13300	15200	26900	31800	7060
39	1220	2.8	37.1	**—**	**304R3**	**BE132S4**	**BX132SB4**	**—**	**—**	13300	15200	26900	31800	7060



P_1 = 5.5 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
41	1210	1.5	35.8	**303L2**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	13100	15000	26600	31500	6970
41	1210	2.9	35.8	**305L2**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	13100	15000	26600	31500	6970
44	1130	1.2	33.3	**301L2**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	3970	3970	13800	15100	2270
46	1030	2.0	31.5	—	**303R3**	**BE132S4**	**BX132SB4**	—	—	12600	14400	25600	30300	6680
46	1030	3.0	31.5	—	**304R3**	**BE132S4**	**BX132SB4**	—	—	12600	14400	25600	30300	6680
47	1040	2.1	30.8	**303L2**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	12500	14300	25400	30100	6630
47	1040	2.7	30.8	**304L2**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	12500	14300	25400	30100	6630
48	1040	1.5	30.7	**301L2**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	3870	3870	13500	14700	2210
48	1000	1.6	30.4	—	**301R3**	**BE132S4**	**BX132SB4**	—	—	3850	3850	13400	14700	2200
55	900	2.0	26.4	**303L2**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	11900	13600	24300	28700	6300
57	840	2.4	25.7	—	**303R3**	**BE132S4**	**BX132SB4**	—	—	11800	13400	24000	28500	6240
59	830	1.0	24.6	**300L2**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	3590	3590	12600	14700	2050
59	830	1.8	24.6	**301L2**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	3590	3590	12600	13800	2050
59	820	1.7	24.8	—	**301R3**	**BE132S4**	**BX132SB4**	—	—	3600	3600	12600	13800	2060
59	840	1.0	24.8	—	**303R2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	11600	13300	23800	28200	6170
60	830	2.6	24.5	**303L2**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	11600	13200	23700	28100	6150
64	770	2.7	22.7	**303L2**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	11300	12900	23200	27500	5990
70	700	2.6	20.8	**303L2**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	11000	12500	22600	26700	5820
73	680	0.9	20.1	**300L2**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	3360	3360	11900	13800	1920
73	680	1.9	20.1	**301L2**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	3360	3360	11900	13000	1920
76	650	2.4	19.2	—	**303R2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	10700	12200	22000	26100	5670
79	620	1.2	18.5	—	**301R2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	3260	3260	11600	12600	1860
80	620	1.2	18.2	**300L2**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	3250	3250	11500	13400	1850
80	620	2.2	18.2	**301L2**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	3250	3250	11500	12600	1850
98	500	1.4	14.8	**300L2**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	3030	3030	10800	12600	1730
98	500	2.6	14.8	**301L2**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	3030	3030	10800	11800	1730
99	500	1.0	14.8	—	**300R2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	3030	3030	10800	12600	1730
99	500	1.9	14.8	—	**301R2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	3030	3030	10800	11800	1730
121	410	1.7	12.1	**300L2**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	2830	2830	10200	11800	1620
121	410	3.0	12.1	**301L2**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	2830	2830	10200	11100	1620
123	400	1.5	11.8	—	**300R2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	2810	2810	10100	11800	1610
123	400	2.9	11.8	—	**301R2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	2810	2810	10100	11100	1610
151	340	2.3	9.67	**303L1**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	8500	9710	17900	21300	4510
162	310	1.0	9.00	**300L1**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	2570	2570	9320	10800	1470
162	310	2.0	9.00	**301L1**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	2570	2570	9320	10200	1470
167	300	2.1	8.74	—	**300R2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	2540	2540	9240	10700	1450
203	250	1.6	7.20	**300L1**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	2380	2380	8720	10100	1360
205	240	2.4	7.13	—	**300R2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	2380	2380	8690	10100	1360
253	200	2.4	5.77	**300L1**	—	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	2210	2210	8160	9480	1260

P_1 = 7.5 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
0.77	82100	1.8	1893	**317ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	410500	436100	150000
0.81	78300	1.0	1805	**315ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	171200	205400	90000
0.92	69200	2.3	1595	**317ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	400600	425500	150000
0.94	67400	1.8	1553	**316ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	256500	287700	150000
0.98	64400	1.0	1485	**314ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	166500	199700	90000
0.98	64700	1.2	1492	**315ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	166600	199800	90000
1.1	55400	1.3	1277	**314ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	163000	195500	86100
1.1	55700	1.6	1284	**315ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	163100	195600	86200
1.1	56800	2.1	1308	**316ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	250300	280700	144600
1.1	57200	2.7	1318	**317ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	389800	414100	145000
1.2	54900	1.0	1266	**313ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	175100	205200	76300
1.2	53700	2.2	1237	**316ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	248300	278500	142000
1.3	48500	1.0	1117	**313ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	172000	201600	73200
1.3	47700	1.5	1099	**314ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	159500	191300	81900
1.3	47900	1.9	1104	**315ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	159600	191400	82000
1.3	47900	2.5	1104	**316ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	244300	274000	136700
1.4	45900	1.0	1058	**311ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	117800	120200	58400
1.4	44000	1.2	1014	**313ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	169600	198800	70800



A

P_1 = 7.5 kW

n_2	M_2	S	i							Rn_2 [N]				
min^{-1}	Nm					IE2	IE3	IE2	IE3	MC	MZ	HC/PC	HZ/PZ	FZ
1.4	45000	1.7	1038	**314ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	158200	189700	80300
1.4	45200	2.2	1043	**315ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	158300	189900	80400
1.4	44200	2.7	1020	**316ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	241500	270900	133100
1.5	42800	1.1	986	**311ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	116600	119000	57000
1.6	38600	1.4	889	**313ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	166500	195100	67800
1.6	40200	1.8	926	**314ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	155700	186700	77300
1.6	40400	2.2	930	**315ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	155800	186800	77500
1.6	39400	1.8	909	**—**	**315MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	155300	186200	76900
1.7	37200	2.0	858	**314ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	154000	184600	75400
1.7	37400	2.6	862	**315ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	154100	184800	75500
1.8	35800	1.2	825	**311ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	113700	116000	53700
1.8	34300	1.4	790	**313ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	163700	191800	65200
1.9	33800	1.1	778	**—**	**313MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	163300	191400	64900
1.9	33900	2.6	782	**—**	**315MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	152000	182200	73100
2.0	32400	1.0	746	**—**	**311MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	112100	114300	52000
2.0	32000	2.3	738	**314ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	150700	180700	71700
2.0	32200	3.0	741	**315ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	150800	180800	71800
2.1	30200	1.7	695	**313ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	160700	188300	62500
2.2	29000	2.6	668	**314ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	148600	178200	69400
2.2	28600	3.0	659	**—**	**315MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	148300	177800	69000
2.3	27600	0.9	637	**310ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	87200	110500	49300
2.3	27200	1.5	627	**311ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	109300	111500	49000
2.3	27300	1.5	629	**—**	**311MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	109300	111600	49100
2.3	27500	1.8	633	**313ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	158600	185800	60500
2.3	28100	1.8	647	**—**	**313MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	159100	186400	61000
2.4	26600	2.0	614	**—**	**314MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	146800	176000	67400
2.5	25600	1.0	590	**310ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	86200	109300	48000
2.5	24900	2.7	575	**314ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	145400	174400	66000
2.5	25500	2.8	588	**314ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	145900	174900	66500
2.6	24600	1.7	568	**311ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	107800	110000	47400
2.6	24500	2.2	564	**313ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	156000	182800	58300
2.7	23200	2.1	535	**—**	**313MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	154800	181400	57200
2.8	22400	1.1	517	**—**	**310MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	84600	107300	46000
2.8	22500	1.8	520	**—**	**311MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	106400	108600	46100
2.8	22300	2.1	514	**313ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	153900	180400	56500
2.8	22900	2.9	528	**—**	**314MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	143700	172300	64100
2.9	22000	1.1	507	**310ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	84400	107000	45700
2.9	22200	2.1	512	**311ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	106200	108400	45800
2.9	21500	2.3	496	**—**	**313MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	153200	179500	55800
3.0	21300	1.5	490	**—**	**311MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	105500	107700	45200
3.1	20200	0.9	465	**309L4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	73700	94900	24600
3.2	19700	1.5	453	**310ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	83100	105300	44000
3.2	19700	1.0	454	**—**	**310MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	83100	105300	44000
3.2	19600	2.9	452	**313ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	151100	177100	54100
3.2	19500	2.4	450	**—**	**313MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	151100	177000	54100
3.3	19000	2.1	438	**—**	**311MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	103800	106000	43500
3.5	17900	1.0	413	**—**	**309R4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	72500	93300	23600
3.5	17900	2.2	413	**—**	**311MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	103000	105100	42700
3.6	17600	1.0	406	**309L4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	72300	93100	23500
3.6	17800	2.6	410	**311ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	102900	105000	42600
3.7	17000	1.1	392	**310ML4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	81300	103100	41900
3.8	16600	1.4	383	**—**	**310MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	81100	102800	41600
3.8	16800	2.7	387	**—**	**313MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	147900	173300	51400
4.2	15100	1.0	349	**307L4**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	30800	38500	69200	91100	27900
4.2	15100	1.4	349	**309L4**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	70800	91100	22300
4.2	15700	1.2	350	**310ML3**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	80100	101500	40400
4.2	15000	2.0	347	**—**	**310MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	79900	101400	40200
4.3	14800	2.5	341	**—**	**311MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	100200	102300	40000
4.4	14400	1.2	331	**—**	**309R4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	70300	90400	22000
4.8	13200	1.7	305	**—**	**310MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	78500	99500	38600
4.8	13600	2.2	304	**313ML3**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	142800	167300	47400
4.9	13000	1.1	300	**—**	**307R4**	**BE132MA4**	**BX132MA4**	**—**	**—**	30100	37600	67800	89100	26600
4.9	13200	1.7	295	**310ML3**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	78100	99100	38200
5.0	13000	2.1	291	**311ML3**	**—**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	98000	100000	38000
5.0	12700	2.9	294	**—**	**311MR4**	**BE132MA4**	**BX132MA4**	**—**	**—**	—	—	98100	100100	38100



P_1 = 7.5 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
5.1	12300	0.9	284	—	**307R4**	**BE132MA4**	**BX132MA4**	—	—	30000	37500	67500	88800	26100
5.1	12700	1.2	284	**309L3**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	69000	88800	20800
5.1	12300	1.4	284	—	**309R4**	**BE132MA4**	**BX132MA4**	—	—	—	—	69000	88800	20900
5.3	12000	2.3	276	—	**310MR4**	**BE132MA4**	**BX132MA4**	—	—	—	—	78000	98900	37300
5.7	11200	1.3	258	—	**307R4**	**BE132MA4**	**BX132MA4**	—	—	30000	37500	67500	88800	25300
5.7	11200	1.6	258	—	**309R4**	**BE132MA4**	**BX132MA4**	—	—	—	—	69000	88800	20200
5.7	11200	2.0	258	—	**310MR4**	**BE132MA4**	**BX132MA4**	—	—	—	—	78000	98900	36500
5.9	11100	1.6	249	**310ML3**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	78000	98900	36100
6.1	10700	1.2	239	**309L3**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	69000	88800	19700
6.1	10300	2.8	238	—	**310MR4**	**BE132MA4**	**BX132MA4**	—	—	—	—	78000	98900	35500
6.3	10100	1.1	232	—	**307R4**	**BE132MA4**	**BX132MA4**	—	—	30000	37500	67500	88800	24400
6.3	10100	1.7	232	—	**309R4**	**BE132MA4**	**BX132MA4**	—	—	—	—	69000	88800	19500
6.3	10300	1.9	230	**310ML3**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	78000	98900	35100
6.6	9880	1.3	221	**307L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	30000	37500	67500	88800	24000
6.6	9970	1.3	223	**309L3**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	69000	88800	19200
6.8	9270	1.1	214	—	**306R4**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	25000	28500	57000	65800	18400
7.1	8920	1.6	206	—	**307R4**	**BE132MA4**	**BX132MA4**	—	—	30000	37500	67500	88800	23400
7.1	8920	2.2	206	—	**309R4**	**BE132MA4**	**BX132MA4**	—	—	—	—	69000	88800	18700
7.1	8930	2.5	206	—	**310MR4**	**BE132MA4**	**BX132MA4**	—	—	—	—	78000	98900	33800
7.2	9020	1.2	202	**307L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	30000	37500	67500	88800	23300
7.2	9020	1.8	202	**309L3**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	69000	88800	18600
7.2	9030	2.5	202	**310ML3**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	78000	98900	33600
7.7	8270	1.7	191	—	**307R4**	**BE132MA4**	**BX132MA4**	—	—	30000	37500	67500	88800	22800
7.7	8270	2.1	191	—	**309R4**	**BE132MA4**	**BX132MA4**	—	—	—	—	69000	88800	18300
8.0	8170	1.8	183	**309L3**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	69000	88800	18000
8.1	7850	1.2	181	—	**306R4**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	25000	28500	57000	65800	17500
8.2	7920	1.6	177	**307L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	30000	37500	67500	88800	22300
8.2	7930	2.3	177	**310ML3**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	78000	98900	32200
8.7	7280	1.0	168	—	**306R4**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	25000	28500	57000	65800	17000
8.8	7170	1.5	165	—	**307R4**	**BE132MA4**	**BX132MA4**	—	—	30000	37500	67500	88800	21800
8.8	7170	2.3	165	—	**309R4**	**BE132MA4**	**BX132MA4**	—	—	—	—	69000	88800	17400
9.0	7220	1.5	162	**307L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	30000	37500	67500	88800	21600
9.0	7220	2.3	162	**309L3**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	69000	88800	17300
9.2	6850	1.4	158	—	**306R4**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	25000	28500	57000	65800	16700
9.6	6800	1.1	152	**306L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	25000	28500	57000	65800	16500
9.6	6590	2.1	152	—	**307R4**	**BE132MA4**	**BX132MA4**	—	—	30000	37500	67500	88800	21200
9.6	6590	2.8	152	—	**309R4**	**BE132MA4**	**BX132MA4**	—	—	—	—	69000	88800	16900
10.0	6540	2.1	146	**307L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	30000	37500	67500	88800	20900
10.4	6300	1.3	141	**306L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	24700	28200	56400	65100	16100
10.5	6210	1.7	139	**307L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	29500	36900	66500	87500	20500
10.5	6210	2.6	139	**309L3**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	68000	87500	16400
11.3	5610	0.9	129	—	**305R4**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	20200	23000	39000	46300	10700
11.6	5630	2.3	126	**307L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	28600	35700	64600	84900	19900
11.6	5630	2.9	126	**309L3**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	66000	84900	15900
12.0	5420	1.4	121	**306L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	23500	26800	53900	62200	15300
12.2	5360	1.6	120	—	**307R3**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	28100	35100	63600	83700	19600
12.2	5360	2.4	120	—	**309R3**	**BE132MA4**	**BX132MA4**	—	—	—	—	65000	83700	15600
12.3	5330	1.2	119	—	**306R3**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	23400	26600	53600	61900	15200
12.9	5070	2.1	113	**307L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	27600	34500	62600	82300	19200
13.0	5020	1.5	112	**306L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	22900	26100	52700	60800	14900
14.0	4670	1.1	105	**305L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	18800	21500	36600	43400	9970
14.0	4660	1.9	104	**306L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	22300	25500	51500	59500	14500
14.6	4490	2.8	100	**307L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	26500	33100	60300	79300	18400
14.7	4430	1.9	99.0	—	**307R3**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	26400	32900	60100	79000	18300
14.7	4430	2.9	99.0	—	**309R3**	**BE132MA4**	**BX132MA4**	—	—	—	—	61400	79000	14700
14.8	4410	1.5	98.5	—	**306R3**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	21900	25000	50700	58500	14200
15.7	4160	2.9	93.0	**307L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	25800	32300	59000	77600	18000
16.2	4030	1.1	90.2	**305L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	17900	20400	35100	41500	9490
16.5	3950	2.2	88.3	**306L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	21100	24100	49000	56600	13700
17.2	3790	2.0	84.7	—	**306R3**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	20900	23800	48400	55900	13600
17.5	3730	2.8	83.4	—	**307R3**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	24900	31100	57100	75100	17300
17.8	3660	1.9	81.9	**306L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	20600	23500	47900	55300	13400
18.1	3600	2.8	80.6	**307L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	24600	30800	56500	74300	17100
18.5	3520	1.2	78.7	—	**305R3**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	17100	19500	33600	39900	9070
18.9	3450	1.0	77.2	**304L3**	—	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	17000	19400	33500	39700	9010



P_1 = 7.5 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N]				
min^{-1}	Nm									MC	MZ	HC/PC	HZ/PZ	FZ
18.9	3450	1.4	77.2	**305L3**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	17000	19400	33500	39700	9010
19.0	3440	2.4	77.0	**306L3**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	20200	23000	47000	54300	13100
19.9	3280	1.1	73.3	**—**	**305R3**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	16700	19100	32900	39000	8850
20.0	3260	2.3	72.9	**—**	**306R3**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	19800	22600	46300	53400	12900
20.1	3340	1.6	72.5	**306L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	19800	22600	46200	53300	12900
20.2	3230	1.0	72.3	**304L3**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	16600	19000	32800	38900	8810
20.2	3230	1.3	72.3	**305L3**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	16600	19000	32800	38900	8810
21.6	3020	2.4	67.5	**—**	**306R3**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	19300	22000	45200	52200	12600
22.4	2920	2.6	65.2	**306L3**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	19100	21800	44800	51700	12400
23.1	2820	1.0	63.1	**—**	**304R3**	**BE132MA4**	**BX132MA4**	**—**	**—**	15900	18100	31500	37300	8420
23.1	2820	1.5	63.1	**—**	**305R3**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	15900	18100	31500	37300	8420
23.2	2820	1.2	63.1	**304L3**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	15900	18100	31500	37300	8420
23.2	2820	1.7	63.1	**305L3**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	15900	18100	31500	37300	8420
25.1	2600	2.9	58.1	**—**	**306R3**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	18400	21000	43200	49900	11900
26.0	2590	2.0	56.3	**306L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	18200	20700	42800	49400	11800
26.2	2570	1.4	55.8	**305L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	15200	17400	30300	36000	8080
26.9	2420	1.5	54.2	**—**	**305R3**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	15100	17200	30100	35700	8010
27.3	2390	0.9	53.4	**303L3**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	15000	17200	30000	35500	7970
27.3	2390	1.4	53.4	**304L3**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	15000	17200	30000	35500	7970
27.3	2390	1.7	53.4	**305L3**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	15000	17200	30000	35500	7970
29.0	2250	1.1	50.3	**—**	**303R3**	**BE132MA4**	**BX132MA4**	**—**	**—**	14700	16800	29400	34900	7810
29.0	2250	1.5	50.3	**—**	**304R3**	**BE132MA4**	**BX132MA4**	**—**	**—**	14700	16800	29400	34900	7810
29.0	2250	2.0	50.3	**—**	**305R3**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	14700	16800	29400	34900	7810
31	2080	1.0	46.6	**—**	**303R3**	**BE132MA4**	**BX132MA4**	**—**	**—**	14400	16400	28800	34100	7610
31	2180	1.1	47.3	**304L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	14400	16500	28900	34200	7650
31	2080	1.4	46.6	**—**	**304R3**	**BE132MA4**	**BX132MA4**	**—**	**—**	14400	16400	28800	34100	7610
31	2080	2.1	46.6	**—**	**305R3**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	14400	16400	28800	34100	7610
33	1950	1.6	43.6	**304L3**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	14000	16000	28200	33400	7450
33	2060	1.7	44.6	**305L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	14100	16200	28400	33600	7500
34	1900	1.1	42.6	**—**	**303R3**	**BE132MA4**	**BX132MA4**	**—**	**—**	13900	15900	28000	33200	7390
34	1900	1.7	42.6	**—**	**304R3**	**BE132MA4**	**BX132MA4**	**—**	**—**	13900	15900	28000	33200	7390
34	1900	2.0	42.6	**—**	**305R3**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	13900	15900	28000	33200	7390
38	1770	1.2	38.4	**303L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	13500	15400	27100	32200	7140
38	1770	1.6	38.4	**304L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	13500	15400	27100	32200	7140
38	1770	2.4	38.4	**305L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	13500	15400	27100	32200	7140
39	1670	1.0	37.3	**—**	**301R3**	**BE132MA4**	**BX132MA4**	**—**	**—**	4120	4120	14300	15600	2360
39	1660	1.4	37.1	**—**	**303R3**	**BE132MA4**	**BX132MA4**	**—**	**—**	13300	15200	26900	31800	7060
39	1660	2.1	37.1	**—**	**304R3**	**BE132MA4**	**BX132MA4**	**—**	**—**	13300	15200	26900	31800	7060
39	1660	2.6	37.1	**—**	**305R3**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	13300	15200	26900	31800	7060
41	1650	1.1	35.8	**303L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	13100	15000	26600	31500	6970
41	1650	2.2	35.8	**305L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	13100	15000	26600	31500	6970
46	1410	1.5	31.5	**—**	**303R3**	**BE132MA4**	**BX132MA4**	**—**	**—**	12600	14400	25600	30300	6680
46	1410	2.2	31.5	**—**	**304R3**	**BE132MA4**	**BX132MA4**	**—**	**—**	12600	14400	25600	30300	6680
46	1410	2.7	31.5	**—**	**305R3**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	12600	14400	25600	30300	6680
47	1420	1.5	30.8	**303L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	12500	14300	25400	30100	6630
47	1420	2.0	30.8	**304L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	12500	14300	25400	30100	6630
48	1420	1.1	30.7	**301L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	3870	3870	13500	14700	2210
48	1360	1.2	30.4	**—**	**301R3**	**BE132MA4**	**BX132MA4**	**—**	**—**	3850	3850	13400	14700	2200
55	1220	1.5	26.4	**303L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	11900	13600	24300	28700	6300
55	1220	2.9	26.4	**305L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	11900	13600	24300	28700	6300
57	1150	1.8	25.7	**—**	**303R3**	**BE132MA4**	**BX132MA4**	**—**	**—**	11800	13400	24000	28500	6240
57	1150	2.6	25.7	**—**	**304R3**	**BE132MA4**	**BX132MA4**	**—**	**—**	11800	13400	24000	28500	6240
59	1130	1.3	24.6	**301L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	3590	3590	12600	13800	2050
59	1110	1.3	24.8	**—**	**301R3**	**BE132MA4**	**BX132MA4**	**—**	**—**	3600	3600	12600	13800	2060
60	1130	1.9	24.5	**303L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	11600	13200	23700	28100	6150
60	1130	2.9	24.5	**304L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	11600	13200	23700	28100	6150
64	1050	2.0	22.7	**303L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	11300	12900	23200	27500	5990
64	1050	2.7	22.7	**304L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	11300	12900	23200	27500	5990
70	960	1.9	20.8	**303L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	11000	12500	22600	26700	5820
73	930	1.4	20.1	**301L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	3360	3360	11900	13000	1920
76	890	1.8	19.2	**—**	**303R2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	10700	12200	22000	26100	5670
80	840	0.9	18.2	**300L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	3250	3250	11500	13400	1850
80	840	1.6	18.2	**301L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	3250	3250	11500	12600	1850
81	840	2.4	18.1	**303L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	10500	12000	21700	25700	5560
92	730	2.5	15.9	**—**	**303R2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	10000	11500	20800	24700	5320



A

P_1 = 7.5 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
95	710	2.4	15.3	**303L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	9910	11300	20600	24400	5260
98	680	1.1	14.8	**300L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	3030	3030	10800	12600	1730
98	680	1.9	14.8	**301L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	3030	3030	10800	11800	1730
99	680	1.4	14.8	**—**	**301R2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	3030	3030	10800	11800	1730
117	580	2.9	12.5	**303L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	9260	10600	19400	23000	4910
121	560	1.2	12.1	**300L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	2830	2830	10200	11800	1620
121	560	2.2	12.1	**301L2**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	2830	2830	10200	11100	1620
123	550	1.1	11.8	**—**	**300R2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	2810	2810	10100	11800	1610
123	550	2.1	11.8	**—**	**301R2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	2810	2810	10100	11100	1610
151	460	1.7	9.67	**303L1**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	8500	9710	17900	21300	4510
162	430	1.5	9.00	**301L1**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	2570	2570	9320	10200	1470
167	400	1.5	8.74	**—**	**300R2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	2540	2540	9240	10700	1450
167	400	2.7	8.74	**—**	**301R2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	2540	2540	9240	10100	1450
203	340	1.2	7.20	**300L1**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	2380	2380	8720	10100	1360
203	340	2.2	7.20	**301L1**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	2380	2380	8720	9530	1360
205	330	1.8	7.13	**—**	**300R2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	2380	2380	8690	10100	1360
253	270	1.7	5.77	**300L1**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	2210	2210	8160	9480	1260
342	200	2.5	4.26	**300L1**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	2000	2000	7450	8660	1140
420	170	2.9	3.48	**300L1**	**—**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	1870	1870	7010	8150	1070

P_1 = 9.2 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
0.77	100500	1.5	1893	**317ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	410500	436100	150000
0.92	84700	1.8	1595	**317ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	400600	425500	150000
0.94	82500	1.5	1553	**316ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	256500	287700	150000
0.98	79300	1.0	1492	**315ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	166600	199800	90000
1.1	67900	1.1	1277	**314ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	163000	195500	86100
1.1	68200	1.3	1284	**315ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	163100	195600	86200
1.1	69500	1.7	1308	**316ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	250300	280700	144600
1.1	70000	2.2	1318	**317ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	389800	414100	145000
1.2	65700	1.8	1237	**316ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	248300	278500	142000
1.3	58400	1.2	1099	**314ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	159500	191300	81900
1.3	58700	1.5	1104	**315ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	159600	191400	82000
1.3	58700	2.0	1104	**316ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	244300	274000	136700
1.3	60200	2.6	1134	**317ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	381500	405300	137900
1.4	53900	1.0	1014	**313ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	169600	198800	70800
1.4	55100	1.4	1038	**314ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	158200	189700	80300
1.4	55400	1.8	1043	**315ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	158300	189900	80400
1.4	54200	2.2	1020	**316ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	241500	270900	133100
1.5	50600	2.8	953	**—**	**317MR4**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	372200	395400	130100
1.6	47200	1.1	889	**313ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	166500	195100	67800
1.6	49200	1.4	926	**314ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	155700	186700	77300
1.6	49400	1.8	930	**315ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	155800	186800	77500
1.6	48300	1.5	909	**—**	**315MR4**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	155300	186200	76900
1.7	45600	1.6	858	**314ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	154000	184600	75400
1.7	45800	2.1	862	**315ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	154100	184800	75500
1.7	46700	2.5	880	**316ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	236500	265300	126700
1.8	43800	1.0	825	**311ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	113700	116000	53700
1.8	42000	1.2	790	**313ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	163700	191800	65200
1.9	41500	2.1	782	**—**	**315MR4**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	152000	182200	73100
1.9	41600	2.8	784	**316ML4**	**—**	**BE132MB4**	**BX160MA4**	**—**	**—**	—	—	232600	260900	121900



P_1 = 9.2 kW

n_2	M_2	S	i							Rn_2 [N]				
min^{-1}	Nm					IE2	IE3	IE2	IE3	MC	MZ	HC/PC	HZ/PZ	FZ
1.9	41500	2.8	782	—	**316MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	232500	260900	121800
2.0	39200	1.9	738	**314ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	150700	180700	71700
2.0	39400	2.4	741	**315ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	150800	180800	71800
2.1	36900	1.4	695	**313ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	160700	188300	62500
2.2	35500	2.2	668	**314ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	148600	178200	69400
2.2	35700	2.7	672	**315ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	148700	178300	69500
2.2	35000	2.4	659	—	**315MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	148300	177800	69000
2.3	33300	1.3	627	**311ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	109300	111500	49000
2.3	33400	1.2	629	—	**311MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	109300	111600	49100
2.3	33600	1.5	633	**313ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	158600	185800	60500
2.3	34300	1.4	647	—	**313MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	159100	186400	61000
2.3	33100	2.9	623	—	**315MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	147100	176400	67800
2.4	32600	1.7	614	—	**314MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	146800	176000	67400
2.5	30500	2.2	575	**314ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	145400	174400	66000
2.5	31200	2.3	588	**314ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	145900	174900	66500
2.6	30200	1.4	568	**311ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	107800	110000	47400
2.6	29900	1.8	564	**313ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	156000	182800	58300
2.7	28400	1.7	535	—	**313MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	154800	181400	57200
2.8	27500	0.9	517	—	**310MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	84600	107300	46000
2.8	27600	1.5	520	—	**311MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	106400	108600	46100
2.8	27300	1.7	514	**313ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	153900	180400	56500
2.8	28000	2.4	528	—	**314MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	143700	172300	64100
2.9	26900	0.9	507	**310ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	84400	107000	45700
2.9	27200	1.7	512	**311ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	106200	108400	45800
2.9	26400	1.8	496	—	**313MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	153200	179500	55800
3.0	26000	1.2	490	—	**311MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	105500	107700	45200
3.0	26300	2.9	495	**314ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	142300	170700	62700
3.2	24100	1.2	453	**310ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	83100	105300	44000
3.2	24000	2.4	452	**313ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	151100	177100	54100
3.2	23900	1.9	450	—	**313MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	151100	177000	54100
3.3	23300	1.7	438	—	**311MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	103800	106000	43500
3.3	23600	2.5	445	—	**314MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	140200	168100	60600
3.5	21900	1.8	413	—	**311MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	103000	105100	42700
3.6	21800	2.1	410	**311ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	102900	105000	42600
3.7	20800	0.9	392	**310ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	81300	103100	41900
3.7	20900	2.7	394	**313ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	148200	173700	51700
3.8	20300	1.2	383	—	**310MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	81100	102800	41600
3.8	20600	2.2	387	—	**313MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	147900	173300	51400
4.2	18500	1.1	349	**309L4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	70800	91100	22300
4.2	19200	1.0	350	**310ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	80100	101500	40400
4.2	18400	1.6	347	—	**310MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	79900	101400	40200
4.2	18500	2.5	348	**311ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	100500	102500	40300
4.3	18100	2.1	341	—	**311MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	100200	102300	40000
4.4	17600	1.0	331	—	**309R4**	**BE132MB4**	**BX160MA4**	—	—	—	—	70300	90400	22000
4.7	16400	2.7	309	—	**313MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	143100	167700	47700
4.8	16200	1.4	305	—	**310MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	78500	99500	38600
4.8	16600	1.8	304	**313ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	142800	167300	47400
4.9	16200	1.4	295	**310ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	78100	99100	38200
5.0	15900	1.7	291	**311ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	98000	100000	38000



P_1 = 9.2 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
5.0	15600	2.4	294	—	**311MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	98100	100100	38100
5.1	15500	1.0	284	**309L3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	69000	88800	20800
5.1	15100	1.1	284	—	**309R4**	**BE132MB4**	**BX160MA4**	—	—	—	—	69000	88800	20900
5.3	14700	1.9	276	—	**310MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	78000	98900	37300
5.7	13700	1.1	258	—	**307R4**	**BE132MB4**	**BX160MA4**	—	—	30000	37500	67500	88800	25300
5.7	13700	1.3	258	—	**309R4**	**BE132MB4**	**BX160MA4**	—	—	—	—	69000	88800	20200
5.7	13700	1.6	258	—	**310MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	78000	98900	36500
5.9	13600	1.3	249	**310ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	78000	98900	36100
6.0	13400	2.7	245	**311ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	98000	100000	35900
6.1	13100	1.0	239	**309L3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	69000	88800	19700
6.1	12600	2.3	238	—	**310MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	78000	98900	35500
6.3	12300	0.9	232	—	**307R4**	**BE132MB4**	**BX160MA4**	—	—	30000	37500	67500	88800	24400
6.3	12300	1.4	232	—	**309R4**	**BE132MB4**	**BX160MA4**	—	—	—	—	69000	88800	19500
6.3	12600	1.5	230	**310ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	78000	98900	35100
6.6	12100	1.1	221	**307L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	30000	37500	67500	88800	24000
6.6	12200	1.1	223	**309L3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	69000	88800	19200
7.1	10900	1.3	206	—	**307R4**	**BE132MB4**	**BX160MA4**	—	—	30000	37500	67500	88800	23400
7.1	10900	1.8	206	—	**309R4**	**BE132MB4**	**BX160MA4**	—	—	—	—	69000	88800	18700
7.1	10900	2.0	206	—	**310MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	78000	98900	33800
7.2	11000	1.0	202	**307L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	30000	37500	67500	88800	23300
7.2	11000	1.5	202	**309L3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	69000	88800	18600
7.2	11100	2.0	202	**310ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	78000	98900	33600
7.7	10100	1.4	191	—	**307R4**	**BE132MB4**	**BX160MA4**	—	—	30000	37500	67500	88800	22800
7.7	10100	1.7	191	—	**309R4**	**BE132MB4**	**BX160MA4**	—	—	—	—	69000	88800	18300
7.7	10100	2.7	189	—	**310MR4**	**BE132MB4**	**BX160MA4**	—	—	—	—	78000	98900	32900
8.0	10000	1.4	183	**309L3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	69000	88800	18000
8.1	9610	1.0	181	—	**306R4**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	25000	28500	57000	65800	17500
8.2	9690	1.3	177	**307L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	30000	37500	67500	88800	22300
8.2	9710	1.8	177	**310ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	78000	98900	32200
8.8	8770	1.2	165	—	**307R4**	**BE132MB4**	**BX160MA4**	—	—	30000	37500	67500	88800	21800
8.8	8770	1.9	165	—	**309R4**	**BE132MB4**	**BX160MA4**	—	—	—	—	69000	88800	17400
8.9	8960	3.0	164	**310ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	78000	98900	31300
9.0	8850	1.2	162	**307L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	30000	37500	67500	88800	21600
9.0	8850	1.8	162	**309L3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	69000	88800	17300
9.2	8380	1.1	158	—	**306R4**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	25000	28500	57000	65800	16700
9.6	8320	0.9	152	**306L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	25000	28500	57000	65800	16500
9.6	8070	1.7	152	—	**307R4**	**BE132MB4**	**BX160MA4**	—	—	30000	37500	67500	88800	21200
9.6	8070	2.3	152	—	**309R4**	**BE132MB4**	**BX160MA4**	—	—	—	—	69000	88800	16900
9.8	8180	2.7	149	**310ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	78000	98900	30400
10.0	8010	1.7	146	**307L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	30000	37500	67500	88800	20900
10.4	7720	1.0	141	**306L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	24700	28200	56400	65100	16100
10.5	7600	1.4	139	**307L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	29500	36900	66500	87500	20500
10.5	7600	2.1	139	**309L3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	68000	87500	16400
11.6	6890	1.9	126	**307L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	28600	35700	64600	84900	19900
11.6	6890	2.4	126	**309L3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	66000	84900	15900
12.0	6640	1.2	121	**306L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	23500	26800	53900	62200	15300
12.2	6560	1.3	120	—	**307R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	28100	35100	63600	83700	19600
12.2	6560	2.0	120	—	**309R3**	**BE132MB4**	**BX160MA4**	—	—	—	—	65000	83700	15600



P_1 = 9.2 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
12.2	6560	2.6	120	—	**310MR3**	**BE132MB4**	**BX160MA4**	—	—	—	—	73500	93200	28200
12.3	6530	1.0	119	—	**306R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	23400	26600	53600	61900	15200
12.9	6200	1.7	113	**307L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	27600	34500	62600	82300	19200
12.9	6200	2.5	113	**309L3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	63900	82300	15400
13.0	6150	1.2	112	**306L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	22900	26100	52700	60800	14900
14.0	5710	1.6	104	**306L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	22300	25500	51500	59500	14500
14.6	5490	2.3	100	**307L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	26500	33100	60300	79300	18400
14.7	5420	1.6	99.0	—	**307R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	26400	32900	60100	79000	18300
14.7	5420	2.4	99.0	—	**309R3**	**BE132MB4**	**BX160MA4**	—	—	—	—	61400	79000	14700
14.7	5420	3.0	99.0	—	**310MR3**	**BE132MB4**	**BX160MA4**	—	—	—	—	69400	88000	26500
14.8	5390	1.2	98.5	—	**306R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	21900	25000	50700	58500	14200
15.7	5090	2.4	93.0	**307L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	25800	32300	59000	77600	18000
15.7	5090	3.0	93.0	**309L3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	60300	77600	14400
16.5	4830	1.8	88.3	**306L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	21100	24100	49000	56600	13700
17.2	4640	1.6	84.7	—	**306R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	20900	23800	48400	55900	13600
17.5	4570	2.2	83.4	—	**307R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	24900	31100	57100	75100	17300
17.8	4480	1.5	81.9	**306L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	20600	23500	47900	55300	13400
18.1	4410	2.3	80.6	**307L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	24600	30800	56500	74300	17100
18.5	4310	1.0	78.7	—	**305R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	17100	19500	33600	39900	9070
18.6	4310	2.6	78.6	—	**307R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	24400	30500	56100	73800	17000
18.9	4230	1.1	77.2	**305L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	17000	19400	33500	39700	9010
19.0	4220	2.0	77.0	**306L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	20200	23000	47000	54300	13100
19.7	4060	2.9	74.1	**307L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	23900	29900	55100	72500	16700
20.0	3990	1.9	72.9	—	**306R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	19800	22600	46300	53400	12900
20.1	4090	1.3	72.5	**306L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	19800	22600	46200	53300	12900
20.2	3960	1.1	72.3	**305L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	16600	19000	32800	38900	8810
20.3	3930	2.6	71.8	—	**307R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	23700	29600	54500	71800	16500
21.6	3700	1.9	67.5	—	**306R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	19300	22000	45200	52200	12600
22.4	3570	2.1	65.2	**306L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	19100	21800	44800	51700	12400
23.1	3450	1.3	63.1	—	**305R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	15900	18100	31500	37300	8420
23.2	3450	1.0	63.1	**304L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	15900	18100	31500	37300	8420
23.2	3450	1.4	63.1	**305L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	15900	18100	31500	37300	8420
25.1	3180	2.4	58.1	—	**306R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	18400	21000	43200	49900	11900
26.0	3180	1.6	56.3	**306L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	18200	20700	42800	49400	11800
26.2	3150	1.1	55.8	**305L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	15200	17400	30300	36000	8080
26.9	2970	1.2	54.2	—	**305R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	15100	17200	30100	35700	8010
27.3	2920	1.1	53.4	**304L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	15000	17200	30000	35500	7970
27.3	2920	1.4	53.4	**305L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	15000	17200	30000	35500	7970
27.4	2920	2.5	53.2	**306L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	17900	20400	42100	48600	11600
29.0	2750	1.3	50.3	—	**304R3**	**BE132MB4**	**BX160MA4**	—	—	14700	16800	29400	34900	7810
29.0	2750	1.6	50.3	—	**305R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	14700	16800	29400	34900	7810
31	2550	1.1	46.6	—	**304R3**	**BE132MB4**	**BX160MA4**	—	—	14400	16400	28800	34100	7610
31	2550	1.7	46.6	—	**305R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	14400	16400	28800	34100	7610
31	2630	2.5	46.5	**306L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	17100	19500	40400	46700	11100
32	2530	3.0	46.3	—	**306R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	17000	19400	40400	46600	11100
33	2390	1.3	43.6	**304L3**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	14000	16000	28200	33400	7450
33	2520	1.4	44.6	**305L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	14100	16200	28400	33600	7500
34	2330	1.4	42.6	—	**304R3**	**BE132MB4**	**BX160MA4**	—	—	13900	15900	28000	33200	7390



P_1 = 9.2 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
34	2330	1.6	42.6	—	**305R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	13900	15900	28000	33200	7390
38	2170	1.0	38.4	**303L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	13500	15400	27100	32200	7140
38	2170	1.3	38.4	**304L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	13500	15400	27100	32200	7140
38	2170	2.0	38.4	**305L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	13500	15400	27100	32200	7140
38	2170	3.0	38.4	**306L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	16000	18300	38200	44100	10400
39	2030	1.2	37.1	—	**303R3**	**BE132MB4**	**BX160MA4**	—	—	13300	15200	26900	31800	7060
39	2030	1.7	37.1	—	**304R3**	**BE132MB4**	**BX160MA4**	—	—	13300	15200	26900	31800	7060
39	2030	2.1	37.1	—	**305R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	13300	15200	26900	31800	7060
41	2020	0.9	35.8	**303L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	13100	15000	26600	31500	6970
41	2020	1.8	35.8	**305L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	13100	15000	26600	31500	6970
46	1720	1.2	31.5	—	**303R3**	**BE132MB4**	**BX160MA4**	—	—	12600	14400	25600	30300	6680
46	1720	1.8	31.5	—	**304R3**	**BE132MB4**	**BX160MA4**	—	—	12600	14400	25600	30300	6680
46	1720	2.2	31.5	—	**305R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	12600	14400	25600	30300	6680
47	1740	1.2	30.8	**303L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	12500	14300	25400	30100	6630
47	1740	1.6	30.8	**304L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	12500	14300	25400	30100	6630
47	1740	2.5	30.8	**305L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	12500	14300	25400	30100	6630
48	1730	0.9	30.7	**301L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	3870	3870	13500	14700	2210
48	1670	1.0	30.4	—	**301R3**	**BE132MB4**	**BX160MA4**	—	—	3850	3850	13400	14700	2200
55	1490	1.2	26.4	**303L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	11900	13600	24300	28700	6300
55	1490	2.4	26.4	**305L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	11900	13600	24300	28700	6300
57	1410	1.5	25.7	—	**303R3**	**BE132MB4**	**BX160MA4**	—	—	11800	13400	24000	28500	6240
57	1410	2.2	25.7	—	**304R3**	**BE132MB4**	**BX160MA4**	—	—	11800	13400	24000	28500	6240
57	1410	2.6	25.7	—	**305R3**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	11800	13400	24000	28500	6240
59	1390	1.1	24.6	**301L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	3590	3590	12600	13800	2050
59	1360	1.0	24.8	—	**301R3**	**BE132MB4**	**BX160MA4**	—	—	3600	3600	12600	13800	2060
60	1380	1.6	24.5	**303L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	11600	13200	23700	28100	6150
60	1380	2.4	24.5	**304L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	11600	13200	23700	28100	6150
60	1380	2.8	24.5	**305L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	11600	13200	23700	28100	6150
64	1280	1.6	22.7	**303L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	11300	12900	23200	27500	5990
64	1280	2.2	22.7	**304L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	11300	12900	23200	27500	5990
70	1170	1.6	20.8	**303L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	11000	12500	22600	26700	5820
70	1170	2.5	20.8	**304L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	11000	12500	22600	26700	5820
70	1170	2.8	20.8	**305L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	11000	12500	22600	26700	5820
73	1130	1.1	20.1	**301L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	3360	3360	11900	13000	1920
76	1080	1.4	19.2	—	**303R2**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	10700	12200	22000	26100	5670
76	1080	2.6	19.2	—	**305R2**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	10700	12200	22000	26100	5670
80	1030	1.3	18.2	**301L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	3250	3250	11500	12600	1850
81	1020	2.0	18.1	**303L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	10500	12000	21700	25700	5560
81	1020	2.9	18.1	**304L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	10500	12000	21700	25700	5560
87	950	2.5	16.8	—	**304R2**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	10200	11700	21200	25100	5420
92	900	2.0	15.9	—	**303R2**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	10000	11500	20800	24700	5320
95	870	2.0	15.3	**303L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	9910	11300	20600	24400	5260
98	840	1.5	14.8	**301L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	3030	3030	10800	11800	1730
99	830	1.1	14.8	—	**301R2**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	3030	3030	10800	11800	1730
107	770	2.6	13.7	—	**303R2**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	9540	10900	19900	23600	5060
117	710	2.3	12.5	**303L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	9260	10600	19400	23000	4910
121	680	1.0	12.1	**300L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	2830	2830	10200	11800	1620
121	680	1.8	12.1	**301L2**	—	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	2830	2830	10200	11100	1620
123	670	1.7	11.8	—	**301R2**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	2810	2810	10100	11100	1610



A

P_1 = 9.2 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
151	560	1.4	9.67	**303L1**	**—**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	8500	9710	17900	21300	4510
162	520	1.2	9.00	**301L1**	**—**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	2570	2570	9320	10200	1470
167	490	1.3	8.74	**—**	**300R2**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	2540	2540	9240	10700	1450
167	490	2.2	8.74	**—**	**301R2**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	2540	2540	9240	10100	1450
195	440	2.8	7.50	**303L1**	**—**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	7810	8920	16600	19700	4140
203	420	1.0	7.20	**300L1**	**—**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	2380	2380	8720	10100	1360
203	420	1.8	7.20	**301L1**	**—**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	2380	2380	8720	9530	1360
205	400	1.5	7.13	**—**	**300R2**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	2380	2380	8690	10100	1360
205	400	2.6	7.13	**—**	**301R2**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	2380	2380	8690	9500	1360
253	340	1.4	5.77	**300L1**	**—**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	2210	2210	8160	9480	1260
253	340	2.8	5.77	**301L1**	**—**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	2210	2210	8160	8910	1260
342	250	2.0	4.26	**300L1**	**—**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	2000	2000	7450	8660	1140
420	200	2.3	3.48	**300L1**	**—**	**BE132MB4**	**BX160MA4**	**ME4LB4**	**MX5SA4**	1870	1870	7010	8150	1070

P_1 = 11 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
0.77	120600	1.2	1893	**317ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	410300	435900	150000
0.92	101600	1.5	1595	**317ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	400400	425300	150000
0.94	99000	1.2	1553	**316ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	256300	287600	150000
1.1	81800	1.1	1284	**315ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	163000	195500	86100
1.1	83400	1.4	1308	**316ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	250100	280600	144500
1.1	84000	1.9	1318	**317ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	389600	413900	144800
1.2	78900	1.5	1237	**316ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	248200	278400	141800
1.3	70000	1.0	1099	**314ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	159400	191200	81800
1.3	70400	1.3	1104	**315ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	159500	191300	81900
1.3	70400	1.7	1104	**316ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	244200	273900	136500
1.3	72300	2.2	1134	**317ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	381300	405100	137700
1.4	66100	1.1	1038	**314ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	158100	189600	80200
1.4	66500	1.5	1043	**315ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	158200	189800	80400
1.4	65000	1.8	1020	**316ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	241400	270800	132900
1.4	65800	2.7	1032	**317ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	376300	399700	133500
1.5	60800	2.3	953	**—**	**317MR4**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	372000	395200	130000
1.6	56700	0.9	889	**313ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	166400	195000	67700
1.6	59000	1.2	926	**314ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	155600	186600	77200
1.6	59300	1.5	930	**315ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	155700	186700	77400
1.6	58000	1.3	909	**—**	**315MR4**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	155200	186100	76800
1.6	57600	2.7	904	**317ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	369200	392200	127700
1.7	54700	1.4	858	**314ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	153900	184600	75300
1.7	54900	1.8	862	**315ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	154000	184700	75400
1.7	56100	2.1	880	**316ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	236400	265100	126600
1.9	50300	1.0	790	**313ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	163600	191700	65100
1.9	49900	1.7	782	**—**	**315MR4**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	151900	182100	73000
1.9	50000	2.3	784	**316ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	232500	260800	121800
1.9	49900	2.3	782	**—**	**316MR4**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	232400	260700	121700
2.0	47000	1.6	738	**314ML4**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	150600	180600	71600



P_1 = 11 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
2.0	47300	2.0	741	**315ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	150700	180800	71700
2.1	44300	1.1	695	**313ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	160700	188300	62400
2.1	45000	2.5	706	**316ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	229100	257000	117600
2.2	42600	1.8	668	**314ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	148500	178100	69300
2.2	42800	2.2	672	**315ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	148600	178200	69400
2.2	42000	2.0	659	—	**315MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	148200	177700	69000
2.2	42000	2.7	659	—	**316MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	226800	254400	114900
2.3	39900	1.0	627	**311ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	109200	111500	49000
2.3	40100	1.0	629	—	**311MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	109300	111500	49000
2.3	40300	1.2	633	**313ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	158500	185800	60500
2.3	41200	1.2	647	—	**313MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	159000	186300	60900
2.3	40000	2.8	628	**316ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	225200	252700	113100
2.4	39100	1.4	614	—	**314MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	146700	175900	67300
2.4	39700	2.4	623	—	**315MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	147000	176300	67700
2.4	39700	2.9	623	—	**316MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	225000	252400	112800
2.5	36600	1.8	575	**314ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	145300	174300	65900
2.5	37500	1.9	588	**314ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	145800	174900	66400
2.5	37700	2.5	591	**315ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	145900	175000	66500
2.6	36200	1.1	568	**311ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	107700	109900	47400
2.6	35900	1.5	564	**313ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	155900	182700	58200
2.7	34100	1.4	535	—	**313MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	154700	181300	57200
2.7	34000	2.8	533	**315ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	143800	172400	64300
2.8	33100	1.2	520	—	**311MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	106400	108500	46000
2.8	33700	2.0	528	—	**314MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	143600	172200	64000
2.8	33500	2.8	525	—	**315MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	143500	172100	63900
2.9	32600	1.4	512	**311ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	106100	108300	45800
2.9	32700	1.5	514	**313ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	153900	180300	56400
3.0	31200	1.0	490	—	**311MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	105500	107600	45100
3.0	31600	1.5	496	—	**313MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	153100	179400	55800
3.0	31500	2.4	495	**314ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	142200	170600	62700
3.2	28900	1.0	453	**310ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	83000	105300	44000
3.2	28800	2.0	452	**313ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	151100	177000	54000
3.2	29200	2.6	458	**314ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	140700	168700	61100
3.3	27900	1.4	438	—	**311MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	103800	105900	43500
3.3	28700	1.6	450	—	**313MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	151000	176900	54000
3.3	28400	2.1	445	—	**314MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	140100	168000	60500
3.5	26300	1.5	413	—	**311MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	102900	105000	42600
3.5	26800	2.6	421	—	**314MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	139000	166700	59400
3.6	26200	1.8	410	**311ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	102800	104900	42500
3.7	25100	2.2	394	**313ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	148100	173600	51600
3.7	25100	3.0	394	**314ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	137700	165100	58100
3.8	24400	1.0	383	—	**310MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	81000	102700	41600
3.8	24700	1.8	387	—	**313MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	147800	173200	51400
4.1	22600	2.6	354	—	**314MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	135600	162700	56100
4.2	22200	1.0	349	**309L4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	70700	91000	22300
4.2	22100	1.3	347	—	**310MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	79900	101300	40200
4.2	22200	2.1	348	**311ML4**	—	**BE160M4**	**BX160MB4**	—	—	—	—	100400	102500	40200
4.2	22000	2.5	346	—	**313MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	145400	170400	49400
4.3	21700	1.7	341	—	**311MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	100200	102200	40000



P_1 = 11 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
4.7	19700	2.2	309	—	**313MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	143100	167600	47600
4.8	19400	1.2	305	—	**310MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	78400	99500	38500
4.8	20000	1.5	304	**313ML3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	142700	167300	47300
5.0	19400	1.2	295	**310ML3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	78100	99000	38100
5.0	19100	1.4	291	**311ML3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	98000	100000	37900
5.0	18700	2.0	294	—	**311MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	98000	100000	38000
5.1	18100	0.9	284	—	**309R4**	**BE160M4**	**BX160MB4**	—	—	—	—	69000	88800	20800
5.2	17900	2.6	281	—	**313MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	142000	166400	46100
5.3	17600	1.6	276	—	**310MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	78000	98900	37300
5.3	17600	2.6	276	—	**314MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	132000	158300	51600
5.5	16900	2.6	266	—	**311MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	98000	100000	36800
5.7	16400	1.1	258	—	**309R4**	**BE160M4**	**BX160MB4**	—	—	—	—	69000	88800	20200
5.7	16500	1.4	258	—	**310MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	78000	98900	36400
5.8	16600	2.6	252	**313ML3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	142000	166400	44500
5.9	16400	1.1	249	**310ML3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	78000	98900	36000
6.0	16100	2.2	245	**311ML3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	98000	100000	35800
6.2	15100	1.9	238	—	**310MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	78000	98900	35400
6.2	15100	2.6	237	—	**313MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	142000	166400	43600
6.2	15100	2.6	238	—	**314MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	132000	158300	49100
6.3	14800	1.1	232	—	**309R4**	**BE160M4**	**BX160MB4**	—	—	—	—	69000	88800	19500
6.4	15100	1.3	230	**310ML3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	78000	98900	35100
6.4	14600	2.6	229	—	**311MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	98000	100000	35000
7.1	13100	1.1	206	—	**307R4**	**BE160M4**	**BX160MB4**	—	—	30000	37500	67500	88800	23400
7.1	13100	1.5	206	—	**309R4**	**BE160M4**	**BX160MB4**	—	—	—	—	69000	88800	18700
7.1	13100	1.7	206	—	**310MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	78000	98900	33800
7.2	13300	2.7	203	**311ML3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	98000	100000	33600
7.3	13200	1.2	202	**309L3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	69000	88800	18600
7.3	13300	1.7	202	**310ML3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	78000	98900	33600
7.3	12800	2.6	201	—	**313MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	142000	166400	41200
7.4	12600	2.6	198	—	**311MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	98000	100000	33400
7.7	12200	1.2	191	—	**307R4**	**BE160M4**	**BX160MB4**	—	—	30000	37500	67500	88800	22800
7.7	12200	1.4	191	—	**309R4**	**BE160M4**	**BX160MB4**	—	—	—	—	69000	88800	18200
7.7	12100	2.3	189	—	**310MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	78000	98900	32900
7.7	12600	2.5	191	**311ML3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	98000	100000	33000
7.7	12100	2.6	189	—	**314MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	132000	158300	45500
7.9	11800	2.6	185	—	**313MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	142000	166400	40100
8.0	12000	1.2	183	**309L3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	69000	88800	18000
8.0	11600	2.6	182	—	**311MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	98000	100000	32400
8.0	12000	2.5	182	**313ML3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	142000	166400	39900
8.3	11600	1.1	177	**307L3**	—	**BE160M4**	**BX160MB4**	—	—	30000	37500	67500	88800	22200
8.3	11600	1.5	177	**310ML3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	78000	98900	32100
8.9	10500	1.0	165	—	**307R4**	**BE160M4**	**BX160MB4**	—	—	30000	37500	67500	88800	21700
8.9	10500	1.5	165	—	**309R4**	**BE160M4**	**BX160MB4**	—	—	—	—	69000	88800	17400
9.0	10800	2.5	164	**310ML3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	78000	98900	31300
9.1	10600	1.0	162	**307L3**	—	**BE160M4**	**BX160MB4**	—	—	30000	37500	67500	88800	21600
9.1	10600	1.5	162	**309L3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	69000	88800	17300
9.1	10200	2.6	160	—	**310MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	78000	98900	31100
9.1	10200	2.6	160	—	**314MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	132000	158300	43100
9.3	10100	1.0	158	—	**306R4**	**BE160M4**	**BX160MB4**	—	—	25000	28500	57000	65800	16700



P_1 = 11 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N]				
min^{-1}	Nm									MC	MZ	HC/PC	HZ/PZ	FZ
9.5	9840	2.6	154	—	**311MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	98000	100000	30700
9.6	9690	1.4	152	—	**307R4**	**BE160M4**	**BX160MB4**	—	—	30000	37500	67500	88800	21100
9.6	9690	1.9	152	—	**309R4**	**BE160M4**	**BX160MB4**	—	—	—	—	69000	88800	16900
9.8	9810	2.2	149	**310ML3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	78000	98900	30400
10.0	9620	1.4	146	**307L3**	—	**BE160M4**	**BX160MB4**	—	—	30000	37500	67500	88800	20900
10.0	9640	2.8	147	—	**311MR3**	**BE160M4**	**BX160MB4**	—	—	—	—	98000	100000	30200
10.6	9120	1.2	139	**307L3**	—	**BE160M4**	**BX160MB4**	—	—	29500	36800	66400	87400	20500
10.6	9120	1.8	139	**309L3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	67900	87400	16400
10.8	8890	2.9	135	**310ML3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	76200	96600	29400
10.8	8660	2.6	136	—	**310MR4**	**BE160M4**	**BX160MB4**	—	—	—	—	76300	96700	29400
11.6	8270	1.6	126	**307L3**	—	**BE160M4**	**BX160MB4**	—	—	28500	35700	64500	84800	19900
11.6	8270	2.0	126	**309L3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	65900	84800	15900
12.1	7970	1.0	121	**306L3**	—	**BE160M4**	**BX160MB4**	—	—	23500	26800	53900	62200	15300
12.2	7870	1.1	120	—	**307R3**	**BE160M4**	**BX160MB4**	—	—	28000	35100	63500	83600	19500
12.2	7870	1.6	120	—	**309R3**	**BE160M4**	**BX160MB4**	—	—	—	—	64900	83600	15600
12.2	7870	2.2	120	—	**310MR3**	**BE160M4**	**BX160MB4**	—	—	—	—	73400	93100	28200
12.3	7820	2.8	119	**310ML3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	73300	92900	28200
12.9	7440	1.4	113	**307L3**	—	**BE160M4**	**BX160MB4**	—	—	27500	34400	62500	82200	19200
12.9	7440	2.1	113	**309L3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	63900	82200	15300
13.0	7380	1.0	112	**306L3**	—	**BE160M4**	**BX160MB4**	—	—	22900	26100	52600	60800	14900
14.1	6850	1.3	104	**306L3**	—	**BE160M4**	**BX160MB4**	—	—	22300	25400	51500	59400	14500
14.6	6590	1.9	100	**307L3**	—	**BE160M4**	**BX160MB4**	—	—	26400	33100	60200	79300	18400
14.6	6590	2.5	100	**309L3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	61600	79300	14700
14.8	6500	1.3	99.0	—	**307R3**	**BE160M4**	**BX160MB4**	—	—	26300	32900	60000	78900	18300
14.8	6500	2.0	99.0	—	**309R3**	**BE160M4**	**BX160MB4**	—	—	—	—	61300	78900	14700
14.8	6500	2.5	99.0	—	**310MR3**	**BE160M4**	**BX160MB4**	—	—	—	—	69300	87900	26500
14.9	6470	1.0	98.5	—	**306R3**	**BE160M4**	**BX160MB4**	—	—	21900	25000	50600	58400	14200
15.8	6110	2.0	93.0	**307L3**	—	**BE160M4**	**BX160MB4**	—	—	25800	32200	58900	77500	18000
15.8	6110	2.5	93.0	**309L3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	60200	77500	14400
16.6	5800	1.5	88.3	**306L3**	—	**BE160M4**	**BX160MB4**	—	—	21100	24100	49000	56500	13700
17.3	5570	1.4	84.7	—	**306R3**	**BE160M4**	**BX160MB4**	—	—	20800	23700	48400	55800	13500
17.6	5480	1.9	83.4	—	**307R3**	**BE160M4**	**BX160MB4**	—	—	24900	31100	57000	75000	17300
17.6	5480	2.6	83.4	—	**309R3**	**BE160M4**	**BX160MB4**	—	—	—	—	58300	75000	13800
17.6	5480	2.6	83.4	—	**310MR3**	**BE160M4**	**BX160MB4**	—	—	—	—	65900	83500	25000
17.9	5380	1.3	81.9	**306L3**	—	**BE160M4**	**BX160MB4**	—	—	20600	23500	47900	55300	13400
18.2	5290	1.9	80.6	**307L3**	—	**BE160M4**	**BX160MB4**	—	—	24600	30700	56400	74200	17100
18.2	5290	2.8	80.6	**309L3**	—	**BE160M4**	**BX160MB4**	—	—	—	—	57700	74200	13700
18.6	5170	2.2	78.6	—	**307R3**	**BE160M4**	**BX160MB4**	—	—	24400	30500	56000	73700	17000
18.6	5170	2.6	78.6	—	**310MR3**	**BE160M4**	**BX160MB4**	—	—	—	—	64700	82100	24500
19.0	5080	1.0	77.2	**305L3**	—	**BE160M4**	**BX160MB4**	—	—	17000	19400	33400	39600	9000
19.0	5060	1.7	77.0	**306L3**	—	**BE160M4**	**BX160MB4**	—	—	20200	23000	47000	54300	13100
19.8	4870	2.4	74.1	**307L3**	—	**BE160M4**	**BX160MB4**	—	—	23900	29900	55000	72400	16600
20.1	4790	1.6	72.9	—	**306R3**	**BE160M4**	**BX160MB4**	—	—	19800	22600	46200	53400	12900
20.2	4910	1.1	72.5	**306L2**	—	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	19800	22500	46200	53300	12800
20.4	4710	2.1	71.8	—	**307R3**	**BE160M4**	**BX160MB4**	—	—	23600	29600	54500	71700	16500
20.4	4710	2.7	71.8	—	**309R3**	**BE160M4**	**BX160MB4**	—	—	—	—	55700	71700	13200
20.4	4710	2.6	71.8	—	**310MR3**	**BE160M4**	**BX160MB4**	—	—	—	—	63000	79800	23800
21.7	4440	1.6	67.5	—	**306R3**	**BE160M4**	**BX160MB4**	—	—	19300	22000	45200	52200	12500
22.5	4290	1.8	65.2	**306L3**	—	**BE160M4**	**BX160MB4**	—	—	19100	21800	44700	51600	12400



P_1 = 11 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
22.5	4270	2.6	65.0	—	**307R3**	**BE160M4**	**BX160MB4**	—	—	22900	28600	52900	69600	15900
22.5	4270	2.6	65.0	—	**309R3**	**BE160M4**	**BX160MB4**	—	—	—	—	54100	69600	12700
22.5	4270	2.6	65.0	—	**310MR3**	**BE160M4**	**BX160MB4**	—	—	—	—	61100	77500	23000
23.2	4140	1.1	63.1	**305L3**	—	**BE160M4**	**BX160MB4**	—	—	15900	18100	31400	37300	8410
24.2	3980	2.8	60.5	**307L3**	—	**BE160M4**	**BX160MB4**	—	—	22300	27900	51800	68100	15600
25.2	3820	2.0	58.1	—	**306R3**	**BE160M4**	**BX160MB4**	—	—	18400	20900	43200	49900	11900
26.0	3810	1.4	56.3	**306L2**	—	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	18200	20700	42800	49400	11800
26.2	3670	2.7	55.9	—	**307R3**	**BE160M4**	**BX160MB4**	—	—	21800	27200	50600	66500	15200
26.2	3670	2.7	55.9	—	**309R3**	**BE160M4**	**BX160MB4**	—	—	—	—	51700	66500	12100
26.2	3670	2.6	55.9	—	**310MR3**	**BE160M4**	**BX160MB4**	—	—	—	—	58400	74100	21900
26.3	3780	0.9	55.8	**305L2**	—	**BE160M4**	**BX160MB4**	—	—	15200	17400	30300	35900	8080
27.4	3510	0.9	53.4	**304L3**	—	**BE160M4**	**BX160MB4**	—	—	15000	17100	29900	35500	7960
27.4	3510	1.1	53.4	**305L3**	—	**BE160M4**	**BX160MB4**	—	—	15000	17100	29900	35500	7960
27.5	3500	2.0	53.2	**306L3**	—	**BE160M4**	**BX160MB4**	—	—	17800	20300	42100	48600	11600
31	3170	2.6	46.7	**307L2**	—	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	20500	25600	47900	63000	14300
32	3150	2.1	46.5	**306L2**	—	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	17100	19400	40400	46600	11100
32	3040	2.5	46.3	—	**306R3**	**BE160M4**	**BX160MB4**	—	—	17000	19400	40300	46600	11100
33	3020	1.2	44.6	**305L2**	—	**BE160M4**	**BX160MB4**	—	—	14100	16200	28400	33600	7500
33	2930	2.7	44.6	—	**307R3**	**BE160M4**	**BX160MB4**	—	—	20200	25200	47200	62100	14000
33	2930	2.7	44.6	—	**309R3**	**BE160M4**	**BX160MB4**	—	—	—	—	48300	62100	11200
33	2930	2.6	44.6	—	**310MR3**	**BE160M4**	**BX160MB4**	—	—	—	—	54600	69200	20300
34	2860	1.1	43.6	**304L3**	—	**BE160M4**	**BX160MB4**	—	—	14000	16000	28200	33400	7440
37	2580	2.6	39.2	—	**306R3**	**BE160M4**	**BX160MB4**	—	—	16100	18400	38400	44300	10500
38	2600	1.1	38.4	**304L2**	—	**BE160M4**	**BX160MB4**	—	—	13400	15400	27100	32100	7130
38	2600	1.7	38.4	**305L2**	—	**BE160M4**	**BX160MB4**	—	—	13400	15400	27100	32100	7130
38	2600	2.5	38.4	**306L2**	—	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	16000	18200	38200	44000	10400
39	2480	2.7	37.7	—	**307R3**	**BE160M4**	**BX160MB4**	—	—	19100	23900	44900	59100	13300
39	2480	2.7	37.7	—	**309R3**	**BE160M4**	**BX160MB4**	—	—	—	—	45900	59100	10600
39	2480	2.6	37.7	—	**310MR3**	**BE160M4**	**BX160MB4**	—	—	—	—	51900	65800	19200
41	2420	1.5	35.8	**305L2**	—	**BE160M4**	**BX160MB4**	—	—	13100	15000	26500	31400	6960
44	2180	2.7	33.2	—	**306R3**	**BE160M4**	**BX160MB4**	—	—	15200	17400	36500	42200	9910
46	2080	2.7	31.6	—	**307R3**	**BE160M4**	**BX160MB4**	—	—	18000	22500	42600	56100	12500
46	2080	2.7	31.6	—	**309R3**	**BE160M4**	**BX160MB4**	—	—	—	—	43600	56100	10000
48	2080	1.0	30.8	**303L2**	—	**BE160M4**	**BX160MB4**	—	—	12500	14300	25400	30100	6620
48	2080	1.4	30.8	**304L2**	—	**BE160M4**	**BX160MB4**	—	—	12500	14300	25400	30100	6620
48	2080	2.1	30.8	**305L2**	—	**BE160M4**	**BX160MB4**	—	—	12500	14300	25400	30100	6620
55	1790	1.0	26.4	**303L2**	—	**BE160M4**	**BX160MB4**	—	—	11900	13600	24200	28700	6290
55	1790	2.0	26.4	**305L2**	—	**BE160M4**	**BX160MB4**	—	—	11900	13600	24200	28700	6290
60	1660	1.3	24.5	**303L2**	—	**BE160M4**	**BX160MB4**	—	—	11600	13200	23700	28100	6140
60	1660	2.0	24.5	**304L2**	—	**BE160M4**	**BX160MB4**	—	—	11600	13200	23700	28100	6140
60	1660	2.3	24.5	**305L2**	—	**BE160M4**	**BX160MB4**	—	—	11600	13200	23700	28100	6140
64	1540	1.4	22.7	**303L2**	—	**BE160M4**	**BX160MB4**	—	—	11300	12900	23200	27400	5990
64	1540	1.8	22.7	**304L2**	—	**BE160M4**	**BX160MB4**	—	—	11300	12900	23200	27400	5990
64	1540	2.6	22.7	**305L2**	—	**BE160M4**	**BX160MB4**	—	—	11300	12900	23200	27400	5990
71	1410	1.3	20.8	**303L2**	—	**BE160M4**	**BX160MB4**	—	—	10900	12500	22500	26700	5810
71	1410	2.1	20.8	**304L2**	—	**BE160M4**	**BX160MB4**	—	—	10900	12500	22500	26700	5810
71	1410	2.3	20.8	**305L2**	—	**BE160M4**	**BX160MB4**	—	—	10900	12500	22500	26700	5810
76	1300	2.7	19.2	—	**306R2**	**BE160M4**	**BX160MB4**	—	—	12700	14500	31000	35800	8250
81	1230	1.7	18.1	**303L2**	—	**BE160M4**	**BX160MB4**	—	—	10500	12000	21600	25600	5550



P_1 = 11 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
81	1230	2.4	18.1	**304L2**	—	**BE160M4**	**BX160MB4**	—	—	10500	12000	21600	25600	5550
81	1230	3.0	18.1	**305L2**	—	**BE160M4**	**BX160MB4**	—	—	10500	12000	21600	25600	5550
92	1080	2.7	15.9	—	**306R2**	**BE160M4**	**BX160MB4**	—	—	11900	13600	29300	33800	7750
95	1040	1.7	15.3	**303L2**	—	**BE160M4**	**BX160MB4**	—	—	9900	11300	20600	24400	5250
95	1040	2.7	15.3	**304L2**	—	**BE160M4**	**BX160MB4**	—	—	9900	11300	20600	24400	5250
95	1040	3.0	15.3	**305L2**	—	**BE160M4**	**BX160MB4**	—	—	9900	11300	20600	24400	5250
107	930	2.7	13.7	—	**306R2**	**BE160M4**	**BX160MB4**	—	—	11300	12900	28000	32300	7370
117	850	1.9	12.5	**303L2**	—	**BE160M4**	**BX160MB4**	—	—	9250	10600	19400	23000	4910
135	740	2.7	10.9	—	**306R2**	**BE160M4**	**BX160MB4**	—	—	10500	12000	26100	30200	6830
152	680	1.1	9.67	**303L1**	—	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	8490	9700	17900	21200	4500
159	620	2.7	9.23	—	**306R2**	**BE160M4**	**BX160MB4**	—	—	9950	11300	24900	28700	6460
195	520	2.3	7.50	**303L1**	—	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	7800	8910	16600	19700	4140

P_1 = 15 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
0.77	164200	0.9	1893	**317ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	410300	435900	150000
0.92	138400	1.1	1595	**317ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	400400	425300	150000
0.94	134700	0.9	1553	**316ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	256300	287600	150000
1.1	113500	1.1	1308	**316ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	250100	280600	144500
1.1	114400	1.4	1318	**317ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	389600	413900	144800
1.2	107400	1.1	1237	**316ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	248200	278400	141800
1.3	95800	0.9	1104	**315ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	159500	191300	81900
1.3	95800	1.2	1104	**316ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	244200	273900	136500
1.3	98400	1.6	1134	**317ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	381300	405100	137700
1.4	90500	1.1	1043	**315ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	158200	189800	80400
1.4	88500	1.3	1020	**316ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	241400	270800	132900
1.4	89600	2.0	1032	**317ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	376300	399700	133500
1.5	82700	1.7	953	—	**317MR4**	**BE160L4**	**BX160L4**	—	—	—	—	372000	395200	130000
1.6	80700	1.1	930	**315ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	155700	186700	77400
1.6	78900	0.9	909	—	**315MR4**	**BE160L4**	**BX160L4**	—	—	—	—	155200	186100	76800
1.6	78400	2.0	904	**317ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	369200	392200	127700
1.7	74400	1.0	858	**314ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	153900	184600	75300
1.7	74800	1.3	862	**315ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	154000	184700	75400
1.7	76300	1.5	880	**316ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	236400	265100	126600
1.8	68700	2.8	792	**317ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	362300	384900	122200
1.8	69700	2.2	803	—	**317MR4**	**BE160L4**	**BX160L4**	—	—	—	—	363000	385600	122800
1.9	67900	1.3	782	—	**315MR4**	**BE160L4**	**BX160L4**	—	—	—	—	151900	182100	73000
1.9	68000	1.7	784	**316ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	232500	260800	121800
1.9	67900	1.7	782	—	**316MR4**	**BE160L4**	**BX160L4**	—	—	—	—	232400	260700	121700
2.0	64000	1.2	738	**314ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	150600	180600	71600
2.0	64300	1.5	741	**315ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	150700	180800	71700
2.0	62400	2.7	719	**317ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	357300	379600	118300
2.1	61300	1.9	706	**316ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	229100	257000	117600
2.2	58000	1.3	668	**314ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	148500	178100	69300
2.2	58300	1.6	672	**315ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	148600	178200	69400
2.2	57200	1.5	659	—	**315MR4**	**BE160L4**	**BX160L4**	—	—	—	—	148200	177700	69000

A



P_1 = 15 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
2.2	57200	2.0	659	—	**316MR4**	**BE160L4**	**BX160L4**	—	—	—	—	226800	254400	114900
2.2	58700	2.7	677	—	**317MR4**	**BE160L4**	**BX160L4**	—	—	—	—	354200	376300	116000
2.3	54500	2.1	628	**316ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	225200	252700	113100
2.3	54300	2.2	626	—	**317MR4**	**BE160L4**	**BX160L4**	—	—	—	—	350300	372100	113000
2.4	53200	1.0	614	—	**314MR4**	**BE160L4**	**BX160L4**	—	—	—	—	146700	175900	67300
2.4	54100	1.8	623	—	**315MR4**	**BE160L4**	**BX160L4**	—	—	—	—	147000	176300	67700
2.4	54100	2.1	623	—	**316MR4**	**BE160L4**	**BX160L4**	—	—	—	—	225000	252400	112800
2.5	49900	1.4	575	**314ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	145300	174300	65900
2.5	51000	1.4	588	**314ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	145800	174900	66400
2.5	51300	1.8	591	**315ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	145900	175000	66500
2.6	48900	1.1	564	**313ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	155900	182700	58200
2.6	48800	2.3	563	**316ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	221700	248800	109000
2.7	46400	1.0	535	—	**313MR4**	**BE160L4**	**BX160L4**	—	—	—	—	154700	181300	57200
2.7	46300	2.0	533	**315ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	143800	172400	64300
2.8	45800	1.4	528	—	**314MR4**	**BE160L4**	**BX160L4**	—	—	—	—	143600	172200	64000
2.8	45600	2.1	525	—	**315MR4**	**BE160L4**	**BX160L4**	—	—	—	—	143500	172100	63900
2.8	45600	2.8	525	—	**316MR4**	**BE160L4**	**BX160L4**	—	—	—	—	219600	246300	106600
2.9	44400	1.0	512	**311ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	106100	108300	45800
2.9	44600	1.1	514	**313ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	153900	180300	56400
2.9	43400	2.9	500	**316ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	218100	244600	104900
3.0	43000	1.1	496	—	**313MR4**	**BE160L4**	**BX160L4**	—	—	—	—	153100	179400	55800
3.0	42900	1.8	495	**314ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	142200	170600	62700
3.0	42200	2.2	487	**315ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	141900	170200	62300
3.2	39200	1.5	452	**313ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	151100	177000	54000
3.2	39700	1.9	458	**314ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	140700	168700	61100
3.3	38000	1.0	438	—	**311MR4**	**BE160L4**	**BX160L4**	—	—	—	—	103800	105900	43500
3.3	39100	1.2	450	—	**313MR4**	**BE160L4**	**BX160L4**	—	—	—	—	151000	176900	54000
3.3	38600	1.5	445	—	**314MR4**	**BE160L4**	**BX160L4**	—	—	—	—	140100	168000	60500
3.3	38300	2.5	441	**315ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	139900	167800	60300
3.4	37300	2.8	430	—	**316MR4**	**BE160L4**	**BX160L4**	—	—	—	—	213400	239400	99700
3.5	35800	1.1	413	—	**311MR4**	**BE160L4**	**BX160L4**	—	—	—	—	102900	105000	42600
3.5	36500	1.9	421	—	**314MR4**	**BE160L4**	**BX160L4**	—	—	—	—	139000	166700	59400
3.6	35600	1.3	410	**311ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	102800	104900	42500
3.6	35500	2.7	409	—	**315MR4**	**BE160L4**	**BX160L4**	—	—	—	—	138500	166000	58800
3.7	34200	1.7	394	**313ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	148100	173600	51600
3.7	34200	2.2	394	**314ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	137700	165100	58100
3.8	33600	1.3	387	—	**313MR4**	**BE160L4**	**BX160L4**	—	—	—	—	147800	173200	51400
4.0	32100	3.0	370	**315ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	136500	163600	56900
4.1	30800	1.9	354	—	**314MR4**	**BE160L4**	**BX160L4**	—	—	—	—	135600	162700	56100
4.2	30100	1.0	347	—	**310MR4**	**BE160L4**	**BX160L4**	—	—	—	—	79900	101300	40200
4.2	30200	1.5	348	**311ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	100400	102500	40200
4.2	30000	1.9	346	—	**313MR4**	**BE160L4**	**BX160L4**	—	—	—	—	145400	170400	49400
4.3	29600	1.3	341	—	**311MR4**	**BE160L4**	**BX160L4**	—	—	—	—	100200	102200	40000
4.7	26800	1.6	309	—	**313MR4**	**BE160L4**	**BX160L4**	—	—	—	—	143100	167600	47600
4.7	27200	2.8	314	**314ML4**	—	**BE160L4**	**BX160L4**	—	—	—	—	133300	159900	53900
4.8	27200	1.1	304	**313ML3**	—	**BE160L4**	**BX160L4**	—	—	—	—	142700	167300	47300
5.0	26000	1.1	291	**311ML3**	—	**BE160L4**	**BX160L4**	—	—	—	—	98000	100000	37900
5.0	25500	1.4	294	—	**311MR4**	**BE160L4**	**BX160L4**	—	—	—	—	98000	100000	38000
5.2	24400	1.9	281	—	**313MR4**	**BE160L4**	**BX160L4**	—	—	—	—	142000	166400	46100



P_1 = 15 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
5.3	24000	1.2	276	—	**310MR4**	**BE160L4**	**BX160L4**	—	—	—	—	78000	98900	37300
5.3	24000	1.9	276	—	**314MR4**	**BE160L4**	**BX160L4**	—	—	—	—	132000	158300	51600
5.5	23100	1.9	266	—	**311MR4**	**BE160L4**	**BX160L4**	—	—	—	—	98000	100000	36800
5.7	22400	1.0	258	—	**310MR4**	**BE160L4**	**BX160L4**	—	—	—	—	78000	98900	36400
5.8	22600	1.9	252	**313ML3**	—	**BE160L4**	**BX160L4**	—	—	—	—	142000	166400	44500
6.0	21900	1.7	245	**311ML3**	—	**BE160L4**	**BX160L4**	—	—	—	—	98000	100000	35800
6.1	21400	2.2	240	**314ML3**	—	**BE160L4**	**BX160L4**	—	—	—	—	132000	158300	49200
6.2	20600	1.4	238	—	**310MR4**	**BE160L4**	**BX160L4**	—	—	—	—	78000	98900	35400
6.2	20600	1.9	237	—	**313MR4**	**BE160L4**	**BX160L4**	—	—	—	—	142000	166400	43600
6.2	20600	1.9	238	—	**314MR4**	**BE160L4**	**BX160L4**	—	—	—	—	132000	158300	49100
6.4	20600	0.9	230	**310ML3**	—	**BE160L4**	**BX160L4**	—	—	—	—	78000	98900	35100
6.4	19800	1.9	229	—	**311MR4**	**BE160L4**	**BX160L4**	—	—	—	—	98000	100000	35000
7.0	18700	2.3	209	**313ML3**	—	**BE160L4**	**BX160L4**	—	—	—	—	142000	166400	41800
7.1	17800	1.1	206	—	**309R4**	**BE160L4**	**BX160L4**	—	—	—	—	69000	88800	18700
7.1	17900	1.2	206	—	**310MR4**	**BE160L4**	**BX160L4**	—	—	—	—	78000	98900	33800
7.2	18100	2.0	203	**311ML3**	—	**BE160L4**	**BX160L4**	—	—	—	—	98000	100000	33600
7.3	18000	0.9	202	**309L3**	—	**BE160L4**	**BX160L4**	—	—	—	—	69000	88800	18600
7.3	18100	1.2	202	**310ML3**	—	**BE160L4**	**BX160L4**	—	—	—	—	78000	98900	33600
7.3	17400	1.9	201	—	**313MR4**	**BE160L4**	**BX160L4**	—	—	—	—	142000	166400	41200
7.4	17200	1.9	198	—	**311MR4**	**BE160L4**	**BX160L4**	—	—	—	—	98000	100000	33400
7.6	17300	2.8	194	**313ML3**	—	**BE160L4**	**BX160L4**	—	—	—	—	142000	166400	40700
7.7	16500	1.0	191	—	**309R4**	**BE160L4**	**BX160L4**	—	—	—	—	69000	88800	18200
7.7	16400	1.7	189	—	**310MR4**	**BE160L4**	**BX160L4**	—	—	—	—	78000	98900	32900
7.7	17100	1.9	191	**311ML3**	—	**BE160L4**	**BX160L4**	—	—	—	—	98000	100000	33000
7.7	16400	1.9	189	—	**314MR4**	**BE160L4**	**BX160L4**	—	—	—	—	132000	158300	45500
7.9	16000	1.9	185	—	**313MR4**	**BE160L4**	**BX160L4**	—	—	—	—	142000	166400	40100
8.0	15800	1.9	182	—	**311MR4**	**BE160L4**	**BX160L4**	—	—	—	—	98000	100000	32400
8.0	16300	1.9	182	**313ML3**	—	**BE160L4**	**BX160L4**	—	—	—	—	142000	166400	39900
8.3	15900	1.1	177	**310ML3**	—	**BE160L4**	**BX160L4**	—	—	—	—	78000	98900	32100
8.3	15700	2.7	176	**313ML3**	—	**BE160L4**	**BX160L4**	—	—	—	—	142000	166400	39500
8.6	15300	2.3	171	**311ML3**	—	**BE160L4**	**BX160L4**	—	—	—	—	98000	100000	31800
8.9	14300	1.1	165	—	**309R4**	**BE160L4**	**BX160L4**	—	—	—	—	69000	88800	17400
9.0	14600	1.8	164	**310ML3**	—	**BE160L4**	**BX160L4**	—	—	—	—	78000	98900	31300
9.1	14400	1.1	162	**309L3**	—	**BE160L4**	**BX160L4**	—	—	—	—	69000	88800	17300
9.1	13900	1.9	160	—	**310MR4**	**BE160L4**	**BX160L4**	—	—	—	—	78000	98900	31100
9.1	14400	2.4	161	**311ML3**	—	**BE160L4**	**BX160L4**	—	—	—	—	98000	100000	31100
9.1	13900	1.9	160	—	**314MR4**	**BE160L4**	**BX160L4**	—	—	—	—	132000	158300	43100
9.5	13400	1.9	154	—	**311MR4**	**BE160L4**	**BX160L4**	—	—	—	—	98000	100000	30700
9.6	13200	1.0	152	—	**307R4**	**BE160L4**	**BX160L4**	—	—	30000	37500	67500	88800	21100
9.6	13200	1.4	152	—	**309R4**	**BE160L4**	**BX160L4**	—	—	—	—	69000	88800	16900
9.6	13700	2.2	153	—	**313MR3**	**BE160L4**	**BX160L4**	—	—	—	—	142000	166400	37700
9.8	13400	1.6	149	**310ML3**	—	**BE160L4**	**BX160L4**	—	—	—	—	78000	98900	30400
10.0	13100	1.0	146	**307L3**	—	**BE160L4**	**BX160L4**	—	—	30000	37500	67500	88800	20900
10.0	13100	2.7	147	**311ML3**	—	**BE160L4**	**BX160L4**	—	—	—	—	98000	100000	30200
10.0	13100	2.1	147	—	**311MR3**	**BE160L4**	**BX160L4**	—	—	—	—	98000	100000	30200
10.6	12400	1.3	139	**309L3**	—	**BE160L4**	**BX160L4**	—	—	—	—	67900	87400	16400
10.8	12100	2.1	135	**310ML3**	—	**BE160L4**	**BX160L4**	—	—	—	—	76200	96600	29400
10.8	11800	1.9	136	—	**310MR4**	**BE160L4**	**BX160L4**	—	—	—	—	76300	96700	29400



P_1 = 15 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
11.0	11900	2.9	133	**311ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	95200	100000	29200
11.6	11300	1.2	126	**307L3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	28500	35700	64500	84800	19900
11.6	11300	1.5	126	**309L3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	65900	84800	15900
12.2	10700	1.2	120	**—**	**309R3**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	64900	83600	15600
12.2	10700	1.6	120	**—**	**310MR3**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	73400	93100	28200
12.3	10600	2.0	119	**310ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	73300	92900	28200
12.9	10100	1.0	113	**307L3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	27500	34400	62500	82200	19200
12.9	10100	1.5	113	**309L3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	63900	82200	15300
13.6	9640	2.5	108	**310ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	71100	90200	27200
14.1	9320	1.0	104	**306L3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	22300	25400	51500	59400	14500
14.5	9020	2.3	101	**310ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	69700	88400	26600
14.6	8970	1.4	100	**307L3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	26400	33100	60200	79300	18400
14.6	8970	1.8	100	**309L3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	61600	79300	14700
14.8	8850	1.0	99.0	**—**	**307R3**	**BE160L4**	**BX160L4**	**—**	**—**	26300	32900	60000	78900	18300
14.8	8850	1.4	99.0	**—**	**309R3**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	61300	78900	14700
14.8	8850	1.8	99.0	**—**	**310MR3**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	69300	87900	26500
15.8	8320	1.5	93.0	**307L3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	25800	32200	58900	77500	18000
15.8	8320	1.8	93.0	**309L3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	60200	77500	14400
15.8	8290	2.8	92.7	**310ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	68000	86200	25900
16.6	7890	1.1	88.3	**306L3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	21100	24100	49000	56500	13700
17.3	7580	1.0	84.7	**—**	**306R3**	**BE160L4**	**BX160L4**	**—**	**—**	20800	23700	48400	55800	13500
17.6	7460	1.4	83.4	**—**	**307R3**	**BE160L4**	**BX160L4**	**—**	**—**	24900	31100	57000	75000	17300
17.6	7460	1.9	83.4	**—**	**309R3**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	58300	75000	13800
17.6	7460	1.9	83.4	**—**	**310MR3**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	65900	83500	25000
17.9	7320	0.9	81.9	**306L3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	20600	23500	47900	55300	13400
18.2	7210	1.4	80.6	**307L3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	24600	30700	56400	74200	17100
18.2	7210	2.1	80.6	**309L3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	57700	74200	13700
18.2	7180	2.9	80.3	**310ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	65100	82600	24700
18.6	7030	1.6	78.6	**—**	**307R3**	**BE160L4**	**BX160L4**	**—**	**—**	24400	30500	56000	73700	17000
18.6	7030	1.9	78.6	**—**	**310MR3**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	64700	82100	24500
19.0	6890	1.2	77.0	**306L3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	20200	23000	47000	54300	13100
19.8	6630	1.8	74.1	**307L3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	23900	29900	55000	72400	16600
19.8	6630	2.3	74.1	**309L3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	56200	72400	13300
20.1	6520	1.1	72.9	**—**	**306R3**	**BE160L4**	**BX160L4**	**—**	**—**	19800	22600	46200	53400	12900
20.4	6420	1.6	71.8	**—**	**307R3**	**BE160L4**	**BX160L4**	**—**	**—**	23600	29600	54500	71700	16500
20.4	6420	2.0	71.8	**—**	**309R3**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	55700	71700	13200
20.4	6420	1.9	71.8	**—**	**310MR3**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	63000	79800	23800
21.7	6040	1.2	67.5	**—**	**306R3**	**BE160L4**	**BX160L4**	**—**	**—**	19300	22000	45200	52200	12500
22.5	5830	1.3	65.2	**306L3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	19100	21800	44700	51600	12400
22.5	5810	1.9	65.0	**—**	**307R3**	**BE160L4**	**BX160L4**	**—**	**—**	22900	28600	52900	69600	15900
22.5	5810	1.9	65.0	**—**	**309R3**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	54100	69600	12700
22.5	5810	1.9	65.0	**—**	**310MR3**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	61100	77500	23000
24.2	5410	2.1	60.5	**307L3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	22300	27900	51800	68100	15600
24.2	5410	2.6	60.5	**309L3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	52900	68100	12400
25.2	5200	1.5	58.1	**—**	**306R3**	**BE160L4**	**BX160L4**	**—**	**—**	18400	20900	43200	49900	11900
26.0	5190	1.0	56.3	**306L2**	**—**	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	18200	20700	42800	49400	11800
26.2	5000	2.0	55.9	**—**	**307R3**	**BE160L4**	**BX160L4**	**—**	**—**	21800	27200	50600	66500	15200
26.2	5000	2.0	55.9	**—**	**309R3**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	51700	66500	12100



P_1 = 15 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
26.2	5000	1.9	55.9	—	**310MR3**	**BE160L4**	**BX160L4**	—	—	—	—	58400	74100	21900
27.5	4760	1.5	53.2	**306L3**	—	**BE160L4**	**BX160L4**	—	—	17800	20300	42100	48600	11600
28.6	4580	2.4	51.3	**307L3**	—	**BE160L4**	**BX160L4**	—	—	21100	26400	49300	64800	14700
28.6	4580	2.9	51.3	**309L3**	—	**BE160L4**	**BX160L4**	—	—	—	—	50400	64800	11800
31	4310	1.9	46.7	**307L2**	—	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	20500	25600	47900	63000	14300
31	4310	2.9	46.7	**309L2**	—	**BE160L4**	**BX160L4**	—	—	—	—	49000	63000	11400
32	4290	1.5	46.5	**306L2**	—	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	17100	19400	40400	46600	11100
32	4140	1.8	46.3	—	**306R3**	**BE160L4**	**BX160L4**	—	—	17000	19400	40300	46600	11100
33	3980	2.0	44.6	—	**307R3**	**BE160L4**	**BX160L4**	—	—	20200	25200	47200	62100	14000
33	3980	2.0	44.6	—	**309R3**	**BE160L4**	**BX160L4**	—	—	—	—	48300	62100	11200
33	3980	1.9	44.6	—	**310MR3**	**BE160L4**	**BX160L4**	—	—	—	—	54600	69200	20300
37	3510	1.9	39.2	—	**306R3**	**BE160L4**	**BX160L4**	—	—	16100	18400	38400	44300	10500
38	3540	1.2	38.4	**305L2**	—	**BE160L4**	**BX160L4**	—	—	13400	15400	27100	32100	7130
38	3540	1.8	38.4	**306L2**	—	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	16000	18200	38200	44000	10400
38	3560	2.3	38.6	**307L2**	—	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	19200	24000	45300	59500	13400
39	3380	2.0	37.7	—	**307R3**	**BE160L4**	**BX160L4**	—	—	19100	23900	44900	59100	13300
39	3380	2.0	37.7	—	**309R3**	**BE160L4**	**BX160L4**	—	—	—	—	45900	59100	10600
39	3380	1.9	37.7	—	**310MR3**	**BE160L4**	**BX160L4**	—	—	—	—	51900	65800	19200
41	3300	1.1	35.8	**305L2**	—	**BE160L4**	**BX160L4**	—	—	13100	15000	26500	31400	6960
44	3050	2.3	33.1	**306L2**	—	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	15200	17400	36500	42100	9890
44	2970	2.0	33.2	—	**306R3**	**BE160L4**	**BX160L4**	—	—	15200	17400	36500	42200	9910
46	2830	2.0	31.6	—	**307R3**	**BE160L4**	**BX160L4**	—	—	18000	22500	42600	56100	12500
46	2830	2.0	31.6	—	**309R3**	**BE160L4**	**BX160L4**	—	—	—	—	43600	56100	10000
48	2840	1.0	30.8	**304L2**	—	**BE160L4**	**BX160L4**	—	—	12500	14300	25400	30100	6620
48	2840	1.5	30.8	**305L2**	—	**BE160L4**	**BX160L4**	—	—	12500	14300	25400	30100	6620
52	2620	2.6	28.4	**306L2**	—	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	14500	16500	34900	40200	9410
55	2440	1.5	26.4	**305L2**	—	**BE160L4**	**BX160L4**	—	—	11900	13600	24200	28700	6290
56	2430	2.6	26.4	**306L2**	—	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	14100	16100	34100	39300	9170
60	2260	1.0	24.5	**303L2**	—	**BE160L4**	**BX160L4**	—	—	11600	13200	23700	28100	6140
60	2260	1.4	24.5	**304L2**	—	**BE160L4**	**BX160L4**	—	—	11600	13200	23700	28100	6140
60	2260	1.7	24.5	**305L2**	—	**BE160L4**	**BX160L4**	—	—	11600	13200	23700	28100	6140
64	2100	1.0	22.7	**303L2**	—	**BE160L4**	**BX160L4**	—	—	11300	12900	23200	27400	5990
64	2100	1.3	22.7	**304L2**	—	**BE160L4**	**BX160L4**	—	—	11300	12900	23200	27400	5990
64	2100	1.9	22.7	**305L2**	—	**BE160L4**	**BX160L4**	—	—	11300	12900	23200	27400	5990
65	2090	3.0	22.7	**306L2**	—	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	13400	15300	32600	37600	8720
71	1920	1.0	20.8	**303L2**	—	**BE160L4**	**BX160L4**	—	—	10900	12500	22500	26700	5810
71	1920	1.6	20.8	**304L2**	—	**BE160L4**	**BX160L4**	—	—	10900	12500	22500	26700	5810
71	1920	1.7	20.8	**305L2**	—	**BE160L4**	**BX160L4**	—	—	10900	12500	22500	26700	5810
76	1770	2.0	19.2	—	**306R2**	**BE160L4**	**BX160L4**	—	—	12700	14500	31000	35800	8250
81	1670	1.2	18.1	**303L2**	—	**BE160L4**	**BX160L4**	—	—	10500	12000	21600	25600	5550
81	1670	1.8	18.1	**304L2**	—	**BE160L4**	**BX160L4**	—	—	10500	12000	21600	25600	5550
81	1670	2.2	18.1	**305L2**	—	**BE160L4**	**BX160L4**	—	—	10500	12000	21600	25600	5550
92	1460	2.0	15.9	—	**306R2**	**BE160L4**	**BX160L4**	—	—	11900	13600	29300	33800	7750
95	1420	1.2	15.3	**303L2**	—	**BE160L4**	**BX160L4**	—	—	9900	11300	20600	24400	5250
95	1420	2.0	15.3	**304L2**	—	**BE160L4**	**BX160L4**	—	—	9900	11300	20600	24400	5250
95	1420	2.2	15.3	**305L2**	—	**BE160L4**	**BX160L4**	—	—	9900	11300	20600	24400	5250
107	1260	2.0	13.7	—	**306R2**	**BE160L4**	**BX160L4**	—	—	11300	12900	28000	32300	7370
117	1160	1.4	12.5	**303L2**	—	**BE160L4**	**BX160L4**	—	—	9250	10600	19400	23000	4910
117	1160	2.3	12.5	**304L2**	—	**BE160L4**	**BX160L4**	—	—	9250	10600	19400	23000	4910

A



A

P_1 = 15 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
117	1160	2.6	12.5	**305L2**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	9250	10600	19400	23000	4910
135	1000	2.0	10.9	**—**	**306R2**	**BE160L4**	**BX160L4**	**—**	**—**	10500	12000	26100	30200	6830
159	850	2.0	9.23	**—**	**306R2**	**BE160L4**	**BX160L4**	**—**	**—**	9950	11300	24900	28700	6460
195	710	1.7	7.50	**303L1**	**—**	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	7800	8910	16600	19700	4140
236	590	2.4	6.20	**303L1**	**—**	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	7320	8360	15700	18600	3880
275	510	3.0	5.33	**303L1**	**—**	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	6960	7950	15000	17800	3690

P_1 = 18.5 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
0.92	170800	0.9	1595	**317ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	400400	425300	150000
1.1	141200	1.1	1318	**317ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	389600	413900	144800
1.1	148800	2.2	1389	**319L4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	453700	499600	196500
1.2	128000	2.7	1195	**319L4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	444100	488900	186800
1.3	118300	1.0	1104	**316ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	244200	273900	136500
1.3	121500	1.3	1134	**317ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	381300	405100	137700
1.4	109200	1.1	1020	**316ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	241400	270800	132900
1.4	110600	1.6	1032	**317ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	376300	399700	133500
1.4	113400	2.3	1059	**318ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	359200	405600	179500
1.5	102100	1.4	953	**—**	**317MR4**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	372000	395200	130000
1.6	96800	1.6	904	**317ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	369200	392200	127700
1.6	97600	2.8	911	**318ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	351600	397000	170700
1.7	92300	1.1	862	**315ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	154000	184700	75400
1.7	94300	1.2	880	**316ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	236400	265100	126600
1.8	84800	2.3	792	**317ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	362300	384900	122200
1.8	86000	1.8	803	**—**	**317MR4**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	363000	385600	122800
1.9	83800	1.0	782	**—**	**315MR4**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	151900	182100	73000
1.9	84000	1.4	784	**316ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	232500	260800	121800
1.9	83800	1.4	782	**—**	**316MR4**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	232400	260700	121700
2.0	79000	0.9	738	**314ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	150600	180600	71600
2.0	79400	1.2	741	**315ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	150700	180800	71700
2.0	77000	2.2	719	**317ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	357300	379600	118300
2.1	75700	1.5	706	**316ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	229100	257000	117600
2.2	71600	1.1	668	**314ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	148500	178100	69300
2.2	71900	1.3	672	**315ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	148600	178200	69400
2.2	70600	1.2	659	**—**	**315MR4**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	148200	177700	69000
2.2	70600	1.6	659	**—**	**316MR4**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	226800	254400	114900
2.2	72500	2.2	677	**—**	**317MR4**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	354200	376300	116000
2.3	67300	1.7	628	**316ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	225200	252700	113100
2.3	67000	1.8	626	**—**	**317MR4**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	350300	372100	113000
2.4	66800	1.4	623	**—**	**315MR4**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	147000	176300	67700
2.4	66800	1.7	623	**—**	**316MR4**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	225000	252400	112800
2.4	66300	2.5	619	**317ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	349700	371500	112500
2.5	61600	1.1	575	**314ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	145300	174300	65900
2.5	63000	1.2	588	**314ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	145800	174900	66400
2.5	63300	1.5	591	**315ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	145900	175000	66500



P_1 = 18.5 kW

n_2	M_2	S	i							Rn_2 [N]				
min^{-1}	Nm					IE2	IE3	IE2	IE3	MC	MZ	HC/PC	HZ/PZ	FZ
2.6	60300	1.9	563	**316ML4**	—	**BE180M4**	**BX180M4**	—	—	—	—	221700	248800	109000
2.7	57100	1.7	533	**315ML4**	—	**BE180M4**	**BX180M4**	—	—	—	—	143800	172400	64300
2.8	56300	1.7	525	—	**315MR4**	**BE180M4**	**BX180M4**	—	—	—	—	143500	172100	63900
2.8	56300	2.2	525	—	**316MR4**	**BE180M4**	**BX180M4**	—	—	—	—	219600	246300	106600
2.8	55700	3.0	520	—	**317MR4**	**BE180M4**	**BX180M4**	—	—	—	—	341100	362400	106200
2.9	53600	2.3	500	**316ML4**	—	**BE180M4**	**BX180M4**	—	—	—	—	218100	244600	104900
3.0	53000	1.4	495	**314ML4**	—	**BE180M4**	**BX180M4**	—	—	—	—	142200	170600	62700
3.0	52100	1.8	487	**315ML4**	—	**BE180M4**	**BX180M4**	—	—	—	—	141900	170200	62300
3.2	49100	1.5	458	**314ML4**	—	**BE180M4**	**BX180M4**	—	—	—	—	140700	168700	61100
3.3	47200	2.0	441	**315ML4**	—	**BE180M4**	**BX180M4**	—	—	—	—	139900	167800	60300
3.3	47900	2.6	447	**316ML4**	—	**BE180M4**	**BX180M4**	—	—	—	—	214600	240700	101000
3.3	47400	2.6	443	—	**316MR4**	**BE180M4**	**BX180M4**	—	—	—	—	214300	240300	100600
3.4	46100	2.3	430	—	**316MR4**	**BE180M4**	**BX180M4**	—	—	—	—	213400	239400	99700
3.6	43800	2.2	409	—	**315MR4**	**BE180M4**	**BX180M4**	—	—	—	—	138500	166000	58800
3.7	42200	1.8	394	**314ML4**	—	**BE180M4**	**BX180M4**	—	—	—	—	137700	165100	58100
3.7	42700	2.4	399	**316ML4**	—	**BE180M4**	**BX180M4**	—	—	—	—	211100	236800	97200
4.0	39600	2.4	370	**315ML4**	—	**BE180M4**	**BX180M4**	—	—	—	—	136500	163600	56900
4.0	38800	2.7	363	—	**316MR4**	**BE180M4**	**BX180M4**	—	—	—	—	208300	233600	94200
4.2	36900	2.6	345	—	**315MR4**	**BE180M4**	**BX180M4**	—	—	—	—	135100	162000	55600
4.2	37000	2.8	346	**316ML4**	—	**BE180M4**	**BX180M4**	—	—	—	—	206800	232000	92700
4.3	36100	2.8	337	—	**316MR4**	**BE180M4**	**BX180M4**	—	—	—	—	206100	231200	91900
4.7	33600	2.2	314	**314ML4**	—	**BE180M4**	**BX180M4**	—	—	—	—	133300	159900	53900
4.8	33500	0.9	304	**313ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	142700	167300	47300
4.8	32400	2.9	302	**315ML4**	—	**BE180M4**	**BX180M4**	—	—	—	—	132600	159000	53200
5.8	27900	1.5	252	**313ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	142000	166400	44500
6.0	27100	1.3	245	**311ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	98000	100000	35800
6.1	26400	1.8	240	**314ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	132000	158300	49200
6.1	26600	2.2	241	**315ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	132000	158300	49300
7.0	23000	1.8	209	**313ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	142000	166400	41800
7.1	22800	2.7	206	**314ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	132000	158300	46800
7.2	22400	1.6	203	**311ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	98000	100000	33600
7.3	22300	1.0	202	**310ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	78000	98900	33600
7.6	21400	2.3	194	**313ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	142000	166400	40700
7.7	21100	1.5	191	**311ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	98000	100000	33000
8.0	20100	1.5	182	**313ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	142000	166400	39900
8.3	19600	0.9	177	**310ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	78000	98900	32100
8.3	19400	2.2	176	**313ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	142000	166400	39500
8.6	18900	1.9	171	**311ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	98000	100000	31800
9.0	18100	1.5	164	**310ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	78000	98900	31300
9.0	18000	2.8	163	**313ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	142000	166400	38500
9.1	17800	2.0	161	**311ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	98000	100000	31100
9.3	17300	2.7	157	—	**314MR3C**	**BE180M4**	**BX180M4**	—	—	—	—	132000	158300	42800
9.6	16900	1.8	153	—	**313MR3**	**BE180M4**	**BX180M4**	—	—	—	—	142000	166400	37700
9.7	16700	2.5	151	**313ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	142000	166400	37500
9.8	16500	1.3	149	**310ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	78000	98900	30400
10.0	16200	2.2	147	**311ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	98000	100000	30200
10.0	16200	1.7	147	—	**311MR3**	**BE180M4**	**BX180M4**	—	—	—	—	98000	100000	30200
10.2	15800	2.6	143	**313ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	141000	165200	36800
10.8	14900	1.7	135	**310ML3**	—	**BE180M4**	**BX180M4**	—	—	—	—	76200	96600	29400

A



A

P_1 = 18.5 kW

n_2 min^{-1}	M_2 Nm	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
11.0	14700	2.4	133	**311ML3**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	95200	100000	29200
11.5	14000	2.9	127	**—**	**313MR3**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	136100	159500	35400
11.9	13600	2.5	124	**—**	**311MR3**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	93100	100000	28500
12.3	13100	1.6	119	**310ML3**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	73300	92900	28200
12.8	12600	2.7	115	**311ML3**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	91000	100000	27800
13.6	11900	2.1	108	**310ML3**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	71100	90200	27200
14.1	11500	2.9	104	**—**	**311MR3**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	88500	100000	26900
14.5	11100	1.9	101	**310ML3**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	69700	88400	26600
15.2	10600	2.8	96.3	**—**	**311MR3**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	86400	100000	26200
15.8	10200	2.3	92.7	**310ML3**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	68000	86200	25900
18.2	8870	2.3	80.3	**310ML3**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	65100	82600	24700
19.8	8160	2.7	73.9	**310ML3**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	63500	80500	24000
23.4	6910	2.9	62.6	**310ML3**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	60400	76600	22700
31	5320	1.6	46.7	**307L2**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	20500	25600	47900	63000	14300
31	5320	2.4	46.7	**309L2**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	49000	63000	11400
32	5290	1.2	46.5	**306L2**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	17100	19400	40400	46600	11100
38	4380	1.5	38.4	**306L2**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	16000	18200	38200	44000	10400
38	4400	1.9	38.6	**307L2**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	19200	24000	45300	59500	13400
38	4400	2.8	38.6	**309L2**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	46300	59500	10700
44	3760	1.8	33.1	**306L2**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	15200	17400	36500	42100	9890
45	3710	2.5	32.6	**307L2**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	18200	22700	43000	56500	12700
48	3490	2.8	30.7	**307L2**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	17800	22300	42200	55600	12400
52	3240	2.1	28.4	**306L2**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	14500	16500	34900	40200	9410
52	3190	2.9	28.0	**307L2**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	17300	21600	41100	54100	12000
56	3000	2.1	26.4	**306L2**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	14100	16100	34100	39300	9170
62	2680	3.0	23.5	**—**	**307R2**	**BE180M4**	**BX180M4**	**—**	**—**	16300	20400	39000	51300	11400
65	2580	2.4	22.7	**306L2**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	13400	15300	32600	37600	8720
81	2060	2.9	18.1	**306L2**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	12400	14200	30400	35100	8090
96	1740	2.9	15.3	**306L2**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	11800	13400	28900	33400	7650
195	880	1.4	7.50	**303L1**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	7800	8910	16600	19700	4140
195	880	2.6	7.50	**305L1**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	7800	8910	16600	19700	4140
223	770	2.4	6.57	**304L1**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	7460	8530	16000	18900	3960
236	730	1.9	6.20	**303L1**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	7320	8360	15700	18600	3880
275	630	2.4	5.33	**303L1**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	6960	7950	15000	17800	3690
345	500	2.9	4.25	**303L1**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	6450	7370	14000	16600	3420

P_1 = 22 kW

n_2 min^{-1}	M_2 Nm	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
1.1	166900	0.9	1318	**317ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	389600	413900	144800
1.1	175800	1.9	1389	**319L4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	453700	499600	196500
1.2	151200	2.3	1195	**319L4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	444100	488900	186800
1.3	143600	1.1	1134	**317ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	381300	405100	137700
1.4	129100	0.9	1020	**316ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	241400	270800	132900
1.4	130700	1.3	1032	**317ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	376300	399700	133500
1.4	134100	2.0	1059	**318ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	359200	405600	179500
1.5	120700	1.2	953	**—**	**317MR4**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	372000	395200	130000



P_1 = 22 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
1.5	127400	2.6	1007	**319L4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	433300	477100	176500
1.6	114400	1.4	904	**317ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	369200	392200	127700
1.6	115300	2.4	911	**318ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	351600	397000	170700
1.6	115400	2.8	912	**319L4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	427300	470400	170800
1.6	114700	2.8	906	**—**	**319R4C**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	426900	470000	170400
1.7	111400	1.0	880	**316ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	236400	265100	126600
1.8	100300	1.9	792	**317ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	362300	384900	122200
1.8	101700	1.5	803	**—**	**317MR4**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	363000	385600	122800
1.9	99300	1.2	784	**316ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	232500	260800	121800
1.9	99000	1.2	782	**—**	**316MR4**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	232400	260700	121700
1.9	97200	2.8	768	**318ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	343100	387400	161200
2.0	93900	1.0	741	**315ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	150700	180800	71700
2.0	91000	1.9	719	**317ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	357300	379600	118300
2.0	91900	2.9	726	**318ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	340400	384300	158300
2.1	89400	1.3	706	**316ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	229100	257000	117600
2.1	87500	2.9	691	**—**	**318MR4C**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	338000	381600	155700
2.2	84600	0.9	668	**314ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	148500	178100	69300
2.2	85000	1.1	672	**315ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	148600	178200	69400
2.2	83400	1.0	659	**—**	**315MR4**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	148200	177700	69000
2.2	83400	1.3	659	**—**	**316MR4**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	226800	254400	114900
2.2	85700	1.8	677	**—**	**317MR4**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	354200	376300	116000
2.3	79500	1.4	628	**316ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	225200	252700	113100
2.3	79200	1.5	626	**—**	**317MR4**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	350300	372100	113000
2.4	78900	1.2	623	**—**	**315MR4**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	147000	176300	67700
2.4	78900	1.4	623	**—**	**316MR4**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	225000	252400	112800
2.4	78300	2.1	619	**317ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	349700	371500	112500
2.5	72800	0.9	575	**314ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	145300	174300	65900
2.5	74400	1.0	588	**314ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	145800	174900	66400
2.5	74800	1.3	591	**315ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	145900	175000	66500
2.6	71300	1.6	563	**316ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	221700	248800	109000
2.7	67500	1.4	533	**315ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	143800	172400	64300
2.7	69800	2.8	552	**317ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	344000	365500	108300
2.8	66500	1.4	525	**—**	**315MR4**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	143500	172100	63900
2.8	66500	1.9	525	**—**	**316MR4**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	219600	246300	106600
2.8	65800	2.5	520	**—**	**317MR4**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	341100	362400	106200
2.9	63400	2.0	500	**316ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	218100	244600	104900
3.0	62600	1.2	495	**314ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	142200	170600	62700
3.0	61600	1.5	487	**315ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	141900	170200	62300
3.0	62400	2.7	493	**317ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	338500	359700	104300
3.2	58000	1.3	458	**314ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	140700	168700	61100
3.3	55800	1.7	441	**315ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	139900	167800	60300
3.3	56600	2.2	447	**316ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	214600	240700	101000
3.3	56000	2.2	443	**—**	**316MR4**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	214300	240300	100600
3.3	55500	2.8	438	**—**	**317MR4**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	332900	353700	100300
3.4	54500	1.9	430	**—**	**316MR4**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	213400	239400	99700
3.6	51800	1.8	409	**—**	**315MR4**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	138500	166000	58800
3.7	49900	1.5	394	**314ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	137700	165100	58100
3.7	50500	2.1	399	**316ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	211100	236800	97200
3.7	50500	3.0	399	**—**	**317MR4**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	328500	349000	97200
4.0	46800	2.0	370	**315ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	136500	163600	56900

A



P_1 = 22 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
4.0	45900	2.2	363	—	316MR4	BE180L4	BX180L4	—	—	—	—	208300	233600	94200
4.2	43700	2.2	345	—	315MR4	BE180L4	BX180L4	—	—	—	—	135100	162000	55600
4.2	43800	2.3	346	316ML4	—	BE180L4	BX180L4	—	—	—	—	206800	232000	92700
4.3	42700	2.4	337	—	316MR4	BE180L4	BX180L4	—	—	—	—	206100	231200	91900
4.4	42600	3.0	336	—	317MR4	BE180L4	BX180L4	—	—	—	—	320500	340500	91800
4.7	39800	1.9	314	314ML4	—	BE180L4	BX180L4	—	—	—	—	133300	159900	53900
4.8	38300	2.5	302	315ML4	—	BE180L4	BX180L4	—	—	—	—	132600	159000	53200
5.1	36600	3.0	289	—	316MR4	BE180L4	BX180L4	—	—	—	—	202000	226600	87300
5.5	34000	2.7	269	—	315MR4	BE180L4	BX180L4	—	—	—	—	132000	158300	51100
5.5	34000	3.0	269	—	316MR4	BE180L4	BX180L4	—	—	—	—	202000	226600	85200
5.6	33200	3.0	262	—	317MR4	BE180L4	BX180L4	—	—	—	—	314300	333900	84500
5.8	32900	1.3	252	313ML3	—	BE180L4	BX180L4	—	—	—	—	142000	166400	44500
6.0	32000	1.1	245	311ML3	—	BE180L4	BX180L4	—	—	—	—	98000	100000	35800
6.1	31300	1.5	240	314ML3	—	BE180L4	BX180L4	—	—	—	—	132000	158300	49200
6.1	31400	1.9	241	315ML3	—	BE180L4	BX180L4	—	—	—	—	132000	158300	49300
6.5	28500	3.0	225	—	315MR4	BE180L4	BX180L4	—	—	—	—	132000	158300	48200
6.5	28500	3.0	225	—	316MR4	BE180L4	BX180L4	—	—	—	—	202000	226600	80400
6.7	27800	3.0	220	—	317MR4	BE180L4	BX180L4	—	—	—	—	314300	333900	79700
7.0	27200	1.6	209	313ML3	—	BE180L4	BX180L4	—	—	—	—	142000	166400	41800
7.1	26900	2.3	206	314ML3	—	BE180L4	BX180L4	—	—	—	—	132000	158300	46800
7.1	27000	2.8	207	315ML3	—	BE180L4	BX180L4	—	—	—	—	132000	158300	46900
7.2	26500	1.4	203	311ML3	—	BE180L4	BX180L4	—	—	—	—	98000	100000	33600
7.6	25300	1.9	194	313ML3	—	BE180L4	BX180L4	—	—	—	—	142000	166400	40700
7.7	25000	1.3	191	311ML3	—	BE180L4	BX180L4	—	—	—	—	98000	100000	33000
8.0	23800	1.3	182	313ML3	—	BE180L4	BX180L4	—	—	—	—	142000	166400	39900
8.3	22900	1.8	176	313ML3	—	BE180L4	BX180L4	—	—	—	—	142000	166400	39500
8.4	22700	2.7	174	314ML3	—	BE180L4	BX180L4	—	—	—	—	132000	158300	44200
8.6	22300	1.6	171	311ML3	—	BE180L4	BX180L4	—	—	—	—	98000	100000	31800
8.9	21400	2.8	164	314ML3	—	BE180L4	BX180L4	—	—	—	—	132000	158300	43400
9.0	21400	1.2	164	310ML3	—	BE180L4	BX180L4	—	—	—	—	78000	98900	31300
9.0	21300	2.4	163	313ML3	—	BE180L4	BX180L4	—	—	—	—	142000	166400	38500
9.1	21000	1.7	161	311ML3	—	BE180L4	BX180L4	—	—	—	—	98000	100000	31100
9.3	20500	2.3	157	—	314MR3C	BE180L4	BX180L4	—	—	—	—	132000	158300	42800
9.3	20500	2.9	157	—	315MR3C	BE180L4	BX180L4	—	—	—	—	132000	158300	42800
9.6	20000	1.5	153	—	313MR3	BE180L4	BX180L4	—	—	—	—	142000	166400	37700
9.7	19700	2.1	151	313ML3	—	BE180L4	BX180L4	—	—	—	—	142000	166400	37500
9.8	19500	1.1	149	310ML3	—	BE180L4	BX180L4	—	—	—	—	78000	98900	30400
10.0	19200	1.8	147	311ML3	—	BE180L4	BX180L4	—	—	—	—	98000	100000	30200
10.0	19100	1.4	147	—	311MR3	BE180L4	BX180L4	—	—	—	—	98000	100000	30200
10.2	18700	2.2	143	313ML3	—	BE180L4	BX180L4	—	—	—	—	141000	165200	36800
10.8	17700	1.5	135	310ML3	—	BE180L4	BX180L4	—	—	—	—	76200	96600	29400
10.9	17600	2.8	135	313ML3	—	BE180L4	BX180L4	—	—	—	—	138500	162300	36100
11.0	17400	2.0	133	311ML3	—	BE180L4	BX180L4	—	—	—	—	95200	100000	29200
11.5	16600	2.4	127	—	313MR3	BE180L4	BX180L4	—	—	—	—	136100	159500	35400
11.9	16100	2.1	124	—	311MR3	BE180L4	BX180L4	—	—	—	—	93100	100000	28500
12.2	15700	2.6	120	313ML3	—	BE180L4	BX180L4	—	—	—	—	133900	156900	34800
12.3	15500	1.4	119	310ML3	—	BE180L4	BX180L4	—	—	—	—	73300	92900	28200
12.8	14900	2.3	115	311ML3	—	BE180L4	BX180L4	—	—	—	—	91000	100000	27800
13.6	14100	1.7	108	310ML3	—	BE180L4	BX180L4	—	—	—	—	71100	90200	27200
13.7	14000	2.7	107	—	313MR3	BE180L4	BX180L4	—	—	—	—	129300	151500	33500



P_1 = 22 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N]				
min^{-1}	Nm									MC	MZ	HC/PC	HZ/PZ	FZ
14.1	13500	2.7	104	**311ML3**	—	**BE180L4**	**BX180L4**	—	—	—	—	88400	100000	26900
14.1	13600	2.4	104	—	**311MR3**	**BE180L4**	**BX180L4**	—	—	—	—	88500	100000	26900
14.5	13200	1.6	101	**310ML3**	—	**BE180L4**	**BX180L4**	—	—	—	—	69700	88400	26600
15.0	12700	3.0	97.5	—	**313MR3**	**BE180L4**	**BX180L4**	—	—	—	—	125700	147300	32400
15.2	12600	2.4	96.3	—	**311MR3**	**BE180L4**	**BX180L4**	—	—	—	—	86400	100000	26200
15.8	12100	1.9	92.7	**310ML3**	—	**BE180L4**	**BX180L4**	—	—	—	—	68000	86200	25900
16.4	11600	3.0	89.3	**311ML3**	—	**BE180L4**	**BX180L4**	—	—	—	—	84500	100000	25600
17.8	10700	3.0	82.2	—	**313MR3**	**BE180L4**	**BX180L4**	—	—	—	—	119400	139900	30600
18.1	10600	2.8	81.1	—	**311MR3**	**BE180L4**	**BX180L4**	—	—	—	—	82100	100000	24800
18.2	10500	2.0	80.3	**310ML3**	—	**BE180L4**	**BX180L4**	—	—	—	—	65100	82600	24700
19.8	9640	2.3	73.9	**310ML3**	—	**BE180L4**	**BX180L4**	—	—	—	—	63500	80500	24000
20.9	9130	3.0	69.9	—	**313MR3**	**BE180L4**	**BX180L4**	—	—	—	—	113800	133300	29000
21.5	8870	3.0	68.0	—	**311MR3**	**BE180L4**	**BX180L4**	—	—	—	—	77800	99300	23400
22.9	8360	3.0	64.0	—	**313MR3**	**BE180L4**	**BX180L4**	—	—	—	—	110800	129800	28200
23.2	8250	3.0	63.2	—	**311MR3**	**BE180L4**	**BX180L4**	—	—	—	—	76200	97100	22800
23.4	8170	2.4	62.6	**310ML3**	—	**BE180L4**	**BX180L4**	—	—	—	—	60400	76600	22700
27.3	7000	3.0	53.7	—	**313MR3**	**BE180L4**	**BX180L4**	—	—	—	—	105100	123100	26600
27.6	6920	2.8	53.0	**310ML3**	—	**BE180L4**	**BX180L4**	—	—	—	—	57500	72900	21500
27.6	6920	3.0	53.0	—	**311MR3**	**BE180L4**	**BX180L4**	—	—	—	—	72200	92100	21500
31	6290	1.3	46.7	**307L2**	—	**BE180L4**	**BX180L4**	—	—	20500	25600	47900	63000	14300
31	6290	2.0	46.7	**309L2**	—	**BE180L4**	**BX180L4**	—	—	—	—	49000	63000	11400
31	6290	2.8	46.7	**310ML2**	—	**BE180L4**	**BX180L4**	—	—	—	—	55400	70200	20600
32	6260	1.0	46.5	**306L2**	—	**BE180L4**	**BX180L4**	—	—	17100	19400	40400	46600	11100
38	5170	1.3	38.4	**306L2**	—	**BE180L4**	**BX180L4**	—	—	16000	18200	38200	44000	10400
38	5200	1.6	38.6	**307L2**	—	**BE180L4**	**BX180L4**	—	—	19200	24000	45300	59500	13400
38	5200	2.4	38.6	**309L2**	—	**BE180L4**	**BX180L4**	—	—	—	—	46300	59500	10700
44	4450	1.5	33.1	**306L2**	—	**BE180L4**	**BX180L4**	—	—	15200	17400	36500	42100	9890
45	4380	2.2	32.6	**307L2**	—	**BE180L4**	**BX180L4**	—	—	18200	22700	43000	56500	12700
45	4380	3.0	32.6	**309L2**	—	**BE180L4**	**BX180L4**	—	—	—	—	43900	56500	10100
48	4130	2.3	30.7	**307L2**	—	**BE180L4**	**BX180L4**	—	—	17800	22300	42200	55600	12400
52	3830	1.8	28.4	**306L2**	—	**BE180L4**	**BX180L4**	—	—	14500	16500	34900	40200	9410
52	3770	2.4	28.0	**307L2**	—	**BE180L4**	**BX180L4**	—	—	17300	21600	41100	54100	12000
56	3550	1.8	26.4	**306L2**	—	**BE180L4**	**BX180L4**	—	—	14100	16100	34100	39300	9170
58	3410	2.7	25.4	**307L2**	—	**BE180L4**	**BX180L4**	—	—	16700	20900	39900	52500	11600
62	3170	2.5	23.5	—	**307R2**	**BE180L4**	**BX180L4**	—	—	16300	20400	39000	51300	11400
62	3170	3.0	23.5	—	**309R2**	**BE180L4**	**BX180L4**	—	—	—	—	39900	51300	9080
65	3050	2.0	22.7	**306L2**	—	**BE180L4**	**BX180L4**	—	—	13400	15300	32600	37600	8720
67	2940	3.0	21.8	**307L2**	—	**BE180L4**	**BX180L4**	—	—	15900	19900	38100	50200	11100
74	2670	3.0	19.8	—	**307R2**	**BE180L4**	**BX180L4**	—	—	15400	19300	37000	48700	10700
74	2670	3.0	19.8	—	**309R2**	**BE180L4**	**BX180L4**	—	—	—	—	37900	48700	8580
81	2430	2.4	18.1	**306L2**	—	**BE180L4**	**BX180L4**	—	—	12400	14200	30400	35100	8090
95	2080	3.0	15.5	—	**307R2**	**BE180L4**	**BX180L4**	—	—	14200	17700	34400	45200	9870
95	2080	3.0	15.5	—	**309R2**	**BE180L4**	**BX180L4**	—	—	—	—	35100	45200	7900
96	2060	2.4	15.3	**306L2**	—	**BE180L4**	**BX180L4**	—	—	11800	13400	28900	33400	7650
113	1740	2.8	13.0	**306L2**	—	**BE180L4**	**BX180L4**	—	—	11100	12700	27500	31800	7240
113	1740	3.0	13.0	—	**307R2**	**BE180L4**	**BX180L4**	—	—	13400	16700	32600	42900	9310
113	1740	3.0	13.0	—	**309R2**	**BE180L4**	**BX180L4**	—	—	—	—	33300	42900	7440
195	1040	1.2	7.50	**303L1**	—	**BE180L4**	**BX180L4**	—	—	7800	8910	16600	19700	4140
195	1040	2.2	7.50	**305L1**	—	**BE180L4**	**BX180L4**	—	—	7800	8910	16600	19700	4140
223	910	2.1	6.57	**304L1**	—	**BE180L4**	**BX180L4**	—	—	7460	8530	16000	18900	3960



A

P_1 = 22 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
236	860	1.6	6.20	**303L1**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	7320	8360	15700	18600	3880
275	740	2.0	5.33	**303L1**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	6960	7950	15000	17800	3690
275	740	2.7	5.33	**304L1**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	6960	7950	15000	17800	3690
345	590	2.4	4.25	**303L1**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	6450	7370	14000	16600	3420
407	500	2.8	3.60	**303L1**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	6110	6980	13300	15800	3240

P_1 = 30 kW

n_2	M_2	S	i			IE2*	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
1.1	239700	1.4	1389	**319L4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	453500	499300	196200
1.2	206200	1.7	1195	**319L4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	443900	488700	186600
1.3	193600	2.7	1122	**321L4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	622200	740600	1106400
1.4	178200	1.0	1032	**317ML4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	376100	399500	133300
1.4	182800	1.4	1059	**318ML4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	359100	405400	179300
1.5	173800	1.9	1007	**319L4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	433100	476900	176300
1.6	156000	1.0	904	**317ML4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	369000	392000	127500
1.6	157300	1.8	911	**318ML4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	351400	396800	170500
1.6	157400	2.0	912	**319L4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	427100	470200	170600
1.6	156500	2.0	906	**—**	**319R4C**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	426700	469800	170200
1.7	146800	2.8	850	**319L4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	422800	465500	166700
1.8	138700	1.1	803	**—**	**317MR4**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	362800	385500	122600
1.8	138500	2.3	802	**319L4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	419300	461700	163400
1.9	136700	1.4	792	**317ML4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	362100	384700	122100
1.9	132500	2.0	768	**318ML4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	342900	387200	161100
1.9	134600	2.4	780	**—**	**319R4C**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	417600	459800	161900
2.0	124100	1.4	719	**317ML4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	357100	379400	118200
2.0	125300	2.1	726	**318ML4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	340200	384100	158100
2.1	121900	0.9	706	**316ML4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	228900	256800	117500
2.1	119300	2.2	691	**—**	**318MR4C**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	337800	381500	155500
2.2	113800	1.0	659	**—**	**316MR4**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	226700	254300	114800
2.2	116800	1.3	677	**—**	**317MR4**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	354100	376100	115800
2.2	113000	2.7	655	**—**	**319R4B**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	407300	448500	152700
2.2	113400	2.7	657	**—**	**319R4C**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	407500	448700	152900
2.3	108400	1.0	628	**316ML4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	225100	252600	113000
2.3	108100	1.1	626	**—**	**317MR4**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	350100	372000	112800
2.3	111700	2.4	647	**318ML4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	334600	377900	152100
2.4	107600	1.1	623	**—**	**316MR4**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	224900	252300	112700
2.4	106800	1.6	619	**317ML4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	349500	371300	112400
2.4	105600	2.5	612	**318ML4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	332000	374900	149300
2.4	107900	2.9	625	**319L4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	404600	445500	150400
2.5	102000	0.9	591	**315ML4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	145800	174900	66400
2.5	102600	2.5	595	**—**	**318MR4C**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	330700	373300	147900
2.6	97200	1.2	563	**316ML4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	221600	248600	108900
2.7	95200	2.0	552	**317ML4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	343900	365300	108200
2.8	92100	1.0	533	**315ML4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	143700	172400	64200
2.8	90700	1.0	525	**—**	**315MR4**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	143400	172000	63900
2.8	90700	1.4	525	**—**	**316MR4**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	219500	246200	106400
2.8	89800	1.9	520	**—**	**317MR4**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	341000	362200	106100
2.9	86400	1.5	500	**316ML4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	218000	244500	104700
2.9	89000	2.9	515	**318ML4**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	324000	365800	141000
2.9	86200	2.9	499	**—**	**318MR4B**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	322500	364100	139500
2.9	86500	2.9	501	**—**	**318MR4C**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	322700	364300	139700

*** The technical information shall be considered as indicative, the configurations should be matching the data provided by motors manufacturers on rated powers greater than 22 kW.**



P_1 = 30 kW

n_2	M_2	S	i			IE2*	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
3.0	84000	1.1	487	**315ML4**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	141900	170100	62300
3.0	85100	2.0	493	**317ML4**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	338400	359500	104200
3.2	79100	0.9	458	**314ML4**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	140600	168700	61000
3.3	76100	1.2	441	**315ML4**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	139900	167700	60200
3.3	77200	1.6	447	**316ML4**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	214500	240600	100900
3.3	76400	1.6	443	—	**316MR4**	**IEC200L4**	**BX200LA4**	—	—	—	—	214200	240200	100500
3.3	77500	2.4	449	**317ML4**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	333900	354700	101000
3.4	74300	1.4	430	—	**316MR4**	**IEC200L4**	**BX200LA4**	—	—	—	—	213300	239300	99600
3.4	75600	2.1	438	—	**317MR4**	**IEC200L4**	**BX200LA4**	—	—	—	—	332700	353500	100200
3.6	70600	1.3	409	—	**315MR4**	**IEC200L4**	**BX200LA4**	—	—	—	—	138400	166000	58800
3.7	68000	1.1	394	**314ML4**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	137600	165100	58000
3.7	68900	1.5	399	**316ML4**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	211000	236700	97100
3.7	68900	2.2	399	—	**317MR4**	**IEC200L4**	**BX200LA4**	—	—	—	—	328300	348800	97100
3.9	65300	2.8	378	**317ML4**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	325800	346100	95400
4.0	63800	1.5	370	**315ML4**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	136400	163600	56800
4.1	62600	1.6	363	—	**316MR4**	**IEC200L4**	**BX200LA4**	—	—	—	—	208100	233500	94100
4.3	59500	1.6	345	—	**315MR4**	**IEC200L4**	**BX200LA4**	—	—	—	—	135000	161900	55500
4.3	59700	1.7	346	**316ML4**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	206700	231900	92600
4.4	58200	1.7	337	—	**316MR4**	**IEC200L4**	**BX200LA4**	—	—	—	—	206000	231100	91800
4.4	58000	2.2	336	—	**317MR4**	**IEC200L4**	**BX200LA4**	—	—	—	—	320400	340400	91700
4.6	54900	2.3	318	**316ML4**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	204300	229100	90000
4.7	54200	1.4	314	**314ML4**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	133200	159800	53800
4.9	52200	1.8	302	**315ML4**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	132500	158900	53100
5.1	49900	2.2	289	—	**316MR4**	**IEC200L4**	**BX200LA4**	—	—	—	—	202000	226600	87200
5.3	47500	2.6	275	**316ML4**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	202000	226600	85800
5.5	46400	2.0	269	—	**315MR4**	**IEC200L4**	**BX200LA4**	—	—	—	—	132000	158300	51100
5.5	46400	2.2	269	—	**316MR4**	**IEC200L4**	**BX200LA4**	—	—	—	—	202000	226600	85100
5.6	45200	2.2	262	—	**317MR4**	**IEC200L4**	**BX200LA4**	—	—	—	—	314300	333900	84400
5.8	44900	1.0	252	**313ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	142000	166400	44500
5.8	43700	2.8	253	**316ML4**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	202000	226600	83500
5.8	44900	2.5	252	**317ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	314300	333900	83400
6.1	42600	1.1	240	**314ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	132000	158300	49200
6.1	42800	1.4	241	**315ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	132000	158300	49200
6.5	38900	2.2	225	—	**315MR4**	**IEC200L4**	**BX200LA4**	—	—	—	—	132000	158300	48200
6.5	38900	2.2	225	—	**316MR4**	**IEC200L4**	**BX200LA4**	—	—	—	—	202000	226600	80300
6.7	37900	2.2	220	—	**317MR4**	**IEC200L4**	**BX200LA4**	—	—	—	—	314300	333900	79600
7.0	37100	1.1	209	**313ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	142000	166400	41700
7.1	36700	1.7	206	**314ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	132000	158300	46700
7.1	36800	2.1	207	**315ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	132000	158300	46800
7.1	36800	2.7	207	**316ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	202000	226600	78000
7.2	36100	1.0	203	**311ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	98000	100000	33600
7.6	34500	1.4	194	**313ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	142000	166400	40700
7.7	34000	0.9	191	**311ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	98000	100000	32900
8.1	32400	0.9	182	**313ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	142000	166400	39900
8.4	31300	1.3	176	**313ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	142000	166400	39400
8.4	31000	2.4	174	**315ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	132000	158300	44200
8.5	30900	2.0	174	**314ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	132000	158300	44200
8.6	30400	1.2	171	**311ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	98000	100000	31700
9.0	29100	0.9	164	**310ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	78000	98900	31300
9.0	29000	1.8	163	**313ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	142000	166400	38400
9.0	29200	2.0	164	**314ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	132000	158300	43300
9.1	28700	1.2	161	**311ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	98000	100000	31100
9.4	28000	1.7	157	—	**314MR3C**	**IEC200L4**	**BX200LA4**	—	—	—	—	132000	158300	42700
9.4	28000	2.1	157	—	**315MR3C**	**IEC200L4**	**BX200LA4**	—	—	—	—	132000	158300	42700
9.6	27200	1.1	153	—	**313MR3**	**IEC200L4**	**BX200LA4**	—	—	—	—	142000	166400	37600
9.7	26900	1.5	151	**313ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	142000	166400	37500
10.0	26200	1.3	147	**311ML3**	—	**IEC200L4**	**BX200LA4**	—	—	—	—	98000	100000	30200
10.0	26100	1.0	147	—	**311MR3**	**IEC200L4**	**BX200LA4**	—	—	—	—	97900	100000	30100

*** The technical information shall be considered as indicative, the configurations should be matching the data provided by motors manufacturers on rated powers greater than 22 kW.**



P_1 = 30 kW

n_2	M_2	S	i							Rn_2 [N]				
min^{-1}	Nm					IE2*	IE3	IE2	IE3	MC	MZ	HC/PC	HZ/PZ	FZ
10.3	25400	1.6	143	**313ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	140800	165000	36800
10.6	24600	2.8	138	**314ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	129600	155400	40900
10.9	24100	1.1	135	**310ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	76100	96500	29300
10.9	24000	2.1	135	**313ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	138400	162100	36100
10.9	24100	2.5	135	**—**	**314MR3C**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	128700	154400	40600
11.0	23700	1.5	133	**311ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	95100	100000	29200
11.6	22600	1.8	127	**—**	**313MR3**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	135900	159300	35400
11.9	22000	1.6	124	**—**	**311MR3**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	93000	100000	28500
12.2	21400	1.9	120	**313ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	133800	156800	34800
12.4	21200	1.0	119	**310ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	73200	92800	28100
12.8	20400	1.7	115	**311ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	90900	100000	27800
12.9	20300	2.9	114	**—**	**314MR3C**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	122300	146600	38400
13.0	20200	2.3	113	**—**	**314MR3B**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	122100	146500	38300
13.0	20200	2.9	113	**—**	**315MR3B**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	122100	146500	38300
13.4	19500	2.3	110	**313ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	130100	152400	33700
13.6	19200	1.3	108	**310ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	71100	90100	27200
13.6	19200	2.9	108	**314ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	120300	144200	37700
13.7	19100	2.0	107	**—**	**313MR3**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	129100	151300	33400
13.7	19200	2.9	108	**—**	**314MR3C**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	120200	144200	37700
14.1	18500	1.8	104	**—**	**311MR3**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	88400	100000	26900
14.2	18500	2.0	104	**311ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	88300	100000	26900
14.6	17900	1.2	101	**310ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	69700	88300	26600
15.1	17400	2.2	97.5	**—**	**313MR3**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	125500	147100	32400
15.3	17100	1.7	96.3	**—**	**311MR3**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	86300	100000	26200
15.9	16500	1.4	92.7	**310ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	67900	86100	25900
15.9	16500	2.7	92.4	**313ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	123600	144800	31800
16.5	15900	2.2	89.3	**311ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	84400	100000	25500
17.9	14600	2.2	82.2	**—**	**313MR3**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	119300	139800	30600
18.1	14400	2.1	81.1	**—**	**311MR3**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	82000	100000	24700
18.3	14300	1.4	80.3	**310ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	65100	82500	24700
19.0	13800	2.4	77.3	**311ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	80800	100000	24400
19.9	13200	1.7	73.9	**310ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	63500	80500	24000
20.7	12700	2.6	71.1	**311ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	78800	100000	23700
21.0	12400	2.2	69.9	**—**	**313MR3**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	113600	133200	29000
21.6	12100	2.2	68.0	**—**	**311MR3**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	77800	99200	23300
23.0	11400	2.2	64.0	**—**	**313MR3**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	110700	129700	28100
23.3	11300	2.2	63.2	**—**	**311MR3**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	76100	97000	22800
23.5	11100	1.8	62.6	**310ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	60400	76600	22700
24.4	10700	2.9	60.2	**311ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	75000	95700	22400
27.4	9550	2.2	53.7	**—**	**313MR3**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	105000	123000	26500
27.7	9440	2.0	53.0	**310ML3**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	57400	72800	21500
27.7	9430	2.2	53.0	**—**	**311MR3**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	72200	92000	21500
31	8570	1.0	46.7	**307L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	20500	25600	47900	63000	14300
31	8570	1.5	46.7	**309L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	48900	63000	11400
31	8570	2.1	46.7	**310ML2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	55300	70100	20600
38	7050	0.9	38.4	**306L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	16000	18200	38100	44000	10400
38	7090	1.2	38.6	**307L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	19200	24000	45200	59500	13400
38	7090	1.8	38.6	**309L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	46200	59500	10700
38	7090	2.5	38.6	**310ML2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	52200	66200	19300
44	6070	1.1	33.1	**306L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	15200	17300	36400	42100	9880
45	5970	1.6	32.6	**307L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	18100	22700	42900	56500	12600
45	5970	2.2	32.6	**309L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	43900	56500	10100
48	5630	1.7	30.7	**307L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	17800	22200	42200	55500	12400
52	5220	1.3	28.4	**306L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	14500	16500	34800	40200	9400
53	5140	1.8	28.0	**307L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	17300	21600	41000	54000	12000
53	5140	2.5	28.0	**309L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	42000	54000	9610
56	4830	1.3	26.4	**306L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	14100	16100	34000	39300	9160
58	4650	2.0	25.4	**307L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	16700	20900	39800	52400	11600

*** The technical information shall be considered as indicative, the configurations should be matching the data provided by motors manufacturers on rated powers greater than 22 kW.**



P_1 = 30 kW

n_2	M_2	S	i			IE2*	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
58	4650	2.3	25.4	**309L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	40700	52400	9300
62	4320	1.9	23.5	**—**	**307R2**	**IEC200L4**	**BX200LA4**	**—**	**—**	16300	20400	39000	51300	11300
62	4320	2.2	23.5	**—**	**309R2**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	39800	51300	9070
65	4160	1.5	22.7	**306L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	13400	15300	32500	37600	8710
67	4000	2.2	21.8	**307L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	15900	19900	38100	50100	11100
67	4000	2.5	21.8	**309L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	38900	50100	8850
74	3640	2.2	19.8	**—**	**307R2**	**IEC200L4**	**BX200LA4**	**—**	**—**	15400	19200	37000	48700	10700
74	3640	2.2	19.8	**—**	**309R2**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	37800	48700	8570
81	3310	1.8	18.1	**306L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	12400	14200	30400	35100	8080
85	3190	2.6	17.4	**307L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	14700	18400	35600	46800	10300
95	2840	2.2	15.5	**—**	**307R2**	**IEC200L4**	**BX200LA4**	**—**	**—**	14200	17700	34300	45200	9860
95	2840	2.2	15.5	**—**	**309R2**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	35100	45200	7890
96	2810	1.8	15.3	**306L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	11800	13400	28900	33400	7640
100	2700	2.9	14.7	**307L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	13900	17400	33800	44500	9700
113	2380	2.0	13.0	**306L2**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	11100	12700	27500	31800	7230
113	2380	2.2	13.0	**—**	**307R2**	**IEC200L4**	**BX200LA4**	**—**	**—**	13300	16700	32600	42800	9290
113	2380	2.2	13.0	**—**	**309R2**	**IEC200L4**	**BX200LA4**	**—**	**—**	—	—	33300	42800	7440
196	1420	1.6	7.50	**305L1**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	7790	8900	16600	19700	4130
196	1420	2.9	7.50	**306L1**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	9270	10600	23300	26900	6030
224	1240	1.5	6.57	**304L1**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	7450	8520	15900	18900	3950
237	1170	1.2	6.20	**303L1**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	7310	8350	15700	18600	3880
237	1170	2.3	6.20	**305L1**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	7310	8350	15700	18600	3880
276	1010	1.5	5.33	**303L1**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	6950	7950	15000	17700	3690
276	1010	2.0	5.33	**304L1**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	6950	7950	15000	17700	3690
276	1010	2.6	5.33	**305L1**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	6950	7950	15000	17700	3690
346	800	1.8	4.25	**303L1**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	6450	7370	14000	16600	3420
346	800	2.4	4.25	**304L1**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	6450	7370	14000	16600	3420
408	680	2.0	3.60	**303L1**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	6100	6970	13300	15800	3230
408	680	2.7	3.60	**304L1**	**—**	**IEC200L4**	**BX200LA4**	**—**	**—**	6100	6970	13300	15800	3230

P_1 = 37 kW

n_2	M_2	S	i			IE2*	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
1.1	293800	1.1	1389	**319L4**	**—**	**IEC225S4**	**BX225SA4**	**—**	**—**	—	—	453100	498800	195800
1.2	252700	1.4	1195	**319L4**	**—**	**IEC225S4**	**BX225SA4**	**—**	**—**	—	—	443400	488200	186200
1.3	237300	2.2	1122	**321L4**	**—**	**IEC225S4**	**BX225SA4**	**—**	**—**	—	—	621600	739900	1104200
1.4	224100	1.2	1059	**318ML4**	**—**	**IEC225S4**	**BX225SA4**	**—**	**—**	—	—	358700	405000	178900
1.5	213000	1.6	1007	**319L4**	**—**	**IEC225S4**	**BX225SA4**	**—**	**—**	—	—	432700	476400	175900
1.6	192800	1.4	911	**318ML4**	**—**	**IEC225S4**	**BX225SA4**	**—**	**—**	—	—	351100	396400	170100
1.6	192900	1.7	912	**319L4**	**—**	**IEC225S4**	**BX225SA4**	**—**	**—**	—	—	426600	469700	170200
1.6	191800	1.7	906	**—**	**319R4C**	**IEC225S4**	**BX225SA4**	**—**	**—**	—	—	426300	469300	169800
1.6	199900	2.9	945	**321L4**	**—**	**IEC225S4**	**BX225SA4**	**—**	**—**	—	—	606600	722000	1048900
1.7	180000	2.2	850	**319L4**	**—**	**IEC225S4**	**BX225SA4**	**—**	**—**	—	—	422400	465100	166300
1.8	169700	1.9	802	**319L4**	**—**	**IEC225S4**	**BX225SA4**	**—**	**—**	—	—	418900	461200	163100
1.9	162400	1.7	768	**318ML4**	**—**	**IEC225S4**	**BX225SA4**	**—**	**—**	—	—	342600	386800	160700
1.9	165000	1.9	780	**—**	**319R4C**	**IEC225S4**	**BX225SA4**	**—**	**—**	—	—	417200	459400	161500
2.0	153600	1.7	726	**318ML4**	**—**	**IEC225S4**	**BX225SA4**	**—**	**—**	—	—	339900	383800	157700
2.1	146300	1.8	691	**—**	**318MR4C**	**IEC225S4**	**BX225SA4**	**—**	**—**	—	—	337500	381100	155200
2.1	151600	2.6	717	**319L4**	**—**	**IEC225S4**	**BX225SA4**	**—**	**—**	—	—	412200	453900	157100
2.2	143400	2.7	678	**319L4**	**—**	**IEC225S4**	**BX225SA4**	**—**	**—**	—	—	408900	450300	154200
2.3	136900	1.9	647	**318ML4**	**—**	**IEC225S4**	**BX225SA4**	**—**	**—**	—	—	334300	377500	151800
2.3	138500	2.2	655	**—**	**319R4B**	**IEC225S4**	**BX225SA4**	**—**	**—**	—	—	406900	448000	152400

*** The technical information shall be considered as indicative, the configurations should be matching the data provided by motors manufacturers on rated powers greater than 22 kW.**



P_1 = 37 kW

n_2 min^{-1}	M_2 Nm	S	i			IE2*	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
2.3	139000	2.2	657	—	**319R4C**	**IEC225S4**	**BX225SA4**	—	—	—	—	407100	448300	152600
2.4	129400	2.0	612	**318ML4**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	331700	374500	149000
2.4	132200	2.3	625	**319L4**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	404200	445100	150000
2.5	125800	2.1	595	—	**318MR4C**	**IEC225S4**	**BX225SA4**	—	—	—	—	330300	373000	147600
2.6	119200	2.5	563	—	**319R4B**	**IEC225S4**	**BX225SA4**	—	—	—	—	398300	438500	144900
2.9	109100	2.3	515	**318ML4**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	323700	365400	140700
2.9	109000	2.7	515	**319L4**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	393200	432900	140700
3.0	105600	2.4	499	—	**318MR4B**	**IEC225S4**	**BX225SA4**	—	—	—	—	322200	363800	139200
3.0	106000	2.4	501	—	**318MR4C**	**IEC225S4**	**BX225SA4**	—	—	—	—	322300	364000	139400
3.1	100900	2.5	477	**318ML4**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	320100	361400	137100
3.1	100300	2.5	474	—	**318MR4C**	**IEC225S4**	**BX225SA4**	—	—	—	—	319800	361100	136800
3.1	100400	2.9	475	—	**319R4B**	**IEC225S4**	**BX225SA4**	—	—	—	—	388600	427900	136900
3.4	90900	2.7	430	—	**318MR4B**	**IEC225S4**	**BX225SA4**	—	—	—	—	315300	356000	132400
3.5	89400	2.8	422	**318ML4**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	314600	355200	131700
3.7	85000	2.9	402	**318ML4**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	312300	352600	129500
3.7	84500	2.9	399	—	**318MR4C**	**IEC225S4**	**BX225SA4**	—	—	—	—	312100	352300	129200
5.9	55000	2.1	252	**317ML3**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	314300	333900	83200
6.1	52500	1.1	241	**315ML3**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	132000	158300	49100
6.2	52200	0.9	240	**314ML3**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	132000	158300	49000
7.1	45200	1.7	207	**315ML3**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	132000	158300	46700
7.1	45200	2.2	207	**316ML3**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	202000	226600	77900
7.2	44900	1.4	206	**314ML3**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	132000	158300	46600
8.5	37900	1.6	174	**314ML3**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	132000	158300	44100
8.5	38100	2.0	174	**315ML3**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	132000	158300	44100
8.5	38100	2.6	174	**316ML3**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	202000	226600	73500
9.0	35800	1.7	164	**314ML3**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	132000	158300	43200
9.0	36000	2.5	165	**315ML3**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	132000	158300	43300
9.4	34300	1.4	157	—	**314MR3C**	**IEC225S4**	**BX225SA4**	—	—	—	—	132000	158300	42600
9.4	34300	1.7	157	—	**315MR3C**	**IEC225S4**	**BX225SA4**	—	—	—	—	132000	158300	42600
10.6	30300	2.9	139	**315ML3**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	129500	155400	40900
10.7	30200	2.3	138	**314ML3**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	129400	155100	40800
11.0	29500	2.0	135	—	**314MR3C**	**IEC225S4**	**BX225SA4**	—	—	—	—	128400	154000	40500
11.0	29500	2.5	135	—	**315MR3C**	**IEC225S4**	**BX225SA4**	—	—	—	—	128400	154000	40500
13.0	24800	1.9	113	—	**314MR3B**	**IEC225S4**	**BX225SA4**	—	—	—	—	121900	146200	38200
13.0	24800	2.3	114	—	**314MR3C**	**IEC225S4**	**BX225SA4**	—	—	—	—	122000	146300	38300
13.0	24800	2.4	113	—	**315MR3B**	**IEC225S4**	**BX225SA4**	—	—	—	—	121900	146200	38200
13.0	24800	2.9	114	—	**315MR3C**	**IEC225S4**	**BX225SA4**	—	—	—	—	122000	146300	38300
13.7	23500	2.3	108	**314ML3**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	120000	143900	37600
13.7	23500	2.4	108	—	**314MR3C**	**IEC225S4**	**BX225SA4**	—	—	—	—	120000	143900	37600
15.2	21300	2.7	97.6	—	**314MR3B**	**IEC225S4**	**BX225SA4**	—	—	—	—	116500	139700	36400
16.0	20200	2.6	92.7	**314ML3**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	114700	137600	35700
32	10500	1.7	46.7	**310ML2**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	55200	70000	20500
38	8690	2.1	38.6	**310ML2**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	52100	66100	19300
45	7320	2.8	32.6	**310ML2**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	49500	62800	18200
48	6900	2.5	30.7	**310ML2**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	48600	61700	17900
58	5700	2.9	25.4	**310ML2**	—	**IEC225S4**	**BX225SA4**	—	—	—	—	45900	58300	16800
197	1740	2.4	7.50	**306L1**	—	**IEC225S4**	**BX225SA4**	—	—	9250	10500	23300	26900	6010
239	1440	2.9	6.20	**306L1**	—	**IEC225S4**	**BX225SA4**	—	—	8680	9900	22000	25400	5640

*** The technical information shall be considered as indicative, the configurations should be matching the data provided by motors manufacturers on rated powers greater than 22 kW.**



P_1 = 45 kW

n_2	M_2	S	i			IE2*	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
1.1	356500	0.9	1389	**319L4**	—	IEC225M4	BX225SB4	—	—	—	—	453100	498800	195800
1.2	306700	1.1	1195	**319L4**	—	IEC225M4	BX225SB4	—	—	—	—	443400	488200	186200
1.2	328500	2.7	1279	**323L4**	—	IEC225M4	BX225SB4	—	—	—	—	0	0	1053000
1.2	328500	2.9	1279	**325L4**	—	IEC225M4	BX225SB4	—	—	—	—	0	0	1340200
1.3	287900	1.8	1122	**321L4**	—	IEC225M4	BX225SB4	—	—	—	—	621600	739900	1104200
1.4	271900	1.0	1059	**318ML4**	—	IEC225M4	BX225SB4	—	—	—	—	358700	405000	178900
1.5	258400	1.3	1007	**319L4**	—	IEC225M4	BX225SB4	—	—	—	—	432700	476400	175900
1.6	233900	1.2	911	**318ML4**	—	IEC225M4	BX225SB4	—	—	—	—	351100	396400	170100
1.6	234100	1.4	912	**319L4**	—	IEC225M4	BX225SB4	—	—	—	—	426600	469700	170200
1.6	232700	1.4	906	—	**319R4C**	IEC225M4	BX225SB4	—	—	—	—	426300	469300	169800
1.6	242600	2.4	945	**321L4**	—	IEC225M4	BX225SB4	—	—	—	—	606600	722000	1048900
1.7	218400	1.9	850	**319L4**	—	IEC225M4	BX225SB4	—	—	—	—	422400	465100	166300
1.8	205900	1.6	802	**319L4**	—	IEC225M4	BX225SB4	—	—	—	—	418900	461200	163100
1.9	197100	1.4	768	**318ML4**	—	IEC225M4	BX225SB4	—	—	—	—	342600	386800	160700
1.9	200200	1.6	780	—	**319R4C**	IEC225M4	BX225SB4	—	—	—	—	417200	459400	161500
1.9	204400	2.7	796	**321L4**	—	IEC225M4	BX225SB4	—	—	—	—	591900	704600	996400
2.0	186400	1.4	726	**318ML4**	—	IEC225M4	BX225SB4	—	—	—	—	339900	383800	157700
2.0	189100	2.9	736	**321L4**	—	IEC225M4	BX225SB4	—	—	—	—	585400	696800	973300
2.0	187900	2.8	732	—	**321R4C**	IEC225M4	BX225SB4	—	—	—	—	584900	696200	971500
2.1	177500	1.5	691	—	**318MR4C**	IEC225M4	BX225SB4	—	—	—	—	337500	381100	155200
2.1	184000	2.2	717	**319L4**	—	IEC225M4	BX225SB4	—	—	—	—	412200	453900	157100
2.2	174000	2.2	678	**319L4**	—	IEC225M4	BX225SB4	—	—	—	—	408900	450300	154200
2.3	166100	1.6	647	**318ML4**	—	IEC225M4	BX225SB4	—	—	—	—	334300	377500	151800
2.3	168100	1.8	655	—	**319R4B**	IEC225M4	BX225SB4	—	—	—	—	406900	448000	152400
2.3	168700	1.8	657	—	**319R4C**	IEC225M4	BX225SB4	—	—	—	—	407100	448300	152600
2.4	157000	1.7	612	**318ML4**	—	IEC225M4	BX225SB4	—	—	—	—	331700	374500	149000
2.4	160500	1.9	625	**319L4**	—	IEC225M4	BX225SB4	—	—	—	—	404200	445100	150000
2.5	152700	1.7	595	—	**318MR4C**	IEC225M4	BX225SB4	—	—	—	—	330300	373000	147600
2.6	146600	2.6	571	**319L4**	—	IEC225M4	BX225SB4	—	—	—	—	399100	439400	145600
2.6	144600	2.1	563	—	**319R4B**	IEC225M4	BX225SB4	—	—	—	—	398300	438500	144900
2.7	143400	2.6	558	**319L4**	—	IEC225M4	BX225SB4	—	—	—	—	397800	438000	144500
2.7	142500	2.6	555	—	**319R4C**	IEC225M4	BX225SB4	—	—	—	—	397400	437600	144200
2.8	135600	2.7	528	**319L4**	—	IEC225M4	BX225SB4	—	—	—	—	394600	434500	141900
2.8	134800	2.7	525	—	**319R4C**	IEC225M4	BX225SB4	—	—	—	—	394300	434100	141600
2.9	132300	1.9	515	**318ML4**	—	IEC225M4	BX225SB4	—	—	—	—	323700	365400	140700
2.9	132200	2.3	515	**319L4**	—	IEC225M4	BX225SB4	—	—	—	—	393200	432900	140700
3.0	128200	1.9	499	—	**318MR4B**	IEC225M4	BX225SB4	—	—	—	—	322200	363800	139200
3.0	128600	2.0	501	—	**318MR4C**	IEC225M4	BX225SB4	—	—	—	—	322300	364000	139400
3.1	122400	2.1	477	**318ML4**	—	IEC225M4	BX225SB4	—	—	—	—	320100	361400	137100
3.1	121600	2.1	474	—	**318MR4C**	IEC225M4	BX225SB4	—	—	—	—	319800	361100	136800
3.1	121800	2.4	475	—	**319R4B**	IEC225M4	BX225SB4	—	—	—	—	388600	427900	136900
3.4	110300	2.2	430	—	**318MR4B**	IEC225M4	BX225SB4	—	—	—	—	315300	356000	132400
3.5	108400	2.3	422	**318ML4**	—	IEC225M4	BX225SB4	—	—	—	—	314600	355200	131700
3.6	105300	2.7	410	**319L4**	—	IEC225M4	BX225SB4	—	—	—	—	380700	419100	130400
3.7	103100	2.4	402	**318ML4**	—	IEC225M4	BX225SB4	—	—	—	—	312300	352600	129500
3.7	102500	2.4	399	—	**318MR4C**	IEC225M4	BX225SB4	—	—	—	—	312100	352300	129200
4.1	92900	2.6	362	—	**318MR4B**	IEC225M4	BX225SB4	—	—	—	—	307700	347400	125100
4.3	87900	2.7	342	—	**318MR4B**	IEC225M4	BX225SB4	—	—	—	—	305300	344700	122800
4.4	86400	2.7	337	**318ML4**	—	IEC225M4	BX225SB4	—	—	—	—	304500	343900	122100
4.7	80300	2.9	313	**318ML4**	—	IEC225M4	BX225SB4	—	—	—	—	301400	340300	119200
4.8	79900	2.9	311	—	**318MR4C**	IEC225M4	BX225SB4	—	—	—	—	301100	340000	118900
5.9	66800	1.7	252	**317ML3**	—	IEC225M4	BX225SB4	—	—	—	—	314300	333900	83200

*** The technical information shall be considered as indicative, the configurations should be matching the data provided by motors manufacturers on rated powers greater than 22 kW.**



P_1 = 45 kW

n_2	M_2	S	i			IE2*	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
6.1	63700	0.9	241	**315ML3**	—	IEC225M4	BX225SB4	—	—	—	—	132000	158300	49100
7.0	56300	2.6	213	**317ML3**	—	IEC225M4	BX225SB4	—	—	—	—	314300	333900	78600
7.1	54800	1.4	207	**315ML3**	—	IEC225M4	BX225SB4	—	—	—	—	132000	158300	46700
7.1	54800	1.8	207	**316ML3**	—	IEC225M4	BX225SB4	—	—	—	—	202000	226600	77900
7.2	54500	1.1	206	**314ML3**	—	IEC225M4	BX225SB4	—	—	—	—	132000	158300	46600
8.5	45900	1.3	174	**314ML3**	—	IEC225M4	BX225SB4	—	—	—	—	132000	158300	44100
8.5	46200	1.6	174	**315ML3**	—	IEC225M4	BX225SB4	—	—	—	—	132000	158300	44100
8.5	46200	2.2	174	**316ML3**	—	IEC225M4	BX225SB4	—	—	—	—	202000	226600	73500
8.9	43900	2.8	166	**317ML3**	—	IEC225M4	BX225SB4	—	—	—	—	314300	333900	72300
9.0	43500	1.4	164	**314ML3**	—	IEC225M4	BX225SB4	—	—	—	—	132000	158300	43200
9.0	43700	2.1	165	**315ML3**	—	IEC225M4	BX225SB4	—	—	—	—	132000	158300	43300
9.0	43700	2.6	165	**316ML3**	—	IEC225M4	BX225SB4	—	—	—	—	202000	226600	72200
9.0	43600	2.6	165	—	**317MR3C**	IEC225M4	BX225SB4	—	—	—	—	314300	333900	72100
9.4	41600	1.1	157	—	**314MR3C**	IEC225M4	BX225SB4	—	—	—	—	132000	158300	42600
9.4	41600	1.4	157	—	**315MR3C**	IEC225M4	BX225SB4	—	—	—	—	132000	158300	42600
10.6	36800	2.4	139	**315ML3**	—	IEC225M4	BX225SB4	—	—	—	—	129500	155400	40900
10.7	36600	1.9	138	**314ML3**	—	IEC225M4	BX225SB4	—	—	—	—	129400	155100	40800
11.0	35800	1.7	135	—	**314MR3C**	IEC225M4	BX225SB4	—	—	—	—	128400	154000	40500
11.0	35800	2.1	135	—	**315MR3C**	IEC225M4	BX225SB4	—	—	—	—	128400	154000	40500
11.0	35800	2.7	135	—	**316MR3C**	IEC225M4	BX225SB4	—	—	—	—	196600	220500	67500
13.0	30000	1.6	113	—	**314MR3B**	IEC225M4	BX225SB4	—	—	—	—	121900	146200	38200
13.0	30100	1.9	114	—	**314MR3C**	IEC225M4	BX225SB4	—	—	—	—	122000	146300	38300
13.0	30000	2.0	113	—	**315MR3B**	IEC225M4	BX225SB4	—	—	—	—	121900	146200	38200
13.0	30100	2.4	114	—	**315MR3C**	IEC225M4	BX225SB4	—	—	—	—	122000	146300	38300
13.7	28500	1.9	108	**314ML3**	—	IEC225M4	BX225SB4	—	—	—	—	120000	143900	37600
13.7	28500	2.0	108	—	**314MR3C**	IEC225M4	BX225SB4	—	—	—	—	120000	143900	37600
13.7	28700	2.9	108	**315ML3**	—	IEC225M4	BX225SB4	—	—	—	—	120200	144200	37600
13.7	28500	2.9	108	—	**315MR3C**	IEC225M4	BX225SB4	—	—	—	—	120000	143900	37600
15.2	25800	2.2	97.6	—	**314MR3B**	IEC225M4	BX225SB4	—	—	—	—	116500	139700	36400
15.2	25800	2.8	97.6	—	**315MR3B**	IEC225M4	BX225SB4	—	—	—	—	116500	139700	36400
16.0	24500	2.2	92.7	**314ML3**	—	IEC225M4	BX225SB4	—	—	—	—	114700	137600	35700
16.3	24000	2.6	90.7	—	**314MR3C**	IEC225M4	BX225SB4	—	—	—	—	114000	136700	35500
18.0	21800	2.5	82.3	—	**314MR3B**	IEC225M4	BX225SB4	—	—	—	—	110700	132700	34300
19.0	20600	2.6	77.8	—	**314MR3B**	IEC225M4	BX225SB4	—	—	—	—	108800	130500	33700
20.0	19600	2.6	73.9	**314ML3**	—	IEC225M4	BX225SB4	—	—	—	—	107200	128500	33100
20.9	18700	2.6	70.7	—	**314MR3C**	IEC225M4	BX225SB4	—	—	—	—	105800	126800	32700
22.6	17300	2.9	65.5	—	**314MR3B**	IEC225M4	BX225SB4	—	—	—	—	103400	124000	31800
23.6	16600	3.0	62.6	**314ML3**	—	IEC225M4	BX225SB4	—	—	—	—	102000	122300	31400
29.0	13500	2.9	51.1	—	**314MR3B**	IEC225M4	BX225SB4	—	—	—	—	95900	115000	29300
32	12800	1.4	46.7	**310ML2**	—	IEC225M4	BX225SB4	—	—	—	—	55200	70000	20500
37	11100	2.7	40.5	**313ML2**	—	IEC225M4	BX225SB4	—	—	—	—	96300	112800	24100
38	10500	1.7	38.6	**310ML2**	—	IEC225M4	BX225SB4	—	—	—	—	52100	66100	19300
38	10600	2.6	38.8	**311ML2**	—	IEC225M4	BX225SB4	—	—	—	—	65600	83700	19300
45	8880	2.3	32.6	**310ML2**	—	IEC225M4	BX225SB4	—	—	—	—	49500	62800	18200
48	8370	2.1	30.7	**310ML2**	—	IEC225M4	BX225SB4	—	—	—	—	48600	61700	17900
53	7640	2.7	28.0	**310ML2**	—	IEC225M4	BX225SB4	—	—	—	—	47300	60000	17300
58	6920	2.4	25.4	**310ML2**	—	IEC225M4	BX225SB4	—	—	—	—	45900	58300	16800
58	6910	2.5	25.3	—	**310MR2C**	IEC225M4	BX225SB4	—	—	—	—	45900	58200	16800
68	5950	2.7	21.8	**310ML2**	—	IEC225M4	BX225SB4	—	—	—	—	43900	55700	15900
197	2110	1.9	7.50	**306L1**	—	IEC225M4	BX225SB4	—	—	9250	10500	23300	26900	6010
239	1740	2.4	6.20	**306L1**	—	IEC225M4	BX225SB4	—	—	8680	9900	22000	25400	5640
278	1500	2.7	5.33	**306L1**	—	IEC225M4	BX225SB4	—	—	8260	9410	21000	24300	5370

*** The technical information shall be considered as indicative, the configurations should be matching the data provided by motors manufacturers on rated powers greater than 22 kW.**



P_1 = 55 kW

n_2	M_2	S	i			IE2*	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
1.2	375400	0.9	1195	**319L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	443400	488200	186200
1.2	402100	2.2	1279	**323L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	—	—	1053000
1.2	402100	2.4	1279	**325L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	—	—	1340200
1.3	352500	1.5	1122	**321L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	621600	739900	1104200
1.3	345900	2.5	1101	**323L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	—	—	1006500
1.3	345900	2.8	1101	**325L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	—	—	1281000
1.4	322200	2.7	1025	**323L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	—	—	985300
1.5	316300	1.1	1007	**319L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	432700	476400	175900
1.6	286300	1.0	911	**318ML4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	351100	396400	170100
1.6	286500	1.1	912	**319L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	426600	469700	170200
1.6	284800	1.1	906	—	**319R4C**	**IEC250M4**	**BX250MA4**	—	—	—	—	426300	469300	169800
1.6	297000	2.0	945	**321L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	606600	722000	1048900
1.7	267300	1.5	850	**319L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	422400	465100	166300
1.8	252100	1.3	802	**319L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	418900	461200	163100
1.9	241300	1.1	768	**318ML4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	342600	386800	160700
1.9	245000	1.3	780	—	**319R4C**	**IEC250M4**	**BX250MA4**	—	—	—	—	417200	459400	161500
1.9	250200	2.2	796	**321L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	591900	704600	996400
2.0	228200	1.2	726	**318ML4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	339900	383800	157700
2.0	231400	2.4	736	**321L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	585400	696800	973300
2.0	230100	2.3	732	—	**321R4C**	**IEC250M4**	**BX250MA4**	—	—	—	—	584900	696200	971500
2.1	217200	1.2	691	—	**318MR4C**	**IEC250M4**	**BX250MA4**	—	—	—	—	337500	381100	155200
2.1	225200	1.8	717	**319L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	412200	453900	157100
2.2	213000	1.8	678	**319L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	408900	450300	154200
2.3	203300	1.3	647	**318ML4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	334300	377500	151800
2.3	205800	1.5	655	—	**319R4B**	**IEC250M4**	**BX250MA4**	—	—	—	—	406900	448000	152400
2.3	206500	1.5	657	—	**319R4C**	**IEC250M4**	**BX250MA4**	—	—	—	—	407100	448300	152600
2.4	192200	1.4	612	**318ML4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	331700	374500	149000
2.4	196400	1.6	625	**319L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	404200	445100	150000
2.4	192300	2.7	612	**321L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	570100	678500	920600
2.4	193800	2.6	617	—	**321R4C**	**IEC250M4**	**BX250MA4**	—	—	—	—	570700	679300	922900
2.5	186900	1.4	595	—	**318MR4C**	**IEC250M4**	**BX250MA4**	—	—	—	—	330300	373000	147600
2.6	179500	2.1	571	**319L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	399100	439400	145600
2.6	177000	1.7	563	—	**319R4B**	**IEC250M4**	**BX250MA4**	—	—	—	—	398300	438500	144900
2.7	175500	2.1	558	**319L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	397800	438000	144500
2.7	174500	2.2	555	—	**319R4C**	**IEC250M4**	**BX250MA4**	—	—	—	—	397400	437600	144200
2.8	166000	2.2	528	**319L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	394600	434500	141900
2.8	165000	2.2	525	—	**319R4C**	**IEC250M4**	**BX250MA4**	—	—	—	—	394300	434100	141600
2.8	166200	2.9	529	—	**321R4B**	**IEC250M4**	**BX250MA4**	—	—	—	—	558300	664600	881200
2.9	162000	1.6	515	**318ML4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	323700	365400	140700
2.9	161800	1.8	515	**319L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	393200	432900	140700
2.9	161000	2.6	512	—	**321R4C**	**IEC250M4**	**BX250MA4**	—	—	—	—	555800	661600	872900
3.0	156900	1.6	499	—	**318MR4B**	**IEC250M4**	**BX250MA4**	—	—	—	—	322200	363800	139200
3.0	157500	1.6	501	—	**318MR4C**	**IEC250M4**	**BX250MA4**	—	—	—	—	322300	364000	139400
3.1	149800	1.7	477	**318ML4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	320100	361400	137100
3.1	148900	1.7	474	—	**318MR4C**	**IEC250M4**	**BX250MA4**	—	—	—	—	319800	361100	136800
3.1	149100	2.0	475	—	**319R4B**	**IEC250M4**	**BX250MA4**	—	—	—	—	388600	427900	136900
3.1	151000	2.6	481	—	**321R4C**	**IEC250M4**	**BX250MA4**	—	—	—	—	550700	655600	856300
3.3	139800	2.5	445	**319L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	385100	424000	134000
3.3	139000	2.5	442	—	**319R4C**	**IEC250M4**	**BX250MA4**	—	—	—	—	384800	423600	133700
3.3	140000	2.9	446	—	**321R4B**	**IEC250M4**	**BX250MA4**	—	—	—	—	544800	648500	837100
3.4	135000	1.8	430	—	**318MR4B**	**IEC250M4**	**BX250MA4**	—	—	—	—	315300	356000	132400
3.5	132800	1.9	422	**318ML4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	314600	355200	131700
3.6	129000	2.2	410	**319L4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	380700	419100	130400
3.7	126200	1.9	402	**318ML4**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	312300	352600	129500
3.7	125500	1.9	399	—	**318MR4C**	**IEC250M4**	**BX250MA4**	—	—	—	—	312100	352300	129200
3.7	126000	2.7	401	—	**319R4B**	**IEC250M4**	**BX250MA4**	—	—	—	—	379400	417700	129400
3.7	125500	2.6	399	—	**321R4C**	**IEC250M4**	**BX250MA4**	—	—	—	—	536300	638400	810000
3.9	119200	2.8	379	—	**319R4B**	**IEC250M4**	**BX250MA4**	—	—	—	—	376400	414400	127000
4.0	116300	2.9	370	—	**321R4B**	**IEC250M4**	**BX250MA4**	—	—	—	—	530600	631500	791800
4.1	113700	2.1	362	—	**318MR4B**	**IEC250M4**	**BX250MA4**	—	—	—	—	307700	347400	125100
4.3	107600	2.2	342	—	**318MR4B**	**IEC250M4**	**BX250MA4**	—	—	—	—	305300	344700	122800

*** The technical information shall be considered as indicative, the configurations should be matching the data provided by motors manufacturers on rated powers greater than 22 kW.**



P_1 = 55 kW

n_2	M_2	S	i			IE2*	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
4.3	108300	2.7	345	—	**319R4C**	IEC250M4	BX250MA4	—	—	—	—	371300	408800	123100
4.3	109100	3.0	347	—	**321R4B**	IEC250M4	BX250MA4	—	—	—	—	525700	625800	776700
4.4	105800	2.2	337	**318ML4**	—	IEC250M4	BX250MA4	—	—	—	—	304500	343900	122100
4.6	100400	3.0	320	—	**319R4B**	IEC250M4	BX250MA4	—	—	—	—	367300	404400	120000
4.7	98400	2.4	313	**318ML4**	—	IEC250M4	BX250MA4	—	—	—	—	301400	340300	119200
4.8	97800	2.4	311	—	**318MR4C**	IEC250M4	BX250MA4	—	—	—	—	301100	340000	118900
4.8	96300	2.6	306	—	**321R4C**	IEC250M4	BX250MA4	—	—	—	—	516400	614700	748100
5.1	90600	2.6	288	—	**318MR4B**	IEC250M4	BX250MA4	—	—	—	—	299000	337600	115900
5.1	90600	2.9	288	—	**321R4B**	IEC250M4	BX250MA4	—	—	—	—	513900	611700	734700
5.6	82400	2.8	262	**318ML4**	—	IEC250M4	BX250MA4	—	—	—	—	299000	337600	112300
5.9	81800	1.4	252	**317ML3**	—	IEC250M4	BX250MA4	—	—	—	—	314300	333900	83200
5.9	78200	3.0	249	—	**319R4B**	IEC250M4	BX250MA4	—	—	—	—	363300	400000	110400
6.6	70600	3.0	225	—	**318MR4B**	IEC250M4	BX250MA4	—	—	—	—	299000	337600	106700
6.7	69500	3.0	221	—	**321R4B**	IEC250M4	BX250MA4	—	—	—	—	513900	611700	678500
7.0	68900	2.1	213	**317ML3**	—	IEC250M4	BX250MA4	—	—	—	—	314300	333900	78600
7.1	67100	1.1	207	**315ML3**	—	IEC250M4	BX250MA4	—	—	—	—	132000	158300	46700
7.1	67100	1.5	207	**316ML3**	—	IEC250M4	BX250MA4	—	—	—	—	202000	226600	77900
7.2	66800	0.9	206	**314ML3**	—	IEC250M4	BX250MA4	—	—	—	—	132000	158300	46600
8.3	58000	2.5	179	**317ML3**	—	IEC250M4	BX250MA4	—	—	—	—	314300	333900	74200
8.5	56200	1.1	174	**314ML3**	—	IEC250M4	BX250MA4	—	—	—	—	132000	158300	44100
8.5	56500	1.3	174	**315ML3**	—	IEC250M4	BX250MA4	—	—	—	—	132000	158300	44100
8.5	56500	1.8	174	**316ML3**	—	IEC250M4	BX250MA4	—	—	—	—	202000	226600	73500
8.9	53700	2.3	166	**317ML3**	—	IEC250M4	BX250MA4	—	—	—	—	314300	333900	72300
9.0	53200	1.1	164	**314ML3**	—	IEC250M4	BX250MA4	—	—	—	—	132000	158300	43200
9.0	53500	1.7	165	**315ML3**	—	IEC250M4	BX250MA4	—	—	—	—	132000	158300	43300
9.0	53500	2.1	165	**316ML3**	—	IEC250M4	BX250MA4	—	—	—	—	202000	226600	72200
9.0	53400	2.1	165	—	**317MR3C**	IEC250M4	BX250MA4	—	—	—	—	314300	333900	72100
9.4	50900	0.9	157	—	**314MR3C**	IEC250M4	BX250MA4	—	—	—	—	132000	158300	42600
9.4	50900	1.2	157	—	**315MR3C**	IEC250M4	BX250MA4	—	—	—	—	132000	158300	42600
10.6	45000	2.0	139	**315ML3**	—	IEC250M4	BX250MA4	—	—	—	—	129500	155400	40900
10.6	45000	2.6	139	**316ML3**	—	IEC250M4	BX250MA4	—	—	—	—	198200	222400	68200
10.7	44800	1.6	138	**314ML3**	—	IEC250M4	BX250MA4	—	—	—	—	129400	155100	40800
10.7	45000	2.7	139	—	**317MR3C**	IEC250M4	BX250MA4	—	—	—	—	308300	327500	68100
11.0	43800	1.4	135	—	**314MR3C**	IEC250M4	BX250MA4	—	—	—	—	128400	154000	40500
11.0	43800	1.7	135	—	**315MR3C**	IEC250M4	BX250MA4	—	—	—	—	128400	154000	40500
11.0	43800	2.2	135	—	**316MR3C**	IEC250M4	BX250MA4	—	—	—	—	196600	220500	67500
12.4	38500	2.8	119	—	**317MR3B**	IEC250M4	BX250MA4	—	—	—	—	294400	312700	64700
12.6	38000	2.9	117	**316ML3**	—	IEC250M4	BX250MA4	—	—	—	—	188300	211200	64400
12.8	37400	2.7	115	—	**317MR3C**	IEC250M4	BX250MA4	—	—	—	—	291600	309800	64100
13.0	36800	1.3	113	—	**314MR3B**	IEC250M4	BX250MA4	—	—	—	—	121900	146200	38200
13.0	36900	1.6	114	—	**314MR3C**	IEC250M4	BX250MA4	—	—	—	—	122000	146300	38300
13.0	36800	1.6	113	—	**315MR3B**	IEC250M4	BX250MA4	—	—	—	—	121900	146200	38200
13.0	36900	2.0	114	—	**315MR3C**	IEC250M4	BX250MA4	—	—	—	—	122000	146300	38300
13.0	36900	2.6	114	**316ML3**	—	IEC250M4	BX250MA4	—	—	—	—	186800	209500	63800
13.0	36900	2.5	114	—	**316MR3C**	IEC250M4	BX250MA4	—	—	—	—	186700	209500	63800
13.7	34900	1.6	108	**314ML3**	—	IEC250M4	BX250MA4	—	—	—	—	120000	143900	37600
13.7	34900	1.6	108	—	**314MR3C**	IEC250M4	BX250MA4	—	—	—	—	120000	143900	37600
13.7	35100	2.4	108	**315ML3**	—	IEC250M4	BX250MA4	—	—	—	—	120200	144200	37600
13.7	34900	2.4	108	—	**315MR3C**	IEC250M4	BX250MA4	—	—	—	—	120000	143900	37600
13.7	34900	2.7	108	—	**316MR3C**	IEC250M4	BX250MA4	—	—	—	—	183600	206000	62600
13.7	35000	2.7	108	—	**317MR3C**	IEC250M4	BX250MA4	—	—	—	—	286100	303900	62700
14.8	32500	3.0	100	—	**317MR3B**	IEC250M4	BX250MA4	—	—	—	—	279600	297100	61100
15.2	31600	1.8	97.6	—	**314MR3B**	IEC250M4	BX250MA4	—	—	—	—	116500	139700	36400
15.2	31600	2.3	97.6	—	**315MR3B**	IEC250M4	BX250MA4	—	—	—	—	116500	139700	36400
15.2	31600	2.8	97.6	—	**316MR3B**	IEC250M4	BX250MA4	—	—	—	—	178300	200000	60600
16.0	30000	1.8	92.7	**314ML3**	—	IEC250M4	BX250MA4	—	—	—	—	114700	137600	35700
16.2	29600	2.7	91.3	**315ML3**	—	IEC250M4	BX250MA4	—	—	—	—	114200	136900	35600
16.3	29400	2.1	90.7	—	**314MR3C**	IEC250M4	BX250MA4	—	—	—	—	114000	136700	35500
16.3	29400	2.6	90.7	—	**315MR3C**	IEC250M4	BX250MA4	—	—	—	—	114000	136700	35500
16.3	29400	2.7	90.7	—	**316MR3C**	IEC250M4	BX250MA4	—	—	—	—	174400	195700	59100
16.5	29100	2.7	89.8	—	**317MR3C**	IEC250M4	BX250MA4	—	—	—	—	270600	287500	59000

*** The technical information shall be considered as indicative, the configurations should be matching the data provided by motors manufacturers on rated powers greater than 22 kW.**



P_1 = 55 kW

n_2	M_2	S	i			IE2*	IE3	IE2	IE3	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ
min^{-1}	Nm													
16.7	28700	2.7	88.7	—	**316MR3C**	**IEC250M4**	**BX250MA4**	—	—	—	—	173300	194400	58700
17.8	27000	3.0	83.3	—	**317MR3B**	**IEC250M4**	**BX250MA4**	—	—	—	—	264500	281000	57500
18.0	26600	2.0	82.3	—	**314MR3B**	**IEC250M4**	**BX250MA4**	—	—	—	—	110700	132700	34300
18.0	26600	2.6	82.3	—	**315MR3B**	**IEC250M4**	**BX250MA4**	—	—	—	—	110700	132700	34300
18.0	26600	3.0	82.3	—	**316MR3B**	**IEC250M4**	**BX250MA4**	—	—	—	—	169400	190000	57200
18.9	25300	3.0	78.1	—	**317MR3B**	**IEC250M4**	**BX250MA4**	—	—	—	—	259500	275600	56300
19.0	25200	2.1	77.8	—	**314MR3B**	**IEC250M4**	**BX250MA4**	—	—	—	—	108800	130500	33700
19.0	25200	2.9	77.8	—	**315MR3B**	**IEC250M4**	**BX250MA4**	—	—	—	—	108800	130500	33700
19.0	25200	3.0	77.8	—	**316MR3B**	**IEC250M4**	**BX250MA4**	—	—	—	—	166600	186800	56200
20.0	23900	2.1	73.9	**314ML3**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	107200	128500	33100
20.9	22900	2.2	70.7	—	**314MR3C**	**IEC250M4**	**BX250MA4**	—	—	—	—	105800	126800	32700
20.9	22900	2.7	70.7	—	**315MR3C**	**IEC250M4**	**BX250MA4**	—	—	—	—	105800	126800	32700
20.9	22900	2.7	70.7	—	**316MR3C**	**IEC250M4**	**BX250MA4**	—	—	—	—	161800	181600	54400
21.5	22300	2.7	68.9	—	**317MR3C**	**IEC250M4**	**BX250MA4**	—	—	—	—	249900	265500	54000
22.6	21200	2.4	65.5	—	**314MR3B**	**IEC250M4**	**BX250MA4**	—	—	—	—	103400	124000	31800
22.6	21200	3.0	65.5	—	**315MR3B**	**IEC250M4**	**BX250MA4**	—	—	—	—	103400	124000	31800
22.6	21200	3.0	65.5	—	**316MR3B**	**IEC250M4**	**BX250MA4**	—	—	—	—	158200	177500	53100
22.8	21000	3.0	64.9	—	**317MR3B**	**IEC250M4**	**BX250MA4**	—	—	—	—	245400	260700	52900
23.1	20800	3.0	64.1	—	**316MR3B**	**IEC250M4**	**BX250MA4**	—	—	—	—	157100	176300	52700
23.6	20300	2.4	62.6	**314ML3**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	102000	122300	31400
29.0	16500	2.4	51.1	—	**314MR3B**	**IEC250M4**	**BX250MA4**	—	—	—	—	95900	115000	29300
29.0	16500	3.0	51.1	—	**315MR3B**	**IEC250M4**	**BX250MA4**	—	—	—	—	95900	115000	29300
29.0	16500	3.0	51.1	—	**316MR3B**	**IEC250M4**	**BX250MA4**	—	—	—	—	146800	164700	48800
29.7	16100	3.0	49.8	—	**317MR3B**	**IEC250M4**	**BX250MA4**	—	—	—	—	226700	240800	48400
32	15600	1.1	46.7	**310ML2**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	55200	70000	20500
37	13500	2.2	40.5	**313ML2**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	96300	112800	24100
38	12900	1.4	38.6	**310ML2**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	52100	66100	19300
38	13000	2.1	38.8	**311ML2**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	65600	83700	19300
45	10900	1.9	32.6	**310ML2**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	49500	62800	18200
45	10900	2.6	32.7	**311ML2**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	62300	79500	18200
48	10200	1.7	30.7	**310ML2**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	48600	61700	17900
53	9350	2.2	28.0	**310ML2**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	47300	60000	17300
56	8830	2.7	26.4	—	**313MR2C**	**IEC250M4**	**BX250MA4**	—	—	—	—	84700	99200	20900
58	8470	2.0	25.4	**310ML2**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	45900	58300	16800
58	8460	2.1	25.3	—	**310MR2C**	**IEC250M4**	**BX250MA4**	—	—	—	—	45900	58200	16800
58	8510	2.7	25.5	**311ML2**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	57800	73700	16800
58	8460	2.7	25.3	—	**311MR2C**	**IEC250M4**	**BX250MA4**	—	—	—	—	57700	73600	16800
67	7340	2.7	22.0	—	**313MR2C**	**IEC250M4**	**BX250MA4**	—	—	—	—	80100	93900	19700
68	7290	2.2	21.8	**310ML2**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	43900	55700	15900
69	7130	2.6	21.3	—	**310MR2C**	**IEC250M4**	**BX250MA4**	—	—	—	—	43600	55300	15800
69	7170	2.9	21.5	**311ML2**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	54900	70100	15900
69	7130	2.7	21.3	—	**311MR2C**	**IEC250M4**	**BX250MA4**	—	—	—	—	54800	69900	15800
78	6380	3.0	19.1	—	**313MR2B**	**IEC250M4**	**BX250MA4**	—	—	—	—	76800	90000	18800
81	6110	3.0	18.3	—	**311MR2B**	**IEC250M4**	**BX250MA4**	—	—	—	—	52300	66800	15000
85	5810	2.7	17.4	**310ML2**	—	**IEC250M4**	**BX250MA4**	—	—	—	—	41000	52000	14800
88	5630	2.7	16.8	—	**313MR2C**	**IEC250M4**	**BX250MA4**	—	—	—	—	74000	86700	18000
89	5560	2.7	16.6	—	**310MR2C**	**IEC250M4**	**BX250MA4**	—	—	—	—	40500	51300	14600
89	5560	2.7	16.6	—	**311MR2C**	**IEC250M4**	**BX250MA4**	—	—	—	—	50900	64900	14600
93	5300	3.0	15.9	—	**313MR2B**	**IEC250M4**	**BX250MA4**	—	—	—	—	72700	85200	17600
96	5150	3.0	15.4	—	**311MR2B**	**IEC250M4**	**BX250MA4**	—	—	—	—	49700	63400	14200
122	4060	3.0	12.2	—	**313MR2B**	**IEC250M4**	**BX250MA4**	—	—	—	—	67100	78600	16100
123	4010	3.0	12.0	—	**311MR2B**	**IEC250M4**	**BX250MA4**	—	—	—	—	46100	58900	13100
197	2580	1.6	7.50	**306L1**	—	**IEC250M4**	**BX250MA4**	—	—	9250	10500	23300	26900	6010
238	2150	2.7	6.23	**307L1**	—	**IEC250M4**	**BX250MA4**	—	—	10400	13000	26100	34300	7270
239	2130	2.0	6.20	**306L1**	—	**IEC250M4**	**BX250MA4**	—	—	8680	9900	22000	25400	5640
278	1840	2.2	5.33	**306L1**	—	**IEC250M4**	**BX250MA4**	—	—	8260	9410	21000	24300	5370
348	1460	2.7	4.25	**306L1**	—	**IEC250M4**	**BX250MA4**	—	—	7660	8730	19600	22700	4970

*** The technical information shall be considered as indicative, the configurations should be matching the data provided by motors manufacturers on rated powers greater than 22 kW.**



25.2 3/V_M - 3/A GEARMOTOR RATING CHARTS

Reading the rating chart.



1	Power applied at gearbox input shaft
2	Gearbox output speed
3	Torque delivered at output shaft: - specified service factor - 10000 h theoretical lifetime
4	Service factor
5	Gear ratio
6	Model and frame size of combined planetary + worm gear unit
7	Model and frame size of combined planetary + helical bevel gear unit
8	IEC motor size and pole number
9	Compact motor size and pole number
10	Permitted overhung loading on output shaft, based on: - service factor f_S=1 - 10000 h theoretical lifetime - speed of output n_2 For forces not applied at shaft middlepoint, see diagrams provided in the specific gearbox overall dimensioning pages
11	Dimensions page. Gearmotor overall dimensions refer to matches with BONFIGLIOLI motors only



Index with reference to the size page.
Gearmotor sizes refer to combinations with BONFIGLIOLI-manufactured motors

3/A 00 L2	267
3/A 01 L2	277
3/A 03 L2	287
3/A 04 L2	299
3/A 05 L2	311
3/A 06 L2	323
3/A 07 L2	335

3/V 00 L3	266
3/V 01 L3	276
3/V 03 L3	286
3/V 04 L3	298
3/V 05 L3	310
3/V 06 L3	322
3/V 07 L3	334
3/V 09 L3	346
3/V 10M L3	358
3/V 10M L4	359
3/V 11M L3	370
3/V 11M L4	371

3/V 13M L3	382
3/V 13M L4	383
3/V 14M L3	394
3/V 14M L4	395
3/V 15M L3	406
3/V 15M L4	407
3/V 16M L3	418
3/V 16M L4	419
3/V 17M L3	428
3/V 17M L4	429
3/V 18M L4	438
3/V 19 L4	448
3/V 21 L4	458



The selection of motors takes into account the requirements of Regulation 2009/125/CE (see section M of this catalogue). When the motor rated power is below 0,12kW, **BN/M** motors can be provided. Starting from 1st July 2021 the regulation 2009/125/CE will apply also to motors equipped with brake, and 8 poles motors.

A

P_1 = 0.12 kW

n_2	M_2	S	i							Rn_2 [N]				
min^{-1}	Nm					IE1	IE2	IE1	IE2	MC/PC	MZ/PZ	HC	HZ	FZ
0.58	1180	1.5	2337	**3/V01L3**	**—**	**BN63A4**	**BE63A4**	**—**	**—**	8710	8710	28800	31500	8000
0.72	940	0.9	1869	**3/V00L3**	**—**	**BN63A4**	**BE63A4**	**—**	**—**	8440	8440	27900	32500	8000
0.72	940	1.8	1869	**3/V01L3**	**—**	**BN63A4**	**BE63A4**	**—**	**—**	8440	8440	27900	30500	8000
0.90	800	1.1	1495	**3/V00L3**	**—**	**BN63A4**	**BE63A4**	**—**	**—**	8180	8180	27000	31400	7990
0.90	800	2.1	1495	**3/V01L3**	**—**	**BN63A4**	**BE63A4**	**—**	**—**	8180	8180	27000	29600	7990
0.98	700	1.8	1381	**3/V00L3**	**—**	**BN63A4**	**BE63A4**	**—**	**—**	8080	8080	26700	31100	7780
0.98	700	2.7	1381	**3/V01L3**	**—**	**BN63A4**	**BE63A4**	**—**	**—**	8080	8080	26700	29200	7780
1.1	640	1.3	1198	**3/V00L3**	**—**	**BN63A4**	**BE63A4**	**—**	**—**	7920	7920	26200	30500	7420
1.1	640	2.6	1198	**3/V01L3**	**—**	**BN63A4**	**BE63A4**	**—**	**—**	7920	7920	26200	28600	7420
1.2	560	2.1	1107	**3/V00L3**	**—**	**BN63A4**	**BE63A4**	**—**	**—**	7830	7830	25900	30100	7230
1.4	600	1.3	997	**3/V00L3**	**—**	**BN63A4**	**BE63A4**	**—**	**—**	7720	7720	25500	29700	6980
1.4	600	2.7	997	**3/V01L3**	**—**	**BN63A4**	**BE63A4**	**—**	**—**	7720	7720	25500	27900	6980
1.5	455	1.7	903	**3/V00L3**	**—**	**BN63A4**	**BE63A4**	**—**	**—**	7610	7610	25200	29300	6760
1.5	455	2.7	903	**3/V01L3**	**—**	**BN63A4**	**BE63A4**	**—**	**—**	7610	7610	25200	27500	6760
1.7	410	2.7	818	**3/V00L3**	**—**	**BN63A4**	**BE63A4**	**—**	**—**	7500	7500	24800	28900	6540
2.0	520	1.2	660	**—**	**3/A00L2**	**BN63A4**	**BE63A4**	**M05A4**	**ME05A4**	7270	7270	24100	28000	6080
2.0	530	2.2	665	**—**	**3/A01L2**	**BN63A4**	**BE63A4**	**M05A4**	**ME05A4**	7280	7280	24100	26300	6100
2.0	390	2.8	689	**3/V00L3**	**—**	**BN63A4**	**BE63A4**	**—**	**—**	7320	7320	24200	28200	6170
2.4	320	2.3	562	**3/V00L3**	**—**	**BN63A4**	**BE63A4**	**—**	**—**	7110	7110	23500	27300	5770
2.5	435	1.4	550	**—**	**3/A00L2**	**BN63A4**	**BE63A4**	**M05A4**	**ME05A4**	7090	7090	23400	27300	5730
2.5	420	2.7	533	**—**	**3/A01L2**	**BN63A4**	**BE63A4**	**M05A4**	**ME05A4**	7060	7060	23300	25500	5660
3.1	350	2.0	441	**—**	**3/A00L2**	**BN63A4**	**BE63A4**	**M05A4**	**ME05A4**	6870	6870	22700	26400	5320
3.4	310	2.7	393	**—**	**3/A01L2**	**BN63A4**	**BE63A4**	**M05A4**	**ME05A4**	6760	6760	22300	24400	5120
3.5	310	1.7	391	**—**	**3/A00L2**	**BN63A4**	**BE63A4**	**M05A4**	**ME05A4**	6750	6750	22300	26000	5110
3.7	290	1.9	369	**—**	**3/A00L2**	**BN63A4**	**BE63A4**	**M05A4**	**ME05A4**	6700	6700	22100	25800	5010
4.2	250	1.7	319	**—**	**3/A00L2**	**BN63A4**	**BE63A4**	**M05A4**	**ME05A4**	6560	6560	21700	25200	4770
4.6	235	2.8	296	**—**	**3/A00L2**	**BN63A4**	**BE63A4**	**M05A4**	**ME05A4**	6500	6500	21500	25000	4660
5.3	200	2.7	253	**—**	**3/A00L2**	**BN63A4**	**BE63A4**	**M05A4**	**ME05A4**	6500	6500	21500	25000	4420

P_1 = 0.12 kW

n_2	M_2	S	i					Rn_2 [N]				
min^{-1}	Nm					IE3	IE3	MC/PC	MZ/PZ	HC	HZ	FZ
0.58	1180	1.5	2337	**3/V01L3**	**—**	**BXN63MA4**	**—**	8710	8710	28800	31500	8000
0.72	940	0.9	1869	**3/V00L3**	**—**	**BXN63MA4**	**—**	8440	8440	27900	32500	8000
0.72	940	1.8	1869	**3/V01L3**	**—**	**BXN63MA4**	**—**	8440	8440	27900	30500	8000
0.90	800	1.1	1495	**3/V00L3**	**—**	**BXN63MA4**	**—**	8180	8180	27000	31400	7990
0.90	800	2.1	1495	**3/V01L3**	**—**	**BXN63MA4**	**—**	8180	8180	27000	29600	7990
0.98	700	1.8	1381	**3/V00L3**	**—**	**BXN63MA4**	**—**	8080	8080	26700	31100	7780
0.98	700	2.7	1381	**3/V01L3**	**—**	**BXN63MA4**	**—**	8080	8080	26700	29200	7780
1.1	640	1.3	1198	**3/V00L3**	**—**	**BXN63MA4**	**—**	7920	7920	26200	30500	7420
1.1	640	2.6	1198	**3/V01L3**	**—**	**BXN63MA4**	**—**	7920	7920	26200	28600	7420
1.2	560	2.1	1107	**3/V00L3**	**—**	**BXN63MA4**	**—**	7830	7830	25900	30100	7230



P_1 = 0.12 kW

n_2 min^{-1}	M_2 Nm	S	i			IE3	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
1.4	600	1.3	997	**3/V00L3**	**—**	**BXN63MA4**	**—**	7720	7720	25500	29700	6980
1.4	600	2.7	997	**3/V01L3**	**—**	**BXN63MA4**	**—**	7720	7720	25500	27900	6980
1.5	455	1.7	903	**3/V00L3**	**—**	**BXN63MA4**	**—**	7610	7610	25200	29300	6760
1.5	455	2.7	903	**3/V01L3**	**—**	**BXN63MA4**	**—**	7610	7610	25200	27500	6760
1.7	410	2.7	818	**3/V00L3**	**—**	**BXN63MA4**	**—**	7500	7500	24800	28900	6540
2.0	520	1.2	660	**—**	**3/A00L2**	**BXN63MA4**	**MXN05MA4**	7270	7270	24100	28000	6080
2.0	530	2.2	665	**—**	**3/A01L2**	**BXN63MA4**	**MXN05MA4**	7280	7280	24100	26300	6100
2.0	390	2.8	689	**3/V00L3**	**—**	**BXN63MA4**	**—**	7320	7320	24200	28200	6170
2.4	320	2.3	562	**3/V00L3**	**—**	**BXN63MA4**	**—**	7110	7110	23500	27300	5770
2.5	435	1.4	550	**—**	**3/A00L2**	**BXN63MA4**	**MXN05MA4**	7090	7090	23400	27300	5730
2.5	420	2.7	533	**—**	**3/A01L2**	**BXN63MA4**	**MXN05MA4**	7060	7060	23300	25500	5660
3.1	350	2.0	441	**—**	**3/A00L2**	**BXN63MA4**	**MXN05MA4**	6870	6870	22700	26400	5320
3.4	310	2.7	393	**—**	**3/A01L2**	**BXN63MA4**	**MXN05MA4**	6760	6760	22300	24400	5120
3.5	310	1.7	391	**—**	**3/A00L2**	**BXN63MA4**	**MXN05MA4**	6750	6750	22300	26000	5110
3.7	290	1.9	369	**—**	**3/A00L2**	**BXN63MA4**	**MXN05MA4**	6700	6700	22100	25800	5010
4.2	250	1.7	319	**—**	**3/A00L2**	**BXN63MA4**	**MXN05MA4**	6560	6560	21700	25200	4770
4.6	235	2.8	296	**—**	**3/A00L2**	**BXN63MA4**	**MXN05MA4**	6500	6500	21500	25000	4660
5.3	200	2.7	253	**—**	**3/A00L2**	**BXN63MA4**	**MXN05MA4**	6500	6500	21500	25000	4420

P_1 = 0.18 kW

n_2 min^{-1}	M_2 Nm	S	i			IE1	IE2	IE1	IE2	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
0.56	1800	1.0	2337	**3/V01L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	8710	8710	28800	31500	8000
0.71	1440	1.2	1869	**3/V01L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	8440	8440	27900	30500	8000
0.88	1230	1.4	1495	**3/V01L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	8180	8180	27000	29600	7990
0.96	1060	1.2	1381	**3/V00L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	8080	8080	26700	31100	7780
0.96	1060	1.8	1381	**3/V01L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	8080	8080	26700	29200	7780
1.1	980	1.7	1198	**3/V01L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	7920	7920	26200	28600	7420
1.2	850	1.4	1107	**3/V00L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	7830	7830	25900	30100	7230
1.2	910	2.2	1105	**3/V01L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	7830	7830	25900	28300	7230
1.3	910	1.7	997	**3/V01L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	7720	7720	25500	27900	6980
1.5	700	1.1	903	**3/V00L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	7610	7610	25200	29300	6760
1.5	700	1.8	903	**3/V01L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	7610	7610	25200	27500	6760
1.6	630	1.8	818	**3/V00L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	7500	7500	24800	28900	6540
1.7	730	2.1	799	**3/V01L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	7480	7480	24700	27000	6480
1.8	880	2.0	731	**—**	**3/A03L2**	**BN63B4**	**BE63B4**	**—**	**—**	23900	27300	46000	54500	18900
1.9	600	1.8	689	**3/V00L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	7320	7320	24200	28200	6170
1.9	600	2.9	689	**3/V01L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	7320	7320	24200	26500	6170
2.0	810	1.4	665	**—**	**3/A01L2**	**BN63B4**	**BE63B4**	**M05B4**	**ME05B4**	7280	7280	24100	26300	6100
2.0	540	2.0	654	**3/V00L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	7270	7270	24000	27900	6070
2.0	540	2.2	654	**3/V01L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	7270	7270	24000	26300	6070
2.2	730	2.5	605	**—**	**3/A03L2**	**BN63B4**	**BE63B4**	**—**	**—**	23200	26500	44800	53100	17700
2.3	690	2.5	574	**—**	**3/A03L2**	**BN63B4**	**BE63B4**	**—**	**—**	23000	26300	44400	52700	17400
2.3	490	1.5	562	**3/V00L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	7110	7110	23500	27300	5770
2.3	490	2.9	562	**3/V01L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	7110	7110	23500	25700	5770
2.5	650	1.7	533	**—**	**3/A01L2**	**BN63B4**	**BE63B4**	**M05B4**	**ME05B4**	7060	7060	23300	25500	5660
2.6	440	2.4	509	**3/V00L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	7010	7010	23200	27000	5580
2.6	440	2.9	509	**3/V01L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	7010	7010	23200	25300	5580
2.7	600	2.9	495	**—**	**3/A03L2**	**BN63B4**	**BE63B4**	**—**	**—**	22600	25800	43500	51600	16600
2.9	550	2.1	454	**—**	**3/A01L2**	**BN63B4**	**BE63B4**	**M05B4**	**ME05B4**	6900	6900	22800	24900	5370
3.0	530	1.3	441	**—**	**3/A00L2**	**BN63B4**	**BE63B4**	**M05B4**	**ME05B4**	6870	6870	22700	26400	5320
3.0	355	2.0	436	**3/V00L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	6860	6860	22700	26400	5300
3.2	360	2.8	415	**3/V00L3**	**—**	**BN63B4**	**BE63B4**	**—**	**—**	6810	6810	22500	26200	5210
3.4	475	1.1	391	**—**	**3/A00L2**	**BN63B4**	**BE63B4**	**M05B4**	**ME05B4**	6750	6750	22300	26000	5110
3.4	475	1.7	393	**—**	**3/A01L2**	**BN63B4**	**BE63B4**	**M05B4**	**ME05B4**	6760	6760	22300	24400	5120
3.6	445	1.3	369	**—**	**3/A00L2**	**BN63B4**	**BE63B4**	**M05B4**	**ME05B4**	6700	6700	22100	25800	5010
4.1	385	1.1	319	**—**	**3/A00L2**	**BN63B4**	**BE63B4**	**M05B4**	**ME05B4**	6560	6560	21700	25200	4770
4.5	360	1.8	296	**—**	**3/A00L2**	**BN63B4**	**BE63B4**	**M05B4**	**ME05B4**	6500	6500	21500	25000	4660
5.2	305	1.8	253	**—**	**3/A00L2**	**BN63B4**	**BE63B4**	**M05B4**	**ME05B4**	6500	6500	21500	25000	4420
6.0	265	2.3	219	**—**	**3/A00L2**	**BN63B4**	**BE63B4**	**M05B4**	**ME05B4**	6500	6500	21500	25000	4210
6.5	245	2.6	203	**—**	**3/A00L2**	**BN63B4**	**BE63B4**	**M05B4**	**ME05B4**	6500	6500	21500	25000	4100
7.7	205	2.7	171	**—**	**3/A00L2**	**BN63B4**	**BE63B4**	**M05B4**	**ME05B4**	6500	6500	21500	25000	3880



A

P_1 = 0.18 kW

n_2 min^{-1}	M_2 Nm	S	i			IE3	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
0.56	1800	1.0	2337	**3/V01L3**	**—**	**BXN63MB4**	**—**	8710	8710	28800	31500	8000
0.71	1440	1.2	1869	**3/V01L3**	**—**	**BXN63MB4**	**—**	8440	8440	27900	30500	8000
0.88	1230	1.4	1495	**3/V01L3**	**—**	**BXN63MB4**	**—**	8180	8180	27000	29600	7990
0.96	1060	1.2	1381	**3/V00L3**	**—**	**BXN63MB4**	**—**	8080	8080	26700	31100	7780
0.96	1060	1.8	1381	**3/V01L3**	**—**	**BXN63MB4**	**—**	8080	8080	26700	29200	7780
1.1	980	1.7	1198	**3/V01L3**	**—**	**BXN63MB4**	**—**	7920	7920	26200	28600	7420
1.2	850	1.4	1107	**3/V00L3**	**—**	**BXN63MB4**	**—**	7830	7830	25900	30100	7230
1.2	910	2.2	1105	**3/V01L3**	**—**	**BXN63MB4**	**—**	7830	7830	25900	28300	7230
1.3	910	1.7	997	**3/V01L3**	**—**	**BXN63MB4**	**—**	7720	7720	25500	27900	6980
1.5	700	1.1	903	**3/V00L3**	**—**	**BXN63MB4**	**—**	7610	7610	25200	29300	6760
1.5	700	1.8	903	**3/V01L3**	**—**	**BXN63MB4**	**—**	7610	7610	25200	27500	6760
1.6	630	1.8	818	**3/V00L3**	**—**	**BXN63MB4**	**—**	7500	7500	24800	28900	6540
1.7	730	2.1	799	**3/V01L3**	**—**	**BXN63MB4**	**—**	7480	7480	24700	27000	6480
1.8	880	2.0	731	**—**	**3/A03L2**	**BXN63MB4**	**—**	23900	27300	46000	54500	18900
1.9	600	1.8	689	**3/V00L3**	**—**	**BXN63MB4**	**—**	7320	7320	24200	28200	6170
1.9	600	2.9	689	**3/V01L3**	**—**	**BXN63MB4**	**—**	7320	7320	24200	26500	6170
2.0	810	1.4	665	**—**	**3/A01L2**	**BXN63MB4**	**MXN05MB4**	7280	7280	24100	26300	6100
2.0	540	2.0	654	**3/V00L3**	**—**	**BXN63MB4**	**—**	7270	7270	24000	27900	6070
2.0	540	2.2	654	**3/V01L3**	**—**	**BXN63MB4**	**—**	7270	7270	24000	26300	6070
2.2	730	2.5	605	**—**	**3/A03L2**	**BXN63MB4**	**—**	23200	26500	44800	53100	17700
2.3	690	2.5	574	**—**	**3/A03L2**	**BXN63MB4**	**—**	23000	26300	44400	52700	17400
2.3	490	1.5	562	**3/V00L3**	**—**	**BXN63MB4**	**—**	7110	7110	23500	27300	5770
2.3	490	2.9	562	**3/V01L3**	**—**	**BXN63MB4**	**—**	7110	7110	23500	25700	5770
2.5	650	1.7	533	**—**	**3/A01L2**	**BXN63MB4**	**MXN05MB4**	7060	7060	23300	25500	5660
2.6	440	2.4	509	**3/V00L3**	**—**	**BXN63MB4**	**—**	7010	7010	23200	27000	5580
2.6	440	2.9	509	**3/V01L3**	**—**	**BXN63MB4**	**—**	7010	7010	23200	25300	5580
2.7	600	2.9	495	**—**	**3/A03L2**	**BXN63MB4**	**—**	22600	25800	43500	51600	16600
2.9	550	2.1	454	**—**	**3/A01L2**	**BXN63MB4**	**MXN05MB4**	6900	6900	22800	24900	5370
3.0	530	1.3	441	**—**	**3/A00L2**	**BXN63MB4**	**MXN05MB4**	6870	6870	22700	26400	5320
3.0	355	2.0	436	**3/V00L3**	**—**	**BXN63MB4**	**—**	6860	6860	22700	26400	5300
3.2	360	2.8	415	**3/V00L3**	**—**	**BXN63MB4**	**—**	6810	6810	22500	26200	5210
3.4	475	1.1	391	**—**	**3/A00L2**	**BXN63MB4**	**MXN05MB4**	6750	6750	22300	26000	5110
3.4	475	1.7	393	**—**	**3/A01L2**	**BXN63MB4**	**MXN05MB4**	6760	6760	22300	24400	5120
3.6	445	1.3	369	**—**	**3/A00L2**	**BXN63MB4**	**MXN05MB4**	6700	6700	22100	25800	5010
4.1	385	1.1	319	**—**	**3/A00L2**	**BXN63MB4**	**MXN05MB4**	6560	6560	21700	25200	4770
4.5	360	1.8	296	**—**	**3/A00L2**	**BXN63MB4**	**MXN05MB4**	6500	6500	21500	25000	4660
5.2	305	1.8	253	**—**	**3/A00L2**	**BXN63MB4**	**MXN05MB4**	6500	6500	21500	25000	4420
6.0	265	2.3	219	**—**	**3/A00L2**	**BXN63MB4**	**MXN05MB4**	6500	6500	21500	25000	4210
6.5	245	2.6	203	**—**	**3/A00L2**	**BXN63MB4**	**MXN05MB4**	6500	6500	21500	25000	4100
7.7	205	2.7	171	**—**	**3/A00L2**	**BXN63MB4**	**MXN05MB4**	6500	6500	21500	25000	3880

P_1 = 0.25 kW

n_2 min^{-1}	M_2 Nm	S	i			IE1	IE2	IE1	IE2	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
0.53	3080	2.3	2588	**3/V06L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	34000	38800	77500	89500	35000
0.58	2770	1.1	2366	**3/V04L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	28200	32200	54400	64500	24000
0.62	2620	1.7	2232	**3/V05L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	28000	32000	53900	63900	24000
0.69	2190	1.1	2009	**3/V03L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	27600	31500	53100	63000	24000
0.73	2220	1.4	1893	**3/V04L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	27300	31200	52700	62400	24000
0.77	2090	2.2	1786	**3/V05L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	27100	31000	52300	61900	24000
0.78	2220	1.3	1774	**3/V04L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	27100	30900	52200	61900	24000
0.80	1880	1.5	1728	**3/V03L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	27000	30800	52000	61600	24000
0.82	2100	2.1	1674	**3/V05L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	26800	30700	51800	61400	24000
0.86	1760	1.4	1610	**3/V03L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	26700	30500	51500	61000	24000
0.90	1800	2.1	1536	**3/V04L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	26500	30300	51100	60600	24000
0.92	1630	1.1	1495	**3/V01L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	8180	8180	27000	29600	7990
0.96	1680	2.8	1431	**3/V05L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	26300	30000	50600	60000	23600
0.97	1780	1.7	1419	**3/V04L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	26200	30000	50600	59900	23600
1.0	1420	1.3	1381	**3/V01L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	8080	8080	26700	29200	7780
1.0	1510	1.9	1385	**3/V03L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	26100	29900	50400	59700	23400
1.1	1440	2.5	1231	**3/V04L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	25700	29400	49500	58700	22500



A

P_1 = 0.25 kW

n_2	M_2	S	i							Rn_2 [N]				
min^{-1}	Nm					IE1	IE2	IE1	IE2	MC/PC	MZ/PZ	HC	HZ	FZ
1.2	1140	1.0	1107	**3/V00L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	7830	7830	25900	30100	7230
1.2	1210	1.7	1105	**3/V01L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	7830	7830	25900	28300	7230
1.2	1310	1.3	1198	**3/V01L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	7920	7920	26200	28600	7420
1.2	1300	1.8	1189	**3/V03L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	25600	29200	49300	58400	22200
1.2	1440	2.5	1152	**3/V04L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	25500	29100	49100	58200	22000
1.3	1120	2.4	1023	**3/V03L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	25000	28600	48300	57200	21100
1.4	1220	1.3	997	**3/V01L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	7720	7720	25500	27900	6980
1.5	930	1.3	903	**3/V01L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	7610	7610	25200	27500	6760
1.5	1110	2.4	923	**3/V03L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	24700	28200	47600	56400	20400
1.6	1230	2.2	887	**3/V04L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	24500	28000	47300	56000	20100
1.7	840	1.3	818	**3/V00L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	7500	7500	24800	28900	6540
1.7	980	1.6	799	**3/V01L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	7480	7480	24700	27000	6480
1.7	960	2.3	793	**3/V03L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	24100	27600	46500	55100	19400
1.9	1180	1.5	731	**—**	**3/A03L2**	**BN71A4**	**BE71A4**	**—**	**—**	23900	27300	46000	54500	18900
1.9	980	2.7	710	**3/V04L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	23700	27100	45800	54300	18700
2.0	800	1.4	689	**3/V00L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	7320	7320	24200	28200	6170
2.0	800	2.1	689	**3/V01L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	7320	7320	24200	26500	6170
2.1	1070	1.1	665	**—**	**3/A01L2**	**BN71A4**	**BE71A4**	**M05C4**	**ME1SA4**	7280	7280	24100	26300	6100
2.1	710	1.5	654	**3/V00L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	7270	7270	24000	27900	6070
2.1	710	1.7	654	**3/V01L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	7270	7270	24000	26300	6070
2.2	750	3.0	623	**3/V03L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	23300	26600	45000	53300	17900
2.3	970	1.8	605	**—**	**3/A03L2**	**BN71A4**	**BE71A4**	**—**	**—**	23200	26500	44800	53100	17700
2.4	920	1.9	574	**—**	**3/A03L2**	**BN71A4**	**BE71A4**	**—**	**—**	23000	26300	44400	52700	17400
2.5	650	1.1	562	**3/V00L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	7110	7110	23500	27300	5770
2.5	650	2.2	562	**3/V01L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	7110	7110	23500	25700	5770
2.6	860	1.3	533	**—**	**3/A01L2**	**BN71A4**	**BE71A4**	**M05C4**	**ME1SA4**	7060	7060	23300	25500	5660
2.7	590	1.8	509	**3/V00L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	7010	7010	23200	27000	5580
2.7	590	2.2	509	**3/V01L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	7010	7010	23200	25300	5580
2.8	800	2.2	495	**—**	**3/A03L2**	**BN71A4**	**BE71A4**	**—**	**—**	22600	25800	43500	51600	16600
3.0	730	1.6	454	**—**	**3/A01L2**	**BN71A4**	**BE71A4**	**M05C4**	**ME1SA4**	6900	6900	22800	24900	5370
3.1	710	1.0	441	**—**	**3/A00L2**	**BN71A4**	**BE71A4**	**M05C4**	**ME1SA4**	6870	6870	22700	26400	5320
3.1	560	2.4	443	**3/V01L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	6870	6870	22700	24800	5330
3.2	475	1.5	436	**3/V00L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	6860	6860	22700	26400	5300
3.3	480	2.1	415	**3/V00L3**	**—**	**BN71A4**	**BE71A4**	**—**	**—**	6810	6810	22500	26200	5210
3.4	660	2.9	409	**—**	**3/A03L2**	**BN71A4**	**BE71A4**	**—**	**—**	22000	25100	42300	50200	15600
3.5	630	1.3	393	**—**	**3/A01L2**	**BN71A4**	**BE71A4**	**M05C4**	**ME1SA4**	6760	6760	22300	24400	5120
3.7	590	0.9	369	**—**	**3/A00L2**	**BN71A4**	**BE71A4**	**M05C4**	**ME1SA4**	6700	6700	22100	25800	5010
3.8	590	2.3	364	**—**	**3/A01L2**	**BN71A4**	**BE71A4**	**M05C4**	**ME1SA4**	6680	6680	22100	24200	4990
4.4	500	2.3	311	**—**	**3/A01L2**	**BN71A4**	**BE71A4**	**M05C4**	**ME1SA4**	6530	6530	21600	23600	4740
4.7	475	1.4	296	**—**	**3/A00L2**	**BN71A4**	**BE71A4**	**M05C4**	**ME1SA4**	6500	6500	21500	25000	4660
5.1	435	2.3	269	**—**	**3/A01L2**	**BN71A4**	**BE71A4**	**M05C4**	**ME1SA4**	6500	6500	21500	23500	4510
5.4	410	2.8	255	**—**	**3/A01L2**	**BN71A4**	**BE71A4**	**M05C4**	**ME1SA4**	6500	6500	21500	23500	4430
5.5	410	1.3	253	**—**	**3/A00L2**	**BN71A4**	**BE71A4**	**M05C4**	**ME1SA4**	6500	6500	21500	25000	4420
6.3	355	1.8	219	**—**	**3/A00L2**	**BN71A4**	**BE71A4**	**M05C4**	**ME1SA4**	6500	6500	21500	25000	4210
6.3	355	2.3	220	**—**	**3/A01L2**	**BN71A4**	**BE71A4**	**M05C4**	**ME1SA4**	6500	6500	21500	23500	4220
6.8	325	2.0	203	**—**	**3/A00L2**	**BN71A4**	**BE71A4**	**M05C4**	**ME1SA4**	6500	6500	21500	25000	4100
8.1	275	2.0	171	**—**	**3/A00L2**	**BN71A4**	**BE71A4**	**M05C4**	**ME1SA4**	6500	6500	21500	25000	3880
10.3	215	2.5	134	**—**	**3/A00L2**	**BN71A4**	**BE71A4**	**M05C4**	**ME1SA4**	6260	6260	20800	24200	3580

P_1 = 0.25 kW

n_2	M_2	S	i					Rn_2 [N]				
min^{-1}	Nm					IE3	IE3	MC/PC	MZ/PZ	HC	HZ	FZ
0.53	3080	2.3	2588	**3/V06L3**	**—**	**BXN71MA4**	**—**	34000	38800	77500	89500	35000
0.58	2770	1.1	2366	**3/V04L3**	**—**	**BXN71MA4**	**—**	28200	32200	54400	64500	24000
0.62	2620	1.7	2232	**3/V05L3**	**—**	**BXN71MA4**	**—**	28000	32000	53900	63900	24000
0.69	2190	1.1	2009	**3/V03L3**	**—**	**BXN71MA4**	**—**	27600	31500	53100	63000	24000
0.73	2220	1.4	1893	**3/V04L3**	**—**	**BXN71MA4**	**—**	27300	31200	52700	62400	24000
0.77	2090	2.2	1786	**3/V05L3**	**—**	**BXN71MA4**	**—**	27100	31000	52300	61900	24000
0.78	2220	1.3	1774	**3/V04L3**	**—**	**BXN71MA4**	**—**	27100	30900	52200	61900	24000
0.80	1880	1.5	1728	**3/V03L3**	**—**	**BXN71MA4**	**—**	27000	30800	52000	61600	24000
0.82	2100	2.1	1674	**3/V05L3**	**—**	**BXN71MA4**	**—**	26800	30700	51800	61400	24000
0.86	1760	1.4	1610	**3/V03L3**	**—**	**BXN71MA4**	**—**	26700	30500	51500	61000	24000
0.90	1800	2.1	1536	**3/V04L3**	**—**	**BXN71MA4**	**—**	26500	30300	51100	60600	24000
0.92	1630	1.1	1495	**3/V01L3**	**—**	**BXN71MA4**	**—**	8180	8180	27000	29600	7990



A

P_1 = 0.25 kW

n_2 min^{-1}	M_2 Nm	S	i			IE3	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
0.96	1680	2.8	1431	**3/V05L3**	**—**	**BXN71MA4**	**—**	26300	30000	50600	60000	23600
0.97	1780	1.7	1419	**3/V04L3**	**—**	**BXN71MA4**	**—**	26200	30000	50600	59900	23600
1.0	1420	1.3	1381	**3/V01L3**	**—**	**BXN71MA4**	**—**	8080	8080	26700	29200	7780
1.0	1510	1.9	1385	**3/V03L3**	**—**	**BXN71MA4**	**—**	26100	29900	50400	59700	23400
1.1	1440	2.5	1231	**3/V04L3**	**—**	**BXN71MA4**	**—**	25700	29400	49500	58700	22500
1.2	1140	1.0	1107	**3/V00L3**	**—**	**BXN71MA4**	**—**	7830	7830	25900	30100	7230
1.2	1210	1.7	1105	**3/V01L3**	**—**	**BXN71MA4**	**—**	7830	7830	25900	28300	7230
1.2	1310	1.3	1198	**3/V01L3**	**—**	**BXN71MA4**	**—**	7920	7920	26200	28600	7420
1.2	1300	1.8	1189	**3/V03L3**	**—**	**BXN71MA4**	**—**	25600	29200	49300	58400	22200
1.2	1440	2.5	1152	**3/V04L3**	**—**	**BXN71MA4**	**—**	25500	29100	49100	58200	22000
1.3	1120	2.4	1023	**3/V03L3**	**—**	**BXN71MA4**	**—**	25000	28600	48300	57200	21100
1.4	1220	1.3	997	**3/V01L3**	**—**	**BXN71MA4**	**—**	7720	7720	25500	27900	6980
1.5	930	1.3	903	**3/V01L3**	**—**	**BXN71MA4**	**—**	7610	7610	25200	27500	6760
1.5	1110	2.4	923	**3/V03L3**	**—**	**BXN71MA4**	**—**	24700	28200	47600	56400	20400
1.6	1230	2.2	887	**3/V04L3**	**—**	**BXN71MA4**	**—**	24500	28000	47300	56000	20100
1.7	840	1.3	818	**3/V00L3**	**—**	**BXN71MA4**	**—**	7500	7500	24800	28900	6540
1.7	980	1.6	799	**3/V01L3**	**—**	**BXN71MA4**	**—**	7480	7480	24700	27000	6480
1.7	960	2.3	793	**3/V03L3**	**—**	**BXN71MA4**	**—**	24100	27600	46500	55100	19400
1.9	1180	1.5	731	**—**	**3/A03L2**	**BXN71MA4**	**—**	23900	27300	46000	54500	18900
1.9	980	2.7	710	**3/V04L3**	**—**	**BXN71MA4**	**—**	23700	27100	45800	54300	18700
2.0	800	1.4	689	**3/V00L3**	**—**	**BXN71MA4**	**—**	7320	7320	24200	28200	6170
2.0	800	2.1	689	**3/V01L3**	**—**	**BXN71MA4**	**—**	7320	7320	24200	26500	6170
2.1	1070	1.1	665	**—**	**3/A01L2**	**BXN71MA4**	**MXN10MA4**	7280	7280	24100	26300	6100
2.1	710	1.5	654	**3/V00L3**	**—**	**BXN71MA4**	**—**	7270	7270	24000	27900	6070
2.1	710	1.7	654	**3/V01L3**	**—**	**BXN71MA4**	**—**	7270	7270	24000	26300	6070
2.2	750	3.0	623	**3/V03L3**	**—**	**BXN71MA4**	**—**	23300	26600	45000	53300	17900
2.3	970	1.8	605	**—**	**3/A03L2**	**BXN71MA4**	**—**	23200	26500	44800	53100	17700
2.4	920	1.9	574	**—**	**3/A03L2**	**BXN71MA4**	**—**	23000	26300	44400	52700	17400
2.5	650	1.1	562	**3/V00L3**	**—**	**BXN71MA4**	**—**	7110	7110	23500	27300	5770
2.5	650	2.2	562	**3/V01L3**	**—**	**BXN71MA4**	**—**	7110	7110	23500	25700	5770
2.6	860	1.3	533	**—**	**3/A01L2**	**BXN71MA4**	**MXN10MA4**	7060	7060	23300	25500	5660
2.7	590	1.8	509	**3/V00L3**	**—**	**BXN71MA4**	**—**	7010	7010	23200	27000	5580
2.7	590	2.2	509	**3/V01L3**	**—**	**BXN71MA4**	**—**	7010	7010	23200	25300	5580
2.8	800	2.2	495	**—**	**3/A03L2**	**BXN71MA4**	**—**	22600	25800	43500	51600	16600
3.0	730	1.6	454	**—**	**3/A01L2**	**BXN71MA4**	**MXN10MA4**	6900	6900	22800	24900	5370
3.1	710	1.0	441	**—**	**3/A00L2**	**BXN71MA4**	**MXN10MA4**	6870	6870	22700	26400	5320
3.1	560	2.4	443	**3/V01L3**	**—**	**BXN71MA4**	**—**	6870	6870	22700	24800	5330
3.2	475	1.5	436	**3/V00L3**	**—**	**BXN71MA4**	**—**	6860	6860	22700	26400	5300
3.3	480	2.1	415	**3/V00L3**	**—**	**BXN71MA4**	**—**	6810	6810	22500	26200	5210
3.4	660	2.9	409	**—**	**3/A03L2**	**BXN71MA4**	**—**	22000	25100	42300	50200	15600
3.5	630	1.3	393	**—**	**3/A01L2**	**BXN71MA4**	**MXN10MA4**	6760	6760	22300	24400	5120
3.7	590	0.9	369	**—**	**3/A00L2**	**BXN71MA4**	**MXN10MA4**	6700	6700	22100	25800	5010
3.8	590	2.3	364	**—**	**3/A01L2**	**BXN71MA4**	**MXN10MA4**	6680	6680	22100	24200	4990
4.4	500	2.3	311	**—**	**3/A01L2**	**BXN71MA4**	**MXN10MA4**	6530	6530	21600	23600	4740
4.7	475	1.4	296	**—**	**3/A00L2**	**BXN71MA4**	**MXN10MA4**	6500	6500	21500	25000	4660
5.1	435	2.3	269	**—**	**3/A01L2**	**BXN71MA4**	**MXN10MA4**	6500	6500	21500	23500	4510
5.4	410	2.8	255	**—**	**3/A01L2**	**BXN71MA4**	**MXN10MA4**	6500	6500	21500	23500	4430
5.5	410	1.3	253	**—**	**3/A00L2**	**BXN71MA4**	**MXN10MA4**	6500	6500	21500	25000	4420
6.3	355	1.8	219	**—**	**3/A00L2**	**BXN71MA4**	**MXN10MA4**	6500	6500	21500	25000	4210
6.3	355	2.3	220	**—**	**3/A01L2**	**BXN71MA4**	**MXN10MA4**	6500	6500	21500	23500	4220
6.8	325	2.0	203	**—**	**3/A00L2**	**BXN71MA4**	**MXN10MA4**	6500	6500	21500	25000	4100
8.1	275	2.0	171	**—**	**3/A00L2**	**BXN71MA4**	**MXN10MA4**	6500	6500	21500	25000	3880
10.3	215	2.5	134	**—**	**3/A00L2**	**BXN71MA4**	**MXN10MA4**	6260	6260	20800	24200	3580

P_1 = 0.37 kW

n_2 min^{-1}	M_2 Nm	S	i			IE1	IE2	IE1	IE2	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
0.53	4620	1.5	2588	**3/V06L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	34000	38800	77500	89500	35000
0.61	3930	1.1	2232	**3/V05L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	28000	32000	53900	63900	24000
0.64	3820	2.2	2139	**3/V06L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	33100	37700	75500	87100	35000
0.77	3150	1.5	1786	**3/V05L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	27100	31000	52300	61900	24000
0.77	3160	2.7	1768	**3/V06L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	32200	36700	73400	84800	35000
0.79	2830	1.0	1728	**3/V03L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	27000	30800	52000	61600	24000
0.82	3150	1.4	1674	**3/V05L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	26800	30700	51800	61400	24000



P_1 = 0.37 kW

n_2	M_2	S	i			IE1	IE2	IE1	IE2	Rn_2 [N]				
min^{-1}	Nm									MC/PC	MZ/PZ	HC	HZ	FZ
0.85	2640	0.9	1610	**3/V03L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	26700	30500	51500	61000	24000
0.89	2710	1.4	1536	**3/V04L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	26500	30300	51100	60600	24000
0.96	2520	1.8	1431	**3/V05L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	26300	30000	50600	60000	23600
0.97	2670	1.1	1419	**3/V04L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	26200	30000	50600	59900	23600
0.99	2270	1.2	1385	**3/V03L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	26100	29900	50400	59700	23400
1.1	2170	1.7	1231	**3/V04L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	25700	29400	49500	58700	22500
1.1	2170	2.5	1231	**3/V05L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	25700	29400	49500	58700	22500
1.2	1810	1.1	1105	**3/V01L3**	**—**	**BN71B4**	**BE71B4**	**—**	**—**	7830	7830	25900	28300	7230
1.2	1950	1.2	1189	**3/V03L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	25600	29200	49300	58400	22200
1.2	2170	1.6	1152	**3/V04L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	25500	29100	49100	58200	22000
1.2	2180	2.0	1116	**3/V05L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	25300	29000	48900	57900	21700
1.3	1680	1.6	1023	**3/V03L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	25000	28600	48300	57200	21100
1.3	1860	2.4	1057	**3/V05L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	25100	28700	48500	57500	21400
1.4	1730	2.2	981	**3/V04L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	24900	28400	48000	56900	20800
1.5	1670	1.6	923	**3/V03L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	24700	28200	47600	56400	20400
1.5	1840	1.5	887	**3/V04L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	24500	28000	47300	56000	20100
1.5	1750	2.5	894	**3/V05L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	24500	28100	47300	56100	20200
1.7	1470	1.1	799	**3/V01L3**	**—**	**BN71B4**	**BE71B4**	**—**	**—**	7480	7480	24700	27000	6480
1.7	1440	1.5	793	**3/V03L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	24100	27600	46500	55100	19400
1.7	1490	2.8	793	**3/V05L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	24100	27600	46500	55100	19400
1.8	1500	2.2	769	**3/V04L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	24000	27500	46300	54900	19200
1.9	1770	1.0	731	**—**	**3/A03L2**	**BN71B4**	**BE71B4**	**—**	**—**	23900	27300	46000	54500	18900
1.9	1330	2.0	736	**3/V03L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	23900	27300	46000	54600	18900
1.9	1480	1.8	710	**3/V04L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	23700	27100	45800	54300	18700
1.9	1450	2.8	715	**3/V05L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	23800	27200	45900	54300	18800
2.0	1200	0.9	689	**3/V00L3**	**—**	**BN71B4**	**BE71B4**	**—**	**—**	7320	7320	24200	28200	6170
2.0	1200	1.4	689	**3/V01L3**	**—**	**BN71B4**	**BE71B4**	**—**	**—**	7320	7320	24200	26500	6170
2.1	1070	1.0	654	**3/V00L3**	**—**	**BN71B4**	**BE71B4**	**—**	**—**	7270	7270	24000	27900	6070
2.1	1070	1.1	654	**3/V01L3**	**—**	**BN71B4**	**BE71B4**	**—**	**—**	7270	7270	24000	26300	6070
2.2	1130	2.0	623	**3/V03L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	23300	26600	45000	53300	17900
2.3	1460	1.2	605	**—**	**3/A03L2**	**BN71B4**	**BE71B4**	**—**	**—**	23200	26500	44800	53100	17700
2.3	1440	2.3	594	**—**	**3/A05L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	23200	26500	44700	52900	17600
2.4	1390	1.3	574	**—**	**3/A03L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	23000	26300	44400	52700	17400
2.4	980	1.4	562	**3/V01L3**	**—**	**BN71B4**	**BE71B4**	**—**	**—**	7110	7110	23500	25700	5770
2.4	1110	2.8	568	**3/V04L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	23000	26300	44400	52600	17400
2.5	980	2.8	544	**3/V03L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	22900	26100	44100	52300	17100
2.6	1260	2.0	520	**—**	**3/A04L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	22700	26000	43800	51900	16900
2.7	880	1.2	509	**3/V00L3**	**—**	**BN71B4**	**BE71B4**	**—**	**—**	7010	7010	23200	27000	5580
2.7	880	1.4	509	**3/V01L3**	**—**	**BN71B4**	**BE71B4**	**—**	**—**	7010	7010	23200	25300	5580
2.7	990	2.0	502	**3/V03L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	22600	25800	43600	51700	16700
2.8	1200	1.4	495	**—**	**3/A03L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	22600	25800	43500	51600	16600
2.9	1140	2.2	469	**—**	**3/A04L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	22400	25600	43200	51200	16300
3.0	1100	1.0	454	**—**	**3/A01L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6900	6900	22800	24900	5370
3.0	830	2.8	460	**3/V03L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	22300	25500	43100	51000	16200
3.1	710	1.0	436	**3/V00L3**	**—**	**BN71B4**	**BE71B4**	**—**	**—**	6860	6860	22700	26400	5300
3.1	850	1.6	443	**3/V01L3**	**—**	**BN71B4**	**BE71B4**	**—**	**—**	6870	6870	22700	24800	5330
3.2	850	2.2	430	**3/V01L3**	**—**	**BN71B4**	**BE71B4**	**—**	**—**	6840	6840	22600	24700	5270
3.3	990	2.0	409	**—**	**3/A03L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	22000	25100	42300	50200	15600
3.3	720	1.4	415	**3/V00L3**	**—**	**BN71B4**	**BE71B4**	**—**	**—**	6810	6810	22500	26200	5210
3.5	930	2.6	386	**—**	**3/A04L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	21800	24900	42000	49800	15300
3.5	780	2.8	395	**3/V03L3**	**—**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	21800	25000	42100	49900	15400
3.8	880	1.5	364	**—**	**3/A01L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6680	6680	22100	24200	4990
3.9	850	2.4	352	**—**	**3/A03L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	21500	24600	41400	49100	14800
3.9	840	2.9	349	**—**	**3/A04L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	21500	24500	41400	49000	14800
4.2	790	2.1	326	**—**	**3/A03L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	21200	24300	41000	48600	14400
4.4	750	1.5	311	**—**	**3/A01L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6530	6530	21600	23600	4740
4.6	720	0.9	296	**—**	**3/A00L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	25000	4660
5.1	650	1.6	269	**—**	**3/A01L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	23500	4510
5.1	650	2.8	269	**—**	**3/A03L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	21000	24000	40500	48000	13500
5.1	650	2.8	269	**—**	**3/A03L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	21000	24000	40500	48000	13500
5.4	620	1.9	255	**—**	**3/A01L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	23500	4430
6.2	530	1.6	220	**—**	**3/A01L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	23500	4220
6.3	530	1.2	219	**—**	**3/A00L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	25000	4210
6.7	490	1.3	203	**—**	**3/A00L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	25000	4100
6.7	495	2.6	204	**—**	**3/A01L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	23500	4120
7.4	445	2.3	184	**—**	**3/A01L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	23500	3980
8.0	415	1.3	171	**—**	**3/A00L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	25000	3880
8.3	400	2.9	166	**—**	**3/A01L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6500	6500	21500	23500	3840



A

P_1 = 0.37 kW

n_2	M_2	S	i			IE1	IE2	IE1	IE2	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
min^{-1}	Nm													
10.2	325	1.7	134	—	**3/A00L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	6260	6260	20800	24200	3580
12.8	260	2.5	107	—	**3/A00L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	5810	5810	19400	22600	3320
13.7	240	2.3	100	—	**3/A00L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	5680	5680	19000	22100	3240
15.5	215	2.6	88.6	—	**3/A00L2**	**BN71B4**	**BE71B4**	**M1SD4**	**ME1SB4**	5450	5450	18400	21300	3120

P_1 = 0.37 kW

n_2	M_2	S	i			IE3	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
min^{-1}	Nm											
0.53	4620	1.5	2588	**3/V06L3**	—	**BXN71MB4**	**MXN10MB4**	34000	38800	77500	89500	35000
0.61	3930	1.1	2232	**3/V05L3**	—	**BXN71MB4**	**MXN10MB4**	28000	32000	53900	63900	24000
0.64	3820	2.2	2139	**3/V06L3**	—	**BXN71MB4**	**MXN10MB4**	33100	37700	75500	87100	35000
0.77	3150	1.5	1786	**3/V05L3**	—	**BXN71MB4**	**MXN10MB4**	27100	31000	52300	61900	24000
0.77	3160	2.7	1768	**3/V06L3**	—	**BXN71MB4**	**MXN10MB4**	32200	36700	73400	84800	35000
0.79	2830	1.0	1728	**3/V03L3**	—	**BXN71MB4**	**MXN10MB4**	27000	30800	52000	61600	24000
0.82	3150	1.4	1674	**3/V05L3**	—	**BXN71MB4**	**MXN10MB4**	26800	30700	51800	61400	24000
0.85	2640	0.9	1610	**3/V03L3**	—	**BXN71MB4**	**MXN10MB4**	26700	30500	51500	61000	24000
0.89	2710	1.4	1536	**3/V04L3**	—	**BXN71MB4**	**MXN10MB4**	26500	30300	51100	60600	24000
0.96	2520	1.8	1431	**3/V05L3**	—	**BXN71MB4**	**MXN10MB4**	26300	30000	50600	60000	23600
0.97	2670	1.1	1419	**3/V04L3**	—	**BXN71MB4**	**MXN10MB4**	26200	30000	50600	59900	23600
0.99	2270	1.2	1385	**3/V03L3**	—	**BXN71MB4**	**MXN10MB4**	26100	29900	50400	59700	23400
1.1	2170	1.7	1231	**3/V04L3**	—	**BXN71MB4**	**MXN10MB4**	25700	29400	49500	58700	22500
1.1	2170	2.5	1231	**3/V05L3**	—	**BXN71MB4**	**MXN10MB4**	25700	29400	49500	58700	22500
1.2	1810	1.1	1105	**3/V01L3**	—	**BXN71MB4**	—	7830	7830	25900	28300	7230
1.2	1950	1.2	1189	**3/V03L3**	—	**BXN71MB4**	**MXN10MB4**	25600	29200	49300	58400	22200
1.2	2170	1.6	1152	**3/V04L3**	—	**BXN71MB4**	**MXN10MB4**	25500	29100	49100	58200	22000
1.2	2180	2.0	1116	**3/V05L3**	—	**BXN71MB4**	**MXN10MB4**	25300	29000	48900	57900	21700
1.3	1680	1.6	1023	**3/V03L3**	—	**BXN71MB4**	**MXN10MB4**	25000	28600	48300	57200	21100
1.3	1860	2.4	1057	**3/V05L3**	—	**BXN71MB4**	**MXN10MB4**	25100	28700	48500	57500	21400
1.4	1730	2.2	981	**3/V04L3**	—	**BXN71MB4**	**MXN10MB4**	24900	28400	48000	56900	20800
1.5	1670	1.6	923	**3/V03L3**	—	**BXN71MB4**	**MXN10MB4**	24700	28200	47600	56400	20400
1.5	1840	1.5	887	**3/V04L3**	—	**BXN71MB4**	**MXN10MB4**	24500	28000	47300	56000	20100
1.5	1750	2.5	894	**3/V05L3**	—	**BXN71MB4**	**MXN10MB4**	24500	28100	47300	56100	20200
1.7	1470	1.1	799	**3/V01L3**	—	**BXN71MB4**	—	7480	7480	24700	27000	6480
1.7	1440	1.5	793	**3/V03L3**	—	**BXN71MB4**	**MXN10MB4**	24100	27600	46500	55100	19400
1.7	1490	2.8	793	**3/V05L3**	—	**BXN71MB4**	**MXN10MB4**	24100	27600	46500	55100	19400
1.8	1500	2.2	769	**3/V04L3**	—	**BXN71MB4**	**MXN10MB4**	24000	27500	46300	54900	19200
1.9	1770	1.0	731	—	**3/A03L2**	**BXN71MB4**	—	23900	27300	46000	54500	18900
1.9	1330	2.0	736	**3/V03L3**	—	**BXN71MB4**	**MXN10MB4**	23900	27300	46000	54600	18900
1.9	1480	1.8	710	**3/V04L3**	—	**BXN71MB4**	**MXN10MB4**	23700	27100	45800	54300	18700
1.9	1450	2.8	715	**3/V05L3**	—	**BXN71MB4**	**MXN10MB4**	23800	27200	45900	54300	18800
2.0	1200	0.9	689	**3/V00L3**	—	**BXN71MB4**	—	7320	7320	24200	28200	6170
2.0	1200	1.4	689	**3/V01L3**	—	**BXN71MB4**	—	7320	7320	24200	26500	6170
2.1	1070	1.0	654	**3/V00L3**	—	**BXN71MB4**	—	7270	7270	24000	27900	6070
2.1	1070	1.1	654	**3/V01L3**	—	**BXN71MB4**	—	7270	7270	24000	26300	6070
2.2	1130	2.0	623	**3/V03L3**	—	**BXN71MB4**	**MXN10MB4**	23300	26600	45000	53300	17900
2.3	1460	1.2	605	—	**3/A03L2**	**BXN71MB4**	—	23200	26500	44800	53100	17700
2.3	1440	2.3	594	—	**3/A05L2**	**BXN71MB4**	—	23200	26500	44700	52900	17600
2.4	1390	1.3	574	—	**3/A03L2**	**BXN71MB4**	**MXN10MB4**	23000	26300	44400	52700	17400
2.4	980	1.4	562	**3/V01L3**	—	**BXN71MB4**	—	7110	7110	23500	25700	5770
2.4	1110	2.8	568	**3/V04L3**	—	**BXN71MB4**	**MXN10MB4**	23000	26300	44400	52600	17400
2.5	980	2.8	544	**3/V03L3**	—	**BXN71MB4**	**MXN10MB4**	22900	26100	44100	52300	17100
2.6	1260	2.0	520	—	**3/A04L2**	**BXN71MB4**	—	22700	26000	43800	51900	16900
2.7	880	1.2	509	**3/V00L3**	—	**BXN71MB4**	—	7010	7010	23200	27000	5580
2.7	880	1.4	509	**3/V01L3**	—	**BXN71MB4**	—	7010	7010	23200	25300	5580
2.7	990	2.0	502	**3/V03L3**	—	**BXN71MB4**	**MXN10MB4**	22600	25800	43600	51700	16700
2.8	1200	1.4	495	—	**3/A03L2**	**BXN71MB4**	**MXN10MB4**	22600	25800	43500	51600	16600
2.9	1140	2.2	469	—	**3/A04L2**	**BXN71MB4**	—	22400	25600	43200	51200	16300
3.0	1100	1.0	454	—	**3/A01L2**	**BXN71MB4**	**MXN10MB4**	6900	6900	22800	24900	5370
3.0	830	2.8	460	**3/V03L3**	—	**BXN71MB4**	**MXN10MB4**	22300	25500	43100	51000	16200
3.1	710	1.0	436	**3/V00L3**	—	**BXN71MB4**	—	6860	6860	22700	26400	5300
3.1	850	1.6	443	**3/V01L3**	—	**BXN71MB4**	—	6870	6870	22700	24800	5330
3.2	850	2.2	430	**3/V01L3**	—	**BXN71MB4**	—	6840	6840	22600	24700	5270
3.3	990	2.0	409	—	**3/A03L2**	**BXN71MB4**	**MXN10MB4**	22000	25100	42300	50200	15600
3.3	720	1.4	415	**3/V00L3**	—	**BXN71MB4**	—	6810	6810	22500	26200	5210



P_1 = 0.37 kW

n_2 min^{-1}	M_2 Nm	S	i			IE3	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
3.5	930	2.6	386	—	3/A04L2	BXN71MB4	—	21800	24900	42000	49800	15300
3.5	780	2.8	395	3/V03L3	—	BXN71MB4	MXN10MB4	21800	25000	42100	49900	15400
3.8	880	1.5	364	—	3/A01L2	BXN71MB4	MXN10MB4	6680	6680	22100	24200	4990
3.9	850	2.4	352	—	3/A03L2	BXN71MB4	MXN10MB4	21500	24600	41400	49100	14800
3.9	840	2.9	349	—	3/A04L2	BXN71MB4	—	21500	24500	41400	49000	14800
4.2	790	2.1	326	—	3/A03L2	BXN71MB4	MXN10MB4	21200	24300	41000	48600	14400
4.4	750	1.5	311	—	3/A01L2	BXN71MB4	MXN10MB4	6530	6530	21600	23600	4740
4.6	720	0.9	296	—	3/A00L2	BXN71MB4	MXN10MB4	6500	6500	21500	25000	4660
5.1	650	1.6	269	—	3/A01L2	BXN71MB4	MXN10MB4	6500	6500	21500	23500	4510
5.1	650	2.8	269	—	3/A03L2	BXN71MB4	MXN10MB4	21000	24000	40500	48000	13500
5.1	650	2.8	269	—	3/A03L2	BXN71MB4	MXN10MB4	21000	24000	40500	48000	13500
5.4	620	1.9	255	—	3/A01L2	BXN71MB4	MXN10MB4	6500	6500	21500	23500	4430
6.2	530	1.6	220	—	3/A01L2	BXN71MB4	MXN10MB4	6500	6500	21500	23500	4220
6.3	530	1.2	219	—	3/A00L2	BXN71MB4	MXN10MB4	6500	6500	21500	25000	4210
6.7	490	1.3	203	—	3/A00L2	BXN71MB4	MXN10MB4	6500	6500	21500	25000	4100
6.7	495	2.6	204	—	3/A01L2	BXN71MB4	MXN10MB4	6500	6500	21500	23500	4120
7.4	445	2.3	184	—	3/A01L2	BXN71MB4	MXN10MB4	6500	6500	21500	23500	3980
8.0	415	1.3	171	—	3/A00L2	BXN71MB4	MXN10MB4	6500	6500	21500	25000	3880
8.3	400	2.9	166	—	3/A01L2	BXN71MB4	MXN10MB4	6500	6500	21500	23500	3840
10.2	325	1.7	134	—	3/A00L2	BXN71MB4	MXN10MB4	6260	6260	20800	24200	3580
12.8	260	2.5	107	—	3/A00L2	BXN71MB4	MXN10MB4	5810	5810	19400	22600	3320
13.7	240	2.3	100	—	3/A00L2	BXN71MB4	MXN10MB4	5680	5680	19000	22100	3240
15.5	215	2.6	88.6	—	3/A00L2	BXN71MB4	MXN10MB4	5450	5450	18400	21300	3120

P_1 = 0.55 kW

n_2 min^{-1}	M_2 Nm	S	i			IE1	IE2	IE1	IE2	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
0.28	12600	2.2	4959	3/V10ML4	—	BN80A4	BE80A4	M1LA4	ME2SA4	—	—	116400	147600	65000
0.28	12600	2.2	4959	3/V10ML4	—	BN80A4	BE80A4	M1LA4	ME2SA4	—	—	116400	147600	65000
0.30	11700	2.6	4637	3/V10ML4	—	BN80A4	BE80A4	M1LA4	ME2SA4	—	—	115300	146200	65000
0.30	11700	2.6	4637	3/V10ML4	—	BN80A4	BE80A4	M1LA4	ME2SA4	—	—	115300	146200	65000
0.34	11800	2.6	4036	3/V10ML4	—	BN80A4	BE80A4	M1LA4	ME2SA4	—	—	113100	143400	65000
0.34	11800	2.6	4036	3/V10ML4	—	BN80A4	BE80A4	M1LA4	ME2SA4	—	—	113100	143400	65000
0.42	9540	2.9	3273	3/V10ML4	—	BN80A4	BE80A4	M1LA4	ME2SA4	—	—	109700	139100	65000
0.42	9540	2.9	3273	3/V10ML4	—	BN80A4	BE80A4	M1LA4	ME2SA4	—	—	109700	139100	65000
0.54	6750	1.0	2588	3/V06L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	34000	38800	77500	89500	35000
0.56	6190	1.8	2472	3/V07L3	—	BN80A4	BE80A4	—	—	40500	50700	91200	120000	45000
0.65	5580	1.5	2139	3/V06L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	33100	37700	75500	87100	35000
0.65	5690	1.9	2150	3/V07L3	—	BN80A4	BE80A4	—	—	39700	49700	89400	117600	45000
0.71	4920	2.5	1964	3/V07L3	—	BN80A4	BE80A4	—	—	39200	49000	88300	116100	45000
0.78	4600	1.0	1786	3/V05L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	27100	31000	52300	61900	24000
0.79	4610	1.9	1768	3/V06L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	32200	36700	73400	84800	35000
0.83	4610	1.0	1674	3/V05L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	26800	30700	51800	61400	24000
0.90	3950	0.9	1536	3/V04L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	26500	30300	51100	60600	24000
0.90	4200	2.6	1545	3/V07L3	—	BN80A4	BE80A4	—	—	37900	47400	85300	112200	45000
0.97	3680	1.3	1431	3/V05L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	26300	30000	50600	60000	23600
1.0	3790	2.2	1395	3/V06L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	31100	35500	71000	82000	34200
1.1	3170	1.1	1231	3/V04L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	25700	29400	49500	58700	22500
1.1	3170	1.7	1231	3/V05L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	25700	29400	49500	58700	22500
1.1	3160	2.5	1212	3/V06L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	30500	34800	69600	80300	32600
1.2	3170	1.1	1152	3/V04L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	25500	29100	49100	58200	22000
1.2	3190	1.4	1116	3/V05L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	25300	29000	48900	57900	21700
1.2	3130	2.6	1153	3/V06L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	30300	34500	69100	79800	32100
1.3	2720	1.6	1057	3/V05L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	25100	28700	48500	57500	21400
1.4	2450	1.1	1023	3/V03L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	25000	28600	48300	57200	21100
1.4	2530	1.5	981	3/V04L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	24900	28400	48000	56900	20800
1.5	2440	1.1	923	3/V03L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	24700	28200	47600	56400	20400
1.5	2790	2.8	930	3/V06L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	29400	33500	67000	77300	29800
1.6	2700	1.0	887	3/V04L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	24500	28000	47300	56000	20100
1.6	2560	1.7	894	3/V05L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	24500	28100	47300	56100	20200
1.8	2100	1.0	793	3/V03L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	24100	27600	46500	55100	19400
1.8	2200	1.5	769	3/V04L3	—	BN80A4	BE80A4	M1LA4	ME2SA4	24000	27500	46300	54900	19200



P_1 = 0.55 kW

n_2	M_2	S	i							Rn_2 [N]				
min^{-1}	Nm					IE1	IE2	IE1	IE2	MC/PC	MZ/PZ	HC	HZ	FZ
1.8	2180	1.9	793	**3/V05L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	24100	27600	46500	55100	19400
1.9	1950	1.4	736	**3/V03L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23900	27300	46000	54600	18900
1.9	2120	1.9	715	**3/V05L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23800	27200	45900	54300	18800
2.0	1750	1.0	689	**3/V01L3**	**—**	**BN80A4**	**BE80A4**	**—**	**—**	7320	7320	24200	26500	6170
2.0	2160	1.2	710	**3/V04L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23700	27100	45800	54300	18700
2.1	2320	2.6	671	**—**	**3/A06L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	28000	32000	64000	73800	26800
2.2	1650	1.3	623	**3/V03L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23300	26600	45000	53300	17900
2.2	1720	2.1	623	**3/V04L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23300	26600	45000	53300	17900
2.2	1720	2.6	623	**3/V05L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23300	26600	45000	53300	17900
2.3	2100	1.6	594	**—**	**3/A05L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23200	26500	44700	52900	17600
2.3	2120	2.8	611	**—**	**3/A06L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	27700	31600	63100	72800	25900
2.4	1620	1.9	568	**3/V04L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23000	26300	44400	52600	17400
2.4	1750	2.8	576	**3/V05L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	23100	26300	44500	52700	17400
2.5	1430	1.0	562	**3/V01L3**	**—**	**BN80A4**	**BE80A4**	**—**	**—**	7110	7110	23500	25700	5770
2.6	1440	1.9	544	**3/V03L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22900	26100	44100	52300	17100
2.6	1570	2.5	529	**3/V05L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22800	26000	43900	52000	17000
2.7	1840	1.4	520	**—**	**3/A04L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22700	26000	43800	51900	16900
2.7	1290	1.0	509	**3/V01L3**	**—**	**BN80A4**	**BE80A4**	**—**	**—**	7010	7010	23200	25300	5580
2.8	1750	1.0	495	**—**	**3/A03L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22600	25800	43500	51600	16600
2.8	1740	2.2	491	**—**	**3/A05L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22500	25800	43500	51500	16500
2.8	1450	1.4	502	**3/V03L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22600	25800	43600	51700	16700
2.8	1290	2.3	501	**3/V04L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22600	25800	43600	51700	16700
3.0	1660	1.5	469	**—**	**3/A04L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22400	25600	43200	51200	16300
3.0	1220	1.9	460	**3/V03L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22300	25500	43100	51000	16200
3.1	1240	1.1	443	**3/V01L3**	**—**	**BN80A4**	**BE80A4**	**—**	**—**	6870	6870	22700	24800	5330
3.1	1300	2.9	453	**3/V04L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22300	25500	43000	50900	16100
3.2	1250	1.5	430	**3/V01L3**	**—**	**BN80A4**	**BE80A4**	**—**	**—**	6840	6840	22600	24700	5270
3.3	1490	2.9	422	**—**	**3/A05L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22100	25200	42500	50400	15700
3.3	1050	0.9	415	**3/V00L3**	**—**	**BN80A4**	**BE80A4**	**—**	**—**	6810	6810	22500	26200	5210
3.4	1450	1.3	409	**—**	**3/A03L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	22000	25100	42300	50200	15600
3.5	1410	2.3	398	**—**	**3/A05L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21900	25000	42200	50000	15400
3.5	1140	1.9	395	**3/V03L3**	**—**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21800	25000	42100	49900	15400
3.6	1370	1.8	386	**—**	**3/A04L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21800	24900	42000	49800	15300
3.8	1290	1.0	364	**—**	**3/A01L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6680	6680	22100	24200	4990
3.9	1250	1.6	352	**—**	**3/A03L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21500	24600	41400	49100	14800
4.0	1230	2.0	349	**—**	**3/A04L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21500	24500	41400	49000	14800
4.3	1150	1.4	326	**—**	**3/A03L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21200	24300	41000	48600	14400
4.4	1120	2.1	317	**—**	**3/A04L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21200	24200	40800	48400	14300
4.5	1100	1.0	311	**—**	**3/A01L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6530	6530	21600	23600	4740
4.9	1000	2.8	283	**—**	**3/A04L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21000	24000	40500	48000	13800
5.2	950	1.1	269	**—**	**3/A01L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	23500	4510
5.2	950	1.9	269	**—**	**3/A03L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21000	24000	40500	48000	13500
5.2	950	1.9	269	**—**	**3/A03L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21000	24000	40500	48000	13500
5.5	900	1.3	255	**—**	**3/A01L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	23500	4430
6.3	780	1.1	220	**—**	**3/A01L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	23500	4220
6.3	780	2.1	220	**—**	**3/A03L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21000	24000	40500	48000	12700
6.8	720	0.9	203	**—**	**3/A00L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	25000	4100
6.8	720	1.8	204	**—**	**3/A01L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	23500	4120
7.6	650	1.6	184	**—**	**3/A01L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	23500	3980
7.6	640	2.8	182	**—**	**3/A03L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	21000	24000	40500	48000	11900
8.1	610	0.9	171	**—**	**3/A00L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	25000	3880
8.4	590	2.0	166	**—**	**3/A01L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6500	6500	21500	23500	3840
10.4	475	1.2	134	**—**	**3/A00L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6260	6260	20800	24200	3580
10.5	470	2.8	133	**—**	**3/A01L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	6250	6250	20800	22700	3570
13.0	380	1.7	107	**—**	**3/A00L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	5810	5810	19400	22600	3320
13.9	355	1.6	100	**—**	**3/A00L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	5680	5680	19000	22100	3240
15.7	315	1.8	88.6	**—**	**3/A00L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	5450	5450	18400	21300	3120
17.3	285	2.3	80.2	**—**	**3/A00L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	5280	5280	17800	20700	3010
19.6	250	2.6	71.0	**—**	**3/A00L2**	**BN80A4**	**BE80A4**	**M1LA4**	**ME2SA4**	5060	5060	17200	20000	2890



P_1 = 0.55 kW

n_2 min^{-1}	M_2 Nm	S	i			IE3	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
0.28	12600	2.2	4959	**3/V10ML4**	**—**	**BXN80MA4**	**MXN20MA4**	—	—	116400	147600	65000
0.28	12600	2.2	4959	**3/V10ML4**	**—**	**BXN80MA4**	**MXN20MA4**	—	—	116400	147600	65000
0.30	11700	2.6	4637	**3/V10ML4**	**—**	**BXN80MA4**	**MXN20MA4**	—	—	115300	146200	65000
0.30	11700	2.6	4637	**3/V10ML4**	**—**	**BXN80MA4**	**MXN20MA4**	—	—	115300	146200	65000
0.34	11800	2.6	4036	**3/V10ML4**	**—**	**BXN80MA4**	**MXN20MA4**	—	—	113100	143400	65000
0.34	11800	2.6	4036	**3/V10ML4**	**—**	**BXN80MA4**	**MXN20MA4**	—	—	113100	143400	65000
0.42	9540	2.9	3273	**3/V10ML4**	**—**	**BXN80MA4**	**MXN20MA4**	—	—	109700	139100	65000
0.42	9540	2.9	3273	**3/V10ML4**	**—**	**BXN80MA4**	**MXN20MA4**	—	—	109700	139100	65000
0.54	6750	1.0	2588	**3/V06L3**	**—**	**BXN80MA4**	**MXN20MA4**	34000	38800	77500	89500	35000
0.56	6190	1.8	2472	**3/V07L3**	**—**	**BXN80MA4**	**—**	40500	50700	91200	120000	45000
0.65	5580	1.5	2139	**3/V06L3**	**—**	**BXN80MA4**	**MXN20MA4**	33100	37700	75500	87100	35000
0.65	5690	1.9	2150	**3/V07L3**	**—**	**BXN80MA4**	**—**	39700	49700	89400	117600	45000
0.71	4920	2.5	1964	**3/V07L3**	**—**	**BXN80MA4**	**—**	39200	49000	88300	116100	45000
0.78	4600	1.0	1786	**3/V05L3**	**—**	**BXN80MA4**	**MXN20MA4**	27100	31000	52300	61900	24000
0.79	4610	1.9	1768	**3/V06L3**	**—**	**BXN80MA4**	**MXN20MA4**	32200	36700	73400	84800	35000
0.83	4610	1.0	1674	**3/V05L3**	**—**	**BXN80MA4**	**MXN20MA4**	26800	30700	51800	61400	24000
0.90	3950	0.9	1536	**3/V04L3**	**—**	**BXN80MA4**	**MXN20MA4**	26500	30300	51100	60600	24000
0.90	4200	2.6	1545	**3/V07L3**	**—**	**BXN80MA4**	**—**	37900	47400	85300	112200	45000
0.97	3680	1.3	1431	**3/V05L3**	**—**	**BXN80MA4**	**MXN20MA4**	26300	30000	50600	60000	23600
1.0	3790	2.2	1395	**3/V06L3**	**—**	**BXN80MA4**	**MXN20MA4**	31100	35500	71000	82000	34200
1.1	3170	1.1	1231	**3/V04L3**	**—**	**BXN80MA4**	**MXN20MA4**	25700	29400	49500	58700	22500
1.1	3170	1.7	1231	**3/V05L3**	**—**	**BXN80MA4**	**MXN20MA4**	25700	29400	49500	58700	22500
1.1	3160	2.5	1212	**3/V06L3**	**—**	**BXN80MA4**	**MXN20MA4**	30500	34800	69600	80300	32600
1.2	3170	1.1	1152	**3/V04L3**	**—**	**BXN80MA4**	**MXN20MA4**	25500	29100	49100	58200	22000
1.2	3190	1.4	1116	**3/V05L3**	**—**	**BXN80MA4**	**MXN20MA4**	25300	29000	48900	57900	21700
1.2	3130	2.6	1153	**3/V06L3**	**—**	**BXN80MA4**	**MXN20MA4**	30300	34500	69100	79800	32100
1.3	2720	1.6	1057	**3/V05L3**	**—**	**BXN80MA4**	**MXN20MA4**	25100	28700	48500	57500	21400
1.4	2450	1.1	1023	**3/V03L3**	**—**	**BXN80MA4**	**MXN20MA4**	25000	28600	48300	57200	21100
1.4	2530	1.5	981	**3/V04L3**	**—**	**BXN80MA4**	**MXN20MA4**	24900	28400	48000	56900	20800
1.5	2440	1.1	923	**3/V03L3**	**—**	**BXN80MA4**	**MXN20MA4**	24700	28200	47600	56400	20400
1.5	2790	2.8	930	**3/V06L3**	**—**	**BXN80MA4**	**MXN20MA4**	29400	33500	67000	77300	29800
1.6	2700	1.0	887	**3/V04L3**	**—**	**BXN80MA4**	**MXN20MA4**	24500	28000	47300	56000	20100
1.6	2560	1.7	894	**3/V05L3**	**—**	**BXN80MA4**	**MXN20MA4**	24500	28100	47300	56100	20200
1.8	2100	1.0	793	**3/V03L3**	**—**	**BXN80MA4**	**MXN20MA4**	24100	27600	46500	55100	19400
1.8	2200	1.5	769	**3/V04L3**	**—**	**BXN80MA4**	**MXN20MA4**	24000	27500	46300	54900	19200
1.8	2180	1.9	793	**3/V05L3**	**—**	**BXN80MA4**	**MXN20MA4**	24100	27600	46500	55100	19400
1.9	1950	1.4	736	**3/V03L3**	**—**	**BXN80MA4**	**MXN20MA4**	23900	27300	46000	54600	18900
1.9	2120	1.9	715	**3/V05L3**	**—**	**BXN80MA4**	**MXN20MA4**	23800	27200	45900	54300	18800
2.0	1750	1.0	689	**3/V01L3**	**—**	**BXN80MA4**	**—**	7320	7320	24200	26500	6170
2.0	2160	1.2	710	**3/V04L3**	**—**	**BXN80MA4**	**MXN20MA4**	23700	27100	45800	54300	18700
2.1	2320	2.6	671	**—**	**3/A06L2**	**BXN80MA4**	**—**	28000	32000	64000	73800	26800
2.2	1650	1.3	623	**3/V03L3**	**—**	**BXN80MA4**	**MXN20MA4**	23300	26600	45000	53300	17900
2.2	1720	2.1	623	**3/V04L3**	**—**	**BXN80MA4**	**MXN20MA4**	23300	26600	45000	53300	17900
2.2	1720	2.6	623	**3/V05L3**	**—**	**BXN80MA4**	**MXN20MA4**	23300	26600	45000	53300	17900
2.3	2100	1.6	594	**—**	**3/A05L2**	**BXN80MA4**	**—**	23200	26500	44700	52900	17600
2.3	2120	2.8	611	**—**	**3/A06L2**	**BXN80MA4**	**—**	27700	31600	63100	72800	25900
2.4	1620	1.9	568	**3/V04L3**	**—**	**BXN80MA4**	**MXN20MA4**	23000	26300	44400	52600	17400
2.4	1750	2.8	576	**3/V05L3**	**—**	**BXN80MA4**	**MXN20MA4**	23100	26300	44500	52700	17400
2.5	1430	1.0	562	**3/V01L3**	**—**	**BXN80MA4**	**—**	7110	7110	23500	25700	5770
2.6	1440	1.9	544	**3/V03L3**	**—**	**BXN80MA4**	**MXN20MA4**	22900	26100	44100	52300	17100
2.6	1570	2.5	529	**3/V05L3**	**—**	**BXN80MA4**	**MXN20MA4**	22800	26000	43900	52000	17000
2.7	1840	1.4	520	**—**	**3/A04L2**	**BXN80MA4**	**—**	22700	26000	43800	51900	16900
2.7	1290	1.0	509	**3/V01L3**	**—**	**BXN80MA4**	**—**	7010	7010	23200	25300	5580
2.8	1750	1.0	495	**—**	**3/A03L2**	**BXN80MA4**	**MXN20MA4**	22600	25800	43500	51600	16600
2.8	1740	2.2	491	**—**	**3/A05L2**	**BXN80MA4**	**—**	22500	25800	43500	51500	16500
2.8	1450	1.4	502	**3/V03L3**	**—**	**BXN80MA4**	**MXN20MA4**	22600	25800	43600	51700	16700
2.8	1290	2.3	501	**3/V04L3**	**—**	**BXN80MA4**	**MXN20MA4**	22600	25800	43600	51700	16700
3.0	1660	1.5	469	**—**	**3/A04L2**	**BXN80MA4**	**—**	22400	25600	43200	51200	16300
3.0	1220	1.9	460	**3/V03L3**	**—**	**BXN80MA4**	**MXN20MA4**	22300	25500	43100	51000	16200
3.1	1240	1.1	443	**3/V01L3**	**—**	**BXN80MA4**	**—**	6870	6870	22700	24800	5330
3.1	1300	2.9	453	**3/V04L3**	**—**	**BXN80MA4**	**MXN20MA4**	22300	25500	43000	50900	16100
3.2	1250	1.5	430	**3/V01L3**	**—**	**BXN80MA4**	**—**	6840	6840	22600	24700	5270
3.3	1490	2.9	422	**—**	**3/A05L2**	**BXN80MA4**	**—**	22100	25200	42500	50400	15700
3.3	1050	0.9	415	**3/V00L3**	**—**	**BXN80MA4**	**—**	6810	6810	22500	26200	5210
3.4	1450	1.3	409	**—**	**3/A03L2**	**BXN80MA4**	**MXN20MA4**	22000	25100	42300	50200	15600

A



A

P_1 = 0.55 kW

n_2	M_2	S	i					Rn_2 [N]				
min^{-1}	Nm					IE3	IE3	MC/PC	MZ/PZ	HC	HZ	FZ
3.5	1410	2.3	398	—	3/A05L2	BXN80MA4	—	21900	25000	42200	50000	15400
3.5	1140	1.9	395	3/V03L3	—	BXN80MA4	MXN20MA4	21800	25000	42100	49900	15400
3.6	1370	1.8	386	—	3/A04L2	BXN80MA4	—	21800	24900	42000	49800	15300
3.8	1290	1.0	364	—	3/A01L2	BXN80MA4	MXN20MA4	6680	6680	22100	24200	4990
3.9	1250	1.6	352	—	3/A03L2	BXN80MA4	MXN20MA4	21500	24600	41400	49100	14800
4.0	1230	2.0	349	—	3/A04L2	BXN80MA4	—	21500	24500	41400	49000	14800
4.3	1150	1.4	326	—	3/A03L2	BXN80MA4	MXN20MA4	21200	24300	41000	48600	14400
4.4	1120	2.1	317	—	3/A04L2	BXN80MA4	—	21200	24200	40800	48400	14300
4.5	1100	1.0	311	—	3/A01L2	BXN80MA4	MXN20MA4	6530	6530	21600	23600	4740
4.9	1000	2.8	283	—	3/A04L2	BXN80MA4	—	21000	24000	40500	48000	13800
5.2	950	1.1	269	—	3/A01L2	BXN80MA4	MXN20MA4	6500	6500	21500	23500	4510
5.2	950	1.9	269	—	3/A03L2	BXN80MA4	MXN20MA4	21000	24000	40500	48000	13500
5.2	950	1.9	269	—	3/A03L2	BXN80MA4	MXN20MA4	21000	24000	40500	48000	13500
5.5	900	1.3	255	—	3/A01L2	BXN80MA4	MXN20MA4	6500	6500	21500	23500	4430
6.3	780	1.1	220	—	3/A01L2	BXN80MA4	MXN20MA4	6500	6500	21500	23500	4220
6.3	780	2.1	220	—	3/A03L2	BXN80MA4	MXN20MA4	21000	24000	40500	48000	12700
6.8	720	0.9	203	—	3/A00L2	BXN80MA4	MXN20MA4	6500	6500	21500	25000	4100
6.8	720	1.8	204	—	3/A01L2	BXN80MA4	MXN20MA4	6500	6500	21500	23500	4120
7.6	650	1.6	184	—	3/A01L2	BXN80MA4	MXN20MA4	6500	6500	21500	23500	3980
7.6	640	2.8	182	—	3/A03L2	BXN80MA4	MXN20MA4	21000	24000	40500	48000	11900
8.1	610	0.9	171	—	3/A00L2	BXN80MA4	MXN20MA4	6500	6500	21500	25000	3880
8.4	590	2.0	166	—	3/A01L2	BXN80MA4	MXN20MA4	6500	6500	21500	23500	3840
10.4	475	1.2	134	—	3/A00L2	BXN80MA4	MXN20MA4	6260	6260	20800	24200	3580
10.5	470	2.8	133	—	3/A01L2	BXN80MA4	MXN20MA4	6250	6250	20800	22700	3570
13.0	380	1.7	107	—	3/A00L2	BXN80MA4	MXN20MA4	5810	5810	19400	22600	3320
13.9	355	1.6	100	—	3/A00L2	BXN80MA4	MXN20MA4	5680	5680	19000	22100	3240
15.7	315	1.8	88.6	—	3/A00L2	BXN80MA4	MXN20MA4	5450	5450	18400	21300	3120
17.3	285	2.3	80.2	—	3/A00L2	BXN80MA4	MXN20MA4	5280	5280	17800	20700	3010
19.6	250	2.6	71.0	—	3/A00L2	BXN80MA4	MXN20MA4	5060	5060	17200	20000	2890

P_1 = 0.75 kW

n_2	M_2	S	i							Rn_2 [N]				
min^{-1}	Nm					IE2	IE3	IE2	IE3	MC/PC	MZ/PZ	HC	HZ	FZ
0.27	18500	2.6	5326	3/V11ML4	—	BE80B4	BX80B4	ME2SB4	MX2SB4	—	—	147800	150800	65000
0.28	17000	3.0	5046	3/V13ML4	—	BE80B4	BX80B4	ME2SB4	MX2SB4	—	—	192000	231000	80000
0.29	16500	1.7	4959	3/V10ML4	—	BE80B4	BX80B4	ME2SB4	MX2SB4	—	—	116400	147600	65000
0.29	16500	1.7	4959	3/V10ML4	—	BE80B4	BX80B4	ME2SB4	MX2SB4	—	—	116400	147600	65000
0.31	15400	1.9	4637	3/V10ML4	—	BE80B4	BX80B4	ME2SB4	MX2SB4	—	—	115300	146200	65000
0.31	15400	1.9	4637	3/V10ML4	—	BE80B4	BX80B4	ME2SB4	MX2SB4	—	—	115300	146200	65000
0.35	15500	1.9	4036	3/V10ML4	—	BE80B4	BX80B4	ME2SB4	MX2SB4	—	—	113100	143400	65000
0.35	15500	1.9	4036	3/V10ML4	—	BE80B4	BX80B4	ME2SB4	MX2SB4	—	—	113100	143400	65000
0.40	12400	2.4	3570	3/V10ML4	—	BE80B4	BX80B4	ME2SB4	MX2SB4	—	—	111100	140900	65000
0.40	12400	2.4	3570	3/V10ML4	—	BE80B4	BX80B4	ME2SB4	MX2SB4	—	—	111100	140900	65000
0.44	12500	2.2	3273	3/V10ML4	—	BE80B4	BX80B4	ME2SB4	MX2SB4	—	—	109700	139100	65000
0.44	12500	2.2	3273	3/V10ML4	—	BE80B4	BX80B4	ME2SB4	MX2SB4	—	—	109700	139100	65000
0.48	11400	2.6	2987	3/V10ML4	—	BE80B4	BX80B4	ME2SB4	MX2SB4	—	—	108300	137300	65000
0.48	11400	2.6	2987	3/V10ML4	—	BE80B4	BX80B4	ME2SB4	MX2SB4	—	—	108300	137300	65000
0.58	8140	1.4	2472	3/V07L3	—	BE80B4	BX80B4	ME2SB4	MX2SB4	40500	50700	91200	120000	45000
0.58	9520	2.9	2455	3/V10ML4	—	BE80B4	BX80B4	ME2SB4	MX2SB4	—	—	105300	133500	65000
0.58	9520	2.9	2455	3/V10ML4	—	BE80B4	BX80B4	ME2SB4	MX2SB4	—	—	105300	133500	65000
0.67	7350	1.2	2139	3/V06L3	—	BE80B4	BX80B4	ME2SB4	MX2SB4	33100	37700	75500	87100	35000
0.67	7480	1.5	2150	3/V07L3	—	BE80B4	BX80B4	ME2SB4	MX2SB4	39700	49700	89400	117600	45000
0.73	6470	1.9	1964	3/V07L3	—	BE80B4	BX80B4	ME2SB4	MX2SB4	39200	49000	88300	116100	45000
0.81	6070	1.4	1768	3/V06L3	—	BE80B4	BX80B4	ME2SB4	MX2SB4	32200	36700	73400	84800	35000
0.93	5520	2.0	1545	3/V07L3	—	BE80B4	BX80B4	ME2SB4	MX2SB4	37900	47400	85300	112200	45000
1.0	4850	1.0	1431	3/V05L3	—	BE80B4	BX80B4	ME2SB4	MX2SB4	26300	30000	50600	60000	23600
1.0	4990	1.7	1395	3/V06L3	—	BE80B4	BX80B4	ME2SB4	MX2SB4	31100	35500	71000	82000	34200
1.0	4910	2.5	1411	3/V07L3	—	BE80B4	BX80B4	ME2SB4	MX2SB4	37400	46800	84200	110800	44100
1.2	4170	1.3	1231	3/V05L3	—	BE80B4	BX80B4	ME2SB4	MX2SB4	25700	29400	49500	58700	22500
1.2	4120	2.0	1153	3/V06L3	—	BE80B4	BX80B4	ME2SB4	MX2SB4	30300	34500	69100	79800	32100
1.2	4160	1.9	1212	3/V06L3	—	BE80B4	BX80B4	ME2SB4	MX2SB4	30500	34800	69600	80300	32600
1.2	4200	2.5	1159	3/V07L3	—	BE80B4	BX80B4	ME2SB4	MX2SB4	36400	45500	81900	107700	41300



P_1 = 0.75 kW

n_2	M_2	S	i							Rn_2 [N]				
min^{-1}	Nm					IE2	IE3	IE2	IE3	MC/PC	MZ/PZ	HC	HZ	FZ
1.3	4200	1.1	1116	**3/V05L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	25300	29000	48900	57900	21700
1.4	3580	1.2	1057	**3/V05L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	25100	28700	48500	57500	21400
1.4	3550	2.7	992	**3/V06L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	29700	33800	67600	78100	30500
1.5	3320	1.2	981	**3/V04L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	24900	28400	48000	56900	20800
1.5	3680	2.1	930	**3/V06L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	29400	33500	67000	77300	29800
1.6	3360	1.3	894	**3/V05L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	24500	28100	47300	56100	20200
1.8	2870	1.5	793	**3/V05L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	24100	27600	46500	55100	19400
1.8	2830	2.7	791	**3/V06L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	28700	32700	65500	75600	28300
1.9	2560	1.1	736	**3/V03L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	23900	27300	46000	54600	18900
1.9	2890	1.2	769	**3/V04L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	24000	27500	46300	54900	19200
2.0	2840	0.9	710	**3/V04L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	23700	27100	45800	54300	18700
2.0	2790	1.5	715	**3/V05L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	23800	27200	45900	54300	18800
2.0	2790	2.7	698	**3/V06L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	28200	32200	64300	74200	27100
2.1	3060	2.0	671	**—**	**3/A06L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	28000	32000	64000	73800	26800
2.3	2790	2.1	611	**—**	**3/A06L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	27700	31600	63100	72800	25900
2.3	2170	1.0	623	**3/V03L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	23300	26600	45000	53300	17900
2.3	2260	1.6	623	**3/V04L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	23300	26600	45000	53300	17900
2.3	2260	2.0	623	**3/V05L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	23300	26600	45000	53300	17900
2.4	2770	1.2	594	**—**	**3/A05L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	23200	26500	44700	52900	17600
2.5	2140	1.5	568	**3/V04L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	23000	26300	44400	52600	17400
2.5	2300	2.1	576	**3/V05L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	23100	26300	44500	52700	17400
2.6	2530	2.9	555	**—**	**3/A06L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	27300	31100	62200	71800	25100
2.6	1890	1.4	544	**3/V03L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22900	26100	44100	52300	17100
2.7	2070	1.9	529	**3/V05L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22800	26000	43900	52000	17000
2.8	2420	1.0	520	**—**	**3/A04L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22700	26000	43800	51900	16900
2.8	1910	1.1	502	**3/V03L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22600	25800	43600	51700	16700
2.9	2290	1.7	491	**—**	**3/A05L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22500	25800	43500	51500	16500
2.9	1700	1.8	501	**3/V04L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22600	25800	43600	51700	16700
3.0	2180	1.1	469	**—**	**3/A04L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22400	25600	43200	51200	16300
3.1	1600	1.4	460	**3/V03L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22300	25500	43100	51000	16200
3.1	1850	2.6	462	**3/V05L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22300	25500	43100	51000	16200
3.2	1700	2.2	453	**3/V04L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22300	25500	43000	50900	16100
3.3	1640	1.1	430	**3/V01L3**	**—**	**BE80B4**	**BX80B4**	**—**	**—**	6840	6840	22600	24700	5270
3.4	1960	2.2	422	**—**	**3/A05L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22100	25200	42500	50400	15700
3.5	1900	1.0	409	**—**	**3/A03L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	22000	25100	42300	50200	15600
3.6	1850	1.7	398	**—**	**3/A05L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21900	25000	42200	50000	15400
3.6	1510	1.5	395	**3/V03L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21800	25000	42100	49900	15400
3.6	1580	2.4	396	**3/V05L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21900	25000	42100	50000	15400
3.7	1800	1.4	386	**—**	**3/A04L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21800	24900	42000	49800	15300
3.7	1450	2.4	384	**3/V04L3**	**—**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21800	24900	41900	49700	15200
4.1	1640	1.2	352	**—**	**3/A03L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21500	24600	41400	49100	14800
4.1	1620	1.5	349	**—**	**3/A04L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21500	24500	41400	49000	14800
4.3	1530	2.4	329	**—**	**3/A05L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21300	24300	41000	48600	14500
4.4	1520	1.1	326	**—**	**3/A03L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21200	24300	41000	48600	14400
4.5	1480	1.6	317	**—**	**3/A04L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21200	24200	40800	48400	14300
5.1	1320	2.2	283	**—**	**3/A04L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40500	48000	13800
5.1	1300	2.8	280	**—**	**3/A05L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40500	48000	13700
5.3	1250	1.5	269	**—**	**3/A03L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40500	48000	13500
5.3	1250	1.5	269	**—**	**3/A03L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40500	48000	13500
5.6	1190	1.0	255	**—**	**3/A01L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6500	6500	21500	23500	4430
6.5	1020	1.6	220	**—**	**3/A03L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40500	48000	12700
7.0	950	1.4	204	**—**	**3/A01L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6500	6500	21500	23500	4120
7.8	860	1.2	184	**—**	**3/A01L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6500	6500	21500	23500	3980
7.9	850	2.2	182	**—**	**3/A03L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	21000	24000	40500	48000	11900
8.6	770	1.5	166	**—**	**3/A01L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6500	6500	21500	23500	3840
10.8	620	2.1	133	**—**	**3/A01L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	6250	6250	20800	22700	3570
13.4	500	1.3	107	**—**	**3/A00L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	5810	5810	19400	22600	3320
14.0	475	2.4	102	**—**	**3/A01L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	5710	5710	19100	20900	3260
14.3	465	1.2	100	**—**	**3/A00L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	5680	5680	19000	22100	3240
16.1	415	1.3	88.6	**—**	**3/A00L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	5450	5450	18400	21300	3120
17.8	375	1.7	80.2	**—**	**3/A00L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	5280	5280	17800	20700	3010
20.1	330	2.0	71.0	**—**	**3/A00L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	5060	5060	17200	20000	2890
23.4	285	2.3	61.2	**—**	**3/A00L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	4820	4820	16400	19100	2750
27.6	240	2.3	51.8	**—**	**3/A00L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	4560	4560	15600	18200	2610
36	185	3.0	39.6	**—**	**3/A00L2**	**BE80B4**	**BX80B4**	**ME2SB4**	**MX2SB4**	4170	4170	14400	16800	2380



P_1 = 0.75 kW

n_2	M_2	S	i					Rn_2 [N]				
min^{-1}	Nm					IE3	IE3	MC/PC	MZ/PZ	HC	HZ	FZ
0.27	18500	2.6	5326	**3/V11ML4**	**—**	**BXN80MB4**	**MXN20MA4**	—	—	147800	150800	65000
0.28	17000	3.0	5046	**3/V13ML4**	**—**	**BXN80MB4**	**MXN20MA4**	—	—	192000	231000	80000
0.29	16500	1.7	4959	**3/V10ML4**	**—**	**BXN80MB4**	**MXN20MA4**	—	—	116400	147600	65000
0.29	16500	1.7	4959	**3/V10ML4**	**—**	**BXN80MB4**	**MXN20MA4**	—	—	116400	147600	65000
0.31	15400	1.9	4637	**3/V10ML4**	**—**	**BXN80MB4**	**MXN20MA4**	—	—	115300	146200	65000
0.31	15400	1.9	4637	**3/V10ML4**	**—**	**BXN80MB4**	**MXN20MA4**	—	—	115300	146200	65000
0.35	15500	1.9	4036	**3/V10ML4**	**—**	**BXN80MB4**	**MXN20MA4**	—	—	113100	143400	65000
0.35	15500	1.9	4036	**3/V10ML4**	**—**	**BXN80MB4**	**MXN20MA4**	—	—	113100	143400	65000
0.40	12400	2.4	3570	**3/V10ML4**	**—**	**BXN80MB4**	**MXN20MA4**	—	—	111100	140900	65000
0.40	12400	2.4	3570	**3/V10ML4**	**—**	**BXN80MB4**	**MXN20MA4**	—	—	111100	140900	65000
0.44	12500	2.2	3273	**3/V10ML4**	**—**	**BXN80MB4**	**MXN20MA4**	—	—	109700	139100	65000
0.44	12500	2.2	3273	**3/V10ML4**	**—**	**BXN80MB4**	**MXN20MA4**	—	—	109700	139100	65000
0.48	11400	2.6	2987	**3/V10ML4**	**—**	**BXN80MB4**	**MXN20MA4**	—	—	108300	137300	65000
0.48	11400	2.6	2987	**3/V10ML4**	**—**	**BXN80MB4**	**MXN20MA4**	—	—	108300	137300	65000
0.58	8140	1.4	2472	**3/V07L3**	**—**	**BXN80MB4**	**MXN20MB4**	40500	50700	91200	120000	45000
0.58	9520	2.9	2455	**3/V10ML4**	**—**	**BXN80MB4**	**MXN20MA4**	—	—	105300	133500	65000
0.58	9520	2.9	2455	**3/V10ML4**	**—**	**BXN80MB4**	**MXN20MA4**	—	—	105300	133500	65000
0.67	7350	1.2	2139	**3/V06L3**	**—**	**BXN80MB4**	**MXN20MB4**	33100	37700	75500	87100	35000
0.67	7480	1.5	2150	**3/V07L3**	**—**	**BXN80MB4**	**MXN20MB4**	39700	49700	89400	117600	45000
0.73	6470	1.9	1964	**3/V07L3**	**—**	**BXN80MB4**	**MXN20MB4**	39200	49000	88300	116100	45000
0.81	6070	1.4	1768	**3/V06L3**	**—**	**BXN80MB4**	**MXN20MB4**	32200	36700	73400	84800	35000
0.93	5520	2.0	1545	**3/V07L3**	**—**	**BXN80MB4**	**MXN20MB4**	37900	47400	85300	112200	45000
1.0	4850	1.0	1431	**3/V05L3**	**—**	**BXN80MB4**	**MXN20MB4**	26300	30000	50600	60000	23600
1.0	4990	1.7	1395	**3/V06L3**	**—**	**BXN80MB4**	**MXN20MB4**	31100	35500	71000	82000	34200
1.0	4910	2.5	1411	**3/V07L3**	**—**	**BXN80MB4**	**MXN20MB4**	37400	46800	84200	110800	44100
1.2	4170	1.3	1231	**3/V05L3**	**—**	**BXN80MB4**	**MXN20MB4**	25700	29400	49500	58700	22500
1.2	4120	2.0	1153	**3/V06L3**	**—**	**BXN80MB4**	**MXN20MB4**	30300	34500	69100	79800	32100
1.2	4160	1.9	1212	**3/V06L3**	**—**	**BXN80MB4**	**MXN20MB4**	30500	34800	69600	80300	32600
1.2	4200	2.5	1159	**3/V07L3**	**—**	**BXN80MB4**	**MXN20MB4**	36400	45500	81900	107700	41300
1.3	4200	1.1	1116	**3/V05L3**	**—**	**BXN80MB4**	**MXN20MB4**	25300	29000	48900	57900	21700
1.4	3580	1.2	1057	**3/V05L3**	**—**	**BXN80MB4**	**MXN20MB4**	25100	28700	48500	57500	21400
1.4	3550	2.7	992	**3/V06L3**	**—**	**BXN80MB4**	**MXN20MB4**	29700	33800	67600	78100	30500
1.5	3320	1.2	981	**3/V04L3**	**—**	**BXN80MB4**	**MXN20MB4**	24900	28400	48000	56900	20800
1.5	3680	2.1	930	**3/V06L3**	**—**	**BXN80MB4**	**MXN20MB4**	29400	33500	67000	77300	29800
1.6	3360	1.3	894	**3/V05L3**	**—**	**BXN80MB4**	**MXN20MB4**	24500	28100	47300	56100	20200
1.8	2870	1.5	793	**3/V05L3**	**—**	**BXN80MB4**	**MXN20MB4**	24100	27600	46500	55100	19400
1.8	2830	2.7	791	**3/V06L3**	**—**	**BXN80MB4**	**MXN20MB4**	28700	32700	65500	75600	28300
1.9	2560	1.1	736	**3/V03L3**	**—**	**BXN80MB4**	**MXN20MB4**	23900	27300	46000	54600	18900
1.9	2890	1.2	769	**3/V04L3**	**—**	**BXN80MB4**	**MXN20MB4**	24000	27500	46300	54900	19200
2.0	2840	0.9	710	**3/V04L3**	**—**	**BXN80MB4**	**MXN20MB4**	23700	27100	45800	54300	18700
2.0	2790	1.5	715	**3/V05L3**	**—**	**BXN80MB4**	**MXN20MB4**	23800	27200	45900	54300	18800
2.0	2790	2.7	698	**3/V06L3**	**—**	**BXN80MB4**	**MXN20MB4**	28200	32200	64300	74200	27100
2.1	3060	2.0	671	**—**	**3/A06L2**	**BXN80MB4**	**—**	28000	32000	64000	73800	26800
2.3	2790	2.1	611	**—**	**3/A06L2**	**BXN80MB4**	**—**	27700	31600	63100	72800	25900
2.3	2170	1.0	623	**3/V03L3**	**—**	**BXN80MB4**	**MXN20MB4**	23300	26600	45000	53300	17900
2.3	2260	1.6	623	**3/V04L3**	**—**	**BXN80MB4**	**MXN20MB4**	23300	26600	45000	53300	17900
2.3	2260	2.0	623	**3/V05L3**	**—**	**BXN80MB4**	**MXN20MB4**	23300	26600	45000	53300	17900
2.4	2770	1.2	594	**—**	**3/A05L2**	**BXN80MB4**	**—**	23200	26500	44700	52900	17600
2.5	2140	1.5	568	**3/V04L3**	**—**	**BXN80MB4**	**MXN20MB4**	23000	26300	44400	52600	17400
2.5	2300	2.1	576	**3/V05L3**	**—**	**BXN80MB4**	**MXN20MB4**	23100	26300	44500	52700	17400
2.6	2530	2.9	555	**—**	**3/A06L2**	**BXN80MB4**	**—**	27300	31100	62200	71800	25100
2.6	1890	1.4	544	**3/V03L3**	**—**	**BXN80MB4**	**MXN20MB4**	22900	26100	44100	52300	17100
2.7	2070	1.9	529	**3/V05L3**	**—**	**BXN80MB4**	**MXN20MB4**	22800	26000	43900	52000	17000
2.8	2420	1.0	520	**—**	**3/A04L2**	**BXN80MB4**	**—**	22700	26000	43800	51900	16900
2.8	1910	1.1	502	**3/V03L3**	**—**	**BXN80MB4**	**MXN20MB4**	22600	25800	43600	51700	16700
2.9	2290	1.7	491	**—**	**3/A05L2**	**BXN80MB4**	**—**	22500	25800	43500	51500	16500
2.9	1700	1.8	501	**3/V04L3**	**—**	**BXN80MB4**	**MXN20MB4**	22600	25800	43600	51700	16700
3.0	2180	1.1	469	**—**	**3/A04L2**	**BXN80MB4**	**—**	22400	25600	43200	51200	16300
3.1	1600	1.4	460	**3/V03L3**	**—**	**BXN80MB4**	**MXN20MB4**	22300	25500	43100	51000	16200
3.1	1850	2.6	462	**3/V05L3**	**—**	**BXN80MB4**	**MXN20MB4**	22300	25500	43100	51000	16200
3.2	1700	2.2	453	**3/V04L3**	**—**	**BXN80MB4**	**MXN20MB4**	22300	25500	43000	50900	16100
3.3	1640	1.1	430	**3/V01L3**	**—**	**BXN80MB4**	**—**	6840	6840	22600	24700	5270
3.4	1960	2.2	422	**—**	**3/A05L2**	**BXN80MB4**	**—**	22100	25200	42500	50400	15700
3.5	1900	1.0	409	**—**	**3/A03L2**	**BXN80MB4**	**MXN20MB4**	22000	25100	42300	50200	15600
3.6	1850	1.7	398	**—**	**3/A05L2**	**BXN80MB4**	**—**	21900	25000	42200	50000	15400
3.6	1510	1.5	395	**3/V03L3**	**—**	**BXN80MB4**	**MXN20MB4**	21800	25000	42100	49900	15400
3.6	1580	2.4	396	**3/V05L3**	**—**	**BXN80MB4**	**MXN20MB4**	21900	25000	42100	50000	15400



P_1 = 0.75 kW

n_2 min^{-1}	M_2 Nm	S	i			IE3	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
3.7	1800	1.4	386	—	3/A04L2	BXN80MB4	—	21800	24900	42000	49800	15300
3.7	1450	2.4	384	3/V04L3	—	BXN80MB4	MXN20MB4	21800	24900	41900	49700	15200
4.1	1640	1.2	352	—	3/A03L2	BXN80MB4	MXN20MB4	21500	24600	41400	49100	14800
4.1	1620	1.5	349	—	3/A04L2	BXN80MB4	—	21500	24500	41400	49000	14800
4.3	1530	2.4	329	—	3/A05L2	BXN80MB4	—	21300	24300	41000	48600	14500
4.4	1520	1.1	326	—	3/A03L2	BXN80MB4	MXN20MB4	21200	24300	41000	48600	14400
4.5	1480	1.6	317	—	3/A04L2	BXN80MB4	—	21200	24200	40800	48400	14300
5.1	1320	2.2	283	—	3/A04L2	BXN80MB4	—	21000	24000	40500	48000	13800
5.1	1300	2.8	280	—	3/A05L2	BXN80MB4	—	21000	24000	40500	48000	13700
5.3	1250	1.5	269	—	3/A03L2	BXN80MB4	MXN20MB4	21000	24000	40500	48000	13500
5.3	1250	1.5	269	—	3/A03L2	BXN80MB4	MXN20MB4	21000	24000	40500	48000	13500
5.6	1190	1.0	255	—	3/A01L2	BXN80MB4	MXN20MB4	6500	6500	21500	23500	4430
6.5	1020	1.6	220	—	3/A03L2	BXN80MB4	MXN20MB4	21000	24000	40500	48000	12700
7.0	950	1.4	204	—	3/A01L2	BXN80MB4	MXN20MB4	6500	6500	21500	23500	4120
7.8	860	1.2	184	—	3/A01L2	BXN80MB4	MXN20MB4	6500	6500	21500	23500	3980
7.9	850	2.2	182	—	3/A03L2	BXN80MB4	MXN20MB4	21000	24000	40500	48000	11900
8.6	770	1.5	166	—	3/A01L2	BXN80MB4	MXN20MB4	6500	6500	21500	23500	3840
10.8	620	2.1	133	—	3/A01L2	BXN80MB4	MXN20MB4	6250	6250	20800	22700	3570
13.4	500	1.3	107	—	3/A00L2	BXN80MB4	MXN20MB4	5810	5810	19400	22600	3320
14.0	475	2.4	102	—	3/A01L2	BXN80MB4	MXN20MB4	5710	5710	19100	20900	3260
14.3	465	1.2	100	—	3/A00L2	BXN80MB4	MXN20MB4	5680	5680	19000	22100	3240
16.1	415	1.3	88.6	—	3/A00L2	BXN80MB4	MXN20MB4	5450	5450	18400	21300	3120
17.8	375	1.7	80.2	—	3/A00L2	BXN80MB4	MXN20MB4	5280	5280	17800	20700	3010
20.1	330	2.0	71.0	—	3/A00L2	BXN80MB4	MXN20MB4	5060	5060	17200	20000	2890
23.4	285	2.3	61.2	—	3/A00L2	BXN80MB4	MXN20MB4	4820	4820	16400	19100	2750
27.6	240	2.3	51.8	—	3/A00L2	BXN80MB4	MXN20MB4	4560	4560	15600	18200	2610
36	185	3.0	39.6	—	3/A00L2	BXN80MB4	MXN20MB4	4170	4170	14400	16800	2380

P_1 = 1.1 kW

n_2 min^{-1}	M_2 Nm	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
0.27	27300	1.7	5326	3/V11ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	147800	150800	65000
0.28	25200	2.0	5046	3/V13ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	192000	231000	80000
0.29	24400	1.1	4959	3/V10ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	116400	147600	65000
0.29	24400	1.1	4959	3/V10ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	116400	147600	65000
0.31	22900	1.3	4637	3/V10ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	115300	146200	65000
0.31	22900	1.3	4637	3/V10ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	115300	146200	65000
0.32	22900	2.1	4410	3/V11ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	143900	146800	65000
0.32	23600	2.4	4536	3/V13ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	192000	231000	80000
0.35	22900	1.3	4036	3/V10ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	113100	143400	65000
0.35	22900	1.3	4036	3/V10ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	113100	143400	65000
0.35	20500	2.4	4106	3/V11ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	142400	145300	65000
0.35	21000	2.9	4046	3/V13ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	192000	231000	80000
0.40	18300	1.6	3570	3/V10ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	111100	140900	65000
0.40	18300	1.6	3570	3/V10ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	111100	140900	65000
0.40	17800	2.4	3557	3/V11ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	139500	142400	65000
0.41	19900	2.9	3515	3/V13ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	192000	231000	80000
0.44	18600	1.5	3273	3/V10ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	109700	139100	65000
0.44	18600	1.5	3273	3/V10ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	109700	139100	65000
0.44	18300	2.6	3222	3/V11ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	137600	140400	65000
0.44	18500	2.9	3263	3/V13ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	192000	231000	80000
0.47	17200	2.8	3063	3/V11ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	136600	139400	65000
0.48	16900	1.8	2987	3/V10ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	108300	137300	65000
0.48	16900	1.8	2987	3/V10ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	108300	137300	65000
0.58	12000	0.9	2472	3/V07L3	—	BE90S4	BX90S4	ME3SA4	MX3SA4	40500	50700	91200	120000	45000
0.58	14100	1.9	2455	3/V10ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	105300	133500	65000
0.58	14100	1.9	2455	3/V10ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	105300	133500	65000
0.66	12200	2.3	2156	3/V10ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	103400	131100	65000
0.66	12200	2.3	2156	3/V10ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	103400	131100	65000
0.67	11100	1.0	2150	3/V07L3	—	BE90S4	BX90S4	ME3SA4	MX3SA4	39700	49700	89400	117600	45000
0.71	11400	2.6	2016	3/V10ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	102400	129800	65000
0.71	11400	2.6	2016	3/V10ML4	—	BE90S4	BX90S4	ME3SA4	MX3SA4	—	—	102400	129800	65000



P_1 = 1.1 kW

n_2	M_2	S	i							Rn_2 [N]				
min^{-1}	Nm					IE2	IE3	IE2	IE3	MC/PC	MZ/PZ	HC	HZ	FZ
0.73	9570	1.3	1964	**3/V07L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	39200	49000	88300	116100	45000
0.77	10500	2.6	1855	**3/V10ML4**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	—	—	101200	128300	65000
0.77	10500	2.6	1855	**3/V10ML4**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	—	—	101200	128300	65000
0.81	8990	1.0	1768	**3/V06L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	32200	36700	73400	84800	35000
0.93	8180	1.3	1545	**3/V07L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	37900	47400	85300	112200	45000
1.0	7380	1.1	1395	**3/V06L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	31100	35500	71000	82000	34200
1.0	7270	1.7	1411	**3/V07L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	37400	46800	84200	110800	44100
1.1	6640	2.2	1288	**3/V07L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	36900	46200	83100	109300	42800
1.2	6100	1.4	1153	**3/V06L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	30300	34500	69100	79800	32100
1.2	6160	1.3	1212	**3/V06L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	30500	34800	69600	80300	32600
1.2	6210	1.7	1159	**3/V07L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	36400	45500	81900	107700	41300
1.4	5250	1.8	992	**3/V06L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	29700	33800	67600	78100	30500
1.4	5370	2.7	1015	**3/V07L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	35700	44600	80300	105700	39500
1.5	5440	1.5	930	**3/V06L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	29400	33500	67000	77300	29800
1.6	4930	2.5	920	**3/V07L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	35200	44000	79200	104200	38200
1.8	4250	1.0	793	**3/V05L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	24100	27600	46500	55100	19400
1.8	4190	1.8	791	**3/V06L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	28700	32700	65500	75600	28300
1.8	4520	2.2	773	**3/V07L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	34300	42900	77300	101600	36100
2.0	4130	1.0	715	**3/V05L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	23800	27200	45900	54300	18800
2.0	4130	1.8	698	**3/V06L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	28200	32200	64300	74200	27100
2.1	4530	1.3	671	**—**	**3/A06L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	28000	32000	64000	73800	26800
2.2	3870	2.4	661	**3/V06L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	28000	31900	63800	73700	26600
2.3	4120	1.4	611	**—**	**3/A06L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	27700	31600	63100	72800	25900
2.3	3340	1.1	623	**3/V04L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	23300	26600	45000	53300	17900
2.3	3340	1.3	623	**3/V05L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	23300	26600	45000	53300	17900
2.5	3160	1.0	568	**3/V04L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	23000	26300	44400	52600	17400
2.5	3410	1.4	576	**3/V05L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	23100	26300	44500	52700	17400
2.5	3330	2.6	569	**3/V06L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	27400	31200	62500	72100	25300
2.6	3740	1.9	555	**—**	**3/A06L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	27300	31100	62200	71800	25100
2.6	2800	1.0	544	**3/V03L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22900	26100	44100	52300	17100
2.7	3060	1.3	529	**3/V05L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22800	26000	43900	52000	17000
2.7	3080	2.5	527	**3/V06L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	27100	30900	61800	71300	24700
2.8	3410	2.1	505	**—**	**3/A06L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	26900	30700	61400	70900	24400
2.9	3380	1.1	491	**—**	**3/A05L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22500	25800	43500	51500	16500
2.9	2510	1.2	501	**3/V04L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22600	25800	43600	51700	16700
3.1	2370	1.0	460	**3/V03L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22300	25500	43100	51000	16200
3.1	2730	1.8	462	**3/V05L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22300	25500	43100	51000	16200
3.2	2520	1.5	453	**3/V04L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22300	25500	43000	50900	16100
3.3	2940	2.6	435	**—**	**3/A06L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	26400	30100	60100	69400	23200
3.4	2910	1.5	422	**—**	**3/A05L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	22100	25200	42500	50400	15700
3.6	2740	1.2	398	**—**	**3/A05L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21900	25000	42200	50000	15400
3.6	2230	1.0	395	**3/V03L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21800	25000	42100	49900	15400
3.6	2340	1.6	396	**3/V05L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21900	25000	42100	50000	15400
3.7	2660	0.9	386	**—**	**3/A04L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21800	24900	42000	49800	15300
3.7	2620	2.2	388	**—**	**3/A06L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	25900	29600	59100	68300	22300
3.7	2140	1.6	384	**3/V04L3**	**—**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21800	24900	41900	49700	15200
3.8	2560	2.4	380	**—**	**3/A06L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	25900	29500	59000	68100	22200
4.1	2400	1.0	349	**—**	**3/A04L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21500	24500	41400	49000	14800
4.3	2270	1.6	329	**—**	**3/A05L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21300	24300	41000	48600	14500
4.5	2180	1.1	317	**—**	**3/A04L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21200	24200	40800	48400	14300
5.1	1950	1.5	283	**—**	**3/A04L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	13800
5.1	1930	1.9	280	**—**	**3/A05L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	13700
5.3	1850	1.0	269	**—**	**3/A03L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	13500
5.3	1850	1.0	269	**—**	**3/A03L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	13500
5.7	1720	2.0	250	**—**	**3/A04L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	13200
5.9	1660	2.6	241	**—**	**3/A05L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	13000
6.3	1560	2.2	226	**—**	**3/A04L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	12800
6.5	1520	1.1	220	**—**	**3/A03L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	12700
6.7	1460	2.1	212	**—**	**3/A05L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	12500
6.7	1460	2.1	212	**—**	**3/A05L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	12500
7.0	1410	0.9	204	**—**	**3/A01L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	6500	6500	21500	23500	4120
7.0	1410	2.5	205	**—**	**3/A04L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	12400
7.9	1250	1.5	182	**—**	**3/A03L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	11900
8.2	1200	2.5	174	**—**	**3/A04L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	11700
8.2	1210	3.0	175	**—**	**3/A05L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	11700



P_1 = 1.1 kW

n_2 min^{-1}	M_2 Nm	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
8.6	1140	1.0	166	—	**3/A01L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	6500	6500	21500	23500	3840
8.8	1120	2.6	162	—	**3/A04L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	11400
8.8	1120	2.6	162	—	**3/A05L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40500	48000	11400
9.6	1030	2.3	149	—	**3/A04L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	21000	24000	40400	47900	11100
10.8	920	1.4	133	—	**3/A01L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	6250	6250	20800	22700	3570
12.2	810	3.0	117	—	**3/A04L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	19300	22100	37600	44500	10300
14.0	700	1.6	102	—	**3/A01L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5710	5710	19100	20900	3260
14.8	670	2.5	96.9	—	**3/A03L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	18200	20700	35500	42100	9630
16.1	610	0.9	88.6	—	**3/A00L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5450	5450	18400	21300	3120
16.2	610	2.7	88.5	—	**3/A03L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	17600	20100	34600	41000	9340
17.6	560	2.3	81.3	—	**3/A01L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5300	5300	17900	19600	3030
17.8	550	1.2	80.2	—	**3/A00L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5280	5280	17800	20700	3010
19.3	510	2.2	74.2	—	**3/A01L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5140	5140	17400	19000	2940
20.1	490	1.3	71.0	—	**3/A00L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	5060	5060	17200	20000	2890
23.4	420	1.5	61.2	—	**3/A00L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	4820	4820	16400	19100	2750
27.6	355	1.5	51.8	—	**3/A00L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	4560	4560	15600	18200	2610
29.1	340	2.5	49.1	—	**3/A01L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	4480	4480	15400	16800	2560
34	285	2.3	41.5	—	**3/A00L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	4240	4240	14600	17000	2420
36	275	2.0	39.6	—	**3/A00L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	4170	4170	14400	16800	2380
45	220	3.0	31.7	—	**3/A00L2**	**BE90S4**	**BX90S4**	**ME3SA4**	**MX3SA4**	3870	3870	13500	15700	2210

P_1 = 1.1 kW

n_2 min^{-1}	M_2 Nm	S	i			IE3	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
0.27	27300	1.7	5326	**3/V11ML4**	—	**BXN90S4**	—	—	—	147800	150800	65000
0.28	25200	2.0	5046	**3/V13ML4**	—	**BXN90S4**	—	—	—	192000	231000	80000
0.29	24400	1.1	4959	**3/V10ML4**	—	**BXN90S4**	—	—	—	116400	147600	65000
0.29	24400	1.1	4959	**3/V10ML4**	—	**BXN90S4**	—	—	—	116400	147600	65000
0.31	22900	1.3	4637	**3/V10ML4**	—	**BXN90S4**	—	—	—	115300	146200	65000
0.31	22900	1.3	4637	**3/V10ML4**	—	**BXN90S4**	—	—	—	115300	146200	65000
0.32	22900	2.1	4410	**3/V11ML4**	—	**BXN90S4**	—	—	—	143900	146800	65000
0.32	23600	2.4	4536	**3/V13ML4**	—	**BXN90S4**	—	—	—	192000	231000	80000
0.35	22900	1.3	4036	**3/V10ML4**	—	**BXN90S4**	—	—	—	113100	143400	65000
0.35	22900	1.3	4036	**3/V10ML4**	—	**BXN90S4**	—	—	—	113100	143400	65000
0.35	20500	2.4	4106	**3/V11ML4**	—	**BXN90S4**	—	—	—	142400	145300	65000
0.35	21000	2.9	4046	**3/V13ML4**	—	**BXN90S4**	—	—	—	192000	231000	80000
0.40	18300	1.6	3570	**3/V10ML4**	—	**BXN90S4**	—	—	—	111100	140900	65000
0.40	18300	1.6	3570	**3/V10ML4**	—	**BXN90S4**	—	—	—	111100	140900	65000
0.40	17800	2.4	3557	**3/V11ML4**	—	**BXN90S4**	—	—	—	139500	142400	65000
0.41	19900	2.9	3515	**3/V13ML4**	—	**BXN90S4**	—	—	—	192000	231000	80000
0.44	18600	1.5	3273	**3/V10ML4**	—	**BXN90S4**	—	—	—	109700	139100	65000
0.44	18600	1.5	3273	**3/V10ML4**	—	**BXN90S4**	—	—	—	109700	139100	65000
0.44	18300	2.6	3222	**3/V11ML4**	—	**BXN90S4**	—	—	—	137600	140400	65000
0.44	18500	2.9	3263	**3/V13ML4**	—	**BXN90S4**	—	—	—	192000	231000	80000
0.47	17200	2.8	3063	**3/V11ML4**	—	**BXN90S4**	—	—	—	136600	139400	65000
0.48	16900	1.8	2987	**3/V10ML4**	—	**BXN90S4**	—	—	—	108300	137300	65000
0.48	16900	1.8	2987	**3/V10ML4**	—	**BXN90S4**	—	—	—	108300	137300	65000
0.58	12000	0.9	2472	**3/V07L3**	—	**BXN90S4**	—	40500	50700	91200	120000	45000
0.58	14100	1.9	2455	**3/V10ML4**	—	**BXN90S4**	—	—	—	105300	133500	65000
0.58	14100	1.9	2455	**3/V10ML4**	—	**BXN90S4**	—	—	—	105300	133500	65000
0.66	12200	2.3	2156	**3/V10ML4**	—	**BXN90S4**	—	—	—	103400	131100	65000
0.66	12200	2.3	2156	**3/V10ML4**	—	**BXN90S4**	—	—	—	103400	131100	65000
0.67	11100	1.0	2150	**3/V07L3**	—	**BXN90S4**	—	39700	49700	89400	117600	45000
0.71	11400	2.6	2016	**3/V10ML4**	—	**BXN90S4**	—	—	—	102400	129800	65000
0.71	11400	2.6	2016	**3/V10ML4**	—	**BXN90S4**	—	—	—	102400	129800	65000
0.73	9570	1.3	1964	**3/V07L3**	—	**BXN90S4**	—	39200	49000	88300	116100	45000
0.77	10500	2.6	1855	**3/V10ML4**	—	**BXN90S4**	—	—	—	101200	128300	65000
0.77	10500	2.6	1855	**3/V10ML4**	—	**BXN90S4**	—	—	—	101200	128300	65000
0.81	8990	1.0	1768	**3/V06L3**	—	**BXN90S4**	—	32200	36700	73400	84800	35000
0.93	8180	1.3	1545	**3/V07L3**	—	**BXN90S4**	—	37900	47400	85300	112200	45000
1.0	7380	1.1	1395	**3/V06L3**	—	**BXN90S4**	—	31100	35500	71000	82000	34200



P_1 = 1.1 kW

n_2	M_2	S	i					Rn_2 [N]				
min^{-1}	Nm					IE3	IE3	MC/PC	MZ/PZ	HC	HZ	FZ
1.0	7270	1.7	1411	**3/V07L3**	**—**	**BXN90S4**	—	37400	46800	84200	110800	44100
1.1	6640	2.2	1288	**3/V07L3**	**—**	**BXN90S4**	—	36900	46200	83100	109300	42800
1.2	6100	1.4	1153	**3/V06L3**	**—**	**BXN90S4**	—	30300	34500	69100	79800	32100
1.2	6160	1.3	1212	**3/V06L3**	**—**	**BXN90S4**	—	30500	34800	69600	80300	32600
1.2	6210	1.7	1159	**3/V07L3**	**—**	**BXN90S4**	—	36400	45500	81900	107700	41300
1.4	5250	1.8	992	**3/V06L3**	**—**	**BXN90S4**	—	29700	33800	67600	78100	30500
1.4	5370	2.7	1015	**3/V07L3**	**—**	**BXN90S4**	—	35700	44600	80300	105700	39500
1.5	5440	1.5	930	**3/V06L3**	**—**	**BXN90S4**	—	29400	33500	67000	77300	29800
1.6	4930	2.5	920	**3/V07L3**	**—**	**BXN90S4**	—	35200	44000	79200	104200	38200
1.8	4250	1.0	793	**3/V05L3**	**—**	**BXN90S4**	—	24100	27600	46500	55100	19400
1.8	4190	1.8	791	**3/V06L3**	**—**	**BXN90S4**	—	28700	32700	65500	75600	28300
1.8	4520	2.2	773	**3/V07L3**	**—**	**BXN90S4**	—	34300	42900	77300	101600	36100
2.0	4130	1.0	715	**3/V05L3**	**—**	**BXN90S4**	—	23800	27200	45900	54300	18800
2.0	4130	1.8	698	**3/V06L3**	**—**	**BXN90S4**	—	28200	32200	64300	74200	27100
2.1	4530	1.3	671	**—**	**3/A06L2**	**BXN90S4**	—	28000	32000	64000	73800	26800
2.2	3870	2.4	661	**3/V06L3**	**—**	**BXN90S4**	—	28000	31900	63800	73700	26600
2.3	4120	1.4	611	**—**	**3/A06L2**	**BXN90S4**	—	27700	31600	63100	72800	25900
2.3	3340	1.1	623	**3/V04L3**	**—**	**BXN90S4**	—	23300	26600	45000	53300	17900
2.3	3340	1.3	623	**3/V05L3**	**—**	**BXN90S4**	—	23300	26600	45000	53300	17900
2.5	3160	1.0	568	**3/V04L3**	**—**	**BXN90S4**	—	23000	26300	44400	52600	17400
2.5	3410	1.4	576	**3/V05L3**	**—**	**BXN90S4**	—	23100	26300	44500	52700	17400
2.5	3330	2.6	569	**3/V06L3**	**—**	**BXN90S4**	—	27400	31200	62500	72100	25300
2.6	3740	1.9	555	**—**	**3/A06L2**	**BXN90S4**	—	27300	31100	62200	71800	25100
2.6	2800	1.0	544	**3/V03L3**	**—**	**BXN90S4**	—	22900	26100	44100	52300	17100
2.7	3060	1.3	529	**3/V05L3**	**—**	**BXN90S4**	—	22800	26000	43900	52000	17000
2.7	3080	2.5	527	**3/V06L3**	**—**	**BXN90S4**	—	27100	30900	61800	71300	24700
2.8	3410	2.1	505	**—**	**3/A06L2**	**BXN90S4**	—	26900	30700	61400	70900	24400
2.9	3380	1.1	491	**—**	**3/A05L2**	**BXN90S4**	—	22500	25800	43500	51500	16500
2.9	2510	1.2	501	**3/V04L3**	**—**	**BXN90S4**	—	22600	25800	43600	51700	16700
3.1	2370	1.0	460	**3/V03L3**	**—**	**BXN90S4**	—	22300	25500	43100	51000	16200
3.1	2730	1.8	462	**3/V05L3**	**—**	**BXN90S4**	—	22300	25500	43100	51000	16200
3.2	2520	1.5	453	**3/V04L3**	**—**	**BXN90S4**	—	22300	25500	43000	50900	16100
3.3	2940	2.6	435	**—**	**3/A06L2**	**BXN90S4**	—	26400	30100	60100	69400	23200
3.4	2910	1.5	422	**—**	**3/A05L2**	**BXN90S4**	—	22100	25200	42500	50400	15700
3.6	2740	1.2	398	**—**	**3/A05L2**	**BXN90S4**	—	21900	25000	42200	50000	15400
3.6	2230	1.0	395	**3/V03L3**	**—**	**BXN90S4**	—	21800	25000	42100	49900	15400
3.6	2340	1.6	396	**3/V05L3**	**—**	**BXN90S4**	—	21900	25000	42100	50000	15400
3.7	2660	0.9	386	**—**	**3/A04L2**	**BXN90S4**	—	21800	24900	42000	49800	15300
3.7	2620	2.2	388	**—**	**3/A06L2**	**BXN90S4**	—	25900	29600	59100	68300	22300
3.7	2140	1.6	384	**3/V04L3**	**—**	**BXN90S4**	—	21800	24900	41900	49700	15200
3.8	2560	2.4	380	**—**	**3/A06L2**	**BXN90S4**	—	25900	29500	59000	68100	22200
4.1	2400	1.0	349	**—**	**3/A04L2**	**BXN90S4**	—	21500	24500	41400	49000	14800
4.3	2270	1.6	329	**—**	**3/A05L2**	**BXN90S4**	—	21300	24300	41000	48600	14500
4.5	2180	1.1	317	**—**	**3/A04L2**	**BXN90S4**	—	21200	24200	40800	48400	14300
5.1	1950	1.5	283	**—**	**3/A04L2**	**BXN90S4**	—	21000	24000	40500	48000	13800
5.1	1930	1.9	280	**—**	**3/A05L2**	**BXN90S4**	—	21000	24000	40500	48000	13700
5.3	1850	1.0	269	**—**	**3/A03L2**	**BXN90S4**	—	21000	24000	40500	48000	13500
5.3	1850	1.0	269	**—**	**3/A03L2**	**BXN90S4**	—	21000	24000	40500	48000	13500
5.7	1720	2.0	250	**—**	**3/A04L2**	**BXN90S4**	—	21000	24000	40500	48000	13200
5.9	1660	2.6	241	**—**	**3/A05L2**	**BXN90S4**	—	21000	24000	40500	48000	13000
6.3	1560	2.2	226	**—**	**3/A04L2**	**BXN90S4**	—	21000	24000	40500	48000	12800
6.5	1520	1.1	220	**—**	**3/A03L2**	**BXN90S4**	—	21000	24000	40500	48000	12700
6.7	1460	2.1	212	**—**	**3/A05L2**	**BXN90S4**	—	21000	24000	40500	48000	12500
6.7	1460	2.1	212	**—**	**3/A05L2**	**BXN90S4**	—	21000	24000	40500	48000	12500
7.0	1410	0.9	204	**—**	**3/A01L2**	**BXN90S4**	—	6500	6500	21500	23500	4120
7.0	1410	2.5	205	**—**	**3/A04L2**	**BXN90S4**	—	21000	24000	40500	48000	12400
7.9	1250	1.5	182	**—**	**3/A03L2**	**BXN90S4**	—	21000	24000	40500	48000	11900
8.2	1200	2.5	174	**—**	**3/A04L2**	**BXN90S4**	—	21000	24000	40500	48000	11700
8.2	1210	3.0	175	**—**	**3/A05L2**	**BXN90S4**	—	21000	24000	40500	48000	11700
8.6	1140	1.0	166	**—**	**3/A01L2**	**BXN90S4**	—	6500	6500	21500	23500	3840
8.8	1120	2.6	162	**—**	**3/A04L2**	**BXN90S4**	—	21000	24000	40500	48000	11400
8.8	1120	2.6	162	**—**	**3/A05L2**	**BXN90S4**	—	21000	24000	40500	48000	11400
9.6	1030	2.3	149	**—**	**3/A04L2**	**BXN90S4**	—	21000	24000	40400	47900	11100
10.8	920	1.4	133	**—**	**3/A01L2**	**BXN90S4**	—	6250	6250	20800	22700	3570
12.2	810	3.0	117	**—**	**3/A04L2**	**BXN90S4**	—	19300	22100	37600	44500	10300



P_1 = 1.1 kW

n_2 min^{-1}	M_2 Nm	S	i			IE3	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
14.0	700	1.6	102	—	3/A01L2	BXN90S4	—	5710	5710	19100	20900	3260
14.8	670	2.5	96.9	—	3/A03L2	BXN90S4	—	18200	20700	35500	42100	9630
16.1	610	0.9	88.6	—	3/A00L2	BXN90S4	—	5450	5450	18400	21300	3120
16.2	610	2.7	88.5	—	3/A03L2	BXN90S4	—	17600	20100	34600	41000	9340
17.6	560	2.3	81.3	—	3/A01L2	BXN90S4	—	5300	5300	17900	19600	3030
17.8	550	1.2	80.2	—	3/A00L2	BXN90S4	—	5280	5280	17800	20700	3010
19.3	510	2.2	74.2	—	3/A01L2	BXN90S4	—	5140	5140	17400	19000	2940
20.1	490	1.3	71.0	—	3/A00L2	BXN90S4	—	5060	5060	17200	20000	2890
23.4	420	1.5	61.2	—	3/A00L2	BXN90S4	—	4820	4820	16400	19100	2750
27.6	355	1.5	51.8	—	3/A00L2	BXN90S4	—	4560	4560	15600	18200	2610
29.1	340	2.5	49.1	—	3/A01L2	BXN90S4	—	4480	4480	15400	16800	2560
34	285	2.3	41.5	—	3/A00L2	BXN90S4	—	4240	4240	14600	17000	2420
36	275	2.0	39.6	—	3/A00L2	BXN90S4	—	4170	4170	14400	16800	2380
45	220	3.0	31.7	—	3/A00L2	BXN90S4	—	3870	3870	13500	15700	2210

P_1 = 1.5 kW

n_2 min^{-1}	M_2 Nm	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
0.27	36900	1.3	5326	3/V11ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	147800	150800	65000
0.28	34100	1.5	5046	3/V13ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	192000	231000	80000
0.31	30900	1.0	4637	3/V10ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	115300	146200	65000
0.31	30900	1.0	4637	3/V10ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	115300	146200	65000
0.32	31000	1.5	4410	3/V11ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	143900	146800	65000
0.32	31900	1.8	4536	3/V13ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	192000	231000	80000
0.35	30900	1.0	4036	3/V10ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	113100	143400	65000
0.35	30900	1.0	4036	3/V10ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	113100	143400	65000
0.35	27700	1.8	4106	3/V11ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	142400	145300	65000
0.35	28400	2.1	4046	3/V13ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	192000	231000	80000
0.40	24800	1.2	3570	3/V10ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	111100	140900	65000
0.40	24800	1.2	3570	3/V10ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	111100	140900	65000
0.40	24000	1.8	3557	3/V11ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	139500	142400	65000
0.41	26900	2.1	3515	3/V13ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	192000	231000	80000
0.44	25100	1.1	3273	3/V10ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	109700	139100	65000
0.44	25100	1.1	3273	3/V10ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	109700	139100	65000
0.44	24700	1.9	3222	3/V11ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	137600	140400	65000
0.44	25000	2.2	3263	3/V13ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	192000	231000	80000
0.47	23200	2.1	3063	3/V11ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	136600	139400	65000
0.48	22900	1.3	2987	3/V10ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	108300	137300	65000
0.48	22900	1.3	2987	3/V10ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	108300	137300	65000
0.54	20400	2.3	2663	3/V11ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	133900	136600	65000
0.58	19000	1.4	2455	3/V10ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	105300	133500	65000
0.58	19000	1.4	2455	3/V10ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	105300	133500	65000
0.66	16500	1.7	2156	3/V10ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	103400	131100	65000
0.66	16500	1.7	2156	3/V10ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	103400	131100	65000
0.71	15500	1.9	2016	3/V10ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	102400	129800	65000
0.71	15500	1.9	2016	3/V10ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	102400	129800	65000
0.73	12900	1.0	1964	3/V07L3	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	39200	49000	88300	116100	45000
0.77	14200	1.9	1855	3/V10ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	101200	128300	65000
0.77	14200	1.9	1855	3/V10ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	101200	128300	65000
0.88	12500	2.2	1617	3/V10ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	99200	125800	65000
0.88	12500	2.2	1617	3/V10ML4	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	—	—	99200	125800	65000
0.93	11000	1.0	1545	3/V07L3	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	37900	47400	85300	112200	45000
1.0	9820	1.3	1411	3/V07L3	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	37400	46800	84200	110800	44100
1.1	8970	1.6	1288	3/V07L3	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	36900	46200	83100	109300	42800
1.2	8240	1.0	1153	3/V06L3	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	30300	34500	69100	79800	32100
1.2	8320	0.9	1212	3/V06L3	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	30500	34800	69600	80300	32600
1.2	8400	1.3	1159	3/V07L3	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	36400	45500	81900	107700	41300
1.4	7090	1.3	992	3/V06L3	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	29700	33800	67600	78100	30500
1.4	7260	2.0	1015	3/V07L3	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	35700	44600	80300	105700	39500
1.5	7350	1.1	930	3/V06L3	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	29400	33500	67000	77300	29800
1.6	6670	1.8	920	3/V07L3	—	BE90LA4	BX90LA4	ME3SB4	MX3SB4	35200	44000	79200	104200	38200



P_1 = 1.5 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N]				
min^{-1}	Nm									MC/PC	MZ/PZ	HC	HZ	FZ
1.8	5660	1.4	791	**3/V06L3**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	28700	32700	65500	75600	28300
1.8	6110	1.6	773	**3/V07L3**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	34300	42900	77300	101600	36100
1.9	5510	2.6	761	**3/V07L3**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	34300	42800	77100	101400	35900
2.0	5580	1.4	698	**3/V06L3**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	28200	32200	64300	74200	27100
2.1	6120	1.0	671	**—**	**3/A06L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	28000	32000	64000	73800	26800
2.2	5220	1.8	661	**3/V06L3**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	28000	31900	63800	73700	26600
2.3	5570	1.1	611	**—**	**3/A06L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	27700	31600	63100	72800	25900
2.3	4510	1.0	623	**3/V05L3**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	23300	26600	45000	53300	17900
2.5	4610	1.1	576	**3/V05L3**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	23100	26300	44500	52700	17400
2.5	4500	1.9	569	**3/V06L3**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	27400	31200	62500	72100	25300
2.6	5060	1.4	555	**—**	**3/A06L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	27300	31100	62200	71800	25100
2.7	4130	0.9	529	**3/V05L3**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	22800	26000	43900	52000	17000
2.7	4170	1.8	527	**3/V06L3**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	27100	30900	61800	71300	24700
2.8	4600	1.6	505	**—**	**3/A06L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	26900	30700	61400	70900	24400
3.1	3690	1.3	462	**3/V05L3**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	22300	25500	43100	51000	16200
3.2	3410	1.1	453	**3/V04L3**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	22300	25500	43000	50900	16100
3.3	3970	2.0	435	**—**	**3/A06L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	26400	30100	60100	69400	23200
3.3	4000	2.3	439	**—**	**3/A07L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	31700	39600	71300	93800	29900
3.3	3410	2.6	427	**3/V06L3**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	26300	30000	59900	69200	23000
3.4	3930	1.1	422	**—**	**3/A05L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	22100	25200	42500	50400	15700
3.5	3690	2.5	405	**—**	**3/A07L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	31300	39100	70500	92700	29100
3.6	3170	1.2	396	**3/V05L3**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21900	25000	42100	50000	15400
3.6	3160	2.4	395	**3/V06L3**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	26000	29600	59300	68400	22400
3.7	3540	1.6	388	**—**	**3/A06L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	25900	29600	59100	68300	22300
3.7	2890	1.2	384	**3/V04L3**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21800	24900	41900	49700	15200
3.7	3160	2.9	386	**3/V07L3**	**—**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	31100	38900	70000	92100	28600
3.8	3460	1.8	380	**—**	**3/A06L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	25900	29500	59000	68100	22200
4.3	3060	1.2	329	**—**	**3/A05L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21300	24300	41000	48600	14500
4.5	2930	2.3	321	**—**	**3/A06L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	25200	28800	57500	66400	20900
5.1	2640	1.1	283	**—**	**3/A04L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	13800
5.1	2610	1.4	280	**—**	**3/A05L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	13700
5.4	2430	2.3	267	**—**	**3/A06L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	25000	28500	57000	65800	19700
5.7	2330	1.5	250	**—**	**3/A04L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	13200
5.9	2240	1.9	241	**—**	**3/A05L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	13000
6.3	2100	1.7	226	**—**	**3/A04L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	12800
6.7	1970	1.6	212	**—**	**3/A05L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	12500
6.7	1970	1.6	212	**—**	**3/A05L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	12500
7.0	1910	1.8	205	**—**	**3/A04L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	12400
7.9	1690	1.1	182	**—**	**3/A03L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	11900
8.2	1620	1.8	174	**—**	**3/A04L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	11700
8.2	1630	2.2	175	**—**	**3/A05L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	11700
8.8	1510	1.9	162	**—**	**3/A04L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	11400
8.8	1510	1.9	162	**—**	**3/A05L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40500	48000	11400
9.6	1390	1.7	149	**—**	**3/A04L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	21000	24000	40400	47900	11100
10.1	1310	2.7	141	**—**	**3/A05L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	20600	23500	39700	47100	10900
10.8	1240	1.0	133	**—**	**3/A01L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	6250	6250	20800	22700	3570
11.1	1200	2.3	129	**—**	**3/A04L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	20000	22800	38700	45900	10600
12.2	1090	2.2	117	**—**	**3/A04L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	19300	22100	37600	44500	10300
14.0	950	1.2	102	**—**	**3/A01L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	5710	5710	19100	20900	3260
14.0	950	2.7	102	**—**	**3/A04L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	18500	21100	36100	42700	9790
14.8	900	1.9	96.9	**—**	**3/A03L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	18200	20700	35500	42100	9630
15.8	840	2.8	90.7	**—**	**3/A04L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	17800	20300	34800	41300	9420
16.2	820	2.0	88.5	**—**	**3/A03L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	17600	20100	34600	41000	9340
17.6	760	1.7	81.3	**—**	**3/A01L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	5300	5300	17900	19600	3030
19.3	690	1.7	74.2	**—**	**3/A01L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	5140	5140	17400	19000	2940
19.5	680	2.6	73.2	**—**	**3/A03L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	16500	18900	32700	38700	8770
20.1	660	1.0	71.0	**—**	**3/A00L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	5060	5060	17200	20000	2890
22.7	590	2.6	62.9	**—**	**3/A03L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	15700	18000	31200	37000	8340
23.4	570	1.1	61.2	**—**	**3/A00L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4820	4820	16400	19100	2750
24.1	550	2.3	59.4	**—**	**3/A01L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4770	4770	16300	17800	2730
26.4	500	2.3	54.2	**—**	**3/A01L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4630	4630	15800	17300	2650
27.6	480	1.1	51.8	**—**	**3/A00L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4560	4560	15600	18200	2610
29.1	455	1.8	49.1	**—**	**3/A01L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4480	4480	15400	16800	2560
33	410	2.3	43.9	**—**	**3/A01L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4320	4320	14900	16300	2470
34	385	1.7	41.5	**—**	**3/A00L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4240	4240	14600	17000	2420



P_1 = 1.5 kW

n_2 min^{-1}	M_2 Nm	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
36	370	1.5	39.6	—	**3/A00L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4170	4170	14400	16800	2380
36	375	2.3	40.1	—	**3/A01L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4190	4190	14500	15800	2390
40	335	2.3	35.8	—	**3/A01L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	4030	4030	14000	15300	2300
45	295	2.2	31.7	—	**3/A00L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	3870	3870	13500	15700	2210
61	220	2.7	23.4	—	**3/A00L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	3500	3500	12300	14300	2000
75	180	2.6	19.1	—	**3/A00L2**	**BE90LA4**	**BX90LA4**	**ME3SB4**	**MX3SB4**	3270	3270	11600	13500	1870

P_1 = 1.5 kW

n_2 min^{-1}	M_2 Nm	S	i			IE3	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
0.27	36900	1.3	5326	**3/V11ML4**	—	**BXN90L4**	—	—	—	147800	150800	65000
0.28	34100	1.5	5046	**3/V13ML4**	—	**BXN90L4**	—	—	—	192000	231000	80000
0.31	30900	1.0	4637	**3/V10ML4**	—	**BXN90L4**	—	—	—	115300	146200	65000
0.31	30900	1.0	4637	**3/V10ML4**	—	**BXN90L4**	—	—	—	115300	146200	65000
0.32	31000	1.5	4410	**3/V11ML4**	—	**BXN90L4**	—	—	—	143900	146800	65000
0.32	31900	1.8	4536	**3/V13ML4**	—	**BXN90L4**	—	—	—	192000	231000	80000
0.35	30900	1.0	4036	**3/V10ML4**	—	**BXN90L4**	—	—	—	113100	143400	65000
0.35	30900	1.0	4036	**3/V10ML4**	—	**BXN90L4**	—	—	—	113100	143400	65000
0.35	27700	1.8	4106	**3/V11ML4**	—	**BXN90L4**	—	—	—	142400	145300	65000
0.35	28400	2.1	4046	**3/V13ML4**	—	**BXN90L4**	—	—	—	192000	231000	80000
0.40	24800	1.2	3570	**3/V10ML4**	—	**BXN90L4**	—	—	—	111100	140900	65000
0.40	24800	1.2	3570	**3/V10ML4**	—	**BXN90L4**	—	—	—	111100	140900	65000
0.40	24000	1.8	3557	**3/V11ML4**	—	**BXN90L4**	—	—	—	139500	142400	65000
0.41	26900	2.1	3515	**3/V13ML4**	—	**BXN90L4**	—	—	—	192000	231000	80000
0.44	25100	1.1	3273	**3/V10ML4**	—	**BXN90L4**	—	—	—	109700	139100	65000
0.44	25100	1.1	3273	**3/V10ML4**	—	**BXN90L4**	—	—	—	109700	139100	65000
0.44	24700	1.9	3222	**3/V11ML4**	—	**BXN90L4**	—	—	—	137600	140400	65000
0.44	25000	2.2	3263	**3/V13ML4**	—	**BXN90L4**	—	—	—	192000	231000	80000
0.47	23200	2.1	3063	**3/V11ML4**	—	**BXN90L4**	—	—	—	136600	139400	65000
0.48	22900	1.3	2987	**3/V10ML4**	—	**BXN90L4**	—	—	—	108300	137300	65000
0.48	22900	1.3	2987	**3/V10ML4**	—	**BXN90L4**	—	—	—	108300	137300	65000
0.54	20400	2.3	2663	**3/V11ML4**	—	**BXN90L4**	—	—	—	133900	136600	65000
0.58	19000	1.4	2455	**3/V10ML4**	—	**BXN90L4**	—	—	—	105300	133500	65000
0.58	19000	1.4	2455	**3/V10ML4**	—	**BXN90L4**	—	—	—	105300	133500	65000
0.66	16500	1.7	2156	**3/V10ML4**	—	**BXN90L4**	—	—	—	103400	131100	65000
0.66	16500	1.7	2156	**3/V10ML4**	—	**BXN90L4**	—	—	—	103400	131100	65000
0.71	15500	1.9	2016	**3/V10ML4**	—	**BXN90L4**	—	—	—	102400	129800	65000
0.71	15500	1.9	2016	**3/V10ML4**	—	**BXN90L4**	—	—	—	102400	129800	65000
0.73	12900	1.0	1964	**3/V07L3**	—	**BXN90L4**	—	39200	49000	88300	116100	45000
0.77	14200	1.9	1855	**3/V10ML4**	—	**BXN90L4**	—	—	—	101200	128300	65000
0.77	14200	1.9	1855	**3/V10ML4**	—	**BXN90L4**	—	—	—	101200	128300	65000
0.88	12500	2.2	1617	**3/V10ML4**	—	**BXN90L4**	—	—	—	99200	125800	65000
0.88	12500	2.2	1617	**3/V10ML4**	—	**BXN90L4**	—	—	—	99200	125800	65000
0.93	11000	1.0	1545	**3/V07L3**	—	**BXN90L4**	—	37900	47400	85300	112200	45000
1.0	9820	1.3	1411	**3/V07L3**	—	**BXN90L4**	—	37400	46800	84200	110800	44100
1.1	8970	1.6	1288	**3/V07L3**	—	**BXN90L4**	—	36900	46200	83100	109300	42800
1.2	8240	1.0	1153	**3/V06L3**	—	**BXN90L4**	—	30300	34500	69100	79800	32100
1.2	8320	0.9	1212	**3/V06L3**	—	**BXN90L4**	—	30500	34800	69600	80300	32600
1.2	8400	1.3	1159	**3/V07L3**	—	**BXN90L4**	—	36400	45500	81900	107700	41300
1.4	7090	1.3	992	**3/V06L3**	—	**BXN90L4**	—	29700	33800	67600	78100	30500
1.4	7260	2.0	1015	**3/V07L3**	—	**BXN90L4**	—	35700	44600	80300	105700	39500
1.5	7350	1.1	930	**3/V06L3**	—	**BXN90L4**	—	29400	33500	67000	77300	29800
1.6	6670	1.8	920	**3/V07L3**	—	**BXN90L4**	—	35200	44000	79200	104200	38200
1.8	5660	1.4	791	**3/V06L3**	—	**BXN90L4**	—	28700	32700	65500	75600	28300
1.8	6110	1.6	773	**3/V07L3**	—	**BXN90L4**	—	34300	42900	77300	101600	36100
1.9	5510	2.6	761	**3/V07L3**	—	**BXN90L4**	—	34300	42800	77100	101400	35900
2.0	5580	1.4	698	**3/V06L3**	—	**BXN90L4**	—	28200	32200	64300	74200	27100
2.1	6120	1.0	671	—	**3/A06L2**	**BXN90L4**	—	28000	32000	64000	73800	26800
2.2	5220	1.8	661	**3/V06L3**	—	**BXN90L4**	—	28000	31900	63800	73700	26600
2.3	5570	1.1	611	—	**3/A06L2**	**BXN90L4**	—	27700	31600	63100	72800	25900
2.3	4510	1.0	623	**3/V05L3**	—	**BXN90L4**	—	23300	26600	45000	53300	17900



P_1 = 1.5 kW

n_2 min^{-1}	M_2 Nm	S	i			IE3	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
2.5	4610	1.1	576	**3/V05L3**	**—**	**BXN90L4**	—	23100	26300	44500	52700	17400
2.5	4500	1.9	569	**3/V06L3**	**—**	**BXN90L4**	—	27400	31200	62500	72100	25300
2.6	5060	1.4	555	**—**	**3/A06L2**	**BXN90L4**	—	27300	31100	62200	71800	25100
2.7	4130	0.9	529	**3/V05L3**	**—**	**BXN90L4**	—	22800	26000	43900	52000	17000
2.7	4170	1.8	527	**3/V06L3**	**—**	**BXN90L4**	—	27100	30900	61800	71300	24700
2.8	4600	1.6	505	**—**	**3/A06L2**	**BXN90L4**	—	26900	30700	61400	70900	24400
3.1	3690	1.3	462	**3/V05L3**	**—**	**BXN90L4**	—	22300	25500	43100	51000	16200
3.2	3410	1.1	453	**3/V04L3**	**—**	**BXN90L4**	—	22300	25500	43000	50900	16100
3.3	3970	2.0	435	**—**	**3/A06L2**	**BXN90L4**	—	26400	30100	60100	69400	23200
3.3	4000	2.3	439	**—**	**3/A07L2**	**BXN90L4**	—	31700	39600	71300	93800	29900
3.3	3410	2.6	427	**3/V06L3**	**—**	**BXN90L4**	—	26300	30000	59900	69200	23000
3.4	3930	1.1	422	**—**	**3/A05L2**	**BXN90L4**	—	22100	25200	42500	50400	15700
3.5	3690	2.5	405	**—**	**3/A07L2**	**BXN90L4**	—	31300	39100	70500	92700	29100
3.6	3170	1.2	396	**3/V05L3**	**—**	**BXN90L4**	—	21900	25000	42100	50000	15400
3.6	3160	2.4	395	**3/V06L3**	**—**	**BXN90L4**	—	26000	29600	59300	68400	22400
3.7	3540	1.6	388	**—**	**3/A06L2**	**BXN90L4**	—	25900	29600	59100	68300	22300
3.7	2890	1.2	384	**3/V04L3**	**—**	**BXN90L4**	—	21800	24900	41900	49700	15200
3.7	3160	2.9	386	**3/V07L3**	**—**	**BXN90L4**	—	31100	38900	70000	92100	28600
3.8	3460	1.8	380	**—**	**3/A06L2**	**BXN90L4**	—	25900	29500	59000	68100	22200
4.3	3060	1.2	329	**—**	**3/A05L2**	**BXN90L4**	—	21300	24300	41000	48600	14500
4.5	2930	2.3	321	**—**	**3/A06L2**	**BXN90L4**	—	25200	28800	57500	66400	20900
5.1	2640	1.1	283	**—**	**3/A04L2**	**BXN90L4**	—	21000	24000	40500	48000	13800
5.1	2610	1.4	280	**—**	**3/A05L2**	**BXN90L4**	—	21000	24000	40500	48000	13700
5.4	2430	2.3	267	**—**	**3/A06L2**	**BXN90L4**	—	25000	28500	57000	65800	19700
5.7	2330	1.5	250	**—**	**3/A04L2**	**BXN90L4**	—	21000	24000	40500	48000	13200
5.9	2240	1.9	241	**—**	**3/A05L2**	**BXN90L4**	—	21000	24000	40500	48000	13000
6.3	2100	1.7	226	**—**	**3/A04L2**	**BXN90L4**	—	21000	24000	40500	48000	12800
6.7	1970	1.6	212	**—**	**3/A05L2**	**BXN90L4**	—	21000	24000	40500	48000	12500
6.7	1970	1.6	212	**—**	**3/A05L2**	**BXN90L4**	—	21000	24000	40500	48000	12500
7.0	1910	1.8	205	**—**	**3/A04L2**	**BXN90L4**	—	21000	24000	40500	48000	12400
7.9	1690	1.1	182	**—**	**3/A03L2**	**BXN90L4**	—	21000	24000	40500	48000	11900
8.2	1620	1.8	174	**—**	**3/A04L2**	**BXN90L4**	—	21000	24000	40500	48000	11700
8.2	1630	2.2	175	**—**	**3/A05L2**	**BXN90L4**	—	21000	24000	40500	48000	11700
8.8	1510	1.9	162	**—**	**3/A04L2**	**BXN90L4**	—	21000	24000	40500	48000	11400
8.8	1510	1.9	162	**—**	**3/A05L2**	**BXN90L4**	—	21000	24000	40500	48000	11400
9.6	1390	1.7	149	**—**	**3/A04L2**	**BXN90L4**	—	21000	24000	40400	47900	11100
10.1	1310	2.7	141	**—**	**3/A05L2**	**BXN90L4**	—	20600	23500	39700	47100	10900
10.8	1240	1.0	133	**—**	**3/A01L2**	**BXN90L4**	—	6250	6250	20800	22700	3570
11.1	1200	2.3	129	**—**	**3/A04L2**	**BXN90L4**	—	20000	22800	38700	45900	10600
12.2	1090	2.2	117	**—**	**3/A04L2**	**BXN90L4**	—	19300	22100	37600	44500	10300
14.0	950	1.2	102	**—**	**3/A01L2**	**BXN90L4**	—	5710	5710	19100	20900	3260
14.0	950	2.7	102	**—**	**3/A04L2**	**BXN90L4**	—	18500	21100	36100	42700	9790
14.8	900	1.9	96.9	**—**	**3/A03L2**	**BXN90L4**	—	18200	20700	35500	42100	9630
15.8	840	2.8	90.7	**—**	**3/A04L2**	**BXN90L4**	—	17800	20300	34800	41300	9420
16.2	820	2.0	88.5	**—**	**3/A03L2**	**BXN90L4**	—	17600	20100	34600	41000	9340
17.6	760	1.7	81.3	**—**	**3/A01L2**	**BXN90L4**	—	5300	5300	17900	19600	3030
19.3	690	1.7	74.2	**—**	**3/A01L2**	**BXN90L4**	—	5140	5140	17400	19000	2940
19.5	680	2.6	73.2	**—**	**3/A03L2**	**BXN90L4**	—	16500	18900	32700	38700	8770
20.1	660	1.0	71.0	**—**	**3/A00L2**	**BXN90L4**	—	5060	5060	17200	20000	2890
22.7	590	2.6	62.9	**—**	**3/A03L2**	**BXN90L4**	—	15700	18000	31200	37000	8340
23.4	570	1.1	61.2	**—**	**3/A00L2**	**BXN90L4**	—	4820	4820	16400	19100	2750
24.1	550	2.3	59.4	**—**	**3/A01L2**	**BXN90L4**	—	4770	4770	16300	17800	2730
26.4	500	2.3	54.2	**—**	**3/A01L2**	**BXN90L4**	—	4630	4630	15800	17300	2650
27.6	480	1.1	51.8	**—**	**3/A00L2**	**BXN90L4**	—	4560	4560	15600	18200	2610
29.1	455	1.8	49.1	**—**	**3/A01L2**	**BXN90L4**	—	4480	4480	15400	16800	2560
33	410	2.3	43.9	**—**	**3/A01L2**	**BXN90L4**	—	4320	4320	14900	16300	2470
34	385	1.7	41.5	**—**	**3/A00L2**	**BXN90L4**	—	4240	4240	14600	17000	2420
36	370	1.5	39.6	**—**	**3/A00L2**	**BXN90L4**	—	4170	4170	14400	16800	2380
36	375	2.3	40.1	**—**	**3/A01L2**	**BXN90L4**	—	4190	4190	14500	15800	2390
40	335	2.3	35.8	**—**	**3/A01L2**	**BXN90L4**	—	4030	4030	14000	15300	2300
45	295	2.2	31.7	**—**	**3/A00L2**	**BXN90L4**	—	3870	3870	13500	15700	2210
61	220	2.7	23.4	**—**	**3/A00L2**	**BXN90L4**	—	3500	3500	12300	14300	2000
75	180	2.6	19.1	**—**	**3/A00L2**	**BXN90L4**	—	3270	3270	11600	13500	1870



P_1 = 2.2 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N]				
min^{-1}	Nm									MC/PC	MZ/PZ	HC	HZ	FZ
0.27	56200	1.6	5234	**3/V15ML4**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	198600	238200	90000
0.28	50100	1.0	5046	**3/V13ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	192000	231000	80000
0.29	51200	1.6	4959	**3/V14ML4**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	197100	236300	90000
0.29	53100	1.9	4950	**3/V15ML4**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	197000	236300	90000
0.29	53100	2.2	4950	**3/V16ML4**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	301500	338200	150000
0.32	45600	1.0	4410	**3/V11ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	143900	146800	65000
0.32	46900	1.2	4536	**3/V13ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	192000	231000	80000
0.33	44500	1.8	4312	**3/V14ML4**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	193200	231700	90000
0.34	44800	2.3	4171	**3/V15ML4**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	192300	230600	90000
0.35	40800	1.2	4106	**3/V11ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	142400	145300	65000
0.35	41800	1.5	4046	**3/V13ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	192000	231000	80000
0.36	44500	1.6	3993	**3/V14ML4**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	191100	229100	90000
0.40	35300	1.2	3557	**3/V11ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	139500	142400	65000
0.41	39600	1.4	3515	**3/V13ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	192000	231000	80000
0.44	36300	1.3	3222	**3/V11ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	137600	140400	65000
0.44	36800	1.5	3263	**3/V13ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	192000	231000	80000
0.45	35400	2.2	3182	**3/V14ML4**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	185000	221800	90000
0.47	34100	1.4	3063	**3/V11ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	136600	139400	65000
0.51	29900	2.7	2782	**3/V14ML4**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	181400	217600	90000
0.52	28600	2.1	2773	**3/V13ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	192000	228600	80000
0.54	30000	1.6	2663	**3/V11ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	133900	136600	65000
0.58	28000	1.0	2455	**3/V10ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	105300	133500	65000
0.58	28000	1.0	2455	**3/V10ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	105300	133500	65000
0.59	24900	1.6	2430	**3/V13ML3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	191500	224400	80000
0.61	23800	1.5	2329	**3/V11ML3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	131300	134000	65000
0.62	23700	2.7	2318	**3/V14ML3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	176800	212000	90000
0.66	24300	1.2	2156	**3/V10ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	103400	131100	65000
0.66	24300	1.2	2156	**3/V10ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	103400	131100	65000
0.71	22700	1.3	2016	**3/V10ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	102400	129800	65000
0.71	22700	1.3	2016	**3/V10ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	102400	129800	65000
0.71	20700	2.8	2019	**3/V13ML3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	186500	218500	80000
0.73	20100	2.1	1963	**3/V11ML3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	128200	130800	65000
0.77	20900	1.3	1855	**3/V10ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	101200	128300	65000
0.77	20900	1.3	1855	**3/V10ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	101200	128300	65000
0.80	17800	1.2	1792	**3/V09L3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	89100	114600	36000
0.87	17200	2.4	1636	**3/V11ML3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	124900	127400	65000
0.88	16200	0.9	1623	**3/V09L3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	87800	113000	36000
0.88	18400	1.5	1617	**3/V10ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	99200	125800	65000
0.88	18400	1.5	1617	**3/V10ML4**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	—	—	99200	125800	65000
0.96	15900	1.1	1497	**3/V09L3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	86800	111700	36000
1.0	15000	1.3	1411	**3/V10ML3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	97300	123400	63700
1.1	13200	1.1	1288	**3/V07L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	36900	46200	83100	109300	42800
1.1	13700	1.6	1288	**3/V09L3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	85000	109300	34200
1.1	13400	2.5	1274	**3/V11ML3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	120500	123000	61600
1.2	12800	1.3	1159	**3/V09L3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	83700	107700	33000
1.2	13100	1.5	1227	**3/V10ML3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	95400	120900	60800
1.3	11900	2.4	1120	**3/V10ML3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	94200	119400	59000
1.4	10400	0.9	992	**3/V06L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	29700	33800	67600	78100	30500
1.4	10700	1.3	1015	**3/V07L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	35700	44600	80300	105700	39500
1.4	10700	1.7	1004	**3/V09L3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	82000	105500	31500
1.4	10700	3.0	1004	**3/V10ML3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	92700	117500	56900
1.6	9800	1.3	920	**3/V07L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	35200	44000	79200	104200	38200
1.6	10200	1.9	920	**3/V10ML3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	91500	116100	55200
1.7	9290	2.2	840	**3/V09L3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	79900	102900	29700
1.8	8310	0.9	791	**3/V06L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	28700	32700	65500	75600	28300
1.8	8980	1.1	773	**3/V07L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	34300	42900	77300	101600	36100
1.8	8520	2.5	800	**3/V09L3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	79400	102200	29200
1.9	8100	1.8	761	**3/V07L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	34300	42800	77100	101400	35900
1.9	8420	1.7	761	**3/V09L3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	78800	101400	28700
2.0	8210	0.9	698	**3/V06L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	28200	32200	64300	74200	27100
2.2	7680	1.2	661	**3/V06L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	28000	31900	63800	73700	26600
2.2	6980	2.1	655	**3/V07L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	33500	41900	75500	99300	34100
2.2	7250	2.4	655	**3/V09L3**	**—**	**BE100LA4**	**BX100LA4**	**—**	**—**	—	—	77100	99300	27300
2.5	6610	1.3	569	**3/V06L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	27400	31200	62500	72100	25300
2.6	7440	1.0	555	**—**	**3/A06L2**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	27300	31100	62200	71800	25100
2.7	6120	1.2	527	**3/V06L3**	**—**	**BE100LA4**	**BX100LA4**	**ME3LA4**	**MX3LA4**	27100	30900	61800	71300	24700

A



P_1 = 2.2 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N]				
min^{-1}	Nm									MC/PC	MZ/PZ	HC	HZ	FZ
2.8	6770	1.1	505	—	3/A06L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	26900	30700	61400	70900	24400
2.8	5890	2.3	507	3/V07L3	—	BE100LA4	BX100LA4	ME3LA4	MX3LA4	32300	40400	72800	95700	31400
3.1	5340	2.3	460	3/V07L3	—	BE100LA4	BX100LA4	ME3LA4	MX3LA4	31900	39900	71800	94400	30400
3.3	5830	1.3	435	—	3/A06L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	26400	30100	60100	69400	23200
3.3	5880	1.6	439	—	3/A07L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	31700	39600	71300	93800	29900
3.3	5020	1.8	427	3/V06L3	—	BE100LA4	BX100LA4	ME3LA4	MX3LA4	26300	30000	59900	69200	23000
3.5	5430	1.7	405	—	3/A07L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	31300	39100	70500	92700	29100
3.6	4640	1.6	395	3/V06L3	—	BE100LA4	BX100LA4	ME3LA4	MX3LA4	26000	29600	59300	68400	22400
3.7	5200	1.1	388	—	3/A06L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	25900	29600	59100	68300	22300
3.7	4640	1.9	386	3/V07L3	—	BE100LA4	BX100LA4	ME3LA4	MX3LA4	31100	38900	70000	92100	28600
3.8	5090	1.2	380	—	3/A06L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	25900	29500	59000	68100	22200
4.2	4570	2.5	341	—	3/A07L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	30600	38200	68800	90400	27500
4.5	4300	1.5	321	—	3/A06L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	25200	28800	57500	66400	20900
5.1	3830	0.9	280	—	3/A05L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	21000	24000	40500	48000	13700
5.1	3780	2.3	282	—	3/A07L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	30000	37500	67500	88800	25800
5.2	3700	2.1	276	—	3/A06L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	25000	28500	57000	65800	19900
5.4	3580	1.5	267	—	3/A06L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	25000	28500	57000	65800	19700
5.7	3420	1.0	250	—	3/A04L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	21000	24000	40500	48000	13200
5.9	3300	1.3	241	—	3/A05L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	21000	24000	40500	48000	13000
5.9	3230	2.8	241	—	3/A07L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	30000	37500	67500	88800	24500
6.3	3090	1.1	226	—	3/A04L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	21000	24000	40500	48000	12800
6.5	2960	2.2	221	—	3/A06L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	25000	28500	57000	65800	18500
6.7	2900	1.1	212	—	3/A05L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	21000	24000	40500	48000	12500
6.7	2900	1.1	212	—	3/A05L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	21000	24000	40500	48000	12500
7.0	2810	1.2	205	—	3/A04L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	21000	24000	40500	48000	12400
7.2	2650	2.1	198	—	3/A06L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	25000	28500	57000	65800	17800
8.2	2380	1.2	174	—	3/A04L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	21000	24000	40500	48000	11700
8.2	2400	1.5	175	—	3/A05L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	21000	24000	40500	48000	11700
8.7	2200	3.0	164	—	3/A06L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	25000	28500	57000	65800	16700
8.8	2220	1.3	162	—	3/A04L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	21000	24000	40500	48000	11400
8.8	2220	1.3	162	—	3/A05L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	21000	24000	40500	48000	11400
9.6	2040	1.2	149	—	3/A04L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	21000	24000	40400	47900	11100
10.1	1930	1.9	141	—	3/A05L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	20600	23500	39700	47100	10900
11.1	1770	1.5	129	—	3/A04L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	20000	22800	38700	45900	10600
11.8	1660	2.1	121	—	3/A05L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	19600	22300	38000	45000	10400
12.2	1600	1.5	117	—	3/A04L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	19300	22100	37600	44500	10300
13.8	1420	2.2	104	—	3/A05L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	18600	21200	36200	42900	9840
14.0	1400	1.8	102	—	3/A04L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	18500	21100	36100	42700	9790
14.8	1330	1.3	96.9	—	3/A03L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	18200	20700	35500	42100	9630
15.8	1240	1.9	90.7	—	3/A04L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	17800	20300	34800	41300	9420
16.2	1210	1.4	88.5	—	3/A03L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	17600	20100	34600	41000	9340
17.5	1120	2.1	81.7	—	3/A04L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	17200	19600	33800	40000	9100
17.6	1110	1.2	81.3	—	3/A01L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	5300	5300	17900	19600	3030
18.9	1040	2.9	75.8	—	3/A05L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	16700	19100	33000	39100	8870
19.3	1020	1.1	74.2	—	3/A01L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	5140	5140	17400	19000	2940
19.5	1000	1.8	73.2	—	3/A03L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	16500	18900	32700	38700	8770
20.9	940	2.7	68.4	—	3/A04L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	16200	18500	32000	37900	8580
22.7	860	1.8	62.9	—	3/A03L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	15700	18000	31200	37000	8340
24.1	810	1.5	59.4	—	3/A01L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	4770	4770	16300	17800	2730
26.4	740	1.6	54.2	—	3/A01L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	4630	4630	15800	17300	2650
27.2	720	2.3	52.5	—	3/A03L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	14800	16900	29600	35000	7850
27.2	720	2.3	52.5	—	3/A03L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	14800	16900	29600	35000	7850
29.1	670	1.2	49.1	—	3/A01L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	4480	4480	15400	16800	2560
33	600	1.5	43.9	—	3/A01L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	4320	4320	14900	16300	2470
34	570	1.1	41.5	—	3/A00L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	4240	4240	14600	17000	2420
35	550	3.0	40.5	—	3/A03L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	13600	15500	27300	32400	7200
36	540	1.0	39.6	—	3/A00L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	4170	4170	14400	16800	2380
36	550	1.6	40.1	—	3/A01L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	4190	4190	14500	15800	2390
40	490	1.6	35.8	—	3/A01L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	4030	4030	14000	15300	2300
45	435	1.5	31.7	—	3/A00L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	3870	3870	13500	15700	2210
46	425	2.8	31.2	—	3/A01L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	3850	3850	13400	14700	2200
61	320	1.8	23.4	—	3/A00L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	3500	3500	12300	14300	2000
62	315	2.8	23.0	—	3/A01L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	3480	3480	12300	13400	1990
75	260	1.8	19.1	—	3/A00L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	3270	3270	11600	13500	1870
76	255	2.8	18.8	—	3/A01L2	BE100LA4	BX100LA4	ME3LA4	MX3LA4	3250	3250	11500	12600	1860



P_1 = 3 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N]				
min^{-1}	Nm									MC/PC	MZ/PZ	HC	HZ	FZ
0.27	76400	1.2	5234	**3/V15ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	198600	238200	90000
0.29	69700	1.2	4959	**3/V14ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	197100	236300	90000
0.29	72300	1.4	4950	**3/V15ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	197000	236300	90000
0.29	72300	1.6	4950	**3/V16ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	301500	338200	150000
0.33	60600	1.3	4312	**3/V14ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	193200	231700	90000
0.34	60900	1.7	4171	**3/V15ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	192300	230600	90000
0.34	60900	2.2	4171	**3/V16ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	294200	330000	150000
0.35	56900	1.1	4046	**3/V13ML4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	—	—	192000	231000	80000
0.36	60500	1.2	3993	**3/V14ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	191100	229100	90000
0.40	53900	1.1	3515	**3/V13ML4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	—	—	192000	231000	80000
0.40	51300	2.6	3514	**3/V16ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	287100	322100	150000
0.44	49400	1.0	3222	**3/V11ML4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	—	—	137600	140400	65000
0.44	50000	1.1	3263	**3/V13ML4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	—	—	192000	231000	80000
0.45	48200	1.6	3182	**3/V14ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	185000	221800	90000
0.46	46400	1.0	3063	**3/V11ML4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	—	—	136600	139400	65000
0.49	42100	2.9	2880	**3/V16ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	279000	313000	150000
0.51	39000	1.5	2773	**3/V13ML4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	—	—	192000	228600	80000
0.51	40600	2.0	2782	**3/V14ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	181400	217600	90000
0.53	40800	1.2	2663	**3/V11ML4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	—	—	133900	136600	65000
0.53	39100	2.9	2678	**3/V16ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	276200	309800	150000
0.57	35200	2.3	2504	**3/V14ML4**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	178700	214300	90000
0.58	33800	1.2	2430	**3/V13ML3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	191500	224400	80000
0.61	32400	1.1	2329	**3/V11ML3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	131300	134000	65000
0.61	32300	2.0	2318	**3/V14ML3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	176800	212000	90000
0.70	30900	1.0	2016	**3/V10ML4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	—	—	102400	129800	65000
0.70	30900	1.0	2016	**3/V10ML4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	—	—	102400	129800	65000
0.70	28100	2.0	2019	**3/V13ML3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	186500	218500	80000
0.71	27800	2.6	1994	**3/V14ML3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	173000	207500	90000
0.72	27300	1.5	1963	**3/V11ML3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	128200	130800	65000
0.77	28400	1.0	1855	**3/V10ML4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	—	—	101200	128300	65000
0.77	28400	1.0	1855	**3/V10ML4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	—	—	101200	128300	65000
0.79	24300	0.9	1792	**3/V09L3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	89100	114600	36000
0.84	24100	2.4	1682	**3/V13ML3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	181700	212900	80000
0.87	23400	1.8	1636	**3/V11ML3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	124900	127400	65000
0.88	25100	1.1	1617	**3/V10ML4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	—	—	99200	125800	65000
0.88	25100	1.1	1617	**3/V10ML4**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	—	—	99200	125800	65000
0.89	22100	2.6	1589	**3/V14ML3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	167500	200900	90000
1.0	20400	1.0	1411	**3/V10ML3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	97300	123400	63700
1.0	19700	2.4	1378	**3/V11ML3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	121800	124300	63200
1.0	20300	2.8	1418	**3/V13ML3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	177300	207700	78500
1.1	18700	1.2	1288	**3/V09L3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	85000	109300	34200
1.1	18200	1.8	1274	**3/V11ML3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	120500	123000	61600
1.1	18500	2.7	1291	**3/V13ML3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	174900	205000	76100
1.1	18600	2.6	1339	**3/V14ML3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	163400	196000	86700
1.2	17400	0.9	1159	**3/V09L3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	83700	107700	33000
1.2	17800	1.1	1227	**3/V10ML3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	95400	120900	60800
1.3	16200	1.8	1120	**3/V10ML3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	94200	119400	59000
1.4	14500	1.0	1015	**3/V07L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	35700	44600	80300	105700	39500
1.4	14500	1.2	1004	**3/V09L3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	82000	105500	31500
1.4	14500	2.2	1004	**3/V10ML3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	92700	117500	56900
1.4	14000	2.6	1004	**3/V11ML3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	116500	118800	56900
1.5	13300	0.9	920	**3/V07L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	35200	44000	79200	104200	38200
1.5	13900	1.4	920	**3/V10ML3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	91500	116100	55200
1.7	12600	1.6	840	**3/V09L3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	79900	102900	29700
1.8	11600	1.8	800	**3/V09L3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	79400	102200	29200
1.9	11000	1.3	761	**3/V07L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	34300	42800	77100	101400	35900
1.9	11500	1.3	761	**3/V09L3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	78800	101400	28700
2.2	9490	1.5	655	**3/V07L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	33500	41900	75500	99300	34100
2.2	9860	1.8	655	**3/V09L3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	77100	99300	27300
2.5	8990	1.0	569	**3/V06L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	27400	31200	62500	72100	25300
2.7	8330	0.9	527	**3/V06L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	27100	30900	61800	71300	24700
2.8	8010	1.7	507	**3/V07L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	32300	40400	72800	95700	31400
3.1	7270	1.7	460	**3/V07L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	31900	39900	71800	94400	30400
3.2	8010	1.1	439	**—**	**3/A07L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	31700	39600	71300	93800	29900
3.2	6650	2.7	442	**3/V09L3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	72900	93800	24000
3.3	7930	1.0	435	**—**	**3/A06L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	26400	30100	60100	69400	23200



P_1 = 3 kW

n_2	M_2	S	i							Rn_2 [N]				
min^{-1}	Nm					IE2	IE3	IE2	IE3	MC/PC	MZ/PZ	HC	HZ	FZ
3.3	6830	1.3	427	**3/V06L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	26300	30000	59900	69200	23000
3.5	7390	1.2	405	**—**	**3/A07L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	31300	39100	70500	92700	29100
3.6	6320	1.2	395	**3/V06L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	26000	29600	59300	68400	22400
3.7	6320	1.4	386	**3/V07L3**	**—**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	31100	38900	70000	92100	28600
3.8	5570	2.3	370	**3/V09L3**	**—**	**BE100LB4**	**BX100LB4**	**—**	**—**	—	—	71100	91500	22600
4.2	6220	1.8	341	**—**	**3/A07L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	30600	38200	68800	90400	27500
4.4	5850	1.1	321	**—**	**3/A06L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25200	28800	57500	66400	20900
5.0	5140	1.7	282	**—**	**3/A07L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	30000	37500	67500	88800	25800
5.1	5030	1.5	276	**—**	**3/A06L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25000	28500	57000	65800	19900
5.3	4870	1.1	267	**—**	**3/A06L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25000	28500	57000	65800	19700
5.9	4490	1.0	241	**—**	**3/A05L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	13000
5.9	4390	2.0	241	**—**	**3/A07L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	30000	37500	67500	88800	24500
6.4	4030	1.6	221	**—**	**3/A06L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25000	28500	57000	65800	18500
6.4	4070	2.2	223	**—**	**3/A07L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	30000	37500	67500	88800	23800
6.9	3820	0.9	205	**—**	**3/A04L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	12400
7.2	3610	1.5	198	**—**	**3/A06L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25000	28500	57000	65800	17800
7.2	3610	2.4	198	**—**	**3/A07L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	30000	37500	67500	88800	22900
7.5	3460	2.2	190	**—**	**3/A06L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25000	28500	57000	65800	17600
8.1	3260	1.1	175	**—**	**3/A05L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	11700
8.2	3240	0.9	174	**—**	**3/A04L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	11700
8.7	2990	2.2	164	**—**	**3/A06L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	25000	28500	57000	65800	16700
8.8	3020	1.0	162	**—**	**3/A04L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	11400
8.8	3020	1.0	162	**—**	**3/A05L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21000	24000	40500	48000	11400
10.1	2630	1.4	141	**—**	**3/A05L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	20600	23500	39700	47100	10900
11.0	2400	1.1	129	**—**	**3/A04L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	20000	22800	38700	45900	10600
11.4	2330	2.3	125	**—**	**3/A06L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	23500	26800	53900	62200	15300
11.7	2250	1.6	121	**—**	**3/A05L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	19600	22300	38000	45000	10400
12.1	2180	1.1	117	**—**	**3/A04L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	19300	22100	37600	44500	10300
13.7	1940	1.6	104	**—**	**3/A05L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	18600	21200	36200	42900	9840
13.9	1900	1.3	102	**—**	**3/A04L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	18500	21100	36100	42700	9790
14.4	1830	2.9	98.3	**—**	**3/A06L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	21700	24800	50200	58000	14100
14.7	1800	0.9	96.9	**—**	**3/A03L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	18200	20700	35500	42100	9630
15.7	1690	1.4	90.7	**—**	**3/A04L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	17800	20300	34800	41300	9420
16.0	1650	1.0	88.5	**—**	**3/A03L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	17600	20100	34600	41000	9340
16.6	1590	2.2	85.6	**—**	**3/A05L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	17400	19900	34200	40600	9240
17.4	1520	1.6	81.7	**—**	**3/A04L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	17200	19600	33800	40000	9100
18.7	1410	2.2	75.8	**—**	**3/A05L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	16700	19100	33000	39100	8870
19.4	1360	1.3	73.2	**—**	**3/A03L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	16500	18900	32700	38700	8770
19.6	1350	2.5	72.5	**—**	**3/A05L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	16500	18800	32600	38600	8740
20.8	1270	2.0	68.4	**—**	**3/A04L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	16200	18500	32000	37900	8580
22.6	1170	1.3	62.9	**—**	**3/A03L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	15700	18000	31200	37000	8340
22.7	1170	2.8	62.6	**—**	**3/A05L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	15700	17900	31200	36900	8330
22.8	1160	2.5	62.4	**—**	**3/A04L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	15700	17900	31100	36900	8320
23.9	1110	1.1	59.4	**—**	**3/A01L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	4770	4770	16300	17800	2730
26.1	1020	2.4	54.5	**—**	**3/A04L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	15000	17100	29900	35400	7950
26.2	1010	1.2	54.2	**—**	**3/A01L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	4630	4630	15800	17300	2650
27.0	980	1.7	52.5	**—**	**3/A03L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	14800	16900	29600	35000	7850
27.0	980	1.7	52.5	**—**	**3/A03L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	14800	16900	29600	35000	7850
28.6	930	2.5	49.7	**—**	**3/A04L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	14500	16600	29100	34500	7710
28.9	910	0.9	49.1	**—**	**3/A01L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	4480	4480	15400	16800	2560
32	820	1.1	43.9	**—**	**3/A01L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	4320	4320	14900	16300	2470
33	810	2.2	43.4	**—**	**3/A03L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	13900	15900	27900	33100	7370
35	750	1.2	40.1	**—**	**3/A01L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	4190	4190	14500	15800	2390
35	750	2.2	40.5	**—**	**3/A03L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	13600	15500	27300	32400	7200
40	670	1.1	35.8	**—**	**3/A01L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	4030	4030	14000	15300	2300
42	620	2.9	33.5	**—**	**3/A03L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	12700	14600	25800	30600	6760
45	590	1.1	31.7	**—**	**3/A00L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	3870	3870	13500	15700	2210
46	580	2.0	31.2	**—**	**3/A01L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	3850	3850	13400	14700	2200
49	540	2.9	28.8	**—**	**3/A03L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	12100	13800	24700	29300	6430
61	435	1.3	23.4	**—**	**3/A00L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	3500	3500	12300	14300	2000
62	430	2.0	23.0	**—**	**3/A01L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	3480	3480	12300	13400	1990
62	430	2.9	23.0	**—**	**3/A03L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	11200	12800	23100	27300	5960
73	360	2.9	19.4	**—**	**3/A03L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	10600	12100	21900	26000	5640
74	355	1.3	19.1	**—**	**3/A00L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	3270	3270	11600	13500	1870
76	350	2.0	18.8	**—**	**3/A01L2**	**BE100LB4**	**BX100LB4**	**ME3LB4**	**MX3LB4**	3250	3250	11500	12600	1860



P_1 = 4 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N]				
min^{-1}	Nm									MC/PC	MZ/PZ	HC	HZ	FZ
0.29	97600	1.0	4950	3/V15ML4	—	BE112M4	BX112M4	—	—	—	—	197000	236300	90000
0.29	97600	1.2	4950	3/V16ML4	—	BE112M4	BX112M4	—	—	—	—	301500	338200	150000
0.32	83300	2.4	4449	3/V17ML4	—	BE112M4	BX112M4	—	—	—	—	442000	470000	150000
0.33	81800	1.0	4312	3/V14ML4	—	BE112M4	BX112M4	—	—	—	—	193200	231700	90000
0.35	82200	1.2	4171	3/V15ML4	—	BE112M4	BX112M4	—	—	—	—	192300	230600	90000
0.35	82200	1.6	4171	3/V16ML4	—	BE112M4	BX112M4	—	—	—	—	294200	330000	150000
0.41	69300	1.9	3514	3/V16ML4	—	BE112M4	BX112M4	—	—	—	—	287100	322100	150000
0.45	65100	1.2	3182	3/V14ML4	—	BE112M4	BX112M4	—	—	—	—	185000	221800	90000
0.50	56800	2.1	2880	3/V16ML4	—	BE112M4	BX112M4	—	—	—	—	279000	313000	150000
0.52	52600	1.1	2773	3/V13ML4	—	BE112M4	BX112M4	ME4SA4	MX4SA4	—	—	192000	228600	80000
0.52	54800	1.5	2782	3/V14ML4	—	BE112M4	BX112M4	—	—	—	—	181400	217600	90000
0.54	52800	2.1	2678	3/V16ML4	—	BE112M4	BX112M4	—	—	—	—	276200	309800	150000
0.58	47500	1.7	2504	3/V14ML4	—	BE112M4	BX112M4	—	—	—	—	178700	214300	90000
0.62	43600	1.5	2318	3/V14ML3	—	BE112M4	BX112M4	—	—	—	—	176800	212000	90000
0.71	38000	1.5	2019	3/V13ML3	—	BE112M4	BX112M4	—	—	—	—	186500	218500	80000
0.72	37500	1.9	1994	3/V14ML3	—	BE112M4	BX112M4	—	—	—	—	173000	207500	90000
0.73	36900	1.1	1963	3/V11ML3	—	BE112M4	BX112M4	—	—	—	—	128200	130800	65000
0.86	32500	1.8	1682	3/V13ML3	—	BE112M4	BX112M4	—	—	—	—	181700	212900	80000
0.87	32100	2.3	1662	3/V14ML3	—	BE112M4	BX112M4	—	—	—	—	168600	202200	90000
0.88	31600	1.3	1636	3/V11ML3	—	BE112M4	BX112M4	—	—	—	—	124900	127400	65000
0.91	29900	1.9	1589	3/V14ML3	—	BE112M4	BX112M4	—	—	—	—	167500	200900	90000
1.0	26600	1.8	1378	3/V11ML3	—	BE112M4	BX112M4	—	—	—	—	121800	124300	63200
1.0	27400	2.1	1418	3/V13ML3	—	BE112M4	BX112M4	—	—	—	—	177300	207700	78500
1.1	24600	1.3	1274	3/V11ML3	—	BE112M4	BX112M4	—	—	—	—	120500	123000	61600
1.1	24900	2.0	1291	3/V13ML3	—	BE112M4	BX112M4	—	—	—	—	174900	205000	76100
1.1	25600	2.4	1324	3/V14ML3	—	BE112M4	BX112M4	—	—	—	—	163200	195700	86300
1.1	25200	1.9	1339	3/V14ML3	—	BE112M4	BX112M4	—	—	—	—	163400	196000	86700
1.3	21900	1.3	1120	3/V10ML3	—	BE112M4	BX112M4	—	—	—	—	94200	119400	59000
1.3	21000	2.4	1088	3/V13ML3	—	BE112M4	BX112M4	—	—	—	—	170700	200000	71900
1.3	21500	2.4	1116	3/V14ML3	—	BE112M4	BX112M4	—	—	—	—	159200	191000	81500
1.4	19600	0.9	1004	3/V09L3	—	BE112M4	BX112M4	—	—	—	—	82000	105500	31500
1.4	19600	1.6	1004	3/V10ML3	—	BE112M4	BX112M4	—	—	—	—	92700	117500	56900
1.4	18900	1.9	1004	3/V11ML3	—	BE112M4	BX112M4	—	—	—	—	116500	118800	56900
1.6	18700	1.0	920	3/V10ML3	—	BE112M4	BX112M4	—	—	—	—	91500	116100	55200
1.6	17400	2.4	900	3/V11ML3	—	BE112M4	BX112M4	—	—	—	—	114700	117000	54800
1.7	17100	1.2	840	3/V09L3	—	BE112M4	BX112M4	—	—	—	—	79900	102900	29700
1.8	15600	1.4	800	3/V09L3	—	BE112M4	BX112M4	—	—	—	—	79400	102200	29200
1.9	14900	1.0	761	3/V07L3	—	BE112M4	BX112M4	ME4SA4	MX4SA4	34300	42800	77100	101400	35900
1.9	15500	0.9	761	3/V09L3	—	BE112M4	BX112M4	—	—	—	—	78800	101400	28700
2.2	12800	1.1	655	3/V07L3	—	BE112M4	BX112M4	ME4SA4	MX4SA4	33500	41900	75500	99300	34100
2.2	13300	1.3	655	3/V09L3	—	BE112M4	BX112M4	—	—	—	—	77100	99300	27300
2.8	10800	1.3	507	3/V07L3	—	BE112M4	BX112M4	ME4SA4	MX4SA4	32300	40400	72800	95700	31400
3.1	9820	1.3	460	3/V07L3	—	BE112M4	BX112M4	ME4SA4	MX4SA4	31900	39900	71800	94400	30400
3.3	8980	2.0	442	3/V09L3	—	BE112M4	BX112M4	—	—	—	—	72900	93800	24000
3.4	9220	1.0	427	3/V06L3	—	BE112M4	BX112M4	ME4SA4	MX4SA4	26300	30000	59900	69200	23000
3.6	9970	0.9	405	—	3/A07L2	BE112M4	BX112M4	ME4SA4	MX4SA4	31300	39100	70500	92700	29100
3.7	8530	1.1	386	3/V07L3	—	BE112M4	BX112M4	ME4SA4	MX4SA4	31100	38900	70000	92100	28600
3.9	7520	1.7	370	3/V09L3	—	BE112M4	BX112M4	—	—	—	—	71100	91500	22600
4.2	8390	1.4	341	—	3/A07L2	BE112M4	BX112M4	ME4SA4	MX4SA4	30600	38200	68800	90400	27500
5.1	6940	1.3	282	—	3/A07L2	BE112M4	BX112M4	ME4SA4	MX4SA4	30000	37500	67500	88800	25800
5.2	6790	1.1	276	—	3/A06L2	BE112M4	BX112M4	ME4SA4	MX4SA4	25000	28500	57000	65800	19900
6.0	5930	1.5	241	—	3/A07L2	BE112M4	BX112M4	ME4SA4	MX4SA4	30000	37500	67500	88800	24500
6.5	5440	1.2	221	—	3/A06L2	BE112M4	BX112M4	ME4SA4	MX4SA4	25000	28500	57000	65800	18500
6.5	5490	1.6	223	—	3/A07L2	BE112M4	BX112M4	ME4SA4	MX4SA4	30000	37500	67500	88800	23800
7.3	4870	1.1	198	—	3/A06L2	BE112M4	BX112M4	ME4SA4	MX4SA4	25000	28500	57000	65800	17800
7.3	4870	1.8	198	—	3/A07L2	BE112M4	BX112M4	ME4SA4	MX4SA4	30000	37500	67500	88800	22900
7.6	4680	1.7	190	—	3/A06L2	BE112M4	BX112M4	ME4SA4	MX4SA4	25000	28500	57000	65800	17600
8.0	4430	2.5	180	—	3/A07L2	BE112M4	BX112M4	ME4SA4	MX4SA4	30000	37500	67500	88800	22200
8.8	4040	1.6	164	—	3/A06L2	BE112M4	BX112M4	ME4SA4	MX4SA4	25000	28500	57000	65800	16700
9.3	3820	2.4	155	—	3/A07L2	BE112M4	BX112M4	ME4SA4	MX4SA4	30000	37500	67500	88800	21100
10.2	3550	1.0	141	—	3/A05L2	BE112M4	BX112M4	ME4SA4	MX4SA4	20600	23500	39700	47100	10900
10.2	3470	2.2	141	—	3/A06L2	BE112M4	BX112M4	ME4SA4	MX4SA4	24500	27900	55900	64600	15900
11.5	3140	1.7	125	—	3/A06L2	BE112M4	BX112M4	ME4SA4	MX4SA4	23500	26800	53900	62200	15300
11.9	3040	1.2	121	—	3/A05L2	BE112M4	BX112M4	ME4SA4	MX4SA4	19600	22300	38000	45000	10400
12.9	2760	2.2	112	—	3/A06L2	BE112M4	BX112M4	ME4SA4	MX4SA4	22700	25900	52200	60300	14700



A

P_1 = 4 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N]				
min^{-1}	Nm									MC/PC	MZ/PZ	HC	HZ	FZ
13.8	2610	1.2	104	—	**3/A05L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	18600	21200	36200	42900	9840
14.1	2560	1.0	102	—	**3/A04L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	18500	21100	36100	42700	9790
14.6	2470	2.2	98.3	—	**3/A06L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	21700	24800	50200	58000	14100
15.9	2280	1.0	90.7	—	**3/A04L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	17800	20300	34800	41300	9420
16.3	2230	2.8	88.5	—	**3/A06L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	21000	23900	48700	56200	13600
16.8	2150	1.6	85.6	—	**3/A05L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	17400	19900	34200	40600	9240
17.6	2050	1.2	81.7	—	**3/A04L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	17200	19600	33800	40000	9100
19.0	1910	1.6	75.8	—	**3/A05L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	16700	19100	33000	39100	8870
19.7	1840	1.0	73.2	—	**3/A03L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	16500	18900	32700	38700	8770
19.9	1820	1.8	72.5	—	**3/A05L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	16500	18800	32600	38600	8740
21.1	1720	1.5	68.4	—	**3/A04L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	16200	18500	32000	37900	8580
22.9	1580	1.0	62.9	—	**3/A03L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	15700	18000	31200	37000	8340
23.0	1570	2.0	62.6	—	**3/A05L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	15700	17900	31200	36900	8330
23.1	1570	1.8	62.4	—	**3/A04L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	15700	17900	31100	36900	8320
25.3	1430	2.3	57.0	—	**3/A05L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	15200	17400	30300	35900	8070
26.4	1370	1.7	54.5	—	**3/A04L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	15000	17100	29900	35400	7950
27.0	1340	2.3	53.3	—	**3/A05L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	14900	17000	29700	35200	7890
27.4	1320	1.3	52.5	—	**3/A03L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	14800	16900	29600	35000	7850
27.4	1320	1.3	52.5	—	**3/A03L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	14800	16900	29600	35000	7850
29	1250	1.8	49.7	—	**3/A04L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	14500	16600	29100	34500	7710
33	1090	1.6	43.4	—	**3/A03L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	13900	15900	27900	33100	7370
33	1110	2.6	44.3	—	**3/A04L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	14000	16000	28100	33300	7420
33	1110	3.0	44.0	—	**3/A05L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	14000	15900	28000	33200	7400
36	1020	1.6	40.5	—	**3/A03L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	13600	15500	27300	32400	7200
37	980	2.3	39.1	—	**3/A04L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	13400	15300	27100	32100	7120
41	890	2.6	35.3	—	**3/A04L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	13000	14800	26200	31100	6880
43	840	2.1	33.5	—	**3/A03L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	12700	14600	25800	30600	6760
46	780	1.5	31.2	—	**3/A01L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3850	3850	13400	14700	2200
48	760	3.0	30.2	—	**3/A04L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	12300	14100	25000	29700	6530
50	720	2.1	28.8	—	**3/A03L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	12100	13800	24700	29300	6430
56	640	3.0	25.6	—	**3/A04L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	11600	13300	23800	28200	6180
62	590	1.0	23.4	—	**3/A00L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3500	3500	12300	14300	2000
63	580	1.5	23.0	—	**3/A01L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3480	3480	12300	13400	1990
63	580	2.1	23.0	—	**3/A03L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	11200	12800	23100	27300	5960
74	490	2.2	19.4	—	**3/A03L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	10600	12100	21900	26000	5640
75	480	1.0	19.1	—	**3/A00L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3270	3270	11600	13500	1870
77	475	1.5	18.8	—	**3/A01L2**	**BE112M4**	**BX112M4**	**ME4SA4**	**MX4SA4**	3250	3250	11500	12600	1860

P_1 = 5.5 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N]				
min^{-1}	Nm									MC/PC	MZ/PZ	HC	HZ	FZ
0.29	130100	0.9	4950	**3/V16ML4**	—	**BE132S4**	**BX132SB4**	—	—	—	—	301500	338200	150000
0.29	135500	0.9	4970	**3/V17ML4**	—	**BE132S4**	**BX132SB4**	—	—	—	—	442000	470000	150000
0.29	139100	1.9	5099	**3/V18ML4**	—	**BE132S4**	**BX132SB4**	—	—	—	—	448200	506000	200000
0.33	111100	1.8	4449	**3/V17ML4**	—	**BE132S4**	**BX132SB4**	—	—	—	—	442000	470000	150000
0.33	119600	2.5	4386	**3/V18ML4**	—	**BE132S4**	**BX132SB4**	—	—	—	—	438600	495300	200000
0.33	124500	2.7	4457	**3/V19L4**	—	**BE132S4**	**BX132SB4**	—	—	—	—	534200	588100	200000
0.35	109600	0.9	4171	**3/V15ML4**	—	**BE132S4**	**BX132SB4**	—	—	—	—	192300	230600	90000
0.35	109600	1.2	4171	**3/V16ML4**	—	**BE132S4**	**BX132SB4**	—	—	—	—	294200	330000	150000
0.35	112600	1.6	4129	**3/V17ML4**	—	**BE132S4**	**BX132SB4**	—	—	—	—	442000	470000	150000
0.40	100800	3.0	3696	**3/V18ML4**	—	**BE132S4**	**BX132SB4**	—	—	—	—	428000	483300	200000
0.42	96300	1.0	3489	**3/V15ML4**	—	**BE132S4**	**BX132SB4**	—	—	—	—	187400	224800	90000
0.42	92400	1.5	3514	**3/V16ML4**	—	**BE132S4**	**BX132SB4**	—	—	—	—	287100	322100	150000
0.44	91100	1.1	3300	**3/V15ML4**	—	**BE132S4**	**BX132SB4**	—	—	—	—	185900	223000	90000
0.46	86400	2.2	3168	**3/V17ML4**	—	**BE132S4**	**BX132SB4**	—	—	—	—	440100	467600	150000
0.51	75700	1.6	2880	**3/V16ML4**	—	**BE132S4**	**BX132SB4**	—	—	—	—	279000	313000	150000
0.52	73100	1.1	2782	**3/V14ML4**	—	**BE132S4**	**BX132SB4**	—	—	—	—	181400	217600	90000
0.53	76700	1.3	2780	**3/V15ML4**	—	**BE132S4**	**BX132SB4**	—	—	—	—	181400	217600	90000
0.53	71100	2.3	2773	**3/V17ML4**	—	**BE132S4**	**BX132SB4**	—	—	—	—	431800	458800	150000
0.55	70400	1.6	2678	**3/V16ML4**	—	**BE132S4**	**BX132SB4**	—	—	—	—	276200	309800	150000
0.58	63300	1.3	2504	**3/V14ML4**	—	**BE132S4**	**BX132SB4**	—	—	—	—	178700	214300	90000



P_1 = 5.5 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
min^{-1}	Nm													
0.62	64700	2.1	2343	**3/V16ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	270900	303900	150000
0.63	58100	1.1	2318	**3/V14ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	176800	212000	90000
0.63	57300	1.4	2318	**3/V15ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	176800	212000	90000
0.72	50600	1.1	2019	**3/V13ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	186500	218500	80000
0.73	50000	1.4	1994	**3/V14ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	173000	207500	90000
0.73	49300	1.9	1994	**3/V15ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	173000	207500	90000
0.76	53000	2.1	1920	**3/V16ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	263300	295400	150000
0.82	49300	2.1	1785	**3/V16ML4**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	260600	292400	150000
0.87	43300	1.3	1682	**3/V13ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	181700	212900	80000
0.88	42800	1.7	1662	**3/V14ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	168600	202200	90000
0.88	42800	2.1	1662	**3/V15ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	168600	202200	90000
0.89	42100	1.0	1636	**3/V11ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	124900	127400	65000
0.90	42800	0.9	1620	**3/V13ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	180700	211700	80000
0.92	39800	1.4	1589	**3/V14ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	167500	200900	90000
0.92	40900	2.7	1589	**3/V16ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	256300	287500	150000
1.0	36500	1.6	1418	**3/V13ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	177300	207700	78500
1.0	36000	2.4	1400	**3/V15ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	164500	197300	88000
1.1	32800	1.0	1274	**3/V11ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	120500	123000	61600
1.1	35500	1.3	1378	**3/V11ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	121800	124300	63200
1.1	33200	1.5	1291	**3/V13ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	174900	205000	76100
1.1	34100	1.8	1324	**3/V14ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	163200	195700	86300
1.1	33600	1.4	1339	**3/V14ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	163400	196000	86700
1.1	35100	2.6	1329	**3/V15ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	163300	195800	86400
1.3	29200	1.0	1120	**3/V10ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	94200	119400	59000
1.3	29100	1.6	1103	**3/V11ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	118000	120400	58700
1.3	28000	1.8	1088	**3/V13ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	170700	200000	71900
1.3	28700	1.8	1116	**3/V14ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	159200	191000	81500
1.4	28400	1.9	1009	**3/V13ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	168900	197900	70100
1.5	26200	1.2	1004	**3/V10ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	92700	117500	56900
1.5	25200	1.4	1004	**3/V11ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	116500	118800	56900
1.5	28000	2.2	997	**3/V14ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	156700	187900	78500
1.6	23200	1.8	900	**3/V11ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	114700	117000	54800
1.6	23600	2.3	893	**3/V14ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	154200	185000	75700
1.7	23000	2.3	870	**3/V13ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	165300	193700	66700
1.8	20900	1.0	800	**3/V09L3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	79400	102200	29200
1.8	23300	1.9	827	**3/V11ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	113300	115600	53300
1.8	22300	2.2	794	**3/V14ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	151700	181900	72800
1.9	22000	1.0	773	**3/V10ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	89300	113200	52100
2.0	19000	2.2	720	**3/V11ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	111100	113300	50900
2.0	19600	2.3	741	**3/V13ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	161600	189300	63200
2.1	20700	1.0	701	**3/V10ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	88100	111600	50400
2.1	18400	2.3	695	**3/V14ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	148800	178500	69700
2.2	17700	1.0	655	**3/V09L3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	77100	99300	27300
2.3	18100	2.2	644	**3/V11ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	109300	111500	49000
2.4	17500	1.1	614	**3/V10ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	86400	109500	48300
2.6	15900	1.6	560	**3/V10ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	85300	108100	46800
2.9	14400	0.9	507	**3/V07L3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	32300	40400	72800	95700	31400
2.9	14400	1.0	507	**3/V09L3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	74400	95700	25100
2.9	14400	1.7	507	**3/V10ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	84100	106600	45300
3.2	13100	0.9	460	**3/V07L3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	31900	39900	71800	94400	30400
3.3	12000	1.5	442	**3/V09L3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	72900	93800	24000
3.3	12400	2.2	436	**3/V10ML3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	82300	104300	43100
3.9	10000	1.3	370	**3/V09L3**	**—**	**BE132S4**	**BX132SB4**	**—**	**—**	—	—	71100	91500	22600
4.3	11200	1.0	341	**—**	**3/A07L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	30600	38200	68800	90400	27500
5.2	9260	0.9	282	**—**	**3/A07L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	30000	37500	67500	88800	25800
6.1	7910	1.1	241	**—**	**3/A07L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	30000	37500	67500	88800	24500
6.5	7320	1.2	223	**—**	**3/A07L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	30000	37500	67500	88800	23800
7.4	6500	1.3	198	**—**	**3/A07L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	30000	37500	67500	88800	22900
7.7	6240	1.2	190	**—**	**3/A06L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	25000	28500	57000	65800	17600
8.1	5910	1.8	180	**—**	**3/A07L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	30000	37500	67500	88800	22200
8.9	5380	1.2	164	**—**	**3/A06L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	25000	28500	57000	65800	16700
9.4	5090	1.8	155	**—**	**3/A07L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	30000	37500	67500	88800	21100
10.4	4630	1.7	141	**—**	**3/A06L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	24500	27900	55900	64600	15900
10.4	4600	2.4	140	**—**	**3/A07L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	29300	36700	66200	87000	20400
11.2	4270	2.6	130	**—**	**3/A07L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	28600	35700	64600	85000	19900



A

P_1 = 5.5 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
min^{-1}	Nm													
11.7	4190	1.3	125	—	**3/A06L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	23500	26800	53900	62200	15300
13.0	3680	1.7	112	—	**3/A06L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	22700	25900	52200	60300	14700
13.4	3580	2.5	109	—	**3/A07L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	26900	33700	61300	80600	18800
14.9	3300	1.6	98.3	—	**3/A06L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	21700	24800	50200	58000	14100
16.5	2970	2.1	88.5	—	**3/A06L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	21000	23900	48700	56200	13600
17.1	2870	1.2	85.6	—	**3/A05L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	17400	19900	34200	40600	9240
18.0	2720	2.4	81.2	—	**3/A06L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	20400	23200	47400	54700	13200
19.3	2540	1.2	75.8	—	**3/A05L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	16700	19100	33000	39100	8870
20.1	2430	1.4	72.5	—	**3/A05L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	16500	18800	32600	38600	8740
20.9	2340	2.4	69.9	—	**3/A06L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	19400	22100	45300	52300	12600
21.3	2290	1.1	68.4	—	**3/A04L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	16200	18500	32000	37900	8580
23.3	2100	1.5	62.6	—	**3/A05L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	15700	17900	31200	36900	8330
23.4	2090	1.4	62.4	—	**3/A04L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	15700	17900	31100	36900	8320
24.3	2010	3.0	60.1	—	**3/A06L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	18400	21000	43300	50000	12000
25.6	1910	1.7	57.0	—	**3/A05L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	15200	17400	30300	35900	8070
26.2	1870	2.4	55.7	—	**3/A06L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	18000	20500	42300	48900	11700
26.8	1830	1.3	54.5	—	**3/A04L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	15000	17100	29900	35400	7950
27.4	1790	1.7	53.3	—	**3/A05L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	14900	17000	29700	35200	7890
28.2	1730	3.0	51.7	—	**3/A06L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	17500	20000	41400	47800	11400
29.4	1670	1.4	49.7	—	**3/A04L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	14500	16600	29100	34500	7710
31	1580	2.4	47.2	—	**3/A06L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	17000	19400	40300	46500	11000
33	1490	1.9	44.3	—	**3/A04L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	14000	16000	28100	33300	7420
33	1480	2.2	44.0	—	**3/A05L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	14000	15900	28000	33200	7400
37	1310	1.7	39.1	—	**3/A04L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	13400	15300	27100	32100	7120
37	1310	2.3	39.0	—	**3/A05L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	13400	15300	27000	32000	7110
41	1180	1.9	35.3	—	**3/A04L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	13000	14800	26200	31100	6880
42	1170	3.0	34.9	—	**3/A06L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	15400	17500	36800	42500	9990
48	1010	2.2	30.2	—	**3/A04L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	12300	14100	25000	29700	6530
57	860	2.2	25.6	—	**3/A04L2**	**BE132S4**	**BX132SB4**	**ME4SB4**	**MX4SB4**	11600	13300	23800	28200	6180

P_1 = 7.5 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
min^{-1}	Nm													
0.28	180100	2.3	5164	**3/V19L4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	545500	600600	200000
0.29	189300	1.4	5099	**3/V18ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	448200	506000	200000
0.33	151200	1.3	4449	**3/V17ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	442000	470000	150000
0.33	162800	1.8	4386	**3/V18ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	438600	495300	200000
0.33	169400	2.0	4457	**3/V19L4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	534200	588100	200000
0.35	149200	0.9	4171	**3/V16ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	294200	330000	150000
0.35	153300	1.2	4129	**3/V17ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	442000	470000	150000
0.36	152000	2.5	4095	**3/V19L4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	527700	581100	200000
0.40	137200	2.2	3696	**3/V18ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	428000	483300	200000
0.42	125700	1.1	3514	**3/V16ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	287100	322100	150000
0.42	129700	2.3	3495	**3/V18ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	424600	479400	200000
0.45	122800	2.9	3231	**3/V19L4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	510200	561700	200000
0.46	117600	1.6	3168	**3/V17ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	440100	467600	150000
0.50	109300	2.5	2945	**3/V18ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	414400	467900	200000
0.51	103000	1.2	2880	**3/V16ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	279000	313000	150000
0.53	104400	1.0	2780	**3/V15ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	181400	217600	90000
0.53	96700	1.7	2773	**3/V17ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	431800	458800	150000
0.55	95800	1.2	2678	**3/V16ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	276200	309800	150000
0.58	86200	0.9	2504	**3/V14ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	178700	214300	90000
0.62	88000	1.5	2343	**3/V16ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	270900	303900	150000
0.63	78000	1.0	2318	**3/V15ML3**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	176800	212000	90000
0.64	85200	2.5	2295	**3/V18ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	399900	451500	200000
0.73	68000	1.0	1994	**3/V14ML3**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	173000	207500	90000
0.73	67100	1.4	1994	**3/V15ML3**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	173000	207500	90000
0.76	72100	1.6	1920	**3/V16ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	263300	295400	150000
0.82	67100	1.6	1785	**3/V16ML4**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	260600	292400	150000
0.87	58900	1.0	1682	**3/V13ML3**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	181700	212900	80000
0.88	58200	1.3	1662	**3/V14ML3**	—	**BE132MA4**	**BX132MA4**	—	—	—	—	168600	202200	90000



P_1 = 7.5 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
min^{-1}	Nm													
0.88	58200	1.6	1662	3/V15ML3	—	BE132MA4	BX132MA4	—	—	—	—	168600	202200	90000
0.92	54200	1.0	1589	3/V14ML3	—	BE132MA4	BX132MA4	—	—	—	—	167500	200900	90000
0.92	55700	2.0	1589	3/V16ML3	—	BE132MA4	BX132MA4	—	—	—	—	256300	287500	150000
1.0	49700	1.1	1418	3/V13ML3	—	BE132MA4	BX132MA4	—	—	—	—	177300	207700	78500
1.0	49100	1.8	1400	3/V15ML3	—	BE132MA4	BX132MA4	—	—	—	—	164500	197300	88000
1.1	48300	1.0	1378	3/V11ML3	—	BE132MA4	BX132MA4	—	—	—	—	121800	124300	63200
1.1	45200	1.1	1291	3/V13ML3	—	BE132MA4	BX132MA4	—	—	—	—	174900	205000	76100
1.1	46400	1.3	1324	3/V14ML3	—	BE132MA4	BX132MA4	—	—	—	—	163200	195700	86300
1.1	45700	1.0	1339	3/V14ML3	—	BE132MA4	BX132MA4	—	—	—	—	163400	196000	86700
1.1	47800	1.9	1329	3/V15ML3	—	BE132MA4	BX132MA4	—	—	—	—	163300	195800	86400
1.1	46400	2.4	1324	3/V16ML3	—	BE132MA4	BX132MA4	—	—	—	—	249700	280100	143900
1.3	39700	1.1	1103	3/V11ML3	—	BE132MA4	BX132MA4	—	—	—	—	118000	120400	58700
1.3	38100	1.3	1088	3/V13ML3	—	BE132MA4	BX132MA4	—	—	—	—	170700	200000	71900
1.3	39100	1.3	1116	3/V14ML3	—	BE132MA4	BX132MA4	—	—	—	—	159200	191000	81500
1.3	40300	2.2	1120	3/V15ML3	—	BE132MA4	BX132MA4	—	—	—	—	159300	191100	81600
1.4	38600	1.4	1009	3/V13ML3	—	BE132MA4	BX132MA4	—	—	—	—	168900	197900	70100
1.5	34300	1.0	1004	3/V11ML3	—	BE132MA4	BX132MA4	—	—	—	—	116500	118800	56900
1.5	38200	1.6	997	3/V14ML3	—	BE132MA4	BX132MA4	—	—	—	—	156700	187900	78500
1.5	38200	2.3	997	3/V15ML3	—	BE132MA4	BX132MA4	—	—	—	—	156700	187900	78500
1.6	31500	1.3	900	3/V11ML3	—	BE132MA4	BX132MA4	—	—	—	—	114700	117000	54800
1.6	32100	1.7	893	3/V14ML3	—	BE132MA4	BX132MA4	—	—	—	—	154200	185000	75700
1.7	31300	1.7	870	3/V13ML3	—	BE132MA4	BX132MA4	—	—	—	—	165300	193700	66700
1.7	32100	2.5	840	3/V15ML3	—	BE132MA4	BX132MA4	—	—	—	—	152900	183400	74200
1.8	31600	1.4	827	3/V11ML3	—	BE132MA4	BX132MA4	—	—	—	—	113300	115600	53300
1.8	30400	1.6	794	3/V14ML3	—	BE132MA4	BX132MA4	—	—	—	—	151700	181900	72800
2.0	25900	1.6	720	3/V11ML3	—	BE132MA4	BX132MA4	—	—	—	—	111100	113300	50900
2.0	26600	1.7	741	3/V13ML3	—	BE132MA4	BX132MA4	—	—	—	—	161600	189300	63200
2.1	25000	1.7	695	3/V14ML3	—	BE132MA4	BX132MA4	—	—	—	—	148800	178500	69700
2.3	24600	1.6	644	3/V11ML3	—	BE132MA4	BX132MA4	—	—	—	—	109300	111500	49000
2.6	21700	1.2	560	3/V10ML3	—	BE132MA4	BX132MA4	—	—	—	—	85300	108100	46800
2.9	19600	1.3	507	3/V10ML3	—	BE132MA4	BX132MA4	—	—	—	—	84100	106600	45300
3.3	16300	1.1	442	3/V09L3	—	BE132MA4	BX132MA4	—	—	—	—	72900	93800	24000
3.3	16900	1.6	436	3/V10ML3	—	BE132MA4	BX132MA4	—	—	—	—	82300	104300	43100
3.9	13600	1.0	370	3/V09L3	—	BE132MA4	BX132MA4	—	—	—	—	71100	91500	22600
6.5	9960	0.9	223	—	3/A07L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	30000	37500	67500	88800	23800
7.4	8850	1.0	198	—	3/A07L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	30000	37500	67500	88800	22900
7.7	8490	0.9	190	—	3/A06L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	25000	28500	57000	65800	17600
8.1	8040	1.4	180	—	3/A07L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	30000	37500	67500	88800	22200
9.4	6930	1.3	155	—	3/A07L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	30000	37500	67500	88800	21100
10.4	6300	1.2	141	—	3/A06L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	24500	27900	55900	64600	15900
10.4	6250	1.8	140	—	3/A07L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	29300	36700	66200	87000	20400
11.2	5810	1.9	130	—	3/A07L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	28600	35700	64600	85000	19900
11.7	5700	1.0	125	—	3/A06L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	23500	26800	53900	62200	15300
13.0	5000	1.2	112	—	3/A06L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	22700	25900	52200	60300	14700
13.4	4870	1.8	109	—	3/A07L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	26900	33700	61300	80600	18800
14.9	4490	1.2	98.3	—	3/A06L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	21700	24800	50200	58000	14100
16.5	4040	1.5	88.5	—	3/A06L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	21000	23900	48700	56200	13600
16.6	4000	2.5	87.7	—	3/A07L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	25100	31400	57500	75600	17500
17.1	3910	0.9	85.6	—	3/A05L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	17400	19900	34200	40600	9240
18.0	3710	1.7	81.2	—	3/A06L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	20400	23200	47400	54700	13200
20.1	3310	1.0	72.5	—	3/A05L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	16500	18800	32600	38600	8740
20.9	3190	1.8	69.9	—	3/A06L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	19400	22100	45300	52300	12600
21.4	3120	2.5	68.3	—	3/A07L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	23100	28900	53300	70100	16100
23.3	2860	1.1	62.6	—	3/A05L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	15700	17900	31200	36900	8330
23.4	2850	1.0	62.4	—	3/A04L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	15700	17900	31100	36900	8320
24.3	2740	2.2	60.1	—	3/A06L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	18400	21000	43300	50000	12000
25.5	2610	2.5	57.3	—	3/A07L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	21800	27200	50600	66500	15200
25.6	2600	1.3	57.0	—	3/A05L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	15200	17400	30300	35900	8070
26.2	2540	1.8	55.7	—	3/A06L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	18000	20500	42300	48900	11700
26.8	2490	1.0	54.5	—	3/A04L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	15000	17100	29900	35400	7950
27.4	2430	1.2	53.3	—	3/A05L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	14900	17000	29700	35200	7890
28.2	2360	2.2	51.7	—	3/A06L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	17500	20000	41400	47800	11400
29.4	2270	1.0	49.7	—	3/A04L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	14500	16600	29100	34500	7710
31	2150	1.8	47.2	—	3/A06L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	17000	19400	40300	46500	11000
33	2020	1.4	44.3	—	3/A04L2	BE132MA4	BX132MA4	ME4LA4	MX4LA4	14000	16000	28100	33300	7420



A

P_1 = 7.5 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
min^{-1}	Nm													
33	2010	1.6	44.0	—	**3/A05L2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	14000	15900	28000	33200	7400
36	1880	2.6	41.1	—	**3/A06L2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	16200	18500	38600	44600	10500
37	1780	1.3	39.1	—	**3/A04L2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	13400	15300	27100	32100	7120
37	1780	1.7	39.0	—	**3/A05L2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	13400	15300	27000	32000	7110
41	1610	1.4	35.3	—	**3/A04L2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	13000	14800	26200	31100	6880
42	1590	2.2	34.9	—	**3/A06L2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	15400	17500	36800	42500	9990
45	1470	2.3	32.2	—	**3/A05L2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	12600	14400	25500	30300	6670
45	1490	2.6	32.7	—	**3/A06L2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	15000	17200	36100	41700	9780
48	1380	1.6	30.2	—	**3/A04L2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	12300	14100	25000	29700	6530
53	1260	2.2	27.7	—	**3/A04L2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	12000	13700	24400	28900	6350
53	1260	2.3	27.7	—	**3/A05L2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	12000	13700	24400	28900	6350
53	1260	2.6	27.7	—	**3/A06L2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	14200	16200	34300	39600	9250
57	1170	1.6	25.6	—	**3/A04L2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	11600	13300	23800	28200	6180
66	1010	2.3	22.1	—	**3/A04L2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	11100	12700	22800	27000	5880
66	1010	2.3	22.1	—	**3/A05L2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	11100	12700	22800	27000	5880
78	850	2.3	18.7	—	**3/A04L2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	10500	12000	21700	25700	5570
78	850	2.3	18.7	—	**3/A05L2**	**BE132MA4**	**BX132MA4**	**ME4LA4**	**MX4LA4**	10500	12000	21700	25700	5570

P_1 = 9.2 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
min^{-1}	Nm													
0.28	220600	1.9	5164	**3/V19L4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	545500	600600	200000
0.29	231800	1.1	5099	**3/V18ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	448200	506000	200000
0.29	218000	2.5	5040	**3/V21L4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	769000	915300	1200000
0.32	209300	2.6	4550	**3/V21L4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	757800	902100	1200000
0.33	185200	1.1	4449	**3/V17ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	442000	470000	150000
0.33	199300	1.5	4386	**3/V18ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	438600	495300	200000
0.33	207500	1.6	4457	**3/V19L4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	534200	588100	200000
0.35	187700	1.0	4129	**3/V17ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	442000	470000	150000
0.36	186100	2.0	4095	**3/V19L4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	527700	581100	200000
0.39	173900	2.6	3780	**3/V21L4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	738000	878500	1200000
0.40	168000	1.8	3696	**3/V18ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	428000	483300	200000
0.42	158900	1.9	3495	**3/V18ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	424600	479400	200000
0.45	150400	2.4	3231	**3/V19L4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	510200	561700	200000
0.46	144000	1.3	3168	**3/V17ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	440100	467600	150000
0.50	133900	2.0	2945	**3/V18ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	414400	467900	200000
0.51	126200	1.0	2880	**3/V16ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	279000	313000	150000
0.53	118400	1.4	2773	**3/V17ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	431800	458800	150000
0.55	117300	1.0	2678	**3/V16ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	276200	309800	150000
0.59	114700	2.6	2464	**3/V18ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	403900	456100	200000
0.62	107800	1.2	2343	**3/V16ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	270900	303900	150000
0.64	104300	2.0	2295	**3/V18ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	399900	451500	200000
0.73	82200	1.1	1994	**3/V15ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	173000	207500	90000
0.76	88300	1.3	1920	**3/V16ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	263300	295400	150000
0.82	82100	1.3	1785	**3/V16ML4**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	260600	292400	150000
0.88	71300	1.0	1662	**3/V14ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	168600	202200	90000
0.88	71300	1.3	1662	**3/V15ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	168600	202200	90000
0.92	68200	1.6	1589	**3/V16ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	256300	287500	150000
1.0	60800	0.9	1418	**3/V13ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	177300	207700	78500
1.0	60100	1.4	1400	**3/V15ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	164500	197300	88000
1.1	55400	0.9	1291	**3/V13ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	174900	205000	76100
1.1	56800	1.1	1324	**3/V14ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	163200	195700	86300
1.1	58500	1.5	1329	**3/V15ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	163300	195800	86400
1.1	56800	2.0	1324	**3/V16ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	249700	280100	143900
1.1	60900	2.5	1365	**3/V17ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	390300	414600	145400
1.2	57600	2.5	1215	**3/V17ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	383800	407800	139800
1.3	48600	0.9	1103	**3/V11ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	118000	120400	58700
1.3	46700	1.1	1088	**3/V13ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	170700	200000	71900
1.3	47900	1.1	1116	**3/V14ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	159200	191000	81500
1.3	49300	1.8	1120	**3/V15ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	159300	191100	81600
1.3	50600	2.5	1134	**3/V17ML3**	—	**BE132MB4**	**BX160MA4**	—	—	—	—	380100	403800	136600



P_1 = 9.2 kW

n_2	M_2	S	i							Rn_2 [N]				
min^{-1}	Nm					IE2	IE3	IE2	IE3	MC/PC	MZ/PZ	HC	HZ	FZ
1.4	47300	1.1	1009	3/V13ML3	—	BE132MB4	BX160MA4	—	—	—	—	168900	197900	70100
1.4	47200	2.5	1059	3/V16ML3	—	BE132MB4	BX160MA4	—	—	—	—	241900	271300	133600
1.4	48600	2.6	1024	3/V17ML3	—	BE132MB4	BX160MA4	—	—	—	—	374500	397900	132100
1.5	46700	1.3	997	3/V14ML3	—	BE132MB4	BX160MA4	—	—	—	—	156700	187900	78500
1.5	46700	1.9	997	3/V15ML3	—	BE132MB4	BX160MA4	—	—	—	—	156700	187900	78500
1.6	38600	1.1	900	3/V11ML3	—	BE132MB4	BX160MA4	—	—	—	—	114700	117000	54800
1.6	39300	1.4	893	3/V14ML3	—	BE132MB4	BX160MA4	—	—	—	—	154200	185000	75700
1.6	39800	2.5	893	3/V16ML3	—	BE132MB4	BX160MA4	—	—	—	—	236000	264800	126200
1.7	38300	1.4	870	3/V13ML3	—	BE132MB4	BX160MA4	—	—	—	—	165300	193700	66700
1.7	39400	2.0	840	3/V15ML3	—	BE132MB4	BX160MA4	—	—	—	—	152900	183400	74200
1.7	40400	2.6	851	3/V17ML3	—	BE132MB4	BX160MA4	—	—	—	—	364700	387500	124200
1.8	38800	1.1	827	3/V11ML3	—	BE132MB4	BX160MA4	—	—	—	—	113300	115600	53300
1.8	37200	1.3	794	3/V14ML3	—	BE132MB4	BX160MA4	—	—	—	—	151700	181900	72800
1.8	37700	2.6	794	3/V16ML3	—	BE132MB4	BX160MA4	—	—	—	—	232200	260400	121400
2.0	31700	1.3	720	3/V11ML3	—	BE132MB4	BX160MA4	—	—	—	—	111100	113300	50900
2.0	32600	1.4	741	3/V13ML3	—	BE132MB4	BX160MA4	—	—	—	—	161600	189300	63200
2.1	30600	1.4	695	3/V14ML3	—	BE132MB4	BX160MA4	—	—	—	—	148800	178500	69700
2.2	31900	2.7	665	3/V15ML3	—	BE132MB4	BX160MA4	—	—	—	—	147900	177300	68600
2.2	31700	2.6	669	3/V16ML3	—	BE132MB4	BX160MA4	—	—	—	—	226500	254100	114600
2.3	30200	1.3	644	3/V11ML3	—	BE132MB4	BX160MA4	—	—	—	—	109300	111500	49000
2.6	26600	1.0	560	3/V10ML3	—	BE132MB4	BX160MA4	—	—	—	—	85300	108100	46800
2.9	24000	1.0	507	3/V10ML3	—	BE132MB4	BX160MA4	—	—	—	—	84100	106600	45300
3.3	20700	1.3	436	3/V10ML3	—	BE132MB4	BX160MA4	—	—	—	—	82300	104300	43100
8.1	9850	1.1	180	—	3/A07L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	30000	37500	67500	88800	22200
9.4	8480	1.1	155	—	3/A07L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	30000	37500	67500	88800	21100
10.4	7710	1.0	141	—	3/A06L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	24500	27900	55900	64600	15900
10.4	7660	1.4	140	—	3/A07L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	29300	36700	66200	87000	20400
11.2	7110	1.6	130	—	3/A07L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	28600	35700	64600	85000	19900
13.0	6130	1.0	112	—	3/A06L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	22700	25900	52200	60300	14700
13.4	5960	1.5	109	—	3/A07L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	26900	33700	61300	80600	18800
14.9	5490	1.0	98.3	—	3/A06L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	21700	24800	50200	58000	14100
16.5	4940	1.3	88.5	—	3/A06L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	21000	23900	48700	56200	13600
16.6	4900	2.1	87.7	—	3/A07L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	25100	31400	57500	75600	17500
18.0	4540	1.4	81.2	—	3/A06L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	20400	23200	47400	54700	13200
20.9	3910	1.5	69.9	—	3/A06L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	19400	22100	45300	52300	12600
21.4	3820	2.1	68.3	—	3/A07L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	23100	28900	53300	70100	16100
23.3	3500	0.9	62.6	—	3/A05L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	15700	17900	31200	36900	8330
24.3	3360	1.8	60.1	—	3/A06L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	18400	21000	43300	50000	12000
25.5	3200	2.1	57.3	—	3/A07L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	21800	27200	50600	66500	15200
25.6	3180	1.0	57.0	—	3/A05L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	15200	17400	30300	35900	8070
26.2	3110	1.5	55.7	—	3/A06L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	18000	20500	42300	48900	11700
27.4	2980	1.0	53.3	—	3/A05L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	14900	17000	29700	35200	7890
28.2	2890	1.8	51.7	—	3/A06L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	17500	20000	41400	47800	11400
31	2640	1.5	47.2	—	3/A06L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	17000	19400	40300	46500	11000
33	2480	1.2	44.3	—	3/A04L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	14000	16000	28100	33300	7420
33	2460	1.3	44.0	—	3/A05L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	14000	15900	28000	33200	7400
36	2300	2.1	41.1	—	3/A06L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	16200	18500	38600	44600	10500
37	2180	1.0	39.1	—	3/A04L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	13400	15300	27100	32100	7120
37	2180	1.4	39.0	—	3/A05L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	13400	15300	27000	32000	7110
41	1970	1.2	35.3	—	3/A04L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	13000	14800	26200	31100	6880
42	1950	1.8	34.9	—	3/A06L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	15400	17500	36800	42500	9990
45	1800	1.8	32.2	—	3/A05L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	12600	14400	25500	30300	6670
45	1830	2.1	32.7	—	3/A06L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	15000	17200	36100	41700	9780
48	1690	1.3	30.2	—	3/A04L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	12300	14100	25000	29700	6530
53	1550	1.8	27.7	—	3/A04L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	12000	13700	24400	28900	6350
53	1550	1.8	27.7	—	3/A05L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	12000	13700	24400	28900	6350
53	1550	2.1	27.7	—	3/A06L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	14200	16200	34300	39600	9250
57	1430	1.3	25.6	—	3/A04L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	11600	13300	23800	28200	6180
66	1230	1.8	22.1	—	3/A04L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	11100	12700	22800	27000	5880
66	1230	1.8	22.1	—	3/A05L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	11100	12700	22800	27000	5880
78	1040	1.8	18.7	—	3/A04L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	10500	12000	21700	25700	5570
78	1040	1.8	18.7	—	3/A05L2	BE132MB4	BX160MA4	ME4LB4	MX5SA4	10500	12000	21700	25700	5570



P_1 = 11 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
min^{-1}	Nm													
0.28	264700	1.6	5164	3/V19L4	—	BE160M4	BX160MB4	—	—	—	—	545500	600600	200000
0.29	278100	1.0	5099	3/V18ML4	—	BE160M4	BX160MB4	—	—	—	—	448200	506000	200000
0.29	261600	2.1	5040	3/V21L4	—	BE160M4	BX160MB4	—	—	—	—	769000	915300	1200000
0.32	251200	2.2	4550	3/V21L4	—	BE160M4	BX160MB4	—	—	—	—	757800	902100	1200000
0.33	239200	1.2	4386	3/V18ML4	—	BE160M4	BX160MB4	—	—	—	—	438600	495300	200000
0.33	248900	1.4	4457	3/V19L4	—	BE160M4	BX160MB4	—	—	—	—	534200	588100	200000
0.36	223300	1.7	4095	3/V19L4	—	BE160M4	BX160MB4	—	—	—	—	527700	581100	200000
0.39	208700	2.2	3780	3/V21L4	—	BE160M4	BX160MB4	—	—	—	—	738000	878500	1200000
0.40	201600	1.5	3696	3/V18ML4	—	BE160M4	BX160MB4	—	—	—	—	428000	483300	200000
0.41	203400	2.6	3600	3/V21L4	—	BE160M4	BX160MB4	—	—	—	—	732900	872400	1200000
0.42	190600	1.6	3495	3/V18ML4	—	BE160M4	BX160MB4	—	—	—	—	424600	479400	200000
0.45	180500	2.0	3231	3/V19L4	—	BE160M4	BX160MB4	—	—	—	—	510200	561700	200000
0.46	172800	1.1	3168	3/V17ML4	—	BE160M4	BX160MB4	—	—	—	—	440100	467600	150000
0.50	160600	1.7	2945	3/V18ML4	—	BE160M4	BX160MB4	—	—	—	—	414400	467900	200000
0.53	142100	1.2	2773	3/V17ML4	—	BE160M4	BX160MB4	—	—	—	—	431800	458800	150000
0.57	144200	2.5	2582	3/V19L4	—	BE160M4	BX160MB4	—	—	—	—	494100	544000	200000
0.59	137600	2.2	2464	3/V18ML4	—	BE160M4	BX160MB4	—	—	—	—	403900	456100	200000
0.63	129300	1.0	2343	3/V16ML4	—	BE160M4	BX160MB4	—	—	—	—	270900	303900	150000
0.64	125200	1.7	2295	3/V18ML4	—	BE160M4	BX160MB4	—	—	—	—	399900	451500	200000
0.71	119400	1.5	2065	3/V17ML4	—	BE160M4	BX160MB4	—	—	—	—	414000	439800	150000
0.73	98600	0.9	1994	3/V15ML3	—	BE160M4	BX160MB4	—	—	—	—	173000	207500	90000
0.76	106000	1.1	1920	3/V16ML4	—	BE160M4	BX160MB4	—	—	—	—	263300	295400	150000
0.79	106900	2.8	1848	3/V18ML4	—	BE160M4	BX160MB4	—	—	—	—	387700	437700	200000
0.82	98500	1.1	1785	3/V16ML4	—	BE160M4	BX160MB4	—	—	—	—	260600	292400	150000
0.82	99400	1.9	1780	3/V17ML4	—	BE160M4	BX160MB4	—	—	—	—	405300	430600	150000
0.84	101100	2.9	1748	3/V18ML4	—	BE160M4	BX160MB4	—	—	—	—	384600	434200	200000
0.88	85600	1.1	1662	3/V15ML3	—	BE160M4	BX160MB4	—	—	—	—	168600	202200	90000
0.92	81800	1.4	1589	3/V16ML3	—	BE160M4	BX160MB4	—	—	—	—	256300	287500	150000
0.99	85200	3.0	1473	3/V18ML4	—	BE160M4	BX160MB4	—	—	—	—	375300	423800	198800
1.0	72100	1.2	1400	3/V15ML3	—	BE160M4	BX160MB4	—	—	—	—	164500	197300	88000
1.1	70200	1.3	1329	3/V15ML3	—	BE160M4	BX160MB4	—	—	—	—	163300	195800	86400
1.1	68200	1.6	1324	3/V16ML3	—	BE160M4	BX160MB4	—	—	—	—	249700	280100	143900
1.1	73100	2.1	1365	3/V17ML3	—	BE160M4	BX160MB4	—	—	—	—	390300	414600	145400
1.2	69100	2.1	1215	3/V17ML3	—	BE160M4	BX160MB4	—	—	—	—	383800	407800	139800
1.3	59200	1.5	1120	3/V15ML3	—	BE160M4	BX160MB4	—	—	—	—	159300	191100	81600
1.3	60700	2.1	1134	3/V17ML3	—	BE160M4	BX160MB4	—	—	—	—	380100	403800	136600
1.4	56700	2.1	1059	3/V16ML3	—	BE160M4	BX160MB4	—	—	—	—	241900	271300	133600
1.4	58300	2.2	1024	3/V17ML3	—	BE160M4	BX160MB4	—	—	—	—	374500	397900	132100
1.5	56700	0.9	1009	3/V13ML3	—	BE160M4	BX160MB4	—	—	—	—	168900	197900	70100
1.5	56100	1.1	997	3/V14ML3	—	BE160M4	BX160MB4	—	—	—	—	156700	187900	78500
1.5	56100	1.6	997	3/V15ML3	—	BE160M4	BX160MB4	—	—	—	—	156700	187900	78500
1.6	47200	1.2	893	3/V14ML3	—	BE160M4	BX160MB4	—	—	—	—	154200	185000	75700
1.6	47800	2.1	893	3/V16ML3	—	BE160M4	BX160MB4	—	—	—	—	236000	264800	126200
1.7	46000	1.2	870	3/V13ML3	—	BE160M4	BX160MB4	—	—	—	—	165300	193700	66700
1.7	47200	1.7	840	3/V15ML3	—	BE160M4	BX160MB4	—	—	—	—	152900	183400	74200
1.7	48400	2.2	851	3/V17ML3	—	BE160M4	BX160MB4	—	—	—	—	364700	387500	124200
1.8	46500	0.9	827	3/V11ML3	—	BE160M4	BX160MB4	—	—	—	—	113300	115600	53300
1.8	44600	1.1	794	3/V14ML3	—	BE160M4	BX160MB4	—	—	—	—	151700	181900	72800
1.8	45200	2.2	794	3/V16ML3	—	BE160M4	BX160MB4	—	—	—	—	232200	260400	121400
1.8	47200	2.9	810	3/V17ML3	—	BE160M4	BX160MB4	—	—	—	—	362200	384800	122100
2.0	38000	1.1	720	3/V11ML3	—	BE160M4	BX160MB4	—	—	—	—	111100	113300	50900
2.0	39200	1.2	741	3/V13ML3	—	BE160M4	BX160MB4	—	—	—	—	161600	189300	63200
2.1	36700	1.2	695	3/V14ML3	—	BE160M4	BX160MB4	—	—	—	—	148800	178500	69700
2.2	38800	1.3	673	3/V13ML3	—	BE160M4	BX160MB4	—	—	—	—	159400	186800	61200
2.2	38300	1.8	665	3/V14ML3	—	BE160M4	BX160MB4	—	—	—	—	147900	177300	68600
2.2	38300	2.2	665	3/V15ML3	—	BE160M4	BX160MB4	—	—	—	—	147900	177300	68600
2.2	38100	2.2	669	3/V16ML3	—	BE160M4	BX160MB4	—	—	—	—	226500	254100	114600
2.3	36200	1.1	644	3/V11ML3	—	BE160M4	BX160MB4	—	—	—	—	109300	111500	49000
2.5	34500	1.6	579	3/V14ML3	—	BE160M4	BX160MB4	—	—	—	—	145000	173900	65500
2.6	32600	1.5	567	3/V13ML3	—	BE160M4	BX160MB4	—	—	—	—	155500	182200	57800
2.6	32200	2.5	560	3/V15ML3	—	BE160M4	BX160MB4	—	—	—	—	144300	173100	64800
2.7	31700	1.3	551	3/V11ML3	—	BE160M4	BX160MB4	—	—	—	—	106900	109100	46600
2.8	29700	1.6	516	3/V13ML3	—	BE160M4	BX160MB4	—	—	—	—	153500	179800	56100
2.9	29400	1.1	510	3/V11ML3	—	BE160M4	BX160MB4	—	—	—	—	105700	107900	45400
2.9	29700	1.9	498	3/V14ML3	—	BE160M4	BX160MB4	—	—	—	—	141900	170200	62300



A

P_1 = 11 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
min^{-1}	Nm													
2.9	29700	2.8	498	**3/V15ML3**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	141900	170200	62300
3.3	25700	1.9	446	**3/V14ML3**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	139700	167500	60100
3.3	25700	2.5	446	**3/V15ML3**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	139700	167500	60100
3.4	24800	1.1	436	**3/V10ML3**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	82300	104300	43100
3.4	24800	1.6	430	**3/V11ML3**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	103200	105300	42800
3.4	25300	1.8	425	**3/V13ML3**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	149300	174900	52600
3.7	23700	1.9	397	**3/V14ML3**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	137400	164800	57800
3.8	23300	2.7	386	**3/V15ML3**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	136900	164100	57300
4.0	21300	1.9	370	**3/V13ML3**	**—**	**BE160M4**	**BX160MB4**	**—**	**—**	—	—	146300	171500	50200
8.1	11800	0.9	180	**—**	**3/A07L2**	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	30000	37500	67500	88800	22200
10.5	9190	1.2	140	**—**	**3/A07L2**	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	29300	36700	66200	87000	20400
11.3	8530	1.3	130	**—**	**3/A07L2**	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	28600	35700	64600	85000	19900
13.4	7160	1.2	109	**—**	**3/A07L2**	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	26900	33700	61300	80600	18800
16.6	5930	1.0	88.5	**—**	**3/A06L2**	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	21000	23900	48700	56200	13600
16.7	5880	1.7	87.7	**—**	**3/A07L2**	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	25100	31400	57500	75600	17500
18.0	5440	1.2	81.2	**—**	**3/A06L2**	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	20400	23200	47400	54700	13200
21.0	4690	1.2	69.9	**—**	**3/A06L2**	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	19400	22100	45300	52300	12600
21.4	4580	1.7	68.3	**—**	**3/A07L2**	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	23100	28900	53300	70100	16100
24.4	4030	1.5	60.1	**—**	**3/A06L2**	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	18400	21000	43300	50000	12000
25.6	3840	1.7	57.3	**—**	**3/A07L2**	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	21800	27200	50600	66500	15200
26.3	3730	1.2	55.7	**—**	**3/A06L2**	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	18000	20500	42300	48900	11700
28.3	3470	1.5	51.7	**—**	**3/A06L2**	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	17500	20000	41400	47800	11400
29.8	3300	2.5	49.2	**—**	**3/A07L2**	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	20700	25900	48300	63600	14400
31	3160	1.2	47.2	**—**	**3/A06L2**	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	17000	19400	40300	46500	11000
36	2760	1.8	41.1	**—**	**3/A06L2**	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	16200	18500	38600	44600	10500
42	2340	1.5	34.9	**—**	**3/A06L2**	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	15400	17500	36800	42500	9990
45	2190	1.8	32.7	**—**	**3/A06L2**	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	15000	17200	36100	41700	9780
53	1860	1.8	27.7	**—**	**3/A06L2**	**BE160M4**	**BX160MB4**	**ME5SA4**	**MX5SB4**	14200	16200	34300	39600	9250

P_1 = 15 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
min^{-1}	Nm													
0.28	360300	1.1	5164	**3/V19L4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	545500	600600	200000
0.29	356100	1.6	5040	**3/V21L4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	769000	915300	1200000
0.32	341800	1.6	4550	**3/V21L4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	757800	902100	1200000
0.33	325600	0.9	4386	**3/V18ML4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	438600	495300	200000
0.33	338800	1.0	4457	**3/V19L4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	534200	588100	200000
0.36	304000	1.3	4095	**3/V19L4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	527700	581100	200000
0.39	284000	1.6	3780	**3/V21L4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	738000	878500	1200000
0.40	274400	1.1	3696	**3/V18ML4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	428000	483300	200000
0.41	276900	1.9	3600	**3/V21L4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	732900	872400	1200000
0.42	259500	1.1	3495	**3/V18ML4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	424600	479400	200000
0.45	245600	1.5	3231	**3/V19L4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	510200	561700	200000
0.50	218600	1.3	2945	**3/V18ML4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	414400	467900	200000
0.54	212500	2.5	2700	**3/V21L4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	703400	837300	1200000
0.57	196300	1.9	2582	**3/V19L4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	494100	544000	200000
0.58	193800	2.6	2520	**3/V21L4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	696500	829000	1200000
0.59	187300	1.6	2464	**3/V18ML4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	403900	456100	200000
0.64	170400	1.2	2295	**3/V18ML4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	399900	451500	200000
0.71	162500	1.1	2065	**3/V17ML4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	414000	439800	150000
0.79	145500	2.0	1848	**3/V18ML4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	387700	437700	200000
0.82	135300	1.4	1780	**3/V17ML4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	405300	430600	150000
0.84	137600	2.2	1748	**3/V18ML4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	384600	434200	200000
0.92	111400	1.0	1589	**3/V16ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	256300	287500	150000
0.99	115900	2.2	1473	**3/V18ML4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	375300	423800	198800
1.1	95600	0.9	1329	**3/V15ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	163300	195800	86400
1.1	92800	1.2	1324	**3/V16ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	249700	280100	143900
1.1	99400	1.5	1365	**3/V17ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	390300	414600	145400
1.2	94100	1.5	1215	**3/V17ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	383800	407800	139800
1.2	98100	2.9	1232	**3/V18ML4**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	365900	413100	187300
1.3	80600	1.1	1120	**3/V15ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	159300	191100	81600



A

P_1 = 15 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
min^{-1}	Nm													
1.3	82600	1.5	1134	**3/V17ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	380100	403800	136600
1.4	77100	1.5	1059	**3/V16ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	241900	271300	133600
1.4	79300	1.6	1024	**3/V17ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	374500	397900	132100
1.5	76300	1.2	997	**3/V15ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	156700	187900	78500
1.6	65100	1.5	893	**3/V16ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	236000	264800	126200
1.7	64300	1.3	840	**3/V15ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	152900	183400	74200
1.7	65900	1.6	851	**3/V17ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	364700	387500	124200
1.8	61500	1.6	794	**3/V16ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	232200	260400	121400
1.8	64200	2.1	810	**3/V17ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	362200	384800	122100
2.1	54200	2.6	683	**3/V17ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	353500	375500	115400
2.2	52700	0.9	673	**3/V13ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	159400	186800	61200
2.2	52100	1.3	665	**3/V14ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	147900	177300	68600
2.2	52100	1.6	665	**3/V15ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	147900	177300	68600
2.2	51800	1.6	669	**3/V16ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	226500	254100	114600
2.4	49300	2.6	608	**3/V17ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	347600	369300	111000
2.5	47000	1.1	579	**3/V14ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	145000	173900	65500
2.6	44400	1.1	567	**3/V13ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	155500	182200	57800
2.6	43900	1.9	560	**3/V15ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	144300	173100	64800
2.6	45000	2.6	567	**3/V17ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	344200	365700	108500
2.7	43200	0.9	551	**3/V11ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	106900	109100	46600
2.8	40400	1.2	516	**3/V13ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	153500	179800	56100
2.8	42000	2.6	530	**3/V16ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	219100	245800	106000
2.9	40400	1.4	498	**3/V14ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	141900	170200	62300
2.9	40400	2.0	498	**3/V15ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	141900	170200	62300
3.3	35000	1.4	446	**3/V14ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	139700	167500	60100
3.3	35000	1.9	446	**3/V15ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	139700	167500	60100
3.3	35400	2.6	446	**3/V16ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	213800	239800	100100
3.4	33700	1.2	430	**3/V11ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	103200	105300	42800
3.4	34500	1.3	425	**3/V13ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	149300	174900	52600
3.7	32200	1.4	397	**3/V14ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	137400	164800	57800
3.8	31700	2.0	386	**3/V15ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	136900	164100	57300
4.0	29000	1.4	370	**3/V13ML3**	**—**	**BE160L4**	**BX160L4**	**—**	**—**	—	—	146300	171500	50200
11.3	11600	1.0	130	**—**	**3/A07L2**	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	28600	35700	64600	85000	19900
13.4	9740	0.9	109	**—**	**3/A07L2**	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	26900	33700	61300	80600	18800
16.7	8000	1.3	87.7	**—**	**3/A07L2**	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	25100	31400	57500	75600	17500
21.4	6230	1.3	68.3	**—**	**3/A07L2**	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	23100	28900	53300	70100	16100
24.4	5480	1.1	60.1	**—**	**3/A06L2**	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	18400	21000	43300	50000	12000
25.6	5230	1.3	57.3	**—**	**3/A07L2**	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	21800	27200	50600	66500	15200
28.3	4720	1.1	51.7	**—**	**3/A06L2**	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	17500	20000	41400	47800	11400
29.8	4490	1.9	49.2	**—**	**3/A07L2**	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	20700	25900	48300	63600	14400
35	3790	2.5	41.5	**—**	**3/A07L2**	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	19500	24400	45900	60400	13600
36	3750	1.3	41.1	**—**	**3/A06L2**	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	16200	18500	38600	44600	10500
42	3180	1.1	34.9	**—**	**3/A06L2**	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	15400	17500	36800	42500	9990
45	2980	1.3	32.7	**—**	**3/A06L2**	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	15000	17200	36100	41700	9780
45	2950	2.7	32.3	**—**	**3/A07L2**	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	18000	22500	42600	56000	12500
53	2530	1.3	27.7	**—**	**3/A06L2**	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	14200	16200	34300	39600	9250
54	2470	2.7	27.1	**—**	**3/A07L2**	**BE160L4**	**BX160L4**	**ME5LA4**	**MX5LA4**	17000	21200	40400	53100	11800

P_1 = 18.5 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
min^{-1}	Nm													
0.28	444800	0.9	5164	**3/V19L4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	545500	600600	200000
0.29	439700	1.3	5040	**3/V21L4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	769000	915300	1200000
0.32	422100	1.3	4550	**3/V21L4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	757800	902100	1200000
0.36	375300	1.0	4095	**3/V19L4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	527700	581100	200000
0.39	350600	1.3	3780	**3/V21L4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	738000	878500	1200000
0.41	341900	1.6	3600	**3/V21L4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	732900	872400	1200000
0.42	320400	0.9	3495	**3/V18ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	424600	479400	200000
0.45	303300	1.2	3231	**3/V19L4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	510200	561700	200000
0.50	269900	1.0	2945	**3/V18ML4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	414400	467900	200000
0.54	262400	2.0	2700	**3/V21L4**	**—**	**BE180M4**	**BX180M4**	**—**	**—**	—	—	703400	837300	1200000



P_1 = 18.5 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
min^{-1}	Nm													
0.57	242400	1.5	2582	3/V19L4	—	BE180M4	BX180M4	—	—	—	—	494100	544000	200000
0.58	239300	2.1	2520	3/V21L4	—	BE180M4	BX180M4	—	—	—	—	696500	829000	1200000
0.59	231300	1.3	2464	3/V18ML4	—	BE180M4	BX180M4	—	—	—	—	403900	456100	200000
0.64	210400	1.0	2295	3/V18ML4	—	BE180M4	BX180M4	—	—	—	—	399900	451500	200000
0.64	221100	2.5	2275	3/V21L4	—	BE180M4	BX180M4	—	—	—	—	686400	817000	1200000
0.78	183700	2.5	1890	3/V21L4	—	BE180M4	BX180M4	—	—	—	—	668500	795700	1200000
0.79	179600	1.7	1848	3/V18ML4	—	BE180M4	BX180M4	—	—	—	—	387700	437700	200000
0.81	178900	3.0	1800	3/V21L4	—	BE180M4	BX180M4	—	—	—	—	663800	790100	1200000
0.82	167100	1.1	1780	3/V17ML4	—	BE180M4	BX180M4	—	—	—	—	405300	430600	150000
0.84	169900	1.8	1748	3/V18ML4	—	BE180M4	BX180M4	—	—	—	—	384600	434200	200000
0.99	143100	1.8	1473	3/V18ML4	—	BE180M4	BX180M4	—	—	—	—	375300	423800	198800
1.1	114600	1.0	1324	3/V16ML3	—	BE180M4	BX180M4	—	—	—	—	249700	280100	143900
1.1	122800	1.3	1365	3/V17ML3	—	BE180M4	BX180M4	—	—	—	—	390300	414600	145400
1.2	116200	1.2	1215	3/V17ML3	—	BE180M4	BX180M4	—	—	—	—	383800	407800	139800
1.2	121100	2.4	1232	3/V18ML4	—	BE180M4	BX180M4	—	—	—	—	365900	413100	187300
1.3	102000	1.3	1134	3/V17ML3	—	BE180M4	BX180M4	—	—	—	—	380100	403800	136600
1.3	114500	2.5	1165	3/V18ML4	—	BE180M4	BX180M4	—	—	—	—	363000	409800	183800
1.4	95200	1.2	1059	3/V16ML3	—	BE180M4	BX180M4	—	—	—	—	241900	271300	133600
1.4	97900	1.3	1024	3/V17ML3	—	BE180M4	BX180M4	—	—	—	—	374500	397900	132100
1.5	94200	0.9	997	3/V15ML3	—	BE180M4	BX180M4	—	—	—	—	156700	187900	78500
1.5	96500	2.5	982	3/V18ML4	—	BE180M4	BX180M4	—	—	—	—	354200	399900	173600
1.6	80300	1.3	893	3/V16ML3	—	BE180M4	BX180M4	—	—	—	—	236000	264800	126200
1.7	79400	1.0	840	3/V15ML3	—	BE180M4	BX180M4	—	—	—	—	152900	183400	74200
1.7	81400	1.3	851	3/V17ML3	—	BE180M4	BX180M4	—	—	—	—	364700	387500	124200
1.8	75900	1.3	794	3/V16ML3	—	BE180M4	BX180M4	—	—	—	—	232200	260400	121400
1.8	79300	1.7	810	3/V17ML3	—	BE180M4	BX180M4	—	—	—	—	362200	384800	122100
1.9	75200	2.5	765	3/V18ML4	—	BE180M4	BX180M4	—	—	—	—	341800	385900	159800
2.1	66900	2.1	683	3/V17ML3	—	BE180M4	BX180M4	—	—	—	—	353500	375500	115400
2.2	64400	1.1	665	3/V14ML3	—	BE180M4	BX180M4	—	—	—	—	147900	177300	68600
2.2	64400	1.3	665	3/V15ML3	—	BE180M4	BX180M4	—	—	—	—	147900	177300	68600
2.2	64000	1.3	669	3/V16ML3	—	BE180M4	BX180M4	—	—	—	—	226500	254100	114600
2.4	60900	2.1	608	3/V17ML3	—	BE180M4	BX180M4	—	—	—	—	347600	369300	111000
2.5	58000	0.9	579	3/V14ML3	—	BE180M4	BX180M4	—	—	—	—	145000	173900	65500
2.6	54200	1.5	560	3/V15ML3	—	BE180M4	BX180M4	—	—	—	—	144300	173100	64800
2.6	55500	2.1	567	3/V17ML3	—	BE180M4	BX180M4	—	—	—	—	344200	365700	108500
2.8	49900	1.0	516	3/V13ML3	—	BE180M4	BX180M4	—	—	—	—	153500	179800	56100
2.8	51900	2.1	530	3/V16ML3	—	BE180M4	BX180M4	—	—	—	—	219100	245800	106000
2.9	49900	1.2	498	3/V14ML3	—	BE180M4	BX180M4	—	—	—	—	141900	170200	62300
2.9	49900	1.7	498	3/V15ML3	—	BE180M4	BX180M4	—	—	—	—	141900	170200	62300
2.9	51300	2.5	512	3/V17ML3	—	BE180M4	BX180M4	—	—	—	—	339200	360400	104800
3.3	43200	1.1	446	3/V14ML3	—	BE180M4	BX180M4	—	—	—	—	139700	167500	60100
3.3	43200	1.5	446	3/V15ML3	—	BE180M4	BX180M4	—	—	—	—	139700	167500	60100
3.3	43700	2.1	446	3/V16ML3	—	BE180M4	BX180M4	—	—	—	—	213800	239800	100100
3.4	41600	0.9	430	3/V11ML3	—	BE180M4	BX180M4	—	—	—	—	103200	105300	42800
3.4	42600	1.1	425	3/V13ML3	—	BE180M4	BX180M4	—	—	—	—	149300	174900	52600
3.4	42600	2.5	425	3/V17ML3	—	BE180M4	BX180M4	—	—	—	—	330400	351000	98500
3.6	41500	2.9	405	3/V17ML3	—	BE180M4	BX180M4	—	—	—	—	328100	348500	96900
3.7	39800	1.2	397	3/V14ML3	—	BE180M4	BX180M4	—	—	—	—	137400	164800	57800
3.7	39800	2.5	397	3/V16ML3	—	BE180M4	BX180M4	—	—	—	—	210300	235900	96300
3.8	39100	1.6	386	3/V15ML3	—	BE180M4	BX180M4	—	—	—	—	136900	164100	57300
4.0	35800	1.1	370	3/V13ML3	—	BE180M4	BX180M4	—	—	—	—	146300	171500	50200
16.7	9880	1.0	87.7	—	3/A07L2	BE180M4	BX180M4	—	—	25100	31400	57500	75600	17500
21.4	7700	1.0	68.3	—	3/A07L2	BE180M4	BX180M4	—	—	23100	28900	53300	70100	16100
25.6	6460	1.0	57.3	—	3/A07L2	BE180M4	BX180M4	—	—	21800	27200	50600	66500	15200
29.8	5540	1.5	49.2	—	3/A07L2	BE180M4	BX180M4	—	—	20700	25900	48300	63600	14400
35	4680	2.1	41.5	—	3/A07L2	BE180M4	BX180M4	—	—	19500	24400	45900	60400	13600
36	4630	1.1	41.1	—	3/A06L2	BE180M4	BX180M4	—	—	16200	18500	38600	44600	10500
45	3680	1.1	32.7	—	3/A06L2	BE180M4	BX180M4	—	—	15000	17200	36100	41700	9780
45	3640	2.2	32.3	—	3/A07L2	BE180M4	BX180M4	—	—	18000	22500	42600	56000	12500
53	3120	1.1	27.7	—	3/A06L2	BE180M4	BX180M4	—	—	14200	16200	34300	39600	9250
54	3050	2.2	27.1	—	3/A07L2	BE180M4	BX180M4	—	—	17000	21200	40400	53100	11800



P_1 = 22 kW

n_2	M_2	S	i			IE2	IE3	IE2	IE3	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
min^{-1}	Nm													
0.29	519600	1.1	5040	**3/V21L4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	769000	915300	1200000
0.32	498800	1.1	4550	**3/V21L4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	757800	902100	1200000
0.39	414400	1.1	3780	**3/V21L4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	738000	878500	1200000
0.41	404100	1.3	3600	**3/V21L4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	732900	872400	1200000
0.45	358400	1.0	3231	**3/V19L4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	510200	561700	200000
0.54	310100	1.7	2700	**3/V21L4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	703400	837300	1200000
0.57	286400	1.3	2582	**3/V19L4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	494100	544000	200000
0.58	282800	1.8	2520	**3/V21L4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	696500	829000	1200000
0.59	273300	1.1	2464	**3/V18ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	403900	456100	200000
0.64	261300	2.1	2275	**3/V21L4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	686400	817000	1200000
0.78	217100	2.1	1890	**3/V21L4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	668500	795700	1200000
0.79	212200	1.4	1848	**3/V18ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	387700	437700	200000
0.81	211400	2.5	1800	**3/V21L4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	663800	790100	1200000
0.82	197500	0.9	1780	**3/V17ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	405300	430600	150000
0.84	200800	1.5	1748	**3/V18ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	384600	434200	200000
0.97	178200	2.9	1517	**3/V21L4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	647800	771000	1200000
0.99	169200	1.5	1473	**3/V18ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	375300	423800	198800
1.1	145100	1.1	1365	**3/V17ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	390300	414600	145400
1.2	137300	1.1	1215	**3/V17ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	383800	407800	139800
1.2	143100	2.0	1232	**3/V18ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	365900	413100	187300
1.2	148000	2.9	1260	**3/V21L4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	630800	750900	1138800
1.3	120500	1.1	1134	**3/V17ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	380100	403800	136600
1.3	135300	2.1	1165	**3/V18ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	363000	409800	183800
1.4	112600	1.0	1059	**3/V16ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	241900	271300	133600
1.4	115700	1.1	1024	**3/V17ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	374500	397900	132100
1.5	114100	2.1	982	**3/V18ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	354200	399900	173600
1.6	94900	1.1	893	**3/V16ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	236000	264800	126200
1.7	96200	1.1	851	**3/V17ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	364700	387500	124200
1.8	89700	1.1	794	**3/V16ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	232200	260400	121400
1.8	93700	1.4	810	**3/V17ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	362200	384800	122100
1.9	88900	2.1	765	**3/V18ML4**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	341800	385900	159800
2.1	79000	1.8	683	**3/V17ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	353500	375500	115400
2.2	76100	1.1	665	**3/V15ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	147900	177300	68600
2.2	75600	1.1	669	**3/V16ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	226500	254100	114600
2.4	72000	1.8	608	**3/V17ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	347600	369300	111000
2.6	64000	1.3	560	**3/V15ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	144300	173100	64800
2.6	65600	1.8	567	**3/V17ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	344200	365700	108500
2.8	61300	1.8	530	**3/V16ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	219100	245800	106000
2.9	59000	1.0	498	**3/V14ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	141900	170200	62300
2.9	59000	1.4	498	**3/V15ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	141900	170200	62300
2.9	60600	2.1	512	**3/V17ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	339200	360400	104800
3.3	51000	0.9	446	**3/V14ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	139700	167500	60100
3.3	51000	1.3	446	**3/V15ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	139700	167500	60100
3.3	51600	1.8	446	**3/V16ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	213800	239800	100100
3.4	50300	0.9	425	**3/V13ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	149300	174900	52600
3.4	50300	2.1	425	**3/V17ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	330400	351000	98500
3.6	49000	2.4	405	**3/V17ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	328100	348500	96900
3.7	47000	1.0	397	**3/V14ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	137400	164800	57800
3.7	47000	2.1	397	**3/V16ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	210300	235900	96300
3.8	46200	1.4	386	**3/V15ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	136900	164100	57300
4.0	42300	0.9	370	**3/V13ML3**	**—**	**BE180L4**	**BX180L4**	**—**	**—**	—	—	146300	171500	50200
29.8	6550	1.3	49.2	**—**	**3/A07L2**	**BE180L4**	**BX180L4**	**—**	**—**	20700	25900	48300	63600	14400
35	5530	1.7	41.5	**—**	**3/A07L2**	**BE180L4**	**BX180L4**	**—**	**—**	19500	24400	45900	60400	13600
45	4350	0.9	32.7	**—**	**3/A06L2**	**BE180L4**	**BX180L4**	**—**	**—**	15000	17200	36100	41700	9780
45	4300	1.8	32.3	**—**	**3/A07L2**	**BE180L4**	**BX180L4**	**—**	**—**	18000	22500	42600	56000	12500
53	3690	0.9	27.7	**—**	**3/A06L2**	**BE180L4**	**BX180L4**	**—**	**—**	14200	16200	34300	39600	9250
54	3610	1.8	27.1	**—**	**3/A07L2**	**BE180L4**	**BX180L4**	**—**	**—**	17000	21200	40400	53100	11800

25.3 RATING CHARTS FOR INLINE UNITS 300M L

Reading the rating chart.



The rated torque of the gearbox, independent of installed mechanical power

1	Reference torque
2	Gearbox drive speed
3	Frame size of the in-line gear unit
4	Gear ratio
5	Gearbox output speed
6	Gearbox rated output torque based on: - service factor f_S=1 - 10000 h theoretical lifetime
7	Gearbox rated input power, based on: - service factor f_S=1 - 10000 h theoretical lifetime
8	Frame size of available IEC motor
9	Permitted overhung loading on output shaft, based on: - service factor f_S=1 - 10000 h theoretical lifetime - speed of output n_2 For forces not applied at shaft middlepoint, see diagrams provided in the specific gearbox overall dimensioning pages
10	Maximum torque
11	Dimensions page



300 L

262

1250 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ	$M_{2\,max}$ Nm
1500	**300L1**	**3.48**	431	470	20.0	71 ... 132	1850	1850	6950	8080	1060	2000
	300L1	**4.26**	352	490	18.8	71 ... 132	1980	1980	7390	8590	1130	2400
	300L1	**5.77**	260	470	13.3	71 ... 132	2190	2190	8090	9410	1250	2400
	300L1	**7.20**	208	410	9.2	71 ... 132	2360	2360	8650	10100	1350	2400
	300L1	**9.00**	167	320	5.7	71 ... 132	2540	2540	9240	10700	1450	2400
	300L2	**12.1**	124	680	9.4	71 ... 132	2810	2810	10100	11800	1600	2000
	300L2	**14.8**	101	720	8.1	71 ... 132	3010	3010	10700	12500	1720	2000
	300L2	**18.2**	83	750	6.9	71 ... 132	3220	3220	11400	13300	1840	2400
	300L2	**20.1**	75	640	5.3	71 ... 132	3320	3320	11800	13700	1900	2000
	300L2	**24.6**	61	800	5.5	71 ... 132	3560	3560	12500	14500	2030	2400
	300L2	**30.7**	49	840	4.6	71 ... 132	3830	3830	13400	15500	2190	2400
	300L2	**33.3**	45	650	3.3	71 ... 132	3940	3940	13700	15900	2250	2400
	300L2	**38.4**	39	840	3.7	71 ... 132	4130	4130	14300	16600	2360	2400
	300L2	**41.5**	36	650	2.6	71 ... 132	4240	4240	14600	17000	2420	2400
	300L2	**51.9**	28.9	650	2.1	71 ... 132	4560	4560	15600	18200	2610	2400
	300L2	**64.8**	23.1	550	1.4	71 ... 132	4910	4910	16700	19400	2810	2400
	300L3	**51.6**	29.1	850	2.8	71 ... 132	4560	4560	15600	18200	2600	2000
	300L3	**63.2**	23.7	850	2.3	71 ... 132	4870	4870	16600	19300	2780	2400
	300L3	**69.9**	21.5	650	1.6	71 ... 132	5040	5040	17100	19900	2880	2000
	300L3	**77.5**	19.4	850	1.9	71 ... 132	5220	5220	17600	20500	2980	2400
	300L3	**85.6**	17.5	850	1.7	71 ... 132	5390	5390	18200	21100	3080	2400
	300L3	**105**	14.3	860	1.4	71 ... 132	5770	5770	19300	22500	3300	2400
	300L3	**116**	13.0	650	0.97	71 ... 132	5960	5960	19900	23100	3410	2400
	300L3	**131**	11.5	860	1.1	71 ... 132	6210	6210	20600	24000	3550	2400
	300L3	**142**	10.6	860	1.0	71 ... 132	6380	6380	21100	24600	3650	2400
	300L3	**177**	8.5	880	0.86	71 ... 132	6500	6500	21500	25000	3920	2400
	300L3	**192**	7.8	650	0.58	71 ... 132	6500	6500	21500	25000	4030	2400
	300L3	**221**	6.8	910	0.71	71 ... 132	6500	6500	21500	25000	4230	2400
	300L3	**240**	6.3	650	0.47	71 ... 132	6500	6500	21500	25000	4340	2400
	300L3	**299**	5.0	650	0.37	71 ... 132	6500	6500	21500	25000	4670	2400
	300L3	**374**	4.0	670	0.31	71 ... 132	6710	6710	22200	25800	5030	2400
	300L4	**330**	4.5	970	0.52	71 ... 132	6590	6590	21800	25300	4830	2400
	300L4	**403**	3.7	680	0.30	71 ... 132	6780	6780	22400	26100	5160	2400
	300L4	**447**	3.4	1020	0.40	71 ... 132	6880	6880	22800	26500	5340	2400
	300L4	**494**	3.0	1030	0.37	71 ... 132	6980	6980	23100	26800	5520	2400
	300L4	**558**	2.7	1060	0.34	71 ... 132	7100	7100	23500	27300	5750	2400
	300L4	**616**	2.4	1070	0.31	71 ... 132	7200	7200	23800	27700	5950	2400
	300L4	**755**	2.0	1110	0.26	71 ... 132	7420	7420	24500	28500	6360	2400
	300L4	**819**	1.8	1130	0.24	71 ... 132	7500	7500	24800	28900	6540	2400
	300L4	**942**	1.6	1160	0.22	71 ... 132	7650	7650	25300	29400	6850	2400
	300L4	**1022**	1.5	1170	0.20	71 ... 132	7740	7740	25600	29800	7040	2400
	300L4	**1108**	1.4	810	0.13	71 ... 132	7830	7830	25900	30100	7230	2400
	300L4	**1275**	1.2	1220	0.17	71 ... 132	7990	7990	26400	30700	7580	2400
	300L4	**1383**	1.1	850	0.11	71 ... 132	8090	8090	26700	31100	7790	2400
	300L4	**1591**	0.94	1250	0.14	71 ... 132	8250	8250	27300	31700	8000	2400
	300L4	**1725**	0.87	860	0.09	71 ... 132	8350	8350	27600	32100	8000	2400
	300L4	**2153**	0.70	860	0.07	71 ... 132	8610	8610	28500	33100	8000	2400
	300L4	**2692**	0.56	1000	0.07	71 ... 132	8890	8890	29400	34000	8000	2400
1000	**300L1**	**3.48**	287	530	16.5	71 ... 132	2120	2120	7850	9130	1210	2000
	300L1	**4.26**	235	560	14.1	71 ... 132	2270	2270	8340	9700	1300	2400
	300L1	**5.77**	173	530	10.0	71 ... 132	2510	2510	9140	10600	1430	2400
	300L1	**7.20**	139	460	6.9	71 ... 132	2700	2700	9760	11400	1540	2400
	300L1	**9.00**	111	360	4.3	71 ... 132	2910	2910	10400	12100	1660	2400
	300L2	**12.1**	83	730	6.7	71 ... 132	3220	3220	11400	13300	1840	2000
	300L2	**14.8**	67	790	5.9	71 ... 132	3440	3440	12100	14100	1970	2000
	300L2	**18.2**	55	820	5.0	71 ... 132	3680	3680	12900	15000	2100	2400
	300L2	**20.1**	50	650	3.6	71 ... 132	3810	3810	13300	15400	2170	2000
	300L2	**24.6**	41	840	3.8	71 ... 132	4070	4070	14100	16400	2330	2400
	300L2	**30.7**	33	850	3.1	71 ... 132	4380	4380	15100	17500	2500	2400
	300L2	**33.3**	30	650	2.2	71 ... 132	4500	4500	15500	18000	2570	2400
	300L2	**38.4**	26.1	850	2.5	71 ... 132	4720	4720	16100	18800	2700	2400

B



300 L

262

1250 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ	$M_{2\,max}$ Nm
1000	**300L2**	**41.5**	24.1	650	1.7	71 ... 132	4850	4850	16500	19200	2770	2400
	300L2	**51.9**	19.3	650	1.4	71 ... 132	5220	5220	17700	20500	2980	2400
	300L2	**64.8**	15.4	550	0.94	71 ... 132	5620	5620	18900	21900	3210	2400
	300L3	**51.6**	19.4	850	1.9	71 ... 132	5210	5210	17600	20500	2980	2000
	300L3	**63.2**	15.8	850	1.5	71 ... 132	5580	5580	18700	21800	3190	2400
	300L3	**69.9**	14.3	650	1.1	71 ... 132	5770	5770	19300	22500	3290	2000
	300L3	**77.5**	12.9	860	1.3	71 ... 132	5970	5970	19900	23200	3410	2400
	300L3	**85.6**	11.7	860	1.2	71 ... 132	6170	6170	20500	23900	3530	2400
	300L3	**105**	9.5	870	0.95	71 ... 132	6500	6500	21500	25000	3770	2400
	300L3	**116**	8.6	650	0.64	71 ... 132	6500	6500	21500	25000	3900	2400
	300L3	**131**	7.6	890	0.78	71 ... 132	6500	6500	21500	25000	4060	2400
	300L3	**142**	7.0	900	0.73	71 ... 132	6500	6500	21500	25000	4170	2400
	300L3	**177**	5.6	930	0.60	71 ... 132	6500	6500	21500	25000	4490	2400
	300L3	**192**	5.2	650	0.39	71 ... 132	6500	6500	21500	25000	4620	2400
	300L3	**221**	4.5	970	0.50	71 ... 132	6590	6590	21800	25400	4840	2400
	300L3	**240**	4.2	670	0.32	71 ... 132	6670	6670	22100	25700	4970	2400
	300L3	**299**	3.3	700	0.27	71 ... 132	6880	6880	22800	26500	5350	2400
	300L3	**374**	2.7	720	0.22	71 ... 132	7110	7110	23500	27300	5760	2400
	300L4	**330**	3.0	1040	0.37	71 ... 132	6980	6980	23100	26900	5530	2400
	300L4	**403**	2.5	730	0.21	71 ... 132	7180	7180	23800	27600	5910	2400
	300L4	**447**	2.2	1090	0.29	71 ... 132	7290	7290	24100	28000	6120	2400
	300L4	**494**	2.0	1110	0.27	71 ... 132	7400	7400	24500	28400	6320	2400
	300L4	**558**	1.8	1130	0.24	71 ... 132	7530	7530	24900	28900	6590	2400
	300L4	**616**	1.6	1150	0.22	71 ... 132	7630	7630	25200	29400	6810	2400
	300L4	**755**	1.3	1190	0.19	71 ... 132	7860	7860	26000	30200	7280	2400
	300L4	**819**	1.2	1210	0.17	71 ... 132	7950	7950	26300	30600	7480	2400
	300L4	**942**	1.1	1240	0.16	71 ... 132	8110	8110	26800	31200	7840	2400
	300L4	**1022**	0.98	1250	0.14	71 ... 132	8210	8210	27100	31600	8000	2400
	300L4	**1108**	0.90	860	0.09	71 ... 132	8300	8300	27500	31900	8000	2400
	300L4	**1275**	0.78	1250	0.12	71 ... 132	8470	8470	28000	32600	8000	2400
	300L4	**1383**	0.72	860	0.07	71 ... 132	8570	8570	28300	33000	8000	2400
	300L4	**1591**	0.63	1250	0.09	71 ... 132	8740	8740	28900	33600	8000	2400
	300L4	**1725**	0.58	860	0.06	71 ... 132	8840	8840	29300	34000	8000	2400
	300L4	**2153**	0.46	860	0.05	71 ... 132	9130	9130	30200	34000	8000	2400
	300L4	**2692**	0.37	1000	0.04	71 ... 132	9420	9420	31000	34000	8000	2400
500	**300L1**	**3.48**	144	650	10.2	71 ... 132	2670	2670	9670	11200	1530	2000
	300L1	**4.26**	117	690	8.7	71 ... 132	2860	2860	10300	11900	1630	2400
	300L1	**5.77**	87	630	5.9	71 ... 132	3160	3160	11200	13100	1810	2400
	300L1	**7.20**	69	530	4.0	71 ... 132	3410	3410	12000	14000	1950	2400
	300L1	**9.00**	56	370	2.2	71 ... 132	3670	3670	12900	14900	2100	2400
	300L2	**12.1**	41	730	3.4	71 ... 132	4050	4050	14100	16300	2310	2000
	300L2	**14.8**	34	840	3.2	71 ... 132	4340	4340	14900	17400	2480	2000
	300L2	**18.2**	27.5	850	2.6	71 ... 132	4640	4640	15900	18500	2650	2400
	300L2	**20.1**	24.9	650	1.8	71 ... 132	4800	4800	16400	19000	2740	2000
	300L2	**24.6**	20.3	850	1.9	71 ... 132	5130	5130	17400	20200	2930	2400
	300L2	**30.7**	16.3	850	1.5	71 ... 132	5520	5520	18600	21600	3160	2400
	300L2	**33.3**	15.0	650	1.1	71 ... 132	5680	5680	19000	22100	3240	2400
	300L2	**38.4**	13.0	860	1.2	71 ... 132	5950	5950	19900	23100	3400	2400
	300L2	**41.5**	12.0	650	0.87	71 ... 132	6110	6110	20300	23600	3490	2400
	300L2	**51.9**	9.6	650	0.70	71 ... 132	6500	6500	21500	25000	3760	2400
	300L2	**64.8**	7.7	550	0.47	71 ... 132	6500	6500	21500	25000	4050	2400
	300L3	**51.6**	9.7	860	0.96	71 ... 132	6500	6500	21500	25000	3750	2000
	300L3	**63.2**	7.9	890	0.81	71 ... 132	6500	6500	21500	25000	4020	2400
	300L3	**69.9**	7.2	650	0.53	71 ... 132	6500	6500	21500	25000	4150	2000
	300L3	**77.5**	6.5	920	0.68	71 ... 132	6500	6500	21500	25000	4300	2400
	300L3	**85.6**	5.8	930	0.62	71 ... 132	6500	6500	21500	25000	4440	2400
	300L3	**105**	4.8	960	0.52	71 ... 132	6540	6540	21600	25200	4750	2400
	300L3	**116**	4.3	670	0.33	71 ... 132	6640	6640	22000	25500	4910	2400
	300L3	**131**	3.8	990	0.44	71 ... 132	6750	6750	22300	26000	5120	2400
	300L3	**142**	3.5	1010	0.41	71 ... 132	6830	6830	22600	26300	5260	2400

B



300 L — 262 — 1250 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ	$M_{2\,max}$ Nm
500	**300L3**	**177**	2.8	1050	0.34	71 ... 132	7050	7050	23300	27100	5660	2400
	300L3	**192**	2.6	730	0.22	71 ... 132	7130	7130	23600	27400	5820	2400
	300L3	**221**	2.3	1090	0.28	71 ... 132	7280	7280	24100	28000	6090	2400
	300L3	**240**	2.1	750	0.18	71 ... 132	7360	7360	24400	28300	6260	2400
	300L3	**299**	1.7	780	0.15	71 ... 132	7600	7600	25100	29200	6740	2400
	300L3	**374**	1.3	820	0.13	71 ... 132	7850	7850	26000	30200	7260	2400
	300L4	**330**	1.5	1170	0.21	71 ... 132	7710	7710	25500	29700	6970	2400
	300L4	**403**	1.2	830	0.12	71 ... 132	7930	7930	26200	30500	7450	2400
	300L4	**447**	1.1	1230	0.16	71 ... 132	8050	8050	26600	31000	7710	2400
	300L4	**494**	1.0	1250	0.15	71 ... 132	8170	8170	27000	31400	7970	2400
	300L4	**558**	0.90	1250	0.13	71 ... 132	8310	8310	27500	32000	8000	2400
	300L4	**616**	0.81	1250	0.12	71 ... 132	8430	8430	27900	32400	8000	2400
	300L4	**755**	0.66	1250	0.10	71 ... 132	8680	8680	28700	33400	8000	2400
	300L4	**819**	0.61	1250	0.09	71 ... 132	8780	8780	29000	33800	8000	2400
	300L4	**942**	0.53	1250	0.08	71 ... 132	8960	8960	29600	34000	8000	2400
	300L4	**1022**	0.49	1250	0.07	71 ... 132	9060	9060	30000	34000	8000	2400
	300L4	**1108**	0.45	860	0.05	71 ... 132	9160	9160	30300	34000	8000	2400
	300L4	**1275**	0.39	1250	0.06	71 ... 132	9350	9350	30900	34000	8000	2400
	300L4	**1383**	0.36	860	0.04	71 ... 132	9460	9460	31000	34000	8000	2400
	300L4	**1591**	0.31	1250	0.05	71 ... 132	9650	9650	31000	34000	8000	2400
	300L4	**1725**	0.29	860	0.03	71 ... 132	9760	9760	31000	34000	8000	2400
	300L4	**2153**	0.23	860	0.02	71 ... 132	10100	10100	31000	34000	8000	2400
	300L4	**2692**	0.19	1000	0.02	71 ... 132	10400	10400	31000	34000	8000	2400

301 L — 272 — 2460 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**301L1**	**3.48**	431	840	30	71 ... 132	1850	1850	6950	7600	1060	3400
	301L1	**4.26**	352	880	30	71 ... 132	1980	1980	7390	8080	1130	3400
	301L1	**5.77**	260	930	26.1	71 ... 132	2190	2190	8090	8840	1250	3400
	301L1	**7.20**	208	750	17.0	71 ... 132	2360	2360	8650	9450	1350	3400
	301L1	**9.00**	167	630	11.3	71 ... 132	2540	2540	9240	10100	1450	3400
	301L2	**12.1**	124	1220	16.8	71 ... 132	2810	2810	10100	11000	1600	3400
	301L2	**14.8**	101	1280	14.4	71 ... 132	3010	3010	10700	11700	1720	3400
	301L2	**18.2**	83	1360	12.5	71 ... 132	3220	3220	11400	12500	1840	3400
	301L2	**20.1**	75	1260	10.5	71 ... 132	3320	3320	11800	12900	1900	3400
	301L2	**24.6**	61	1490	10.1	71 ... 132	3560	3560	12500	13700	2030	3400
	301L2	**30.7**	49	1580	8.6	71 ... 132	3830	3830	13400	14600	2190	3400
	301L2	**33.3**	45	1300	6.5	71 ... 132	3940	3940	13700	15000	2250	3400
	301L2	**38.4**	39	1540	6.7	71 ... 132	4130	4130	14300	15600	2360	3400
	301L2	**41.5**	36	1300	5.2	71 ... 132	4240	4240	14600	16000	2420	3400
	301L2	**51.9**	28.9	1300	4.2	71 ... 132	4560	4560	15600	17100	2610	3400
	301L2	**64.8**	23.1	1150	3.0	71 ... 132	4910	4910	16700	18300	2810	3400
	301L3	**51.6**	29.1	1630	5.4	71 ... 132	4560	4560	15600	17100	2600	3400
	301L3	**63.2**	23.7	1650	4.5	71 ... 132	4870	4870	16600	18100	2780	3400
	301L3	**69.9**	21.5	1300	3.2	71 ... 132	5040	5040	17100	18700	2880	3400
	301L3	**77.5**	19.4	1670	3.7	71 ... 132	5220	5220	17600	19300	2980	3400
	301L3	**85.6**	17.5	1680	3.4	71 ... 132	5390	5390	18200	19900	3080	3400
	301L3	**105**	14.3	1700	2.8	71 ... 132	5770	5770	19300	21100	3300	3400
	301L3	**116**	13.0	1300	1.9	71 ... 132	5960	5960	19900	21700	3410	3400
	301L3	**131**	11.5	1720	2.3	71 ... 132	6210	6210	20600	22600	3550	3400
	301L3	**142**	10.6	1720	2.1	71 ... 132	6380	6380	21100	23100	3650	3400
	301L3	**177**	8.5	1770	1.7	71 ... 132	6500	6500	21500	23500	3920	3400
	301L3	**192**	7.8	1300	1.2	71 ... 132	6500	6500	21500	23500	4030	3400
	301L3	**221**	6.8	1790	1.4	71 ... 132	6500	6500	21500	23500	4230	3400
	301L3	**240**	6.3	1300	0.93	71 ... 132	6500	6500	21500	23500	4340	3400
	301L3	**299**	5.0	1300	0.75	71 ... 132	6500	6500	21500	23500	4670	3400
	301L3	**374**	4.0	1350	0.62	71 ... 132	6710	6710	22200	24300	5030	3400



301 L

272

2460 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**301L4**	**330**	4.5	1920	1.0	71 ... 132	6590	6590	21800	23800	4830	3400
	301L4	**403**	3.7	1370	0.60	71 ... 132	6780	6780	22400	24500	5160	3400
	301L4	**447**	3.4	2030	0.81	71 ... 132	6880	6880	22800	24900	5340	3400
	301L4	**494**	3.0	2070	0.74	71 ... 132	6980	6980	23100	25200	5520	3400
	301L4	**558**	2.7	2110	0.67	71 ... 132	7100	7100	23500	25700	5750	3400
	301L4	**616**	2.4	2150	0.62	71 ... 132	7200	7200	23800	26000	5950	3400
	301L4	**755**	2.0	2220	0.52	71 ... 132	7420	7420	24500	26800	6360	3400
	301L4	**819**	1.8	2240	0.49	71 ... 132	7500	7500	24800	27100	6540	3400
	301L4	**942**	1.6	2290	0.43	71 ... 132	7650	7650	25300	27700	6850	3400
	301L4	**1022**	1.5	2320	0.40	71 ... 132	7740	7740	25600	28000	7040	3400
	301L4	**1108**	1.4	1630	0.26	71 ... 132	7830	7830	25900	28300	7230	3400
	301L4	**1275**	1.2	2400	0.33	71 ... 132	7990	7990	26400	28900	7580	3400
	301L4	**1383**	1.1	1700	0.22	71 ... 132	8090	8090	26700	29200	7790	3400
	301L4	**1591**	0.94	2000	0.22	71 ... 132	8250	8250	27300	29800	8000	3400
	301L4	**1725**	0.87	1720	0.18	71 ... 132	8350	8350	27600	30200	8000	3400
	301L4	**2153**	0.70	1720	0.14	71 ... 132	8610	8610	28500	31100	8000	3400
	301L4	**2692**	0.56	1720	0.11	71 ... 132	8890	8890	29400	32200	8000	3400
1000	**301L1**	**3.48**	287	950	29.4	71 ... 132	2120	2120	7850	8580	1210	3400
	301L1	**4.26**	235	990	25.1	71 ... 132	2270	2270	8340	9120	1300	3400
	301L1	**5.77**	173	1050	19.7	71 ... 132	2510	2510	9140	9990	1430	3400
	301L1	**7.20**	139	850	12.8	71 ... 132	2700	2700	9760	10700	1540	3400
	301L1	**9.00**	111	710	8.5	71 ... 132	2910	2910	10400	11400	1660	3400
	301L2	**12.1**	83	1330	12.3	71 ... 132	3220	3220	11400	12500	1840	3400
	301L2	**14.8**	67	1440	10.8	71 ... 132	3440	3440	12100	13300	1970	3400
	301L2	**18.2**	55	1530	9.4	71 ... 132	3680	3680	12900	14100	2100	3400
	301L2	**20.1**	50	1300	7.2	71 ... 132	3810	3810	13300	14500	2170	3400
	301L2	**24.6**	41	1600	7.2	71 ... 132	4070	4070	14100	15400	2330	3400
	301L2	**30.7**	33	1620	5.9	71 ... 132	4380	4380	15100	16500	2500	3400
	301L2	**33.3**	30	1300	4.3	71 ... 132	4500	4500	15500	16900	2570	3400
	301L2	**38.4**	26.1	1550	4.5	71 ... 132	4720	4720	16100	17600	2700	3400
	301L2	**41.5**	24.1	1300	3.5	71 ... 132	4850	4850	16500	18100	2770	3400
	301L2	**51.9**	19.3	1300	2.8	71 ... 132	5220	5220	17700	19300	2980	3400
	301L2	**64.8**	15.4	1150	2.0	71 ... 132	5620	5620	18900	20600	3210	3400
	301L3	**51.6**	19.4	1670	3.7	71 ... 132	5210	5210	17600	19300	2980	3400
	301L3	**63.2**	15.8	1690	3.1	71 ... 132	5580	5580	18700	20500	3190	3400
	301L3	**69.9**	14.3	1300	2.1	71 ... 132	5770	5770	19300	21100	3290	3400
	301L3	**77.5**	12.9	1710	2.5	71 ... 132	5970	5970	19900	21800	3410	3400
	301L3	**85.6**	11.7	1710	2.3	71 ... 132	6170	6170	20500	22400	3530	3400
	301L3	**105**	9.5	1740	1.9	71 ... 132	6500	6500	21500	23500	3770	3400
	301L3	**116**	8.6	1300	1.3	71 ... 132	6500	6500	21500	23500	3900	3400
	301L3	**131**	7.6	1790	1.6	71 ... 132	6500	6500	21500	23500	4060	3400
	301L3	**142**	7.0	1810	1.5	71 ... 132	6500	6500	21500	23500	4170	3400
	301L3	**177**	5.6	1860	1.2	71 ... 132	6500	6500	21500	23500	4490	3400
	301L3	**192**	5.2	1300	0.78	71 ... 132	6500	6500	21500	23500	4620	3400
	301L3	**221**	4.5	1850	0.96	71 ... 132	6590	6590	21800	23800	4840	3400
	301L3	**240**	4.2	1340	0.64	71 ... 132	6670	6670	22100	24100	4970	3400
	301L3	**299**	3.3	1390	0.53	71 ... 132	6880	6880	22800	24900	5350	3400
	301L3	**374**	2.7	1440	0.44	71 ... 132	7110	7110	23500	25700	5760	3400
	301L4	**330**	3.0	2070	0.74	71 ... 132	6980	6980	23100	25200	5530	3400
	301L4	**403**	2.5	1460	0.43	71 ... 132	7180	7180	23800	26000	5910	3400
	301L4	**447**	2.2	2180	0.58	71 ... 132	7290	7290	24100	26400	6120	3400
	301L4	**494**	2.0	2210	0.53	71 ... 132	7400	7400	24500	26700	6320	3400
	301L4	**558**	1.8	2250	0.48	71 ... 132	7530	7530	24900	27200	6590	3400
	301L4	**616**	1.6	2290	0.44	71 ... 132	7630	7630	25200	27600	6810	3400
	301L4	**755**	1.3	2360	0.37	71 ... 132	7860	7860	26000	28400	7280	3400
	301L4	**819**	1.2	2390	0.34	71 ... 132	7950	7950	26300	28700	7480	3400
	301L4	**942**	1.1	2440	0.31	71 ... 132	8110	8110	26800	29300	7840	3400
	301L4	**1022**	0.98	2460	0.28	71 ... 132	8210	8210	27100	29700	8000	3400
	301L4	**1108**	0.90	1720	0.18	71 ... 132	8300	8300	27500	30000	8000	3400
	301L4	**1275**	0.78	2460	0.23	71 ... 132	8470	8470	28000	30600	8000	3400

B



301 L

272

2460 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1000	**301L4**	**1383**	0.72	1720	0.15	71 ... 132	8570	8570	28300	31000	8000	3400
	301L4	**1591**	0.63	2000	0.15	71 ... 132	8740	8740	28900	31600	8000	3400
	301L4	**1725**	0.58	1720	0.12	71 ... 132	8840	8840	29300	32000	8000	3400
	301L4	**2153**	0.46	1720	0.09	71 ... 132	9130	9130	30200	33000	8000	3400
	301L4	**2692**	0.37	1720	0.08	71 ... 132	9420	9420	31000	34000	8000	3400
500	**301L1**	**3.48**	144	1170	18.1	71 ... 132	2670	2670	9670	10600	1530	3400
	301L1	**4.26**	117	1220	15.4	71 ... 132	2860	2860	10300	11200	1630	3400
	301L1	**5.77**	87	1250	11.7	71 ... 132	3160	3160	11200	12300	1810	3400
	301L1	**7.20**	69	1050	7.8	71 ... 132	3410	3410	12000	13100	1950	3400
	301L1	**9.00**	56	730	4.4	71 ... 132	3670	3670	12900	14000	2100	3400
	301L2	**12.1**	41	1430	6.6	71 ... 132	4050	4050	14100	15400	2310	3400
	301L2	**14.8**	34	1620	6.1	71 ... 132	4340	4340	14900	16300	2480	3400
	301L2	**18.2**	27.5	1630	5.0	71 ... 132	4640	4640	15900	17300	2650	3400
	301L2	**20.1**	24.9	1300	3.6	71 ... 132	4800	4800	16400	17900	2740	3400
	301L2	**24.6**	20.3	1660	3.8	71 ... 132	5130	5130	17400	19000	2930	3400
	301L2	**30.7**	16.3	1680	3.1	71 ... 132	5520	5520	18600	20300	3160	3400
	301L2	**33.3**	15.0	1300	2.2	71 ... 132	5680	5680	19000	20800	3240	3400
	301L2	**38.4**	13.0	1560	2.3	71 ... 132	5950	5950	19900	21700	3400	3400
	301L2	**41.5**	12.0	1300	1.7	71 ... 132	6110	6110	20300	22200	3490	3400
	301L2	**51.9**	9.6	1300	1.4	71 ... 132	6500	6500	21500	23500	3760	3400
	301L2	**64.8**	7.7	1150	0.99	71 ... 132	6500	6500	21500	23500	4050	3400
	301L3	**51.6**	9.7	1740	1.9	71 ... 132	6500	6500	21500	23500	3750	3400
	301L3	**63.2**	7.9	1780	1.6	71 ... 132	6500	6500	21500	23500	4020	3400
	301L3	**69.9**	7.2	1300	1.1	71 ... 132	6500	6500	21500	23500	4150	3400
	301L3	**77.5**	6.5	1830	1.4	71 ... 132	6500	6500	21500	23500	4300	3400
	301L3	**85.6**	5.8	1850	1.2	71 ... 132	6500	6500	21500	23500	4440	3400
	301L3	**105**	4.8	1910	1.0	71 ... 132	6540	6540	21600	23700	4750	3400
	301L3	**116**	4.3	1330	0.66	71 ... 132	6640	6640	22000	24000	4910	3400
	301L3	**131**	3.8	1980	0.87	71 ... 132	6750	6750	22300	24400	5120	3400
	301L3	**142**	3.5	2010	0.81	71 ... 132	6830	6830	22600	24700	5260	3400
	301L3	**177**	2.8	2090	0.68	71 ... 132	7050	7050	23300	25500	5660	3400
	301L3	**192**	2.6	1450	0.43	71 ... 132	7130	7130	23600	25800	5820	3400
	301L3	**221**	2.3	2000	0.52	71 ... 132	7280	7280	24100	26300	6090	3400
	301L3	**240**	2.1	1510	0.36	71 ... 132	7360	7360	24400	26600	6260	3400
	301L3	**299**	1.7	1570	0.30	71 ... 132	7600	7600	25100	27500	6740	3400
	301L3	**374**	1.3	1630	0.25	71 ... 132	7850	7850	26000	28400	7260	3400
	301L4	**330**	1.5	2310	0.41	71 ... 132	7710	7710	25500	27900	6970	3400
	301L4	**403**	1.2	1650	0.24	71 ... 132	7930	7930	26200	28700	7450	3400
	301L4	**447**	1.1	2420	0.32	71 ... 132	8050	8050	26600	29100	7710	3400
	301L4	**494**	1.0	2460	0.29	71 ... 132	8170	8170	27000	29500	7970	3400
	301L4	**558**	0.90	2460	0.26	71 ... 132	8310	8310	27500	30000	8000	3400
	301L4	**616**	0.81	2460	0.24	71 ... 132	8430	8430	27900	30500	8000	3400
	301L4	**755**	0.66	2460	0.19	71 ... 132	8680	8680	28700	31400	8000	3400
	301L4	**819**	0.61	2460	0.18	71 ... 132	8780	8780	29000	31700	8000	3400
	301L4	**942**	0.53	2460	0.15	71 ... 132	8960	8960	29600	32400	8000	3400
	301L4	**1022**	0.49	2460	0.14	71 ... 132	9060	9060	30000	32800	8000	3400
	301L4	**1108**	0.45	1720	0.09	71 ... 132	9160	9160	30300	33100	8000	3400
	301L4	**1275**	0.39	2460	0.11	71 ... 132	9350	9350	30900	33800	8000	3400
	301L4	**1383**	0.36	1720	0.07	71 ... 132	9460	9460	31000	34000	8000	3400
	301L4	**1591**	0.31	2000	0.07	71 ... 132	9650	9650	31000	34000	8000	3400
	301L4	**1725**	0.29	1720	0.06	71 ... 132	9760	9760	31000	34000	8000	3400
	301L4	**2153**	0.23	1720	0.05	71 ... 132	10100	10100	31000	34000	8000	3400
	301L4	**2692**	0.19	1720	0.04	71 ... 132	10400	10400	31000	34000	8000	3400

B



303 L

282

2970 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**303L1**	**3.60**	417	1380	40	132 ... 200	6060	6920	13200	15700	3210	5200
	303L1	**4.25**	353	1430	40	132 ... 200	6400	7320	13900	16500	3400	5200
	303L1	**5.33**	281	1490	40	132 ... 200	6910	7890	14900	17600	3660	5200
	303L1	**6.20**	242	1400	36	132 ... 200	7260	8300	15600	18500	3850	5200
	303L1	**7.50**	200	1220	26.3	132 ... 200	7740	8840	16500	19500	4100	5200
	303L1	**9.67**	155	750	12.6	132 ... 200	8420	9620	17800	21100	4470	5200
	303L2	**12.5**	120	1640	20.0	71 ... 160	9180	10500	19200	22800	4870	5200
	303L2	**15.3**	98	1710	18.6	71 ... 160	9820	11200	20400	24200	5210	5200
	303L2	**18.1**	83	2020	18.6	71 ... 160	10400	11900	21500	25500	5510	5200
	303L2	**20.8**	72	1820	14.6	71 ... 160	10900	12400	22400	26500	5760	5200
	303L2	**22.7**	66	2100	15.4	71 ... 160	11200	12800	23000	27300	5940	5200
	303L2	**24.5**	61	2150	14.6	71 ... 160	11500	13100	23500	27900	6090	5200
	303L2	**26.4**	57	1820	11.5	71 ... 160	11800	13500	24100	28500	6250	5200
	303L2	**30.8**	49	2140	11.6	71 ... 160	12400	14200	25200	29800	6570	5200
	303L2	**35.8**	42	1820	8.5	71 ... 160	13000	14900	26300	31200	6910	5200
	303L2	**38.4**	39	2150	9.3	71 ... 160	13300	15200	26900	31900	7070	5200
	303L2	**44.6**	34	1820	6.8	71 ... 160	14000	16000	28200	33400	7440	5200
	303L2	**55.8**	26.9	1820	5.4	71 ... 160	15100	17300	30100	35700	8010	5200
	303L3	**53.4**	28.1	2170	7.0	71 ... 160	14900	17000	29700	35200	7900	5200
	303L3	**63.1**	23.8	2510	6.8	71 ... 160	15700	18000	31200	37000	8340	5200
	303L3	**72.3**	20.8	2230	5.3	71 ... 160	16500	18800	32500	38600	8730	5200
	303L3	**77.2**	19.4	2520	5.6	71 ... 160	16800	19200	33200	39300	8930	5200
	303L3	**90.2**	16.6	2250	4.3	71 ... 160	17700	20300	34800	41200	9400	5200
	303L3	**105**	14.4	2580	4.2	71 ... 160	18600	21300	36300	43100	9880	5200
	303L3	**113**	13.3	1820	2.8	71 ... 160	19100	21800	37200	44100	10100	5200
	303L3	**124**	12.1	1820	2.5	71 ... 160	19700	22600	38300	45400	10500	5200
	303L3	**141**	10.6	2610	3.2	71 ... 160	20600	23500	39800	47200	10900	5200
	303L3	**152**	9.8	1820	2.1	71 ... 160	21000	24000	40500	48000	11200	5200
	303L3	**164**	9.2	2200	2.3	71 ... 160	21000	24000	40500	48000	11500	5200
	303L3	**178**	8.5	2210	2.1	71 ... 160	21000	24000	40500	48000	11800	5200
	303L3	**190**	7.9	1830	1.7	71 ... 160	21000	24000	40500	48000	12100	5200
	303L3	**220**	6.8	2250	1.8	71 ... 160	21000	24000	40500	48000	12700	5200
	303L3	**258**	5.8	1840	1.2	71 ... 160	21000	24000	40500	48000	13300	5200
	303L3	**276**	5.4	2230	1.4	71 ... 160	21000	24000	40500	48000	13700	5200
	303L3	**321**	4.7	1860	1.0	71 ... 160	21200	24200	40900	48500	14400	5200
	303L3	**389**	3.9	1690	0.75	71 ... 160	21800	24900	42000	49800	15300	5200
	303L3	**402**	3.7	1940	0.83	71 ... 160	21900	25000	42200	50000	15500	5200
	303L4	**413**	3.6	2360	1.0	71 ... 160	22000	25100	42400	50200	15600	5200
	303L4	**446**	3.4	2810	1.1	71 ... 160	22200	25400	42900	50800	16000	5200
	303L4	**492**	3	2690	0.97	71 ... 160	22500	25800	43500	51500	16600	5200
	303L4	**556**	2.7	2810	0.90	71 ... 160	22900	26200	44200	52400	17200	5200
	303L4	**649**	2.3	2320	0.63	71 ... 160	23400	26800	45200	53600	18200	5200
	303L4	**718**	2.1	2150	0.53	71 ... 160	23800	27200	45900	54400	18800	5200
	303L4	**816**	1.8	2720	0.59	71 ... 160	24200	27700	46700	55400	19600	5200
	303L4	**896**	1.7	2230	0.44	71 ... 160	24600	28100	47400	56100	20200	5200
	303L4	**1018**	1.5	2740	0.48	71 ... 160	25000	28600	48200	57200	21100	5200
	303L4	**1098**	1.4	2310	0.37	71 ... 160	25300	28900	48700	57800	21600	5200
	303L4	**1278**	1.2	2790	0.39	71 ... 160	25800	29500	49800	59000	22800	5200
	303L4	**1370**	1.1	2400	0.31	71 ... 160	26100	29800	50300	59600	23300	5200
	303L4	**1586**	0.95	2250	0.25	71 ... 160	26600	30400	51400	60900	24000	5200
	303L4	**1854**	0.81	2440	0.23	71 ... 160	27200	31100	52500	62300	24000	5200
	303L4	**1991**	0.75	2850	0.25	71 ... 160	27500	31500	53100	62900	24000	5200
	303L4	**2243**	0.67	2000	0.16	71 ... 160	28000	32000	54000	64000	24000	5200
	303L4	**2799**	0.54	2000	0.13	71 ... 160	28900	33000	55700	66000	24000	5200
1000	**303L1**	**3.60**	278	1560	40	132 ... 200	6930	7920	14900	17700	3680	5200
	303L1	**4.25**	235	1620	40	132 ... 200	7330	8380	15700	18600	3890	5200
	303L1	**5.33**	188	1680	34	132 ... 200	7900	9030	16800	19900	4190	5200
	303L1	**6.20**	161	1580	27.5	132 ... 200	8310	9500	17600	20800	4410	5200
	303L1	**7.50**	133	1380	19.8	132 ... 200	8860	10100	18600	22100	4700	5200
	303L1	**9.67**	103	850	9.5	132 ... 200	9640	11000	20100	23800	5110	5200



303 L

282

2970 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1000	**303L2**	**12.5**	80	1850	16.4	71 ... 160	10500	12000	21700	25700	5570	5200
	303L2	**15.3**	65	1940	14.0	71 ... 160	11200	12800	23100	27400	5960	5200
	303L2	**18.1**	55	2280	14.0	71 ... 160	11900	13600	24300	28800	6300	5200
	303L2	**20.8**	48	2030	10.9	71 ... 160	12400	14200	25300	30000	6600	5200
	303L2	**22.7**	44	2140	10.5	71 ... 160	12800	14600	26000	30800	6800	5200
	303L2	**24.5**	41	2320	10.5	71 ... 160	13100	15000	26600	31500	6970	5200
	303L2	**26.4**	38	1820	7.7	71 ... 160	13500	15400	27200	32200	7150	5200
	303L2	**30.8**	33	2160	7.8	71 ... 160	14200	16200	28400	33700	7520	5200
	303L2	**35.8**	28.0	1820	5.7	71 ... 160	14900	17000	29800	35300	7910	5200
	303L2	**38.4**	26.0	2160	6.3	71 ... 160	15300	17400	30400	36000	8100	5200
	303L2	**44.6**	22.4	1820	4.5	71 ... 160	16000	18300	31800	37700	8510	5200
	303L2	**55.8**	17.9	1820	3.6	71 ... 160	17300	19800	34000	40300	9170	5200
	303L3	**53.4**	18.7	2230	4.8	71 ... 160	17000	19500	33600	39800	9040	5200
	303L3	**63.1**	15.9	2570	4.7	71 ... 160	18000	20600	35300	41800	9550	5200
	303L3	**72.3**	13.8	2270	3.6	71 ... 160	18800	21500	36700	43500	10000	5200
	303L3	**77.2**	12.9	2600	3.9	71 ... 160	19300	22000	37500	44400	10200	5200
	303L3	**90.2**	11.1	2300	2.9	71 ... 160	20300	23200	39300	46500	10800	5200
	303L3	**105**	9.6	2660	2.9	71 ... 160	21000	24000	40500	48000	11300	5200
	303L3	**113**	8.9	1820	1.9	71 ... 160	21000	24000	40500	48000	11600	5200
	303L3	**124**	8.0	1830	1.7	71 ... 160	21000	24000	40500	48000	12000	5200
	303L3	**141**	7.1	2630	2.1	71 ... 160	21000	24000	40500	48000	12500	5200
	303L3	**152**	6.6	1830	1.4	71 ... 160	21000	24000	40500	48000	12800	5200
	303L3	**164**	6.1	2220	1.6	71 ... 160	21000	24000	40500	48000	13100	5200
	303L3	**178**	5.6	2220	1.4	71 ... 160	21000	24000	40500	48000	13500	5200
	303L3	**190**	5.3	1840	1.1	71 ... 160	21000	24000	40500	48000	13800	5200
	303L3	**220**	4.5	2240	1.2	71 ... 160	21300	24300	41100	48700	14500	5200
	303L3	**258**	3.9	1920	0.86	71 ... 160	21800	24900	42000	49800	15300	5200
	303L3	**276**	3.6	2330	0.97	71 ... 160	22000	25100	42400	50300	15600	5200
	303L3	**321**	3.1	2000	0.71	71 ... 160	22500	25700	43300	51400	16400	5200
	303L3	**389**	2.6	1750	0.52	71 ... 160	23100	26400	44500	52800	17500	5200
	303L3	**402**	2.5	2080	0.59	71 ... 160	23200	26500	44700	53000	17700	5200
	303L4	**413**	2.4	2530	0.72	71 ... 160	23300	26600	44900	53200	17900	5200
	303L4	**446**	2.2	2830	0.75	71 ... 160	23500	26900	45400	53800	18300	5200
	303L4	**492**	2.0	2720	0.65	71 ... 160	23900	27300	46100	54600	19000	5200
	303L4	**556**	1.8	2870	0.61	71 ... 160	24300	27800	46900	55600	19700	5200
	303L4	**649**	1.5	2360	0.43	71 ... 160	24800	28400	47900	56800	20800	5200
	303L4	**718**	1.4	2300	0.38	71 ... 160	25200	28800	48600	57600	21500	5200
	303L4	**816**	1.2	2750	0.40	71 ... 160	25700	29300	49500	58700	22400	5200
	303L4	**896**	1.1	2390	0.32	71 ... 160	26000	29700	50200	59500	23100	5200
	303L4	**1018**	0.98	2770	0.32	71 ... 160	26500	30300	51100	60600	24000	5200
	303L4	**1098**	0.91	2440	0.26	71 ... 160	26800	30600	51700	61200	24000	5200
	303L4	**1278**	0.78	2850	0.26	71 ... 160	27400	31300	52800	62600	24000	5200
	303L4	**1370**	0.73	2440	0.21	71 ... 160	27600	31600	53300	63200	24000	5200
	303L4	**1586**	0.63	2250	0.17	71 ... 160	28200	32300	54400	64500	24000	5200
	303L4	**1854**	0.54	2440	0.16	71 ... 160	28900	33000	55700	66000	24000	5200
	303L4	**1991**	0.50	2850	0.17	71 ... 160	29200	33300	56200	66700	24000	5200
	303L4	**2243**	0.45	2000	0.11	71 ... 160	29700	33900	57200	67800	24000	5200
	303L4	**2799**	0.36	2000	0.08	71 ... 160	30600	35000	59000	70000	24000	5200
500	**303L1**	**3.60**	139	1920	28.8	132 ... 200	8740	9980	18400	21800	4630	5200
	303L1	**4.25**	118	1990	25.3	132 ... 200	9230	10600	19300	22900	4900	5200
	303L1	**5.33**	94	2040	20.6	132 ... 200	9960	11400	20700	24500	5280	5200
	303L1	**6.20**	81	1820	15.8	132 ... 200	10500	12000	21700	25700	5560	5200
	303L1	**7.50**	67	1590	11.4	132 ... 200	11200	12800	22900	27200	5920	5200
	303L1	**9.67**	52	860	4.8	132 ... 200	12100	13900	24700	29300	6440	5200
	303L2	**12.5**	40	2150	9.6	71 ... 160	13200	15100	26700	31700	7020	5200
	303L2	**15.3**	33	2150	7.8	71 ... 160	14200	16200	28400	33700	7510	5200
	303L2	**18.1**	27.6	2460	7.5	71 ... 160	15000	17100	29900	35400	7940	5200
	303L2	**20.8**	24.1	2110	5.7	71 ... 160	15700	17900	31100	36900	8310	5200
	303L2	**22.7**	22.0	2170	5.3	71 ... 160	16100	18500	32000	37900	8570	5200
	303L2	**24.5**	20.4	2460	5.6	71 ... 160	16600	18900	32700	38800	8780	5200
	303L2	**26.4**	18.9	1820	3.8	71 ... 160	17000	19400	33500	39600	9010	5200



303 L

282

2970 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
500	**303L2**	**30.8**	16.3	2180	3.9	71 ... 160	17900	20400	35000	41500	9480	5200
	303L2	**35.8**	14.0	1820	2.8	71 ... 160	18800	21500	36600	43400	9960	5200
	303L2	**38.4**	13.0	2190	3.2	71 ... 160	19200	22000	37400	44300	10200	5200
	303L2	**44.6**	11.2	1820	2.3	71 ... 160	20200	23100	39100	46400	10700	5200
	303L2	**55.8**	9.0	1820	1.8	71 ... 160	21000	24000	40500	48000	11600	5200
	303L3	**53.4**	9.4	2310	2.5	71 ... 160	21000	24000	40500	48000	11400	5200
	303L3	**63.1**	7.9	2700	2.5	71 ... 160	21000	24000	40500	48000	12000	5200
	303L3	**72.3**	6.9	2310	1.8	71 ... 160	21000	24000	40500	48000	12600	5200
	303L3	**77.2**	6.5	2750	2.0	71 ... 160	21000	24000	40500	48000	12900	5200
	303L3	**90.2**	5.5	2310	1.5	71 ... 160	21000	24000	40500	48000	13600	5200
	303L3	**105**	4.8	2810	1.5	71 ... 160	21100	24200	40800	48300	14200	5200
	303L3	**113**	4.4	1880	0.96	71 ... 160	21400	24400	41200	48800	14600	5200
	303L3	**124**	4.0	1910	0.88	71 ... 160	21700	24800	41800	49500	15100	5200
	303L3	**141**	3.5	2670	1.1	71 ... 160	22100	25200	42600	50400	15800	5200
	303L3	**152**	3.3	1980	0.75	71 ... 160	22300	25500	43000	51000	16200	5200
	303L3	**164**	3.1	2430	0.85	71 ... 160	22500	25800	43500	51500	16500	5200
	303L3	**178**	2.8	2470	0.80	71 ... 160	22800	26100	44000	52100	17000	5200
	303L3	**190**	2.6	2060	0.62	71 ... 160	23000	26300	44400	52600	17400	5200
	303L3	**220**	2.3	2210	0.57	71 ... 160	23500	26900	45300	53700	18300	5200
	303L3	**258**	1.9	2170	0.48	71 ... 160	24000	27500	46400	54900	19200	5200
	303L3	**276**	1.8	2580	0.54	71 ... 160	24300	27800	46800	55500	19700	5200
	303L3	**321**	1.6	2260	0.40	71 ... 160	24800	28400	47900	56700	20700	5200
	303L3	**389**	1.3	1930	0.28	71 ... 160	25500	29100	49200	58300	22100	5200
	303L3	**402**	1.2	2350	0.34	71 ... 160	25600	29300	49400	58500	22300	5200
	303L4	**413**	1.2	2780	0.40	71 ... 160	25700	29400	49600	58800	22500	5200
	303L4	**446**	1.1	2950	0.39	71 ... 160	26000	29700	50100	59400	23100	5200
	303L4	**492**	1.0	2770	0.33	71 ... 160	26400	30100	50900	60300	23900	5200
	303L4	**556**	0.90	2970	0.32	71 ... 160	26800	30700	51700	61300	24000	5200
	303L4	**649**	0.77	2410	0.22	71 ... 160	27400	31400	52900	62700	24000	5200
	303L4	**718**	0.70	2440	0.20	71 ... 160	27800	31800	53700	63600	24000	5200
	303L4	**816**	0.61	2770	0.20	71 ... 160	28300	32400	54700	64800	24000	5200
	303L4	**896**	0.56	2440	0.16	71 ... 160	28700	32800	55400	65700	24000	5200
	303L4	**1018**	0.49	2770	0.16	71 ... 160	29300	33400	56400	66900	24000	5200
	303L4	**1098**	0.46	2440	0.13	71 ... 160	29600	33800	57000	67600	24000	5200
	303L4	**1278**	0.39	2850	0.13	71 ... 160	30200	34500	58300	69100	24000	5200
	303L4	**1370**	0.36	2440	0.11	71 ... 160	30500	34900	58900	69800	24000	5200
	303L4	**1586**	0.32	2250	0.08	71 ... 160	31200	35600	60100	71200	24000	5200
	303L4	**1854**	0.27	2440	0.08	71 ... 160	31900	36400	61500	72800	24000	5200
	303L4	**1991**	0.25	2850	0.08	71 ... 160	32200	36800	62100	73600	24000	5200
	303L4	**2243**	0.22	2000	0.05	71 ... 160	32700	37400	63200	74000	24000	5200
	303L4	**2799**	0.18	2000	0.04	71 ... 160	33800	38600	64000	74000	24000	5200

304 L

294

3960 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**304L1**	**3.60**	417	1840	50	132 ... 200	6060	6920	13200	15700	3210	7300
	304L1	**4.25**	353	1900	50	132 ... 200	6400	7320	13900	16500	3400	7300
	304L1	**5.33**	281	1990	50	132 ... 200	6910	7890	14900	17600	3660	7300
	304L1	**6.57**	228	1870	46	132 ... 200	7400	8460	15800	18800	3930	7300
	304L2	**12.5**	120	2680	30	71 ... 160	9180	10500	19200	22800	4870	7300
	304L2	**15.3**	98	2840	30	71 ... 160	9820	11200	20400	24200	5210	7300
	304L2	**18.1**	83	2940	27.1	71 ... 160	10400	11900	21500	25500	5510	7300
	304L2	**20.8**	72	2960	23.8	71 ... 160	10900	12400	22400	26500	5760	7300
	304L2	**22.7**	66	2790	20.5	71 ... 160	11200	12800	23000	27300	5940	7300
	304L2	**24.5**	61	3230	22.0	71 ... 160	11500	13100	23500	27900	6090	7300
	304L2	**30.8**	49	2850	15.5	71 ... 160	12400	14200	25200	29800	6570	7300
	304L2	**38.4**	39	2850	12.4	71 ... 160	13300	15200	26900	31900	7070	7300
	304L2	**47.3**	32	2390	8.4	71 ... 160	14300	16300	28700	34000	7580	7300



304 L

294

3960 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**304L2**	**59.1**	25.4	2390	6.7	71 ... 160	15400	17600	30600	36300	8170	7300
	304L3	**43.6**	34	3190	12.6	71 ... 160	13900	15900	28000	33100	7380	7300
	304L3	**53.4**	28.1	3230	10.4	71 ... 160	14900	17000	29700	35200	7900	7300
	304L3	**63.1**	23.8	3480	9.5	71 ... 160	15700	18000	31200	37000	8340	7300
	304L3	**72.3**	20.8	3290	7.8	71 ... 160	16500	18800	32500	38600	8730	7300
	304L3	**77.2**	19.4	3490	7.8	71 ... 160	16800	19200	33200	39300	8930	7300
	304L3	**90.2**	16.6	3320	6.3	71 ... 160	17700	20300	34800	41200	9400	7300
	304L3	**105**	14.4	3520	5.8	71 ... 160	18600	21300	36300	43100	9880	7300
	304L3	**111**	13.6	3380	5.3	71 ... 160	19000	21700	37000	43800	10100	7300
	304L3	**130**	11.5	3530	4.7	71 ... 160	20000	22900	38800	46000	10600	7300
	304L3	**141**	10.6	3540	4.3	71 ... 160	20600	23500	39800	47200	10900	7300
	304L3	**150**	10.0	3440	4.0	71 ... 160	21000	24000	40500	48000	11100	7300
	304L3	**165**	9.1	2390	2.5	71 ... 160	21000	24000	40500	48000	11500	7300
	304L3	**178**	8.5	2850	2.8	71 ... 160	21000	24000	40500	48000	11800	7300
	304L3	**202**	7.4	2390	2.0	71 ... 160	21000	24000	40500	48000	12300	7300
	304L3	**220**	6.8	3610	2.8	71 ... 160	21000	24000	40500	48000	12700	7300
	304L3	**273**	5.5	2390	1.5	71 ... 160	21000	24000	40500	48000	13600	7300
	304L3	**341**	4.4	2420	1.2	71 ... 160	21400	24400	41300	48900	14700	7300
	304L3	**426**	3.5	2470	1.0	71 ... 160	22100	25200	42600	50500	15800	7300
	304L4	**413**	3.6	3000	1.3	71 ... 160	22000	25100	42400	50200	15600	7300
	304L4	**446**	3.4	3720	1.5	71 ... 160	22200	25400	42900	50800	16000	7300
	304L4	**492**	3.0	3730	1.3	71 ... 160	22500	25800	43500	51500	16600	7300
	304L4	**556**	2.7	3740	1.2	71 ... 160	22900	26200	44200	52400	17200	7300
	304L4	**649**	2.3	3540	0.97	71 ... 160	23400	26800	45200	53600	18200	7300
	304L4	**702**	2.1	2630	0.66	71 ... 160	23700	27100	45700	54200	18600	7300
	304L4	**816**	1.8	3820	0.83	71 ... 160	24200	27700	46700	55400	19600	7300
	304L4	**1018**	1.5	3870	0.67	71 ... 160	25000	28600	48200	57200	21100	7300
	304L4	**1164**	1.3	2870	0.44	71 ... 160	25500	29100	49200	58300	22100	7300
	304L4	**1271**	1.2	3920	0.55	71 ... 160	25800	29500	49800	59000	22700	7300
	304L4	**1344**	1.1	3690	0.49	71 ... 160	26000	29700	50200	59500	23100	7300
	304L4	**1586**	0.95	3960	0.44	71 ... 160	26600	30400	51400	60900	24000	7300
	304L4	**1815**	0.83	3000	0.29	71 ... 160	27200	31000	52400	62100	24000	7300
	304L4	**1991**	0.75	3740	0.33	71 ... 160	27500	31500	53100	62900	24000	7300
	304L4	**2269**	0.66	3000	0.23	71 ... 160	28000	32000	54100	64100	24000	7300
	304L4	**2453**	0.61	3000	0.22	71 ... 160	28400	32400	54700	64800	24000	7300
1000	**304L1**	**3.60**	278	2080	50	132 ... 200	6930	7920	14900	17700	3680	7300
	304L1	**4.25**	235	2150	50	132 ... 200	7330	8380	15700	18600	3890	7300
	304L1	**5.33**	188	2240	45	132 ... 200	7900	9030	16800	19900	4190	7300
	304L1	**6.57**	152	2110	35	132 ... 200	8470	9680	17900	21200	4500	7300
	304L2	**12.5**	80	2920	25.9	71 ... 160	10500	12000	21700	25700	5570	7300
	304L2	**15.3**	65	3010	21.8	71 ... 160	11200	12800	23100	27400	5960	7300
	304L2	**18.1**	55	3330	20.4	71 ... 160	11900	13600	24300	28800	6300	7300
	304L2	**20.8**	48	3130	16.8	71 ... 160	12400	14200	25300	30000	6600	7300
	304L2	**22.7**	44	2850	13.9	71 ... 160	12800	14600	26000	30800	6800	7300
	304L2	**24.5**	41	3440	15.6	71 ... 160	13100	15000	26600	31500	6970	7300
	304L2	**30.8**	33	2850	10.3	71 ... 160	14200	16200	28400	33700	7520	7300
	304L2	**38.4**	26.0	2850	8.3	71 ... 160	15300	17400	30400	36000	8100	7300
	304L2	**47.3**	21.1	2390	5.6	71 ... 160	16400	18700	32400	38300	8680	7300
	304L2	**59.1**	16.9	2390	4.5	71 ... 160	17600	20100	34600	41000	9350	7300
	304L3	**43.6**	22.9	3270	8.6	71 ... 160	15900	18200	31600	37400	8450	7300
	304L3	**53.4**	18.7	3310	7.1	71 ... 160	17000	19500	33600	39800	9040	7300
	304L3	**63.1**	15.9	3510	6.4	71 ... 160	18000	20600	35300	41800	9550	7300
	304L3	**72.3**	13.8	3370	5.4	71 ... 160	18800	21500	36700	43500	10000	7300
	304L3	**77.2**	12.9	3520	5.2	71 ... 160	19300	22000	37500	44400	10200	7300
	304L3	**90.2**	11.1	3420	4.3	71 ... 160	20300	23200	39300	46500	10800	7300
	304L3	**105**	9.6	3550	3.9	71 ... 160	21000	24000	40500	48000	11300	7300
	304L3	**111**	9.0	3450	3.6	71 ... 160	21000	24000	40500	48000	11500	7300
	304L3	**130**	7.7	3600	3.2	71 ... 160	21000	24000	40500	48000	12200	7300
	304L3	**141**	7.1	3610	2.9	71 ... 160	21000	24000	40500	48000	12500	7300
	304L3	**150**	6.7	3470	2.7	71 ... 160	21000	24000	40500	48000	12700	7300



304 L

294

3960 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1000	**304L3**	**165**	6.1	2390	1.7	71 ... 160	21000	24000	40500	48000	13200	7300
	304L3	**178**	5.6	2850	1.8	71 ... 160	21000	24000	40500	48000	13500	7300
	304L3	**202**	5.0	2390	1.4	71 ... 160	21000	24000	40500	48100	14100	7300
	304L3	**220**	4.5	3670	1.9	71 ... 160	21300	24300	41100	48700	14500	7300
	304L3	**273**	3.7	2460	1.0	71 ... 160	22000	25100	42300	50200	15600	7300
	304L3	**341**	2.9	2520	0.85	71 ... 160	22700	25900	43700	51800	16800	7300
	304L3	**426**	2.3	2590	0.70	71 ... 160	23400	26700	45100	53500	18100	7300
	304L4	**413**	2.4	3210	0.92	71 ... 160	23300	26600	44900	53200	17900	7300
	304L4	**446**	2.2	3770	1.0	71 ... 160	23500	26900	45400	53800	18300	7300
	304L4	**492**	2.0	3800	0.91	71 ... 160	23900	27300	46100	54600	19000	7300
	304L4	**556**	1.8	3820	0.81	71 ... 160	24300	27800	46900	55600	19700	7300
	304L4	**649**	1.5	3620	0.66	71 ... 160	24800	28400	47900	56800	20800	7300
	304L4	**702**	1.4	2820	0.48	71 ... 160	25100	28700	48500	57400	21300	7300
	304L4	**816**	1.2	3910	0.57	71 ... 160	25700	29300	49500	58700	22400	7300
	304L4	**1018**	0.98	3960	0.46	71 ... 160	26500	30300	51100	60600	24000	7300
	304L4	**1164**	0.86	3000	0.30	71 ... 160	27000	30900	52100	61700	24000	7300
	304L4	**1271**	0.79	3960	0.37	71 ... 160	27300	31300	52700	62500	24000	7300
	304L4	**1344**	0.74	3710	0.33	71 ... 160	27600	31500	53200	63000	24000	7300
	304L4	**1586**	0.63	3960	0.30	71 ... 160	28200	32300	54400	64500	24000	7300
	304L4	**1815**	0.55	3000	0.20	71 ... 160	28800	32900	55500	65800	24000	7300
	304L4	**1991**	0.50	3740	0.22	71 ... 160	29200	33300	56200	66700	24000	7300
	304L4	**2269**	0.44	3000	0.16	71 ... 160	29700	34000	57300	67900	24000	7300
	304L4	**2453**	0.41	3000	0.14	71 ... 160	30000	34300	57900	68700	24000	7300
500	**304L1**	**3.60**	139	2560	38	132 ... 200	8740	9980	18400	21800	4630	7300
	304L1	**4.25**	118	2650	34	132 ... 200	9230	10600	19300	22900	4900	7300
	304L1	**5.33**	94	2720	27.6	132 ... 200	9960	11400	20700	24500	5280	7300
	304L1	**6.57**	76	2390	19.6	132 ... 200	10700	12200	22000	26100	5660	7300
	304L2	**12.5**	40	3160	14.0	71 ... 160	13200	15100	26700	31700	7020	7300
	304L2	**15.3**	33	3200	11.6	71 ... 160	14200	16200	28400	33700	7510	7300
	304L2	**18.1**	27.6	3470	10.7	71 ... 160	15000	17100	29900	35400	7940	7300
	304L2	**20.8**	24.1	3260	8.7	71 ... 160	15700	17900	31100	36900	8310	7300
	304L2	**22.7**	22.0	2850	7.0	71 ... 160	16100	18500	32000	37900	8570	7300
	304L2	**24.5**	20.4	3490	7.9	71 ... 160	16600	18900	32700	38800	8780	7300
	304L2	**30.8**	16.3	2850	5.2	71 ... 160	17900	20400	35000	41500	9480	7300
	304L2	**38.4**	13.0	2850	4.1	71 ... 160	19200	22000	37400	44300	10200	7300
	304L2	**47.3**	10.6	2390	2.8	71 ... 160	20600	23600	39800	47200	10900	7300
	304L2	**59.1**	8.5	2390	2.2	71 ... 160	21000	24000	40500	48000	11800	7300
	304L3	**43.6**	11.5	3410	4.5	71 ... 160	20100	22900	38900	46100	10600	7300
	304L3	**53.4**	9.4	3450	3.7	71 ... 160	21000	24000	40500	48000	11400	7300
	304L3	**63.1**	7.9	3590	3.3	71 ... 160	21000	24000	40500	48000	12000	7300
	304L3	**72.3**	6.9	3470	2.8	71 ... 160	21000	24000	40500	48000	12600	7300
	304L3	**77.2**	6.5	3630	2.7	71 ... 160	21000	24000	40500	48000	12900	7300
	304L3	**90.2**	5.5	3490	2.2	71 ... 160	21000	24000	40500	48000	13600	7300
	304L3	**105**	4.8	3690	2.0	71 ... 160	21100	24200	40800	48300	14200	7300
	304L3	**111**	4.5	3500	1.8	71 ... 160	21300	24300	41100	48700	14500	7300
	304L3	**130**	3.8	3710	1.6	71 ... 160	21800	24900	42100	49900	15300	7300
	304L3	**141**	3.5	3720	1.5	71 ... 160	22100	25200	42600	50400	15800	7300
	304L3	**150**	3.3	3510	1.3	71 ... 160	22200	25400	42900	50800	16000	7300
	304L3	**165**	3.0	2510	0.87	71 ... 160	22600	25800	43500	51500	16600	7300
	304L3	**178**	2.8	3130	1.0	71 ... 160	22800	26100	44000	52100	17000	7300
	304L3	**202**	2.5	2560	0.73	71 ... 160	23200	26500	44800	53100	17700	7300
	304L3	**220**	2.3	3740	0.97	71 ... 160	23500	26900	45300	53700	18300	7300
	304L3	**273**	1.8	2700	0.57	71 ... 160	24200	27700	46700	55400	19600	7300
	304L3	**341**	1.5	2810	0.47	71 ... 160	25000	28600	48300	57200	21100	7300
	304L3	**426**	1.2	2920	0.39	71 ... 160	25800	29500	49800	59000	22700	7300
	304L4	**413**	1.2	3620	0.52	71 ... 160	25700	29400	49600	58800	22500	7300
	304L4	**446**	1.1	3930	0.52	71 ... 160	26000	29700	50100	59400	23100	7300
	304L4	**492**	1.0	3960	0.48	71 ... 160	26400	30100	50900	60300	23900	7300
	304L4	**556**	0.90	3960	0.42	71 ... 160	26800	30700	51700	61300	24000	7300
	304L4	**649**	0.77	3710	0.34	71 ... 160	27400	31400	52900	62700	24000	7300

B



304 L

294

3960 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
500	**304L4**	**702**	0.71	3000	0.25	71 ... 160	27700	31700	53500	63400	24000	7300
	304L4	**816**	0.61	3960	0.29	71 ... 160	28300	32400	54700	64800	24000	7300
	304L4	**1018**	0.49	3960	0.23	71 ... 160	29300	33400	56400	66900	24000	7300
	304L4	**1164**	0.43	3000	0.15	71 ... 160	29800	34100	57500	68200	24000	7300
	304L4	**1271**	0.39	3960	0.18	71 ... 160	30200	34500	58200	69000	24000	7300
	304L4	**1344**	0.37	3710	0.16	71 ... 160	30400	34800	58700	69600	24000	7300
	304L4	**1586**	0.32	3960	0.15	71 ... 160	31200	35600	60100	71200	24000	7300
	304L4	**1815**	0.28	3000	0.10	71 ... 160	31800	36300	61300	72600	24000	7300
	304L4	**1991**	0.25	3740	0.11	71 ... 160	32200	36800	62100	73600	24000	7300
	304L4	**2269**	0.22	3000	0.08	71 ... 160	32800	37500	63300	74000	24000	7300
	304L4	**2453**	0.20	3000	0.07	71 ... 160	33200	37900	64000	74000	24000	7300

305 L

306

5800 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**305L1**	**3.60**	417	2370	60	132 ... 200	6060	6920	13200	15700	3210	8800
	305L1	**4.25**	353	2450	60	132 ... 200	6400	7320	13900	16500	3400	8800
	305L1	**5.33**	281	2560	60	132 ... 200	6910	7890	14900	17600	3660	8800
	305L1	**6.20**	242	2650	60	132 ... 200	7260	8300	15600	18500	3850	8800
	305L1	**7.50**	200	2270	49	132 ... 200	7740	8840	16500	19500	4100	8800
	305L2	**12.5**	120	2930	30	71 ... 160	9180	10500	19200	22800	4870	8800
	305L2	**15.3**	98	3060	30	71 ... 160	9820	11200	20400	24200	5210	8800
	305L2	**18.1**	83	3620	30	71 ... 160	10400	11900	21500	25500	5510	8800
	305L2	**20.8**	72	3250	26.1	71 ... 160	10900	12400	22400	26500	5760	8800
	305L2	**22.7**	66	3940	29.0	71 ... 160	11200	12800	23000	27300	5940	8800
	305L2	**24.5**	61	3830	26.1	71 ... 160	11500	13100	23500	27900	6090	8800
	305L2	**26.4**	57	3530	22.3	71 ... 160	11800	13500	24100	28500	6250	8800
	305L2	**30.8**	49	4280	23.2	71 ... 160	12400	14200	25200	29800	6570	8800
	305L2	**35.8**	42	3560	16.6	71 ... 160	13000	14900	26300	31200	6910	8800
	305L2	**38.4**	39	4300	18.7	71 ... 160	13300	15200	26900	31900	7070	8800
	305L2	**44.6**	34	3560	13.3	71 ... 160	14000	16000	28200	33400	7440	8800
	305L2	**55.8**	26.9	3540	10.6	71 ... 160	15100	17300	30100	35700	8010	8800
	305L3	**53.4**	28.1	4000	12.9	71 ... 160	14900	17000	29700	35200	7900	8800
	305L3	**63.1**	23.8	4720	12.9	71 ... 160	15700	18000	31200	37000	8340	8800
	305L3	**72.3**	20.8	4160	9.9	71 ... 160	16500	18800	32500	38600	8730	8800
	305L3	**77.2**	19.4	4820	10.7	71 ... 160	16800	19200	33200	39300	8930	8800
	305L3	**90.2**	16.6	4260	8.1	71 ... 160	17700	20300	34800	41200	9400	8800
	305L3	**105**	14.4	5030	8.3	71 ... 160	18600	21300	36300	43100	9880	8800
	305L3	**113**	13.3	3590	5.5	71 ... 160	19100	21800	37200	44100	10100	8800
	305L3	**124**	12.1	3590	5.0	71 ... 160	19700	22600	38300	45400	10500	8800
	305L3	**141**	10.6	5180	6.3	71 ... 160	20600	23500	39800	47200	10900	8800
	305L3	**152**	9.8	3600	4.1	71 ... 160	21000	24000	40500	48000	11200	8800
	305L3	**164**	9.2	4410	4.6	71 ... 160	21000	24000	40500	48000	11500	8800
	305L3	**178**	8.5	4420	4.3	71 ... 160	21000	24000	40500	48000	11800	8800
	305L3	**190**	7.9	3600	3.3	71 ... 160	21000	24000	40500	48000	12100	8800
	305L3	**220**	6.8	4750	3.7	71 ... 160	21000	24000	40500	48000	12700	8800
	305L3	**258**	5.8	3600	2.4	71 ... 160	21000	24000	40500	48000	13300	8800
	305L3	**276**	5.4	4460	2.8	71 ... 160	21000	24000	40500	48000	13700	8800
	305L3	**321**	4.7	3640	1.9	71 ... 160	21200	24200	40900	48500	14400	8800
	305L3	**389**	3.9	3170	1.4	71 ... 160	21800	24900	42000	49800	15300	8800
	305L3	**402**	3.7	3760	1.6	71 ... 160	21900	25000	42200	50000	15500	8800
	305L4	**413**	3.6	4720	2.0	71 ... 160	22000	25100	42400	50200	15600	8800
	305L4	**446**	3.4	5490	2.2	71 ... 160	22200	25400	42900	50800	16000	8800
	305L4	**492**	3.0	5340	1.9	71 ... 160	22500	25800	43500	51500	16600	8800
	305L4	**556**	2.7	5500	1.8	71 ... 160	22900	26200	44200	52400	17200	8800
	305L4	**649**	2.3	4510	1.2	71 ... 160	23400	26800	45200	53600	18200	8800
	305L4	**718**	2.1	4130	1.0	71 ... 160	23800	27200	45900	54400	18800	8800
	305L4	**816**	1.8	5410	1.2	71 ... 160	24200	27700	46700	55400	19600	8800



305 L

306

5800 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**305L4**	**896**	1.7	4290	0.85	71 ... 160	24600	28100	47400	56100	20200	8800
	305L4	**1018**	1.5	5450	0.95	71 ... 160	25000	28600	48200	57200	21100	8800
	305L4	**1098**	1.4	4440	0.72	71 ... 160	25300	28900	48700	57800	21600	8800
	305L4	**1278**	1.2	5500	0.76	71 ... 160	25800	29500	49800	59000	22800	8800
	305L4	**1370**	1.1	4620	0.60	71 ... 160	26100	29800	50300	59600	23300	8800
	305L4	**1586**	0.95	4750	0.53	71 ... 160	26600	30400	51400	60900	24000	8800
	305L4	**1854**	0.81	4690	0.45	71 ... 160	27200	31100	52500	62300	24000	8800
	305L4	**1991**	0.75	5600	0.50	71 ... 160	27500	31500	53100	62900	24000	8800
	305L4	**2243**	0.67	3800	0.30	71 ... 160	28000	32000	54000	64000	24000	8800
	305L4	**2799**	0.54	3800	0.24	71 ... 160	28900	33000	55700	66000	24000	8800
1000	**305L1**	**3.60**	278	2680	60	132 ... 200	6930	7920	14900	17700	3680	8800
	305L1	**4.25**	235	2770	60	132 ... 200	7330	8380	15700	18600	3890	8800
	305L1	**5.33**	188	2890	58	132 ... 200	7900	9030	16800	19900	4190	8800
	305L1	**6.20**	161	3000	52	132 ... 200	8310	9500	17600	20800	4410	8800
	305L1	**7.50**	133	2560	37	132 ... 200	8860	10100	18600	22100	4700	8800
	305L2	**12.5**	80	3300	29.4	71 ... 160	10500	12000	21700	25700	5570	8800
	305L2	**15.3**	65	3460	25.1	71 ... 160	11200	12800	23100	27400	5960	8800
	305L2	**18.1**	55	4090	25.1	71 ... 160	11900	13600	24300	28800	6300	8800
	305L2	**20.8**	48	3650	19.5	71 ... 160	12400	14200	25300	30000	6600	8800
	305L2	**22.7**	44	4290	21.0	71 ... 160	12800	14600	26000	30800	6800	8800
	305L2	**24.5**	41	4200	19.1	71 ... 160	13100	15000	26600	31500	6970	8800
	305L2	**26.4**	38	3560	15.0	71 ... 160	13500	15400	27200	32200	7150	8800
	305L2	**30.8**	33	4310	15.6	71 ... 160	14200	16200	28400	33700	7520	8800
	305L2	**35.8**	28.0	3570	11.1	71 ... 160	14900	17000	29800	35300	7910	8800
	305L2	**38.4**	26.0	4330	12.5	71 ... 160	15300	17400	30400	36000	8100	8800
	305L2	**44.6**	22.4	3570	8.9	71 ... 160	16000	18300	31800	37700	8510	8800
	305L2	**55.8**	17.9	3560	7.1	71 ... 160	17300	19800	34000	40300	9170	8800
	305L3	**53.4**	18.7	4190	9.0	71 ... 160	17000	19500	33600	39800	9040	8800
	305L3	**63.1**	15.9	4980	9.1	71 ... 160	18000	20600	35300	41800	9550	8800
	305L3	**72.3**	13.8	4340	6.9	71 ... 160	18800	21500	36700	43500	10000	8800
	305L3	**77.2**	12.9	5110	7.6	71 ... 160	19300	22000	37500	44400	10200	8800
	305L3	**90.2**	11.1	4440	5.7	71 ... 160	20300	23200	39300	46500	10800	8800
	305L3	**105**	9.6	5310	5.8	71 ... 160	21000	24000	40500	48000	11300	8800
	305L3	**113**	8.9	3600	3.7	71 ... 160	21000	24000	40500	48000	11600	8800
	305L3	**124**	8.0	3600	3.3	71 ... 160	21000	24000	40500	48000	12000	8800
	305L3	**141**	7.1	5260	4.3	71 ... 160	21000	24000	40500	48000	12500	8800
	305L3	**152**	6.6	3600	2.7	71 ... 160	21000	24000	40500	48000	12800	8800
	305L3	**164**	6.1	4450	3.1	71 ... 160	21000	24000	40500	48000	13100	8800
	305L3	**178**	5.6	4460	2.9	71 ... 160	21000	24000	40500	48000	13500	8800
	305L3	**190**	5.3	3600	2.2	71 ... 160	21000	24000	40500	48000	13800	8800
	305L3	**220**	4.5	4750	2.5	71 ... 160	21300	24300	41100	48700	14500	8800
	305L3	**258**	3.9	3740	1.7	71 ... 160	21800	24900	42000	49800	15300	8800
	305L3	**276**	3.6	4670	1.9	71 ... 160	22000	25100	42400	50300	15600	8800
	305L3	**321**	3.1	3870	1.4	71 ... 160	22500	25700	43300	51400	16400	8800
	305L3	**389**	2.6	3290	0.97	71 ... 160	23100	26400	44500	52800	17500	8800
	305L3	**402**	2.5	4000	1.1	71 ... 160	23200	26500	44700	53000	17700	8800
	305L4	**413**	2.4	5060	1.4	71 ... 160	23300	26600	44900	53200	17900	8800
	305L4	**446**	2.2	5530	1.5	71 ... 160	23500	26900	45400	53800	18300	8800
	305L4	**492**	2.0	5390	1.3	71 ... 160	23900	27300	46100	54600	19000	8800
	305L4	**556**	1.8	5610	1.2	71 ... 160	24300	27800	46900	55600	19700	8800
	305L4	**649**	1.5	4600	0.84	71 ... 160	24800	28400	47900	56800	20800	8800
	305L4	**718**	1.4	4430	0.73	71 ... 160	25200	28800	48600	57600	21500	8800
	305L4	**816**	1.2	5490	0.80	71 ... 160	25700	29300	49500	58700	22400	8800
	305L4	**896**	1.1	4600	0.61	71 ... 160	26000	29700	50200	59500	23100	8800
	305L4	**1018**	0.98	5530	0.64	71 ... 160	26500	30300	51100	60600	24000	8800
	305L4	**1098**	0.91	4690	0.51	71 ... 160	26800	30600	51700	61200	24000	8800
	305L4	**1278**	0.78	5600	0.52	71 ... 160	27400	31300	52800	62600	24000	8800
	305L4	**1370**	0.73	4690	0.40	71 ... 160	27600	31600	53300	63200	24000	8800
	305L4	**1586**	0.63	4750	0.35	71 ... 160	28200	32300	54400	64500	24000	8800
	305L4	**1854**	0.54	4690	0.30	71 ... 160	28900	33000	55700	66000	24000	8800
	305L4	**1991**	0.50	5600	0.33	71 ... 160	29200	33300	56200	66700	24000	8800

B



305 L

306

5800 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1000	**305L4**	**2243**	0.45	3800	0.20	71 ... 160	29700	33900	57200	67800	24000	8800
	305L4	**2799**	0.36	3800	0.16	71 ... 160	30600	35000	59000	70000	24000	8800
500	**305L1**	**3.60**	139	3300	49	132 ... 200	8740	9980	18400	21800	4630	8800
	305L1	**4.25**	118	3410	43	132 ... 200	9230	10600	19300	22900	4900	8800
	305L1	**5.33**	94	3560	36	132 ... 200	9960	11400	20700	24500	5280	8800
	305L1	**6.20**	81	3490	30	132 ... 200	10500	12000	21700	25700	5560	8800
	305L1	**7.50**	67	2910	20.9	132 ... 200	11200	12800	22900	27200	5920	8800
	305L2	**12.5**	40	3890	17.3	71 ... 160	13200	15100	26700	31700	7020	8800
	305L2	**15.3**	33	3930	14.3	71 ... 160	14200	16200	28400	33700	7510	8800
	305L2	**18.1**	27.6	4580	14.1	71 ... 160	15000	17100	29900	35400	7940	8800
	305L2	**20.8**	24.1	3970	10.6	71 ... 160	15700	17900	31100	36900	8310	8800
	305L2	**22.7**	22.0	4340	10.6	71 ... 160	16100	18500	32000	37900	8570	8800
	305L2	**24.5**	20.4	4680	10.6	71 ... 160	16600	18900	32700	38800	8780	8800
	305L2	**26.4**	18.9	3580	7.5	71 ... 160	17000	19400	33500	39600	9010	8800
	305L2	**30.8**	16.3	4360	7.9	71 ... 160	17900	20400	35000	41500	9480	8800
	305L2	**35.8**	14.0	3590	5.6	71 ... 160	18800	21500	36600	43400	9960	8800
	305L2	**38.4**	13.0	4380	6.3	71 ... 160	19200	22000	37400	44300	10200	8800
	305L2	**44.6**	11.2	3600	4.5	71 ... 160	20200	23100	39100	46400	10700	8800
	305L2	**55.8**	9.0	3600	3.6	71 ... 160	21000	24000	40500	48000	11600	8800
	305L3	**53.4**	9.4	4490	4.8	71 ... 160	21000	24000	40500	48000	11400	8800
	305L3	**63.1**	7.9	5360	4.9	71 ... 160	21000	24000	40500	48000	12000	8800
	305L3	**72.3**	6.9	4490	3.6	71 ... 160	21000	24000	40500	48000	12600	8800
	305L3	**77.2**	6.5	5410	4.0	71 ... 160	21000	24000	40500	48000	12900	8800
	305L3	**90.2**	5.5	4490	2.9	71 ... 160	21000	24000	40500	48000	13600	8800
	305L3	**105**	4.8	5480	3.0	71 ... 160	21100	24200	40800	48300	14200	8800
	305L3	**113**	4.4	3670	1.9	71 ... 160	21400	24400	41200	48800	14600	8800
	305L3	**124**	4.0	3720	1.7	71 ... 160	21700	24800	41800	49500	15100	8800
	305L3	**141**	3.5	5320	2.2	71 ... 160	22100	25200	42600	50400	15800	8800
	305L3	**152**	3.3	3840	1.4	71 ... 160	22300	25500	43000	51000	16200	8800
	305L3	**164**	3.1	4870	1.7	71 ... 160	22500	25800	43500	51500	16500	8800
	305L3	**178**	2.8	4940	1.6	71 ... 160	22800	26100	44000	52100	17000	8800
	305L3	**190**	2.6	3970	1.2	71 ... 160	23000	26300	44400	52600	17400	8800
	305L3	**220**	2.3	4750	1.2	71 ... 160	23500	26900	45300	53700	18300	8800
	305L3	**258**	1.9	4180	0.93	71 ... 160	24000	27500	46400	54900	19200	8800
	305L3	**276**	1.8	5140	1.1	71 ... 160	24300	27800	46800	55500	19700	8800
	305L3	**321**	1.6	4340	0.78	71 ... 160	24800	28400	47900	56700	20700	8800
	305L3	**389**	1.3	3660	0.54	71 ... 160	25500	29100	49200	58300	22100	8800
	305L3	**402**	1.2	4520	0.64	71 ... 160	25600	29300	49400	58500	22300	8800
	305L4	**413**	1.2	5480	0.78	71 ... 160	25700	29400	49600	58800	22500	8800
	305L4	**446**	1.1	5760	0.76	71 ... 160	26000	29700	50100	59400	23100	8800
	305L4	**492**	1.0	5530	0.66	71 ... 160	26400	30100	50900	60300	23900	8800
	305L4	**556**	0.9	5800	0.62	71 ... 160	26800	30700	51700	61300	24000	8800
	305L4	**649**	0.77	4700	0.43	71 ... 160	27400	31400	52900	62700	24000	8800
	305L4	**718**	0.70	4690	0.39	71 ... 160	27800	31800	53700	63600	24000	8800
	305L4	**816**	0.61	5530	0.4	71 ... 160	28300	32400	54700	64800	24000	8800
	305L4	**896**	0.56	4690	0.31	71 ... 160	28700	32800	55400	65700	24000	8800
	305L4	**1018**	0.49	5530	0.32	71 ... 160	29300	33400	56400	66900	24000	8800
	305L4	**1098**	0.46	4690	0.25	71 ... 160	29600	33800	57000	67600	24000	8800
	305L4	**1278**	0.39	5600	0.26	71 ... 160	30200	34500	58300	69100	24000	8800
	305L4	**1370**	0.36	4690	0.2	71 ... 160	30500	34900	58900	69800	24000	8800
	305L4	**1586**	0.32	4750	0.18	71 ... 160	31200	35600	60100	71200	24000	8800
	305L4	**1854**	0.27	4690	0.15	71 ... 160	31900	36400	61500	72800	24000	8800
	305L4	**1991**	0.25	5600	0.17	71 ... 160	32200	36800	62100	73600	24000	8800
	305L4	**2243**	0.22	3800	0.1	71 ... 160	32700	37400	63200	74000	24000	8800
	305L4	**2799**	0.18	3800	0.08	71 ... 160	33800	38600	64000	74000	24000	8800

B



306 L

318

10840 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**306L1**	**3.60**	417	3760	75	160 ... 250	7210	8220	18600	21500	4690	14900
	306L1	**4.25**	353	3890	75	160 ... 250	7620	8690	19600	22600	4950	14900
	306L1	**5.33**	281	4060	75	160 ... 250	8220	9370	20900	24200	5340	14900
	306L1	**6.20**	242	4200	75	160 ... 250	8640	9850	21900	25300	5620	14900
	306L1	**7.50**	200	4090	75	160 ... 250	9210	10500	23200	26800	5980	14900
	306L2	**13.0**	116	4820	40	132 ... 200	11100	12600	27300	31600	7180	14900
	306L2	**15.3**	98	4990	40	132 ... 200	11700	13300	28700	33200	7590	14900
	306L2	**18.1**	83	5890	40	132 ... 200	12300	14100	30200	34900	8020	14900
	306L2	**22.7**	66	6140	40	132 ... 200	13300	15200	32300	37300	8650	14900
	306L2	**26.4**	57	6370	40	132 ... 200	14000	16000	33800	39100	9100	14900
	306L2	**28.4**	53	6700	39	132 ... 200	14400	16400	34600	40000	9330	14900
	306L2	**33.1**	45	6870	35	132 ... 200	15100	17200	36200	41800	9810	14900
	306L2	**38.4**	39	6470	28.1	132 ... 200	15900	18100	37900	43700	10300	14900
	306L2	**46.5**	32	6470	23.2	132 ... 200	16900	19300	40100	46300	11000	14900
	306L2	**56.3**	26.7	5210	15.5	132 ... 200	18000	20600	42500	49000	11700	14900
	306L2	**72.5**	20.7	5290	12.2	132 ... 200	19600	22400	45800	52900	12700	14900
	306L3	**53.2**	28.2	7100	20.0	71 ... 160	17700	20200	41800	48200	11500	14900
	306L3	**65.2**	23.0	7480	19.7	71 ... 160	18900	21600	44400	51300	12300	14900
	306L3	**77.0**	19.5	8350	18.7	71 ... 160	20000	22800	46700	53900	13000	14900
	306L3	**81.9**	18.3	6890	14.5	71 ... 160	20400	23300	47500	54900	13300	14900
	306L3	**88.3**	17.0	8550	16.7	71 ... 160	20900	23900	48600	56100	13600	14900
	306L3	**104**	14.4	8900	14.7	71 ... 160	22100	25200	51100	59000	14400	14900
	306L3	**112**	13.4	7410	11.3	71 ... 160	22700	25900	52300	60300	14800	14900
	306L3	**121**	12.4	7790	11.1	71 ... 160	23300	26500	53500	61700	15100	14900
	306L3	**141**	10.6	7900	9.6	71 ... 160	24500	27900	55900	64600	15900	14900
	306L3	**152**	9.9	7590	8.6	71 ... 160	25000	28500	57000	65800	16300	14900
	306L3	**190**	7.9	6510	5.9	71 ... 160	25000	28500	57000	65800	17600	14900
	306L3	**205**	7.3	8110	6.8	71 ... 160	25000	28500	57000	65800	18000	14900
	306L3	**222**	6.8	6520	5.1	71 ... 160	25000	28500	57000	65800	18500	14900
	306L3	**238**	6.3	8180	5.9	71 ... 160	25000	28500	57000	65800	19000	14900
	306L3	**268**	5.6	5500	3.5	71 ... 160	25000	28500	57000	65800	19700	14900
	306L3	**288**	5.2	5500	3.3	71 ... 160	25000	28500	57000	65800	20200	14900
	306L3	**325**	4.6	5540	2.9	71 ... 160	25300	28800	57600	66500	21000	14900
	306L3	**405**	3.7	5670	2.4	71 ... 160	26100	29700	59500	68700	22600	14900
	306L4	**391**	3.8	6840	3.1	71 ... 160	26000	29600	59200	68300	22400	14900
	306L4	**444**	3.4	9850	3.9	71 ... 160	26400	30100	60300	69600	23300	14900
	306L4	**509**	2.9	9450	3.3	71 ... 160	27000	30700	61500	71000	24400	14900
	306L4	**589**	2.5	9320	2.8	71 ... 160	27500	31400	62800	72500	25600	14900
	306L4	**636**	2.4	9450	2.6	71 ... 160	27800	31700	63500	73200	26300	14900
	306L4	**700**	2.1	9470	2.4	71 ... 160	28200	32200	64300	74300	27100	14900
	306L4	**809**	1.9	7690	1.7	71 ... 160	28800	32800	65700	75800	28500	14900
	306L4	**877**	1.7	7710	1.6	71 ... 160	29100	33200	66400	76700	29300	14900
	306L4	**1015**	1.5	9460	1.7	71 ... 160	29800	33900	67800	78300	30700	14900
	306L4	**1095**	1.4	7790	1.3	71 ... 160	30100	34300	68600	79200	31500	14900
	306L4	**1279**	1.2	8400	1.2	71 ... 160	30800	35100	70100	80900	33200	14900
	306L4	**1475**	1.0	10100	1.2	71 ... 160	31400	35800	71600	82600	34800	14900
	306L4	**1597**	0.94	8630	0.96	71 ... 160	31700	36200	72400	83600	35000	14900
	306L4	**1843**	0.81	10100	0.97	71 ... 160	32400	36900	73900	85300	35000	14900
	306L4	**2074**	0.72	7000	0.60	71 ... 160	33000	37600	75100	86700	35000	14900
	306L4	**2337**	0.64	7000	0.53	71 ... 160	33500	38200	76400	88200	35000	14900
	306L4	**2916**	0.51	7000	0.43	71 ... 160	34600	39400	78900	91100	35000	14900
1000	**306L1**	**3.60**	278	4250	75	160 ... 250	8250	9410	21000	24300	5360	14900
	306L1	**4.25**	235	4390	75	160 ... 250	8720	9950	22100	25500	5670	14900
	306L1	**5.33**	188	4580	75	160 ... 250	9410	10700	23700	27300	6120	14900
	306L1	**6.20**	161	4750	75	160 ... 250	9890	11300	24800	28600	6430	14900
	306L1	**7.50**	133	4620	67	160 ... 250	10500	12000	26200	30300	6850	14900
	306L2	**13.0**	77	5450	40	132 ... 200	12700	14400	30900	35600	8220	14900
	306L2	**15.3**	65	5640	40	132 ... 200	13400	15200	32500	37500	8690	14900
	306L2	**18.1**	55	6650	40	132 ... 200	14100	16100	34100	39400	9180	14900
	306L2	**22.7**	44	6840	34	132 ... 200	15200	17400	36500	42200	9910	14900

B



306 L

318

10840 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1000	**306L2**	**26.4**	38	6780	28.6	132 ... 200	16000	18300	38200	44100	10400	14900
	306L2	**28.4**	35	7040	27.6	132 ... 200	16400	18700	39100	45100	10700	14900
	306L2	**33.1**	30	7150	24.1	132 ... 200	17300	19700	40900	47200	11200	14900
	306L2	**38.4**	26.0	6480	18.7	132 ... 200	18200	20700	42800	49400	11800	14900
	306L2	**46.5**	21.5	6480	15.5	132 ... 200	19400	22100	45300	52300	12600	14900
	306L2	**56.3**	17.8	5330	10.5	132 ... 200	20600	23500	48000	55400	13400	14900
	306L2	**72.5**	13.8	5400	8.3	132 ... 200	22500	25600	51800	59700	14600	14900
	306L3	**53.2**	18.8	7890	17.0	71 ... 160	20300	23100	47200	54500	13200	14900
	306L3	**65.2**	15.3	8320	14.6	71 ... 160	21700	24700	50100	57900	14100	14900
	306L3	**77.0**	13.0	9090	13.5	71 ... 160	22900	26100	52700	60800	14900	14900
	306L3	**81.9**	12.2	7310	10.2	71 ... 160	23400	26700	53700	62000	15200	14900
	306L3	**88.3**	11.3	9230	12.0	71 ... 160	24000	27300	54900	63400	15600	14900
	306L3	**104**	9.6	9610	10.6	71 ... 160	25000	28500	57000	65800	16500	14900
	306L3	**112**	8.9	7590	7.8	71 ... 160	25000	28500	57000	65800	16900	14900
	306L3	**121**	8.2	8050	7.6	71 ... 160	25000	28500	57000	65800	17300	14900
	306L3	**141**	7.1	8120	6.6	71 ... 160	25000	28500	57000	65800	18200	14900
	306L3	**152**	6.6	7590	5.7	71 ... 160	25000	28500	57000	65800	18700	14900
	306L3	**190**	5.3	6530	3.9	71 ... 160	25000	28500	57000	65800	20100	14900
	306L3	**205**	4.9	8330	4.7	71 ... 160	25100	28600	57200	66000	20600	14900
	306L3	**222**	4.5	6650	3.4	71 ... 160	25400	28900	57800	66800	21200	14900
	306L3	**238**	4.2	8550	4.1	71 ... 160	25600	29200	58400	67500	21700	14900
	306L3	**268**	3.7	5670	2.4	71 ... 160	26100	29700	59400	68600	22600	14900
	306L3	**288**	3.5	5710	2.3	71 ... 160	26300	30000	60000	69300	23100	14900
	306L3	**325**	3.1	5780	2.0	71 ... 160	26800	30500	61100	70500	24100	14900
	306L3	**405**	2.5	5910	1.7	71 ... 160	27700	31500	63000	72800	25900	14900
	306L4	**391**	2.6	7340	2.2	71 ... 160	27500	31400	62700	72400	25600	14900
	306L4	**444**	2.3	9910	2.6	71 ... 160	28000	31900	63900	73700	26700	14900
	306L4	**509**	2.0	9450	2.2	71 ... 160	28600	32600	65100	75200	27900	14900
	306L4	**589**	1.7	9650	1.9	71 ... 160	29200	33300	66500	76800	29300	14900
	306L4	**636**	1.6	9450	1.8	71 ... 160	29500	33600	67200	77600	30100	14900
	306L4	**700**	1.4	9790	1.7	71 ... 160	29900	34100	68200	78700	31100	14900
	306L4	**809**	1.2	7820	1.1	71 ... 160	30500	34800	69600	80300	32600	14900
	306L4	**877**	1.1	7850	1.1	71 ... 160	30900	35200	70400	81300	33500	14900
	306L4	**1015**	0.99	9540	1.1	71 ... 160	31500	35900	71900	83000	35000	14900
	306L4	**1095**	0.91	7890	0.85	71 ... 160	31900	36300	72700	83900	35000	14900
	306L4	**1279**	0.78	8630	0.80	71 ... 160	32600	37200	74300	85800	35000	14900
	306L4	**1475**	0.68	10100	0.81	71 ... 160	33300	37900	75800	87500	35000	14900
	306L4	**1597**	0.63	8630	0.64	71 ... 160	33600	38300	76700	88500	35000	14900
	306L4	**1843**	0.54	10100	0.65	71 ... 160	34300	39100	78300	90400	35000	14900
	306L4	**2074**	0.48	7000	0.40	71 ... 160	34900	39800	79600	91900	35000	14900
	306L4	**2337**	0.43	7000	0.35	71 ... 160	35500	40500	81000	93500	35000	14900
	306L4	**2916**	0.34	7000	0.28	71 ... 160	36700	41800	83600	96500	35000	14900
500	**306L1**	**3.60**	139	5230	75	160 ... 250	10400	11900	25900	29900	6760	14900
	306L1	**4.25**	118	5410	69	160 ... 250	11000	12500	27200	31400	7140	14900
	306L1	**5.33**	94	5640	57	160 ... 250	11900	13500	29100	33600	7700	14900
	306L1	**6.20**	81	5770	50	160 ... 250	12500	14200	30500	35200	8100	14900
	306L1	**7.50**	67	5040	36	160 ... 250	13300	15100	32300	37200	8630	14900
	306L2	**13.0**	39	6470	27.8	132 ... 200	15900	18200	38000	43900	10400	14900
	306L2	**15.3**	33	6830	24.8	132 ... 200	16800	19200	40000	46100	10900	14900
	306L2	**18.1**	27.7	7760	23.9	132 ... 200	17800	20300	42000	48500	11600	14900
	306L2	**22.7**	22.1	7820	19.2	132 ... 200	19200	21900	45000	51900	12500	14900
	306L2	**26.4**	19.0	7190	15.2	132 ... 200	20200	23000	47000	54300	13100	14900
	306L2	**28.4**	17.6	7530	14.7	132 ... 200	20700	23600	48100	55600	13500	14900
	306L2	**33.1**	15.1	7640	12.9	132 ... 200	21800	24800	50400	58100	14200	14900
	306L2	**38.4**	13.0	6490	9.4	132 ... 200	22900	26100	52700	60800	14900	14900
	306L2	**46.5**	10.8	6500	7.8	132 ... 200	24400	27800	55800	64400	15900	14900
	306L2	**56.3**	8.9	5500	5.4	132 ... 200	25000	28500	57000	65800	16900	14900
	306L2	**72.5**	6.9	5500	4.2	132 ... 200	25000	28500	57000	65800	18400	14900
	306L3	**53.2**	9.4	9300	10.0	71 ... 160	25000	28500	57000	65800	16600	14900
	306L3	**65.2**	7.7	9320	8.2	71 ... 160	25000	28500	57000	65800	17800	14900



306 L — 318 — 10840 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
500	**306L3**	**77.0**	6.5	9750	7.3	71 ... 160	25000	28500	57000	65800	18800	14900
	306L3	**81.9**	6.1	7650	5.4	71 ... 160	25000	28500	57000	65800	19100	14900
	306L3	**88.3**	5.7	9450	6.1	71 ... 160	25000	28500	57000	65800	19600	14900
	306L3	**104**	4.8	9850	5.4	71 ... 160	25100	28700	57300	66200	20800	14900
	306L3	**112**	4.5	7590	3.9	71 ... 160	25400	29000	58000	66900	21300	14900
	306L3	**121**	4.1	8580	4.1	71 ... 160	25700	29300	58600	67600	21800	14900
	306L3	**141**	3.5	8800	3.6	71 ... 160	26300	29900	59900	69100	23000	14900
	306L3	**152**	3.3	7590	2.9	71 ... 160	26500	30300	60500	69900	23500	14900
	306L3	**190**	2.6	7300	2.2	71 ... 160	27400	31200	62500	72100	25300	14900
	306L3	**205**	2.4	9370	2.6	71 ... 160	27700	31600	63100	72900	26000	14900
	306L3	**222**	2.3	7500	1.9	71 ... 160	28000	31900	63900	73700	26700	14900
	306L3	**238**	2.1	9390	2.3	71 ... 160	28300	32300	64500	74500	27300	14900
	306L3	**268**	1.9	6230	1.3	71 ... 160	28800	32800	65600	75800	28400	14900
	306L3	**288**	1.7	6320	1.3	71 ... 160	29100	33100	66300	76500	29100	14900
	306L3	**325**	1.5	6460	1.1	71 ... 160	29600	33700	67400	77900	30300	14900
	306L3	**405**	1.2	6730	0.95	71 ... 160	30500	34800	69600	80400	32600	14900
	306L4	**391**	1.3	8270	1.3	71 ... 160	30400	34600	69300	79900	32200	14900
	306L4	**444**	1.1	10300	1.4	71 ... 160	30900	35300	70500	81400	33600	14900
	306L4	**509**	0.98	9450	1.1	71 ... 160	31500	36000	71900	83000	35000	14900
	306L4	**589**	0.85	10100	1.0	71 ... 160	32200	36700	73400	84800	35000	14900
	306L4	**636**	0.79	9450	0.88	71 ... 160	32600	37100	74200	85700	35000	14900
	306L4	**700**	0.71	10100	0.85	71 ... 160	33000	37600	75300	86900	35000	14900
	306L4	**809**	0.62	7890	0.58	71 ... 160	33700	38400	76800	88700	35000	14900
	306L4	**877**	0.57	7890	0.53	71 ... 160	34100	38900	77700	89700	35000	14900
	306L4	**1015**	0.49	9540	0.56	71 ... 160	34800	39700	79400	91600	35000	14900
	306L4	**1095**	0.46	7890	0.43	71 ... 160	35200	40100	80200	92600	35000	14900
	306L4	**1279**	0.39	8630	0.40	71 ... 160	36000	41000	82000	94700	35000	14900
	306L4	**1475**	0.34	10100	0.40	71 ... 160	36700	41900	83700	96600	35000	14900
	306L4	**1597**	0.31	8630	0.32	71 ... 160	37100	42300	84700	97700	35000	14900
	306L4	**1843**	0.27	10100	0.32	71 ... 160	37900	43200	86400	99800	35000	14900
	306L4	**2074**	0.24	7000	0.20	71 ... 160	38600	43900	87900	101500	35000	14900
	306L4	**2337**	0.21	7000	0.18	71 ... 160	39200	44700	89400	103200	35000	14900
	306L4	**2916**	0.17	7000	0.14	71 ... 160	40500	46100	92300	106500	35000	14900

307 L — 330 — 15680 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**307L1**	**3.43**	438	5110	115	180 ... 250	8510	10600	21700	28600	5930	18600
	307L1	**4.09**	367	5260	115	180 ... 250	9030	11300	22900	30100	6290	21000
	307L1	**5.25**	286	5540	115	180 ... 250	9810	12300	24700	32500	6830	21000
	307L1	**6.23**	241	5750	115	180 ... 250	10400	13000	26000	34200	7230	21000
	307L2	**12.3**	122	7510	60	132 ... 200	13000	16300	31900	42000	9080	18600
	307L2	**14.7**	102	7730	60	132 ... 200	13800	17300	33600	44300	9640	21000
	307L2	**17.4**	86	8120	60	132 ... 200	14600	18300	35400	46500	10200	21000
	307L2	**21.8**	69	8690	60	132 ... 200	15800	19700	37900	49800	11000	21000
	307L2	**25.4**	59	9090	60	132 ... 200	16600	20700	39600	52100	11600	21000
	307L2	**28.0**	54	9150	55	132 ... 200	17100	21400	40800	53700	11900	21000
	307L2	**30.7**	49	9590	52	132 ... 200	17700	22100	41900	55200	12300	21000
	307L2	**32.6**	46	9410	48	132 ... 200	18000	22500	42700	56200	12600	21000
	307L2	**38.6**	39	8310	36	132 ... 200	19100	23900	44900	59100	13300	21000
	307L2	**46.7**	32	8360	29.9	132 ... 200	20300	25400	47600	62600	14200	21000
	307L3	**51.3**	29.3	10700	30	71 ... 160	21000	26200	48900	64300	14600	21000
	307L3	**60.5**	24.8	11100	30	71 ... 160	22200	27700	51400	67600	15400	21000
	307L3	**74.1**	20.2	11600	27.0	71 ... 160	23700	29600	54600	71900	16500	21000
	307L3	**80.6**	18.6	10200	21.8	71 ... 160	24400	30500	56000	73700	17000	21000
	307L3	**93.0**	16.1	12200	22.6	71 ... 160	25600	32000	58500	76900	17800	21000
	307L3	**100**	15.0	12400	21.3	71 ... 160	26200	32800	59800	78700	18300	21000
	307L3	**113**	13.2	10500	16.0	71 ... 160	27300	34100	62000	81600	19000	21000



307 L

330

15680 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**307L3**	**126**	11.9	13000	17.8	71 ... 160	28300	35400	64000	84200	19700	21000
	307L3	**139**	10.8	10700	13.3	71 ... 160	29200	36500	65900	86800	20400	21000
	307L3	**146**	10.3	13400	15.8	71 ... 160	29800	37200	67000	88100	20700	21000
	307L3	**162**	9.3	10800	11.6	71 ... 160	30000	37500	67500	88800	21400	21000
	307L3	**177**	8.5	12300	12.0	71 ... 160	30000	37500	67500	88800	22100	21000
	307L3	**202**	7.4	11000	9.4	71 ... 160	30000	37500	67500	88800	23100	21000
	307L3	**221**	6.8	12700	9.9	71 ... 160	30000	37500	67500	88800	23800	21000
	307L3	**239**	6.3	8700	6.3	71 ... 160	30000	37500	67500	88800	24400	21000
	307L3	**284**	5.3	11300	6.8	71 ... 160	30000	37500	67500	88800	25800	21000
	307L3	**336**	4.5	8840	4.5	71 ... 160	30500	38100	68600	90300	27300	21000
	307L4	**349**	4.3	14900	7.6	71 ... 160	30700	38300	69000	90700	27700	21000
	307L4	**406**	3.7	11900	5.2	71 ... 160	31300	39100	70500	92700	29100	21000
	307L4	**465**	3.2	12200	4.6	71 ... 160	31900	39900	71900	94500	30500	21000
	307L4	**509**	2.9	14000	4.9	71 ... 160	32400	40400	72800	95800	31400	21000
	307L4	**579**	2.6	14900	4.6	71 ... 160	33000	41200	74100	97500	32800	21000
	307L4	**654**	2.3	12900	3.5	71 ... 160	33500	41900	75400	99200	34100	21000
	307L4	**722**	2.1	15000	3.7	71 ... 160	34000	42500	76500	100700	35300	21000
	307L4	**801**	1.9	13300	3.0	71 ... 160	34500	43100	77700	102200	36500	21000
	307L4	**906**	1.7	15200	3.0	71 ... 160	35100	43900	79000	104000	38000	21000
	307L4	**999**	1.5	13800	2.5	71 ... 160	35600	44500	80200	105500	39300	21000
	307L4	**1157**	1.3	14200	2.2	71 ... 160	36400	45500	81900	107700	41300	21000
	307L4	**1274**	1.2	12300	1.7	71 ... 160	36900	46100	83000	109200	42600	21000
	307L4	**1408**	1.1	15600	2.0	71 ... 160	37400	46800	84200	110800	44100	21000
	307L4	**1591**	0.94	15000	1.7	71 ... 160	38100	47600	85700	112700	45000	21000
	307L4	**1767**	0.85	15700	1.6	71 ... 160	38600	48300	87000	114400	45000	21000
	307L4	**2041**	0.73	14300	1.2	71 ... 160	39500	49300	88800	116800	45000	21000
	307L4	**2423**	0.62	11000	0.81	71 ... 160	40400	50500	91000	119700	45000	21000
1000	**307L1**	**3.43**	292	5770	115	180 ... 250	9750	12200	24500	32300	6790	18600
	307L1	**4.09**	244	5940	115	180 ... 250	10300	12900	25900	34000	7200	21000
	307L1	**5.25**	190	6260	115	180 ... 250	11200	14000	27900	36700	7820	21000
	307L1	**6.23**	160	6500	113	180 ... 250	11900	14900	29400	38600	8280	21000
	307L2	**12.3**	81	8060	60	132 ... 200	14900	18700	36000	47400	10400	18600
	307L2	**14.7**	68	8720	60	132 ... 200	15800	19800	38000	50000	11000	21000
	307L2	**17.4**	58	9170	59	132 ... 200	16700	20900	39900	52500	11700	21000
	307L2	**21.8**	46	9740	50	132 ... 200	18100	22600	42800	56200	12600	21000
	307L2	**25.4**	39	10100	44	132 ... 200	19000	23700	44700	58800	13200	21000
	307L2	**28.0**	36	9630	38	132 ... 200	19600	24500	46100	60600	13700	21000
	307L2	**30.7**	33	10200	37	132 ... 200	20200	25300	47400	62300	14100	21000
	307L2	**32.6**	31	9760	33	132 ... 200	20600	25800	48200	63400	14400	21000
	307L2	**38.6**	25.9	8430	24.3	132 ... 200	21800	27300	50700	66800	15200	21000
	307L2	**46.7**	21.4	8480	20.2	132 ... 200	23300	29100	53700	70700	16200	21000
	307L3	**51.3**	19.5	11700	26.2	71 ... 160	24000	30000	55200	72700	16700	21000
	307L3	**60.5**	16.5	12100	23.0	71 ... 160	25400	31700	58100	76400	17700	21000
	307L3	**74.1**	13.5	12700	19.6	71 ... 160	27100	33900	61700	81200	18900	21000
	307L3	**80.6**	12.4	10600	15.1	71 ... 160	27900	34900	63300	83200	19400	21000
	307L3	**93.0**	10.8	13300	16.4	71 ... 160	29300	36600	66000	86900	20400	21000
	307L3	**100**	10.0	13500	15.5	71 ... 160	30000	37500	67500	88800	20900	21000
	307L3	**113**	8.8	10900	11.0	71 ... 160	30000	37500	67500	88800	21800	21000
	307L3	**126**	7.9	14000	12.7	71 ... 160	30000	37500	67500	88800	22600	21000
	307L3	**139**	7.2	11000	9.1	71 ... 160	30000	37500	67500	88800	23300	21000
	307L3	**146**	6.8	13800	10.8	71 ... 160	30000	37500	67500	88800	23700	21000
	307L3	**162**	6.2	11100	7.9	71 ... 160	30000	37500	67500	88800	24500	21000
	307L3	**177**	5.6	12300	8.0	71 ... 160	30000	37500	67500	88800	25300	21000
	307L3	**202**	5.0	11300	6.4	71 ... 160	30000	37500	67600	88900	26400	21000
	307L3	**221**	4.5	13000	6.8	71 ... 160	30400	38000	68500	90100	27200	21000
	307L3	**239**	4.2	8920	4.3	71 ... 160	30800	38500	69300	91100	27900	21000
	307L3	**284**	3.5	12000	4.8	71 ... 160	31500	39400	70900	93300	29600	21000
	307L3	**336**	3.0	9370	3.2	71 ... 160	32300	40400	72700	95700	31300	21000
	307L4	**349**	2.9	14900	5.0	71 ... 160	32500	40600	73100	96200	31700	21000
	307L4	**406**	2.5	12700	3.7	71 ... 160	33200	41500	74700	98200	33300	21000
	307L4	**465**	2.2	13000	3.3	71 ... 160	33800	42300	76100	100200	34900	21000

B



307 L

330

15680 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1000	**307L4**	**509**	2.0	14300	3.3	71 ... 160	34300	42900	77100	101500	35900	21000
	307L4	**579**	1.7	15200	3.1	71 ... 160	34900	43600	78600	103400	37500	21000
	307L4	**654**	1.5	13800	2.5	71 ... 160	35500	44400	79900	105200	39100	21000
	307L4	**722**	1.4	15400	2.5	71 ... 160	36000	45000	81100	106700	40400	21000
	307L4	**801**	1.2	14300	2.1	71 ... 160	36600	45700	82300	108300	41800	21000
	307L4	**906**	1.1	15600	2.0	71 ... 160	37200	46500	83800	110200	43500	21000
	307L4	**999**	1.0	14800	1.8	71 ... 160	37800	47200	84900	111700	45000	21000
	307L4	**1157**	0.86	14800	1.5	71 ... 160	38500	48200	86700	114100	45000	21000
	307L4	**1274**	0.78	12300	1.1	71 ... 160	39100	48900	87900	115700	45000	21000
	307L4	**1408**	0.71	15700	1.3	71 ... 160	39600	49600	89200	117400	45000	21000
	307L4	**1591**	0.63	15000	1.1	71 ... 160	40300	50400	90800	119400	45000	21000
	307L4	**1767**	0.57	15700	1.0	71 ... 160	41000	51200	92100	121200	45000	21000
	307L4	**2041**	0.49	14300	0.83	71 ... 160	41800	52300	94100	123700	45000	21000
	307L4	**2423**	0.41	11000	0.54	71 ... 160	42800	53600	96400	126800	45000	21000
500	**307L1**	**3.43**	146	7110	112	180 ... 250	12300	15300	30200	39700	8550	18600
	307L1	**4.09**	122	7320	97	180 ... 250	13000	16300	31900	41900	9070	21000
	307L1	**5.25**	95	7700	79	180 ... 250	14200	17700	34300	45200	9850	21000
	307L1	**6.23**	80	7720	67	180 ... 250	15000	18700	36100	47500	10400	21000
	307L2	**12.3**	41	8390	38	132 ... 200	18800	23500	44400	58400	13100	18600
	307L2	**14.7**	34	10400	39	132 ... 200	20000	25000	46800	61500	13900	21000
	307L2	**17.4**	28.8	10800	34	132 ... 200	21100	26400	49200	64700	14700	21000
	307L2	**21.8**	22.9	11300	28.8	132 ... 200	22800	28400	52600	69200	15800	21000
	307L2	**25.4**	19.7	11700	25.6	132 ... 200	23900	29900	55100	72400	16700	21000
	307L2	**28.0**	17.9	10200	20.4	132 ... 200	24700	30900	56700	74600	17200	21000
	307L2	**30.7**	16.3	11400	20.7	132 ... 200	25500	31900	58300	76700	17700	21000
	307L2	**32.6**	15.4	10400	17.7	132 ... 200	26000	32500	59300	78100	18100	21000
	307L2	**38.6**	12.9	8620	12.4	132 ... 200	27500	34400	62500	82200	19200	21000
	307L2	**46.7**	10.7	8680	10.3	132 ... 200	29300	36700	66100	87000	20400	21000
	307L3	**51.3**	9.8	13600	15.2	71 ... 160	30000	37500	67500	88800	21100	21000
	307L3	**60.5**	8.3	13900	13.2	71 ... 160	30000	37500	67500	88800	22300	21000
	307L3	**74.1**	6.7	14300	11.0	71 ... 160	30000	37500	67500	88800	23800	21000
	307L3	**80.6**	6.2	11100	7.9	71 ... 160	30000	37500	67500	88800	24500	21000
	307L3	**93.0**	5.4	14700	9.1	71 ... 160	30000	37500	67500	88800	25700	21000
	307L3	**100**	5.0	14900	8.5	71 ... 160	30000	37500	67500	88800	26300	21000
	307L3	**113**	4.4	11500	5.8	71 ... 160	30500	38200	68700	90400	27400	21000
	307L3	**126**	4.0	14900	6.8	71 ... 160	31000	38800	69800	91800	28400	21000
	307L3	**139**	3.6	11900	4.9	71 ... 160	31400	39300	70700	93100	29400	21000
	307L3	**146**	3.4	14000	5.5	71 ... 160	31700	39600	71300	93800	29900	21000
	307L3	**162**	3.1	12300	4.4	71 ... 160	32100	40200	72300	95100	30900	21000
	307L3	**177**	2.8	12300	4.0	71 ... 160	32500	40700	73200	96300	31800	21000
	307L3	**202**	2.5	12700	3.6	71 ... 160	33200	41500	74600	98200	33200	21000
	307L3	**221**	2.3	13900	3.6	71 ... 160	33600	42000	75600	99400	34300	21000
	307L3	**239**	2.1	9860	2.4	71 ... 160	34000	42500	76500	100600	35200	21000
	307L3	**284**	1.8	13300	2.7	71 ... 160	34800	43500	78300	103100	37200	21000
	307L3	**336**	1.5	10400	1.8	71 ... 160	35700	44600	80300	105600	39400	21000
	307L4	**349**	1.4	15400	2.6	71 ... 160	35900	44800	80700	106200	39900	21000
	307L4	**406**	1.2	14300	2.1	71 ... 160	36600	45800	82400	108500	42000	21000
	307L4	**465**	1.1	14700	1.9	71 ... 160	37400	46700	84100	110600	43900	21000
	307L4	**509**	0.98	15000	1.7	71 ... 160	37900	47300	85200	112000	45000	21000
	307L4	**579**	0.86	15700	1.6	71 ... 160	38600	48200	86700	114100	45000	21000
	307L4	**654**	0.77	14800	1.3	71 ... 160	39200	49000	88300	116100	45000	21000
	307L4	**722**	0.69	15700	1.3	71 ... 160	39800	49700	89500	117800	45000	21000
	307L4	**801**	0.62	14800	1.1	71 ... 160	40400	50500	90900	119500	45000	21000
	307L4	**906**	0.55	15700	1.0	71 ... 160	41100	51400	92500	121700	45000	21000
	307L4	**999**	0.50	14800	0.88	71 ... 160	41700	52100	93800	123400	45000	21000
	307L4	**1157**	0.43	14800	0.76	71 ... 160	42600	53200	95800	126000	45000	21000
	307L4	**1274**	0.39	12300	0.57	71 ... 160	43200	53900	97100	127700	45000	21000
	307L4	**1408**	0.36	15700	0.66	71 ... 160	43800	54700	98500	129600	45000	21000
	307L4	**1591**	0.31	15000	0.56	71 ... 160	44500	55700	100200	131800	45000	21000
	307L4	**1767**	0.28	15700	0.52	71 ... 160	45200	56500	101700	133800	45000	21000
	307L4	**2041**	0.24	14300	0.42	71 ... 160	46200	57700	103900	136600	45000	21000
	307L4	**2423**	0.21	11000	0.27	71 ... 160	47300	59100	106400	140000	45000	21000



309 L

342

23240 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**309L1**	**3.43**	438	7010	150	180 ... 250	—	—	22200	28600	4740	27900
	309L1	**4.09**	367	7220	150	180 ... 250	—	—	23400	30100	5030	29000
	309L1	**5.25**	286	7600	150	180 ... 250	—	—	25200	32500	5470	29000
	309L1	**6.23**	241	7900	150	180 ... 250	—	—	26600	34200	5790	29000
	309L2	**12.3**	122	7890	60	132 ... 200	—	—	32600	42000	7270	27900
	309L2	**14.7**	102	9410	60	132 ... 200	—	—	34400	44300	7710	29000
	309L2	**17.4**	86	9730	60	132 ... 200	—	—	36100	46500	8150	29000
	309L2	**21.8**	69	10100	60	132 ... 200	—	—	38700	49800	8790	29000
	309L2	**25.4**	59	10500	60	132 ... 200	—	—	40500	52100	9240	29000
	309L2	**28.0**	54	12500	60	132 ... 200	—	—	41700	53700	9550	29000
	309L2	**32.6**	46	13000	60	132 ... 200	—	—	43600	56200	10000	29000
	309L2	**38.6**	39	12500	54	132 ... 200	—	—	45900	59100	10600	29000
	309L2	**46.7**	32	12500	45	132 ... 200	—	—	48600	62600	11300	29000
	309L3	**51.3**	29.3	13400	30	71 ... 160	—	—	50000	64300	11700	29000
	309L3	**60.5**	24.8	14100	30	71 ... 160	—	—	52500	67600	12300	29000
	309L3	**74.1**	20.2	15000	30	71 ... 160	—	—	55800	71900	13200	29000
	309L3	**80.6**	18.6	14800	30	71 ... 160	—	—	57300	73700	13600	29000
	309L3	**93.0**	16.1	15100	27.9	71 ... 160	—	—	59800	76900	14200	29000
	309L3	**100**	15.0	16500	28.3	71 ... 160	—	—	61200	78700	14600	29000
	309L3	**113**	13.2	15500	23.6	71 ... 160	—	—	63400	81600	15200	29000
	309L3	**126**	11.9	16400	22.4	71 ... 160	—	—	65500	84200	15800	29000
	309L3	**139**	10.8	16000	19.9	71 ... 160	—	—	67400	86800	16300	29000
	309L3	**162**	9.3	16300	17.3	71 ... 160	—	—	69000	88800	17100	29000
	309L3	**183**	8.2	14300	13.5	71 ... 160	—	—	69000	88800	17800	29000
	309L3	**202**	7.4	16500	14.1	71 ... 160	—	—	69000	88800	18400	29000
	309L3	**223**	6.7	13000	10.0	71 ... 160	—	—	69000	88800	19100	29000
	309L3	**239**	6.3	13000	9.4	71 ... 160	—	—	69000	88800	19500	29000
	309L3	**284**	5.3	15700	9.6	71 ... 160	—	—	69000	88800	20700	29000
	309L3	**336**	4.5	13200	6.8	71 ... 160	—	—	70100	90300	21900	29000
	309L4	**349**	4.3	21300	10.8	71 ... 160	—	—	70500	90700	22100	29000
	309L4	**406**	3.7	17800	7.8	71 ... 160	—	—	72000	92700	23300	29000
	309L4	**465**	3.2	18300	7.0	71 ... 160	—	—	73500	94500	24400	29000
	309L4	**509**	2.9	14300	5.0	71 ... 160	—	—	74400	95800	25100	29000
	309L4	**579**	2.6	21300	6.5	71 ... 160	—	—	75800	97500	26200	29000
	309L4	**654**	2.3	18100	4.9	71 ... 160	—	—	77100	99200	27300	29000
	309L4	**722**	2.1	21300	5.2	71 ... 160	—	—	78200	100700	28200	29000
	309L4	**801**	1.9	18200	4.0	71 ... 160	—	—	79400	102200	29200	29000
	309L4	**906**	1.7	17900	3.5	71 ... 160	—	—	80800	104000	30400	29000
	309L4	**999**	1.5	18200	3.2	71 ... 160	—	—	81900	105500	31400	29000
	309L4	**1149**	1.3	16200	2.5	71 ... 160	—	—	83600	107600	32900	29000
	309L4	**1286**	1.2	16500	2.3	71 ... 160	—	—	84900	109300	34200	29000
	309L4	**1380**	1.1	16700	2.2	71 ... 160	—	—	85800	110400	35000	29000
	309L4	**1605**	0.93	17000	1.9	71 ... 160	—	—	87700	112800	36000	29000
	309L4	**1723**	0.87	17000	1.8	71 ... 160	—	—	88600	114000	36000	29000
	309L4	**2003**	0.75	17000	1.5	71 ... 160	—	—	90500	116500	36000	29000
	309L4	**2423**	0.62	17000	1.2	71 ... 160	—	—	93000	119700	36000	29000
1000	**309L1**	**3.43**	292	7920	150	180 ... 250	—	—	25100	32300	5430	27900
	309L1	**4.09**	244	8150	150	180 ... 250	—	—	26400	34000	5760	29000
	309L1	**5.25**	190	8580	150	180 ... 250	—	—	28500	36700	6260	29000
	309L1	**6.23**	160	8920	150	180 ... 250	—	—	30000	38600	6620	29000
	309L2	**12.3**	81	8900	60	132 ... 200	—	—	36800	47400	8320	27900
	309L2	**14.7**	68	10600	60	132 ... 200	—	—	38800	50000	8820	29000
	309L2	**17.4**	58	11000	60	132 ... 200	—	—	40800	52500	9330	29000
	309L2	**21.8**	46	11400	58	132 ... 200	—	—	43700	56200	10100	29000
	309L2	**25.4**	39	11500	50	132 ... 200	—	—	45700	58800	10600	29000
	309L2	**28.0**	36	13500	53	132 ... 200	—	—	47100	60600	10900	29000
	309L2	**32.6**	31	13800	47	132 ... 200	—	—	49300	63400	11500	29000
	309L2	**38.6**	25.9	12600	36	132 ... 200	—	—	51900	66800	12200	29000
	309L2	**46.7**	21.4	12700	30	132 ... 200	—	—	54900	70700	13000	29000

B



309 L

342

23240 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1000	**309L3**	**51.3**	19.5	14900	30	71 ... 160	—	—	56500	72700	13400	29000
	309L3	**60.5**	16.5	16000	30	71 ... 160	—	—	59300	76400	14100	29000
	309L3	**74.1**	13.5	17000	26.3	71 ... 160	—	—	63100	81200	15100	29000
	309L3	**80.6**	12.4	15700	22.3	71 ... 160	—	—	64700	83200	15500	29000
	309L3	**93.0**	10.8	16800	20.7	71 ... 160	—	—	67500	86900	16300	29000
	309L3	**100**	10.0	18600	21.3	71 ... 160	—	—	69000	88800	16700	29000
	309L3	**113**	8.8	16300	16.5	71 ... 160	—	—	69000	88800	17400	29000
	309L3	**126**	7.9	17300	15.7	71 ... 160	—	—	69000	88800	18000	29000
	309L3	**139**	7.2	16500	13.7	71 ... 160	—	—	69000	88800	18600	29000
	309L3	**162**	6.2	16700	11.9	71 ... 160	—	—	69000	88800	19600	29000
	309L3	**183**	5.5	14300	9.0	71 ... 160	—	—	69000	88800	20400	29000
	309L3	**202**	5.0	17000	9.7	71 ... 160	—	—	69100	88900	21100	29000
	309L3	**223**	4.5	13200	6.8	71 ... 160	—	—	70100	90200	21800	29000
	309L3	**239**	4.2	13300	6.4	71 ... 160	—	—	70800	91100	22300	29000
	309L3	**284**	3.5	15800	6.4	71 ... 160	—	—	72500	93300	23600	29000
	309L3	**336**	3.0	14000	4.8	71 ... 160	—	—	74300	95700	25000	29000
	309L4	**349**	2.9	21300	7.2	71 ... 160	—	—	74700	96200	25300	29000
	309L4	**406**	2.5	19100	5.6	71 ... 160	—	—	76300	98200	26600	29000
	309L4	**465**	2.2	19500	5.0	71 ... 160	—	—	77800	100200	27900	29000
	309L4	**509**	2.0	14400	3.3	71 ... 160	—	—	78900	101500	28700	29000
	309L4	**579**	1.7	21400	4.4	71 ... 160	—	—	80300	103400	30000	29000
	309L4	**654**	1.5	18200	3.3	71 ... 160	—	—	81700	105200	31200	29000
	309L4	**722**	1.4	21500	3.5	71 ... 160	—	—	82900	106700	32300	29000
	309L4	**801**	1.2	18300	2.7	71 ... 160	—	—	84100	108300	33400	29000
	309L4	**906**	1.1	18400	2.4	71 ... 160	—	—	85600	110200	34800	29000
	309L4	**999**	1.0	18300	2.2	71 ... 160	—	—	86800	111700	36000	29000
	309L4	**1149**	0.87	17000	1.7	71 ... 160	—	—	88600	114000	36000	29000
	309L4	**1286**	0.78	17000	1.6	71 ... 160	—	—	90000	115800	36000	29000
	309L4	**1380**	0.72	17000	1.5	71 ... 160	—	—	90900	117000	36000	29000
	309L4	**1605**	0.62	17000	1.3	71 ... 160	—	—	92900	119600	36000	29000
	309L4	**1723**	0.58	17000	1.2	71 ... 160	—	—	93900	120800	36000	29000
	309L4	**2003**	0.50	17000	1.0	71 ... 160	—	—	95900	123400	36000	29000
	309L4	**2423**	0.41	17000	0.83	71 ... 160	—	—	98500	126800	36000	29000
500	**309L1**	**3.43**	146	9750	150	180 ... 250	—	—	30900	39700	6840	27900
	309L1	**4.09**	122	10000	132	180 ... 250	—	—	32600	41900	7250	29000
	309L1	**5.25**	95	10600	109	180 ... 250	—	—	35100	45200	7880	29000
	309L1	**6.23**	80	10900	94	180 ... 250	—	—	36900	47500	8350	29000
	309L2	**12.3**	41	10600	48	132 ... 200	—	—	45400	58400	10500	27900
	309L2	**14.7**	34	12900	49	132 ... 200	—	—	47800	61500	11100	29000
	309L2	**17.4**	28.8	13500	43	132 ... 200	—	—	50300	64700	11800	29000
	309L2	**21.8**	22.9	13700	35	132 ... 200	—	—	53800	69200	12700	29000
	309L2	**25.4**	19.7	12800	28.2	132 ... 200	—	—	56300	72400	13300	29000
	309L2	**28.0**	17.9	14900	29.6	132 ... 200	—	—	58000	74600	13800	29000
	309L2	**32.6**	15.4	15200	26.0	132 ... 200	—	—	60700	78100	14500	29000
	309L2	**38.6**	12.9	12900	18.6	132 ... 200	—	—	63900	82200	15300	29000
	309L2	**46.7**	10.7	13000	15.4	132 ... 200	—	—	67600	87000	16300	29000
	309L3	**51.3**	9.8	17700	19.8	71 ... 160	—	—	69000	88800	16800	29000
	309L3	**60.5**	8.3	19300	18.3	71 ... 160	—	—	69000	88800	17800	29000
	309L3	**74.1**	6.7	20100	15.5	71 ... 160	—	—	69000	88800	19100	29000
	309L3	**80.6**	6.2	16700	11.9	71 ... 160	—	—	69000	88800	19600	29000
	309L3	**93.0**	5.4	17500	10.8	71 ... 160	—	—	69000	88800	20600	29000
	309L3	**100**	5.0	21300	12.2	71 ... 160	—	—	69000	88800	21100	29000
	309L3	**113**	4.4	17100	8.7	71 ... 160	—	—	70200	90400	21900	29000
	309L3	**126**	4.0	17500	8.0	71 ... 160	—	—	71300	91800	22700	29000
	309L3	**139**	3.6	17500	7.2	71 ... 160	—	—	72300	93100	23500	29000
	309L3	**162**	3.1	18400	6.5	71 ... 160	—	—	73900	95100	24700	29000
	309L3	**183**	2.7	14300	4.5	71 ... 160	—	—	75200	96800	25700	29000
	309L3	**202**	2.5	19100	5.4	71 ... 160	—	—	76300	98200	26600	29000
	309L3	**223**	2.2	14700	3.8	71 ... 160	—	—	77400	99600	27500	29000
	309L3	**239**	2.1	14900	3.6	71 ... 160	—	—	78200	100600	28200	29000
	309L3	**284**	1.8	15800	3.2	71 ... 160	—	—	80100	103100	29800	29000

B



309 L

342

23240 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
500	**309L3**	**336**	1.5	15800	2.7	71 ... 160	—	—	82100	105600	31500	29000
	309L4	**349**	1.4	21500	3.6	71 ... 160	—	—	82500	106200	31900	29000
	309L4	**406**	1.2	21300	3.1	71 ... 160	—	—	84300	108500	33600	29000
	309L4	**465**	1.1	21700	2.8	71 ... 160	—	—	85900	110600	35100	29000
	309L4	**509**	0.98	14700	1.7	71 ... 160	—	—	87100	112000	36000	29000
	309L4	**579**	0.86	21600	2.2	71 ... 160	—	—	88700	114100	36000	29000
	309L4	**654**	0.77	18300	1.7	71 ... 160	—	—	90200	116100	36000	29000
	309L4	**722**	0.69	21600	1.8	71 ... 160	—	—	91500	117800	36000	29000
	309L4	**801**	0.62	18300	1.4	71 ... 160	—	—	92900	119500	36000	29000
	309L4	**906**	0.55	18500	1.2	71 ... 160	—	—	94500	121700	36000	29000
	309L4	**999**	0.50	18300	1.1	71 ... 160	—	—	95900	123400	36000	29000
	309L4	**1149**	0.44	17000	0.87	71 ... 160	—	—	97800	125900	36000	29000
	309L4	**1286**	0.39	17000	0.78	71 ... 160	—	—	99400	127900	36000	29000
	309L4	**1380**	0.36	17000	0.73	71 ... 160	—	—	100400	129200	36000	29000
	309L4	**1605**	0.31	17000	0.63	71 ... 160	—	—	102600	132000	36000	29000
	309L4	**1723**	0.29	17000	0.58	71 ... 160	—	—	103600	133400	36000	29000
	309L4	**2003**	0.25	17000	0.50	71 ... 160	—	—	105900	136300	36000	29000
	309L4	**2423**	0.21	17000	0.42	71 ... 160	—	—	108800	140000	36000	29000

310M L

354

33640 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**310ML1**	**4.09**	367	11700	175	200 ... 250	—	—	26500	33600	9080	47600
	310ML1	**5.25**	286	12300	175	200 ... 250	—	—	28500	36200	9870	47600
	310ML1	**6.23**	241	12800	175	200 ... 250	—	—	30000	38100	10400	47600
	310ML2	**14.7**	102	14900	75	160 ... 250	—	—	38900	49300	13900	47600
	310ML2	**17.4**	86	15400	75	160 ... 250	—	—	40900	51800	14700	47600
	310ML2	**21.8**	69	16100	75	160 ... 250	—	—	43700	55500	15900	47600
	310ML2	**25.4**	59	16700	75	160 ... 250	—	—	45800	58000	16700	47600
	310ML2	**28**	54	20300	75	160 ... 250	—	—	47100	59800	17200	47600
	310ML2	**30.7**	49	17100	75	160 ... 250	—	—	48500	61400	17800	47600
	310ML2	**32.6**	46	20800	75	160 ... 250	—	—	49300	62500	18100	47600
	310ML2	**38.6**	39	17800	75	160 ... 250	—	—	51900	65800	19200	47600
	310ML2	**46.7**	32	17800	64	160 ... 250	—	—	55000	69700	20500	47600
	310ML3	**53**	28.3	19100	40	132 ... 200	—	—	57100	72400	21300	47600
	310ML3	**62.6**	24.0	19800	40	132 ... 200	—	—	60000	76100	22500	47600
	310ML3	**73.9**	20.3	22300	40	132 ... 200	—	—	63100	80000	23800	47600
	310ML3	**80.3**	18.7	20600	40	132 ... 200	—	—	64700	82000	24500	47600
	310ML3	**92.7**	16.2	23200	40	132 ... 200	—	—	67500	85600	25700	47600
	310ML3	**101**	14.9	20800	36	132 ... 200	—	—	69200	87800	26400	47600
	310ML3	**108**	13.9	24300	39	132 ... 200	—	—	70600	89600	27000	47600
	310ML3	**119**	12.6	21500	31	132 ... 200	—	—	72800	92300	27900	47600
	310ML3	**135**	11.1	25800	33	132 ... 200	—	—	75600	95900	29100	47600
	310ML3	**149**	10.0	21700	25	132 ... 200	—	—	77900	98800	30100	47600
	310ML3	**164**	9.2	26600	27.9	132 ... 200	—	—	78000	98900	31100	47600
	310ML3	**177**	8.5	17900	17.3	132 ... 200	—	—	78000	98900	31900	47600
	310ML3	**202**	7.4	22100	18.8	132 ... 200	—	—	78000	98900	33300	47600
	310ML3	**230**	6.5	19300	14.5	132 ... 200	—	—	78000	98900	34800	47600
	310ML3	**249**	6.0	17900	12.4	132 ... 200	—	—	78000	98900	35700	47600
	310ML3	**295**	5.1	22700	13.2	132 ... 200	—	—	78000	98900	37800	47600
	310ML3	**350**	4.3	18500	9.1	132 ... 200	—	—	79800	101100	40000	47600
	310ML4	**392**	3.8	18900	8.5	71 ... 160	—	—	81000	102700	41500	47600
	310ML4	**453**	3.3	29000	11.3	71 ... 160	—	—	82700	104900	43600	47600
	310ML4	**507**	3.0	24900	8.7	71 ... 160	—	—	84100	106600	45300	47600
	310ML4	**590**	2.5	25600	7.7	71 ... 160	—	—	85900	108900	47600	47600
	310ML4	**637**	2.4	25900	7.2	71 ... 160	—	—	86900	110100	48800	47600
	310ML4	**726**	2.1	26500	6.5	71 ... 160	—	—	88500	112200	51000	47600



310M L

354

33640 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**310ML4**	**798**	1.9	27000	6.0	71 ... 160	—	—	89700	113700	52700	47600
	310ML4	**974**	1.5	32000	5.8	71 ... 160	—	—	92300	117000	56300	47600
	310ML4	**1002**	1.5	28100	5.0	71 ... 160	—	—	92700	117500	56800	47600
	310ML4	**1164**	1.3	28800	4.4	71 ... 160	—	—	94700	120000	59700	47600
	310ML4	**1259**	1.2	24800	3.5	71 ... 160	—	—	95700	121400	61300	47600
	310ML4	**1438**	1.0	23800	2.9	71 ... 160	—	—	97600	123700	64100	47600
	310ML4	**1672**	0.90	23900	2.5	71 ... 160	—	—	99700	126400	65000	47600
	310ML4	**1794**	0.84	23900	2.4	71 ... 160	—	—	100700	127700	65000	47600
	310ML4	**2022**	0.74	23900	2.1	71 ... 160	—	—	102400	129900	65000	47600
	310ML4	**2523**	0.59	23900	1.7	71 ... 160	—	—	105700	134100	65000	47600
1000	**310ML1**	**4.09**	244	13200	175	200 ... 250	—	—	29900	37900	10400	47600
	310ML1	**5.25**	190	13900	175	200 ... 250	—	—	32200	40900	11300	47600
	310ML1	**6.23**	160	14400	175	200 ... 250	—	—	33900	43000	12000	47600
	310ML2	**14.7**	68	16800	75	160 ... 250	—	—	43900	55700	15900	47600
	310ML2	**17.4**	58	17400	75	160 ... 250	—	—	46100	58500	16800	47600
	310ML2	**21.8**	46	18100	75	160 ... 250	—	—	49400	62600	18200	47600
	310ML2	**25.4**	39	18500	75	160 ... 250	—	—	51700	65500	19100	47600
	310ML2	**28**	36	20900	75	160 ... 250	—	—	53200	67500	19700	47600
	310ML2	**30.7**	33	17700	64	160 ... 250	—	—	54700	69400	20300	47600
	310ML2	**32.6**	31	21000	72	160 ... 250	—	—	55700	70600	20800	47600
	310ML2	**38.6**	25.9	17800	51	160 ... 250	—	—	58600	74300	22000	47600
	310ML2	**46.7**	21.4	17800	42	160 ... 250	—	—	62100	78700	23400	47600
	310ML3	**53**	18.9	21600	40	132 ... 200	—	—	64500	81800	24400	47600
	310ML3	**62.6**	16.0	22400	40	132 ... 200	—	—	67800	85900	25800	47600
	310ML3	**73.9**	13.5	24600	38	132 ... 200	—	—	71200	90300	27300	47600
	310ML3	**80.3**	12.4	21300	30	132 ... 200	—	—	73000	92600	28000	47600
	310ML3	**92.7**	10.8	25700	32	132 ... 200	—	—	76300	96700	29400	47600
	310ML3	**101**	9.9	21700	24.7	132 ... 200	—	—	78000	98900	30300	47600
	310ML3	**108**	9.3	26700	28.4	132 ... 200	—	—	78000	98900	30900	47600
	310ML3	**119**	8.4	21900	21.1	132 ... 200	—	—	78000	98900	32000	47600
	310ML3	**135**	7.4	27700	23.5	132 ... 200	—	—	78000	98900	33400	47600
	310ML3	**149**	6.7	22300	17.1	132 ... 200	—	—	78000	98900	34500	47600
	310ML3	**164**	6.1	27000	18.9	132 ... 200	—	—	78000	98900	35600	47600
	310ML3	**177**	5.6	18000	11.6	132 ... 200	—	—	78000	98900	36500	47600
	310ML3	**202**	5.0	22700	12.9	132 ... 200	—	—	78100	99000	38100	47600
	310ML3	**230**	4.3	19300	9.6	132 ... 200	—	—	79600	100900	39800	47600
	310ML3	**249**	4.0	18700	8.6	132 ... 200	—	—	80500	102100	40900	47600
	310ML3	**295**	3.4	23900	9.3	132 ... 200	—	—	82500	104600	43300	47600
	310ML3	**350**	2.9	19900	6.5	132 ... 200	—	—	84500	107200	45800	47600
	310ML4	**392**	2.6	20300	6.1	71 ... 160	—	—	85900	108900	47600	47600
	310ML4	**453**	2.2	29000	7.6	71 ... 160	—	—	87700	111200	49900	47600
	310ML4	**507**	2.0	26700	6.2	71 ... 160	—	—	89100	113000	51800	47600
	310ML4	**590**	1.7	27400	5.5	71 ... 160	—	—	91000	115400	54500	47600
	310ML4	**637**	1.6	27800	5.2	71 ... 160	—	—	92000	116700	55900	47600
	310ML4	**726**	1.4	28500	4.6	71 ... 160	—	—	93800	118900	58400	47600
	310ML4	**798**	1.3	28900	4.3	71 ... 160	—	—	95100	120500	60300	47600
	310ML4	**974**	1.0	33100	4.0	71 ... 160	—	—	97800	124000	64400	47600
	310ML4	**1002**	1.0	30100	3.6	71 ... 160	—	—	98200	124500	65000	47600
	310ML4	**1164**	0.86	30100	3.1	71 ... 160	—	—	100300	127200	65000	47600
	310ML4	**1259**	0.79	24800	2.3	71 ... 160	—	—	101400	128600	65000	47600
	310ML4	**1438**	0.70	23900	2.0	71 ... 160	—	—	103400	131100	65000	47600
	310ML4	**1672**	0.60	23900	1.7	71 ... 160	—	—	105600	133900	65000	47600
	310ML4	**1794**	0.56	23900	1.6	71 ... 160	—	—	106700	135300	65000	47600
	310ML4	**2022**	0.49	23900	1.4	71 ... 160	—	—	108600	137600	65000	47600
	310ML4	**2523**	0.40	23900	1.1	71 ... 160	—	—	112000	142100	65000	47600
500	**310ML1**	**4.09**	122	16200	175	200 ... 250	—	—	36800	46700	13100	47600
	310ML1	**5.25**	95	17100	175	200 ... 250	—	—	39700	50300	14200	47600
	310ML1	**6.23**	80	17000	147	200 ... 250	—	—	41800	53000	15100	47600
	310ML2	**14.7**	34	20100	75	160 ... 250	—	—	54100	68500	20100	47600

B



310M L

354

33640 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
500	**310ML2**	**17.4**	28.8	20700	66	160 ... 250	—	—	56800	72000	21200	47600
	310ML2	**21.8**	22.9	21500	55	160 ... 250	—	—	60800	77100	22900	47600
	310ML2	**25.4**	19.7	21500	47	160 ... 250	—	—	63600	80700	24100	47600
	310ML2	**28**	17.9	21300	42	160 ... 250	—	—	65500	83100	24900	47600
	310ML2	**30.7**	16.3	18600	34	160 ... 250	—	—	67400	85400	25600	47600
	310ML2	**32.6**	15.4	21400	37	160 ... 250	—	—	68600	87000	26100	47600
	310ML2	**38.6**	12.9	17800	25.7	160 ... 250	—	—	72200	91500	27700	47600
	310ML2	**46.7**	10.7	17800	21.2	160 ... 250	—	—	76400	96900	29500	47600
	310ML3	**53**	9.4	26400	28.6	132 ... 200	—	—	78000	98900	30800	47600
	310ML3	**62.6**	8.0	26900	24.6	132 ... 200	—	—	78000	98900	32500	47600
	310ML3	**73.9**	6.8	28100	21.8	132 ... 200	—	—	78000	98900	34400	47600
	310ML3	**80.3**	6.2	22400	16.0	132 ... 200	—	—	78000	98900	35300	47600
	310ML3	**92.7**	5.4	29000	17.9	132 ... 200	—	—	78000	98900	37100	47600
	310ML3	**101**	5.0	22700	12.9	132 ... 200	—	—	78100	99000	38100	47600
	310ML3	**108**	4.6	28100	14.9	132 ... 200	—	—	78800	100000	39000	47600
	310ML3	**119**	4.2	23400	11.3	132 ... 200	—	—	80000	101400	40300	47600
	310ML3	**135**	3.7	29900	12.7	132 ... 200	—	—	81400	103300	42000	47600
	310ML3	**149**	3.3	24400	9.4	132 ... 200	—	—	82600	104700	43400	47600
	310ML3	**164**	3.1	27200	9.5	132 ... 200	—	—	83700	106100	44800	47600
	310ML3	**177**	2.8	19900	6.4	132 ... 200	—	—	84600	107300	46000	47600
	310ML3	**202**	2.5	25700	7.3	132 ... 200	—	—	86200	109300	48000	47600
	310ML3	**230**	2.2	19400	4.8	132 ... 200	—	—	87900	111400	50200	47600
	310ML3	**249**	2.0	21200	4.9	132 ... 200	—	—	88900	112700	51500	47600
	310ML3	**295**	1.7	24800	4.8	132 ... 200	—	—	91000	115400	54500	47600
	310ML3	**350**	1.4	22500	3.7	132 ... 200	—	—	93300	118300	57700	47600
	310ML4	**392**	1.3	22900	3.5	71 ... 160	—	—	94800	120200	59900	47600
	310ML4	**453**	1.1	29000	3.8	71 ... 160	—	—	96800	122700	62900	47600
	310ML4	**507**	0.99	30100	3.5	71 ... 160	—	—	98400	124700	65000	47600
	310ML4	**590**	0.85	30100	3.0	71 ... 160	—	—	100500	127400	65000	47600
	310ML4	**637**	0.79	30100	2.8	71 ... 160	—	—	101600	128800	65000	47600
	310ML4	**726**	0.69	30100	2.5	71 ... 160	—	—	103500	131300	65000	47600
	310ML4	**798**	0.63	30100	2.2	71 ... 160	—	—	104900	133100	65000	47600
	310ML4	**974**	0.51	33200	2.0	71 ... 160	—	—	108000	136900	65000	47600
	310ML4	**1002**	0.50	30100	1.8	71 ... 160	—	—	108400	137500	65000	47600
	310ML4	**1164**	0.43	30100	1.5	71 ... 160	—	—	110800	140400	65000	47600
	310ML4	**1259**	0.40	24800	1.2	71 ... 160	—	—	112000	142000	65000	47600
	310ML4	**1438**	0.35	23900	0.98	71 ... 160	—	—	114200	144700	65000	47600
	310ML4	**1672**	0.30	23900	0.85	71 ... 160	—	—	116600	147900	65000	47600
	310ML4	**1794**	0.28	23900	0.79	71 ... 160	—	—	117800	149400	65000	47600
	310ML4	**2022**	0.25	23900	0.70	71 ... 160	—	—	119800	152000	65000	47600
	310ML4	**2523**	0.20	23900	0.56	71 ... 160	—	—	123700	156800	65000	47600

311M L

366

49210 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**311ML1**	**4.09**	367	16600	200	200 ... 250	—	—	33300	42400	9080	58300
	311ML1	**5.25**	286	17500	200	200 ... 250	—	—	35800	45700	9870	58300
	311ML1	**6.23**	241	18200	200	200 ... 250	—	—	37700	48100	10400	58300
	311ML2	**14.0**	107	20300	115	180 ... 250	—	—	48100	61400	13700	58300
	311ML2	**16.7**	90	20900	115	180 ... 250	—	—	50800	64700	14500	58300
	311ML2	**18.0**	83	25300	115	180 ... 250	—	—	51900	66200	14900	58300
	311ML2	**21.5**	70	20800	115	180 ... 250	—	—	54700	69800	15800	58300
	311ML2	**25.5**	59	22800	115	180 ... 250	—	—	57600	73400	16700	58300
	311ML2	**27.6**	54	28200	115	180 ... 250	—	—	59000	75200	17200	58300
	311ML2	**32.7**	46	28900	115	180 ... 250	—	—	62100	79200	18200	58300
	311ML2	**38.8**	39	27200	115	180 ... 250	—	—	65300	83300	19200	58300
	311ML3	**50.5**	29.7	27600	60	132 ... 200	—	—	70700	90200	21000	58300



311M L

366

49210 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**311ML3**	**60.2**	24.9	30700	60	132 ... 200	—	—	74500	95100	22300	58300
	311ML3	**71.1**	21.1	32200	60	132 ... 200	—	—	78300	99900	23500	58300
	311ML3	**77.3**	19.4	32600	60	132 ... 200	—	—	80300	100000	24200	58300
	311ML3	**89.3**	16.8	34500	60	132 ... 200	—	—	83900	100000	25400	58300
	311ML3	**104**	14.5	36100	60	132 ... 200	—	—	87700	100000	26700	58300
	311ML3	**115**	13.1	34000	51	132 ... 200	—	—	90400	100000	27600	58300
	311ML3	**133**	11.3	34600	45	132 ... 200	—	—	94600	100000	29000	58300
	311ML3	**147**	10.2	34900	41	132 ... 200	—	—	97400	100000	30000	58300
	311ML3	**161**	9.3	35200	38	132 ... 200	—	—	98000	100000	30900	58300
	311ML3	**171**	8.8	35300	36	132 ... 200	—	—	98000	100000	31500	58300
	311ML3	**191**	7.8	32000	28.8	132 ... 200	—	—	98000	100000	32700	58300
	311ML3	**203**	7.4	35700	30	132 ... 200	—	—	98000	100000	33400	58300
	311ML3	**245**	6.1	36200	25.4	132 ... 200	—	—	98000	100000	35500	58300
	311ML3	**291**	5.2	27500	16.2	132 ... 200	—	—	98000	100000	37600	58300
	311ML4	**348**	4.3	45700	23.3	71 ... 160	—	—	100100	102100	39900	58300
	311ML4	**410**	3.7	46000	19.9	71 ... 160	—	—	102500	104600	42200	58300
	311ML4	**512**	2.9	46300	16.0	71 ... 160	—	—	105800	107900	45400	58300
	311ML4	**568**	2.6	41000	12.8	71 ... 160	—	—	107300	109500	47000	58300
	311ML4	**627**	2.4	41700	11.8	71 ... 160	—	—	108900	111100	48600	58300
	311ML4	**825**	1.8	43500	9.4	71 ... 160	—	—	113200	115500	53300	58300
	311ML4	**986**	1.5	44800	8.1	71 ... 160	—	—	116200	118500	56500	58300
	311ML4	**1058**	1.4	45300	7.6	71 ... 160	—	—	117300	119700	57900	58300
	311ML4	**1230**	1.2	46300	6.7	71 ... 160	—	—	119900	122300	60800	58300
	311ML4	**1415**	1.1	41200	5.2	71 ... 160	—	—	122300	124800	63800	58300
	311ML4	**1680**	0.89	36500	3.9	71 ... 160	—	—	125300	127900	65000	58300
	311ML4	**1766**	0.85	41300	4.1	71 ... 160	—	—	126200	128800	65000	58300
	311ML4	**2096**	0.72	36500	3.1	71 ... 160	—	—	129400	132000	65000	58300
1000	**311ML1**	**4.09**	244	18800	200	200 ... 250	—	—	37600	47900	10400	58300
	311ML1	**5.25**	190	19700	200	200 ... 250	—	—	40500	51600	11300	58300
	311ML1	**6.23**	160	20500	200	200 ... 250	—	—	42600	54400	12000	58300
	311ML2	**14.0**	71	22900	115	180 ... 250	—	—	54400	69300	15700	58300
	311ML2	**16.7**	60	23600	115	180 ... 250	—	—	57300	73100	16600	58300
	311ML2	**18.0**	56	28600	115	180 ... 250	—	—	58600	74700	17000	58300
	311ML2	**21.5**	47	23500	115	180 ... 250	—	—	61800	78800	18100	58300
	311ML2	**25.5**	39	25100	109	180 ... 250	—	—	65000	83000	19100	58300
	311ML2	**27.6**	36	30100	115	180 ... 250	—	—	66600	84900	19600	58300
	311ML2	**32.7**	31	30400	103	180 ... 250	—	—	70100	89400	20800	58300
	311ML2	**38.8**	25.8	27200	78	180 ... 250	—	—	73800	94100	22000	58300
	311ML3	**50.5**	19.8	29300	60	132 ... 200	—	—	79800	100000	24000	58300
	311ML3	**60.2**	16.6	34600	60	132 ... 200	—	—	84200	100000	25500	58300
	311ML3	**71.1**	14.1	36400	59	132 ... 200	—	—	88500	100000	26900	58300
	311ML3	**77.3**	12.9	34100	51	132 ... 200	—	—	90700	100000	27700	58300
	311ML3	**89.3**	11.2	39000	50	132 ... 200	—	—	94700	100000	29000	58300
	311ML3	**104**	9.6	40600	45	132 ... 200	—	—	98000	100000	30500	58300
	311ML3	**115**	8.7	35300	35	132 ... 200	—	—	98000	100000	31600	58300
	311ML3	**133**	7.5	35700	31	132 ... 200	—	—	98000	100000	33200	58300
	311ML3	**147**	6.8	35900	28.0	132 ... 200	—	—	98000	100000	34300	58300
	311ML3	**161**	6.2	36200	25.8	132 ... 200	—	—	98000	100000	35400	58300
	311ML3	**171**	5.9	36300	24.4	132 ... 200	—	—	98000	100000	36100	58300
	311ML3	**191**	5.2	32000	19.2	132 ... 200	—	—	98000	100000	37400	58300
	311ML3	**203**	4.9	36800	20.8	132 ... 200	—	—	98200	100200	38200	58300
	311ML3	**245**	4.1	38000	17.8	132 ... 200	—	—	100900	103000	40700	58300
	311ML3	**291**	3.4	29400	11.6	132 ... 200	—	—	103400	105500	43100	58300
	311ML4	**348**	2.9	46400	15.8	71 ... 160	—	—	106100	108200	45700	58300
	311ML4	**410**	2.4	46700	13.4	71 ... 160	—	—	108600	110800	48300	58300

B



311M L

366

49210 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
	311ML4	**512**	2	47300	10.9	71 ... 160	—	—	112100	114400	52000	58300
	311ML4	**568**	1.8	43700	9.1	71 ... 160	—	—	113700	116100	53800	58300
1000	**311ML4**	**627**	1.6	44400	8.4	71 ... 160	—	—	115400	117700	55600	58300
	311ML4	**825**	1.2	46400	6.7	71 ... 160	—	—	120000	122400	61000	58300
	311ML4	**986**	1	47700	5.7	71 ... 160	—	—	123100	125600	64700	58300
	311ML4	**1058**	0.94	47800	5.3	71 ... 160	—	—	124300	126900	65000	58300
	311ML4	**1230**	0.81	47800	4.6	71 ... 160	—	—	127000	129600	65000	58300
	311ML4	**1415**	0.71	41300	3.4	71 ... 160	—	—	129600	132300	65000	58300
	311ML4	**1680**	0.6	36500	2.6	71 ... 160	—	—	132800	135500	65000	58300
	311ML4	**1766**	0.57	41300	2.8	71 ... 160	—	—	133800	136500	65000	58300
	311ML4	**2096**	0.48	36500	2.1	71 ... 160	—	—	137100	139900	65000	58300
500	**311ML1**	**4.09**	122	23100	200	200 ... 250	—	—	46200	59000	13100	58300
	311ML1	**5.25**	95	24300	200	200 ... 250	—	—	49800	63600	14200	58300
	311ML1	**6.23**	80	24700	200	200 ... 250	—	—	52500	66900	15100	58300
	311ML2	**14.0**	36	26800	106	180 ... 250	—	—	66900	85400	19800	58300
	311ML2	**16.7**	29.9	29000	97	180 ... 250	—	—	70600	90000	20900	58300
	311ML2	**18.0**	27.8	31400	97	180 ... 250	—	—	72100	92000	21500	58300
	311ML2	**21.5**	23.3	28100	73	180 ... 250	—	—	76100	97000	22800	58300
	311ML2	**25.5**	19.6	28400	62	180 ... 250	—	—	80100	100000	24100	58300
	311ML2	**27.6**	18.1	32600	66	180 ... 250	—	—	82000	100000	24700	58300
	311ML2	**32.7**	15.3	33200	56	180 ... 250	—	—	86300	100000	26200	58300
	311ML2	**38.8**	12.9	27200	39	180 ... 250	—	—	90800	100000	27700	58300
	311ML3	**50.5**	9.9	32400	37	132 ... 200	—	—	98000	100000	30300	58300
	311ML3	**60.2**	8.3	41600	40	132 ... 200	—	—	98000	100000	32100	58300
	311ML3	**71.1**	7.0	42800	35	132 ... 200	—	—	98000	100000	33900	58300
	311ML3	**77.3**	6.5	36100	26.8	132 ... 200	—	—	98000	100000	34900	58300
	311ML3	**89.3**	5.6	44600	28.6	132 ... 200	—	—	98000	100000	36600	58300
	311ML3	**104**	4.8	45500	25.2	132 ... 200	—	—	98500	100500	38500	58300
	311ML3	**115**	4.4	37600	18.8	132 ... 200	—	—	99900	102000	39800	58300
	311ML3	**133**	3.8	38600	16.6	132 ... 200	—	—	102100	104200	41800	58300
	311ML3	**147**	3.4	39200	15.3	132 ... 200	—	—	103500	105700	43200	58300
	311ML3	**161**	3.1	39900	14.2	132 ... 200	—	—	104900	107000	44600	58300
	311ML3	**171**	2.9	40300	13.5	132 ... 200	—	—	105800	108000	45400	58300
	311ML3	**191**	2.6	32000	9.6	132 ... 200	—	—	107500	109700	47200	58300
	311ML3	**203**	2.5	41200	11.6	132 ... 200	—	—	108400	110600	48100	58300
	311ML3	**245**	2.0	41200	9.6	132 ... 200	—	—	111400	113700	51300	58300
	311ML3	**291**	1.7	33200	6.5	132 ... 200	—	—	114200	116500	54300	58300
	311ML4	**348**	1.4	48200	8.2	71 ... 160	—	—	117100	119500	57600	58300
	311ML4	**410**	1.2	48600	7.0	71 ... 160	—	—	119900	122300	60900	58300
	311ML4	**512**	0.98	49200	5.7	71 ... 160	—	—	123800	126300	65000	58300
	311ML4	**568**	0.88	47800	5.0	71 ... 160	—	—	125600	128200	65000	58300
	311ML4	**627**	0.80	47800	4.5	71 ... 160	—	—	127400	130000	65000	58300
	311ML4	**825**	0.61	47800	3.4	71 ... 160	—	—	132500	135200	65000	58300
	311ML4	**986**	0.51	47800	2.9	71 ... 160	—	—	135900	138700	65000	58300
	311ML4	**1058**	0.47	47800	2.7	71 ... 160	—	—	137300	140100	65000	58300
	311ML4	**1230**	0.41	47800	2.3	71 ... 160	—	—	140300	143100	65000	58300
	311ML4	**1415**	0.35	41300	1.7	71 ... 160	—	—	143100	146000	65000	58300
	311ML4	**1680**	0.30	36500	1.3	71 ... 160	—	—	146600	149600	65000	58300
	311ML4	**1766**	0.28	41300	1.4	71 ... 160	—	—	147700	150700	65000	58300
	311ML4	**2096**	0.24	36500	1.0	71 ... 160	—	—	151400	154400	65000	58300

B



313M L

378

60940 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**313ML2**	**14.2**	106	28200	150	180 ... 250	—	—	70000	82000	16900	105000
	313ML2	**16.9**	89	29000	150	180 ... 250	—	—	73800	86500	18000	105000
	313ML2	**18.5**	81	35600	150	180 ... 250	—	—	75800	88800	18500	105000
	313ML2	**21.8**	69	30500	150	180 ... 250	—	—	79600	93200	19500	105000
	313ML2	**25.8**	58	31700	150	180 ... 250	—	—	83800	98100	20700	105000
	313ML2	**28.4**	53	39800	150	180 ... 250	—	—	86100	100900	21300	105000
	313ML2	**33.6**	45	40100	150	180 ... 250	—	—	90700	106300	22600	105000
	313ML2	**40.5**	37	30200	124	180 ... 250	—	—	95900	112300	24000	105000
	313ML3	**51.1**	29.3	31700	60	132 ... 200	—	—	102800	120500	25900	105000
	313ML3	**61.0**	24.6	37800	60	132 ... 200	—	—	108400	127000	27500	105000
	313ML3	**72.0**	20.8	39100	60	132 ... 200	—	—	113900	133500	29100	105000
	313ML3	**78.3**	19.2	42800	60	132 ... 200	—	—	116800	136900	29900	105000
	313ML3	**92.4**	16.2	44600	60	132 ... 200	—	—	122800	143900	31600	105000
	313ML3	**110**	13.7	45200	60	132 ... 200	—	—	129300	151500	33500	105000
	313ML3	**120**	12.4	41300	59	132 ... 200	—	—	133000	155800	34500	105000
	313ML3	**135**	11.1	49100	60	132 ... 200	—	—	137500	161200	35800	105000
	313ML3	**143**	10.5	41400	50	132 ... 200	—	—	140000	164000	36500	105000
	313ML3	**151**	9.9	41400	47	132 ... 200	—	—	142000	166400	37200	105000
	313ML3	**163**	9.2	50800	54	132 ... 200	—	—	142000	166400	38200	105000
	313ML3	**176**	8.5	41800	41	132 ... 200	—	—	142000	166400	39100	105000
	313ML3	**182**	8.2	30200	28.6	132 ... 200	—	—	142000	166400	39600	105000
	313ML3	**194**	7.7	48600	43	132 ... 200	—	—	142000	166400	40400	105000
	313ML3	**209**	7.2	42200	35	132 ... 200	—	—	142000	166400	41400	105000
	313ML3	**252**	5.9	42700	29.1	132 ... 200	—	—	142000	166400	44200	105000
	313ML3	**304**	4.9	30300	17.2	132 ... 200	—	—	142300	166700	47000	105000
	313ML4	**394**	3.8	56400	25.4	71 ... 160	—	—	147600	173000	51200	105000
	313ML4	**452**	3.3	56800	22.3	71 ... 160	—	—	150600	176400	53600	105000
	313ML4	**514**	2.9	47400	16.4	71 ... 160	—	—	153300	179700	56000	105000
	313ML4	**564**	2.7	54200	17.1	71 ... 160	—	—	155400	182100	57700	105000
	313ML4	**633**	2.4	48800	13.7	71 ... 160	—	—	158000	185100	60000	105000
	313ML4	**695**	2.2	50000	12.8	71 ... 160	—	—	160100	187600	61900	105000
	313ML4	**790**	1.9	49300	11.1	71 ... 160	—	—	163100	191100	64600	105000
	313ML4	**889**	1.7	52200	10.4	71 ... 160	—	—	165800	194300	67200	105000
	313ML4	**1014**	1.5	53400	9.3	71 ... 160	—	—	169000	198000	70200	105000
	313ML4	**1117**	1.3	50100	8.0	71 ... 160	—	—	171300	200800	72500	105000
	313ML4	**1266**	1.2	55500	7.8	71 ... 160	—	—	174400	204400	75600	105000
	313ML4	**1394**	1.1	50600	6.4	71 ... 160	—	—	176800	207200	78100	105000
	313ML4	**1502**	1.0	57100	6.7	71 ... 160	—	—	178700	209500	80000	105000
	313ML4	**1817**	0.83	57100	5.6	71 ... 160	—	—	183700	215200	80000	105000
	313ML4	**2187**	0.69	40100	3.3	71 ... 160	—	—	188600	221000	80000	105000
1000	**313ML1**	**4.14**	241	26300	250	—	—	—	54600	64000	12800	105000
	313ML1	**5.40**	185	27700	250	—	—	—	59200	69300	14000	105000
	313ML1	**6.50**	154	26500	250	—	—	—	62500	73300	14900	105000
	313ML2	**14.2**	70	31800	150	180 ... 250	—	—	79100	92700	19400	105000
	313ML2	**16.9**	59	32800	150	180 ... 250	—	—	83400	97700	20500	105000
	313ML2	**18.5**	54	40200	150	180 ... 250	—	—	85600	100300	21200	105000
	313ML2	**21.8**	46	34300	150	180 ... 250	—	—	89900	105300	22300	105000
	313ML2	**25.8**	39	35300	150	180 ... 250	—	—	94600	110800	23600	105000
	313ML2	**28.4**	35	40700	150	180 ... 250	—	—	97300	114000	24400	105000
	313ML2	**33.6**	29.7	40400	134	180 ... 250	—	—	102400	120000	25800	105000
	313ML2	**40.5**	24.7	30200	83	180 ... 250	—	—	108300	126900	27500	105000
	313ML3	**51.1**	19.6	35800	60	132 ... 200	—	—	116100	136100	29700	105000
	313ML3	**61.0**	16.4	42700	60	132 ... 200	—	—	122400	143500	31500	105000
	313ML3	**72.0**	13.9	44200	60	132 ... 200	—	—	128700	150800	33300	105000
	313ML3	**78.3**	12.8	47400	60	132 ... 200	—	—	132000	154600	34200	105000
	313ML3	**92.4**	10.8	49400	60	132 ... 200	—	—	138700	162500	36200	105000
	313ML3	**110**	9.1	48600	51	132 ... 200	—	—	142000	166400	38300	105000
	313ML3	**120**	8.3	41900	40	132 ... 200	—	—	142000	166400	39500	105000
	313ML3	**135**	7.4	52600	45	132 ... 200	—	—	142000	166400	41000	105000
	313ML3	**143**	7.0	42300	34	132 ... 200	—	—	142000	166400	41800	105000
	313ML3	**151**	6.6	42400	32	132 ... 200	—	—	142000	166400	42600	105000



313M L

378

60940 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1000	**313ML3**	**163**	6.1	53000	37	132 ... 200	—	—	142000	166400	43700	105000
	313ML3	**176**	5.7	42800	28.0	132 ... 200	—	—	142000	166400	44800	105000
	313ML3	**182**	5.5	30300	19.1	132 ... 200	—	—	142000	166400	45300	105000
	313ML3	**194**	5.2	48600	28.8	132 ... 200	—	—	142000	166400	46300	105000
	313ML3	**209**	4.8	43500	23.9	132 ... 200	—	—	142900	167400	47400	105000
	313ML3	**252**	4.0	44900	20.4	132 ... 200	—	—	146800	172000	50600	105000
	313ML3	**304**	3.3	32600	12.3	132 ... 200	—	—	150700	176600	53800	105000
	313ML4	**394**	2.5	57600	17.3	71 ... 160	—	—	156400	183300	58700	105000
	313ML4	**452**	2.2	58100	15.2	71 ... 160	—	—	159500	186900	61400	105000
	313ML4	**514**	1.9	50900	11.7	71 ... 160	—	—	162500	190400	64100	105000
	313ML4	**564**	1.8	54200	11.4	71 ... 160	—	—	164700	193000	66100	105000
	313ML4	**633**	1.6	49700	9.3	71 ... 160	—	—	167400	196200	68700	105000
	313ML4	**695**	1.4	53600	9.1	71 ... 160	—	—	169700	198800	70900	105000
	313ML4	**790**	1.3	50200	7.5	71 ... 160	—	—	172800	202500	74000	105000
	313ML4	**889**	1.1	56000	7.4	71 ... 160	—	—	175700	205900	76900	105000
	313ML4	**1014**	0.99	57100	6.7	71 ... 160	—	—	179100	209800	80000	105000
	313ML4	**1117**	0.9	50800	5.4	71 ... 160	—	—	181600	212700	80000	105000
	313ML4	**1266**	0.79	57100	5.3	71 ... 160	—	—	184800	216600	80000	105000
	313ML4	**1394**	0.72	50800	4.3	71 ... 160	—	—	187400	219600	80000	105000
	313ML4	**1502**	0.67	57100	4.5	71 ... 160	—	—	189400	221900	80000	105000
	313ML4	**1817**	0.55	57100	3.7	71 ... 160	—	—	192000	228100	80000	105000
	313ML4	**2187**	0.46	40100	2.2	71 ... 160	—	—	192000	231000	80000	105000
500	**313ML1**	**4.14**	121	32400	250	—	—	—	67300	78800	16200	105000
	313ML1	**5.40**	93	34200	250	—	—	—	72800	85300	17700	105000
	313ML1	**6.50**	77	30200	250	—	—	—	77000	90200	18800	105000
	313ML2	**14.2**	35	37800	148	180 ... 250	—	—	97300	114100	24400	105000
	313ML2	**16.9**	29.5	39000	128	180 ... 250	—	—	102600	120300	25900	105000
	313ML2	**18.5**	27.0	41200	124	180 ... 250	—	—	105400	123500	26700	105000
	313ML2	**21.8**	23.0	40900	105	180 ... 250	—	—	110600	129600	28100	105000
	313ML2	**25.8**	19.4	41600	90	180 ... 250	—	—	116500	136500	29800	105000
	313ML2	**28.4**	17.6	41100	81	180 ... 250	—	—	119800	140400	30700	105000
	313ML2	**33.6**	14.9	41100	68	180 ... 250	—	—	126100	147800	32500	105000
	313ML2	**40.5**	12.3	30200	41	180 ... 250	—	—	133300	156200	34600	105000
	313ML3	**51.1**	9.8	43900	49	132 ... 200	—	—	142000	166400	37400	105000
	313ML3	**61.0**	8.2	51200	48	132 ... 200	—	—	142000	166400	39700	105000
	313ML3	**72.0**	6.9	52300	42	132 ... 200	—	—	142000	166400	41900	105000
	313ML3	**78.3**	6.4	53700	39	132 ... 200	—	—	142000	166400	43100	105000
	313ML3	**92.4**	5.4	55000	34	132 ... 200	—	—	142000	166400	45600	105000
	313ML3	**110**	4.6	48600	25.4	132 ... 200	—	—	143900	168600	48300	105000
	313ML3	**120**	4.1	44600	21.2	132 ... 200	—	—	145800	170900	49800	105000
	313ML3	**135**	3.7	56500	24.0	132 ... 200	—	—	148200	173700	51700	105000
	313ML3	**143**	3.5	45900	18.4	132 ... 200	—	—	149400	175100	52700	105000
	313ML3	**151**	3.3	46400	17.6	132 ... 200	—	—	150600	176500	53700	105000
	313ML3	**163**	3.1	54100	19.0	132 ... 200	—	—	152300	178400	55100	105000
	313ML3	**176**	2.8	47600	15.5	132 ... 200	—	—	153900	180400	56500	105000
	313ML3	**182**	2.7	33600	10.6	132 ... 200	—	—	154700	181300	57100	105000
	313ML3	**194**	2.6	48600	14.4	132 ... 200	—	—	156100	182900	58300	105000
	313ML3	**209**	2.4	49000	13.5	132 ... 200	—	—	157700	184800	59800	105000
	313ML3	**252**	2.0	50700	11.5	132 ... 200	—	—	162100	189900	63700	105000
	313ML3	**304**	1.6	36800	6.9	132 ... 200	—	—	166400	195000	67800	105000
	313ML4	**394**	1.3	60100	9.0	71 ... 160	—	—	172700	202400	73900	105000
	313ML4	**452**	1.1	60600	7.9	71 ... 160	—	—	176100	206400	77300	105000
	313ML4	**514**	0.97	57100	6.6	71 ... 160	—	—	179400	210200	80000	105000
	313ML4	**564**	0.89	54200	5.7	71 ... 160	—	—	181800	213000	80000	105000
	313ML4	**633**	0.79	50800	4.7	71 ... 160	—	—	184800	216600	80000	105000
	313ML4	**695**	0.72	57100	4.9	71 ... 160	—	—	187300	219500	80000	105000
	313ML4	**790**	0.63	50800	3.8	71 ... 160	—	—	190800	223600	80000	105000
	313ML4	**889**	0.56	57100	3.8	71 ... 160	—	—	192000	227400	80000	105000
	313ML4	**1014**	0.49	57100	3.3	71 ... 160	—	—	192000	231000	80000	105000
	313ML4	**1117**	0.45	50800	2.7	71 ... 160	—	—	192000	231000	80000	105000
	313ML4	**1266**	0.40	57100	2.7	71 ... 160	—	—	192000	231000	80000	105000



313M L

378

60940 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
500	**313ML4**	**1394**	0.36	50800	2.2	71 ... 160	—	—	192000	231000	80000	105000
	313ML4	**1502**	0.33	57100	2.2	71 ... 160	—	—	192000	231000	80000	105000
	313ML4	**1817**	0.28	57100	1.9	71 ... 160	—	—	192000	231000	80000	105000
	313ML4	**2187**	0.23	40100	1.1	71 ... 160	—	—	192000	231000	80000	105000

314M L

390

80640 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**314ML2**	**17.4**	86	38500	175	200 ... 250	—	—	69200	82900	20400	115000
	314ML2	**22.3**	67	40500	175	200 ... 250	—	—	74500	89400	22100	115000
	314ML2	**26.5**	57	42100	175	200 ... 250	—	—	78500	94100	23400	115000
	314ML2	**28.0**	54	50800	175	200 ... 250	—	—	79800	95700	23900	115000
	314ML2	**33.2**	45	51700	175	200 ... 250	—	—	84000	100700	25300	115000
	314ML2	**38.6**	39	47400	175	200 ... 250	—	—	87900	105400	26600	115000
	314ML3	**62.6**	24.0	49200	75	160 ... 250	—	—	101600	121800	31200	115000
	314ML3	**73.9**	20.3	50900	75	160 ... 250	—	—	106700	128000	33000	115000
	314ML3	**92.7**	16.2	53100	75	160 ... 250	—	—	114300	137000	35600	115000
	314ML3	**108**	13.9	55000	75	160 ... 250	—	—	119500	143400	37400	115000
	314ML3	**138**	10.8	69500	75	160 ... 250	—	—	128800	154500	40700	115000
	314ML3	**164**	9.1	59500	62	160 ... 250	—	—	132000	158300	43100	115000
	314ML3	**174**	8.6	60200	60	160 ... 250	—	—	132000	158300	43900	115000
	314ML3	**206**	7.3	60900	51	160 ... 250	—	—	132000	158300	46400	115000
	314ML3	**240**	6.3	47800	34	160 ... 250	—	—	132000	158300	48800	115000
	314ML4	**314**	4.8	75700	40	132 ... 200	—	—	132900	159300	53400	115000
	314ML4	**394**	3.8	74700	34	132 ... 200	—	—	137200	164600	57600	115000
	314ML4	**458**	3.3	74800	29.0	132 ... 200	—	—	140200	168200	60600	115000
	314ML4	**495**	3.0	75600	27.1	132 ... 200	—	—	141800	170000	62200	115000
	314ML4	**575**	2.6	67200	20.7	132 ... 200	—	—	144900	173700	65400	115000
	314ML4	**588**	2.6	72400	21.9	132 ... 200	—	—	145300	174300	65900	115000
	314ML4	**668**	2.2	76300	20.2	132 ... 200	—	—	148000	177500	68700	115000
	314ML4	**738**	2.0	73700	17.7	132 ... 200	—	—	150100	180000	71000	115000
	314ML4	**858**	1.7	74600	15.4	132 ... 200	—	—	153400	183900	74700	115000
	314ML4	**926**	1.6	70200	13.4	132 ... 200	—	—	155100	186000	76600	115000
	314ML4	**1038**	1.4	75700	12.9	132 ... 200	—	—	157600	189000	79600	115000
	314ML4	**1099**	1.4	71300	11.5	132 ... 200	—	—	158900	190600	81100	115000
	314ML4	**1277**	1.2	72300	10.0	132 ... 200	—	—	162400	194700	85300	115000
	314ML4	**1485**	1.0	63100	7.5	132 ... 200	—	—	165900	198900	89700	115000
	314ML4	**1796**	0.84	63300	6.2	132 ... 200	—	—	170500	204400	90000	115000
1000	**314ML2**	**17.4**	58	43400	175	200 ... 250	—	—	78100	93700	23300	115000
	314ML2	**22.3**	45	45700	175	200 ... 250	—	—	84200	100900	25300	115000
	314ML2	**26.5**	38	46100	175	200 ... 250	—	—	88600	106300	26800	115000
	314ML2	**28.0**	36	53400	175	200 ... 250	—	—	90100	108100	27300	115000
	314ML2	**33.2**	30	53800	175	200 ... 250	—	—	94800	113700	28900	115000
	314ML2	**38.6**	25.9	47400	137	200 ... 250	—	—	99200	119000	30400	115000
	314ML3	**62.6**	16.0	55600	75	160 ... 250	—	—	114700	137500	35700	115000
	314ML3	**73.9**	13.5	57500	75	160 ... 250	—	—	120500	144600	37800	115000
	314ML3	**92.7**	10.8	59900	74	160 ... 250	—	—	129000	154800	40700	115000
	314ML3	**108**	9.3	62100	66	160 ... 250	—	—	132000	158300	42800	115000
	314ML3	**138**	7.2	71700	59	160 ... 250	—	—	132000	158300	46500	115000
	314ML3	**164**	6.1	59500	42	160 ... 250	—	—	132000	158300	49300	115000
	314ML3	**174**	5.8	61800	41	160 ... 250	—	—	132000	158300	50200	115000
	314ML3	**206**	4.9	62500	35	160 ... 250	—	—	132600	159000	53200	115000
	314ML3	**240**	4.2	49500	23.7	160 ... 250	—	—	135400	162400	55900	115000
	314ML4	**314**	3.2	75700	28.5	132 ... 200	—	—	140800	168800	61200	115000
	314ML4	**394**	2.5	75700	22.7	132 ... 200	—	—	145400	174400	66000	115000



314M L

390

80640 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1000	**314ML4**	**458**	2.2	76400	19.7	132 ... 200	—	—	148600	178200	69400	115000
	314ML4	**495**	2.0	76800	18.4	132 ... 200	—	—	150200	180200	71200	115000
	314ML4	**575**	1.7	69700	14.3	132 ... 200	—	—	153500	184100	74800	115000
	314ML4	**588**	1.7	74700	15.0	132 ... 200	—	—	154000	184700	75400	115000
	314ML4	**668**	1.5	78400	13.9	132 ... 200	—	—	156800	188100	78700	115000
	314ML4	**738**	1.4	76100	12.2	132 ... 200	—	—	159100	190800	81300	115000
	314ML4	**858**	1.2	77100	10.6	132 ... 200	—	—	162500	194900	85500	115000
	314ML4	**926**	1.1	72800	9.3	132 ... 200	—	—	164300	197000	87700	115000
	314ML4	**1038**	0.96	78000	8.9	132 ... 200	—	—	167000	200300	90000	115000
	314ML4	**1099**	0.91	73300	7.9	132 ... 200	—	—	168400	201900	90000	115000
	314ML4	**1277**	0.78	73300	6.8	132 ... 200	—	—	172000	206300	90000	115000
	314ML4	**1485**	0.67	63300	5.0	132 ... 200	—	—	175800	210800	90000	115000
	314ML4	**1796**	0.56	63300	4.2	132 ... 200	—	—	180600	216600	90000	115000
500	**314ML1**	**4.25**	118	41700	260	—	—	—	63000	75600	18400	115000
	314ML1	**5.33**	94	43100	260	—	—	—	67500	80900	19800	115000
	314ML1	**6.20**	81	43500	260	—	—	—	70600	84600	20800	115000
	314ML2	**17.4**	28.8	52900	169	200 ... 250	—	—	96100	115300	29400	115000
	314ML2	**22.3**	22.4	56100	140	200 ... 250	—	—	103600	124300	31900	115000
	314ML2	**26.5**	18.9	52700	111	200 ... 250	—	—	109100	130800	33800	115000
	314ML2	**28.0**	17.9	56800	113	200 ... 250	—	—	110900	133000	34400	115000
	314ML2	**33.2**	15.0	57400	96	200 ... 250	—	—	116800	140000	36500	115000
	314ML2	**38.6**	12.9	47400	68	200 ... 250	—	—	122200	146500	38300	115000
	314ML3	**62.6**	8.0	67500	62	160 ... 250	—	—	132000	158300	45000	115000
	314ML3	**73.9**	6.8	69800	54	160 ... 250	—	—	132000	158300	47600	115000
	314ML3	**92.7**	5.4	73800	46	160 ... 250	—	—	132000	158300	51300	115000
	314ML3	**108**	4.6	74900	40	160 ... 250	—	—	133400	160000	54000	115000
	314ML3	**138**	3.6	72400	30	160 ... 250	—	—	138300	165800	58600	115000
	314ML3	**164**	3.0	59500	20.8	160 ... 250	—	—	141700	169900	62100	115000
	314ML3	**174**	2.9	66400	21.9	160 ... 250	—	—	142800	171300	63300	115000
	314ML3	**206**	2.4	67700	18.8	160 ... 250	—	—	146400	175500	67000	115000
	314ML3	**240**	2.1	55700	13.3	160 ... 250	—	—	149500	179300	70400	115000
	314ML4	**314**	1.6	78100	14.7	132 ... 200	—	—	155400	186400	77100	115000
	314ML4	**394**	1.3	79300	11.9	132 ... 200	—	—	160600	192600	83100	115000
	314ML4	**458**	1.1	80200	10.3	132 ... 200	—	—	164100	196700	87400	115000
	314ML4	**495**	1.0	80600	9.6	132 ... 200	—	—	165900	198900	89700	115000
	314ML4	**575**	0.87	73300	7.5	132 ... 200	—	—	169500	203200	90000	115000
	314ML4	**588**	0.85	78000	7.8	132 ... 200	—	—	170000	203900	90000	115000
	314ML4	**668**	0.75	80600	7.1	132 ... 200	—	—	173200	207700	90000	115000
	314ML4	**738**	0.68	78000	6.3	132 ... 200	—	—	175600	210600	90000	115000
	314ML4	**858**	0.58	78000	5.4	132 ... 200	—	—	179400	215200	90000	115000
	314ML4	**926**	0.54	73300	4.7	132 ... 200	—	—	181400	217600	90000	115000
	314ML4	**1038**	0.48	78000	4.4	132 ... 200	—	—	184400	221100	90000	115000
	314ML4	**1099**	0.46	73300	3.9	132 ... 200	—	—	185900	222900	90000	115000
	314ML4	**1277**	0.39	73300	3.4	132 ... 200	—	—	189900	227800	90000	115000
	314ML4	**1485**	0.34	63300	2.5	132 ... 200	—	—	194100	232700	90000	115000
	314ML4	**1796**	0.28	63300	2.1	132 ... 200	—	—	199400	239200	90000	115000

315M L

402

100800 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**315ML2**	**17.4**	86	57200	200	200 ... 250	—	—	69200	82900	20400	135000
	315ML2	**22.3**	67	61600	200	200 ... 250	—	—	74500	89400	22100	135000
	315ML2	**26.5**	57	64900	200	200 ... 250	—	—	78500	94100	23400	135000
	315ML2	**28.0**	54	63700	200	200 ... 250	—	—	79800	95700	23900	135000
	315ML2	**33.2**	45	65600	200	200 ... 250	—	—	84000	100700	25300	135000
	315ML2	**38.6**	39	59200	200	200 ... 250	—	—	87900	105400	26600	135000



315M L

402

100800 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**315ML3**	**59.6**	25.2	75800	115	180 ... 250	—	—	100100	120000	30700	135000
	315ML3	**71.1**	21.1	77700	115	180 ... 250	—	—	105500	126500	32600	135000
	315ML3	**91.3**	16.4	80700	115	180 ... 250	—	—	113700	136400	35400	135000
	315ML3	**108**	13.8	83200	115	180 ... 250	—	—	119700	143600	37500	135000
	315ML3	**139**	10.8	87800	109	180 ... 250	—	—	129000	154700	40700	135000
	315ML3	**165**	9.1	89700	94	180 ... 250	—	—	132000	158300	43100	135000
	315ML3	**174**	8.6	75300	74	180 ... 250	—	—	132000	158300	43900	135000
	315ML3	**207**	7.2	76100	63	180 ... 250	—	—	132000	158300	46500	135000
	315ML3	**241**	6.2	59700	43	180 ... 250	—	—	132000	158300	48900	135000
	315ML4	**302**	5.0	94600	56	132 ... 200	—	—	132100	158500	52800	135000
	315ML4	**370**	4.1	94600	45	132 ... 200	—	—	136000	163100	56400	135000
	315ML4	**441**	3.4	94600	38	132 ... 200	—	—	139500	167300	59800	135000
	315ML4	**487**	3.1	94600	34	132 ... 200	—	—	141500	169600	61800	135000
	315ML4	**533**	2.8	94600	31	132 ... 200	—	—	143300	171900	63800	135000
	315ML4	**591**	2.5	94600	28.4	132 ... 200	—	—	145400	174400	66000	135000
	315ML4	**672**	2.2	95400	25.2	132 ... 200	—	—	148100	177600	68900	135000
	315ML4	**741**	2.0	96000	23.0	132 ... 200	—	—	150200	180100	71200	135000
	315ML4	**862**	1.7	97000	20.0	132 ... 200	—	—	153500	184100	74800	135000
	315ML4	**930**	1.6	87800	16.7	132 ... 200	—	—	155200	186100	76800	135000
	315ML4	**1043**	1.4	98300	16.7	132 ... 200	—	—	157700	189100	79700	135000
	315ML4	**1104**	1.4	89100	14.3	132 ... 200	—	—	159000	190700	81300	135000
	315ML4	**1284**	1.2	90400	12.5	132 ... 200	—	—	162500	194800	85400	135000
	315ML4	**1492**	1.0	79000	9.4	132 ... 200	—	—	166000	199100	89800	135000
	315ML4	**1805**	0.83	79100	7.8	132 ... 200	—	—	170600	204600	90000	135000
1000	**315ML2**	**17.4**	58	64600	200	200 ... 250	—	—	78100	93700	23300	135000
	315ML2	**22.3**	45	68600	200	200 ... 250	—	—	84200	100900	25300	135000
	315ML2	**26.5**	38	70700	200	200 ... 250	—	—	88600	106300	26800	135000
	315ML2	**28.0**	36	67000	200	200 ... 250	—	—	90100	108100	27300	135000
	315ML2	**33.2**	30	67900	200	200 ... 250	—	—	94800	113700	28900	135000
	315ML2	**38.6**	25.9	59200	171	200 ... 250	—	—	99200	119000	30400	135000
	315ML3	**59.6**	16.8	81300	115	180 ... 250	—	—	113000	135500	35200	135000
	315ML3	**71.1**	14.1	83600	115	180 ... 250	—	—	119200	142900	37300	135000
	315ML3	**91.3**	11.0	87300	110	180 ... 250	—	—	128400	154000	40500	135000
	315ML3	**108**	9.2	89600	95	180 ... 250	—	—	132000	158300	42900	135000
	315ML3	**139**	7.2	91600	76	180 ... 250	—	—	132000	158300	46600	135000
	315ML3	**165**	6.1	93000	65	180 ... 250	—	—	132000	158300	49400	135000
	315ML3	**174**	5.7	77200	51	180 ... 250	—	—	132000	158300	50300	135000
	315ML3	**207**	4.8	78200	43	180 ... 250	—	—	132700	159100	53200	135000
	315ML3	**241**	4.2	61900	29.5	180 ... 250	—	—	135500	162500	56000	135000
	315ML4	**302**	3.3	94600	37	132 ... 200	—	—	140000	167900	60400	135000
	315ML4	**370**	2.7	94600	30	132 ... 200	—	—	144100	172800	64600	135000
	315ML4	**441**	2.3	95300	25.5	132 ... 200	—	—	147800	177200	68500	135000
	315ML4	**487**	2.1	95900	23.3	132 ... 200	—	—	149900	179800	70800	135000
	315ML4	**533**	1.9	96500	21.4	132 ... 200	—	—	151900	182100	73000	135000
	315ML4	**591**	1.7	97200	19.5	132 ... 200	—	—	154100	184800	75500	135000
	315ML4	**672**	1.5	98100	17.3	132 ... 200	—	—	156900	188200	78800	135000
	315ML4	**741**	1.3	98700	15.8	132 ... 200	—	—	159200	190900	81500	135000
	315ML4	**862**	1.2	99800	13.7	132 ... 200	—	—	162600	195000	85700	135000
	315ML4	**930**	1.1	91000	11.6	132 ... 200	—	—	164400	197200	87900	135000
	315ML4	**1043**	0.96	100800	11.4	132 ... 200	—	—	167100	200400	90000	135000
	315ML4	**1104**	0.91	91600	9.8	132 ... 200	—	—	168500	202100	90000	135000
	315ML4	**1284**	0.78	91600	8.4	132 ... 200	—	—	172200	206500	90000	135000
	315ML4	**1492**	0.67	79100	6.3	132 ... 200	—	—	175900	210900	90000	135000
	315ML4	**1805**	0.55	79100	5.2	132 ... 200	—	—	180700	216800	90000	135000
500	**315ML1**	**4.25**	118	52100	260	—	—	—	63000	75600	18400	135000
	315ML1	**5.33**	94	53900	260	—	—	—	67500	80900	19800	135000
	315ML1	**6.20**	81	54300	260	—	—	—	70600	84600	20800	135000

B



315M L

402

100800 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
500	**315ML2**	**17.4**	28.8	74100	200	200 ... 250	—	—	96100	115300	29400	135000
	315ML2	**22.3**	22.4	77400	193	200 ... 250	—	—	103600	124300	31900	135000
	315ML2	**26.5**	18.9	79700	167	200 ... 250	—	—	109100	130800	33800	135000
	315ML2	**28.0**	17.9	71000	141	200 ... 250	—	—	110900	133000	34400	135000
	315ML2	**33.2**	15.0	72100	121	200 ... 250	—	—	116800	140000	36500	135000
	315ML2	**38.6**	12.9	59200	85	200 ... 250	—	—	122200	146500	38300	135000
	315ML3	**59.6**	8.4	90300	87	180 ... 250	—	—	132000	158300	44300	135000
	315ML3	**71.1**	7.0	91800	74	180 ... 250	—	—	132000	158300	47000	135000
	315ML3	**91.3**	5.5	93800	59	180 ... 250	—	—	132000	158300	51100	135000
	315ML3	**108**	4.6	94600	50	180 ... 250	—	—	133500	160100	54100	135000
	315ML3	**139**	3.6	94600	39	180 ... 250	—	—	138400	165900	58700	135000
	315ML3	**165**	3.0	94600	33	180 ... 250	—	—	141800	170000	62200	135000
	315ML3	**174**	2.9	83000	27.3	180 ... 250	—	—	142900	171400	63400	135000
	315ML3	**207**	2.4	84600	23.4	180 ... 250	—	—	146500	175600	67100	135000
	315ML3	**241**	2.1	69700	16.6	180 ... 250	—	—	149600	179500	70500	135000
	315ML4	**302**	1.7	97400	19.0	132 ... 200	—	—	154600	185400	76100	135000
	315ML4	**370**	1.4	98700	15.8	132 ... 200	—	—	159100	190800	81400	135000
	315ML4	**441**	1.1	99900	13.4	132 ... 200	—	—	163200	195700	86300	135000
	315ML4	**487**	1.0	100600	12.2	132 ... 200	—	—	165500	198500	89200	135000
	315ML4	**533**	0.94	100800	11.2	132 ... 200	—	—	167700	201100	90000	135000
	315ML4	**591**	0.85	100800	10.1	132 ... 200	—	—	170100	204000	90000	135000
	315ML4	**672**	0.74	100800	8.9	132 ... 200	—	—	173300	207800	90000	135000
	315ML4	**741**	0.67	100800	8.0	132 ... 200	—	—	175700	210800	90000	135000
	315ML4	**862**	0.58	100800	6.9	132 ... 200	—	—	179600	215300	90000	135000
	315ML4	**930**	0.54	91600	5.8	132 ... 200	—	—	181500	217700	90000	135000
	315ML4	**1043**	0.48	100800	5.7	132 ... 200	—	—	184500	221300	90000	135000
	315ML4	**1104**	0.45	91600	4.9	132 ... 200	—	—	186000	223100	90000	135000
	315ML4	**1284**	0.39	91600	4.2	132 ... 200	—	—	190100	227900	90000	135000
	315ML4	**1492**	0.34	79100	3.1	132 ... 200	—	—	194200	232900	90000	135000
	315ML4	**1805**	0.28	79100	2.6	132 ... 200	—	—	199600	239300	90000	135000

316M L

414

134390 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**316ML2**	**17.4**	86	68500	200	200 ... 250	—	—	105800	118700	33900	192000
	316ML2	**21.8**	69	78800	200	200 ... 250	—	—	113300	127100	36600	192000
	316ML2	**22.3**	67	72100	200	200 ... 250	—	—	114000	127900	36900	192000
	316ML2	**26.5**	57	75000	200	200 ... 250	—	—	120100	134700	39100	192000
	316ML2	**28.0**	54	85000	200	200 ... 250	—	—	122100	137000	39800	192000
	316ML2	**33.2**	45	87500	200	200 ... 250	—	—	128500	144200	42100	192000
	316ML3	**59.6**	25.2	83700	115	180 ... 250	—	—	153200	171800	51200	192000
	316ML3	**71.1**	21.1	86100	115	180 ... 250	—	—	161500	181200	54300	192000
	316ML3	**76.5**	19.6	99900	115	180 ... 250	—	—	165100	185200	55600	192000
	316ML3	**89.3**	16.8	91900	115	180 ... 250	—	—	172900	193900	58600	192000
	316ML3	**96.0**	15.6	95800	115	180 ... 250	—	—	176700	198200	60000	192000
	316ML3	**114**	13.2	97200	115	180 ... 250	—	—	186000	208700	63500	192000
	316ML3	**117**	12.8	111000	115	180 ... 250	—	—	187600	210400	64100	192000
	316ML3	**139**	10.8	116100	115	180 ... 250	—	—	197400	221500	67900	192000
	316ML3	**165**	9.1	113600	115	180 ... 250	—	—	202000	226600	71900	192000
	316ML3	**174**	8.6	99500	98	180 ... 250	—	—	202000	226600	73200	192000
	316ML3	**207**	7.2	99500	83	180 ... 250	—	—	202000	226600	77500	192000
	316ML4	**215**	7.0	117100	60	132 ... 200	—	—	202000	226600	78500	192000
	316ML4	**253**	5.9	120300	60	132 ... 200	—	—	202000	226600	82900	192000
	316ML4	**275**	5.4	123100	60	132 ... 200	—	—	202000	226600	85300	192000
	316ML4	**318**	4.7	123900	60	132 ... 200	—	—	203700	228500	89400	192000
	316ML4	**346**	4.3	101800	52	132 ... 200	—	—	206100	231200	92000	192000



316M L

414

134390 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**316ML4**	**399**	3.8	104200	46	132 ... 200	—	—	210400	236000	96500	192000
	316ML4	**447**	3.4	125100	50	132 ... 200	—	—	213800	239900	100200	192000
	316ML4	**500**	3.0	125500	44	132 ... 200	—	—	217300	243800	104000	192000
	316ML4	**563**	2.7	113600	36	132 ... 200	—	—	221000	247900	108200	192000
	316ML4	**628**	2.4	111800	32	132 ... 200	—	—	224500	251800	112200	192000
	316ML4	**706**	2.1	113200	28.4	132 ... 200	—	—	228300	256100	116700	192000
	316ML4	**784**	1.9	114400	25.9	132 ... 200	—	—	231700	259900	120800	192000
	316ML4	**880**	1.7	115500	23.3	132 ... 200	—	—	235600	264300	125600	192000
1000	**316ML4**	**1020**	1.5	117500	20.4	132 ... 200	—	—	240600	269900	131900	192000
	316ML4	**1104**	1.4	118400	19.0	132 ... 200	—	—	243300	273000	135400	192000
	316ML4	**1237**	1.2	117200	16.8	132 ... 200	—	—	247300	277400	140700	192000
	316ML4	**1308**	1.1	120500	16.3	132 ... 200	—	—	249300	279700	143300	192000
	316ML4	**1553**	0.97	122200	14.0	132 ... 200	—	—	255500	286600	150000	192000
	316ML2	**17.4**	58	77400	200	200 ... 250	—	—	119500	134100	38900	192000
	316ML2	**21.8**	46	87400	200	200 ... 250	—	—	127900	143500	41900	192000
	316ML2	**22.3**	45	81000	200	200 ... 250	—	—	128800	144500	42200	192000
	316ML2	**26.5**	38	83100	200	200 ... 250	—	—	135600	152100	44700	192000
	316ML2	**28.0**	36	89300	200	200 ... 250	—	—	137900	154700	45500	192000
	316ML2	**33.2**	30	90600	200	200 ... 250	—	—	145100	162800	48200	192000
	316ML3	**59.6**	16.8	94500	115	180 ... 250	—	—	173000	194000	58600	192000
	316ML3	**71.1**	14.1	97200	115	180 ... 250	—	—	182400	204600	62100	192000
	316ML3	**76.5**	13.1	110800	115	180 ... 250	—	—	186400	209100	63700	192000
	316ML3	**89.3**	11.2	97800	115	180 ... 250	—	—	195200	219000	67000	192000
	316ML3	**96.0**	10.4	99200	115	180 ... 250	—	—	199500	223800	68700	192000
	316ML3	**114**	8.8	99500	100	180 ... 250	—	—	202000	226600	72700	192000
	316ML3	**117**	8.5	119700	115	180 ... 250	—	—	202000	226600	73400	192000
	316ML3	**139**	7.2	121000	100	180 ... 250	—	—	202000	226600	77700	192000
	316ML3	**165**	6.1	113600	79	180 ... 250	—	—	202000	226600	82300	192000
	316ML3	**174**	5.7	99500	65	180 ... 250	—	—	202000	226600	83800	192000
	316ML3	**207**	4.8	100100	55	180 ... 250	—	—	203000	227700	88700	192000
	316ML4	**215**	4.7	123900	60	132 ... 200	—	—	204000	228900	89800	192000
	316ML4	**253**	3.9	124500	58	132 ... 200	—	—	208900	234400	94900	192000
	316ML4	**275**	3.6	124800	54	132 ... 200	—	—	211400	237200	97600	192000
	316ML4	**318**	3.1	125300	47	132 ... 200	—	—	215800	242100	102400	192000
	316ML4	**346**	2.9	108700	37	132 ... 200	—	—	218400	245000	105300	192000
	316ML4	**399**	2.5	111300	33	132 ... 200	—	—	222900	250100	110400	192000
	316ML4	**447**	2.2	126600	33	132 ... 200	—	—	226600	254200	114700	192000
	316ML4	**500**	2.0	128100	30	132 ... 200	—	—	230300	258300	119100	192000
	316ML4	**563**	1.8	115300	24.2	132 ... 200	—	—	234200	262700	123900	192000
	316ML4	**628**	1.6	116500	21.9	132 ... 200	—	—	237900	266800	128500	192000
	316ML4	**706**	1.4	117900	19.7	132 ... 200	—	—	241900	271400	133600	192000
	316ML4	**784**	1.3	119200	18.0	132 ... 200	—	—	245500	275400	138300	192000
	316ML4	**880**	1.1	117500	15.8	132 ... 200	—	—	249600	280000	143700	192000
	316ML4	**1020**	0.98	122200	14.2	132 ... 200	—	—	254900	286000	150000	192000
	316ML4	**1104**	0.91	122200	13.1	132 ... 200	—	—	257800	289200	150000	192000
	316ML4	**1237**	0.81	118100	11.3	132 ... 200	—	—	262100	294000	150000	192000
	316ML4	**1308**	0.76	122200	11.0	132 ... 200	—	—	264200	296300	150000	192000
	316ML4	**1553**	0.64	122200	9.3	132 ... 200	—	—	270700	303700	150000	192000
500	**316ML1**	**4.25**	118	69500	280	—	—	—	96400	108200	30600	192000
	316ML1	**5.33**	94	71800	280	—	—	—	103200	115800	33000	192000
	316ML2	**17.4**	28.8	92100	200	200 ... 250	—	—	147100	165100	49000	192000
	316ML2	**21.8**	22.9	92700	200	200 ... 250	—	—	157500	176700	52800	192000
	316ML2	**22.3**	22.4	96600	200	200 ... 250	—	—	158600	177900	53200	192000
	316ML2	**26.5**	18.9	97900	200	200 ... 250	—	—	166900	187300	56300	192000
	316ML2	**28.0**	17.9	94700	188	200 ... 250	—	—	169700	190400	57400	192000
	316ML2	**33.2**	15.0	96100	161	200 ... 250	—	—	178700	200500	60800	192000
	316ML3	**59.6**	8.4	113600	109	180 ... 250	—	—	202000	226600	73800	192000
	316ML3	**71.1**	7.0	115500	93	180 ... 250	—	—	202000	226600	78300	192000
	316ML3	**76.5**	6.5	121700	91	180 ... 250	—	—	202000	226600	80200	192000

B



316M L

414

134390 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
500	**316ML3**	**89.3**	5.6	99500	64	180 ... 250	—	—	202000	226600	84500	192000
	316ML3	**96.0**	5.2	99500	59	180 ... 250	—	—	202000	226600	86500	192000
	316ML3	**114**	4.4	101600	51	180 ... 250	—	—	205800	230900	91600	192000
	316ML3	**117**	4.3	124300	61	180 ... 250	—	—	206600	231800	92500	192000
	316ML3	**139**	3.6	124900	52	180 ... 250	—	—	211700	237500	97900	192000
	316ML3	**165**	3.0	113600	40	180 ... 250	—	—	217000	243400	103700	192000
	316ML3	**174**	2.9	108900	36	180 ... 250	—	—	218700	245400	105600	192000
	316ML3	**207**	2.4	111700	31	180 ... 250	—	—	224100	251400	111800	192000
	316ML4	**215**	2.3	126400	35	132 ... 200	—	—	225300	252700	113100	192000
	316ML4	**253**	2.0	127100	29.7	132 ... 200	—	—	230700	258800	119600	192000
	316ML4	**275**	1.8	129000	27.7	132 ... 200	—	—	233500	261900	123000	192000
	316ML4	**318**	1.6	128000	23.8	132 ... 200	—	—	238300	267300	129000	192000
	316ML4	**346**	1.4	117700	20.1	132 ... 200	—	—	241200	270500	132600	192000
	316ML4	**399**	1.3	119400	17.7	132 ... 200	—	—	246100	276100	139100	192000
	316ML4	**447**	1.1	129400	17.1	132 ... 200	—	—	250200	280700	144500	192000
	316ML4	**500**	1.0	134400	15.9	132 ... 200	—	—	254300	285200	150000	192000
	316ML4	**563**	0.89	118100	12.4	132 ... 200	—	—	258600	290000	150000	192000
	316ML4	**628**	0.80	122200	11.5	132 ... 200	—	—	262600	294600	150000	192000
	316ML4	**706**	0.71	122200	10.2	132 ... 200	—	—	267100	299600	150000	192000
	316ML4	**784**	0.64	122200	9.2	132 ... 200	—	—	271100	304100	150000	192000
	316ML4	**880**	0.57	118100	7.9	132 ... 200	—	—	275600	309200	150000	192000
	316ML4	**1020**	0.49	122200	7.1	132 ... 200	—	—	281500	315700	150000	192000
	316ML4	**1104**	0.45	122200	6.5	132 ... 200	—	—	284700	319400	150000	192000
	316ML4	**1237**	0.40	118100	5.6	132 ... 200	—	—	289400	324600	150000	192000
	316ML4	**1308**	0.38	122200	5.5	132 ... 200	—	—	291700	327200	150000	192000
	316ML4	**1553**	0.32	122200	4.7	132 ... 200	—	—	298900	335300	150000	192000

317M L

424

207490 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**317ML3**	**58.1**	25.8	111900	150	180 ... 250	—	—	236500	251200	50800	393000
	317ML3	**69.3**	21.6	115100	150	180 ... 250	—	—	249300	264900	53800	393000
	317ML3	**89.0**	16.9	121100	150	180 ... 250	—	—	268700	285500	58500	393000
	317ML3	**106**	14.2	125900	150	180 ... 250	—	—	282900	300500	61900	393000
	317ML3	**116**	12.9	155100	150	180 ... 250	—	—	291000	309100	63900	393000
	317ML3	**138**	10.9	162800	150	180 ... 250	—	—	306300	325400	67700	393000
	317ML3	**166**	9.1	121300	126	180 ... 250	—	—	314300	333900	72000	393000
	317ML3	**179**	8.4	144000	138	180 ... 250	—	—	314300	333900	73900	393000
	317ML3	**213**	7.1	145600	118	180 ... 250	—	—	314300	333900	78200	393000
	317ML3	**252**	5.9	113800	78	180 ... 250	—	—	314300	333900	82800	393000
	317ML4	**378**	4.0	181400	60	132 ... 200	—	—	324900	345100	94800	393000
	317ML4	**449**	3.3	184400	60	132 ... 200	—	—	332900	353700	100300	393000
	317ML4	**493**	3.0	166900	60	132 ... 200	—	—	337400	358400	103500	393000
	317ML4	**552**	2.7	193500	60	132 ... 200	—	—	342900	364300	107500	393000
	317ML4	**619**	2.4	167300	48	132 ... 200	—	—	348500	370300	111600	393000
	317ML4	**719**	2.1	169400	42	132 ... 200	—	—	356100	378300	117400	393000
	317ML4	**792**	1.9	193700	43	132 ... 200	—	—	361100	383600	121200	393000
	317ML4	**904**	1.7	156000	31	132 ... 200	—	—	367900	390900	126700	393000
	317ML4	**1032**	1.5	174400	30	132 ... 200	—	—	375000	398400	132400	393000
	317ML4	**1134**	1.3	156000	24.4	132 ... 200	—	—	380100	403800	136600	393000
	317ML4	**1318**	1.1	156000	21.0	132 ... 200	—	—	388300	412500	143700	393000
	317ML4	**1595**	0.94	156000	17.4	132 ... 200	—	—	399000	423900	150000	393000
	317ML4	**1893**	0.79	150300	14.1	132 ... 200	—	—	408900	434400	150000	393000
1000	**317ML2**	**16.9**	59	104300	250	—	—	—	184500	196000	38500	393000
	317ML2	**22.1**	45	109800	250	—	—	—	199800	212300	42100	393000
	317ML2	**26.6**	38	106800	250	—	—	—	211200	224400	44800	393000
	317ML2	**28.4**	35	123400	250	—	—	—	215300	228800	45700	393000
	317ML2	**34.1**	29.3	126000	250	—	—	—	227600	241800	48700	393000



317M L

424

207490 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1000	**317ML2**	**40.5**	24.7	113000	250	—	—	—	239700	254600	51500	393000
	317ML3	**58.1**	17.2	126300	150	180 ... 250	—	—	267100	283700	58100	393000
	317ML3	**69.3**	14.4	130000	150	180 ... 250	—	—	281600	299200	61600	393000
	317ML3	**89.0**	11.2	136800	150	180 ... 250	—	—	303500	322400	67000	393000
	317ML3	**106**	9.5	142200	150	180 ... 250	—	—	314300	333900	70900	393000
	317ML3	**116**	8.6	166900	150	180 ... 250	—	—	314300	333900	73200	393000
	317ML3	**138**	7.3	166900	139	180 ... 250	—	—	314300	333900	77400	393000
	317ML3	**166**	6.0	121300	84	180 ... 250	—	—	314300	333900	82400	393000
	317ML3	**179**	5.6	147900	95	180 ... 250	—	—	314300	333900	84600	393000
	317ML3	**213**	4.7	149600	81	180 ... 250	—	—	317100	336800	89500	393000
	317ML3	**252**	4.0	118800	54	180 ... 250	—	—	324900	345200	94800	393000
	317ML4	**378**	2.6	194400	60	132 ... 200	—	—	344200	365700	108500	393000
	317ML4	**449**	2.2	193700	51	132 ... 200	—	—	352800	374800	114800	393000
	317ML4	**493**	2.0	169800	41	132 ... 200	—	—	357500	379800	118500	393000
	317ML4	**552**	1.8	200100	43	132 ... 200	—	—	363300	386000	123000	393000
	317ML4	**619**	1.6	172900	33	132 ... 200	—	—	369300	392300	127800	393000
	317ML4	**719**	1.4	175100	28.8	132 ... 200	—	—	377300	400900	134400	393000
	317ML4	**792**	1.3	193700	28.9	132 ... 200	—	—	382600	406400	138800	393000
	317ML4	**904**	1.1	156000	20.4	132 ... 200	—	—	389900	414200	145000	393000
	317ML4	**1032**	0.97	179800	20.6	132 ... 200	—	—	397300	422100	150000	393000
	317ML4	**1134**	0.88	156000	16.3	132 ... 200	—	—	402700	427800	150000	393000
	317ML4	**1318**	0.76	156000	14.0	132 ... 200	—	—	411500	437100	150000	393000
	317ML4	**1595**	0.63	156000	11.6	132 ... 200	—	—	422800	449200	150000	393000
	317ML4	**1893**	0.53	150300	9.4	132 ... 200	—	—	433300	460300	150000	393000
500	**317ML2**	**16.9**	29.5	126900	250	—	—	—	227200	241400	48500	393000
	317ML2	**22.1**	22.6	133100	250	—	—	—	246000	261300	53000	393000
	317ML2	**26.6**	18.8	114100	239	—	—	—	260100	276300	56400	393000
	317ML2	**28.4**	17.6	133500	250	—	—	—	265100	281600	57600	393000
	317ML2	**34.1**	14.7	136300	222	—	—	—	280300	297700	61300	393000
	317ML2	**40.5**	12.3	113000	155	—	—	—	295000	313400	64900	393000
	317ML3	**58.1**	8.6	155500	150	180 ... 250	—	—	314300	333900	73200	393000
	317ML3	**69.3**	7.2	160000	132	180 ... 250	—	—	314300	333900	77600	393000
	317ML3	**89.0**	5.6	168400	109	180 ... 250	—	—	314300	333900	84400	393000
	317ML3	**106**	4.7	173900	94	180 ... 250	—	—	316800	336500	89300	393000
	317ML3	**116**	4.3	166900	83	180 ... 250	—	—	321000	341000	92200	393000
	317ML3	**138**	3.6	166900	70	180 ... 250	—	—	329000	349500	97600	393000
	317ML3	**166**	3.0	121300	42	180 ... 250	—	—	337800	358900	103800	393000
	317ML3	**179**	2.8	154800	50	180 ... 250	—	—	341600	362900	106500	393000
	317ML3	**213**	2.4	156000	42	180 ... 250	—	—	350100	371900	112800	393000
	317ML3	**252**	2.0	133700	30	180 ... 250	—	—	358700	381100	119400	393000
	317ML4	**378**	1.3	204000	32	132 ... 200	—	—	380100	403800	136700	393000
	317ML4	**449**	1.1	193700	25.5	132 ... 200	—	—	389500	413800	144700	393000
	317ML4	**493**	1.0	179600	21.6	132 ... 200	—	—	394700	419400	149300	393000
	317ML4	**552**	0.91	207500	22.2	132 ... 200	—	—	401100	426200	150000	393000
	317ML4	**619**	0.81	179800	17.2	132 ... 200	—	—	407800	433200	150000	393000
	317ML4	**719**	0.70	179800	14.8	132 ... 200	—	—	416600	442600	150000	393000
	317ML4	**792**	0.63	193700	14.5	132 ... 200	—	—	422400	448800	150000	393000
	317ML4	**904**	0.55	156000	10.2	132 ... 200	—	—	430400	457300	150000	393000
	317ML4	**1032**	0.48	179800	10.3	132 ... 200	—	—	438700	466100	150000	393000
	317ML4	**1134**	0.44	156000	8.1	132 ... 200	—	—	442000	470000	150000	393000
	317ML4	**1318**	0.38	156000	7.0	132 ... 200	—	—	442000	470000	150000	393000
	317ML4	**1595**	0.31	156000	5.8	132 ... 200	—	—	442000	470000	150000	393000
	317ML4	**1893**	0.26	150300	4.7	132 ... 200	—	—	442000	470000	150000	393000

B



318M L

434

297550 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**318ML3**	**76.5**	19.6	194800	200	200 ... 250	—	—	244300	275900	74200	500000
	318ML3	**98.2**	15.3	205100	200	200 ... 250	—	—	263300	297300	80600	500000
	318ML3	**117**	12.9	212500	200	200 ... 250	—	—	277200	313000	85300	500000
	318ML3	**123**	12.2	215000	200	200 ... 250	—	—	281900	318200	86900	500000
	318ML3	**146**	10.3	222700	200	200 ... 250	—	—	296700	335000	92000	500000
	318ML3	**170**	8.8	225300	200	200 ... 250	—	—	299000	337600	96800	500000
	318ML4	**262**	5.7	230200	115	180 ... 250	—	—	299000	337600	111800	500000
	318ML4	**313**	4.8	233400	115	180 ... 250	—	—	300800	339600	118600	500000
	318ML4	**337**	4.5	236300	115	180 ... 250	—	—	304000	343200	121500	500000
	318ML4	**402**	3.7	243400	108	180 ... 250	—	—	311700	352000	128900	500000
	318ML4	**422**	3.6	245500	103	180 ... 250	—	—	314000	354500	131100	500000
	318ML4	**477**	3.1	250600	93	180 ... 250	—	—	319400	360700	136500	500000
	318ML4	**515**	2.9	253900	87	180 ... 250	—	—	323000	364700	140100	500000
	318ML4	**612**	2.5	261300	76	180 ... 250	—	—	331000	373800	148300	500000
	318ML4	**647**	2.3	263400	72	180 ... 250	—	—	333700	376800	151100	500000
	318ML4	**726**	2.1	267800	65	180 ... 250	—	—	339200	383000	157000	500000
	318ML4	**768**	2.0	270000	62	180 ... 250	—	—	341900	386100	160000	500000
	318ML4	**911**	1.6	276800	54	180 ... 250	—	—	350400	395700	169400	500000
	318ML4	**1059**	1.4	261400	44	180 ... 250	—	—	358000	404300	178100	500000
1000	**318ML3**	**76.5**	13.1	211900	200	200 ... 250	—	—	275900	311500	84900	500000
	318ML3	**98.2**	10.2	223100	200	200 ... 250	—	—	297400	335700	92300	500000
	318ML3	**117**	8.6	225600	200	200 ... 250	—	—	299000	337600	97700	500000
	318ML3	**123**	8.1	226200	200	200 ... 250	—	—	299000	337600	99500	500000
	318ML3	**146**	6.8	228200	179	200 ... 250	—	—	299000	337600	105400	500000
	318ML3	**170**	5.9	229900	155	200 ... 250	—	—	299000	337600	110800	500000
	318ML4	**262**	3.8	242600	109	180 ... 250	—	—	310800	350900	128000	500000
	318ML4	**313**	3.2	249900	94	180 ... 250	—	—	318700	359900	135800	500000
	318ML4	**337**	3.0	253000	89	180 ... 250	—	—	322100	363700	139100	500000
	318ML4	**402**	2.5	260700	77	180 ... 250	—	—	330300	373000	147600	500000
	318ML4	**422**	2.4	262600	74	180 ... 250	—	—	332700	375700	150100	500000
	318ML4	**477**	2.1	267200	66	180 ... 250	—	—	338500	382200	156200	500000
	318ML4	**515**	1.9	270300	62	180 ... 250	—	—	342300	386500	160400	500000
	318ML4	**612**	1.6	277100	54	180 ... 250	—	—	350800	396100	169800	500000
	318ML4	**647**	1.5	279300	51	180 ... 250	—	—	353600	399200	173000	500000
	318ML4	**726**	1.4	284000	46	180 ... 250	—	—	359500	405900	179800	500000
	318ML4	**768**	1.3	286400	44	180 ... 250	—	—	362300	409100	183100	500000
	318ML4	**911**	1.1	293600	38	180 ... 250	—	—	371300	419300	193900	500000
	318ML4	**1059**	0.94	264700	29.6	180 ... 250	—	—	379400	428400	200000	500000
500	**318ML2**	**18.7**	26.7	182700	260	—	—	—	222600	251300	66900	500000
	318ML2	**23.5**	21.3	191500	260	—	—	—	238300	269100	72100	500000
	318ML2	**27.3**	18.3	197600	260	—	—	—	249300	281500	75900	500000
	318ML3	**76.5**	6.5	228700	171	200 ... 250	—	—	299000	337600	107000	500000
	318ML3	**98.2**	5.1	231500	135	200 ... 250	—	—	299000	337600	116200	500000
	318ML3	**117**	4.3	237800	117	200 ... 250	—	—	305600	345100	123100	500000
	318ML3	**123**	4.1	240000	112	200 ... 250	—	—	308000	347800	125400	500000
	318ML3	**146**	3.4	247100	97	200 ... 250	—	—	315700	356400	132800	500000
	318ML3	**170**	2.9	250200	84	200 ... 250	—	—	322500	364200	139600	500000
	318ML4	**262**	1.9	271000	61	180 ... 250	—	—	343200	387500	161300	500000
	318ML4	**313**	1.6	278000	53	180 ... 250	—	—	351900	397400	171100	500000
	318ML4	**337**	1.5	281000	49	180 ... 250	—	—	355600	401500	175300	500000
	318ML4	**402**	1.2	288200	42	180 ... 250	—	—	364700	411800	185900	500000
	318ML4	**422**	1.2	290400	41	180 ... 250	—	—	367300	414800	189100	500000
	318ML4	**477**	1.0	295500	37	180 ... 250	—	—	373700	422000	196800	500000
	318ML4	**515**	0.97	297600	34	180 ... 250	—	—	377900	426700	200000	500000
	318ML4	**612**	0.82	297600	28.8	180 ... 250	—	—	387300	437300	200000	500000
	318ML4	**647**	0.77	297600	27.2	180 ... 250	—	—	390400	440800	200000	500000
	318ML4	**726**	0.69	297600	24.2	180 ... 250	—	—	396900	448100	200000	500000
	318ML4	**768**	0.65	297600	22.9	180 ... 250	—	—	400100	451700	200000	500000
	318ML4	**911**	0.55	297600	19.3	180 ... 250	—	—	410000	462900	200000	500000
	318ML4	**1059**	0.47	264700	14.8	180 ... 250	—	—	418900	473000	200000	500000

B



319 L

444

471190 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**319L3**	**84.8**	17.7	213400	200	200 ... 250	—	—	306100	337000	76700	680000
	319L3	**100**	15.0	220900	200	200 ... 250	—	—	322000	354500	81200	680000
	319L3	**109**	13.8	230000	200	200 ... 250	—	—	329900	363200	83400	680000
	319L3	**126**	11.9	236500	200	200 ... 250	—	—	344700	379500	87600	680000
	319L3	**129**	11.6	242100	200	200 ... 250	—	—	347300	382400	88300	680000
	319L3	**137**	11.0	246200	200	200 ... 250	—	—	353200	388800	90000	680000
	319L3	**162**	9.3	251600	200	200 ... 250	—	—	363300	400000	95200	680000
	319L3	**188**	8.0	263000	200	200 ... 250	—	—	363300	400000	100100	680000
	319L3	**192**	7.8	257200	200	200 ... 250	—	—	363300	400000	100700	680000
	319L3	**223**	6.7	262200	200	200 ... 250	—	—	363300	400000	105900	680000
	319L4	**291**	5.2	308900	115	180 ... 250	—	—	363300	400000	115700	680000
	319L4	**347**	4.3	325700	115	180 ... 250	—	—	370900	408400	122700	680000
	319L4	**410**	3.7	287000	115	180 ... 250	—	—	379900	418300	129800	680000
	319L4	**445**	3.4	351000	115	180 ... 250	—	—	384300	423200	133400	680000
	319L4	**515**	2.9	298100	103	180 ... 250	—	—	392500	432100	140000	680000
	319L4	**528**	2.8	369500	115	180 ... 250	—	—	393900	433700	141200	680000
	319L4	**558**	2.7	375700	115	180 ... 250	—	—	397000	437100	143900	680000
	319L4	**571**	2.6	378200	115	180 ... 250	—	—	398300	438500	145000	680000
	319L4	**625**	2.4	307900	87	180 ... 250	—	—	403500	444200	149400	680000
	319L4	**678**	2.2	390100	102	180 ... 250	—	—	408200	449400	153500	680000
	319L4	**717**	2.1	399500	99	180 ... 250	—	—	411400	453000	156300	680000
	319L4	**802**	1.9	321000	71	180 ... 250	—	—	418100	460300	162300	680000
	319L4	**850**	1.8	403900	84	180 ... 250	—	—	421600	464200	165500	680000
	319L4	**912**	1.6	319400	62	180 ... 250	—	—	425800	468800	169400	680000
	319L4	**1007**	1.5	333400	59	180 ... 250	—	—	431900	475500	175100	680000
	319L4	**1195**	1.3	343000	51	180 ... 250	—	—	442600	487300	185400	680000
	319L4	**1389**	1.1	333700	43	180 ... 250	—	—	452200	497900	194900	680000
1000	**319L3**	**84.8**	11.8	241000	200	200 ... 250	—	—	345700	380600	87900	680000
	319L3	**100**	10.0	249300	200	200 ... 250	—	—	363300	400000	92900	680000
	319L3	**109**	9.2	259800	200	200 ... 250	—	—	363300	400000	95500	680000
	319L3	**126**	7.9	256700	200	200 ... 250	—	—	363300	400000	100200	680000
	319L3	**129**	7.7	273400	200	200 ... 250	—	—	363300	400000	101100	680000
	319L3	**137**	7.3	278100	200	200 ... 250	—	—	363300	400000	103000	680000
	319L3	**162**	6.2	265100	188	200 ... 250	—	—	363300	400000	108900	680000
	319L3	**188**	5.3	281200	171	200 ... 250	—	—	363300	400000	114600	680000
	319L3	**192**	5.2	271000	162	200 ... 250	—	—	363300	400000	115300	680000
	319L3	**223**	4.5	277400	143	200 ... 250	—	—	369000	406200	121300	680000
	319L4	**291**	3.4	348800	115	180 ... 250	—	—	383200	421900	132500	680000
	319L4	**347**	2.9	367800	115	180 ... 250	—	—	393000	432700	140500	680000
	319L4	**410**	2.4	307100	89	180 ... 250	—	—	402600	443200	148600	680000
	319L4	**445**	2.2	393200	105	180 ... 250	—	—	407300	448400	152700	680000
	319L4	**515**	1.9	319000	73	180 ... 250	—	—	415900	457900	160300	680000
	319L4	**528**	1.9	390600	87	180 ... 250	—	—	417400	459500	161700	680000
	319L4	**558**	1.8	413600	88	180 ... 250	—	—	420700	463200	164700	680000
	319L4	**571**	1.8	405900	84	180 ... 250	—	—	422000	464700	165900	680000
	319L4	**625**	1.6	329400	62	180 ... 250	—	—	427500	470700	171000	680000
	319L4	**678**	1.5	411400	72	180 ... 250	—	—	432500	476200	175700	680000
	319L4	**717**	1.4	437400	72	180 ... 250	—	—	436000	480000	179000	680000
	319L4	**802**	1.2	343400	51	180 ... 250	—	—	443000	487800	185800	680000
	319L4	**850**	1.2	428500	60	180 ... 250	—	—	446800	491900	189500	680000
	319L4	**912**	1.1	333200	43	180 ... 250	—	—	451200	496800	193900	680000
	319L4	**1007**	0.99	356300	42	180 ... 250	—	—	457600	503900	200000	680000
	319L4	**1195**	0.84	356300	35	180 ... 250	—	—	469000	516300	200000	680000
	319L4	**1389**	0.72	336400	28.7	180 ... 250	—	—	479200	527600	200000	680000
500	**319L2**	**20.7**	24.1	194500	260	—	—	—	278900	307100	69200	680000
	319L2	**24.5**	20.4	201300	260	—	—	—	293400	323000	73200	680000
	319L2	**26.0**	19.2	208200	260	—	—	—	298600	328700	74700	680000
	319L2	**30.8**	16.3	215500	260	—	—	—	314100	345800	79000	680000
	319L2	**35.8**	14.0	225400	260	—	—	—	328600	361800	83000	680000
	319L3	**84.8**	5.9	296700	200	200 ... 250	—	—	363300	400000	110700	680000

B



319 L — 444 — 471190 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
500	**319L3**	**100**	5.0	272600	156	200 ... 250	—	—	363500	400200	117100	680000
	319L3	**109**	4.6	319800	169	200 ... 250	—	—	367700	404800	120300	680000
	319L3	**126**	4.0	283100	129	200 ... 250	—	—	375400	413400	126300	680000
	319L3	**129**	3.9	336700	150	200 ... 250	—	—	376800	414900	127400	680000
	319L3	**137**	3.7	342300	144	200 ... 250	—	—	379800	418200	129700	680000
	319L3	**162**	3.1	295100	105	200 ... 250	—	—	389100	428400	137200	680000
	319L3	**188**	2.7	284000	87	200 ... 250	—	—	397700	437900	144400	680000
	319L3	**192**	2.6	303700	91	200 ... 250	—	—	398700	439000	145300	680000
	319L3	**223**	2.2	309300	80	200 ... 250	—	—	407400	448500	152800	680000
	319L4	**291**	1.7	417300	85	180 ... 250	—	—	423100	465800	166900	680000
	319L4	**347**	1.4	434200	74	180 ... 250	—	—	433900	477800	177000	680000
	319L4	**410**	1.2	344700	50	180 ... 250	—	—	444500	489400	187300	680000
	319L4	**445**	1.1	459100	61	180 ... 250	—	—	449700	495100	192400	680000
	319L4	**515**	0.97	356300	41	180 ... 250	—	—	459100	505500	200000	680000
	319L4	**528**	0.95	406500	46	180 ... 250	—	—	460800	507300	200000	680000
	319L4	**558**	0.90	471200	50	180 ... 250	—	—	464500	511400	200000	680000
	319L4	**571**	0.88	443000	46	180 ... 250	—	—	466000	513000	200000	680000
	319L4	**625**	0.80	356300	34	180 ... 250	—	—	472000	519700	200000	680000
	319L4	**678**	0.74	433000	38	180 ... 250	—	—	477500	525800	200000	680000
	319L4	**717**	0.70	471200	39	180 ... 250	—	—	481300	530000	200000	680000
	319L4	**802**	0.62	356300	26.3	180 ... 250	—	—	489100	538600	200000	680000
	319L4	**850**	0.59	438800	31	180 ... 250	—	—	493300	543100	200000	680000
	319L4	**912**	0.55	336400	21.8	180 ... 250	—	—	498200	548500	200000	680000
	319L4	**1007**	0.50	356300	20.9	180 ... 250	—	—	505300	556300	200000	680000
	319L4	**1195**	0.42	356300	17.6	180 ... 250	—	—	517800	570100	200000	680000
	319L4	**1389**	0.36	336400	14.3	180 ... 250	—	—	529000	582500	200000	680000

321 L — 454 — 655740 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**321L4**	**258**	5.8	401700	150	180 ... 250	—	—	513900	611700	707900	934000
	321L4	**308**	4.9	423600	150	180 ... 250	—	—	515900	614000	746400	934000
	321L4	**395**	3.8	456500	150	180 ... 250	—	—	534600	636300	804400	934000
	321L4	**469**	3.2	480500	150	180 ... 250	—	—	547800	652100	846800	934000
	321L4	**515**	2.9	494200	150	180 ... 250	—	—	555200	660900	871000	934000
	321L4	**612**	2.5	519900	150	180 ... 250	—	—	569000	677200	916900	934000
	321L4	**736**	2.0	545400	131	180 ... 250	—	—	584200	695400	969400	934000
	321L4	**796**	1.9	556600	124	180 ... 250	—	—	590800	703200	992400	934000
	321L4	**945**	1.6	581800	109	180 ... 250	—	—	605400	720700	1044700	934000
	321L4	**1122**	1.3	530200	84	180 ... 250	—	—	620400	738500	1099800	934000
1000	**321L3**	**75.3**	13.3	313500	250	—	—	—	472000	561800	552400	934000
	321L3	**98.2**	10.2	339400	250	—	—	—	511100	608300	598100	934000
	321L3	**118**	8.5	358800	250	—	—	—	513900	611700	632300	934000
	321L3	**126**	7.9	365800	250	—	—	—	513900	611700	644600	934000
	321L3	**152**	6.6	386700	250	—	—	—	513900	611700	681500	934000
	321L3	**180**	5.6	407100	250	—	—	—	513900	611700	717400	934000
	321L4	**258**	3.9	453700	150	180 ... 250	—	—	533000	634500	799500	934000
	321L4	**308**	3.2	478300	150	180 ... 250	—	—	546600	650700	843000	934000
	321L4	**395**	2.5	515500	150	180 ... 250	—	—	566500	674300	908500	934000
	321L4	**469**	2.1	539100	136	180 ... 250	—	—	580500	691000	956400	934000
	321L4	**515**	1.9	552400	127	180 ... 250	—	—	588300	700300	983600	934000
	321L4	**612**	1.6	577400	112	180 ... 250	—	—	602900	717600	1035500	934000
	321L4	**736**	1.4	605800	97	180 ... 250	—	—	619100	736900	1094700	934000
	321L4	**796**	1.3	618200	92	180 ... 250	—	—	626000	745200	1120700	934000
	321L4	**945**	1.1	646200	81	180 ... 250	—	—	641500	763600	1179800	934000
	321L4	**1122**	0.89	536400	57	180 ... 250	—	—	657400	782500	1200000	934000



321 L

454

655740 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
500	**321L3**	**75.3**	6.6	385900	250	—	—	—	513900	611700	680100	934000
	321L3	**98.2**	5.1	417900	244	—	—	—	513900	611700	736400	934000
	321L3	**118**	4.2	441800	214	—	—	—	526300	626500	778500	934000
	321L3	**126**	4.0	450300	205	—	—	—	531200	632200	793600	934000
	321L3	**152**	3.3	476100	180	—	—	—	545400	649200	839000	934000
	321L3	**180**	2.8	501200	160	—	—	—	558900	665300	883200	934000
	321L4	**258**	1.9	552700	127	180 ... 250	—	—	588500	700500	984200	934000
	321L4	**308**	1.6	578500	111	180 ... 250	—	—	603500	718400	1037800	934000
	321L4	**395**	1.3	617100	92	180 ... 250	—	—	625400	744500	1118500	934000
	321L4	**469**	1.1	645100	81	180 ... 250	—	—	640900	762900	1177400	934000
	321L4	**515**	0.97	655700	75	180 ... 250	—	—	649600	773200	1200000	934000
	321L4	**612**	0.82	655700	63	180 ... 250	—	—	665700	792300	1200000	934000
	321L4	**736**	0.68	655700	53	180 ... 250	—	—	683500	813600	1200000	934000
	321L4	**796**	0.63	655700	49	180 ... 250	—	—	691200	822700	1200000	934000
	321L4	**945**	0.53	655700	41	180 ... 250	—	—	708300	843100	1200000	934000
	321L4	**1122**	0.45	536400	28.3	180 ... 250	—	—	725900	864000	1200000	934000

323 L

464

890310 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**323L4**	**341**	4.4	757500	200	200 ... 250	—	—	—	—	705300	1580000
	323L4	**390**	3.8	774100	200	200 ... 250	—	—	—	—	734300	1580000
	323L4	**438**	3.4	788700	200	200 ... 250	—	—	—	—	760100	1580000
	323L4	**500**	3.0	806000	200	200 ... 250	—	—	—	—	791300	1580000
	323L4	**569**	2.6	822800	200	200 ... 250	—	—	—	—	822300	1580000
	323L4	**628**	2.4	832800	200	200 ... 250	—	—	—	—	847100	1580000
	323L4	**703**	2.1	840100	200	200 ... 250	—	—	—	—	876200	1580000
	323L4	**758**	2.0	844900	198	200 ... 250	—	—	—	—	896200	1580000
	323L4	**882**	1.7	854800	172	200 ... 250	—	—	—	—	938000	1580000
	323L4	**1025**	1.5	864700	150	200 ... 250	—	—	—	—	981300	1580000
	323L4	**1101**	1.4	869400	140	200 ... 250	—	—	—	—	1002400	1580000
	323L4	**1279**	1.2	879500	122	200 ... 250	—	—	—	—	1048800	1580000
1000	**323L4**	**341**	2.9	808800	200	200 ... 250	—	—	—	—	796500	1580000
	323L4	**390**	2.6	826500	200	200 ... 250	—	—	—	—	829200	1580000
	323L4	**438**	2.3	835700	200	200 ... 250	—	—	—	—	858400	1580000
	323L4	**500**	2.0	844300	200	200 ... 250	—	—	—	—	893700	1580000
	323L4	**569**	1.8	852600	177	200 ... 250	—	—	—	—	928700	1580000
	323L4	**628**	1.6	859100	162	200 ... 250	—	—	—	—	956700	1580000
	323L4	**703**	1.4	866600	146	200 ... 250	—	—	—	—	989500	1580000
	323L4	**758**	1.3	871600	136	200 ... 250	—	—	—	—	1012100	1580000
	323L4	**882**	1.1	881800	118	200 ... 250	—	—	—	—	1059300	1580000
	323L4	**1025**	0.98	890300	103	200 ... 250	—	—	—	—	1100000	1580000
	323L4	**1101**	0.91	890300	96	200 ... 250	—	—	—	—	1100000	1580000
	323L4	**1279**	0.78	890300	82	200 ... 250	—	—	—	—	1100000	1580000
500	**323L3**	**83.3**	6.0	702600	260	—	—	—	—	—	642600	1580000
	323L3	**105**	4.8	747400	260	—	—	—	—	—	687900	1580000
	323L3	**113**	4.4	756600	260	—	—	—	—	—	703700	1580000
	323L3	**120**	4.2	763800	260	—	—	—	—	—	716200	1580000
	323L3	**142**	3.5	784900	260	—	—	—	—	—	753300	1580000
	323L3	**165**	3.0	804200	260	—	—	—	—	—	788100	1580000
	323L3	**205**	2.4	831600	232	—	—	—	—	—	842300	1580000
	323L4	**341**	1.5	864600	150	200 ... 250	—	—	—	—	980600	1580000
	323L4	**390**	1.3	873500	132	200 ... 250	—	—	—	—	1020900	1580000
	323L4	**438**	1.1	881300	119	200 ... 250	—	—	—	—	1056800	1580000
	323L4	**500**	1.0	890300	105	200 ... 250	—	—	—	—	1100000	1580000
	323L4	**569**	0.88	890300	93	200 ... 250	—	—	—	—	1100000	1580000
	323L4	**628**	0.80	890300	84	200 ... 250	—	—	—	—	1100000	1580000

B



323 L

464

890310 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
500	**323L4**	**703**	0.71	890300	75	200 ... 250	—	—	—	—	1100000	1580000
	323L4	**758**	0.66	890300	70	200 ... 250	—	—	—	—	1100000	1580000
	323L4	**882**	0.57	890300	60	200 ... 250	—	—	—	—	1100000	1580000
	323L4	**1025**	0.49	890300	51	200 ... 250	—	—	—	—	1100000	1580000
	323L4	**1101**	0.45	890300	48	200 ... 250	—	—	—	—	1100000	1580000
	323L4	**1279**	0.39	890300	41	200 ... 250	—	—	—	—	1100000	1580000

325 L

468

1286700 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**325L4**	**341**	4.4	931900	200	200 ... 250	—	—	—	—	897700	2000000
	325L4	**390**	3.8	952300	200	200 ... 250	—	—	—	—	934500	2000000
	325L4	**438**	3.4	1004300	200	200 ... 250	—	—	—	—	967400	2000000
	325L4	**500**	3.0	1026300	200	200 ... 250	—	—	—	—	1007100	2000000
	325L4	**569**	2.6	1066500	200	200 ... 250	—	—	—	—	1046600	2000000
	325L4	**628**	2.4	1093000	200	200 ... 250	—	—	—	—	1078100	2000000
	325L4	**703**	2.1	1101500	200	200 ... 250	—	—	—	—	1115200	2000000
	325L4	**758**	2.0	1147900	200	200 ... 250	—	—	—	—	1140600	2000000
	325L4	**882**	1.7	1154000	200	200 ... 250	—	—	—	—	1193800	2000000
	325L4	**1025**	1.5	1190200	200	200 ... 250	—	—	—	—	1248900	2000000
	325L4	**1101**	1.4	963200	155	200 ... 250	—	—	—	—	1275800	2000000
	325L4	**1279**	1.2	963200	134	200 ... 250	—	—	—	—	1334800	2000000
1000	**325L4**	**341**	2.9	1052400	200	200 ... 250	—	—	—	—	1013800	2000000
	325L4	**390**	2.6	1075400	200	200 ... 250	—	—	—	—	1055400	2000000
	325L4	**438**	2.3	1120700	200	200 ... 250	—	—	—	—	1092500	2000000
	325L4	**500**	2.0	1130200	200	200 ... 250	—	—	—	—	1137400	2000000
	325L4	**569**	1.8	1157600	200	200 ... 250	—	—	—	—	1182000	2000000
	325L4	**628**	1.6	1179300	200	200 ... 250	—	—	—	—	1217600	2000000
	325L4	**703**	1.4	1197000	200	200 ... 250	—	—	—	—	1259400	2000000
	325L4	**758**	1.3	1228300	192	200 ... 250	—	—	—	—	1288100	2000000
	325L4	**882**	1.1	1254000	168	200 ... 250	—	—	—	—	1348200	2000000
	325L4	**1025**	0.98	1286700	148	200 ... 250	—	—	—	—	1400000	2000000
	325L4	**1101**	0.91	963200	104	200 ... 250	—	—	—	—	1400000	2000000
	325L4	**1279**	0.78	963200	89	200 ... 250	—	—	—	—	1400000	2000000
500	**325L3**	**83.3**	6.0	849100	260	—	—	—	—	—	817900	2000000
	325L3	**105**	4.8	908900	260	—	—	—	—	—	875600	2000000
	325L3	**113**	4.4	898100	260	—	—	—	—	—	895600	2000000
	325L3	**120**	4.2	928800	260	—	—	—	—	—	911500	2000000
	325L3	**142**	3.5	961400	260	—	—	—	—	—	958700	2000000
	325L3	**165**	3.0	1005800	260	—	—	—	—	—	1003000	2000000
	325L3	**205**	2.4	963200	260	—	—	—	—	—	1072000	2000000
	325L4	**341**	1.5	1206900	200	200 ... 250	—	—	—	—	1248100	2000000
	325L4	**390**	1.3	1228100	186	200 ... 250	—	—	—	—	1299300	2000000
	325L4	**438**	1.1	1258300	170	200 ... 250	—	—	—	—	1345100	2000000
	325L4	**500**	1.0	1286700	152	200 ... 250	—	—	—	—	1400000	2000000
	325L4	**569**	0.88	1286700	134	200 ... 250	—	—	—	—	1400000	2000000
	325L4	**628**	0.80	1286700	121	200 ... 250	—	—	—	—	1400000	2000000
	325L4	**703**	0.71	1286700	108	200 ... 250	—	—	—	—	1400000	2000000
	325L4	**758**	0.66	1286600	100	200 ... 250	—	—	—	—	1400000	2000000
	325L4	**882**	0.57	1286700	86	200 ... 250	—	—	—	—	1400000	2000000
	325L4	**1025**	0.49	1286700	74	200 ... 250	—	—	—	—	1400000	2000000
	325L4	**1101**	0.45	963200	52	200 ... 250	—	—	—	—	1400000	2000000
	325L4	**1279**	0.39	963200	45	200 ... 250	—	—	—	—	1400000	2000000

25.4 RATING CHARTS FOR RIGHT ANGLE UNITS 300M R

Reading the rating chart.



The rated torque of the gearbox, independent of installed mechanical power

1	Reference torque
2	Gearbox drive speed
3	Frame size of the right-angle gear unit. NOTE: letters (B) (C) near size indication identify different angle reduction dimensions. See dimensions pages.
4	Gear ratio
5	Gearbox output speed
6	Gearbox rated output torque based on: - service factor f_S=1 - 10000 h theoretical lifetime
7	Gearbox rated input power, based on: - service factor f_S=1 - 10000 h theoretical lifetime
8	Frame size of available IEC motor
9	Permitted overhung loading on output shaft, based on: - service factor f_S=1 - 10000 h theoretical lifetime - speed of output n_2 For forces not applied at shaft middlepoint, see diagrams provided in the specific gearbox overall dimensioning pages
10	Maximum torque
11	Dimensions page

B



300 R

264

1250 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ	$M_{2\,max}$ Nm
1500	**300R2**	**7.13**	210	580	13.7	71 ... 132	2360	2360	8620	10000	1350	2000
	300R2	**8.74**	172	610	11.7	71 ... 132	2520	2520	9160	10700	1440	2400
	300R2	**11.8**	127	590	8.3	71 ... 132	2790	2790	10000	11700	1590	2400
	300R2	**14.8**	102	510	5.7	71 ... 132	3000	3000	10700	12500	1710	2400
	300R2	**18.5**	81	370	3.3	71 ... 132	3230	3230	11500	13300	1850	2400
	300R3	**24.8**	60	730	5.1	71 ... 132	3570	3570	12500	14600	2040	2000
	300R3	**30.4**	49	840	4.8	71 ... 132	3820	3820	13300	15500	2180	2400
	300R3	**37.3**	40	840	3.9	71 ... 132	4090	4090	14200	16500	2330	2400
	300R3	**41.2**	36	650	2.7	71 ... 132	4220	4220	14600	17000	2410	2400
	300R3	**50.4**	29.8	850	2.9	71 ... 132	4520	4520	15500	18000	2580	2400
	300R3	**62.9**	23.8	850	2.3	71 ... 132	4870	4870	16600	19300	2780	2400
	300R3	**68.2**	22.0	650	1.6	71 ... 132	5000	5000	17000	19700	2860	2400
	300R3	**78.7**	19.1	850	1.9	71 ... 132	5240	5240	17700	20600	2990	2400
	300R3	**85.2**	17.6	650	1.3	71 ... 132	5380	5380	18100	21100	3070	2400
	300R3	**106**	14.1	650	1.1	71 ... 132	5800	5800	19400	22600	3310	2400
	300R3	**133**	11.3	550	0.71	71 ... 132	6240	6240	20700	24100	3570	2400
	300R4	**106**	14.2	860	1.4	71 ... 132	5790	5790	19400	22500	3310	2400
	300R4	**130**	11.6	860	1.2	71 ... 132	6190	6190	20600	23900	3540	2400
	300R4	**143**	10.5	650	0.81	71 ... 132	6400	6400	21200	24700	3660	2400
	300R4	**159**	9.4	870	0.97	71 ... 132	6500	6500	21500	25000	3780	2400
	300R4	**175**	8.5	880	0.89	71 ... 132	6500	6500	21500	25000	3910	2400
	300R4	**215**	7.0	910	0.75	71 ... 132	6500	6500	21500	25000	4190	2400
	300R4	**237**	6.3	650	0.49	71 ... 132	6500	6500	21500	25000	4330	2400
	300R4	**268**	5.6	930	0.62	71 ... 132	6500	6500	21500	25000	4510	2400
	300R4	**291**	5.2	950	0.58	71 ... 132	6500	6500	21500	25000	4630	2400
	300R4	**363**	4.1	980	0.48	71 ... 132	6680	6680	22100	25700	4990	2400
	300R4	**394**	3.8	680	0.31	71 ... 132	6760	6760	22400	26000	5120	2400
	300R4	**453**	3.3	1020	0.40	71 ... 132	6890	6890	22800	26500	5370	2400
	300R4	**491**	3.1	710	0.25	71 ... 132	6970	6970	23100	26800	5510	2400
	300R4	**613**	2.4	730	0.21	71 ... 132	7200	7200	23800	27700	5940	2400
	300R4	**766**	2.0	760	0.18	71 ... 132	7430	7430	24600	28600	6400	2400
1000	**300R2**	**7.13**	140	660	10.3	71 ... 132	2700	2700	9740	11300	1540	2000
	300R2	**8.74**	114	690	8.8	71 ... 132	2880	2880	10300	12000	1650	2400
	300R2	**11.8**	85	630	6.0	71 ... 132	3190	3190	11300	13200	1820	2400
	300R2	**14.8**	68	530	4.0	71 ... 132	3440	3440	12100	14100	1960	2400
	300R2	**18.5**	54	370	2.2	71 ... 132	3700	3700	12900	15100	2110	2400
	300R3	**24.8**	40	730	3.4	71 ... 132	4090	4090	14200	16500	2330	2000
	300R3	**30.4**	33	850	3.2	71 ... 132	4370	4370	15000	17500	2500	2400
	300R3	**37.3**	26.8	850	2.6	71 ... 132	4680	4680	16000	18600	2670	2400
	300R3	**41.2**	24.3	650	1.8	71 ... 132	4840	4840	16500	19200	2760	2400
	300R3	**50.4**	19.8	850	1.9	71 ... 132	5170	5170	17500	20400	2960	2400
	300R3	**62.9**	15.9	850	1.6	71 ... 132	5570	5570	18700	21800	3180	2400
	300R3	**68.2**	14.7	650	1.1	71 ... 132	5720	5720	19200	22300	3270	2400
	300R3	**78.7**	12.7	860	1.3	71 ... 132	6000	6000	20000	23300	3430	2400
	300R3	**85.2**	11.7	650	0.88	71 ... 132	6160	6160	20500	23800	3520	2400
	300R3	**106**	9.4	650	0.70	71 ... 132	6500	6500	21500	25000	3790	2400
	300R3	**133**	7.5	550	0.48	71 ... 132	6500	6500	21500	25000	4080	2400
	300R4	**106**	9.4	870	0.97	71 ... 132	6500	6500	21500	25000	3780	2400
	300R4	**130**	7.7	890	0.81	71 ... 132	6500	6500	21500	25000	4050	2400
	300R4	**143**	7.0	650	0.54	71 ... 132	6500	6500	21500	25000	4190	2400
	300R4	**159**	6.3	920	0.68	71 ... 132	6500	6500	21500	25000	4330	2400
	300R4	**175**	5.7	930	0.63	71 ... 132	6500	6500	21500	25000	4480	2400
	300R4	**215**	4.7	960	0.53	71 ... 132	6570	6570	21700	25300	4790	2400
	300R4	**237**	4.2	670	0.33	71 ... 132	6660	6660	22000	25600	4950	2400
	300R4	**268**	3.7	1000	0.44	71 ... 132	6780	6780	22400	26100	5160	2400
	300R4	**291**	3.4	1010	0.41	71 ... 132	6860	6860	22700	26400	5300	2400
	300R4	**363**	2.8	1050	0.34	71 ... 132	7080	7080	23400	27200	5710	2400
	300R4	**394**	2.5	730	0.22	71 ... 132	7160	7160	23700	27500	5860	2400
	300R4	**453**	2.2	1090	0.29	71 ... 132	7310	7310	24200	28100	6140	2400
	300R4	**491**	2.0	760	0.18	71 ... 132	7390	7390	24400	28400	6310	2400
	300R4	**613**	1.6	790	0.15	71 ... 132	7630	7630	25200	29300	6800	2400
	300R4	**766**	1.3	820	0.13	71 ... 132	7880	7880	26000	30300	7320	2400

B



300 R — 264 — 1250 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ	$M_{2\,max}$ Nm
500	**300R2**	**7.13**	70	730	5.7	71 ... 132	3400	3400	12000	13900	1940	2000
	300R2	**8.74**	57	820	5.2	71 ... 132	3630	3630	12700	14800	2080	2400
	300R2	**11.8**	42	650	3.1	71 ... 132	4020	4020	14000	16200	2300	2400
	300R2	**14.8**	34	550	2.1	71 ... 132	4330	4330	14900	17300	2470	2400
	300R2	**18.5**	27.1	370	1.1	71 ... 132	4660	4660	15900	18500	2660	2400
	300R3	**24.8**	20.1	730	1.7	71 ... 132	5150	5150	17400	20300	2940	2000
	300R3	**30.4**	16.4	850	1.6	71 ... 132	5510	5510	18500	21500	3150	2400
	300R3	**37.3**	13.4	860	1.3	71 ... 132	5890	5890	19700	22900	3370	2400
	300R3	**41.2**	12.1	650	0.91	71 ... 132	6090	6090	20300	23600	3480	2400
	300R3	**50.4**	9.9	860	0.98	71 ... 132	6500	6500	21500	25000	3720	2400
	300R3	**62.9**	7.9	890	0.81	71 ... 132	6500	6500	21500	25000	4010	2400
	300R3	**68.2**	7.3	650	0.55	71 ... 132	6500	6500	21500	25000	4120	2400
	300R3	**78.7**	6.4	920	0.67	71 ... 132	6500	6500	21500	25000	4320	2400
	300R3	**85.2**	5.9	650	0.44	71 ... 132	6500	6500	21500	25000	4430	2400
	300R3	**106**	4.7	660	0.35	71 ... 132	6560	6560	21700	25200	4780	2400
	300R3	**133**	3.8	570	0.25	71 ... 132	6770	6770	22400	26000	5140	2400
	300R4	**106**	4.7	960	0.54	71 ... 132	6550	6550	21700	25200	4770	2400
	300R4	**130**	3.9	990	0.45	71 ... 132	6750	6750	22300	25900	5100	2400
	300R4	**143**	3.5	690	0.29	71 ... 132	6840	6840	22600	26300	5270	2400
	300R4	**159**	3.1	1030	0.38	71 ... 132	6940	6940	23000	26700	5460	2400
	300R4	**175**	2.8	1050	0.35	71 ... 132	7040	7040	23300	27100	5640	2400
	300R4	**215**	2.3	1080	0.30	71 ... 132	7250	7250	24000	27900	6040	2400
	300R4	**237**	2.1	750	0.19	71 ... 132	7350	7350	24300	28300	6240	2400
	300R4	**268**	1.9	1120	0.25	71 ... 132	7480	7480	24800	28800	6500	2400
	300R4	**291**	1.7	1140	0.23	71 ... 132	7570	7570	25000	29100	6680	2400
	300R4	**363**	1.4	1180	0.19	71 ... 132	7810	7810	25800	30100	7190	2400
	300R4	**394**	1.3	820	0.12	71 ... 132	7910	7910	26100	30400	7390	2400
	300R4	**453**	1.1	1230	0.16	71 ... 132	8070	8070	26700	31000	7740	2400
	300R4	**491**	1.0	860	0.10	71 ... 132	8160	8160	27000	31400	7950	2400
	300R4	**613**	0.82	860	0.08	71 ... 132	8420	8420	27900	32400	8000	2400
	300R4	**766**	0.65	860	0.07	71 ... 132	8690	8690	28800	33400	8000	2400

301 R — 274 — 2060 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**301R2**	**7.13**	210	1040	15.0	71 ... 132	2360	2360	8620	9420	1350	3400
	301R2	**8.74**	172	1090	15.0	71 ... 132	2520	2520	9160	10000	1440	3400
	301R2	**11.8**	127	1150	15.0	71 ... 132	2790	2790	10000	11000	1590	3400
	301R2	**14.8**	102	940	10.6	71 ... 132	3000	3000	10700	11700	1710	3400
	301R2	**18.5**	81	740	6.7	71 ... 132	3230	3230	11500	12500	1850	3400
	301R3	**24.8**	60	1390	9.7	71 ... 132	3570	3570	12500	13700	2040	3400
	301R3	**30.4**	49	1580	8.9	71 ... 132	3820	3820	13300	14600	2180	3400
	301R3	**37.3**	40	1600	7.4	71 ... 132	4090	4090	14200	15500	2330	3400
	301R3	**41.2**	36	1300	5.4	71 ... 132	4220	4220	14600	15900	2410	3400
	301R3	**50.4**	29.8	1630	5.6	71 ... 132	4520	4520	15500	16900	2580	3400
	301R3	**62.9**	23.8	1650	4.5	71 ... 132	4870	4870	16600	18100	2780	3400
	301R3	**68.2**	22.0	1300	3.3	71 ... 132	5000	5000	17000	18600	2860	3400
	301R3	**78.7**	19.1	1570	3.4	71 ... 132	5240	5240	17700	19400	2990	3400
	301R3	**85.2**	17.6	1300	2.6	71 ... 132	5380	5380	18100	19800	3070	3400
	301R3	**106**	14.1	1300	2.1	71 ... 132	5800	5800	19400	21200	3310	3400
	301R3	**133**	11.3	1150	1.5	71 ... 132	6240	6240	20700	22700	3570	3400
	301R4	**106**	14.2	1700	2.8	71 ... 132	5790	5790	19400	21200	3310	3400
	301R4	**130**	11.6	1720	2.3	71 ... 132	6190	6190	20600	22500	3540	3400
	301R4	**143**	10.5	1300	1.6	71 ... 132	6400	6400	21200	23200	3660	3400
	301R4	**159**	9.4	1740	1.9	71 ... 132	6500	6500	21500	23500	3780	3400



301 R

274

2060 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**301R4**	**175**	8.5	1770	1.8	71 ... 132	6500	6500	21500	23500	3910	3400
	301R4	**215**	7.0	1820	1.5	71 ... 132	6500	6500	21500	23500	4190	3400
	301R4	**237**	6.3	1300	0.97	71 ... 132	6500	6500	21500	23500	4330	3400
	301R4	**268**	5.6	1870	1.2	71 ... 132	6500	6500	21500	23500	4510	3400
	301R4	**291**	5.2	1890	1.2	71 ... 132	6500	6500	21500	23500	4630	3400
	301R4	**363**	4.1	1960	0.96	71 ... 132	6680	6680	22100	24100	4990	3400
	301R4	**394**	3.8	1360	0.61	71 ... 132	6760	6760	22400	24400	5120	3400
	301R4	**453**	3.3	1930	0.76	71 ... 132	6890	6890	22800	24900	5370	3400
	301R4	**491**	3.1	1410	0.51	71 ... 132	6970	6970	23100	25200	5510	3400
	301R4	**613**	2.4	1470	0.42	71 ... 132	7200	7200	23800	26000	5940	3400
	301R4	**766**	2.0	1530	0.35	71 ... 132	7430	7430	24600	26900	6400	3400
1000	**301R2**	**7.13**	140	1170	15.0	71 ... 132	2700	2700	9740	10600	1540	3400
	301R2	**8.74**	114	1230	15.0	71 ... 132	2880	2880	10300	11300	1650	3400
	301R2	**11.8**	85	1250	11.8	71 ... 132	3190	3190	11300	12400	1820	3400
	301R2	**14.8**	68	1050	7.9	71 ... 132	3440	3440	12100	13200	1960	3400
	301R2	**18.5**	54	740	4.5	71 ... 132	3700	3700	12900	14200	2110	3400
	301R3	**24.8**	40	1430	6.6	71 ... 132	4090	4090	14200	15500	2330	3400
	301R3	**30.4**	33	1620	6.1	71 ... 132	4370	4370	15000	16400	2500	3400
	301R3	**37.3**	26.8	1640	5.0	71 ... 132	4680	4680	16000	17500	2670	3400
	301R3	**41.2**	24.3	1300	3.6	71 ... 132	4840	4840	16500	18000	2760	3400
	301R3	**50.4**	19.8	1660	3.8	71 ... 132	5170	5170	17500	19100	2960	3400
	301R3	**62.9**	15.9	1690	3.1	71 ... 132	5570	5570	18700	20500	3180	3400
	301R3	**68.2**	14.7	1300	2.2	71 ... 132	5720	5720	19200	21000	3270	3400
	301R3	**78.7**	12.7	1590	2.3	71 ... 132	6000	6000	20000	21900	3430	3400
	301R3	**85.2**	11.7	1300	1.8	71 ... 132	6160	6160	20500	22400	3520	3400
	301R3	**106**	9.4	1300	1.4	71 ... 132	6500	6500	21500	23500	3790	3400
	301R3	**133**	7.5	1150	0.99	71 ... 132	6500	6500	21500	23500	4080	3400
	301R4	**106**	9.4	1740	1.9	71 ... 132	6500	6500	21500	23500	3780	3400
	301R4	**130**	7.7	1790	1.6	71 ... 132	6500	6500	21500	23500	4050	3400
	301R4	**143**	7.0	1300	1.1	71 ... 132	6500	6500	21500	23500	4190	3400
	301R4	**159**	6.3	1840	1.4	71 ... 132	6500	6500	21500	23500	4330	3400
	301R4	**175**	5.7	1870	1.3	71 ... 132	6500	6500	21500	23500	4480	3400
	301R4	**215**	4.7	1920	1.1	71 ... 132	6570	6570	21700	23700	4790	3400
	301R4	**237**	4.2	1340	0.67	71 ... 132	6660	6660	22000	24100	4950	3400
	301R4	**268**	3.7	2000	0.88	71 ... 132	6780	6780	22400	24500	5160	3400
	301R4	**291**	3.4	2030	0.82	71 ... 132	6860	6860	22700	24800	5300	3400
	301R4	**363**	2.8	2100	0.69	71 ... 132	7080	7080	23400	25600	5710	3400
	301R4	**394**	2.5	1460	0.44	71 ... 132	7160	7160	23700	25900	5860	3400
	301R4	**453**	2.2	2000	0.52	71 ... 132	7310	7310	24200	26400	6140	3400
	301R4	**491**	2.0	1510	0.36	71 ... 132	7390	7390	24400	26700	6310	3400
	301R4	**613**	1.6	1580	0.30	71 ... 132	7630	7630	25200	27600	6800	3400
	301R4	**766**	1.3	1640	0.25	71 ... 132	7880	7880	26000	28500	7320	3400
500	**301R2**	**7.13**	70	1370	10.6	71 ... 132	3400	3400	12000	13100	1940	3400
	301R2	**8.74**	57	1520	9.7	71 ... 132	3630	3630	12700	13900	2080	3400
	301R2	**11.8**	42	1300	6.1	71 ... 132	4020	4020	14000	15200	2300	3400
	301R2	**14.8**	34	1150	4.3	71 ... 132	4330	4330	14900	16300	2470	3400
	301R2	**18.5**	27.1	740	2.2	71 ... 132	4660	4660	15900	17400	2660	3400
	301R3	**24.8**	20.1	1430	3.3	71 ... 132	5150	5150	17400	19000	2940	3400
	301R3	**30.4**	16.4	1680	3.2	71 ... 132	5510	5510	18500	20200	3150	3400
	301R3	**37.3**	13.4	1700	2.6	71 ... 132	5890	5890	19700	21500	3370	3400
	301R3	**41.2**	12.1	1300	1.8	71 ... 132	6090	6090	20300	22200	3480	3400
	301R3	**50.4**	9.9	1730	2.0	71 ... 132	6500	6500	21500	23500	3720	3400
	301R3	**62.9**	7.9	1760	1.6	71 ... 132	6500	6500	21500	23500	4010	3400
	301R3	**68.2**	7.3	1300	1.1	71 ... 132	6500	6500	21500	23500	4120	3400
	301R3	**78.7**	6.4	1600	1.2	71 ... 132	6500	6500	21500	23500	4320	3400
	301R3	**85.2**	5.9	1300	0.88	71 ... 132	6500	6500	21500	23500	4430	3400
	301R3	**106**	4.7	1310	0.71	71 ... 132	6560	6560	21700	23700	4780	3400
	301R3	**133**	3.8	1150	0.50	71 ... 132	6770	6770	22400	24500	5140	3400
	301R4	**106**	4.7	1920	1.1	71 ... 132	6550	6550	21700	23700	4770	3400

B



301 R — 274 — 2060 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
500	**301R4**	**130**	3.9	1990	0.91	71 ... 132	6750	6750	22300	24400	5100	3400
	301R4	**143**	3.5	1380	0.57	71 ... 132	6840	6840	22600	24700	5270	3400
	301R4	**159**	3.1	2060	0.77	71 ... 132	6940	6940	23000	25100	5460	3400
	301R4	**175**	2.8	2090	0.71	71 ... 132	7040	7040	23300	25500	5640	3400
	301R4	**215**	2.3	2160	0.60	71 ... 132	7250	7250	24000	26200	6040	3400
	301R4	**237**	2.1	1510	0.37	71 ... 132	7350	7350	24300	26600	6240	3400
	301R4	**268**	1.9	2240	0.49	71 ... 132	7480	7480	24800	27100	6500	3400
	301R4	**291**	1.7	2270	0.46	71 ... 132	7570	7570	25000	27400	6680	3400
	301R4	**363**	1.4	2340	0.38	71 ... 132	7810	7810	25800	28300	7190	3400
	301R4	**394**	1.3	1650	0.25	71 ... 132	7910	7910	26100	28600	7390	3400
	301R4	**453**	1.1	2000	0.26	71 ... 132	8070	8070	26700	29200	7740	3400
	301R4	**491**	1.0	1710	0.21	71 ... 132	8160	8160	27000	29500	7950	3400
	301R4	**613**	0.82	1720	0.17	71 ... 132	8420	8420	27900	30400	8000	3400
	301R4	**766**	0.65	1720	0.13	71 ... 132	8690	8690	28800	31400	8000	3400

303 R — 284 — 2970 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**303R2**	**9.23**	163	1680	30	71 ... 132	8290	9470	17500	20800	4400	5200
	303R2	**10.9**	138	1900	29.1	71 ... 132	8760	10000	18400	21900	4650	5200
	303R2	**13.7**	110	1970	24.1	71 ... 132	9450	10800	19700	23400	5010	5200
	303R2	**15.9**	94	1820	19.1	71 ... 132	9940	11400	20700	24500	5270	5200
	303R2	**19.2**	78	1550	13.5	71 ... 132	10600	12100	21900	25900	5620	5200
	303R2	**24.8**	61	860	5.8	71 ... 132	11500	13200	23600	28000	6110	5200
	303R3	**25.7**	58	2030	13.6	71 ... 132	11700	13300	23900	28300	6190	5200
	303R3	**31.5**	48	2110	11.5	71 ... 132	12500	14300	25300	30000	6620	5200
	303R3	**37.1**	40	2390	11.1	71 ... 132	13200	15100	26600	31600	7000	5200
	303R3	**42.6**	35	2070	8.4	71 ... 132	13800	15800	27800	32900	7320	5200
	303R3	**46.6**	32	2160	8.0	71 ... 132	14200	16300	28500	33800	7550	5200
	303R3	**50.3**	29.8	2380	8.2	71 ... 132	14600	16700	29200	34600	7740	5200
	303R3	**54.2**	27.7	1820	5.8	71 ... 132	15000	17100	29800	35400	7930	5200
	303R3	**63.1**	23.8	2170	5.9	71 ... 132	15700	18000	31200	37000	8350	5200
	303R3	**73.3**	20.5	1820	4.3	71 ... 132	16500	18900	32700	38700	8780	5200
	303R3	**78.7**	19.1	2180	4.8	71 ... 132	16900	19400	33400	39600	8990	5200
	303R3	**91.5**	16.4	1820	3.4	71 ... 132	17800	20400	34900	41400	9450	5200
	303R3	**114**	13.1	1820	2.7	71 ... 132	19200	21900	37300	44300	10200	5200
	303R4	**129**	11.6	2620	3.6	71 ... 132	20000	22800	38700	45900	10600	5200
	303R4	**148**	10.1	2310	2.8	71 ... 132	20900	23900	40400	47800	11100	5200
	303R4	**158**	9.5	2660	3.0	71 ... 132	21000	24000	40500	48000	11300	5200
	303R4	**185**	8.1	2310	2.2	71 ... 132	21000	24000	40500	48000	11900	5200
	303R4	**214**	7.0	2730	2.3	71 ... 132	21000	24000	40500	48000	12500	5200
	303R4	**231**	6.5	1830	1.4	71 ... 132	21000	24000	40500	48000	12900	5200
	303R4	**255**	5.9	1840	1.3	71 ... 132	21000	24000	40500	48000	13300	5200
	303R4	**290**	5.2	2650	1.6	71 ... 132	21000	24000	40500	48000	13900	5200
	303R4	**313**	4.8	1850	1.1	71 ... 132	21100	24100	40700	48300	14200	5200
	303R4	**336**	4.5	2270	1.2	71 ... 132	21300	24400	41200	48800	14600	5200
	303R4	**364**	4.1	2310	1.1	71 ... 132	21600	24700	41600	49300	15000	5200
	303R4	**390**	3.8	1930	0.88	71 ... 132	21800	24900	42000	49800	15300	5200
	303R4	**452**	3.3	2250	0.88	71 ... 132	22300	25400	42900	50900	16100	5200
	303R4	**528**	2.8	2030	0.68	71 ... 132	22800	26000	43900	52000	16900	5200
	303R4	**567**	2.6	2430	0.76	71 ... 132	23000	26300	44400	52600	17400	5200
	303R4	**659**	2.3	2110	0.57	71 ... 132	23500	26900	45300	53700	18200	5200
	303R4	**797**	1.9	1820	0.41	71 ... 132	24100	27600	46600	55200	19400	5200
	303R4	**824**	1.8	2200	0.47	71 ... 132	24300	27700	46800	55400	19700	5200
1000	**303R2**	**9.23**	108	1890	22.8	71 ... 132	9490	10800	19800	23500	5030	5200
	303R2	**10.9**	92	2140	21.9	71 ... 132	10000	11500	20800	24700	5320	5200
	303R2	**13.7**	73	2080	16.9	71 ... 132	10800	12400	22300	26400	5740	5200
	303R2	**15.9**	63	1820	12.7	71 ... 132	11400	13000	23300	27600	6030	5200



303 R

284

2970 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1000	**303R2**	**19.2**	52	1640	9.5	71 ... 132	12100	13900	24700	29300	6430	5200
	303R2	**24.8**	40	860	3.9	71 ... 132	13200	15100	26600	31600	7000	5200
	303R3	**25.7**	39	2160	9.6	71 ... 132	13300	15300	26900	31900	7080	5200
	303R3	**31.5**	32	2160	7.9	71 ... 132	14300	16300	28600	33900	7580	5200
	303R3	**37.1**	26.9	2460	7.6	71 ... 132	15100	17300	30100	35700	8010	5200
	303R3	**42.6**	23.5	2110	5.7	71 ... 132	15800	18100	31300	37200	8380	5200
	303R3	**46.6**	21.5	2170	5.3	71 ... 132	16300	18600	32200	38200	8640	5200
	303R3	**50.3**	19.9	2470	5.6	71 ... 132	16700	19100	32900	39000	8860	5200
	303R3	**54.2**	18.5	1820	3.9	71 ... 132	17100	19600	33700	39900	9080	5200
	303R3	**63.1**	15.9	2180	4.0	71 ... 132	18000	20600	35300	41800	9550	5200
	303R3	**73.3**	13.6	1820	2.8	71 ... 132	18900	21600	36900	43700	10000	5200
	303R3	**78.7**	12.7	2190	3.2	71 ... 132	19400	22200	37700	44700	10300	5200
	303R3	**91.5**	10.9	1820	2.3	71 ... 132	20400	23300	39400	46700	10800	5200
	303R3	**114**	8.7	1820	1.8	71 ... 132	21000	24000	40500	48000	11700	5200
	303R4	**129**	7.7	2710	2.5	71 ... 132	21000	24000	40500	48000	12100	5200
	303R4	**148**	6.7	2310	1.8	71 ... 132	21000	24000	40500	48000	12700	5200
	303R4	**158**	6.3	2760	2.1	71 ... 132	21000	24000	40500	48000	13000	5200
	303R4	**185**	5.4	2310	1.5	71 ... 132	21000	24000	40500	48000	13700	5200
	303R4	**214**	4.7	2810	1.6	71 ... 132	21200	24200	40900	48500	14400	5200
	303R4	**231**	4.3	1890	0.97	71 ... 132	21400	24500	41300	49000	14700	5200
	303R4	**255**	3.9	1920	0.89	71 ... 132	21700	24900	41900	49700	15200	5200
	303R4	**290**	3.4	2680	1.1	71 ... 132	22100	25300	42700	50600	15900	5200
	303R4	**313**	3.2	1990	0.75	71 ... 132	22400	25600	43200	51200	16300	5200
	303R4	**336**	3.0	2440	0.86	71 ... 132	22600	25800	43600	51700	16700	5200
	303R4	**364**	2.7	2480	0.81	71 ... 132	22900	26100	44100	52300	17100	5200
	303R4	**390**	2.6	2070	0.63	71 ... 132	23100	26400	44600	52800	17500	5200
	303R4	**452**	2.2	2250	0.59	71 ... 132	23600	27000	45500	53900	18400	5200
	303R4	**528**	1.9	2180	0.49	71 ... 132	24100	27600	46500	55100	19400	5200
	303R4	**567**	1.8	2600	0.54	71 ... 132	24400	27900	47000	55700	19900	5200
	303R4	**659**	1.5	2270	0.41	71 ... 132	24900	28500	48000	56900	20900	5200
	303R4	**797**	1.3	1930	0.29	71 ... 132	25600	29200	49300	58500	22300	5200
	303R4	**824**	1.2	2360	0.34	71 ... 132	25700	29400	49600	58800	22500	5200
500	**303R2**	**9.23**	54	2260	13.7	71 ... 132	12000	13700	24400	28900	6340	5200
	303R2	**10.9**	46	2570	13.2	71 ... 132	12600	14400	25600	30400	6700	5200
	303R2	**13.7**	37	2150	8.8	71 ... 132	13600	15600	27400	32500	7230	5200
	303R2	**15.9**	31	1820	6.4	71 ... 132	14300	16400	28700	34000	7600	5200
	303R2	**19.2**	26.0	1650	4.8	71 ... 132	15300	17500	30400	36000	8100	5200
	303R2	**24.8**	20.2	860	1.9	71 ... 132	16600	19000	32800	38900	8810	5200
	303R3	**25.7**	19.5	2230	5.0	71 ... 132	16800	19200	33200	39300	8920	5200
	303R3	**31.5**	15.9	2250	4.1	71 ... 132	18000	20600	35200	41800	9550	5200
	303R3	**37.1**	13.5	2590	4.0	71 ... 132	19000	21700	37000	43900	10100	5200
	303R3	**42.6**	11.7	2190	3.0	71 ... 132	19900	22700	38600	45700	10600	5200
	303R3	**46.6**	10.7	2200	2.7	71 ... 132	20500	23400	39700	47000	10900	5200
	303R3	**50.3**	9.9	2620	3.0	71 ... 132	21000	24000	40500	48000	11200	5200
	303R3	**54.2**	9.2	1820	1.9	71 ... 132	21000	24000	40500	48000	11400	5200
	303R3	**63.1**	7.9	2210	2.0	71 ... 132	21000	24000	40500	48000	12000	5200
	303R3	**73.3**	6.8	1830	1.4	71 ... 132	21000	24000	40500	48000	12700	5200
	303R3	**78.7**	6.4	2220	1.6	71 ... 132	21000	24000	40500	48000	13000	5200
	303R3	**91.5**	5.5	1840	1.2	71 ... 132	21000	24000	40500	48000	13600	5200
	303R3	**114**	4.4	1880	0.94	71 ... 132	21400	24500	41300	48900	14700	5200
	303R4	**129**	3.9	2810	1.3	71 ... 132	21800	24900	42000	49800	15300	5200
	303R4	**148**	3.4	2310	0.92	71 ... 132	22200	25400	42800	50800	16000	5200
	303R4	**158**	3.2	2810	1.0	71 ... 132	22400	25600	43200	51300	16400	5200
	303R4	**185**	2.7	2310	0.74	71 ... 132	22900	26200	44200	52400	17200	5200
	303R4	**214**	2.3	2820	0.78	71 ... 132	23400	26800	45200	53500	18100	5200
	303R4	**231**	2.2	2130	0.55	71 ... 132	23700	27000	45600	54100	18600	5200
	303R4	**255**	2.0	2170	0.50	71 ... 132	24000	27400	46300	54900	19200	5200
	303R4	**290**	1.7	2730	0.56	71 ... 132	24400	27900	47200	55900	20000	5200
	303R4	**313**	1.6	2250	0.43	71 ... 132	24700	28200	47700	56500	20500	5200
	303R4	**336**	1.5	2700	0.48	71 ... 132	25000	28500	48100	57100	21000	5200



303 R — 284 — 2970 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
500	**303R4**	**364**	1.4	2730	0.44	71 ... 132	25300	28900	48700	57700	21600	5200
	303R4	**390**	1.3	2340	0.35	71 ... 132	25500	29200	49200	58300	22100	5200
	303R4	**452**	1.1	2250	0.29	71 ... 132	26000	29800	50200	59500	23200	5200
	303R4	**528**	0.95	2440	0.27	71 ... 132	26600	30400	51400	60900	24000	5200
	303R4	**567**	0.88	2850	0.30	71 ... 132	26900	30700	51900	61500	24000	5200
	303R4	**659**	0.76	2440	0.22	71 ... 132	27500	31400	53000	62800	24000	5200
	303R4	**797**	0.63	2000	0.15	71 ... 132	28200	32300	54500	64600	24000	5200
	303R4	**824**	0.61	2440	0.18	71 ... 132	28400	32400	54700	64900	24000	5200

304 R — 296 — 3960 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**304R2**	**9.23**	163	1680	30	71 ... 132	8290	9470	17500	20800	4400	6600
	304R2	**10.9**	138	1980	30	71 ... 132	8760	10000	18400	21900	4650	6600
	304R2	**13.7**	110	2490	30	71 ... 132	9450	10800	19700	23400	5010	6600
	304R2	**16.8**	89	2390	23.7	71 ... 132	10100	11600	21000	24900	5370	6600
	304R3	**25.7**	58	3020	15.0	71 ... 132	11700	13300	23900	28300	6190	7300
	304R3	**31.5**	48	3090	15.0	71 ... 132	12500	14300	25300	30000	6620	7300
	304R3	**37.1**	40	3440	15.0	71 ... 132	13200	15100	26600	31600	7000	7300
	304R3	**42.6**	35	3190	12.9	71 ... 132	13800	15800	27800	32900	7320	7300
	304R3	**46.6**	32	2850	10.5	71 ... 132	14200	16300	28500	33800	7550	7300
	304R3	**50.3**	29.8	3460	11.9	71 ... 132	14600	16700	29200	34600	7740	7300
	304R3	**63.1**	23.8	2850	7.8	71 ... 132	15700	18000	31200	37000	8350	7300
	304R3	**78.7**	19.1	2850	6.2	71 ... 132	16900	19400	33400	39600	8990	7300
	304R3	**97.0**	15.5	2390	4.2	71 ... 132	18200	20800	35500	42100	9630	7300
	304R3	**121**	12.4	2390	3.4	71 ... 132	19600	22400	38000	45000	10400	7300
	304R4	**89.4**	16.8	3330	6.6	71 ... 132	17700	20200	34700	41100	9370	7300
	304R4	**109**	13.7	3370	5.5	71 ... 132	18900	21600	36900	43700	10000	7300
	304R4	**129**	11.6	3530	4.8	71 ... 132	20000	22800	38700	45900	10600	7300
	304R4	**148**	10.1	3440	4.1	71 ... 132	20900	23900	40400	47800	11100	7300
	304R4	**158**	9.5	3550	4.0	71 ... 132	21000	24000	40500	48000	11300	7300
	304R4	**185**	8.1	3460	3.3	71 ... 132	21000	24000	40500	48000	11900	7300
	304R4	**214**	7.0	3620	3.0	71 ... 132	21000	24000	40500	48000	12500	7300
	304R4	**227**	6.6	3480	2.7	71 ... 132	21000	24000	40500	48000	12800	7300
	304R4	**267**	5.6	3660	2.4	71 ... 132	21000	24000	40500	48000	13500	7300
	304R4	**290**	5.2	3680	2.3	71 ... 132	21000	24000	40500	48000	13900	7300
	304R4	**307**	4.9	3500	2.0	71 ... 132	21100	24100	40600	48100	14100	7300
	304R4	**338**	4.4	2420	1.3	71 ... 132	21400	24400	41200	48800	14600	7300
	304R4	**364**	4.1	2940	1.4	71 ... 132	21600	24700	41600	49300	15000	7300
	304R4	**414**	3.6	2470	1.1	71 ... 132	22000	25100	42400	50300	15600	7300
	304R4	**452**	3.3	3690	1.4	71 ... 132	22300	25400	42900	50900	16100	7300
	304R4	**560**	2.7	2540	0.81	71 ... 132	23000	26200	44300	52500	17300	7300
	304R4	**699**	2.1	2630	0.67	71 ... 132	23700	27100	45700	54200	18600	7300
1000	**304R2**	**9.23**	108	1890	22.8	71 ... 132	9490	10800	19800	23500	5030	6600
	304R2	**10.9**	92	2240	22.9	71 ... 132	10000	11500	20800	24700	5320	6600
	304R2	**13.7**	73	2690	21.9	71 ... 132	10800	12400	22300	26400	5740	6600
	304R2	**16.8**	59	2390	15.8	71 ... 132	11600	13300	23700	28100	6150	6600
	304R3	**25.7**	39	3130	14.0	71 ... 132	13300	15300	26900	31900	7080	7300
	304R3	**31.5**	32	3180	11.6	71 ... 132	14300	16300	28600	33900	7580	7300
	304R3	**37.1**	26.9	3470	10.7	71 ... 132	15100	17300	30100	35700	8010	7300
	304R3	**42.6**	23.5	3270	8.8	71 ... 132	15800	18100	31300	37200	8380	7300
	304R3	**46.6**	21.5	2850	7.0	71 ... 132	16300	18600	32200	38200	8640	7300
	304R3	**50.3**	19.9	3490	8.0	71 ... 132	16700	19100	32900	39000	8860	7300
	304R3	**63.1**	15.9	2850	5.2	71 ... 132	18000	20600	35300	41800	9550	7300
	304R3	**78.7**	12.7	2850	4.2	71 ... 132	19400	22200	37700	44700	10300	7300
	304R3	**97.0**	10.3	2390	2.8	71 ... 132	20800	23800	40100	47600	11000	7300
	304R3	**121**	8.2	2390	2.3	71 ... 132	21000	24000	40500	48000	11900	7300



304 R

296

3960 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1000	**304R4**	**89.4**	11.2	3420	4.5	71 ... 132	20200	23100	39200	46400	10700	7300
	304R4	**109**	9.1	3450	3.7	71 ... 132	21000	24000	40500	48000	11500	7300
	304R4	**129**	7.7	3590	3.3	71 ... 132	21000	24000	40500	48000	12100	7300
	304R4	**148**	6.7	3470	2.8	71 ... 132	21000	24000	40500	48000	12700	7300
	304R4	**158**	6.3	3640	2.7	71 ... 132	21000	24000	40500	48000	13000	7300
	304R4	**185**	5.4	3490	2.2	71 ... 132	21000	24000	40500	48000	13700	7300
	304R4	**214**	4.7	3700	2.0	71 ... 132	21200	24200	40900	48500	14400	7300
	304R4	**227**	4.4	3500	1.8	71 ... 132	21400	24400	41200	48900	14600	7300
	304R4	**267**	3.7	3720	1.6	71 ... 132	21900	25000	42200	50000	15500	7300
	304R4	**290**	3.4	3720	1.5	71 ... 132	22100	25300	42700	50600	15900	7300
	304R4	**307**	3.3	3510	1.4	71 ... 132	22300	25500	43000	51000	16200	7300
	304R4	**338**	3.0	2520	0.88	71 ... 132	22600	25900	43600	51700	16700	7300
	304R4	**364**	2.7	3140	1.0	71 ... 132	22900	26100	44100	52300	17100	7300
	304R4	**414**	2.4	2580	0.74	71 ... 132	23300	26600	44900	53200	17900	7300
	304R4	**452**	2.2	3740	0.98	71 ... 132	23600	27000	45500	53900	18400	7300
	304R4	**560**	1.8	2720	0.57	71 ... 132	24300	27800	46900	55600	19800	7300
	304R4	**699**	1.4	2830	0.48	71 ... 132	25100	28700	48400	57400	21300	7300
500	**304R2**	**9.23**	54	2330	14.1	71 ... 132	12000	13700	24400	28900	6340	6600
	304R2	**10.9**	46	2720	13.9	71 ... 132	12600	14400	25600	30400	6700	6600
	304R2	**13.7**	37	2850	11.6	71 ... 132	13600	15600	27400	32500	7230	6600
	304R2	**16.8**	29.7	2390	7.9	71 ... 132	14600	16700	29200	34600	7750	6600
	304R3	**25.7**	19.5	3290	7.3	71 ... 132	16800	19200	33200	39300	8920	7300
	304R3	**31.5**	15.9	3330	6.1	71 ... 132	18000	20600	35200	41800	9550	7300
	304R3	**37.1**	13.5	3520	5.4	71 ... 132	19000	21700	37000	43900	10100	7300
	304R3	**42.6**	11.7	3410	4.6	71 ... 132	19900	22700	38600	45700	10600	7300
	304R3	**46.6**	10.7	2850	3.5	71 ... 132	20500	23400	39700	47000	10900	7300
	304R3	**50.3**	9.9	3540	4.0	71 ... 132	21000	24000	40500	48000	11200	7300
	304R3	**63.1**	7.9	2850	2.6	71 ... 132	21000	24000	40500	48000	12000	7300
	304R3	**78.7**	6.4	2850	2.1	71 ... 132	21000	24000	40500	48000	13000	7300
	304R3	**97.0**	5.2	2390	1.4	71 ... 132	21000	24000	40500	48000	13900	7300
	304R3	**121**	4.1	2440	1.2	71 ... 132	21600	24700	41600	49300	15000	7300
	304R4	**89.4**	5.6	3490	2.3	71 ... 132	21000	24000	40500	48000	13500	7300
	304R4	**109**	4.6	3500	1.9	71 ... 132	21300	24300	41000	48600	14500	7300
	304R4	**129**	3.9	3710	1.7	71 ... 132	21800	24900	42000	49800	15300	7300
	304R4	**148**	3.4	3510	1.4	71 ... 132	22200	25400	42800	50800	16000	7300
	304R4	**158**	3.2	3730	1.4	71 ... 132	22400	25600	43200	51300	16400	7300
	304R4	**185**	2.7	3520	1.1	71 ... 132	22900	26200	44200	52400	17200	7300
	304R4	**214**	2.3	3770	1.0	71 ... 132	23400	26800	45200	53500	18100	7300
	304R4	**227**	2.2	3550	0.93	71 ... 132	23600	27000	45500	53900	18400	7300
	304R4	**267**	1.9	3820	0.84	71 ... 132	24200	27600	46600	55200	19500	7300
	304R4	**290**	1.7	3830	0.78	71 ... 132	24400	27900	47200	55900	20000	7300
	304R4	**307**	1.6	3610	0.70	71 ... 132	24600	28200	47500	56300	20400	7300
	304R4	**338**	1.5	2810	0.49	71 ... 132	25000	28600	48200	57100	21100	7300
	304R4	**364**	1.4	3540	0.58	71 ... 132	25300	28900	48700	57700	21600	7300
	304R4	**414**	1.2	2910	0.42	71 ... 132	25700	29400	49600	58800	22500	7300
	304R4	**452**	1.1	3930	0.51	71 ... 132	26000	29800	50200	59500	23200	7300
	304R4	**560**	0.89	3010	0.32	71 ... 132	26900	30700	51800	61400	24000	7300
	304R4	**699**	0.71	3010	0.25	71 ... 132	27700	31700	53500	63400	24000	7300

305 R

308

5600 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**305R2**	**9.23**	163	1680	30	71 ... 132	8290	9470	17500	20800	4400	7700
	305R2	**10.9**	138	1980	30	71 ... 132	8760	10000	18400	21900	4650	7700
	305R2	**13.7**	110	2490	30	71 ... 132	9450	10800	19700	23400	5010	7700
	305R2	**15.9**	94	2890	30	71 ... 132	9940	11400	20700	24500	5270	7700
	305R2	**19.2**	78	2860	24.9	71 ... 132	10600	12100	21900	25900	5620	7700



305 R

308

5600 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**305R3**	**25.7**	58	3630	15.0	71 ... 132	11700	13300	23900	28300	6190	8800
	305R3	**31.5**	48	3770	15.0	71 ... 132	12500	14300	25300	30000	6620	8800
	305R3	**37.1**	40	4340	15.0	71 ... 132	13200	15100	26600	31600	7000	8800
	305R3	**42.6**	35	3790	15.0	71 ... 132	13800	15800	27800	32900	7320	8800
	305R3	**46.6**	32	4310	15.0	71 ... 132	14200	16300	28500	33800	7550	8800
	305R3	**50.3**	29.8	4410	15.0	71 ... 132	14600	16700	29200	34600	7740	8800
	305R3	**54.2**	27.7	3570	11.3	71 ... 132	15000	17100	29800	35400	7930	8800
	305R3	**63.1**	23.8	4330	11.8	71 ... 132	15700	18000	31200	37000	8350	8800
	305R3	**73.3**	20.5	3580	8.4	71 ... 132	16500	18900	32700	38700	8780	8800
	305R3	**78.7**	19.1	4350	9.5	71 ... 132	16900	19400	33400	39600	8990	8800
	305R3	**91.5**	16.4	3580	6.7	71 ... 132	17800	20400	34900	41400	9450	8800
	305R3	**114**	13.1	3580	5.4	71 ... 132	19200	21900	37300	44300	10200	8800
	305R4	**129**	11.6	5200	7.1	71 ... 132	20000	22800	38700	45900	10600	8800
	305R4	**148**	10.1	4480	5.4	71 ... 132	20900	23900	40400	47800	11100	8800
	305R4	**158**	9.5	5310	6.0	71 ... 132	21000	24000	40500	48000	11300	8800
	305R4	**185**	8.1	4490	4.3	71 ... 132	21000	24000	40500	48000	11900	8800
	305R4	**214**	7.0	5390	4.5	71 ... 132	21000	24000	40500	48000	12500	8800
	305R4	**231**	6.5	3600	2.8	71 ... 132	21000	24000	40500	48000	12900	8800
	305R4	**255**	5.9	3600	2.5	71 ... 132	21000	24000	40500	48000	13300	8800
	305R4	**290**	5.2	5300	3.2	71 ... 132	21000	24000	40500	48000	13900	8800
	305R4	**313**	4.8	3620	2.1	71 ... 132	21100	24100	40700	48300	14200	8800
	305R4	**336**	4.5	4560	2.4	71 ... 132	21300	24400	41200	48800	14600	8800
	305R4	**364**	4.1	4620	2.3	71 ... 132	21600	24700	41600	49300	15000	8800
	305R4	**390**	3.8	3750	1.7	71 ... 132	21800	24900	42000	49800	15300	8800
	305R4	**452**	3.3	4750	1.9	71 ... 132	22300	25400	42900	50900	16100	8800
	305R4	**528**	2.8	3920	1.3	71 ... 132	22800	26000	43900	52000	16900	8800
	305R4	**567**	2.6	4860	1.5	71 ... 132	23000	26300	44400	52600	17400	8800
	305R4	**659**	2.3	4070	1.1	71 ... 132	23500	26900	45300	53700	18200	8800
	305R4	**797**	1.9	3450	0.77	71 ... 132	24100	27600	46600	55200	19400	8800
	305R4	**824**	1.8	4230	0.91	71 ... 132	24300	27700	46800	55400	19700	8800
1000	**305R2**	**9.23**	108	1890	22.8	71 ... 132	9490	10800	19800	23500	5030	7700
	305R2	**10.9**	92	2240	22.9	71 ... 132	10000	11500	20800	24700	5320	7700
	305R2	**13.7**	73	2810	22.9	71 ... 132	10800	12400	22300	26400	5740	7700
	305R2	**15.9**	63	3270	22.9	71 ... 132	11400	13000	23300	27600	6030	7700
	305R2	**19.2**	52	2990	17.3	71 ... 132	12100	13900	24700	29300	6430	7700
	305R3	**25.7**	39	3900	15.0	71 ... 132	13300	15300	26900	31900	7080	8800
	305R3	**31.5**	32	3950	14.4	71 ... 132	14300	16300	28600	33900	7580	8800
	305R3	**37.1**	26.9	4600	14.2	71 ... 132	15100	17300	30100	35700	8010	8800
	305R3	**42.6**	23.5	3990	10.7	71 ... 132	15800	18100	31300	37200	8380	8800
	305R3	**46.6**	21.5	4340	10.7	71 ... 132	16300	18600	32200	38200	8640	8800
	305R3	**50.3**	19.9	4700	10.7	71 ... 132	16700	19100	32900	39000	8860	8800
	305R3	**54.2**	18.5	3580	7.6	71 ... 132	17100	19600	33700	39900	9080	8800
	305R3	**63.1**	15.9	4370	7.9	71 ... 132	18000	20600	35300	41800	9550	8800
	305R3	**73.3**	13.6	3590	5.6	71 ... 132	18900	21600	36900	43700	10000	8800
	305R3	**78.7**	12.7	4380	6.4	71 ... 132	19400	22200	37700	44700	10300	8800
	305R3	**91.5**	10.9	3600	4.5	71 ... 132	20400	23300	39400	46700	10800	8800
	305R3	**114**	8.7	3600	3.6	71 ... 132	21000	24000	40500	48000	11700	8800
	305R4	**129**	7.7	5370	4.9	71 ... 132	21000	24000	40500	48000	12100	8800
	305R4	**148**	6.7	4490	3.6	71 ... 132	21000	24000	40500	48000	12700	8800
	305R4	**158**	6.3	5420	4.0	71 ... 132	21000	24000	40500	48000	13000	8800
	305R4	**185**	5.4	4490	2.9	71 ... 132	21000	24000	40500	48000	13700	8800
	305R4	**214**	4.7	5480	3.0	71 ... 132	21200	24200	40900	48500	14400	8800
	305R4	**231**	4.3	3680	1.9	71 ... 132	21400	24500	41300	49000	14700	8800
	305R4	**255**	3.9	3740	1.7	71 ... 132	21700	24900	41900	49700	15200	8800
	305R4	**290**	3.4	5350	2.2	71 ... 132	22100	25300	42700	50600	15900	8800
	305R4	**313**	3.2	3850	1.5	71 ... 132	22400	25600	43200	51200	16300	8800
	305R4	**336**	3.0	4890	1.7	71 ... 132	22600	25800	43600	51700	16700	8800
	305R4	**364**	2.7	4960	1.6	71 ... 132	22900	26100	44100	52300	17100	8800
	305R4	**390**	2.6	3980	1.2	71 ... 132	23100	26400	44600	52800	17500	8800
	305R4	**452**	2.2	4750	1.2	71 ... 132	23600	27000	45500	53900	18400	8800
	305R4	**528**	1.9	4200	0.94	71 ... 132	24100	27600	46500	55100	19400	8800

B



305 R — 308 — 5600 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1000	**305R4**	**567**	1.8	5160	1.1	71 ... 132	24400	27900	47000	55700	19900	8800
	305R4	**659**	1.5	4360	0.78	71 ... 132	24900	28500	48000	56900	20900	8800
	305R4	**797**	1.3	3670	0.54	71 ... 132	25600	29200	49300	58500	22300	8800
	305R4	**824**	1.2	4530	0.65	71 ... 132	25700	29400	49600	58800	22500	8800
500	**305R2**	**9.23**	54	2330	14.1	71 ... 132	12000	13700	24400	28900	6340	7700
	305R2	**10.9**	46	2750	14.0	71 ... 132	12600	14400	25600	30400	6700	7700
	305R2	**13.7**	37	3340	13.6	71 ... 132	13600	15600	27400	32500	7230	7700
	305R2	**15.9**	31	3530	12.4	71 ... 132	14300	16400	28700	34000	7600	7700
	305R2	**19.2**	26	3040	8.8	71 ... 132	15300	17500	30400	36000	8100	7700
	305R3	**25.7**	19.5	4190	9.4	71 ... 132	16800	19200	33200	39300	8920	8800
	305R3	**31.5**	15.9	4260	7.8	71 ... 132	18000	20600	35200	41800	9550	8800
	305R3	**37.1**	13.5	5080	7.8	71 ... 132	19000	21700	37000	43900	10100	8800
	305R3	**42.6**	11.7	4340	5.9	71 ... 132	19900	22700	38600	45700	10600	8800
	305R3	**46.6**	10.7	4390	5.4	71 ... 132	20500	23400	39700	47000	10900	8800
	305R3	**50.3**	9.9	5230	6.0	71 ... 132	21000	24000	40500	48000	11200	8800
	305R3	**54.2**	9.2	3600	3.8	71 ... 132	21000	24000	40500	48000	11400	8800
	305R3	**63.1**	7.9	4420	4.0	71 ... 132	21000	24000	40500	48000	12000	8800
	305R3	**73.3**	6.8	3600	2.8	71 ... 132	21000	24000	40500	48000	12700	8800
	305R3	**78.7**	6.4	4450	3.2	71 ... 132	21000	24000	40500	48000	13000	8800
	305R3	**91.5**	5.5	3600	2.3	71 ... 132	21000	24000	40500	48000	13600	8800
	305R3	**114**	4.4	3670	1.8	71 ... 132	21400	24500	41300	48900	14700	8800
	305R4	**129**	3.9	5480	2.5	71 ... 132	21800	24900	42000	49800	15300	8800
	305R4	**148**	3.4	4490	1.8	71 ... 132	22200	25400	42800	50800	16000	8800
	305R4	**158**	3.2	5490	2.1	71 ... 132	22400	25600	43200	51300	16400	8800
	305R4	**185**	2.7	4490	1.4	71 ... 132	22900	26200	44200	52400	17200	8800
	305R4	**214**	2.3	5520	1.5	71 ... 132	23400	26800	45200	53500	18100	8800
	305R4	**231**	2.2	4100	1.1	71 ... 132	23700	27000	45600	54100	18600	8800
	305R4	**255**	2.0	4170	0.97	71 ... 132	24000	27400	46300	54900	19200	8800
	305R4	**290**	1.7	5450	1.1	71 ... 132	24400	27900	47200	55900	20000	8800
	305R4	**313**	1.6	4320	0.82	71 ... 132	24700	28200	47700	56500	20500	8800
	305R4	**336**	1.5	5350	0.94	71 ... 132	25000	28500	48100	57100	21000	8800
	305R4	**364**	1.4	5400	0.88	71 ... 132	25300	28900	48700	57700	21600	8800
	305R4	**390**	1.3	4490	0.68	71 ... 132	25500	29200	49200	58300	22100	8800
	305R4	**452**	1.1	4750	0.62	71 ... 132	26000	29800	50200	59500	23200	8800
	305R4	**528**	0.95	4690	0.53	71 ... 132	26600	30400	51400	60900	24000	8800
	305R4	**567**	0.88	5600	0.58	71 ... 132	26900	30700	51900	61500	24000	8800
	305R4	**659**	0.76	4690	0.42	71 ... 132	27500	31400	53000	62800	24000	8800
	305R4	**797**	0.63	3800	0.28	71 ... 132	28200	32300	54500	64600	24000	8800
	305R4	**824**	0.61	4690	0.34	71 ... 132	28400	32400	54700	64900	24000	8800

306 R — 320 — 7300 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**306R2**	**9.23**	163	1680	30	71 ... 160	9870	11200	24700	28500	6410	12000
	306R2	**10.9**	138	1980	30	71 ... 160	10400	11900	26000	30000	6780	12000
	306R2	**13.7**	110	2490	30	71 ... 160	11200	12800	27800	32100	7310	12000
	306R2	**15.9**	94	2890	30	71 ... 160	11800	13500	29100	33600	7690	12000
	306R2	**19.2**	78	3490	30	71 ... 160	12600	14400	30800	35500	8190	12000
	306R3	**33.2**	45	5810	30	71 ... 160	15100	17200	36300	41900	9830	14900
	306R3	**39.2**	38	6550	28.8	71 ... 160	16000	18200	38100	44000	10400	14900
	306R3	**46.3**	32	7510	27.9	71 ... 160	16900	19300	40100	46200	11000	14900
	306R3	**58.1**	25.8	7580	22.5	71 ... 160	18200	20800	42900	49500	11800	14900
	306R3	**67.5**	22.2	7090	18.1	71 ... 160	19200	21800	44900	51800	12500	14900
	306R3	**72.9**	20.6	7420	17.5	71 ... 160	19700	22400	45900	53000	12800	14900
	306R3	**84.7**	17.7	7530	15.3	71 ... 160	20700	23600	48000	55400	13400	14900
	306R3	**98.5**	15.2	6490	11.3	71 ... 160	21700	24800	50200	58000	14100	14900
	306R3	**119**	12.6	6490	9.4	71 ... 160	23200	26400	53200	61400	15000	14900



306 R

320

7300 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**306R3**	**144**	10.4	5490	6.6	71 ... 160	24700	28100	56300	65000	16000	14900
	306R4	**158**	9.5	9620	10.8	71 ... 160	25000	28500	57000	65800	16500	14900
	306R4	**168**	8.9	7560	8.0	71 ... 160	25000	28500	57000	65800	16900	14900
	306R4	**181**	8.3	9450	9.3	71 ... 160	25000	28500	57000	65800	17300	14900
	306R4	**214**	7.0	9730	8.1	71 ... 160	25000	28500	57000	65800	18300	14900
	306R4	**230**	6.5	7590	5.8	71 ... 160	25000	28500	57000	65800	18700	14900
	306R4	**249**	6.0	8200	5.9	71 ... 160	25000	28500	57000	65800	19200	14900
	306R4	**289**	5.2	8280	5.1	71 ... 160	25000	28500	57000	65800	20200	14900
	306R4	**312**	4.8	7590	4.3	71 ... 160	25100	28700	57300	66200	20700	14900
	306R4	**389**	3.9	7590	3.5	71 ... 160	25900	29600	59200	68300	22300	14900
	306R4	**420**	3.6	8790	3.7	71 ... 160	26200	29900	59800	69000	22900	14900
	306R4	**455**	3.3	7020	2.7	71 ... 160	26500	30200	60500	69800	23500	14900
	306R4	**488**	3.1	9020	3.3	71 ... 160	26800	30600	61100	70500	24100	14900
	306R4	**550**	2.7	7260	2.3	71 ... 160	27300	31100	62200	71800	25100	14900
	306R4	**590**	2.5	8480	2.5	71 ... 160	27500	31400	62800	72500	25600	14900
	306R4	**665**	2.3	6010	1.6	71 ... 160	28000	31900	63900	73700	26700	14900
	306R4	**830**	1.8	6270	1.3	71 ... 160	28900	33000	65900	76100	28700	14900
1000												
	306R2	**9.23**	108	1890	22.8	71 ... 160	11300	12900	27900	32200	7340	12000
	306R2	**10.9**	92	2240	22.9	71 ... 160	11900	13600	29300	33800	7760	12000
	306R2	**13.7**	73	2810	22.9	71 ... 160	12900	14700	31400	36200	8370	12000
	306R2	**15.9**	63	3270	22.9	71 ... 160	13500	15400	32800	37900	8800	12000
	306R2	**19.2**	52	3940	22.8	71 ... 160	14400	16400	34800	40100	9380	12000
	306R3	**33.2**	30	6330	21.9	71 ... 160	17300	19700	41000	47300	11300	14900
	306R3	**39.2**	25.5	7280	21.3	71 ... 160	18300	20900	43000	49700	11900	14900
	306R3	**46.3**	21.6	8170	20.3	71 ... 160	19300	22000	45200	52200	12600	14900
	306R3	**58.1**	17.2	8200	16.2	71 ... 160	20900	23800	48400	55900	13600	14900
	306R3	**67.5**	14.8	7340	12.5	71 ... 160	21900	25000	50700	58500	14300	14900
	306R3	**72.9**	13.7	7710	12.1	71 ... 160	22500	25600	51800	59800	14600	14900
	306R3	**84.7**	11.8	7820	10.6	71 ... 160	23700	27000	54200	62600	15400	14900
	306R3	**98.5**	10.2	6500	7.6	71 ... 160	24900	28400	56700	65500	16200	14900
	306R3	**119**	8.4	6510	6.3	71 ... 160	25000	28500	57000	65800	17200	14900
	306R3	**144**	6.9	5500	4.4	71 ... 160	25000	28500	57000	65800	18400	14900
	306R4	**158**	6.3	9760	7.3	71 ... 160	25000	28500	57000	65800	18900	14900
	306R4	**168**	6.0	7660	5.4	71 ... 160	25000	28500	57000	65800	19300	14900
	306R4	**181**	5.5	9450	6.2	71 ... 160	25000	28500	57000	65800	19800	14900
	306R4	**214**	4.7	9850	5.5	71 ... 160	25200	28800	57500	66400	20900	14900
	306R4	**230**	4.3	7590	3.9	71 ... 160	25500	29100	58200	67100	21500	14900
	306R4	**249**	4.0	8620	4.1	71 ... 160	25800	29400	58800	67900	22000	14900
	306R4	**289**	3.5	8840	3.6	71 ... 160	26300	30000	60100	69400	23100	14900
	306R4	**312**	3.2	7590	2.9	71 ... 160	26600	30400	60700	70100	23700	14900
	306R4	**389**	2.6	7590	2.3	71 ... 160	27500	31300	62700	72400	25500	14900
	306R4	**420**	2.4	9390	2.6	71 ... 160	27800	31700	63400	73200	26200	14900
	306R4	**455**	2.2	7530	2.0	71 ... 160	28100	32000	64100	74000	26900	14900
	306R4	**488**	2.0	9390	2.3	71 ... 160	28400	32400	64700	74700	27600	14900
	306R4	**550**	1.8	7740	1.7	71 ... 160	28900	32900	65900	76000	28700	14900
	306R4	**590**	1.7	8910	1.8	71 ... 160	29200	33300	66500	76800	29400	14900
	306R4	**665**	1.5	6490	1.2	71 ... 160	29700	33800	67700	78100	30600	14900
	306R4	**830**	1.2	6760	0.96	71 ... 160	30600	34900	69900	80600	32900	14900
500												
	306R2	**9.23**	54	2330	14.1	71 ... 160	14200	16200	34300	39600	9250	12000
	306R2	**10.9**	46	2750	14.0	71 ... 160	15000	17100	36100	41700	9770	12000
	306R2	**13.7**	37	3460	14.1	71 ... 160	16200	18500	38600	44600	10500	12000
	306R2	**15.9**	31	4020	14.1	71 ... 160	17100	19400	40400	46600	11100	12000
	306R2	**19.2**	26	4510	13.1	71 ... 160	18200	20700	42800	49400	11800	12000
	306R3	**33.2**	15.1	7350	12.7	71 ... 160	21800	24900	50400	58200	14200	14900
	306R3	**39.2**	12.8	8730	12.8	71 ... 160	23100	26300	53000	61200	15000	14900
	306R3	**46.3**	10.8	9450	11.7	71 ... 160	24400	27800	55700	64300	15800	14900
	306R3	**58.1**	8.6	9100	9.0	71 ... 160	25000	28500	57000	65800	17100	14900
	306R3	**67.5**	7.4	7590	6.4	71 ... 160	25000	28500	57000	65800	18000	14900
	306R3	**72.9**	6.9	8140	6.4	71 ... 160	25000	28500	57000	65800	18400	14900

B



306 R

320

7300 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
500	**306R3**	**84.7**	5.9	8210	5.6	71 ... 160	25000	28500	57000	65800	19400	14900
	306R3	**98.5**	5.1	6530	3.8	71 ... 160	25000	28500	57000	65800	20400	14900
	306R3	**119**	4.2	6730	3.2	71 ... 160	25600	29200	58400	67500	21700	14900
	306R3	**144**	3.5	5710	2.3	71 ... 160	26300	30000	60100	69300	23100	14900
	306R4	**158**	3.2	9850	3.7	71 ... 160	26700	30400	60800	70200	23800	14900
	306R4	**168**	3.0	7700	2.7	71 ... 160	26900	30700	61400	70800	24300	14900
	306R4	**181**	2.8	9450	3.1	71 ... 160	27200	31000	62000	71600	24900	14900
	306R4	**214**	2.3	9890	2.7	71 ... 160	27900	31800	63500	73300	26400	14900
	306R4	**230**	2.2	7640	2.0	71 ... 160	28200	32100	64200	74100	27000	14900
	306R4	**249**	2.0	9520	2.3	71 ... 160	28500	32500	64900	74900	27700	14900
	306R4	**289**	1.7	9430	1.9	71 ... 160	29100	33200	66300	76600	29200	14900
	306R4	**312**	1.6	7730	1.5	71 ... 160	29400	33500	67000	77400	29900	14900
	306R4	**389**	1.3	8240	1.3	71 ... 160	30400	34600	69200	79900	32200	14900
	306R4	**420**	1.2	9940	1.4	71 ... 160	30700	35000	70000	80800	33000	14900
	306R4	**455**	1.1	8490	1.1	71 ... 160	31000	35400	70800	81700	33900	14900
	306R4	**488**	1.0	9530	1.2	71 ... 160	31400	35700	71500	82500	34700	14900
	306R4	**550**	0.91	8500	0.91	71 ... 160	31900	36400	72700	83900	35000	14900
	306R4	**590**	0.85	9500	0.95	71 ... 160	32200	36700	73500	84800	35000	14900
	306R4	**665**	0.75	7000	0.62	71 ... 160	32800	37400	74700	86300	35000	14900
	306R4	**830**	0.60	7000	0.50	71 ... 160	33800	38600	77100	89000	35000	14900

307 R

332

14000 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**307R2**	**13.0**	116	5110	66	132 ... 200	13300	16600	32400	42600	9230	18600
	307R2	**15.5**	97	6090	66	132 ... 200	14100	17600	34100	44900	9790	21000
	307R2	**19.8**	76	7820	66	132 ... 200	15300	19100	36800	48400	10600	21000
	307R2	**23.5**	64	7970	57	132 ... 200	16200	20200	38700	50900	11300	21000
	307R3	**31.6**	47	5570	30	71 ... 160	17900	22300	42300	55700	12400	18600
	307R3	**37.7**	40	6650	30	71 ... 160	18900	23700	44600	58700	13200	21000
	307R3	**44.6**	34	7860	30	71 ... 160	20000	25000	46900	61700	13900	21000
	307R3	**55.9**	26.8	9860	30	71 ... 160	21600	27000	50200	66000	15000	21000
	307R3	**65.0**	23.1	11000	29.1	71 ... 160	22700	28400	52500	69100	15800	21000
	307R3	**71.8**	20.9	10100	24.2	71 ... 160	23500	29300	54100	71200	16300	21000
	307R3	**78.6**	19.1	11100	24.3	71 ... 160	24200	30200	55600	73200	16800	21000
	307R3	**83.4**	18.0	10200	21.1	71 ... 160	24700	30800	56600	74500	17200	21000
	307R3	**99.0**	15.2	8580	14.9	71 ... 160	26100	32600	59600	78400	18200	21000
	307R3	**120**	12.5	8630	12.4	71 ... 160	27800	34800	63100	83000	19400	21000
	307R4	**152**	9.9	13500	15.0	71 ... 160	30000	37500	67500	88800	21000	21000
	307R4	**165**	9.1	10900	11.7	71 ... 160	30000	37500	67500	88800	21600	21000
	307R4	**191**	7.9	14000	13.0	71 ... 160	30000	37500	67500	88800	22600	21000
	307R4	**206**	7.3	14100	12.2	71 ... 160	30000	37500	67500	88800	23200	21000
	307R4	**232**	6.5	11100	8.5	71 ... 160	30000	37500	67500	88800	24200	21000
	307R4	**258**	5.8	14600	10.0	71 ... 160	30000	37500	67500	88800	25000	21000
	307R4	**284**	5.3	11300	7.0	71 ... 160	30000	37500	67500	88800	25900	21000
	307R4	**300**	5.0	14000	8.3	71 ... 160	30000	37500	67500	88800	26300	21000
	307R4	**331**	4.5	11500	6.2	71 ... 160	30400	38000	68500	90100	27200	21000
	307R4	**363**	4.1	12300	6.0	71 ... 160	30800	38500	69400	91200	28000	21000
	307R4	**413**	3.6	11900	5.1	71 ... 160	31400	39300	70700	93000	29300	21000
	307R4	**453**	3.3	13400	5.3	71 ... 160	31800	39800	71600	94200	30200	21000
	307R4	**490**	3.1	9330	3.4	71 ... 160	32200	40200	72400	95300	31000	21000
	307R4	**581**	2.6	12600	3.9	71 ... 160	33000	41200	74200	97600	32800	21000
	307R4	**690**	2.2	9800	2.5	71 ... 160	33800	42200	76000	100000	34700	21000
1000	**307R2**	**13.0**	77	5770	50	132 ... 200	15200	19000	36600	48100	10600	18600
	307R2	**15.5**	65	6880	50	132 ... 200	16100	20100	38500	50700	11200	21000
	307R2	**19.8**	50	8830	50	132 ... 200	17500	21900	41500	54700	12200	21000
	307R2	**23.5**	42	8290	39	132 ... 200	18500	23200	43700	57500	12900	21000



307 R

332

14000 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1000	**307R3**	**31.6**	32	6180	22.4	71 ... 160	20400	25600	47800	62900	14200	18600
	307R3	**37.7**	26.5	7510	22.8	71 ... 160	21700	27100	50400	66300	15100	21000
	307R3	**44.6**	22.4	8870	22.9	71 ... 160	22900	28600	53000	69700	16000	21000
	307R3	**55.9**	17.9	11100	22.9	71 ... 160	24700	30900	56700	74600	17200	21000
	307R3	**65.0**	15.4	12200	21.4	71 ... 160	26000	32500	59300	78000	18100	21000
	307R3	**71.8**	13.9	10500	16.7	71 ... 160	26900	33600	61100	80400	18700	21000
	307R3	**78.6**	12.7	11800	17.3	71 ... 160	27700	34600	62800	82600	19300	21000
	307R3	**83.4**	12.0	10600	14.6	71 ... 160	28200	35300	63900	84100	19700	21000
	307R3	**99.0**	10.1	8700	10.1	71 ... 160	29900	37400	67300	88500	20800	21000
	307R3	**120**	8.4	8700	8.3	71 ... 160	30000	37500	67500	88800	22200	21000
	307R4	**152**	6.6	14300	11.2	71 ... 160	30000	37500	67500	88800	24000	21000
	307R4	**165**	6.1	11200	8.0	71 ... 160	30000	37500	67500	88800	24700	21000
	307R4	**191**	5.2	14800	9.2	71 ... 160	30000	37500	67500	88800	25900	21000
	307R4	**206**	4.9	14900	8.6	71 ... 160	30100	37600	67800	89200	26600	21000
	307R4	**232**	4.3	11600	5.9	71 ... 160	30600	38300	69000	90700	27700	21000
	307R4	**258**	3.9	14900	6.8	71 ... 160	31100	38900	70000	92100	28600	21000
	307R4	**284**	3.5	12000	5.0	71 ... 160	31500	39400	71000	93400	29600	21000
	307R4	**300**	3.3	14000	5.5	71 ... 160	31800	39700	71500	94100	30100	21000
	307R4	**331**	3.0	12300	4.4	71 ... 160	32200	40300	72500	95400	31100	21000
	307R4	**363**	2.8	12300	4.0	71 ... 160	32700	40800	73500	96700	32100	21000
	307R4	**413**	2.4	12800	3.7	71 ... 160	33300	41600	74900	98500	33500	21000
	307R4	**453**	2.2	14000	3.6	71 ... 160	33700	42100	75900	99800	34600	21000
	307R4	**490**	2.0	9900	2.4	71 ... 160	34100	42600	76700	100900	35500	21000
	307R4	**581**	1.7	13300	2.7	71 ... 160	34900	43700	78600	103400	37600	21000
	307R4	**690**	1.4	10400	1.8	71 ... 160	35800	44800	80600	106000	39800	21000
500	**307R2**	**13.0**	39	6780	29.1	132 ... 200	19100	23900	45000	59200	13300	18600
	307R2	**15.5**	32	7950	28.6	132 ... 200	20300	25400	47500	62400	14100	21000
	307R2	**19.8**	25.2	9630	27.0	132 ... 200	22000	27600	51100	67300	15300	21000
	307R2	**23.5**	21.2	8480	20.1	132 ... 200	23300	29200	53800	70800	16200	21000
	307R3	**31.6**	15.8	7380	13.4	71 ... 160	25800	32200	58800	77400	17900	18600
	307R3	**37.7**	13.2	9250	14.1	71 ... 160	27300	34100	62000	81600	19000	21000
	307R3	**44.6**	11.2	10900	14.1	71 ... 160	28900	36100	65200	85800	20100	21000
	307R3	**55.9**	8.9	13500	13.9	71 ... 160	30000	37500	67500	88800	21700	21000
	307R3	**65.0**	7.7	13700	12.1	71 ... 160	30000	37500	67500	88800	22800	21000
	307R3	**71.8**	7.0	11100	8.8	71 ... 160	30000	37500	67500	88800	23600	21000
	307R3	**78.6**	6.4	12300	9.0	71 ... 160	30000	37500	67500	88800	24300	21000
	307R3	**83.4**	6.0	11200	7.7	71 ... 160	30000	37500	67500	88800	24800	21000
	307R3	**99.0**	5.1	8700	5.0	71 ... 160	30000	37500	67500	88800	26200	21000
	307R3	**120**	4.2	8930	4.3	71 ... 160	30800	38500	69300	91100	27900	21000
	307R4	**152**	3.3	14900	5.8	71 ... 160	31800	39800	71700	94300	30300	21000
	307R4	**165**	3.0	12300	4.4	71 ... 160	32200	40300	72500	95400	31100	21000
	307R4	**191**	2.6	14900	4.6	71 ... 160	32900	41100	74000	97400	32600	21000
	307R4	**206**	2.4	14900	4.3	71 ... 160	33300	41600	74800	98400	33500	21000
	307R4	**232**	2.2	13000	3.3	71 ... 160	33800	42300	76100	100200	34800	21000
	307R4	**258**	1.9	15100	3.5	71 ... 160	34400	42900	77300	101700	36100	21000
	307R4	**284**	1.8	13500	2.8	71 ... 160	34800	43500	78400	103100	37300	21000
	307R4	**300**	1.7	14400	2.8	71 ... 160	35100	43900	79000	103900	38000	21000
	307R4	**331**	1.5	13800	2.5	71 ... 160	35600	44500	80100	105400	39200	21000
	307R4	**363**	1.4	12300	2.0	71 ... 160	36100	45100	81100	106800	40400	21000
	307R4	**413**	1.2	14400	2.1	71 ... 160	36700	45900	82700	108800	42200	21000
	307R4	**453**	1.1	14900	1.9	71 ... 160	37200	46500	83800	110200	43500	21000
	307R4	**490**	1.0	11000	1.3	71 ... 160	37700	47100	84700	111400	44700	21000
	307R4	**581**	0.86	14300	1.5	71 ... 160	38600	48200	86800	114200	45000	21000
	307R4	**690**	0.72	11000	0.94	71 ... 160	39500	49400	88900	117000	45000	21000



309 R

344

16460 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**309R2**	**13.0**	116	5110	66	132 ... 200	—	—	33100	42600	7390	27400
	309R2	**15.5**	97	6090	66	132 ... 200	—	—	34900	44900	7830	27400
	309R2	**19.8**	76	7820	66	132 ... 200	—	—	37600	48400	8510	27400
	309R2	**23.5**	64	9280	66	132 ... 200	—	—	39600	50900	9010	27400
	309R3	**31.6**	47	5580	30	71 ... 160	—	—	43300	55700	9950	27900
	309R3	**37.7**	40	6650	30	71 ... 160	—	—	45600	58700	10500	29000
	309R3	**44.6**	34	7860	30	71 ... 160	—	—	47900	61700	11100	29000
	309R3	**55.9**	26.8	9860	30	71 ... 160	—	—	51300	66000	12000	29000
	309R3	**65.0**	23.1	11200	29.6	71 ... 160	—	—	53700	69100	12600	29000
	309R3	**71.8**	20.9	12700	30	71 ... 160	—	—	55300	71200	13100	29000
	309R3	**83.4**	18.0	14000	28.8	71 ... 160	—	—	57900	74500	13700	29000
	309R3	**99.0**	15.2	12800	22.2	71 ... 160	—	—	60900	78400	14500	29000
	309R3	**120**	12.5	12900	18.6	71 ... 160	—	—	64500	83000	15500	29000
	309R4	**152**	9.9	18600	15.0	71 ... 160	—	—	69000	88800	16800	29000
	309R4	**165**	9.1	16300	15.0	71 ... 160	—	—	69000	88800	17300	29000
	309R4	**191**	7.9	17300	15.0	71 ... 160	—	—	69000	88800	18100	29000
	309R4	**206**	7.3	19800	15.0	71 ... 160	—	—	69000	88800	18600	29000
	309R4	**232**	6.5	16700	12.7	71 ... 160	—	—	69000	88800	19300	29000
	309R4	**258**	5.8	17400	12.0	71 ... 160	—	—	69000	88800	20000	29000
	309R4	**284**	5.3	16900	10.5	71 ... 160	—	—	69000	88800	20700	29000
	309R4	**331**	4.5	17200	9.2	71 ... 160	—	—	70000	90100	21800	29000
	309R4	**374**	4.0	14300	6.8	71 ... 160	—	—	71200	91700	22700	29000
	309R4	**413**	3.6	17900	7.7	71 ... 160	—	—	72200	93000	23400	29000
	309R4	**457**	3.3	13800	5.4	71 ... 160	—	—	73300	94300	24200	29000
	309R4	**490**	3.1	14000	5.1	71 ... 160	—	—	74000	95300	24800	29000
	309R4	**581**	2.6	15800	4.8	71 ... 160	—	—	75800	97600	26200	29000
	309R4	**690**	2.2	14800	3.8	71 ... 160	—	—	77700	100000	27800	29000
1000	**309R2**	**13.0**	77	5770	50	132 ... 200	—	—	37400	48100	8450	27400
	309R2	**15.5**	65	6880	50	132 ... 200	—	—	39400	50700	8970	27400
	309R2	**19.8**	50	8830	50	132 ... 200	—	—	42500	54700	9740	27400
	309R2	**23.5**	42	10200	48	132 ... 200	—	—	44700	57500	10300	27400
	309R3	**31.6**	32	6300	22.9	71 ... 160	—	—	48900	62900	11400	27900
	309R3	**37.7**	26.5	7510	22.8	71 ... 160	—	—	51500	66300	12100	29000
	309R3	**44.6**	22.4	8870	22.9	71 ... 160	—	—	54100	69700	12800	29000
	309R3	**55.9**	17.9	11100	22.9	71 ... 160	—	—	58000	74600	13800	29000
	309R3	**65.0**	15.4	12500	22.0	71 ... 160	—	—	60600	78000	14500	29000
	309R3	**71.8**	13.9	14300	22.9	71 ... 160	—	—	62500	80400	15000	29000
	309R3	**83.4**	12.0	15500	21.3	71 ... 160	—	—	65300	84100	15700	29000
	309R3	**99.0**	10.1	13000	15.1	71 ... 160	—	—	68800	88500	16700	29000
	309R3	**120**	8.4	13000	12.5	71 ... 160	—	—	69000	88800	17700	29000
	309R4	**152**	6.6	20200	15.0	71 ... 160	—	—	69000	88800	19200	29000
	309R4	**165**	6.1	16700	12.0	71 ... 160	—	—	69000	88800	19800	29000
	309R4	**191**	5.2	17500	10.8	71 ... 160	—	—	69000	88800	20700	29000
	309R4	**206**	4.9	21300	12.2	71 ... 160	—	—	69300	89200	21200	29000
	309R4	**232**	4.3	17200	8.8	71 ... 160	—	—	70500	90700	22100	29000
	309R4	**258**	3.9	17500	8.0	71 ... 160	—	—	71600	92100	22900	29000
	309R4	**284**	3.5	17500	7.3	71 ... 160	—	—	72600	93400	23700	29000
	309R4	**331**	3.0	18500	6.6	71 ... 160	—	—	74200	95400	24900	29000
	309R4	**374**	2.7	14300	4.5	71 ... 160	—	—	75500	97100	25900	29000
	309R4	**413**	2.4	19200	5.5	71 ... 160	—	—	76500	98500	26800	29000
	309R4	**457**	2.2	14800	3.8	71 ... 160	—	—	77600	99900	27700	29000
	309R4	**490**	2.0	14900	3.6	71 ... 160	—	—	78400	100900	28400	29000
	309R4	**581**	1.7	15800	3.2	71 ... 160	—	—	80400	103400	30000	29000
	309R4	**690**	1.4	15900	2.7	71 ... 160	—	—	82300	106000	31800	29000
500	**309R2**	**13.0**	39	6780	29.1	132 ... 200	—	—	46000	59200	10700	27400
	309R2	**15.5**	32	7950	28.6	132 ... 200	—	—	48500	62400	11300	27400
	309R2	**19.8**	25.2	10200	28.5	132 ... 200	—	—	52300	67300	12300	27400
	309R2	**23.5**	21.2	11200	26.4	132 ... 200	—	—	55000	70800	13000	27400
	309R3	**31.6**	15.8	7760	14.1	71 ... 160	—	—	60100	77400	14300	27900

B



309 R

344

16460 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
500	**309R3**	**37.7**	13.2	9250	14.1	71 ... 160	—	—	63400	81600	15200	29000
	309R3	**44.6**	11.2	10900	14.1	71 ... 160	—	—	66700	85800	16100	29000
	309R3	**55.9**	8.9	13700	14.1	71 ... 160	—	—	69000	88800	17300	29000
	309R3	**65.0**	7.7	14100	12.5	71 ... 160	—	—	69000	88800	18200	29000
	309R3	**71.8**	7.0	16400	13.1	71 ... 160	—	—	69000	88800	18800	29000
	309R3	**83.4**	6.0	16700	11.5	71 ... 160	—	—	69000	88800	19800	29000
	309R3	**99.0**	5.1	13000	7.5	71 ... 160	—	—	69000	88800	21000	29000
	309R3	**120**	4.2	13400	6.4	71 ... 160	—	—	70800	91100	22400	29000
	309R4	**152**	3.3	21300	8.3	71 ... 160	—	—	73200	94300	24200	29000
	309R4	**165**	3.0	18400	6.6	71 ... 160	—	—	74100	95400	24900	29000
	309R4	**191**	2.6	17500	5.4	71 ... 160	—	—	75700	97400	26100	29000
	309R4	**206**	2.4	21300	6.1	71 ... 160	—	—	76500	98400	26800	29000
	309R4	**232**	2.2	18100	4.6	71 ... 160	—	—	77800	100200	27900	29000
	309R4	**258**	1.9	17800	4.1	71 ... 160	—	—	79000	101700	28900	29000
	309R4	**284**	1.8	18200	3.8	71 ... 160	—	—	80100	103100	29800	29000
	309R4	**331**	1.5	20600	3.7	71 ... 160	—	—	81900	105400	31400	29000
	309R4	**374**	1.3	14600	2.3	71 ... 160	—	—	83300	107200	32700	29000
	309R4	**413**	1.2	21300	3.1	71 ... 160	—	—	84500	108800	33800	29000
	309R4	**457**	1.1	16700	2.2	71 ... 160	—	—	85700	110300	34900	29000
	309R4	**490**	1.0	16900	2.0	71 ... 160	—	—	86600	111400	35800	29000
	309R4	**581**	0.86	15800	1.6	71 ... 160	—	—	88700	114200	36000	29000
	309R4	**690**	0.72	17000	1.5	71 ... 160	—	—	90900	117000	36000	29000

310M R

356

33640 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**310MR2B**	**12.0**	125	11900	130	160 ... 225	—	—	36600	46400	13000	47600
	310MR2B	**15.4**	97	15200	130	160 ... 225	—	—	39400	50000	14100	47600
	310MR2B	**18.3**	82	17000	130	160 ... 225	—	—	41500	52600	15000	47600
	310MR2C	**16.6**	90	15000	130	160 ... 250	—	—	40300	51100	14500	47600
	310MR2C	**21.3**	70	18700	130	160 ... 250	—	—	43500	55100	15800	47600
	310MR2C	**25.3**	59	17500	115	160 ... 250	—	—	45800	58000	16700	47600
	310MR3	**37.7**	40	6480	29.6	71 ... 160	—	—	51600	65400	19000	47600
	310MR3	**44.6**	34	7650	29.5	71 ... 160	—	—	54200	68700	20100	47600
	310MR3	**55.9**	26.8	9600	29.5	71 ... 160	—	—	58000	73600	21700	47600
	310MR3	**65.0**	23.1	11200	29.5	71 ... 160	—	—	60700	77000	22800	47600
	310MR3	**71.8**	20.9	12300	29.5	71 ... 160	—	—	62500	79300	23600	47600
	310MR3	**78.6**	19.1	13500	29.6	71 ... 160	—	—	64300	81500	24300	47600
	310MR3	**83.4**	18.0	14300	29.6	71 ... 160	—	—	65400	82900	24800	47600
	310MR3	**99.0**	15.2	16000	27.9	71 ... 160	—	—	68900	87300	26300	47600
	310MR3	**120**	12.5	17100	24.6	71 ... 160	—	—	72900	92400	28000	47600
	310MR4	**136**	11.0	22600	29.5	71 ... 160	—	—	75700	96000	29200	47600
	310MR4	**160**	9.4	26100	28.8	71 ... 160	—	—	78000	98900	30900	47600
	310MR4	**189**	7.9	27400	25.7	71 ... 160	—	—	78000	98900	32600	47600
	310MR4	**206**	7.3	22100	19.1	71 ... 160	—	—	78000	98900	33500	47600
	310MR4	**238**	6.3	28400	21.2	71 ... 160	—	—	78000	98900	35200	47600
	310MR4	**258**	5.8	22500	15.4	71 ... 160	—	—	78000	98900	36200	47600
	310MR4	**276**	5.4	27900	17.9	71 ... 160	—	—	78000	98900	37000	47600
	310MR4	**305**	4.9	22800	13.2	71 ... 160	—	—	78200	99100	38200	47600
	310MR4	**347**	4.3	29600	15.2	71 ... 160	—	—	79600	101000	39900	47600
	310MR4	**383**	3.9	23700	11.0	71 ... 160	—	—	80800	102400	41200	47600
	310MR4	**454**	3.3	19400	7.6	71 ... 160	—	—	82800	104900	43600	47600
	310MR4	**517**	2.9	25000	8.6	71 ... 160	—	—	84300	106900	45600	47600
	310MR4	**590**	2.5	19300	5.8	71 ... 160	—	—	85900	108900	47600	47600
	310MR4	**639**	2.3	20600	5.7	71 ... 160	—	—	86900	110200	48900	47600
	310MR4	**757**	2.0	24800	5.8	71 ... 160	—	—	89000	112900	51700	47600
	310MR4	**898**	1.7	21900	4.3	71 ... 160	—	—	91200	115700	54800	47600



310M R

356

33640 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1000	**310MR2B**	**12.0**	83	13400	124	160 ... 225	—	—	41300	52400	14900	47600
	310MR2B	**15.4**	65	17200	124	160 ... 225	—	—	44500	56400	16200	47600
	310MR2B	**18.3**	55	17700	107	160 ... 225	—	—	46900	59400	17100	47600
	310MR2C	**16.6**	60	16900	113	160 ... 250	—	—	45500	57700	16600	47600
	310MR2C	**21.3**	47	20700	108	160 ... 250	—	—	49100	62200	18000	47600
	310MR2C	**25.3**	39	17800	78	160 ... 250	—	—	51700	65500	19100	47600
	310MR3	**37.7**	26.5	7320	22.2	71 ... 160	—	—	58200	73800	21800	47600
	310MR3	**44.6**	22.4	8640	22.2	71 ... 160	—	—	61200	77600	23000	47600
	310MR3	**55.9**	17.9	10800	22.2	71 ... 160	—	—	65500	83100	24900	47600
	310MR3	**65.0**	15.4	12600	22.2	71 ... 160	—	—	68500	86900	26100	47600
	310MR3	**71.8**	13.9	13900	22.2	71 ... 160	—	—	70600	89500	27000	47600
	310MR3	**78.6**	12.7	15200	22.3	71 ... 160	—	—	72600	92000	27800	47600
	310MR3	**83.4**	12.0	16200	22.2	71 ... 160	—	—	73900	93700	28400	47600
	310MR3	**99.0**	10.1	17800	20.6	71 ... 160	—	—	77800	98600	30100	47600
	310MR3	**120**	8.4	17900	17.1	71 ... 160	—	—	78000	98900	32000	47600
	310MR4	**136**	7.4	25600	22.2	71 ... 160	—	—	78000	98900	33400	47600
	310MR4	**160**	6.2	28200	20.8	71 ... 160	—	—	78000	98900	35300	47600
	310MR4	**189**	5.3	29100	18.2	71 ... 160	—	—	78000	98900	37300	47600
	310MR4	**206**	4.9	22800	13.1	71 ... 160	—	—	78300	99300	38400	47600
	310MR4	**238**	4.2	30000	14.9	71 ... 160	—	—	79900	101400	40300	47600
	310MR4	**258**	3.9	23700	10.9	71 ... 160	—	—	80900	102600	41400	47600
	310MR4	**276**	3.6	28100	12.0	71 ... 160	—	—	81700	103600	42300	47600
	310MR4	**305**	3.3	24400	9.5	71 ... 160	—	—	82800	105000	43800	47600
	310MR4	**347**	2.9	30400	10.4	71 ... 160	—	—	84400	107000	45700	47600
	310MR4	**383**	2.6	25400	7.9	71 ... 160	—	—	85600	108500	47200	47600
	310MR4	**454**	2.2	20800	5.4	71 ... 160	—	—	87700	111200	50000	47600
	310MR4	**517**	1.9	26800	6.1	71 ... 160	—	—	89300	113300	52200	47600
	310MR4	**590**	1.7	19400	3.9	71 ... 160	—	—	91000	115400	54500	47600
	310MR4	**639**	1.6	22100	4.1	71 ... 160	—	—	92100	116700	56000	47600
	310MR4	**757**	1.3	24800	3.9	71 ... 160	—	—	94300	119600	59200	47600
	310MR4	**898**	1.1	23500	3.1	71 ... 160	—	—	96700	122600	62700	47600
500	**310MR2B**	**12.0**	42	16400	76	160 ... 225	—	—	50900	64500	18800	47600
	310MR2B	**15.4**	32	19400	70	160 ... 225	—	—	54800	69500	20400	47600
	310MR2B	**18.3**	27.3	17800	54	160 ... 225	—	—	57700	73200	21600	47600
	310MR2C	**16.6**	30	20200	68	160 ... 250	—	—	56100	71100	20900	47600
	310MR2C	**21.3**	23.4	21200	55	160 ... 250	—	—	60400	76600	22700	47600
	310MR2C	**25.3**	19.7	17800	39	160 ... 250	—	—	63600	80700	24100	47600
	310MR3	**37.7**	13.2	9010	13.7	71 ... 160	—	—	71700	90900	27500	47600
	310MR3	**44.6**	11.2	10600	13.7	71 ... 160	—	—	75300	95500	29000	47600
	310MR3	**55.9**	8.9	13300	13.7	71 ... 160	—	—	78000	98900	31300	47600
	310MR3	**65.0**	7.7	15500	13.7	71 ... 160	—	—	78000	98900	32900	47600
	310MR3	**71.8**	7.0	17100	13.7	71 ... 160	—	—	78000	98900	34000	47600
	310MR3	**78.6**	6.4	18300	13.3	71 ... 160	—	—	78000	98900	35100	47600
	310MR3	**83.4**	6.0	19900	13.7	71 ... 160	—	—	78000	98900	35800	47600
	310MR3	**99.0**	5.1	18000	10.4	71 ... 160	—	—	78000	98900	37900	47600
	310MR3	**120**	4.2	18600	8.9	71 ... 160	—	—	80000	101500	40400	47600
	310MR4	**136**	3.7	29600	12.9	71 ... 160	—	—	81500	103300	42100	47600
	310MR4	**160**	3.1	31100	11.5	71 ... 160	—	—	83400	105800	44500	47600
	310MR4	**189**	2.6	31700	9.9	71 ... 160	—	—	85400	108300	47000	47600
	310MR4	**206**	2.4	25800	7.4	71 ... 160	—	—	86500	109600	48400	47600
	310MR4	**238**	2.1	32200	8.0	71 ... 160	—	—	88300	111900	50700	47600
	310MR4	**258**	1.9	26800	6.1	71 ... 160	—	—	89300	113300	52200	47600
	310MR4	**276**	1.8	28100	6.0	71 ... 160	—	—	90200	114300	53300	47600
	310MR4	**305**	1.6	27600	5.4	71 ... 160	—	—	91500	116000	55100	47600
	310MR4	**347**	1.4	32100	5.5	71 ... 160	—	—	93200	118100	57500	47600
	310MR4	**383**	1.3	28700	4.4	71 ... 160	—	—	94500	119800	59500	47600
	310MR4	**454**	1.1	23500	3.1	71 ... 160	—	—	96800	122800	62900	47600
	310MR4	**517**	0.97	30100	3.4	71 ... 160	—	—	98600	125100	65000	47600
	310MR4	**590**	0.85	19500	2.0	71 ... 160	—	—	100500	127400	65000	47600
	310MR4	**639**	0.78	23900	2.2	71 ... 160	—	—	101700	128900	65000	47600
	310MR4	**757**	0.66	24800	1.9	71 ... 160	—	—	104100	132100	65000	47600
	310MR4	**898**	0.56	23900	1.6	71 ... 160	—	—	106700	135300	65000	47600

B



311M R

368

49210 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**311MR2B**	**12.0**	125	11900	150	180 ... 250	—	—	46000	58600	13000	58300
	311MR2B	**15.4**	97	15200	150	180 ... 250	—	—	49500	63200	14100	58300
	311MR2B	**18.3**	82	18100	150	180 ... 250	—	—	52100	66500	15000	58300
	311MR2C	**16.6**	90	15000	150	180 ... 250	—	—	50700	64600	14500	58300
	311MR2C	**21.3**	70	19200	150	180 ... 250	—	—	54600	69600	15800	58300
	311MR2C	**25.3**	59	22800	150	180 ... 250	—	—	57500	73300	16700	58300
	311MR3	**53.0**	28.3	20300	66	132 ... 200	—	—	71700	91500	21300	58300
	311MR3	**63.2**	23.7	24200	66	132 ... 200	—	—	75600	96500	22600	58300
	311MR3	**68.0**	22.1	26000	66	132 ... 200	—	—	77300	98600	23200	58300
	311MR3	**81.1**	18.5	29800	63	132 ... 200	—	—	81500	100000	24600	58300
	311MR3	**96.3**	15.6	29600	53	132 ... 200	—	—	85800	100000	26000	58300
	311MR3	**104**	14.4	33100	55	132 ... 200	—	—	87800	100000	26700	58300
	311MR3	**124**	12.1	34200	48	132 ... 200	—	—	92500	100000	28300	58300
	311MR3	**147**	10.2	27200	32	132 ... 200	—	—	97300	100000	29900	58300
	311MR4	**154**	9.7	25700	29.5	71 ... 160	—	—	98000	100000	30500	58300
	311MR4	**182**	8.2	30400	29.5	71 ... 160	—	—	98000	100000	32200	58300
	311MR4	**198**	7.6	32800	29.3	71 ... 160	—	—	98000	100000	33100	58300
	311MR4	**229**	6.6	38100	29.6	71 ... 160	—	—	98000	100000	34700	58300
	311MR4	**266**	5.6	43900	29.3	71 ... 160	—	—	98000	100000	36500	58300
	311MR4	**294**	5.1	36600	22.1	71 ... 160	—	—	98000	100000	37700	58300
	311MR4	**341**	4.4	37500	19.5	71 ... 160	—	—	99800	101900	39700	58300
	311MR4	**413**	3.6	38800	16.7	71 ... 160	—	—	102600	104700	42300	58300
	311MR4	**438**	3.4	39200	15.9	71 ... 160	—	—	103400	105600	43100	58300
	311MR4	**490**	3.1	32000	11.6	71 ... 160	—	—	105100	107300	44800	58300
	311MR4	**520**	2.9	40200	13.7	71 ... 160	—	—	106000	108200	45700	58300
	311MR4	**629**	2.4	41200	11.6	71 ... 160	—	—	108900	111100	48600	58300
	311MR4	**746**	2.0	32300	7.7	71 ... 160	—	—	111600	113900	51500	58300
1000	**311MR2B**	**12.0**	83	13400	124	180 ... 250	—	—	51900	66200	14900	58300
	311MR2B	**15.4**	65	17200	124	180 ... 250	—	—	55900	71300	16200	58300
	311MR2B	**18.3**	55	20400	124	180 ... 250	—	—	58900	75100	17100	58300
	311MR2C	**16.6**	60	16900	113	180 ... 250	—	—	57200	73000	16600	58300
	311MR2C	**21.3**	47	21700	113	180 ... 250	—	—	61700	78700	18000	58300
	311MR2C	**25.3**	39	24400	107	180 ... 250	—	—	64900	82800	19100	58300
	311MR3	**53.0**	18.9	22900	50	132 ... 200	—	—	81000	100000	24400	58300
	311MR3	**63.2**	15.8	27300	50	132 ... 200	—	—	85400	100000	25900	58300
	311MR3	**68.0**	14.7	29400	50	132 ... 200	—	—	87300	100000	26500	58300
	311MR3	**81.1**	12.3	33200	47	132 ... 200	—	—	92000	100000	28100	58300
	311MR3	**96.3**	10.4	31800	38	132 ... 200	—	—	96900	100000	29800	58300
	311MR3	**104**	9.6	35100	39	132 ... 200	—	—	98000	100000	30600	58300
	311MR3	**124**	8.1	35500	33	132 ... 200	—	—	98000	100000	32400	58300
	311MR3	**147**	6.8	27300	21.4	132 ... 200	—	—	98000	100000	34300	58300
	311MR4	**154**	6.5	29000	22.2	71 ... 160	—	—	98000	100000	34900	58300
	311MR4	**182**	5.5	34300	22.2	71 ... 160	—	—	98000	100000	36900	58300
	311MR4	**198**	5.0	36600	21.8	71 ... 160	—	—	98000	100000	37900	58300
	311MR4	**229**	4.4	42300	21.9	71 ... 160	—	—	99900	101900	39800	58300
	311MR4	**266**	3.8	45900	20.4	71 ... 160	—	—	102100	104200	41800	58300
	311MR4	**294**	3.4	39200	15.8	71 ... 160	—	—	103500	105600	43200	58300
	311MR4	**341**	2.9	40300	14.0	71 ... 160	—	—	105800	107900	45400	58300
	311MR4	**413**	2.4	41600	11.9	71 ... 160	—	—	108700	110900	48400	58300
	311MR4	**438**	2.3	42000	11.3	71 ... 160	—	—	109600	111800	49400	58300
	311MR4	**490**	2.0	32300	7.8	71 ... 160	—	—	111400	113700	51200	58300
	311MR4	**520**	1.9	41200	9.4	71 ... 160	—	—	112300	114600	52300	58300
	311MR4	**629**	1.6	41200	7.8	71 ... 160	—	—	115400	117800	55700	58300
	311MR4	**746**	1.3	34600	5.5	71 ... 160	—	—	118300	120700	59000	58300
500	**311MR2B**	**12.0**	42	16400	76	180 ... 250	—	—	63900	81500	18800	58300
	311MR2B	**15.4**	32	21200	76	180 ... 250	—	—	68900	87800	20400	58300
	311MR2B	**18.3**	27.3	23100	70	180 ... 250	—	—	72500	92500	21600	58300
	311MR2C	**16.6**	30	20800	70	180 ... 250	—	—	70400	89900	20900	58300
	311MR2C	**21.3**	23.4	26700	70	180 ... 250	—	—	75900	96800	22700	58300
	311MR2C	**25.3**	19.7	25800	57	180 ... 250	—	—	79900	100000	24100	58300

B



311M R

368

49210 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
500	**311MR3**	**53.0**	9.4	28100	30	132 ... 200	—	—	98000	100000	30800	58300
	311MR3	**63.2**	7.9	33600	31	132 ... 200	—	—	98000	100000	32600	58300
	311MR3	**68.0**	7.4	34600	29.2	132 ... 200	—	—	98000	100000	33400	58300
	311MR3	**81.1**	6.2	36200	25.6	132 ... 200	—	—	98000	100000	35500	58300
	311MR3	**96.3**	5.2	32000	19.1	132 ... 200	—	—	98000	100000	37500	58300
	311MR3	**104**	4.8	36900	20.4	132 ... 200	—	—	98600	100600	38500	58300
	311MR3	**124**	4.0	38000	17.6	132 ... 200	—	—	101000	103100	40800	58300
	311MR3	**147**	3.4	29400	11.5	132 ... 200	—	—	103500	105600	43200	58300
	311MR4	**154**	3.2	35800	13.7	71 ... 160	—	—	104300	106400	43900	58300
	311MR4	**182**	2.7	42200	13.7	71 ... 160	—	—	106800	109000	46400	58300
	311MR4	**198**	2.5	41300	12.3	71 ... 160	—	—	108100	110300	47700	58300
	311MR4	**229**	2.2	47000	12.1	71 ... 160	—	—	110300	112500	50100	58300
	311MR4	**266**	1.9	47400	10.5	71 ... 160	—	—	112700	115000	52700	58300
	311MR4	**294**	1.7	44000	8.9	71 ... 160	—	—	114300	116600	54400	58300
	311MR4	**341**	1.5	45000	7.8	71 ... 160	—	—	116800	119200	57200	58300
	311MR4	**413**	1.2	46400	6.6	71 ... 160	—	—	120000	122400	61000	58300
	311MR4	**438**	1.1	46800	6.3	71 ... 160	—	—	121000	123500	62200	58300
	311MR4	**490**	1.0	33500	4.0	71 ... 160	—	—	123000	125500	64600	58300
	311MR4	**520**	0.96	41300	4.7	71 ... 160	—	—	124000	126500	65000	58300
	311MR4	**629**	0.80	41300	3.9	71 ... 160	—	—	127400	130000	65000	58300
	311MR4	**746**	0.67	36500	2.9	71 ... 160	—	—	130600	133300	65000	58300

313M R

380

60940 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**313MR2B**	**12.2**	123	12000	150	180 ... 250	—	—	66800	78300	16100	86300
	313MR2B	**15.9**	95	15700	150	180 ... 250	—	—	72400	84800	17600	86300
	313MR2B	**19.1**	79	18800	150	180 ... 250	—	—	76500	89700	18700	86300
	313MR2C	**16.8**	89	15200	150	180 ... 250	—	—	73700	86400	17900	105000
	313MR2C	**22.0**	68	19800	150	180 ... 250	—	—	79800	93500	19600	105000
	313MR2C	**26.4**	57	23800	150	180 ... 250	—	—	84400	98800	20800	105000
	313MR3	**53.7**	28.0	20500	66	132 ... 200	—	—	104300	122200	26400	105000
	313MR3	**64.0**	23.4	24500	66	132 ... 200	—	—	110000	128900	28000	105000
	313MR3	**69.9**	21.4	26700	66	132 ... 200	—	—	112900	132400	28800	105000
	313MR3	**82.2**	18.3	31400	66	132 ... 200	—	—	118500	138900	30400	105000
	313MR3	**97.5**	15.4	37300	66	132 ... 200	—	—	124800	146200	32200	105000
	313MR3	**107**	14.0	38200	61	132 ... 200	—	—	128400	150400	33200	105000
	313MR3	**127**	11.8	40300	55	132 ... 200	—	—	135100	158300	35100	105000
	313MR3	**153**	9.8	30200	34	132 ... 200	—	—	142000	166400	37400	105000
	313MR4	**185**	8.1	30700	29.6	71 ... 160	—	—	142000	166400	39800	105000
	313MR4	**201**	7.5	33400	29.6	71 ... 160	—	—	142000	166400	40900	105000
	313MR4	**237**	6.3	39500	29.6	71 ... 160	—	—	142000	166400	43200	105000
	313MR4	**281**	5.3	46800	29.6	71 ... 160	—	—	142000	166400	45800	105000
	313MR4	**309**	4.9	43400	24.9	71 ... 160	—	—	142600	167100	47200	105000
	313MR4	**346**	4.3	55700	28.6	71 ... 160	—	—	144900	169800	49000	105000
	313MR4	**387**	3.9	45100	20.7	71 ... 160	—	—	147300	172600	50900	105000
	313MR4	**450**	3.3	46300	18.2	71 ... 160	—	—	150500	176300	53600	105000
	313MR4	**496**	3.0	48600	17.4	71 ... 160	—	—	152600	178800	55300	105000
	313MR4	**535**	2.8	47700	15.8	71 ... 160	—	—	154200	180700	56700	105000
	313MR4	**647**	2.3	49300	13.5	71 ... 160	—	—	158500	185700	60400	105000
	313MR4	**778**	1.9	35800	8.1	71 ... 160	—	—	162700	190700	64300	105000
1000	**313MR2B**	**12.2**	82	13600	124	180 ... 250	—	—	75500	88500	18400	86300
	313MR2B	**15.9**	63	17700	124	180 ... 250	—	—	81700	95800	20100	86300
	313MR2B	**19.1**	52	21300	124	180 ... 250	—	—	86400	101300	21400	86300
	313MR2C	**16.8**	59	17100	113	180 ... 250	—	—	83200	97500	20500	105000
	313MR2C	**22.0**	46	22300	113	180 ... 250	—	—	90100	105600	22400	105000
	313MR2C	**26.4**	38	25600	108	180 ... 250	—	—	95300	111600	23800	105000



313M R

380

60940 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1000	**313MR3**	**53.7**	18.6	23200	50	132 ... 200	—	—	117800	138100	30200	105000
	313MR3	**64.0**	15.6	27700	50	132 ... 200	—	—	124200	145600	32000	105000
	313MR3	**69.9**	14.3	30200	50	132 ... 200	—	—	127600	149500	33000	105000
	313MR3	**82.2**	12.2	35500	50	132 ... 200	—	—	133900	156900	34800	105000
	313MR3	**97.5**	10.3	42100	50	132 ... 200	—	—	140900	165100	36800	105000
	313MR3	**107**	9.3	41600	45	132 ... 200	—	—	142000	166400	38000	105000
	313MR3	**127**	7.9	42000	38	132 ... 200	—	—	142000	166400	40200	105000
	313MR3	**153**	6.5	30200	22.7	132 ... 200	—	—	142000	166400	42800	105000
	313MR4	**185**	5.4	34700	22.2	71 ... 160	—	—	142000	166400	45500	105000
	313MR4	**201**	5.0	37700	22.2	71 ... 160	—	—	142100	166500	46800	105000
	313MR4	**237**	4.2	44600	22.2	71 ... 160	—	—	145500	170500	49500	105000
	313MR4	**281**	3.6	48200	20.3	71 ... 160	—	—	149100	174700	52400	105000
	313MR4	**309**	3.2	46500	17.8	71 ... 160	—	—	151100	177000	54100	105000
	313MR4	**346**	2.9	57100	19.6	71 ... 160	—	—	153500	179900	56100	105000
	313MR4	**387**	2.6	48400	14.8	71 ... 160	—	—	156100	182900	58300	105000
	313MR4	**450**	2.2	49700	13.1	71 ... 160	—	—	159500	186900	61300	105000
	313MR4	**496**	2.0	49100	11.7	71 ... 160	—	—	161700	189500	63300	105000
	313MR4	**535**	1.9	51200	11.3	71 ... 160	—	—	163400	191500	64900	105000
	313MR4	**647**	1.5	53000	9.7	71 ... 160	—	—	167900	196800	69200	105000
	313MR4	**778**	1.3	38400	5.8	71 ... 160	—	—	172400	202100	73600	105000
500	**313MR2B**	**12.2**	41	16600	76	180 ... 250	—	—	92900	108900	23200	86300
	313MR2B	**15.9**	32	21800	76	180 ... 250	—	—	100600	117900	25300	86300
	313MR2B	**19.1**	26.2	24700	72	180 ... 250	—	—	106400	124700	26900	86300
	313MR2C	**16.8**	29.7	21100	70	180 ... 250	—	—	102500	120100	25800	105000
	313MR2C	**22.0**	22.8	27500	70	180 ... 250	—	—	110900	130000	28200	105000
	313MR2C	**26.4**	18.9	27900	59	180 ... 250	—	—	117300	137400	30000	105000
	313MR3	**53.7**	9.3	28500	30	132 ... 200	—	—	142000	166400	38000	105000
	313MR3	**64.0**	7.8	34100	31	132 ... 200	—	—	142000	166400	40300	105000
	313MR3	**69.9**	7.1	37200	31	132 ... 200	—	—	142000	166400	41500	105000
	313MR3	**82.2**	6.1	43700	31	132 ... 200	—	—	142000	166400	43800	105000
	313MR3	**97.5**	5.1	48400	28.5	132 ... 200	—	—	142000	166400	46400	105000
	313MR3	**107**	4.7	43700	23.4	132 ... 200	—	—	143400	168000	47900	105000
	313MR3	**127**	3.9	45000	20.3	132 ... 200	—	—	147000	172200	50700	105000
	313MR3	**153**	3.3	32600	12.2	132 ... 200	—	—	150900	176800	53900	105000
	313MR4	**185**	2.7	42700	13.7	71 ... 160	—	—	155000	181600	57400	105000
	313MR4	**201**	2.5	46500	13.7	71 ... 160	—	—	156900	183800	59000	105000
	313MR4	**237**	2.1	53700	13.4	71 ... 160	—	—	160600	188200	62400	105000
	313MR4	**281**	1.8	49400	10.4	71 ... 160	—	—	164600	192900	66000	105000
	313MR4	**309**	1.6	52500	10.1	71 ... 160	—	—	166800	195500	68100	105000
	313MR4	**346**	1.4	59600	10.2	71 ... 160	—	—	169500	198600	70700	105000
	313MR4	**387**	1.3	54600	8.3	71 ... 160	—	—	172300	201900	73500	105000
	313MR4	**450**	1.1	56100	7.4	71 ... 160	—	—	176100	206300	77300	105000
	313MR4	**496**	1.0	50800	6.1	71 ... 160	—	—	178500	209200	79800	105000
	313MR4	**535**	0.94	57100	6.3	71 ... 160	—	—	180400	211400	80000	105000
	313MR4	**647**	0.77	57100	5.2	71 ... 160	—	—	185400	217300	80000	105000
	313MR4	**778**	0.64	40100	3.0	71 ... 160	—	—	190400	223100	80000	105000

314M R

392

80640 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**314MR3B**	**51.1**	29.4	39100	130	180 ... 250	—	—	95500	114600	29200	115000
	314MR3B	**65.5**	22.9	50200	130	180 ... 250	—	—	103000	123500	31700	115000
	314MR3B	**77.8**	19.3	52500	116	180 ... 250	—	—	108400	130000	33600	115000
	314MR3B	**82.3**	18.2	54400	114	180 ... 250	—	—	110200	132200	34200	115000
	314MR3B	**97.6**	15.4	57300	101	180 ... 250	—	—	116000	139200	36200	115000
	314MR3B	**113**	13.2	47400	72	180 ... 250	—	—	121400	145600	38100	115000
	314MR3C	**70.7**	21.2	49400	120	180 ... 250	—	—	105300	126300	32500	115000



314M R

392

80640 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**314MR3C**	**90.7**	16.5	61300	116	180 ... 250	—	—	113500	136100	35300	115000
	314MR3C	**108**	13.9	55800	89	180 ... 250	—	—	119500	143300	37400	115000
	314MR3C	**114**	13.2	58300	88	180 ... 250	—	—	121500	145700	38100	115000
	314MR3C	**135**	11.1	59100	75	180 ... 250	—	—	127900	153400	40300	115000
	314MR3C	**157**	9.5	47400	52	180 ... 250	—	—	132000	158300	42400	115000
	314MR4	**160**	9.4	26700	29.5	71 ... 160	—	—	132000	158300	42700	115000
	314MR4	**189**	7.9	31500	29.5	71 ... 160	—	—	132000	158300	45100	115000
	314MR4	**238**	6.3	39600	29.5	71 ... 160	—	—	132000	158300	48700	115000
	314MR4	**276**	5.4	46000	29.6	71 ... 160	—	—	132000	158300	51200	115000
	314MR4	**354**	4.2	59000	29.5	71 ... 160	—	—	135200	162100	55600	115000
	314MR4	**421**	3.6	68500	28.9	71 ... 160	—	—	138500	166100	58900	115000
	314MR4	**445**	3.4	59300	23.6	71 ... 160	—	—	139600	167500	60000	115000
	314MR4	**528**	2.8	65900	22.2	71 ... 160	—	—	143100	171600	63500	115000
	314MR4	**614**	2.4	54200	15.7	71 ... 160	—	—	146200	175300	66800	115000
1000	**314MR3B**	**51.1**	19.6	44200	99	180 ... 250	—	—	107900	129400	33400	115000
	314MR3B	**65.5**	15.3	56700	99	180 ... 250	—	—	116300	139500	36300	115000
	314MR3B	**77.8**	12.9	56700	84	180 ... 250	—	—	122400	146800	38400	115000
	314MR3B	**82.3**	12.2	57900	81	180 ... 250	—	—	124500	149300	39100	115000
	314MR3B	**97.6**	10.2	59600	70	180 ... 250	—	—	131000	157200	41400	115000
	314MR3B	**113**	8.8	47500	48	180 ... 250	—	—	132000	158300	43600	115000
	314MR3C	**70.7**	14.1	55800	90	180 ... 250	—	—	119000	142700	37200	115000
	314MR3C	**90.7**	11.0	69100	87	180 ... 250	—	—	128200	153800	40400	115000
	314MR3C	**108**	9.3	59500	63	180 ... 250	—	—	132000	158300	42800	115000
	314MR3C	**114**	8.8	60200	61	180 ... 250	—	—	132000	158300	43600	115000
	314MR3C	**135**	7.4	60800	52	180 ... 250	—	—	132000	158300	46200	115000
	314MR3C	**157**	6.4	47800	35	180 ... 250	—	—	132000	158300	48600	115000
	314MR4	**160**	6.2	30200	22.2	71 ... 160	—	—	132000	158300	48900	115000
	314MR4	**189**	5.3	35600	22.2	71 ... 160	—	—	132000	158300	51700	115000
	314MR4	**238**	4.2	44700	22.2	71 ... 160	—	—	135300	162200	55700	115000
	314MR4	**276**	3.6	52000	22.2	71 ... 160	—	—	138200	165800	58600	115000
	314MR4	**354**	2.8	66700	22.2	71 ... 160	—	—	143200	171800	63700	115000
	314MR4	**421**	2.4	74500	21.0	71 ... 160	—	—	146800	176000	67400	115000
	314MR4	**445**	2.2	65800	17.5	71 ... 160	—	—	148000	177500	68700	115000
	314MR4	**528**	1.9	69200	15.5	71 ... 160	—	—	151600	181800	72700	115000
	314MR4	**614**	1.6	58200	11.2	71 ... 160	—	—	154900	185800	76500	115000
500	**314MR3B**	**51.1**	9.8	54400	61	180 ... 250	—	—	132000	158300	42100	115000
	314MR3B	**65.5**	7.6	67400	59	180 ... 250	—	—	132000	158300	45700	115000
	314MR3B	**77.8**	6.4	59500	44	180 ... 250	—	—	132000	158300	48400	115000
	314MR3B	**82.3**	6.1	61600	43	180 ... 250	—	—	132000	158300	49300	115000
	314MR3B	**97.6**	5.1	62200	37	180 ... 250	—	—	132000	158300	52200	115000
	314MR3B	**113**	4.4	49000	24.8	180 ... 250	—	—	134400	161200	54900	115000
	314MR3C	**70.7**	7.1	68400	56	180 ... 250	—	—	132000	158300	46900	115000
	314MR3C	**90.7**	5.5	72200	46	180 ... 250	—	—	132000	158300	51000	115000
	314MR3C	**108**	4.6	59500	32	180 ... 250	—	—	133400	160000	53900	115000
	314MR3C	**114**	4.4	63200	32	180 ... 250	—	—	134500	161300	55000	115000
	314MR3C	**135**	3.7	64500	27.4	180 ... 250	—	—	137800	165300	58200	115000
	314MR3C	**157**	3.2	51800	18.9	180 ... 250	—	—	140800	168900	61200	115000
	314MR4	**160**	3.1	37100	13.7	71 ... 160	—	—	141200	169400	61600	115000
	314MR4	**189**	2.6	43800	13.7	71 ... 160	—	—	144600	173400	65100	115000
	314MR4	**238**	2.1	55000	13.7	71 ... 160	—	—	149400	179100	70200	115000
	314MR4	**276**	1.8	64000	13.7	71 ... 160	—	—	152600	183000	73800	115000
	314MR4	**354**	1.4	82100	13.7	71 ... 160	—	—	158200	189700	80300	115000
	314MR4	**421**	1.2	76700	10.8	71 ... 160	—	—	162100	194400	85000	115000
	314MR4	**445**	1.1	72200	9.6	71 ... 160	—	—	163400	195900	86600	115000
	314MR4	**528**	0.95	73300	8.2	71 ... 160	—	—	167400	200800	90000	115000
	314MR4	**614**	0.81	63300	6.1	71 ... 160	—	—	171100	205100	90000	115000

B



315M R

404

100800 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**315MR3B**	**51.1**	29.4	48900	150	180 ... 250	—	—	95500	114600	29200	135000
	315MR3B	**65.5**	22.9	62700	150	180 ... 250	—	—	103000	123500	31700	135000
	315MR3B	**77.8**	19.3	73600	150	180 ... 250	—	—	108400	130000	33600	135000
	315MR3B	**82.3**	18.2	68000	142	180 ... 250	—	—	110200	132200	34200	135000
	315MR3B	**97.6**	15.4	72000	127	180 ... 250	—	—	116000	139200	36200	135000
	315MR3B	**113**	13.2	59200	90	180 ... 250	—	—	121400	145600	38100	135000
	315MR3C	**70.7**	21.2	61700	150	180 ... 250	—	—	105300	126300	32500	135000
	315MR3C	**90.7**	16.5	77300	147	180 ... 250	—	—	113500	136100	35300	135000
	315MR3C	**108**	13.9	83100	133	180 ... 250	—	—	119500	143300	37400	135000
	315MR3C	**114**	13.2	72900	110	180 ... 250	—	—	121500	145700	38100	135000
	315MR3C	**135**	11.1	74000	94	180 ... 250	—	—	127900	153400	40300	135000
	315MR3C	**157**	9.5	59300	65	180 ... 250	—	—	132000	158300	42400	135000
	315MR4	**225**	6.7	83600	66	132 ... 200	—	—	132000	158300	47800	135000
	315MR4	**269**	5.6	92800	61	132 ... 200	—	—	132000	158300	50700	135000
	315MR4	**345**	4.3	94600	49	132 ... 200	—	—	134700	161500	55100	135000
	315MR4	**409**	3.7	94600	41	132 ... 200	—	—	138000	165500	58400	135000
	315MR4	**525**	2.9	94600	32	132 ... 200	—	—	143000	171500	63400	135000
	315MR4	**623**	2.4	94900	27.0	132 ... 200	—	—	146500	175700	67200	135000
	315MR4	**659**	2.3	85100	22.9	132 ... 200	—	—	147700	177100	68400	135000
	315MR4	**782**	1.9	86400	19.6	132 ... 200	—	—	151400	181500	72400	135000
	315MR4	**909**	1.6	72500	14.2	132 ... 200	—	—	154700	185500	76200	135000
1000	**315MR3B**	**51.1**	19.6	55200	124	180 ... 250	—	—	107900	129400	33400	135000
	315MR3B	**65.5**	15.3	70900	124	180 ... 250	—	—	116300	139500	36300	135000
	315MR3B	**77.8**	12.9	82700	122	180 ... 250	—	—	122400	146800	38400	135000
	315MR3B	**82.3**	12.2	72400	101	180 ... 250	—	—	124500	149300	39100	135000
	315MR3B	**97.6**	10.2	74500	88	180 ... 250	—	—	131000	157200	41400	135000
	315MR3B	**113**	8.8	59400	60	180 ... 250	—	—	132000	158300	43600	135000
	315MR3C	**70.7**	14.1	69700	113	180 ... 250	—	—	119000	142700	37200	135000
	315MR3C	**90.7**	11.0	86500	109	180 ... 250	—	—	128200	153800	40400	135000
	315MR3C	**108**	9.3	89500	95	180 ... 250	—	—	132000	158300	42800	135000
	315MR3C	**114**	8.8	75200	76	180 ... 250	—	—	132000	158300	43600	135000
	315MR3C	**135**	7.4	76000	65	180 ... 250	—	—	132000	158300	46200	135000
	315MR3C	**157**	6.4	59700	44	180 ... 250	—	—	132000	158300	48600	135000
	315MR4	**225**	4.4	91700	48	132 ... 200	—	—	134300	161000	54800	135000
	315MR4	**269**	3.7	94600	42	132 ... 200	—	—	137700	165100	58100	135000
	315MR4	**345**	2.9	94600	32	132 ... 200	—	—	142700	171100	63100	135000
	315MR4	**409**	2.4	94800	27.4	132 ... 200	—	—	146200	175300	66800	135000
	315MR4	**525**	1.9	96400	21.7	132 ... 200	—	—	151500	181700	72600	135000
	315MR4	**623**	1.6	97600	18.5	132 ... 200	—	—	155300	186200	76900	135000
	315MR4	**659**	1.5	88300	15.8	132 ... 200	—	—	156500	187700	78300	135000
	315MR4	**782**	1.3	89600	13.6	132 ... 200	—	—	160400	192400	82900	135000
	315MR4	**909**	1.1	77800	10.1	132 ... 200	—	—	163900	196500	87200	135000
500	**315MR3B**	**51.1**	9.8	68000	76	180 ... 250	—	—	132000	158300	42100	135000
	315MR3B	**65.5**	7.6	85700	75	180 ... 250	—	—	132000	158300	45700	135000
	315MR3B	**77.8**	6.4	92500	68	180 ... 250	—	—	132000	158300	48400	135000
	315MR3B	**82.3**	6.1	77000	54	180 ... 250	—	—	132000	158300	49300	135000
	315MR3B	**97.6**	5.1	77800	46	180 ... 250	—	—	132000	158300	52200	135000
	315MR3B	**113**	4.4	61200	31	180 ... 250	—	—	134400	161200	54900	135000
	315MR3C	**70.7**	7.1	85600	69	180 ... 250	—	—	132000	158300	46900	135000
	315MR3C	**90.7**	5.5	93800	59	180 ... 250	—	—	132000	158300	51000	135000
	315MR3C	**108**	4.6	94600	50	180 ... 250	—	—	133400	160000	53900	135000
	315MR3C	**114**	4.4	79100	40	180 ... 250	—	—	134500	161300	55000	135000
	315MR3C	**135**	3.7	80600	34	180 ... 250	—	—	137800	165300	58200	135000
	315MR3C	**157**	3.2	64800	23.7	180 ... 250	—	—	140800	168900	61200	135000
	315MR4	**225**	2.2	95400	25.1	132 ... 200	—	—	148200	177800	69000	135000
	315MR4	**269**	1.9	96600	21.3	132 ... 200	—	—	152000	182300	73200	135000
	315MR4	**345**	1.4	98200	16.8	132 ... 200	—	—	157500	188900	79500	135000
	315MR4	**409**	1.2	99400	14.4	132 ... 200	—	—	161400	193600	84200	135000

B



315M R

404

100800 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
	315MR4	**525**	0.95	100800	11.4	132 ... 200	—	—	167300	200600	90000	135000
	315MR4	**623**	0.80	100800	9.6	132 ... 200	—	—	171400	205600	90000	135000
	315MR4	**659**	0.76	91600	8.2	132 ... 200	—	—	172800	207200	90000	135000
	315MR4	**782**	0.64	91600	6.9	132 ... 200	—	—	177100	212400	90000	135000
	315MR4	**909**	0.55	79100	5.1	132 ... 200	—	—	180900	217000	90000	135000

316M R

416

134390 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**316MR3B**	**51.1**	29.4	48900	150	180 ... 250	—	—	146200	164000	48600	192000
	316MR3B	**64.1**	23.4	61400	150	180 ... 250	—	—	156500	175600	52400	192000
	316MR3B	**65.5**	22.9	62700	150	180 ... 250	—	—	157600	176800	52800	192000
	316MR3B	**77.8**	19.3	74500	150	180 ... 250	—	—	165900	186100	55900	192000
	316MR3B	**82.3**	18.2	78700	150	180 ... 250	—	—	168700	189200	57000	192000
	316MR3B	**97.6**	15.4	89000	150	180 ... 250	—	—	177600	199200	60300	192000
	316MR3C	**70.7**	21.2	61700	150	180 ... 250	—	—	161200	180800	54200	192000
	316MR3C	**88.7**	16.9	77500	150	180 ... 250	—	—	172600	193600	58400	192000
	316MR3C	**90.7**	16.5	79200	150	180 ... 250	—	—	173700	194900	58900	192000
	316MR3C	**108**	13.9	94000	150	180 ... 250	—	—	182900	205200	62300	192000
	316MR3C	**114**	13.2	92900	140	180 ... 250	—	—	186000	208600	63500	192000
	316MR3C	**135**	11.1	97700	124	180 ... 250	—	—	195800	219600	67200	192000
	316MR4	**225**	6.7	83600	66	132 ... 200	—	—	202000	226600	79700	192000
	316MR4	**269**	5.6	99700	66	132 ... 200	—	—	202000	226600	84600	192000
	316MR4	**289**	5.2	107200	66	132 ... 200	—	—	202000	226600	86600	192000
	316MR4	**337**	4.4	101400	53	132 ... 200	—	—	205400	230400	91200	192000
	316MR4	**363**	4.1	102600	50	132 ... 200	—	—	207500	232800	93400	192000
	316MR4	**430**	3.5	105500	43	132 ... 200	—	—	212700	238600	98900	192000
	316MR4	**443**	3.4	125100	50	132 ... 200	—	—	213500	239500	99900	192000
	316MR4	**525**	2.9	125700	42	132 ... 200	—	—	218800	245500	105700	192000
	316MR4	**623**	2.4	113800	32	132 ... 200	—	—	224200	251600	111900	192000
	316MR4	**659**	2.3	112400	30	132 ... 200	—	—	226000	253600	114000	192000
	316MR4	**782**	1.9	114300	25.9	132 ... 200	—	—	231600	259800	120700	192000
1000	**316MR3B**	**51.1**	19.6	55200	124	180 ... 250	—	—	165100	185200	55700	192000
	316MR3B	**64.1**	15.6	69300	124	180 ... 250	—	—	176800	198300	60000	192000
	316MR3B	**65.5**	15.3	70900	124	180 ... 250	—	—	178000	199600	60500	192000
	316MR3B	**77.8**	12.9	84100	124	180 ... 250	—	—	187300	210200	64000	192000
	316MR3B	**82.3**	12.2	88900	124	180 ... 250	—	—	190500	213700	65200	192000
	316MR3B	**97.6**	10.2	98900	116	180 ... 250	—	—	200500	225000	69100	192000
	316MR3C	**70.7**	14.1	69700	113	180 ... 250	—	—	182000	204200	62000	192000
	316MR3C	**88.7**	11.3	87500	113	180 ... 250	—	—	194900	218600	66900	192000
	316MR3C	**90.7**	11.0	89500	113	180 ... 250	—	—	196200	220100	67400	192000
	316MR3C	**108**	9.3	104900	112	180 ... 250	—	—	202000	226600	71400	192000
	316MR3C	**114**	8.8	99500	100	180 ... 250	—	—	202000	226600	72700	192000
	316MR3C	**135**	7.4	99500	84	180 ... 250	—	—	202000	226600	77000	192000
	316MR4	**225**	4.4	94400	50	132 ... 200	—	—	205500	230500	91300	192000
	316MR4	**269**	3.7	112300	49	132 ... 200	—	—	210700	236400	96800	192000
	316MR4	**289**	3.5	117500	48	132 ... 200	—	—	212900	238800	99200	192000
	316MR4	**337**	3.0	108300	38	132 ... 200	—	—	217600	244200	104400	192000
	316MR4	**363**	2.8	109600	36	132 ... 200	—	—	219900	246700	107000	192000
	316MR4	**430**	2.3	112100	31	132 ... 200	—	—	225400	252800	113300	192000
	316MR4	**443**	2.3	127000	34	132 ... 200	—	—	226300	253800	114300	192000
	316MR4	**525**	1.9	128600	29.0	132 ... 200	—	—	231900	260100	121000	192000
	316MR4	**623**	1.6	115800	22.0	132 ... 200	—	—	237600	266600	128100	192000
	316MR4	**659**	1.5	117100	21.0	132 ... 200	—	—	239500	268700	130500	192000
	316MR4	**782**	1.3	119200	18.0	132 ... 200	—	—	245500	275300	138200	192000
	316MR3B	**51.1**	9.8	68000	76	180 ... 250	—	—	202000	226600	70100	192000
	316MR3B	**64.1**	7.8	85300	76	180 ... 250	—	—	202000	226600	75600	192000



316M R

416

134390 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
500	**316MR3B**	**65.5**	7.6	87200	76	180 ... 250	—	—	202000	226600	76200	192000
	316MR3B	**77.8**	6.4	103500	76	180 ... 250	—	—	202000	226600	80700	192000
	316MR3B	**82.3**	6.1	98000	68	180 ... 250	—	—	202000	226600	82200	192000
	316MR3B	**97.6**	5.1	99500	58	180 ... 250	—	—	202000	226600	87000	192000
	316MR3C	**70.7**	7.1	85800	70	180 ... 250	—	—	202000	226600	78100	192000
	316MR3C	**88.7**	5.6	97900	63	180 ... 250	—	—	202000	226600	84300	192000
	316MR3C	**90.7**	5.5	110200	70	180 ... 250	—	—	202000	226600	84900	192000
	316MR3C	**108**	4.6	113600	61	180 ... 250	—	—	204100	229000	89900	192000
	316MR3C	**114**	4.4	101600	51	180 ... 250	—	—	205800	230800	91600	192000
	316MR3C	**135**	3.7	104500	44	180 ... 250	—	—	210900	236600	97000	192000
	316MR4	**225**	2.2	114300	30	132 ... 200	—	—	226800	254500	115000	192000
	316MR4	**269**	1.9	128800	28.3	132 ... 200	—	—	232600	261000	122000	192000
	316MR4	**289**	1.7	129400	26.5	132 ... 200	—	—	235100	263700	124900	192000
	316MR4	**337**	1.5	117400	20.6	132 ... 200	—	—	240300	269600	131500	192000
	316MR4	**363**	1.4	118300	19.3	132 ... 200	—	—	242800	272400	134800	192000
	316MR4	**430**	1.2	120300	16.5	132 ... 200	—	—	248800	279100	142700	192000
	316MR4	**443**	1.1	133300	17.8	132 ... 200	—	—	249800	280200	144000	192000
	316MR4	**525**	0.95	134400	15.1	132 ... 200	—	—	256000	287200	150000	192000
	316MR4	**623**	0.80	118100	11.2	132 ... 200	—	—	262400	294300	150000	192000
	316MR4	**659**	0.76	122200	11.0	132 ... 200	—	—	264400	296700	150000	192000
	316MR4	**782**	0.64	122200	9.2	132 ... 200	—	—	271000	304000	150000	192000

317M R

426

207490 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**317MR3B**	**49.8**	30	47700	150	180 ... 250	—	—	225800	239800	48200	393000
	317MR3B	**64.9**	23.1	62100	150	180 ... 250	—	—	244400	259700	52700	393000
	317MR3B	**78.1**	19.2	74800	150	180 ... 250	—	—	258400	274500	56000	393000
	317MR3B	**83.3**	18.0	79700	150	180 ... 250	—	—	263400	279900	57200	393000
	317MR3B	**100**	15.0	96000	150	180 ... 250	—	—	278500	295900	60900	393000
	317MR3B	**119**	12.6	106600	150	180 ... 250	—	—	293200	311500	64400	393000
	317MR3C	**68.9**	21.8	60200	150	180 ... 250	—	—	248900	264400	53700	393000
	317MR3C	**89.8**	16.7	78400	150	180 ... 250	—	—	269500	286300	58700	393000
	317MR3C	**108**	13.9	94400	150	180 ... 250	—	—	284900	302700	62400	393000
	317MR3C	**115**	13.0	100600	150	180 ... 250	—	—	290400	308600	63800	393000
	317MR3C	**139**	10.8	121200	150	180 ... 250	—	—	307100	326200	67800	393000
	317MR3C	**165**	9.1	113100	118	180 ... 250	—	—	314300	333900	71800	393000
	317MR4	**220**	6.8	81500	66	132 ... 200	—	—	314300	333900	79000	393000
	317MR4	**262**	5.7	97200	66	132 ... 200	—	—	314300	333900	83800	393000
	317MR4	**336**	4.5	124700	66	132 ... 200	—	—	319400	339400	91100	393000
	317MR4	**399**	3.8	148000	66	132 ... 200	—	—	327400	347800	96500	393000
	317MR4	**438**	3.4	156700	63	132 ... 200	—	—	331800	352500	99500	393000
	317MR4	**520**	2.9	166200	57	132 ... 200	—	—	340000	361200	105400	393000
	317MR4	**626**	2.4	121500	34	132 ... 200	—	—	349100	370900	112100	393000
	317MR4	**677**	2.2	156000	41	132 ... 200	—	—	353000	375100	115000	393000
	317MR4	**803**	1.9	155900	34	132 ... 200	—	—	361800	384300	121800	393000
	317MR4	**953**	1.6	139100	25.9	132 ... 200	—	—	370700	393900	129000	393000
1000	**317MR3B**	**49.8**	20.1	53800	124	180 ... 250	—	—	255000	270900	55200	393000
	317MR3B	**64.9**	15.4	70200	124	180 ... 250	—	—	276100	293300	60300	393000
	317MR3B	**78.1**	12.8	84400	124	180 ... 250	—	—	291800	310000	64100	393000
	317MR3B	**83.3**	12.0	90000	124	180 ... 250	—	—	297500	316100	65500	393000
	317MR3B	**100**	10.0	108400	124	180 ... 250	—	—	314300	333900	69700	393000
	317MR3B	**119**	8.4	113300	109	180 ... 250	—	—	314300	333900	73800	393000
	317MR3C	**68.9**	14.5	67900	113	180 ... 250	—	—	281100	298600	61500	393000
	317MR3C	**89.8**	11.1	88600	113	180 ... 250	—	—	304400	323300	67200	393000
	317MR3C	**108**	9.2	106000	112	180 ... 250	—	—	314300	333900	71500	393000

B



317M R

426

207490 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1000	**317MR3C**	**115**	8.7	113700	113	180 ... 250	—	—	314300	333900	73000	393000
	317MR3C	**139**	7.2	135200	112	180 ... 250	—	—	314300	333900	77700	393000
	317MR3C	**165**	6.1	113800	79	180 ... 250	—	—	314300	333900	82200	393000
	317MR4	**220**	4.6	92000	50	132 ... 200	—	—	318500	338400	90500	393000
	317MR4	**262**	3.8	109800	50	132 ... 200	—	—	326600	347000	96000	393000
	317MR4	**336**	3.0	140900	50	132 ... 200	—	—	338500	359600	104300	393000
	317MR4	**399**	2.5	167200	50	132 ... 200	—	—	346900	368500	110400	393000
	317MR4	**438**	2.3	168200	45	132 ... 200	—	—	351600	373500	113900	393000
	317MR4	**520**	1.9	170500	39	132 ... 200	—	—	360300	382700	120600	393000
	317MR4	**626**	1.6	123500	23.3	132 ... 200	—	—	369900	393000	128300	393000
	317MR4	**677**	1.5	156000	27.3	132 ... 200	—	—	374100	397400	131700	393000
	317MR4	**803**	1.2	155900	23.0	132 ... 200	—	—	383400	407300	139400	393000
	317MR4	**953**	1.0	149000	18.5	132 ... 200	—	—	392900	417400	147600	393000
500	**317MR3B**	**49.8**	10.0	66300	76	180 ... 250	—	—	313900	333500	69500	393000
	317MR3B	**64.9**	7.7	86400	76	180 ... 250	—	—	314300	333900	75900	393000
	317MR3B	**78.1**	6.4	104000	76	180 ... 250	—	—	314300	333900	80800	393000
	317MR3B	**83.3**	6.0	110800	76	180 ... 250	—	—	314300	333900	82500	393000
	317MR3B	**100**	5.0	133400	76	180 ... 250	—	—	314400	334000	87800	393000
	317MR3B	**119**	4.2	117600	57	180 ... 250	—	—	322200	342300	92900	393000
	317MR3C	**68.9**	7.3	83600	70	180 ... 250	—	—	314300	333900	77500	393000
	317MR3C	**89.8**	5.6	109000	70	180 ... 250	—	—	314300	333900	84600	393000
	317MR3C	**108**	4.6	121300	64	180 ... 250	—	—	317800	337700	90000	393000
	317MR3C	**115**	4.3	139900	70	180 ... 250	—	—	320800	340800	92000	393000
	317MR3C	**139**	3.6	152200	63	180 ... 250	—	—	329400	349900	97800	393000
	317MR3C	**165**	3.0	124300	43	180 ... 250	—	—	337500	358600	103600	393000
	317MR4	**220**	2.3	112800	30	132 ... 200	—	—	351700	373600	114000	393000
	317MR4	**262**	1.9	135100	31	132 ... 200	—	—	360600	383100	120900	393000
	317MR4	**336**	1.5	173400	31	132 ... 200	—	—	373700	397000	131400	393000
	317MR4	**399**	1.3	186800	27.7	132 ... 200	—	—	383000	406900	139100	393000
	317MR4	**438**	1.1	177900	24.0	132 ... 200	—	—	388200	412400	143500	393000
	317MR4	**520**	0.96	179800	20.5	132 ... 200	—	—	397800	422600	150000	393000
	317MR4	**626**	0.80	125800	11.9	132 ... 200	—	—	408400	433900	150000	393000
	317MR4	**677**	0.74	156000	13.6	132 ... 200	—	—	413000	438800	150000	393000
	317MR4	**803**	0.62	155900	11.5	132 ... 200	—	—	423300	449700	150000	393000
	317MR4	**953**	0.52	150300	9.3	132 ... 200	—	—	433700	460800	150000	393000

318M R

436

297550 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**318MR4B**	**225**	6.7	208700	150	180 ... 250	—	—	299000	337600	106200	500000
	318MR4B	**288**	5.2	231100	142	180 ... 250	—	—	299000	337600	115400	500000
	318MR4B	**342**	4.4	237000	123	180 ... 250	—	—	304700	344000	122200	500000
	318MR4B	**362**	4.1	239200	117	180 ... 250	—	—	307100	346800	124500	500000
	318MR4B	**430**	3.5	246200	102	180 ... 250	—	—	314700	355400	131800	500000
	318MR4B	**499**	3.0	249400	89	180 ... 250	—	—	321600	363100	138600	500000
	318MR4C	**311**	4.8	233200	133	180 ... 250	—	—	300600	339400	118400	500000
	318MR4C	**399**	3.8	243200	108	180 ... 250	—	—	311500	351700	128700	500000
	318MR4C	**474**	3.2	250300	94	180 ... 250	—	—	319200	360400	136200	500000
	318MR4C	**501**	3.0	252700	89	180 ... 250	—	—	321700	363300	138800	500000
	318MR4C	**595**	2.5	260100	78	180 ... 250	—	—	329700	372300	146900	500000
	318MR4C	**691**	2.2	257500	66	180 ... 250	—	—	336900	380400	154500	500000
1000	**318MR4B**	**225**	4.5	232800	123	180 ... 250	—	—	304000	343300	121600	500000
	318MR4B	**288**	3.5	246500	101	180 ... 250	—	—	315000	355700	132100	500000
	318MR4B	**342**	2.9	253800	88	180 ... 250	—	—	322900	364500	139900	500000
	318MR4B	**362**	2.8	256200	84	180 ... 250	—	—	325400	367400	142500	500000
	318MR4B	**430**	2.3	263200	72	180 ... 250	—	—	333500	376500	150900	500000



318M R

436

297550 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1000	**318MR4B**	**499**	2.0	258200	61	180 ... 250	—	—	340700	384700	158700	500000
	318MR4C	**311**	3.2	249700	95	180 ... 250	—	—	318500	359600	135500	500000
	318MR4C	**399**	2.5	260500	77	180 ... 250	—	—	330000	372600	147300	500000
	318MR4C	**474**	2.1	267000	67	180 ... 250	—	—	338200	381900	155900	500000
	318MR4C	**501**	2.0	269200	64	180 ... 250	—	—	340900	384900	158800	500000
	318MR4C	**595**	1.7	276000	55	180 ... 250	—	—	349400	394500	168200	500000
	318MR4C	**691**	1.4	261200	45	180 ... 250	—	—	357000	403000	176800	500000
500	**318MR4B**	**225**	2.2	265000	70	180 ... 250	—	—	335700	379000	153200	500000
	318MR4B	**288**	1.7	274700	56	180 ... 250	—	—	347800	392700	166500	500000
	318MR4B	**342**	1.5	281600	49	180 ... 250	—	—	356500	402500	176300	500000
	318MR4B	**362**	1.4	283900	46	180 ... 250	—	—	359300	405700	179600	500000
	318MR4B	**430**	1.2	291100	40	180 ... 250	—	—	368200	415700	190100	500000
	318MR4B	**499**	1.0	264700	31	180 ... 250	—	—	376200	424800	199900	500000
	318MR4C	**311**	1.6	277800	53	180 ... 250	—	—	351600	397000	170700	500000
	318MR4C	**399**	1.3	288000	43	180 ... 250	—	—	364400	411400	185500	500000
	318MR4C	**474**	1.1	295200	37	180 ... 250	—	—	373400	421600	196400	500000
	318MR4C	**501**	1.0	297600	35	180 ... 250	—	—	376400	425000	200000	500000
	318MR4C	**595**	0.84	297600	29.6	180 ... 250	—	—	385700	435500	200000	500000
	318MR4C	**691**	0.72	264700	22.6	180 ... 250	—	—	394100	445000	200000	500000

319 R

446

471190 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**319R4B**	**249**	6.0	231200	150	180 ... 250	—	—	363300	400000	109900	680000
	319R4B	**320**	4.7	296700	150	180 ... 250	—	—	366600	403600	119400	680000
	319R4B	**379**	4.0	334500	150	180 ... 250	—	—	375700	413600	126500	680000
	319R4B	**401**	3.7	340200	150	180 ... 250	—	—	378700	416900	128800	680000
	319R4B	**475**	3.2	294100	110	180 ... 250	—	—	387900	427100	136300	680000
	319R4B	**563**	2.7	302600	95	180 ... 250	—	—	397500	437700	144300	680000
	319R4B	**655**	2.3	308600	84	180 ... 250	—	—	406100	447200	151700	680000
	319R4C	**345**	4.4	291900	150	180 ... 250	—	—	370600	408000	122500	680000
	319R4C	**442**	3.4	350400	141	180 ... 250	—	—	384000	422800	133100	680000
	319R4C	**525**	2.9	368800	125	180 ... 250	—	—	393500	433300	140900	680000
	319R4C	**555**	2.7	375000	120	180 ... 250	—	—	396700	436800	143600	680000
	319R4C	**657**	2.3	310500	84	180 ... 250	—	—	406300	447400	151900	680000
	319R4C	**780**	1.9	319500	73	180 ... 250	—	—	416400	458500	160800	680000
	319R4C	**906**	1.7	319200	62	180 ... 250	—	—	425500	468400	169100	680000
1000	**319R4B**	**249**	4.0	261100	124	180 ... 250	—	—	374800	412700	125800	680000
	319R4B	**320**	3.1	335100	124	180 ... 250	—	—	388400	427700	136700	680000
	319R4B	**379**	2.6	377800	118	180 ... 250	—	—	398100	438300	144800	680000
	319R4B	**401**	2.5	384100	113	180 ... 250	—	—	401300	441800	147500	680000
	319R4B	**475**	2.1	314600	78	180 ... 250	—	—	411000	452500	156000	680000
	319R4B	**563**	1.8	323800	68	180 ... 250	—	—	421200	463800	165200	680000
	319R4B	**655**	1.5	321900	58	180 ... 250	—	—	430400	473800	173700	680000
	319R4C	**345**	2.9	329600	113	180 ... 250	—	—	392700	432300	140200	680000
	319R4C	**442**	2.3	392600	105	180 ... 250	—	—	406900	448000	152400	680000
	319R4C	**525**	1.9	400600	90	180 ... 250	—	—	417000	459100	161300	680000
	319R4C	**555**	1.8	413100	88	180 ... 250	—	—	420300	462800	164400	680000
	319R4C	**657**	1.5	332200	60	180 ... 250	—	—	430600	474100	173900	680000
	319R4C	**780**	1.3	341800	52	180 ... 250	—	—	441200	485800	184100	680000
	319R4C	**906**	1.1	333000	43	180 ... 250	—	—	450800	496400	193600	680000
500	**319R4B**	**249**	2.0	321400	76	180 ... 250	—	—	413900	455700	158500	680000
	319R4B	**320**	1.6	412200	76	180 ... 250	—	—	428900	472200	172300	680000
	319R4B	**379**	1.3	424300	66	180 ... 250	—	—	439500	483900	182400	680000
	319R4B	**401**	1.2	448500	66	180 ... 250	—	—	443000	487800	185800	680000
	319R4B	**475**	1.1	353200	44	180 ... 250	—	—	453800	499700	196500	680000
	319R4B	**563**	0.89	356300	37	180 ... 250	—	—	465000	512000	200000	680000
	319R4B	**655**	0.76	336400	30	180 ... 250	—	—	475200	523200	200000	680000



319 R

446

471190 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
500	**319R4C**	**345**	1.5	405900	70	180 ... 250	—	—	433600	477300	176700	680000
	319R4C	**442**	1.1	458400	61	180 ... 250	—	—	449300	494700	192000	680000
	319R4C	**525**	0.95	443000	50	180 ... 250	—	—	460400	506900	200000	680000
	319R4C	**555**	0.90	471200	50	180 ... 250	—	—	464100	511000	200000	680000
	319R4C	**657**	0.76	356300	32	180 ... 250	—	—	475400	523400	200000	680000
	319R4C	**780**	0.64	356300	27.0	180 ... 250	—	—	487200	536400	200000	680000
	319R4C	**906**	0.55	336400	22.0	180 ... 250	—	—	497800	548000	200000	680000

B

321 R

456

655200 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)	Rn_2 [N] MC	MZ	HC/PC	HZ/PZ	FZ	$M_{2\,max}$ Nm
1500	**321R4B**	**221**	6.8	205600	150	180 ... 250	—	—	513900	611700	675800	934000
	321R4B	**288**	5.2	265300	150	180 ... 250	—	—	513900	611700	731700	934000
	321R4B	**347**	4.3	320600	150	180 ... 250	—	—	524700	624600	773600	934000
	321R4B	**370**	4.1	341300	150	180 ... 250	—	—	529600	630300	788600	934000
	321R4B	**446**	3.4	409600	150	180 ... 250	—	—	543800	647300	833700	934000
	321R4B	**529**	2.8	484700	150	180 ... 250	—	—	557200	663300	877700	934000
	321R4C	**306**	4.9	249000	144	180 ... 250	—	—	515400	613500	745100	934000
	321R4C	**399**	3.8	324600	144	180 ... 250	—	—	535300	637200	806700	934000
	321R4C	**481**	3.1	390700	144	180 ... 250	—	—	549700	654300	852900	934000
	321R4C	**512**	2.9	416600	144	180 ... 250	—	—	554700	660300	869400	934000
	321R4C	**617**	2.4	501400	144	180 ... 250	—	—	569600	678000	919200	934000
	321R4C	**732**	2.0	521400	126	180 ... 250	—	—	583700	694800	967600	934000
1000	**321R4B**	**221**	4.5	233700	125	180 ... 250	—	—	521400	620600	763200	934000
	321R4B	**288**	3.5	304200	125	180 ... 250	—	—	541500	644500	826400	934000
	321R4B	**347**	2.9	361600	123	180 ... 250	—	—	556000	661800	873700	934000
	321R4B	**370**	2.7	391600	125	180 ... 250	—	—	561100	667900	890600	934000
	321R4B	**446**	2.2	460100	122	180 ... 250	—	—	576200	685900	941500	934000
	321R4B	**529**	1.9	513000	115	180 ... 250	—	—	590500	702800	991200	934000
	321R4C	**306**	3.3	281200	109	180 ... 250	—	—	546200	650100	841500	934000
	321R4C	**399**	2.5	366600	109	180 ... 250	—	—	567200	675200	911100	934000
	321R4C	**481**	2.1	441300	109	180 ... 250	—	—	582500	693300	963200	934000
	321R4C	**512**	2.0	470500	109	180 ... 250	—	—	587800	699700	981900	934000
	321R4C	**617**	1.6	566500	109	180 ... 250	—	—	603600	718500	1038100	934000
	321R4C	**732**	1.4	529800	86	180 ... 250	—	—	618600	736300	1092800	934000
500	**321R4B**	**221**	2.3	290300	78	180 ... 250	—	—	575600	685200	939600	934000
	321R4B	**288**	1.7	379500	78	180 ... 250	—	—	597900	711600	1017400	934000
	321R4B	**347**	1.4	450300	77	180 ... 250	—	—	613900	730700	1075600	934000
	321R4B	**370**	1.4	483100	77	180 ... 250	—	—	619500	737400	1096500	934000
	321R4B	**446**	1.1	567200	75	180 ... 250	—	—	636200	757200	1159200	934000
	321R4B	**529**	0.95	536400	60	180 ... 250	—	—	651900	776000	1200000	934000
	321R4C	**306**	1.6	346300	67	180 ... 250	—	—	603000	717800	1036000	934000
	321R4C	**399**	1.3	451600	67	180 ... 250	—	—	626300	745500	1121700	934000
	321R4C	**481**	1.0	543700	67	180 ... 250	—	—	643100	765500	1185800	934000
	321R4C	**512**	0.98	575400	66	180 ... 250	—	—	649000	772500	1200000	934000
	321R4C	**617**	0.81	655200	63	180 ... 250	—	—	666400	793300	1200000	934000
	321R4C	**732**	0.68	536400	43	180 ... 250	—	—	682900	812900	1200000	934000

25.5 3/V_M - PLANETARYWORM RATING CHARTS

Reading the rating chart.



n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC) B5	B5 / B14				Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
1500	**3/V 10M L4**	1617	**0.93**	28100	3.5	71	80	90	100	112	—	—	99200	125800	65000
	3/V 10M L4	1855	**0.81**	27100	3.0	71	80	90	100	112	—	—	101200	128300	65000
	3/V 10M L4	2016	**0.74**	29400	3.0	71	80	90	100	112	—	—	102400	129800	65000
	3/V 10M L4	2156	**0.70**	28100	2.7	71	80	90	100	112	—	—	103400	131100	65000
	3/V 10M L4	2455	**0.61**	27200	2.2	71	80	90	100	112	—	—	105300	133500	65000

1	Reference torque
2	Gearbox drive speed
3	Frame size of combined worm + planetary gearbox
4	Gear ratio
5	Gearbox output speed
6	Gearbox rated output torque based on: - service factor f_S=1 - 10000 h theoretical lifetime
7	Gearbox rated input power, based on: - service factor f_S=1 - 10000 h theoretical lifetime
8	Frame size of compatible IEC electric motor - IEC inputs marked with * feature a lowered key.
9	Permitted overhung loading on output shaft, based on: - service factor f_S=1 - 10000 h theoretical lifetime - speed of output n_2 For forces not applied at shaft middlepoint, see diagrams provided in the specific gearbox overall dimensioning pages
10	Dimensions page

B



3/V 00 L3 — 266 — 1250 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC) B5 / B14			Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
1500	**3/V 00 L3**	**415**	3.6	1000	0.57	63	71	80	6810	6810	22500	26200	5210
	3/V 00 L3	**436**	3.4	730	0.42	63	71	—	6860	6860	22700	26400	5300
	3/V 00 L3	**509**	2.9	1040	0.48	63	71	80	7010	7010	23200	27000	5580
	3/V 00 L3	**562**	2.7	720	0.30	63	71	80	7110	7110	23500	27300	5770
	3/V 00 L3	**654**	2.3	1090	0.41	63	71	—	7270	7270	24000	27900	6070
	3/V 00 L3	**689**	2.2	1100	0.37	63	71	80	7320	7320	24200	28200	6170
	3/V 00 L3	**818**	1.8	1110	0.36	63	71	—	7500	7500	24800	28900	6540
	3/V 00 L3	**903**	1.7	790	0.23	63	71	—	7610	7610	25200	29300	6760
	3/V 00 L3	**997**	1.5	800	0.18	63	71	80	7720	7720	25500	29700	6980
	3/V 00 L3	**1107**	1.4	1190	0.28	63	71	—	7830	7830	25900	30100	7230
	3/V 00 L3	**1198**	1.3	830	0.17	63	71	—	7920	7920	26200	30500	7420
	3/V 00 L3	**1381**	1.1	1230	0.24	63	71	—	8080	8080	26700	31100	7780
	3/V 00 L3	**1495**	1.0	860	0.14	63	71	—	8180	8180	27000	31400	7990
	3/V 00 L3	**1869**	0.80	860	0.12	63	71	—	8440	8440	27900	32500	8000
	3/V 00 L3	**2337**	0.64	860	0.10	63	71	—	8710	8710	28800	33500	8000

3/V 01 L3 — 276 — 2460 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC) B5 / B14			Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
1500	**3/V 01 L3**	**430**	3.5	1880	0.90	63	71	80	6840	6840	22600	24700	5270
	3/V 01 L3	**443**	3.4	1370	0.66	63	71	80	6870	6870	22700	24800	5330
	3/V 01 L3	**509**	2.9	1270	0.58	63	71	80	7010	7010	23200	25300	5580
	3/V 01 L3	**562**	2.7	1400	0.58	63	71	80	7110	7110	23500	25700	5770
	3/V 01 L3	**654**	2.3	1180	0.45	63	71	—	7270	7270	24000	26300	6070
	3/V 01 L3	**689**	2.2	1710	0.58	63	71	80	7320	7320	24200	26500	6170
	3/V 01 L3	**799**	1.9	1540	0.43	63	71	80	7480	7480	24700	27000	6480
	3/V 01 L3	**903**	1.7	1230	0.36	63	71	—	7610	7610	25200	27500	6760
	3/V 01 L3	**997**	1.5	1600	0.36	63	71	80	7720	7720	25500	27900	6980
	3/V 01 L3	**1105**	1.4	1990	0.45	63	71	—	7830	7830	25900	28300	7230
	3/V 01 L3	**1198**	1.3	1650	0.34	63	71	—	7920	7920	26200	28600	7420
	3/V 01 L3	**1381**	1.1	1880	0.36	63	71	—	8080	8080	26700	29200	7780
	3/V 01 L3	**1495**	1.0	1720	0.29	63	71	—	8180	8180	27000	29600	7990
	3/V 01 L3	**1869**	0.80	1720	0.24	63	71	—	8440	8440	27900	30500	8000
	3/V 01 L3	**2337**	0.64	1720	0.20	63	71	—	8710	8710	28800	31500	8000

3/V 03 L3 — 286 — 2970 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC) B5 / B14			Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
1500	**3/V 03 L3**	**395**	3.8	2210	1.2	71	80	90	21800	25000	42100	49900	15400
	3/V 03 L3	**460**	3.3	2310	1.1	71	80	90	22300	25500	43100	51000	16200
	3/V 03 L3	**502**	3.0	2020	0.83	71	80	90	22600	25800	43600	51700	16700
	3/V 03 L3	**544**	2.8	2730	1.1	71	80	90	22900	26100	44100	52300	17100
	3/V 03 L3	**623**	2.4	2220	0.80	71	80	90	23300	26600	45000	53300	17900
	3/V 03 L3	**736**	2.0	2720	0.83	71	80	90	23900	27300	46000	54600	18900
	3/V 03 L3	**793**	1.9	2180	0.62	71	80	90	24100	27600	46500	55100	19400
	3/V 03 L3	**923**	1.6	2670	0.65	71	80	90	24700	28200	47600	56400	20400
	3/V 03 L3	**1023**	1.5	2710	0.66	71	80	—	25000	28600	48300	57200	21100
	3/V 03 L3	**1189**	1.3	2340	0.49	71	80	—	25600	29200	49300	58400	22200
	3/V 03 L3	**1385**	1.1	2820	0.51	71	80	—	26100	29900	50400	59700	23400
	3/V 03 L3	**1610**	0.93	2440	0.38	71	80	—	26700	30500	51500	61000	24000
	3/V 03 L3	**1728**	0.87	2850	0.41	71	80	—	27000	30800	52000	61600	24000
	3/V 03 L3	**2009**	0.75	2440	0.30	71	80	—	27600	31500	53100	63000	24000
	3/V 03 L3	**2511**	0.60	2300	0.23	71	80	—	28400	32500	54900	65000	24000



3/V 04 L3 — 298 — 3960 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)					Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
						B5	B5 / B14								
1500	3/V 04 L3	384	3.9	3510	1.9	71	80	90	100	112	21800	24900	41900	49700	15200
	3/V 04 L3	453	3.3	3730	1.7	71	80	90	100	112	22300	25500	43000	50900	16100
	3/V 04 L3	501	3.0	3010	1.4	71	80	90	100	112	22600	25800	43600	51700	16700
	3/V 04 L3	568	2.6	3160	1.2	71	80	90	100	112	23000	26300	44400	52600	17400
	3/V 04 L3	623	2.4	3530	1.2	71	80	90	100	112	23300	26600	45000	53300	17900
	3/V 04 L3	710	2.1	2640	0.73	71	80	90	100	112	23700	27100	45800	54300	18700
	3/V 04 L3	769	1.9	3330	0.90	71	80	90	100	112	24000	27500	46300	54900	19200
	3/V 04 L3	887	1.7	2740	0.61	71	80	90	100	112	24500	28000	47300	56000	20100
	3/V 04 L3	981	1.5	3860	0.91	71	80	90	100	112	24900	28400	48000	56900	20800
	3/V 04 L3	1152	1.3	3570	0.67	71	80	90	100	112	25500	29100	49100	58200	22000
	3/V 04 L3	1231	1.2	3610	0.68	71	80	90	100	112	25700	29400	49500	58700	22500
	3/V 04 L3	1419	1.1	2970	0.45	71	80	90	100	112	26200	30000	50600	59900	23600
	3/V 04 L3	1536	0.98	3740	0.56	71	80	90	100	112	26500	30300	51100	60600	24000
	3/V 04 L3	1774	0.85	3000	0.37	71	80	90	100	112	27100	30900	52200	61900	24000
	3/V 04 L3	1893	0.79	3000	0.37	71	80	90	100	112	27300	31200	52700	62400	24000
	3/V 04 L3	2366	0.63	3000	0.29	71	80	90	100	112	28200	32200	54400	64500	24000

3/V 05 L3 — 310 — 5800 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)					Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
						B5	B5 / B14								
1500	3/V 05 L3	396	3.8	3760	1.9	71	80	90	100	112	21900	25000	42100	50000	15400
	3/V 05 L3	462	3.3	4820	2.0	71	80	90	100	112	22300	25500	43100	51000	16200
	3/V 05 L3	529	2.8	3920	1.5	71	80	90	100	112	22800	26000	43900	52000	17000
	3/V 05 L3	576	2.6	4870	1.7	71	80	90	100	112	23100	26300	44500	52700	17400
	3/V 05 L3	623	2.4	4460	1.6	71	80	90	100	112	23300	26600	45000	53300	17900
	3/V 05 L3	715	2.1	4120	1.2	71	80	90	100	112	23800	27200	45900	54300	18800
	3/V 05 L3	793	1.9	4200	1.1	71	80	90	100	112	24100	27600	46500	55100	19400
	3/V 05 L3	894	1.7	4290	1.0	71	80	90	100	112	24500	28100	47300	56100	20200
	3/V 05 L3	1057	1.4	4410	0.97	71	80	90	100	112	25100	28700	48500	57500	21400
	3/V 05 L3	1116	1.3	4460	0.83	71	80	90	100	112	25300	29000	48900	57900	21700
	3/V 05 L3	1231	1.2	5470	1.0	71	80	90	100	112	25700	29400	49500	58700	22500
	3/V 05 L3	1431	1.0	4650	0.75	71	80	90	100	112	26300	30000	50600	60000	23600
	3/V 05 L3	1674	0.90	4430	0.57	71	80	90	100	112	26800	30700	51800	61400	24000
	3/V 05 L3	1786	0.84	4690	0.61	71	80	90	100	112	27100	31000	52300	61900	24000
	3/V 05 L3	2232	0.67	4430	0.46	71	80	90	100	112	28000	32000	53900	63900	24000

3/V 06 L3 — 322 — 10840 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)					Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
						B5	B5 / B14								
1500	3/V 06 L3	395	3.8	7590	3.8	71	80	90	100	112	26000	29600	59300	68400	22400
	3/V 06 L3	427	3.5	8820	4.1	71	80	90	100	112	26300	30000	59900	69200	23000
	3/V 06 L3	527	2.8	7590	2.9	71	80	90	100	112	27100	30900	61800	71300	24700
	3/V 06 L3	569	2.6	8560	3.0	71	80	90	100	112	27400	31200	62500	72100	25300
	3/V 06 L3	661	2.3	9370	2.8	71	80	90	100	112	28000	31900	63800	73700	26600
	3/V 06 L3	698	2.2	7540	2.1	71	80	90	100	112	28200	32200	64300	74200	27100
	3/V 06 L3	791	1.9	7680	2.1	71	80	90	100	112	28700	32700	65500	75600	28300
	3/V 06 L3	930	1.6	7890	1.7	71	80	90	100	112	29400	33500	67000	77300	29800
	3/V 06 L3	992	1.5	9450	2.1	71	80	90	100	112	29700	33800	67600	78100	30500
	3/V 06 L3	1153	1.3	8250	1.6	71	80	90	100	112	30300	34500	69100	79800	32100
	3/V 06 L3	1212	1.2	7820	1.5	71	80	90	100	112	30500	34800	69600	80300	32600
	3/V 06 L3	1395	1.1	8400	1.3	71	80	90	100	112	31100	35500	71000	82000	34200
	3/V 06 L3	1768	0.85	8630	1.1	71	80	90	100	112	32200	36700	73400	84800	35000
	3/V 06 L3	2139	0.70	8500	0.91	71	80	90	100	112	33100	37700	75500	87100	35000
	3/V 06 L3	2588	0.58	7000	0.62	71	80	90	100	112	34000	38800	77500	89500	35000



3/V 07 L3

334

15680 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)					Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
						B5 / B14				B5					
1500	**3/V 07 L3**	**386**	3.9	9020	4.5	80	90	100	112	132	31100	38900	70000	92100	28600
	3/V 07 L3	**460**	3.3	12300	5.3	80	90	100	112	132	31900	39900	71800	94400	30400
	3/V 07 L3	**507**	3.0	13600	5.3	80	90	100	112	132	32300	40400	72800	95700	31400
	3/V 07 L3	**655**	2.3	14400	4.8	80	90	100	112	132	33500	41900	75500	99300	34100
	3/V 07 L3	**761**	2.0	14200	4.0	80	90	100	112	132	34300	42800	77100	101400	35900
	3/V 07 L3	**773**	1.9	9970	2.6	80	90	100	112	132	34300	42900	77300	101600	36100
	3/V 07 L3	**920**	1.6	12300	2.9	80	90	100	112	132	35200	44000	79200	104200	38200
	3/V 07 L3	**1015**	1.5	14400	3.1	80	90	100	112	132	35700	44600	80300	105700	39500
	3/V 07 L3	**1159**	1.3	10600	2.0	80	90	100	112	132	36400	45500	81900	107700	41300
	3/V 07 L3	**1288**	1.2	14500	2.5	80	90	100	112	132	36900	46200	83100	109300	42800
	3/V 07 L3	**1411**	1.1	12300	2.0	80	90	100	112	132	37400	46800	84200	110800	44100
	3/V 07 L3	**1545**	0.97	11000	1.6	80	90	100	112	132	37900	47400	85300	112200	45000
	3/V 07 L3	**1964**	0.76	12300	1.5	80	90	100	112	132	39200	49000	88300	116100	45000
	3/V 07 L3	**2150**	0.70	11000	1.2	80	90	100	112	132	39700	49700	89400	117600	45000
	3/V 07 L3	**2472**	0.61	11000	1.1	80	90	100	112	132	40500	50700	91200	120000	45000

3/V 09 L3

346

23240 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)				Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
						B5								
1500	**3/V 09 L3**	**370**	4.1	13000	7.3	100	112	132	—	—	—	71100	91500	22600
	3/V 09 L3	**442**	3.4	17700	8.4	100	112	132	—	—	—	72900	93800	24000
	3/V 09 L3	**507**	3.0	14300	5.6	—	—	132	160	—	—	74400	95700	25100
	3/V 09 L3	**655**	2.3	17600	5.6	100	112	132	—	—	—	77100	99300	27300
	3/V 09 L3	**761**	2.0	14400	3.9	100	112	132	—	—	—	78800	101400	28700
	3/V 09 L3	**800**	1.9	21400	5.8	100	112	132	—	—	—	79400	102200	29200
	3/V 09 L3	**840**	1.8	20100	5.0	100	112	132	—	—	—	79900	102900	29700
	3/V 09 L3	**1004**	1.5	18100	3.9	100	112	132	—	—	—	82000	105500	31500
	3/V 09 L3	**1159**	1.3	16200	2.9	100	112	132	—	—	—	83700	107700	33000
	3/V 09 L3	**1288**	1.2	21500	3.6	100	112	132	—	—	—	85000	109300	34200
	3/V 09 L3	**1497**	1.0	18300	2.6	100	112	132	—	—	—	86800	111700	36000
	3/V 09 L3	**1623**	0.92	14700	2.1	100	112	—	—	—	—	87800	113000	36000
	3/V 09 L3	**1792**	0.84	22000	2.8	100	112	—	—	—	—	89100	114600	36000
	3/V 09 L3	**2150**	0.70	17000	1.7	100	112	132	—	—	—	91400	117600	36000
	3/V 09 L3	**2472**	0.61	17000	1.6	100	112	—	—	—	—	93300	120000	36000

3/V 10M L3

358

33640 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)				Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
						B5								
1500	**3/V 10M L3**	**436**	3.4	26700	12.2	—	—	132	160 (*)	—	—	82300	104300	43100
	3/V 10M L3	**507**	3.0	24900	9.7	—	—	132	160 (*)	—	—	84100	106600	45300
	3/V 10M L3	**560**	2.7	25300	9.0	—	—	132	160 (*)	—	—	85300	108100	46800
	3/V 10M L3	**614**	2.4	19300	6.3	—	—	132	160 (*)	—	—	86400	109500	48300
	3/V 10M L3	**701**	2.1	20900	5.7	—	—	132	160 (*)	—	—	88100	111600	50400
	3/V 10M L3	**773**	1.9	21300	5.5	—	—	132	160 (*)	—	—	89300	113200	52100
	3/V 10M L3	**920**	1.6	19400	4.4	100	112	132	—	—	—	91500	116100	55200
	3/V 10M L3	**1004**	1.5	31800	6.9	100	112	132	—	—	—	92700	117500	56900
	3/V 10M L3	**1120**	1.3	28600	5.5	100	112	132	—	—	—	94200	119400	59000
	3/V 10M L3	**1227**	1.2	19400	3.4	100	112	132	—	—	—	95400	120900	60800
	3/V 10M L3	**1411**	1.1	19500	3.0	100	112	132	—	—	—	97300	123400	63700



3/V 10M L4 — 359 — 33640 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)					Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
						B5	B5 / B14								
1500	3/V 10M L4	1617	0.93	28100	3.5	71	80	90	100	112	—	—	99200	125800	65000
	3/V 10M L4	1855	0.81	27100	3.0	71	80	90	100	112	—	—	101200	128300	65000
	3/V 10M L4	2016	0.74	29400	3.0	71	80	90	100	112	—	—	102400	129800	65000
	3/V 10M L4	2156	0.70	28100	2.7	71	80	90	100	112	—	—	103400	131100	65000
	3/V 10M L4	2455	0.61	27200	2.2	71	80	90	100	112	—	—	105300	133500	65000
	3/V 10M L4	2987	0.50	30100	2.1	71	80	90	100	112	—	—	108300	137300	65000
	3/V 10M L4	3273	0.46	27200	1.7	71	80	90	100	112	—	—	109700	139100	65000
	3/V 10M L4	3570	0.42	30100	1.9	71	80	90	100	112	—	—	111100	140900	65000
	3/V 10M L4	4036	0.37	30100	1.5	71	80	90	100	112	—	—	113100	143400	65000
	3/V 10M L4	4637	0.32	30100	1.5	71	80	90	100	112	—	—	115300	146200	65000
	3/V 10M L4	4959	0.30	28100	1.3	71	80	90	100	112	—	—	116400	147600	65000

B

3/V 11M L3 — 370 — 49210 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)					Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
						B5									
1500	3/V 11M L3	430	3.5	39100	17.9	—	—	—	160	180 (*)	—	—	107800	134200	42800
	3/V 11M L3	510	2.9	32000	12.3	—	—	—	160	180 (*)	—	—	113400	141300	45400
	3/V 11M L3	551	2.7	40800	14.5	—	—	—	160	180 (*)	—	—	116100	144600	46600
	3/V 11M L3	644	2.3	40000	12.5	—	—	132	160	—	—	—	121700	151600	49000
	3/V 11M L3	720	2.1	41400	12.3	—	—	132	160	—	—	—	125800	156700	50900
	3/V 11M L3	827	1.8	43500	10.6	—	—	132	160	—	—	—	131100	163400	53300
	3/V 11M L3	900	1.7	41400	10.1	100	112	132	—	—	—	—	134500	167600	54800
	3/V 11M L3	1004	1.5	35700	8.0	100	112	132	—	—	—	—	139000	173200	56900
	3/V 11M L3	1103	1.4	45600	8.8	—	—	132	160	—	—	—	143000	178100	58700
	3/V 11M L3	1274	1.2	33200	5.7	100	112	132	—	—	—	—	149300	186000	61600
	3/V 11M L3	1378	1.1	47200	7.5	100	112	132	—	—	—	—	152900	190400	63200
	3/V 11M L3	1636	0.92	41300	5.5	100	112	132	—	—	—	—	157000	195000	65000
	3/V 11M L3	1963	0.76	41300	4.7	100	112	132	—	—	—	—	157000	195000	65000
	3/V 11M L3	2329	0.64	36500	3.5	100	112	132	—	—	—	—	157000	195000	65000

3/V 11M L4 — 371 — 49210 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)					Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
						B5 / B14				B5					
1500	3/V 11M L4	2663	0.56	47800	3.7	80	90	100	112	132	—	—	133900	136600	65000
	3/V 11M L4	3063	0.49	47800	3.2	80	90	100	112	132	—	—	136600	139400	65000
	3/V 11M L4	3222	0.47	47800	3.0	80	90	100	112	132	—	—	137600	140400	65000
	3/V 11M L4	3557	0.42	42300	2.8	80	90	100	112	132	—	—	139500	142400	65000
	3/V 11M L4	4106	0.37	48900	2.8	80	90	100	112	132	—	—	142400	145300	65000
	3/V 11M L4	4410	0.34	47800	2.4	80	90	100	112	132	—	—	143900	146800	65000
	3/V 11M L4	5326	0.28	47800	2.0	80	90	100	112	132	—	—	147800	150800	65000



3/V 13M L3

382

60940 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)					Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
						B5									
1500	3/V 13M L3	370	4.1	39500	21	—	—	—	160	180 (*)	—	—	146300	171500	50200
	3/V 13M L3	425	3.5	45900	20	—	—	—	160	180 (*)	—	—	149300	174900	52600
	3/V 13M L3	516	2.9	48600	18.5	—	—	—	160	180 (*)	—	—	153500	179800	56100
	3/V 13M L3	567	2.6	48200	16.7	—	—	—	160	180 (*)	—	—	155500	182200	57800
	3/V 13M L3	673	2.2	49700	14.5	—	—	—	160	180 (*)	—	—	159400	186800	61200
	3/V 13M L3	741	2.0	45800	13.2	—	—	132	160	—	—	—	161600	189300	63200
	3/V 13M L3	810	1.9	36000	8.7	—	—	—	160	180 (*)	—	—	163600	191800	65100
	3/V 13M L3	870	1.7	53800	13.2	—	—	132	160	—	—	—	165300	193700	66700
	3/V 13M L3	1009	1.5	53300	10.6	—	—	132	160	—	—	—	168900	197900	70100
	3/V 13M L3	1088	1.4	51200	10.3	100	112	132	—	—	—	—	170700	200000	71900
	3/V 13M L3	1291	1.2	50400	8.6	100	112	132	—	—	—	—	174900	205000	76100
	3/V 13M L3	1418	1.1	56600	8.8	100	112	132	—	—	—	—	177300	207700	78500
	3/V 13M L3	1620	0.93	40100	5.3	—	—	132	160	—	—	—	180700	211700	80000
	3/V 13M L3	1682	0.89	57100	7.5	100	112	132	—	—	—	—	181700	212900	80000
	3/V 13M L3	2019	0.74	57100	6.4	100	112	132	—	—	—	—	186500	218500	80000
	3/V 13M L3	2430	0.62	40100	3.7	100	112	132	—	—	—	—	191500	224400	80000

B

3/V 13M L4

383

60940 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)					Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
						B5 / B14				B5					
1500	3/V 13M L4	2773	0.54	59100	4.8	80	90	100	112	132	—	—	192000	228600	80000
	3/V 13M L4	3263	0.46	54100	3.4	80	90	100	112	132	—	—	192000	231000	80000
	3/V 13M L4	3515	0.43	57100	3.3	80	90	100	112	132	—	—	192000	231000	80000
	3/V 13M L4	4046	0.37	60900	3.4	80	90	100	112	132	—	—	192000	231000	80000
	3/V 13M L4	4536	0.33	57100	2.8	80	90	100	112	132	—	—	192000	231000	80000
	3/V 13M L4	5046	0.30	50800	2.3	80	90	100	112	132	—	—	192000	231000	80000

3/V 14M L3

394

80640 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)					Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
						B5									
1500	3/V 14M L3	397	3.8	46100	22	—	—	—	160	180 (*)	—	—	137400	164800	57800
	3/V 14M L3	446	3.4	47700	21	—	—	—	160	180 (*)	—	—	139700	167500	60100
	3/V 14M L3	498	3.0	57800	22	—	—	—	160	180 (*)	—	—	141900	170200	62300
	3/V 14M L3	579	2.6	53700	17.6	—	—	—	160	180 (*)	—	—	145000	173900	65500
	3/V 14M L3	665	2.3	68100	20	—	—	—	160	180 (*)	—	—	147900	177300	68600
	3/V 14M L3	695	2.2	43000	13.2	—	—	132	160	—	—	—	148800	178500	69700
	3/V 14M L3	794	1.9	49300	12.5	—	—	132	160	—	—	—	151700	181900	72800
	3/V 14M L3	893	1.7	55200	13.2	—	—	132	160	—	—	—	154200	185000	75700
	3/V 14M L3	997	1.5	61900	12.5	—	—	132	160	—	—	—	156700	187900	78500
	3/V 14M L3	1116	1.3	52500	10.3	100	112	132	—	—	—	—	159200	191000	81500
	3/V 14M L3	1324	1.1	61500	10.2	100	112	132	—	—	—	—	163200	195700	86300
	3/V 14M L3	1339	1.1	47700	8.0	100	112	132	—	—	—	—	163400	196000	86700
	3/V 14M L3	1589	0.94	56600	8.0	100	112	132	—	—	—	—	167500	200900	90000
	3/V 14M L3	1662	0.90	73300	9.7	100	112	132	—	—	—	—	168600	202200	90000
	3/V 14M L3	1994	0.75	71000	8.0	100	112	132	—	—	—	—	173000	207500	90000
	3/V 14M L3	2318	0.65	63300	6.2	100	112	132	—	—	—	—	176800	212000	90000



3/V 14M L4 — 395 — 80640 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)				Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
						B5								
1500	3/V 14M L4	2504	0.60	80600	7.2	100	112	132	—	—	—	178700	214300	90000
	3/V 14M L4	2782	0.54	80600	6.2	100	112	132	—	—	—	181400	217600	90000
	3/V 14M L4	3182	0.47	78000	5.1	100	112	132	—	—	—	185000	221800	90000
	3/V 14M L4	3472	0.43	73300	4.3	—	—	132	160	—	—	187300	224600	90000
	3/V 14M L4	3993	0.38	73300	3.8	100	112	132	—	—	—	191100	229100	90000
	3/V 14M L4	4312	0.35	80600	4.2	100	112	132	—	—	—	193200	231700	90000
	3/V 14M L4	4959	0.30	80600	3.6	100	112	132	—	—	—	197100	236300	90000

B

3/V 15M L3 — 406 — 100800 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)					Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
						B5									
1500	3/V 15M L3	386	3.9	62600	30	132	160	180	200	225	—	—	136900	164100	57300
	3/V 15M L3	446	3.4	65100	29	132	160	180	200	225	—	—	139700	167500	60100
	3/V 15M L3	498	3.0	82600	31	132	160	180	200	225	—	—	141900	170200	62300
	3/V 15M L3	560	2.7	81700	29	132	160	180	200	225	—	—	144300	173100	64800
	3/V 15M L3	665	2.3	85200	25	132	160	180	200	225	—	—	147900	177300	68600
	3/V 15M L3	840	1.8	80400	19.2	132	160	180	200	225	—	—	152900	183400	74200
	3/V 15M L3	997	1.5	88300	17.8	132	160	180	200	225	—	—	156700	187900	78500
	3/V 15M L3	1120	1.3	89200	17.1	132	160	180	200	225	—	—	159300	191100	81600
	3/V 15M L3	1329	1.1	90600	14.6	132	160	180	200	225	—	—	163300	195800	86400
	3/V 15M L3	1400	1.1	86900	13.6	132	160	180	200	225	—	—	164500	197300	88000
	3/V 15M L3	1662	0.90	91600	12.1	132	160	180	200	225	—	—	168600	202200	90000
	3/V 15M L3	1994	0.75	91600	10.5	132	160	180	200	225	—	—	173000	207500	90000
	3/V 15M L3	2318	0.65	79100	7.8	132	160	180	200	225	—	—	176800	212000	90000

3/V 15M L4 — 407 — 100800 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)				Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
						B5								
1500	3/V 15M L4	2780	0.54	100800	7.4	—	—	132	160 (*)	—	—	181400	217600	90000
	3/V 15M L4	3300	0.45	100800	6.3	—	—	132	160 (*)	—	—	185900	223000	90000
	3/V 15M L4	3489	0.43	91600	5.4	—	—	132	160 (*)	—	—	187400	224800	90000
	3/V 15M L4	4171	0.36	100800	5.2	100	112	132	—	—	—	192300	230600	90000
	3/V 15M L4	4950	0.30	100800	4.4	100	112	132	—	—	—	197000	236300	90000
	3/V 15M L4	5234	0.29	91600	3.8	100	112	132	—	—	—	198600	238200	90000



3/V 16M L3

418

134390 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)					Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
						B5									
1500	**3/V 16M L3**	**397**	3.8	99700	48	132	160	180	200	225	—	—	210300	235900	96300
	3/V 16M L3	**446**	3.4	93400	41	132	160	180	200	225	—	—	213800	239800	100100
	3/V 16M L3	**530**	2.8	110900	41	132	160	180	200	225	—	—	219100	245800	106000
	3/V 16M L3	**669**	2.2	84000	25	132	160	180	200	225	—	—	226500	254100	114600
	3/V 16M L3	**794**	1.9	99700	25	132	160	180	200	225	—	—	232200	260400	121400
	3/V 16M L3	**893**	1.7	100800	24	132	160	180	200	225	—	—	236000	264800	126200
	3/V 16M L3	**1059**	1.4	116400	23	132	160	180	200	225	—	—	241900	271300	133600
	3/V 16M L3	**1324**	1.1	112100	18.6	132	160	180	200	225	—	—	249700	280100	143900
	3/V 16M L3	**1589**	0.94	112100	15.5	132	160	180	200	225	—	—	256300	287500	150000

3/V 16M L4

419

134390 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)					Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
						B5									
1500	**3/V 16M L4**	**1785**	0.84	105900	12.2	—	—	132	160 (*)		—	—	260600	292400	150000
	3/V 16M L4	**1920**	0.78	113900	12.2	—	—	132	160 (*)		—	—	263300	295400	150000
	3/V 16M L4	**2343**	0.64	134400	11.8	—	—	132	160 (*)		—	—	270900	303900	150000
	3/V 16M L4	**2678**	0.56	111600	9.0	100	112	132	—		—	—	276200	309800	150000
	3/V 16M L4	**2880**	0.52	120000	9.0	100	112	132	—		—	—	279000	313000	150000
	3/V 16M L4	**3514**	0.43	134400	8.2	100	112	132	—		—	—	287100	322100	150000
	3/V 16M L4	**4171**	0.36	134400	6.9	100	112	132	—		—	—	294200	330000	150000
	3/V 16M L4	**4950**	0.30	118100	5.1	100	112	132	—		—	—	301500	338200	150000

3/V 17M L3

428

207490 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)					Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
						B5									
1500	**3/V 17M L3**	**405**	3.7	120100	55	132	160	180	200	225	—	—	328100	348500	96900
	3/V 17M L3	**425**	3.5	106700	48	132	160	180	200	225	—	—	330400	351000	98500
	3/V 17M L3	**512**	2.9	128400	48	132	160	180	200	225	—	—	339200	360400	104800
	3/V 17M L3	**567**	2.6	118700	41	132	160	180	200	225	—	—	344200	365700	108500
	3/V 17M L3	**608**	2.5	128800	40	132	160	180	200	225	—	—	347600	369300	111000
	3/V 17M L3	**683**	2.2	142900	41	132	160	180	200	225	—	—	353500	375500	115400
	3/V 17M L3	**810**	1.9	135200	32	132	160	180	200	225	—	—	362200	384800	122100
	3/V 17M L3	**851**	1.8	106700	25	132	160	180	200	225	—	—	364700	387500	124200
	3/V 17M L3	**1024**	1.5	128400	25	132	160	180	200	225	—	—	374500	397900	132100
	3/V 17M L3	**1134**	1.3	128000	24	132	160	180	200	225	—	—	380100	403800	136600
	3/V 17M L3	**1215**	1.2	144900	24	132	160	180	200	225	—	—	383800	407800	139800
	3/V 17M L3	**1365**	1.1	154100	24	132	160	180	200	225	—	—	390300	414600	145400



3/V 17M L4 — 429 — 207490 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC) B5					Rn$_2$ [N] MC/PC	MZ/PZ	HC	HZ	FZ
1500	3/V 17M L4	1780	0.84	184300	21	—	—	—	160	180 (*)	—	—	405300	430600	150000
	3/V 17M L4	2065	0.73	179800	17.0	—	—	—	160	180 (*)	—	—	414000	439800	150000
	3/V 17M L4	2485	0.60	125800	9.9	—	—	—	160	180 (*)	—	—	425100	451600	150000
	3/V 17M L4	2773	0.54	166400	13.2	—	—	132	160	—	—	—	431800	458800	150000
	3/V 17M L4	3168	0.47	190800	12.5	—	—	132	160	—	—	—	440100	467600	150000
	3/V 17M L4	3583	0.42	156000	8.8	—	—	—	160	180 (*)	—	—	442000	470000	150000
	3/V 17M L4	4129	0.36	179800	9.0	—	—	132	160	—	—	—	442000	470000	150000
	3/V 17M L4	4449	0.34	203000	10.3	100	112	132	—	—	—	—	442000	470000	150000
	3/V 17M L4	4970	0.30	125800	5.2	—	—	132	160	—	—	—	442000	470000	150000

B

3/V 18M L4 — 438 — 297550 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC) B5					Rn$_2$ [N] MC/PC	MZ/PZ	HC	HZ	FZ
1500	3/V 18M L4	765	2.0	185000	47	132	160	180	200	225	—	—	341800	385900	159800
	3/V 18M L4	982	1.5	237400	47	132	160	180	200	225	—	—	354200	399900	173600
	3/V 18M L4	1165	1.3	281800	47	132	160	180	200	225	—	—	363000	409800	183800
	3/V 18M L4	1232	1.2	289200	45	132	160	180	200	225	—	—	365900	413100	187300
	3/V 18M L4	1473	1.0	255400	34	132	160	180	200	225	—	—	375300	423800	198800
	3/V 18M L4	1748	0.86	297600	33	132	160	180	200	225	—	—	384600	434200	200000
	3/V 18M L4	1848	0.81	297600	31	132	160	180	200	225	—	—	387700	437700	200000
	3/V 18M L4	2295	0.65	212900	19.2	132	160	180	200	225	—	—	399900	451500	200000
	3/V 18M L4	2464	0.61	297600	24	132	160	180	200	225	—	—	403900	456100	200000
	3/V 18M L4	2945	0.51	273300	19.2	132	160	180	200	225	—	—	414400	467900	200000
	3/V 18M L4	3495	0.43	297600	17.7	132	160	180	200	225	—	—	424600	479400	200000
	3/V 18M L4	3696	0.41	297600	16.7	132	160	180	200	225	—	—	428000	483300	200000
	3/V 18M L4	4386	0.34	297600	14.1	132	160	180	200	225	—	—	438600	495300	200000
	3/V 18M L4	5099	0.29	264700	10.8	132	160	180	200	225	—	—	448200	506000	200000

3/V 19 L4 — 448 — 471190 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC) B5					Rn$_2$ [N] MC/PC	MZ/PZ	HC	HZ	FZ
1500	3/V 19 L4	2582	0.58	365200	29	132	160	180	200	225	—	—	494100	544000	200000
	3/V 19 L4	3231	0.46	356300	22	132	160	180	200	225	—	—	510200	561700	200000
	3/V 19 L4	4095	0.37	380000	19.2	132	160	180	200	225	—	—	527700	581100	200000
	3/V 19 L4	4457	0.34	336400	15.3	132	160	180	200	225	—	—	534200	588100	200000
	3/V 19 L4	5164	0.29	412400	17.6	132	160	180	200	225	—	—	545500	600600	200000



3/V 21 L4

458

655740 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)					Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
						B5									V
1500	**3/V 21 L4**	**1062**	1.4	443000	79	132	160	180	200	225	—	—	615600	732700	1081800
	3/V 21 L4	**1260**	1.2	425500	65	132	160	180	200	225	—	—	630800	750900	1138800
	3/V 21 L4	**1517**	0.99	512200	65	132	160	180	200	225	—	—	647800	771000	1200000
	3/V 21 L4	**1800**	0.83	536400	57	132	160	180	200	225	—	—	663800	790100	1200000
	3/V 21 L4	**1890**	0.79	460000	48	132	160	180	200	225	—	—	668500	795700	1200000
	3/V 21 L4	**2275**	0.66	553700	48	132	160	180	200	225	—	—	686400	817000	1200000
	3/V 21 L4	**2520**	0.60	511700	41	132	160	180	200	225	—	—	696500	829000	1200000
	3/V 21 L4	**2700**	0.56	536400	39	132	160	180	200	225	—	—	703400	837300	1200000
	3/V 21 L4	**3600**	0.42	536400	30	132	160	180	200	225	—	—	732900	872400	1200000
	3/V 21 L4	**3780**	0.40	460000	25	132	160	180	200	225	—	—	738000	878500	1200000
	3/V 21 L4	**4550**	0.33	553700	25	132	160	180	200	225	—	—	757800	902100	1200000
	3/V 21 L4	**5040**	0.30	552000	24	132	160	180	200	225	—	—	769000	915300	1200000

B

25.6 3/A - COMBINED UNITS RATING CHARTS

Reading the rating chart.



1	Reference torque
2	Gearbox drive speed
3	Frame size of combined planetary + bevel helical unit
4	Gear ratio
5	Gearbox output speed
6	Gearbox rated output torque based on: - service factor f_S=1 - 10000 h theoretical lifetime
7	Gearbox rated input power, based on: - service factor f_S=1 - 10000 h theoretical lifetime
8	Frame size of available IEC motor
9	Permitted overhung loading on output shaft, based on: - service factor f_S=1 - 10000 h theoretical lifetime - speed of output n_2 For forces not applied at shaft middlepoint, see diagrams provided in the specific gearbox overall dimensioning pages
10	Dimensions page

B



3/A 00 L2 — 267 — 1250 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)									Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
1500	**3/A 00 L2**	**19.1**	78	470	4.3	63	71	80	90	100	112	—	—	—	3270	3270	11600	13500	1870
	3/A 00 L2	**23.4**	64	580	4.3	63	71	80	90	100	112	—	—	—	3500	3500	12300	14300	2000
	3/A 00 L2	**31.7**	47	650	3.5	63	71	80	90	100	112	—	—	—	3870	3870	13500	15700	2210
	3/A 00 L2	**39.6**	38	550	2.4	63	71	80	90	100	112	—	—	—	4170	4170	14400	16800	2380
	3/A 00 L2	**41.5**	36	650	2.7	63	71	80	90	100	112	—	—	—	4240	4240	14600	17000	2420
	3/A 00 L2	**51.8**	28.9	550	1.8	63	71	80	90	100	112	—	—	—	4560	4560	15600	18200	2610
	3/A 00 L2	**61.2**	24.5	650	1.8	63	71	80	90	100	112	—	—	—	4820	4820	16400	19100	2750
	3/A 00 L2	**71.0**	21.1	650	1.6	63	71	80	90	100	112	—	—	—	5060	5060	17200	20000	2890
	3/A 00 L2	**80.2**	18.7	650	1.4	63	71	80	90	100	112	—	—	—	5280	5280	17800	20700	3010
	3/A 00 L2	**88.6**	16.9	550	1.1	63	71	80	90	100	112	—	—	—	5450	5450	18400	21300	3120
	3/A 00 L2	**100**	15.0	550	0.95	63	71	80	90	100	112	—	—	—	5680	5680	19000	22100	3240
	3/A 00 L2	**107**	14.0	650	1.0	63	71	80	90	100	112	—	—	—	5810	5810	19400	22600	3320
	3/A 00 L2	**134**	11.2	550	0.71	63	71	80	90	100	112	—	—	—	6260	6260	20800	24200	3580
	3/A 00 L2	**171**	8.8	550	0.55	63	71	80	90	100	112	—	—	—	6500	6500	21500	25000	3880
	3/A 00 L2	**203**	7.4	650	0.55	63	71	80	90	100	112	—	—	—	6500	6500	21500	25000	4100
	3/A 00 L2	**219**	6.9	620	0.49	63	71	80	90	100	112	—	—	—	6500	6500	21500	25000	4210
	3/A 00 L2	**253**	5.9	550	0.37	63	71	80	90	100	112	—	—	—	6500	6500	21500	25000	4420
	3/A 00 L2	**296**	5.1	650	0.38	63	71	80	90	100	112	—	—	—	6500	6500	21500	25000	4660
	3/A 00 L2	**319**	4.7	440	0.24	63	71	—	—	—	—	—	—	—	6560	6560	21700	25200	4770
	3/A 00 L2	**369**	4.1	560	0.26	63	71	80	90	100	112	—	—	—	6700	6700	22100	25800	5010
	3/A 00 L2	**391**	3.8	540	0.24	63	71	—	—	—	—	—	—	—	6750	6750	22300	26000	5110
	3/A 00 L2	**441**	3.4	690	0.27	63	71	—	—	—	—	—	—	—	6870	6870	22700	26400	5320
	3/A 00 L2	**550**	2.7	590	0.19	63	71	—	—	—	—	—	—	—	7090	7090	23400	27300	5730
	3/A 00 L2	**660**	2.3	610	0.16	63	71	—	—	—	—	—	—	—	7270	7270	24100	28000	6080

B

3/A 01 L2 — 277 — 2460 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)									Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
1500	**3/A 01 L2**	**18.8**	80	710	6.5	—	—	80	90	100	112	—	—	—	3250	3250	11500	12600	1860
	3/A 01 L2	**23.0**	65	870	6.5	—	—	80	90	100	112	—	—	—	3480	3480	12300	13400	1990
	3/A 01 L2	**31.2**	48	1180	6.5	—	—	80	90	100	112	—	—	—	3850	3850	13400	14700	2200
	3/A 01 L2	**35.8**	42	760	3.7	—	—	80	90	100	112	—	—	—	4030	4030	14000	15300	2300
	3/A 01 L2	**40.1**	37	870	3.7	63	71	80	90	100	112	—	—	—	4190	4190	14500	15800	2390
	3/A 01 L2	**43.9**	34	930	3.7	—	—	80	90	100	112	—	—	—	4320	4320	14900	16300	2470
	3/A 01 L2	**49.1**	31	830	2.9	63	71	80	90	100	112	—	—	—	4480	4480	15400	16800	2560
	3/A 01 L2	**54.2**	27.7	1180	3.7	63	71	80	90	100	112	—	—	—	4630	4630	15800	17300	2650
	3/A 01 L2	**59.4**	25.2	1260	3.7	—	—	80	90	100	112	—	—	—	4770	4770	16300	17800	2730
	3/A 01 L2	**74.2**	20.2	1150	2.7	—	—	80	90	100	112	—	—	—	5140	5140	17400	19000	2940
	3/A 01 L2	**81.3**	18.4	1300	2.8	63	71	80	90	100	112	—	—	—	5300	5300	17900	19600	3030
	3/A 01 L2	**102**	14.8	1150	2.0	63	71	80	90	100	112	—	—	—	5710	5710	19100	20900	3260
	3/A 01 L2	**133**	11.3	1300	1.7	63	71	80	90	100	112	—	—	—	6250	6250	20800	22700	3570
	3/A 01 L2	**166**	9.0	1150	1.2	63	71	80	90	100	112	—	—	—	6500	6500	21500	23500	3840
	3/A 01 L2	**184**	8.1	1030	0.97	63	71	80	90	100	112	—	—	—	6500	6500	21500	23500	3980
	3/A 01 L2	**204**	7.3	1300	1.1	63	71	80	90	100	112	—	—	—	6500	6500	21500	23500	4120
	3/A 01 L2	**220**	6.8	830	0.65	63	71	80	90	100	112	—	—	—	6500	6500	21500	23500	4220
	3/A 01 L2	**255**	5.9	1150	0.78	63	71	80	90	100	112	—	—	—	6500	6500	21500	23500	4430
	3/A 01 L2	**269**	5.6	1010	0.65	63	71	80	90	100	112	—	—	—	6500	6500	21500	23500	4510
	3/A 01 L2	**311**	4.8	1150	0.64	63	71	80	90	100	112	—	—	—	6530	6530	21600	23600	4740
	3/A 01 L2	**364**	4.1	1340	0.64	63	71	80	90	100	112	—	—	—	6680	6680	22100	24200	4990
	3/A 01 L2	**393**	3.8	830	0.36	63	71	—	—	—	—	—	—	—	6760	6760	22300	24400	5120
	3/A 01 L2	**454**	3.3	1150	0.44	63	71	80	90	100	112	—	—	—	6900	6900	22800	24900	5370
	3/A 01 L2	**533**	2.8	1120	0.36	63	71	—	—	—	—	—	—	—	7060	7060	23300	25500	5660
	3/A 01 L2	**665**	2.3	1150	0.30	63	71	—	—	—	—	—	—	—	7280	7280	24100	26300	6100



3/A 03 L2

287

2970 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)									Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
1500	**3/A 03 L2**	**19.4**	77	1050	9.3	—	—	80	90	100	112	—	—	—	10600	12100	21900	26000	5640
	3/A 03 L2	**23.0**	65	1240	9.3	—	—	80	90	100	112	—	—	—	11200	12800	23100	27300	5960
	3/A 03 L2	**28.8**	52	1550	9.3	—	—	80	90	100	112	—	—	—	12100	13800	24700	29300	6430
	3/A 03 L2	**33.5**	45	1800	9.3	—	—	80	90	100	112	—	—	—	12700	14600	25800	30600	6760
	3/A 03 L2	**40.5**	37	1650	7.0	—	—	80	90	100	112	—	—	—	13600	15500	27300	32400	7200
	3/A 03 L2	**43.4**	35	1800	7.2	—	—	80	90	100	112	—	—	—	13900	15900	27900	33100	7370
	3/A 03 L2	**52.5**	28.6	1650	5.4	—	—	80	90	100	112	—	—	—	14800	16900	29600	35000	7850
	3/A 03 L2	**52.5**	28.6	1650	5.4	—	—	80	90	100	112	—	—	—	14800	16900	29600	35000	7850
	3/A 03 L2	**62.9**	23.8	1550	4.2	63	71	80	90	100	112	—	—	—	15700	18000	31200	37000	8340
	3/A 03 L2	**73.2**	20.5	1800	4.2	63	71	80	90	100	112	—	—	—	16500	18900	32700	38700	8770
	3/A 03 L2	**88.5**	16.9	1650	3.2	63	71	80	90	100	112	—	—	—	17600	20100	34600	41000	9340
	3/A 03 L2	**96.9**	15.5	1690	3.0	63	71	80	90	100	112	—	—	—	18200	20700	35500	42100	9630
	3/A 03 L2	**182**	8.3	1830	1.7	63	71	80	90	100	112	—	—	—	21000	24000	40500	48000	11900
	3/A 03 L2	**220**	6.8	1650	1.3	63	71	80	90	100	112	—	—	—	21000	24000	40500	48000	12700
	3/A 03 L2	**269**	5.6	1840	1.2	63	71	80	90	100	112	—	—	—	21000	24000	40500	48000	13500
	3/A 03 L2	**269**	5.6	1840	1.2	63	71	80	90	100	112	—	—	—	21000	24000	40500	48000	13500
	3/A 03 L2	**326**	4.6	1660	0.88	63	71	80	90	100	112	—	—	—	21200	24300	41000	48600	14400
	3/A 03 L2	**352**	4.3	2020	0.99	63	71	80	90	100	112	—	—	—	21500	24600	41400	49100	14800
	3/A 03 L2	**409**	3.7	1940	0.82	63	71	80	90	100	112	—	—	—	22000	25100	42300	50200	15600
	3/A 03 L2	**495**	3.0	1720	0.60	63	71	80	90	100	112	—	—	—	22600	25800	43500	51600	16600
	3/A 03 L2	**574**	2.6	1740	0.52	63	71	80	90	100	112	—	—	—	23000	26300	44400	52700	17400
	3/A 03 L2	**605**	2.5	1800	0.51	63	71	80	90	100	112	—	—	—	23200	26500	44800	53100	17700
	3/A 03 L2	**731**	2.1	1800	0.42	63	71	80	90	100	112	—	—	—	23900	27300	46000	54500	18900

3/A 04 L2

299

3960 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)									Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
1500	**3/A 04 L2**	**18.7**	80	1920	17.7	—	—	80	90	100	112	132	—	—	10500	12000	21700	25700	5570
	3/A 04 L2	**22.1**	68	2270	17.7	—	—	80	90	100	112	132	—	—	11100	12700	22800	27000	5880
	3/A 04 L2	**25.6**	59	1920	12.9	—	—	80	90	100	112	132	—	—	11600	13300	23800	28200	6180
	3/A 04 L2	**27.7**	54	2830	17.6	—	—	80	90	100	112	132	—	—	12000	13700	24400	28900	6350
	3/A 04 L2	**30.2**	50	2270	12.9	—	—	80	90	100	112	132	—	—	12300	14100	25000	29700	6530
	3/A 04 L2	**35.3**	43	2270	11.1	—	—	80	90	100	112	132	—	—	13000	14800	26200	31100	6880
	3/A 04 L2	**39.1**	38	2270	10.0	—	—	80	90	100	112	132	—	—	13400	15300	27100	32100	7120
	3/A 04 L2	**44.3**	34	2850	11.1	—	—	80	90	100	112	132	—	—	14000	16000	28100	33300	7420
	3/A 04 L2	**49.7**	30	2270	7.9	63	71	80	90	100	112	132	—	—	14500	16600	29100	34500	7710
	3/A 04 L2	**54.5**	27.5	2390	7.5	—	—	80	90	100	112	132	—	—	15000	17100	29900	35400	7950
	3/A 04 L2	**62.4**	24.0	2850	7.9	63	71	80	90	100	112	132	—	—	15700	17900	31100	36900	8320
	3/A 04 L2	**68.4**	21.9	2510	6.3	—	—	80	90	100	112	132	—	—	16200	18500	32000	37900	8580
	3/A 04 L2	**81.7**	18.4	2370	5.0	63	71	80	90	100	112	132	—	—	17200	19600	33800	40000	9100
	3/A 04 L2	**90.7**	16.5	2390	4.5	—	—	80	90	100	112	132	—	—	17800	20300	34800	41300	9420
	3/A 04 L2	**102**	14.7	2550	4.3	63	71	80	90	100	112	132	—	—	18500	21100	36100	42700	9790
	3/A 04 L2	**117**	12.8	2390	3.5	—	—	80	90	100	112	132	—	—	19300	22100	37600	44500	10300
	3/A 04 L2	**129**	11.6	2720	3.6	63	71	80	90	100	112	132	—	—	20000	22800	38700	45900	10600
	3/A 04 L2	**149**	10.1	2390	2.8	63	71	80	90	100	112	132	—	—	21000	24000	40400	47900	11100
	3/A 04 L2	**162**	9.2	2900	3.1	63	71	80	90	100	112	132	—	—	21000	24000	40500	48000	11400
	3/A 04 L2	**174**	8.6	2970	2.9	63	71	80	90	100	112	—	—	—	21000	24000	40500	48000	11700
	3/A 04 L2	**205**	7.3	3500	2.9	63	71	80	90	100	112	—	—	—	21000	24000	40500	48000	12400
	3/A 04 L2	**226**	6.6	3500	2.7	63	71	80	90	100	112	—	—	—	21000	24000	40500	48000	12800
	3/A 04 L2	**250**	6.0	3500	2.4	63	71	80	90	100	112	—	—	—	21000	24000	40500	48000	13200
	3/A 04 L2	**283**	5.3	2850	1.7	63	71	80	90	100	112	—	—	—	21000	24000	40500	48000	13800
	3/A 04 L2	**317**	4.7	2400	1.3	63	71	80	90	100	112	—	—	—	21200	24200	40800	48400	14300
	3/A 04 L2	**349**	4.3	2430	1.2	63	71	80	90	100	112	—	—	—	21500	24500	41400	49000	14800
	3/A 04 L2	**386**	3.9	2450	1.1	63	71	80	90	100	112	—	—	—	21800	24900	42000	49800	15300
	3/A 04 L2	**469**	3.2	2500	0.92	63	71	80	90	100	112	—	—	—	22400	25600	43200	51200	16300
	3/A 04 L2	**520**	2.9	2520	0.84	63	71	80	90	100	112	—	—	—	22700	26000	43800	51900	16900



3/A 05 L2

311

5800 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)									Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
1500	**3/A 05L2**	**18.7**	80	1920	17.7	—	—	80	90	100	112	132	—	—	10500	12000	21700	25700	5570
	3/A 05L2	**22.1**	68	2270	17.7	—	—	80	90	100	112	132	—	—	11100	12700	22800	27000	5880
	3/A 05L2	**27.7**	54	2850	17.7	—	—	80	90	100	112	132	—	—	12000	13700	24400	28900	6350
	3/A 05L2	**32.2**	47	3310	17.7	—	—	80	90	100	112	132	—	—	12600	14400	25500	30300	6670
	3/A 05L2	**39.0**	38	3020	13.3	—	—	80	90	100	112	132	—	—	13400	15300	27000	32000	7110
	3/A 05L2	**44.0**	34	3310	12.9	—	—	80	90	100	112	132	—	—	14000	15900	28000	33200	7400
	3/A 05L2	**53.3**	28.2	3040	9.8	—	—	80	90	100	112	132	—	—	14900	17000	29700	35200	7890
	3/A 05L2	**57.0**	26.3	3310	10.0	—	—	80	90	100	112	132	—	—	15200	17400	30300	35900	8070
	3/A 05L2	**62.6**	24.0	3220	8.9	—	—	80	90	100	112	132	—	—	15700	17900	31200	36900	8330
	3/A 05L2	**72.5**	20.7	3310	7.9	63	71	80	90	100	112	132	—	—	16500	18800	32600	38600	8740
	3/A 05L2	**75.8**	19.8	3060	7.0	—	—	80	90	100	112	132	—	—	16700	19100	33000	39100	8870
	3/A 05L2	**85.6**	17.5	3520	7.1	—	—	80	90	100	112	132	—	—	17400	19900	34200	40600	9240
	3/A 05L2	**104**	14.5	3080	5.1	—	—	80	90	100	112	132	—	—	18600	21200	36200	42900	9840
	3/A 05L2	**121**	12.4	3520	5.0	63	71	80	90	100	112	132	—	—	19600	22300	38000	45000	10400
	3/A 05L2	**141**	10.7	3600	4.4	63	71	80	90	100	112	132	—	—	20600	23500	39700	47100	10900
	3/A 05L2	**162**	9.2	2900	3.1	63	71	80	90	100	112	132	—	—	21000	24000	40500	48000	11400
	3/A 05L2	**175**	8.5	3600	3.5	63	71	80	90	100	112	132	—	—	21000	24000	40500	48000	11700
	3/A 05L2	**212**	7.1	3100	2.5	63	71	80	90	100	112	132	—	—	21000	24000	40500	48000	12500
	3/A 05L2	**212**	7.1	3100	2.5	63	71	80	90	100	112	132	—	—	21000	24000	40500	48000	12500
	3/A 05L2	**241**	6.2	4290	3.1	63	71	80	90	100	112	132	—	—	21000	24000	40500	48000	13000
	3/A 05L2	**280**	5.4	3600	2.2	63	71	80	90	100	112	132	—	—	21000	24000	40500	48000	13700
	3/A 05L2	**329**	4.6	3650	1.9	63	71	80	90	100	112	—	—	—	21300	24300	41000	48600	14500
	3/A 05L2	**398**	3.8	3180	1.4	63	71	80	90	100	112	—	—	—	21900	25000	42200	50000	15400
	3/A 05L2	**422**	3.6	4400	1.8	63	71	80	90	100	112	—	—	—	22100	25200	42500	50400	15700
	3/A 05L2	**491**	3.1	3880	1.4	63	71	80	90	100	112	—	—	—	22500	25800	43500	51500	16500
	3/A 05L2	**594**	2.5	3300	0.96	63	71	80	90	100	112	—	—	—	23200	26500	44700	52900	17600

3/A 06 L2

323

10840 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)									Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
1500	**3/A 06L2**	**27.7**	54	3320	21	—	—	80	90	100	112	132	160	180	14200	16200	34300	39600	9250
	3/A 06L2	**32.7**	46	3920	21	—	—	80	90	100	112	132	160	180	15000	17200	36100	41700	9780
	3/A 06L2	**34.9**	43	3490	17.2	—	—	80	90	100	112	132	160	180	15400	17500	36800	42500	9990
	3/A 06L2	**41.1**	37	4910	21	—	—	80	90	100	112	132	160	180	16200	18500	38600	44600	10500
	3/A 06L2	**47.2**	32	3840	14.0	—	—	80	90	100	112	132	160	180	17000	19400	40300	46500	11000
	3/A 06L2	**51.7**	29.0	5170	17.2	—	—	80	90	100	112	132	160	180	17500	20000	41400	47800	11400
	3/A 06L2	**55.7**	26.9	4530	14.0	—	—	80	90	100	112	132	160	180	18000	20500	42300	48900	11700
	3/A 06L2	**60.1**	24.9	6010	17.2	—	—	80	90	100	112	132	160	180	18400	21000	43300	50000	12000
	3/A 06L2	**69.9**	21.5	5690	14.0	—	—	80	90	100	112	132	160	180	19400	22100	45300	52300	12600
	3/A 06L2	**81.2**	18.5	6480	13.8	—	—	80	90	100	112	132	160	180	20400	23200	47400	54700	13200
	3/A 06L2	**88.5**	16.9	6210	12.1	—	—	80	90	100	112	132	160	180	21000	23900	48700	56200	13600
	3/A 06L2	**98.3**	15.3	5380	9.4	—	—	80	90	100	112	132	160	180	21700	24800	50200	58000	14100
	3/A 06L2	**112**	13.4	6180	9.8	—	—	80	90	100	112	132	160	180	22700	25900	52200	60300	14700
	3/A 06L2	**125**	12.0	5440	7.5	—	—	80	90	100	112	132	160	180	23500	26800	53900	62200	15300
	3/A 06L2	**141**	10.7	7760	9.8	—	—	80	90	100	112	132	160	180	24500	27900	55900	64600	15900
	3/A 06L2	**164**	9.2	6500	7.1	—	—	80	90	100	112	132	160	180	25000	28500	57000	65800	16700
	3/A 06L2	**190**	7.9	7760	7.3	—	—	80	90	100	112	132	160	180	25000	28500	57000	65800	17600
	3/A 06L2	**198**	7.6	5500	4.9	—	—	80	90	100	112	132	160	180	25000	28500	57000	65800	17800
	3/A 06L2	**221**	6.8	6520	5.3	—	—	80	90	100	112	132	160	180	25000	28500	57000	65800	18500
	3/A 06L2	**267**	5.6	5500	3.7	—	—	80	90	100	112	132	160	180	25000	28500	57000	65800	19700
	3/A 06L2	**276**	5.4	7760	5.0	63	71	80	90	100	112	132	160	180	25000	28500	57000	65800	19900
	3/A 06L2	**321**	4.7	6610	3.7	63	71	80	90	100	112	132	160	180	25200	28800	57500	66400	20900
	3/A 06L2	**388**	3.9	5640	2.6	63	71	80	90	100	112	132	160	180	25900	29600	59100	68300	22300
	3/A 06L2	**380**	3.9	6180	2.9	63	71	80	90	100	112	132	160	180	25900	29500	59000	68100	22200
	3/A 06L2	**435**	3.5	7760	3.2	63	71	80	90	100	112	132	160	180	26400	30100	60100	69400	23200
	3/A 06L2	**505**	3.0	7150	2.5	63	71	80	90	100	112	132	160	180	26900	30700	61400	70900	24400
	3/A 06L2	**555**	2.7	7270	2.3	63	71	80	90	100	112	132	160	180	27300	31100	62200	71800	25100
	3/A 06L2	**611**	2.5	5920	1.7	63	71	80	90	100	112	132	160	180	27700	31600	63100	72800	25900
	3/A 06L2	**671**	2.2	6020	1.6	63	71	80	90	100	112	132	160	180	28000	32000	64000	73800	26800



3/A 07 L2

335

15680 Nm

n_1 min^{-1}		i	n_2 min^{-1}	M_{n2} Nm	P_{n1} kW	P (IEC)									Rn_2 [N] MC/PC	MZ/PZ	HC	HZ	FZ
1500	**3/A 07L2**	**27.1**	55	6650	42	—	—	—	—	—	—	132	160	180	17000	21200	40400	53100	11800
	3/A 07L2	**32.3**	46	7940	42	—	—	—	—	—	—	132	160	180	18000	22500	42600	56000	12500
	3/A 07L2	**41.5**	36	9620	40	—	—	—	—	—	—	132	160	180	19500	24400	45900	60400	13600
	3/A 07L2	**49.2**	30	8380	29	—	—	—	—	—	—	132	160	180	20700	25900	48300	63600	14400
	3/A 07L2	**57.3**	26.2	6650	20	—	—	80	90	100	112	132	160	180	21800	27200	50600	66500	15200
	3/A 07L2	**68.3**	22.0	7940	20	—	—	80	90	100	112	132	160	180	23100	28900	53300	70100	16100
	3/A 07L2	**87.7**	17.1	10200	20	—	—	80	90	100	112	132	160	180	25100	31400	57500	75600	17500
	3/A 07L2	**109**	13.8	8860	14.5	—	—	80	90	100	112	132	160	180	26900	33700	61300	80600	18800
	3/A 07L2	**130**	11.6	11100	15.2	—	—	80	90	100	112	132	160	180	28600	35700	64600	85000	19900
	3/A 07L2	**140**	10.7	11100	14.1	—	—	80	90	100	112	132	160	180	29300	36700	66200	87000	20400
	3/A 07L2	**155**	9.7	9000	10.3	—	—	80	90	100	112	132	160	180	30000	37500	67500	88800	21100
	3/A 07L2	**180**	8.3	10900	10.8	—	—	80	90	100	112	132	160	180	30000	37500	67500	88800	22200
	3/A 07L2	**198**	7.6	8700	7.8	—	—	80	90	100	112	132	160	180	30000	37500	67500	88800	22900
	3/A 07L2	**223**	6.7	9000	7.2	63	71	80	90	100	112	132	160	180	30000	37500	67500	88800	23800
	3/A 07L2	**241**	6.2	9000	6.6	63	71	80	90	100	112	132	160	180	30000	37500	67500	88800	24500
	3/A 07L2	**282**	5.3	8700	5.5	—	—	80	90	100	112	132	160	180	30000	37500	67500	88800	25800
	3/A 07L2	**341**	4.4	11500	6.0	63	71	80	90	100	112	132	160	180	30600	38200	68800	90400	27500
	3/A 07L2	**405**	3.7	9080	4.0	63	71	80	90	100	112	132	160	180	31300	39100	70500	92700	29100
	3/A 07L2	**439**	3.4	9180	3.7	63	71	80	90	100	112	132	160	180	31700	39600	71300	93800	29900

B



B

25.7 RATING CHARTS FOR INLINE UNITS 300M L

Reading the rating chart.



	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
L2	14.2	48640	48640	48640	48640	35280	28650	150	*	1500	2000	3200	6L	105000
	16.9	60940	57660	55630	50400	34420	27960	150	*	1500	2000	3200	6L	105000
	18.5	57130	48690	43150	41430	41090	33380	150	*	1500	2000	3200	6L	105000
	21.8	60940	57660	55630	50400	33620	27300	150	39	1500	2000	3200	6L	105000

2 3 4 5 6 7 8 9 10 11

* BONFIGLIOLI TECHNICAL SERVICE

Rated hydraulic brake torque lower than applicable torque

1	Reference torque
2	Number of reduction stages (in-line gear unit)
3	Gear ratio
4	Gearbox rated output torque based on: - service factor f_S=1 - $n_2 \cdot h$ indicated
5	Maximum power transmitted to input shaft
6	Gearbox thermal capacity
7	Input angular speed for continuous duty
8	Maximum input angular speed for intermittent duty 20% based 60 min running
9	Rated brake torque (Hydraulic brake)
10	Negative multidisc hydraulic brake
11	Maximum output torque at gearbox
12	Page where dimensions can be sorted from

C



300 L

262

1250 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
L1	3.48	760	730	730	730	730	730	20	*	2000	4000	260	4F	2000
	4.26	1250	1070	950	860	840	720	20	*	2000	4000	330	4H	2400
	5.77	860	730	650	650	650	630	20	*	2000	4000	260	4F	2400
	7.20	700	600	550	550	550	510	16.5	*	2000	4000	160	4D	2400
	9.00	460	390	370	370	370	370	8.9	*	2000	4000	160	4D	2400
L2	12.1	760	730	730	730	730	730	11.9	7.6	2000	4000	100	4B	2000
	14.8	1250	1070	950	860	840	720	12.6	7.7	2000	4000	100	4B	2000
	18.2	1250	1070	950	860	840	720	10.4	8.4	2000	4000	100	4B	2400
	20.1	860	730	650	650	650	630	7.2	6.6	2000	4000	100	4B	2000
	24.6	1250	1070	950	860	840	720	7.8	7.7	2000	4000	100	4B	2400
	30.7	1250	1070	950	860	840	720	6.4	7.0	2000	4000	50	4A	2400
	33.3	860	730	650	650	650	630	4.3	6.6	2000	4000	50	4A	2400
	38.4	1250	1070	950	860	840	720	5.2	6.8	2000	4000	50	4A	2400
	41.5	860	730	650	650	650	630	3.5	6.1	2000	4000	50	4A	2400
	51.9	860	730	650	650	650	630	2.9	5.9	2000	4000	50	4A	2400
	64.8	700	600	550	550	550	510	2.0	5.2	2000	4000	50	4A	2400
L3	51.6	1250	1070	950	860	840	720	4.2	5.6	2000	4000	50	4A	2000
	63.2	1250	1070	950	860	840	720	3.5	5.9	2000	4000	50	4A	2400
	69.9	860	730	650	650	650	630	2.4	4.9	2000	4000	50	4A	2000
	77.5	1250	1070	950	860	840	720	3.0	5.9	2000	4000	50	4A	2400
	85.6	1250	1070	950	860	840	720	2.7	5.7	2000	4000	50	4A	2400
	105	1250	1070	950	860	840	720	2.2	5.6	2000	4000	50	4A	2400
	116	860	730	650	650	650	630	1.6	5.0	2000	4000	50	4A	2400
	131	1250	1070	950	860	840	720	1.8	5.3	2000	4000	50	4A	2400
	142	1250	1070	950	860	840	720	1.6	5.1	2000	4000	50	4A	2400
	177	1250	1070	950	860	840	720	1.3	4.8	2000	4000	50	4A	2400
	192	860	730	650	650	650	630	1.0	4.6	2000	4000	50	4A	2400
	221	1250	1070	950	860	840	720	1.0	4.4	2000	4000	50	4A	2400
	240	860	730	650	650	650	630	0.82	4.4	2000	4000	50	4A	2400
	299	860	730	650	650	650	630	0.66	4.1	2000	4000	50	4A	2400
	374	860	730	650	650	650	630	0.53	4.0	2000	4000	50	4A	2400
L4	330	1250	1070	950	860	840	720	0.72	4.2	2000	4000	50	4A	2400
	403	860	730	650	650	650	630	0.50	3.8	2000	4000	50	4A	2400
	447	1250	1070	950	860	840	720	0.53	4.1	2000	4000	50	4A	2400
	494	1250	1070	950	860	840	720	0.48	3.8	2000	4000	50	4A	2400
	558	1250	1070	950	860	840	720	0.42	3.9	2000	4000	50	4A	2400
	616	1250	1070	950	860	840	720	0.38	3.6	2000	4000	50	4A	2400
	755	1250	1070	950	860	840	720	0.31	3.6	2000	4000	50	4A	2400
	819	1250	1070	950	860	840	720	0.29	3.5	2000	4000	50	4A	2400
	942	1250	1070	950	860	840	720	0.25	3.4	2000	4000	50	4A	2400
	1022	1250	1070	950	860	840	720	0.23	3.4	2000	4000	50	4A	2400
	1108	860	730	650	650	650	630	0.18	3.3	2000	4000	50	4A	2400
	1275	1250	1070	950	860	840	720	0.19	3.2	2000	4000	50	4A	2400
	1383	860	730	650	650	650	630	0.15	3.2	2000	4000	50	4A	2400
	1591	1250	1070	950	860	840	720	0.15	3.1	2000	4000	50	4A	2400
	1725	860	730	650	650	650	630	0.12	3.1	2000	4000	50	4A	2400
	2153	860	730	650	650	650	630	0.09	3.0	2000	4000	50	4A	2400
	2692	1000	1000	890	850	760	630	0.09	2.9	2000	4000	50	4A	2400

301 L

272

2460 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
L1	3.48	1490	1430	1430	1430	1430	1300	30	*	2000	4000	440	4L	3400
	4.26	2460	2140	1890	1730	1580	1280	30	*	2000	4000	440	4L	3400
	5.77	1720	1460	1300	1300	1300	1240	30	*	2000	4000	400	4K	3400
	7.20	1150	1150	1150	1150	1150	940	30	*	2000	4000	260	4F	3400



301 L

272

2460 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
L1	9.00	920	780	730	730	730	730	15.8	*	2000	4000	260	4F	3400
L2	12.1	1490	1430	1430	1430	1430	1300	23.9	9.0	2000	4000	160	4D	3400
	14.8	2460	2140	1890	1730	1580	1280	25.0	9.4	2000	4000	160	4D	3400
	18.2	2460	2140	1890	1730	1580	1280	20.7	10.2	2000	4000	160	4D	3400
	20.1	1720	1460	1300	1300	1300	1240	14.4	8.1	2000	4000	160	4D	3400
	24.6	2460	2140	1890	1730	1580	1280	15.6	9.2	2000	4000	160	4D	3400
	30.7	2000	2000	1830	1730	1580	1280	12.6	8.3	2000	4000	100	4B	3400
	33.3	1720	1460	1300	1300	1300	1240	8.7	7.9	2000	4000	100	4B	3400
	38.4	1600	1570	1570	1570	1530	1280	10.1	8.0	2000	4000	100	4B	3400
	41.5	1720	1460	1300	1300	1300	1240	7.0	7.3	2000	4000	100	4B	3400
	51.9	1720	1460	1300	1300	1300	1240	5.9	7.0	2000	4000	50	4A	3400
	64.8	1150	1150	1150	1150	1150	940	4.0	6.3	2000	4000	50	4A	3400
L3	51.6	2460	2140	1890	1730	1580	1280	8.3	5.8	2000	4000	50	4A	3400
	63.2	2460	2140	1890	1730	1580	1280	7.0	6.2	2000	4000	50	4A	3400
	69.9	1720	1460	1300	1300	1300	1240	4.7	5.2	2000	4000	50	4A	3400
	77.5	2460	2140	1890	1730	1580	1280	5.9	6.2	2000	4000	50	4A	3400
	85.6	2460	2140	1890	1730	1580	1280	5.4	5.9	2000	4000	50	4A	3400
	105	2460	2140	1890	1730	1580	1280	4.4	5.9	2000	4000	50	4A	3400
	116	1720	1460	1300	1300	1300	1240	3.1	5.3	2000	4000	50	4A	3400
	131	2460	2140	1890	1730	1580	1280	3.5	5.5	2000	4000	50	4A	3400
	142	2460	2140	1890	1730	1580	1280	3.2	5.3	2000	4000	50	4A	3400
	177	2460	2140	1890	1730	1580	1280	2.6	5.0	2000	4000	50	4A	3400
	192	1720	1460	1300	1300	1300	1240	2.0	4.8	2000	4000	50	4A	3400
	221	2000	2000	1830	1730	1580	1280	2.1	4.6	2000	4000	50	4A	3400
	240	1720	1460	1300	1300	1300	1240	1.6	4.5	2000	4000	50	4A	3400
	299	1720	1460	1300	1300	1300	1240	1.3	4.2	2000	4000	50	4A	3400
	374	1720	1460	1300	1300	1300	1240	1.0	4.1	2000	4000	50	4A	3400
L4	330	2460	2140	1890	1730	1580	1280	1.4	4.1	2000	4000	50	4A	3400
	403	1720	1460	1300	1300	1300	1240	1.00	3.7	2000	4000	50	4A	3400
	447	2460	2140	1890	1730	1580	1280	1.06	4.0	2000	4000	50	4A	3400
	494	2460	2140	1890	1730	1580	1280	0.96	3.7	2000	4000	50	4A	3400
	558	2460	2140	1890	1730	1580	1280	0.85	3.8	2000	4000	50	4A	3400
	616	2460	2140	1890	1730	1580	1280	0.77	3.5	2000	4000	50	4A	3400
	755	2460	2140	1890	1730	1580	1280	0.63	3.4	2000	4000	50	4A	3400
	819	2460	2140	1890	1730	1580	1280	0.58	3.4	2000	4000	50	4A	3400
	942	2460	2140	1890	1730	1580	1280	0.50	3.3	2000	4000	50	4A	3400
	1022	2460	2140	1890	1730	1580	1280	0.46	3.2	2000	4000	50	4A	3400
	1108	1720	1460	1300	1300	1300	1240	0.36	3.2	2000	4000	50	4A	3400
	1275	2460	2140	1890	1730	1580	1280	0.37	3.1	2000	4000	50	4A	3400
	1383	1720	1460	1300	1300	1300	1240	0.29	3.1	2000	4000	50	4A	3400
	1591	2000	2000	1830	1730	1580	1280	0.30	3.0	2000	4000	50	4A	3400
	1725	1720	1460	1300	1300	1300	1240	0.23	2.9	2000	4000	50	4A	3400
	2153	1720	1460	1300	1300	1300	1240	0.19	2.9	2000	4000	50	4A	3400
	2692	1720	1460	1300	1300	1300	1240	0.15	2.8	2000	4000	50	4A	3400

303 L

282

2970 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
L1	3.60	2410	2310	2310	2310	2310	2120	40	*	1800	3800	800	5G	5200
	4.25	2970	2810	2810	2650	2570	2090	40	*	1800	3800	800	5G	5200
	5.33	2850	2520	2230	2200	2140	2030	40	*	1800	3800	630	5E	5200
	6.20	2440	2080	1840	1820	1820	1820	40	*	1800	3800	500	5C	5200
	7.50	2000	1750	1650	1650	1650	1500	40	*	1800	3800	400	5B	5200
	9.67	1050	900	860	860	860	860	17.3	*	1800	3800	400	5B	5200
L2	12.5	2410	2310	2310	2310	2130	1730	20	12.7	2000	4000	260	4F	5200

C



303 L

282

2970 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
L2	15.3	2410	2310	2310	2310	2100	1700	20	13.5	2000	4000	260	4F	5200
	18.1	2970	2810	2810	2650	2350	1910	20	13.7	2000	4000	260	4F	5200
	20.8	2410	2210	2210	2210	2030	1650	20	12.0	2000	4000	160	4D	5200
	22.7	2850	2520	2230	2200	2140	2030	20	12.5	2000	4000	160	4D	5200
	24.5	2770	2700	2650	2620	2280	1850	20	12.1	2000	4000	160	4D	5200
	26.4	2440	2080	1840	1820	1820	1820	15.2	11.2	2000	4000	160	4D	5200
	30.8	2850	2520	2230	2200	2140	2030	15.9	11.2	2000	4000	160	4D	5200
	35.8	2440	2080	1840	1820	1820	1820	11.2	10.1	2000	4000	100	4B	5200
	38.4	2850	2450	2230	2200	2140	2030	12.8	10.0	2000	4000	100	4B	5200
	44.6	2440	2080	1840	1820	1820	1820	9.2	9.2	2000	4000	100	4B	5200
	55.8	2300	2080	1840	1820	1820	1820	7.6	8.7	2000	4000	100	4B	5200
L3	53.4	2410	2310	2310	2310	2100	1700	9.3	8.2	2000	4000	100	4B	5200
	63.1	2970	2810	2810	2650	2390	1940	9.8	8.6	2000	4000	100	4B	5200
	72.3	2410	2310	2310	2310	2130	1730	7.0	8.0	2000	4000	50	4A	5200
	77.2	2970	2810	2810	2650	2350	1910	8.2	8.6	2000	4000	50	4A	5200
	90.2	2410	2310	2310	2310	2130	1730	5.6	7.4	2000	4000	50	4A	5200
	105	2970	2810	2810	2650	2350	1910	6.2	8.0	2000	4000	50	4A	5200
	113	2440	2080	1840	1820	1820	1820	4.4	7.4	2000	4000	50	4A	5200
	124	2440	2080	1840	1820	1820	1820	4.0	7.0	2000	4000	50	4A	5200
	141	2770	2700	2650	2620	2280	1850	4.4	7.1	2000	4000	50	4A	5200
	152	2440	2080	1840	1820	1820	1820	3.4	7.0	2000	4000	50	4A	5200
	164	2850	2520	2230	2200	2140	2030	3.9	7.0	2000	4000	50	4A	5200
	178	2850	2520	2230	2200	2140	2030	3.6	6.7	2000	4000	50	4A	5200
	190	2440	2080	1840	1820	1820	1820	2.8	6.6	2000	4000	50	4A	5200
	220	2250	2200	2250	2250	1830	1800	2.3	6.0	2000	4000	50	4A	5200
	258	2440	2080	1840	1820	1820	1820	2.0	5.9	2000	4000	50	4A	5200
	276	2850	2450	2230	2200	2140	2030	2.4	5.8	2000	4000	50	4A	5200
	321	2440	2080	1840	1820	1820	1820	1.6	5.4	2000	4000	50	4A	5200
	389	2000	1750	1650	1650	1650	1500	1.2	5.2	2000	4000	50	4A	5200
	402	2440	2080	1840	1820	1820	1820	1.3	5.3	2000	4000	50	4A	5200
L4	413	2850	2520	2230	2200	2140	2030	1.6	5.8	2000	4000	50	4A	5200
	446	2970	2810	2810	2650	2350	1910	1.5	5.8	2000	4000	50	4A	5200
	492	2770	2700	2650	2620	2280	1850	1.3	5.4	2000	4000	50	4A	5200
	556	2970	2810	2810	2650	2350	1910	1.2	5.5	2000	4000	50	4A	5200
	649	2410	2310	2310	2310	2130	1730	0.84	4.7	2000	4000	50	4A	5200
	718	2440	2080	1840	1820	1820	1820	0.76	4.9	2000	4000	50	4A	5200
	816	2770	2700	2650	2620	2280	1850	0.80	4.9	2000	4000	50	4A	5200
	896	2440	2080	1840	1820	1820	1820	0.61	4.7	2000	4000	50	4A	5200
	1018	2770	2700	2650	2620	2280	1850	0.64	4.7	2000	4000	50	4A	5200
	1098	2440	2080	1840	1820	1820	1820	0.50	4.6	2000	4000	50	4A	5200
	1278	2850	2520	2230	2200	2140	2030	0.53	4.5	2000	4000	50	4A	5200
	1370	2440	2080	1840	1820	1820	1820	0.40	4.4	2000	4000	50	4A	5200
	1586	2250	2250	2250	2250	1830	1800	0.34	4.2	2000	4000	50	4A	5200
	1854	2440	2080	1840	1820	1820	1820	0.29	4.2	2000	4000	50	4A	5200
	1991	2850	2450	2230	2200	2140	2030	0.34	4.1	2000	4000	50	4A	5200
	2243	2000	1750	1650	1650	1650	1500	0.21	4.1	2000	4000	50	4A	5200
	2799	2000	1750	1650	1650	1650	1500	0.17	4.0	2000	4000	50	4A	5200

304 L

294

3960 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
L1	3.60	3710	3520	3500	3440	3120	2830	50	*	1800	3800	800	5G	7300
	4.25	3960	3750	3690	3540	3430	2780	50	*	1800	3800	800	5G	7300
	5.33	3740	3190	2850	2850	2850	2710	50	*	1800	3800	630	5E	7300
	6.57	3000	2560	2390	2390	2390	2390	50	*	1800	3800	500	5C	7300
L2	12.5	3710	3520	3500	3440	3120	2830	30	12.9	2000	4000	260	4F	7300



304 L

294

3960 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
L2	15.3	3710	3520	3500	3440	3120	2830	30	13.9	2000	4000	260	4F	7300
	18.1	3960	3750	3690	3540	3430	2780	30	14.2	2000	4000	260	4F	7300
	20.8	3710	3520	3500	3440	3120	2830	30	12.4	2000	4000	160	4D	7300
	22.7	3740	3190	2850	2850	2850	2710	28	13.0	2000	4000	160	4D	7300
	24.5	3960	3750	3690	3540	3430	2780	30	12.5	2000	4000	160	4D	7300
	30.8	3740	3190	2850	2850	2850	2710	20	11.6	2000	4000	160	4D	7300
	38.4	3740	3190	2850	2850	2850	2710	16.2	10.4	2000	4000	160	4D	7300
	47.3	3000	2560	2390	2390	2390	2390	10.9	9.0	2000	4000	100	4B	7300
	59.1	3000	2560	2390	2390	2390	2390	8.9	8.7	2000	4000	100	4B	7300
L3	43.6	3710	3520	3500	3440	3120	2830	18.4	8.5	2000	4000	50	4A	7300
	53.4	3710	3520	3500	3440	3120	2830	15.1	8.6	2000	4000	50	4A	7300
	63.1	3960	3750	3690	3540	3430	2780	13.4	8.7	2000	4000	50	4A	7300
	72.3	3710	3520	3500	3440	3120	2830	11.2	7.8	2000	4000	50	4A	7300
	77.2	3960	3750	3690	3540	3430	2780	11.0	9.1	2000	4000	50	4A	7300
	90.2	3710	3520	3500	3440	3080	2830	9.0	7.1	2000	4000	50	4A	7300
	105	3960	3750	3690	3540	3430	2780	8.4	8.5	2000	4000	50	4A	7300
	111	3710	3520	3500	3440	3120	2830	7.5	7.8	2000	4000	50	4A	7300
	130	3960	3750	3690	3540	3430	2780	6.8	7.9	2000	4000	50	4A	7300
	141	3960	3750	3690	3540	3430	2780	6.3	7.5	2000	4000	50	4A	7300
	150	3710	3520	3500	3440	3120	2830	5.6	7.0	2000	4000	50	4A	7300
	165	3000	2560	2390	2390	2390	2390	3.8	6.7	2000	4000	50	4A	7300
	178	3740	3190	2850	2850	2850	2710	4.5	7.1	2000	4000	50	4A	7300
	202	3000	2560	2390	2390	2390	2390	3.1	6.6	2000	4000	50	4A	7300
	220	3960	3710	3660	3540	3430	2780	4.1	6.4	2000	4000	50	4A	7300
	273	3000	2560	2390	2390	2390	2390	2.3	6.0	2000	4000	50	4A	7300
	341	3000	2560	2390	2390	2390	2390	1.8	5.8	2000	4000	50	4A	7300
	426	3000	2560	2390	2390	2390	2390	1.5	5.4	2000	4000	50	4A	7300
L4	413	3740	3190	2850	2850	2850	2710	2.0	6.2	2000	4000	50	4A	7300
	446	3960	3750	3690	3540	3430	2780	2.1	5.9	2000	4000	50	4A	7300
	492	3960	3750	3690	3540	3430	2780	1.9	5.3	2000	4000	50	4A	7300
	556	3960	3750	3690	3540	3430	2780	1.7	5.8	2000	4000	50	4A	7300
	649	3710	3520	3500	3440	3120	2830	1.4	4.9	2000	4000	50	4A	7300
	702	3000	2560	2390	2390	2390	2390	0.93	5.1	2000	4000	50	4A	7300
	816	3960	3750	3690	3540	3430	2780	1.1	5.1	2000	4000	50	4A	7300
	1018	3960	3750	3690	3540	3430	2780	0.92	4.9	2000	4000	50	4A	7300
	1164	3000	2560	2390	2390	2390	2390	0.56	4.7	2000	4000	50	4A	7300
	1271	3960	3750	3690	3540	3430	2780	0.74	4.6	2000	4000	50	4A	7300
	1344	3710	3520	3500	3440	3080	2830	0.65	4.3	2000	4000	50	4A	7300
	1586	3960	3710	3660	3540	3430	2780	0.59	4.4	2000	4000	50	4A	7300
	1815	3000	2560	2390	2390	2390	2390	0.36	4.4	2000	4000	50	4A	7300
	1991	3740	3190	2850	2850	2850	2710	0.42	4.2	2000	4000	50	4A	7300
	2269	3000	2560	2390	2390	2390	2390	0.29	4.3	2000	4000	50	4A	7300
	2453	3000	2560	2390	2390	2390	2390	0.27	4.0	2000	4000	50	4A	7300

305 L

306

5800 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
L1	3.60	4700	4490	4490	4490	4480	3640	60	*	1800	3800	1000	5K	8800
	4.25	5800	5500	5480	5300	4410	3580	60	*	1800	3800	1000	5K	8800
	5.33	5600	5040	4470	4400	4280	3490	60	*	1800	3800	1000	5K	8800
	6.20	4690	4000	3600	3600	3550	3460	60	*	1800	3800	800	5G	8800
	7.50	3800	3300	3100	3100	3000	2790	60	*	1800	3800	630	5E	8800
L2	12.5	4700	4490	4490	4490	3800	3090	30	13.3	2000	4000	400	4K	8800
	15.3	4700	4490	4490	4490	3750	3040	30	14.3	2000	4000	330	4H	8800
	18.1	5800	5500	5480	5300	4210	3420	30	14.9	2000	4000	400	4K	8800
	20.8	4700	4450	4430	4430	3630	2950	30	12.9	2000	4000	260	4F	8800

C



305 L

306

5800 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
L2	22.7	5600	5040	4470	4400	4280	3490	30	13.9	2000	4000	330	4H	8800
	24.5	5530	5400	5300	5230	4070	3310	30	13.3	2000	4000	330	4H	8800
	26.4	4690	4000	3600	3600	3550	3460	30	12.5	2000	4000	260	4F	8800
	30.8	5600	5040	4470	4400	4280	3490	30	12.3	2000	4000	260	4F	8800
	35.8	4690	4000	3600	3600	3550	3460	22.4	11.2	2000	4000	160	4D	8800
	38.4	5600	4900	4470	4400	4280	3490	25.5	11.0	2000	4000	160	4D	8800
	44.6	4690	4000	3600	3600	3550	3460	18.3	10.1	2000	4000	160	4D	8800
	55.8	4430	4000	3600	3600	3500	3460	15.2	9.7	2000	4000	160	4D	8800
L3	53.4	4700	4490	4490	4490	3750	3040	18.8	9.1	2000	4000	100	4B	8800
	63.1	5800	5480	5480	5300	4270	3470	19.4	9.5	2000	4000	160	4D	8800
	72.3	4700	4490	4490	4490	3800	3090	14.1	8.8	2000	4000	100	4B	8800
	77.2	5800	5500	5480	5300	4210	3420	16.3	9.6	2000	4000	100	4B	8800
	90.2	4700	4490	4490	4490	3800	3090	11.4	8.2	2000	4000	100	4B	8800
	105	5800	5500	5480	5300	4210	3420	12.3	8.9	2000	4000	100	4B	8800
	113	4690	4000	3600	3600	3550	3460	8.7	8.4	2000	4000	100	4B	8800
	124	4690	4000	3600	3600	3550	3460	8.0	7.8	2000	4000	50	4A	8800
	141	5530	5350	5300	5230	4070	3310	8.9	7.9	2000	4000	100	4B	8800
	152	4690	4000	3600	3600	3550	3460	6.7	7.8	2000	4000	50	4A	8800
	164	5600	5040	4470	4400	4280	3490	7.7	7.8	2000	4000	50	4A	8800
	178	5600	5040	4470	4400	4280	3490	7.2	7.5	2000	4000	50	4A	8800
	190	4690	4000	3600	3600	3550	3460	5.5	7.3	2000	4000	50	4A	8800
	220	4750	4750	4750	4750	3660	3210	4.9	6.7	2000	4000	50	4A	8800
	258	4690	4000	3600	3600	3550	3460	4.1	6.6	2000	4000	50	4A	8800
	276	5600	4900	4470	4400	4280	3490	4.6	6.4	2000	4000	50	4A	8800
	321	4690	4000	3600	3600	3550	3460	3.3	6.1	2000	4000	50	4A	8800
	389	3800	3300	3100	3100	3000	2790	2.2	5.8	2000	4000	50	4A	8800
	402	4690	4000	3600	3600	3550	3460	2.6	5.9	2000	4000	50	4A	8800
L4	413	5600	5040	4470	4400	4280	3490	3.2	6.4	2000	4000	50	4A	8800
	446	5800	5500	5480	5300	4210	3420	3.1	6.4	2000	4000	50	4A	8800
	492	5530	5350	5300	5230	4070	3310	2.6	5.9	2000	4000	50	4A	8800
	556	5800	5500	5480	5300	4210	3420	2.5	6.0	2000	4000	50	4A	8800
	649	4700	4490	4490	4490	3800	3090	1.7	5.1	2000	4000	50	4A	8800
	718	4690	4000	3600	3600	3550	3460	1.5	5.3	2000	4000	50	4A	8800
	816	5530	5350	5300	5230	4070	3310	1.6	5.3	2000	4000	50	4A	8800
	896	4690	4000	3600	3600	3550	3460	1.2	5.1	2000	4000	50	4A	8800
	1018	5530	5350	5300	5230	4070	3310	1.3	5.1	2000	4000	50	4A	8800
	1098	4690	4000	3600	3600	3550	3460	0.99	4.9	2000	4000	50	4A	8800
	1278	5600	5040	4470	4400	4280	3490	1.0	4.9	2000	4000	50	4A	8800
	1370	4690	4000	3600	3600	3550	3460	0.79	4.7	2000	4000	50	4A	8800
	1586	4750	4750	4750	4750	3660	3210	0.71	4.5	2000	4000	50	4A	8800
	1854	4690	4000	3600	3600	3550	3460	0.59	4.4	2000	4000	50	4A	8800
	1991	5600	4900	4470	4400	4280	3490	0.67	4.3	2000	4000	50	4A	8800
	2243	3800	3300	3100	3100	3000	2790	0.40	4.3	2000	4000	50	4A	8800
	2799	3800	3300	3100	3100	3000	2790	0.32	4.1	2000	4000	50	4A	8800

306 L

318

10840 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
L1	3.60	10840	10380	10380	10380	7100	5770	75	*	1600	3000	2750	6K	14900
	4.25	10420	9850	9850	9600	6990	5680	75	*	1600	3000	2750	6K	14900
	5.33	10080	9350	8300	7950	6810	5530	75	*	1600	3000	2200	6G	14900
	6.20	8630	7370	6530	6500	6460	5480	75	*	1600	3000	1600	6E	14900
	7.50	7000	5900	5500	5500	5040	5040	75	*	1600	3000	1200	6C	14900
L2	13.0	8020	8020	8020	8020	6210	5040	40	21.2	1800	3800	800	5G	14900
	15.3	9770	9340	9340	9300	6110	4960	40	22.8	1800	3800	800	5G	14900
	18.1	10420	9850	9850	9600	6860	5570	40	23.7	1800	3800	630	5E	14900



306 L

318

10840 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
L2	22.7	9560	9100	9100	9100	6680	5430	40	22.5	1800	3800	500	5C	14900
	26.4	7890	7590	7590	7590	6620	5380	40	20.4	1800	3800	400	5B	14900
	28.4	10080	9350	8300	7950	6810	5530	40	20.2	1800	3800	400	5B	14900
	33.1	9540	9350	8300	7950	6810	5530	40	18.5	1800	3800	400	5B	14900
	38.4	8630	7370	6530	6500	6460	5480	34	16.6	1800	3800	400	5B	14900
	46.5	8500	7370	6530	6500	6460	5480	29	15.5	1800	3800	400	5B	14900
	56.3	7000	5900	5500	5500	5040	5040	21	14.5	1800	3800	400	5B	14900
	72.5	6400	5900	5500	5500	5040	5040	16.3	12.6	1800	3800	400	5B	14900
L3	53.2	9770	9340	9340	9300	6110	4960	20	13.0	2000	4000	260	4F	14900
	65.2	9770	9340	9340	9300	6110	4960	20	13.4	2000	4000	160	4D	14900
	77.0	10420	9850	9850	9600	6860	5570	20	13.6	2000	4000	160	4D	14900
	81.9	8320	7700	7700	7530	5950	4830	20	12.5	2000	4000	160	4D	14900
	88.3	9450	9450	9450	9450	6970	5660	20	12.3	2000	4000	160	4D	14900
	104	10420	9850	9850	9600	6860	5570	20	12.3	2000	4000	160	4D	14900
	112	7890	7590	7590	7590	6620	5380	15.2	11.6	2000	4000	160	4D	14900
	121	10080	9350	8300	7950	6810	5530	17.2	11.7	2000	4000	100	4B	14900
	141	9540	9350	8300	7950	6810	5530	14.8	10.9	2000	4000	100	4B	14900
	152	7890	7590	7590	7590	6620	5380	11.3	10.6	2000	4000	100	4B	14900
	190	8630	7370	6530	6500	6460	5480	10.2	9.8	2000	4000	100	4B	14900
	205	10080	9350	8300	7950	6810	5530	10.6	9.9	2000	4000	100	4B	14900
	222	8630	7370	6530	6500	6460	5480	8.8	9.4	2000	4000	50	4A	14900
	238	9540	9350	8300	7950	6810	5530	9.0	9.3	2000	4000	50	4A	14900
	268	7000	5900	5500	5500	5040	5040	6.0	8.9	2000	4000	50	4A	14900
	288	7000	5900	5500	5500	5040	5040	5.6	8.9	2000	4000	50	4A	14900
	325	7000	5900	5500	5500	5040	5040	4.9	8.4	2000	4000	50	4A	14900
	405	7000	5900	5500	5500	5040	5040	4.0	7.9	2000	4000	50	4A	14900
L4	391	8630	7370	6530	6500	6460	5480	5.1	8.0	2000	4000	50	4A	14900
	444	10420	9850	9850	9600	6860	5570	5.3	8.1	2000	4000	50	4A	14900
	509	9450	9450	9450	9450	6970	5660	4.1	7.7	2000	4000	50	4A	14900
	589	10080	9350	8300	7950	6810	5530	3.8	7.6	2000	4000	50	4A	14900
	636	9450	9450	9450	9450	6970	5660	3.3	7.2	2000	4000	50	4A	14900
	700	10080	9350	8300	7950	6810	5530	3.2	7.6	2000	4000	50	4A	14900
	809	7890	7590	7590	7590	6620	5380	2.2	7.1	2000	4000	50	4A	14900
	877	7890	7590	7590	7590	6620	5380	2.0	6.9	2000	4000	50	4A	14900
	1015	9540	9350	8300	7950	6810	5530	2.2	6.8	2000	4000	50	4A	14900
	1095	7890	7590	7590	7590	6620	5380	1.6	6.5	2000	4000	50	4A	14900
	1279	8630	7370	6530	6500	6460	5480	1.6	6.3	2000	4000	50	4A	14900
	1475	10080	9350	8300	7950	6810	5530	1.5	6.1	2000	4000	50	4A	14900
	1597	8630	7370	6530	6500	6460	5480	1.3	5.9	2000	4000	50	4A	14900
	1843	10080	9350	8300	7950	6810	5530	1.2	5.9	2000	4000	50	4A	14900
	2074	7000	5900	5500	5500	5040	5040	0.80	5.7	2000	4000	50	4A	14900
	2337	7000	5900	5500	5500	5040	5040	0.71	5.6	2000	4000	50	4A	14900
	2916	7000	5900	5500	5500	5040	5040	0.57	5.2	2000	4000	50	4A	14900

307 L

330

15680 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
L1	3.43	9000	9000	9000	9000	8300	7960	115	*	1500	2500	3300	6L	18600
	4.09	15680	14890	14890	13510	9560	7770	115	*	1500	2500	3300	6L	21000
	5.25	14840	12700	11300	10790	9340	7590	115	*	1500	2500	3300	6L	21000
	6.23	11000	9600	8700	8700	8240	7490	115	*	1500	2500	2200	6G	21000
L2	12.3	9000	9000	9000	9000	8300	7960	60	17.7	1800	3800	1000	5K	18600
	14.7	15680	14890	14890	13510	9560	7770	60	17.0	1800	3800	800	5G	21000
	17.4	15680	14890	14890	13510	9560	7770	60	21.2	1800	3800	1000	5K	21000
	21.8	15680	14890	14890	13510	9560	7770	60	21.8	1800	3800	800	5G	21000
	25.4	14670	14010	14010	13510	9560	7770	60	20.6	1800	3800	630	5E	21000



307 L

330

15680 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
L2	28.0	14840	12700	11300	10790	9340	7590	60	21.2	1800	3800	500	5C	21000
	30.7	12300	12300	12300	12300	9560	7770	60	19.5	1800	3800	500	5C	21000
	32.6	14840	12700	11300	10790	9340	7590	60	19.9	1800	3800	500	5C	21000
	38.6	11000	9600	8700	8700	8240	7490	46	18.0	1800	3800	400	5B	21000
	46.7	11000	9600	8700	8700	8240	7490	39	17.0	1800	3800	400	5B	21000
L3	51.3	15680	14890	14890	13510	9560	7770	30	14.4	2000	4000	330	4H	21000
	60.5	15680	14890	14890	13510	9560	7770	30	14.5	2000	4000	330	4H	21000
	74.1	15680	14890	14890	13510	9560	7770	30	15.1	2000	4000	260	4F	21000
	80.6	14840	12700	11300	10790	9340	7590	30	14.3	2000	4000	260	4F	21000
	93.0	15680	14890	14890	13510	9560	7770	30	14.2	2000	4000	260	4F	21000
	100	15680	14890	14890	13510	9560	7770	30	13.8	2000	4000	260	4F	21000
	113	14840	12700	11300	10790	9340	7590	26	12.5	2000	4000	160	4D	21000
	126	15680	14890	14890	13510	9560	7770	26	13.0	2000	4000	160	4D	21000
	139	14840	12700	11300	10790	9340	7590	22	12.8	2000	4000	160	4D	21000
	146	15000	14010	14010	13510	9560	7770	23	12.1	2000	4000	160	4D	21000
	162	14840	12700	11300	10790	9340	7590	19.4	12.5	2000	4000	100	4B	21000
	177	12300	12300	12300	12300	9560	7770	15.9	11.3	2000	4000	100	4B	21000
	202	14840	12700	11300	10790	9340	7590	15.9	11.5	2000	4000	100	4B	21000
	221	15000	13800	12900	12500	9560	7770	15.6	10.5	2000	4000	100	4B	21000
	239	11000	9600	8700	8700	8240	7490	10.5	10.8	2000	4000	50	4A	21000
	284	14330	12700	11300	10790	9340	7590	11.3	10.2	2000	4000	50	4A	21000
	336	11000	9600	8700	8700	8240	7490	7.5	9.6	2000	4000	50	4A	21000
L4	349	15680	14890	14890	13510	9560	7770	10.2	9.8	2000	4000	50	4A	21000
	406	14840	12700	11300	10790	9340	7590	8.2	10.1	2000	4000	50	4A	21000
	465	14840	12700	11300	10790	9340	7590	7.1	9.4	2000	4000	50	4A	21000
	509	15000	14010	14010	13510	9560	7770	7.0	8.4	2000	4000	50	4A	21000
	579	15680	14890	14890	13510	9560	7770	6.1	8.8	2000	4000	50	4A	21000
	654	14840	12700	11300	10790	9340	7590	5.1	8.6	2000	4000	50	4A	21000
	722	15680	14890	14890	13510	9560	7770	4.9	8.2	2000	4000	50	4A	21000
	801	14840	12700	11300	10790	9340	7590	4.1	8.5	2000	4000	50	4A	21000
	906	15680	14890	14890	13510	9560	7770	3.9	7.9	2000	4000	50	4A	21000
	999	14840	12700	11300	10790	9340	7590	3.3	8.0	2000	4000	50	4A	21000
	1157	14840	12700	11300	10790	9340	7590	2.9	7.5	2000	4000	50	4A	21000
	1274	12300	12300	12300	12300	9560	7770	2.3	7.1	2000	4000	50	4A	21000
	1408	15680	14890	14890	13510	9560	7770	2.5	7.1	2000	4000	50	4A	21000
	1591	15000	13800	12900	12500	9560	7770	2.2	6.6	2000	4000	50	4A	21000
	1767	15680	14890	14890	13510	9560	7770	2.0	6.8	2000	4000	50	4A	21000
	2041	14330	12700	11300	10790	9340	7590	1.6	6.5	2000	4000	50	4A	21000
	2423	11000	9600	8700	8700	8240	7490	1.1	6.2	2000	4000	50	4A	21000

309 L

342

23240 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
L1	3.43	13000	13000	13000	13000	12310	10920	150	*	1500	2000	3300	6L	27900
	4.09	23240	22070	22070	20260	13120	10660	150	*	1500	2000	3300	6L	29000
	5.25	21980	19060	16940	16190	12810	10410	150	*	1500	2000	3300	6L	29000
	6.23	17000	14400	13000	13000	12370	10280	150	*	1500	2000	3300	6L	29000
L2	12.3	13000	13000	13000	13000	10290	8360	60	25.7	1800	3800	1000	5K	27900
	14.7	17730	17730	17730	17730	11650	9460	60	25.4	1800	3800	1000	5K	29000
	17.4	21620	21260	21260	18580	11460	9310	60	30	1800	3800	1000	5K	29000
	21.8	18510	17500	17500	17140	11160	9070	60	30	1800	3800	1000	5K	29000
	25.4	14670	14300	14300	14300	11060	8990	60	28.4	1800	3800	800	5G	29000
	28.0	21980	19060	16940	16190	12810	10410	60	29.7	1800	3800	800	5G	29000
	32.6	18300	18100	16940	16190	12810	10410	60	27.6	1800	3800	630	5E	29000
	38.6	17000	14400	13000	13000	12370	10280	60	25.1	1800	3800	500	5C	29000
	46.7	17000	14400	13000	13000	12370	10280	58	23.5	1800	3800	400	5B	29000



309 L

342

23240 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
L3	51.3	17730	17730	17730	17730	11650	9460	30	20.2	2000	4000	400	4K	29000
	60.5	21620	21260	21260	18580	11460	9310	30	20.3	2000	4000	400	4K	29000
	74.1	21620	21260	21260	18580	11460	9310	30	20.7	2000	4000	260	4F	29000
	80.6	21980	19060	16940	16190	12810	10410	30	19.9	2000	4000	260	4F	29000
	93.0	18510	17500	17500	17140	11160	9070	30	19.3	2000	4000	260	4F	29000
	100	21620	21260	21260	18580	11460	9310	30	18.6	2000	4000	260	4F	29000
	113	18300	18100	16940	16190	12810	10410	30	17.1	2000	4000	260	4F	29000
	126	18510	17500	17500	17140	11160	9070	30	17.4	2000	4000	260	4F	29000
	139	18300	18100	16940	16190	12810	10410	30	17.2	2000	4000	160	4D	29000
	162	21980	19060	16940	16190	12810	10410	29	16.9	2000	4000	160	4D	29000
	183	14670	14300	14300	14300	11060	8990	18.2	14.8	2000	4000	100	4B	29000
	202	21980	19060	16940	16190	12810	10410	23.9	15.4	2000	4000	100	4B	29000
	223	17000	14400	13000	13000	12370	10280	17.5	14.7	2000	4000	100	4B	29000
	239	17000	14400	13000	13000	12370	10280	16.3	14.5	2000	4000	100	4B	29000
	284	15800	15800	15800	15000	12810	10410	12.8	13.6	2000	4000	100	4B	29000
	336	17000	14400	13000	13000	12370	10280	11.6	12.8	2000	4000	100	4B	29000
L4	349	21620	21260	21260	18580	11460	9310	14.4	12.7	2000	4000	100	4B	29000
	406	21980	19060	16940	16190	12810	10410	12.3	13.3	2000	4000	50	4A	29000
	465	21980	19060	16940	16190	12810	10410	10.7	12.3	2000	4000	50	4A	29000
	509	14670	14300	14300	14300	11060	8990	6.7	11.0	2000	4000	50	4A	29000
	579	21620	21260	21260	18580	11460	9310	8.7	11.4	2000	4000	50	4A	29000
	654	18300	18100	16940	16190	12810	10410	6.6	11.2	2000	4000	50	4A	29000
	722	21620	21260	21260	18580	11460	9310	7.0	10.6	2000	4000	50	4A	29000
	801	18300	18100	16940	16190	12810	10410	5.4	11.0	2000	4000	50	4A	29000
	906	18510	17500	17500	17140	11160	9070	4.7	10.2	2000	4000	50	4A	29000
	999	18300	18100	16940	16190	12810	10410	4.3	10.3	2000	4000	50	4A	29000
	1149	17000	14400	13000	13000	12370	10280	3.5	9.9	2000	4000	50	4A	29000
	1286	17000	14400	13000	13000	12370	10280	3.1	9.6	2000	4000	50	4A	29000
	1380	17000	14400	13000	13000	12370	10280	2.9	9.4	2000	4000	50	4A	29000
	1605	17000	14400	13000	13000	12370	10280	2.5	9.0	2000	4000	50	4A	29000
	1723	17000	14400	13000	13000	12370	10280	2.3	8.9	2000	4000	50	4A	29000
	2003	17000	14400	13000	13000	12370	10280	1.9	8.4	2000	4000	50	4A	29000
	2423	17000	14400	13000	13000	12370	10280	1.7	8.0	2000	4000	50	4A	29000

310M L

354

33640 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
L1	4.09	33640	31900	29360	26490	21190	17220	175	*	1750	1800	—	—	47600
	5.25	30110	25640	22700	21660	20710	16820	175	*	1750	1800	—	—	47600
	6.23	23930	20350	18000	17810	17810	16620	175	*	1750	1800	—	—	47600
L2	14.7	33640	31900	29360	26490	18470	15000	75	27.5	1750	3000	2750	6K	47600
	17.4	33640	31900	29360	26490	18180	14770	75	34	1750	3000	2200	6G	47600
	21.8	33170	30650	29360	26490	17700	14380	75	36	1750	3000	2200	6G	47600
	25.4	26060	24860	24860	24860	17540	14250	75	34	1750	3000	1600	6E	47600
	28.0	30110	25640	22700	21660	20710	16820	75	35	1750	3000	1600	6E	47600
	30.7	19480	19330	19330	19330	17120	13900	75	33	1750	3000	1200	6C	47600
	32.6	30110	25640	22700	21660	20710	16820	75	33	1750	3000	1200	6C	47600
	38.6	23930	20350	18000	17810	17810	16620	75	28.8	1750	3000	900	6B	47600
	46.7	23930	20350	18000	17810	17810	16620	75	27.8	1750	3000	900	6B	47600
L3	53.0	30730	30730	29360	26160	16140	13110	40	26.1	1800	3800	630	5E	47600
	62.6	33640	31900	29360	25750	15890	12910	40	26.8	1800	3800	630	5E	47600
	73.9	33640	31900	29360	26490	17850	14500	40	27.2	1800	3800	500	5C	47600
	80.3	30110	25640	22700	21660	18920	15370	40	25.5	1800	3800	400	5B	47600
	92.7	33640	31900	29350	26250	17380	14110	40	25.9	1800	3800	400	5B	47600
	101	30110	25640	22700	21660	18420	14960	40	24.4	1800	3800	400	5B	47600
	108	28060	28060	28060	26500	17220	13990	40	24.1	1800	3800	400	5B	47600

C



310M L

354

33640 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
L3	119	30110	25640	22700	21660	20710	16820	40	23.8	1800	3800	400	5B	47600
	135	33170	30640	29350	26500	17700	14380	40	22.4	1800	3800	400	5B	47600
	149	30110	25640	22700	21660	20710	16820	40	22.8	1800	3800	400	5B	47600
	164	27150	27150	27150	26490	17700	14380	34	21.0	1800	3800	400	5B	47600
	177	23930	20350	18000	17810	17810	16620	28	20.6	1800	3800	400	5B	47600
	202	30110	25640	22700	21660	20710	16820	31	19.9	1800	3800	400	5B	47600
	230	19480	19330	19330	19330	17120	13900	17.5	18.5	1800	3800	400	5B	47600
	249	23930	20350	18000	17810	17810	16620	20	18.4	1800	3800	400	5B	47600
	295	24820	24820	22700	21660	20380	16550	17.4	17.8	1800	3800	400	5B	47600
	350	23930	20350	18000	17810	17810	16620	14.1	16.4	1800	3800	400	5B	47600
L4	392	23930	20350	18000	17810	17810	16620	14.5	15.4	2000	4000	100	4B	47600
	453	28950	28950	28950	25070	15470	12570	15.1	15.0	2000	4000	100	4B	47600
	507	30110	25640	22700	21660	20710	16820	14.0	15.8	2000	4000	100	4B	47600
	590	30110	25640	22700	21660	20510	16600	12.1	14.8	2000	4000	100	4B	47600
	637	30110	25640	22700	21660	20710	16820	11.2	14.9	2000	4000	100	4B	47600
	726	30110	25640	22700	21660	18420	14960	9.8	13.4	2000	4000	50	4A	47600
	798	30110	25640	22700	21660	20510	16660	8.9	13.7	2000	4000	50	4A	47600
	974	33170	30640	29350	26500	17700	14380	8.1	12.4	2000	4000	50	4A	47600
	1002	30110	25640	22700	21660	20710	16820	7.1	13.0	2000	4000	50	4A	47600
	1164	30110	25640	22700	21660	20710	16820	6.1	12.3	2000	4000	50	4A	47600
	1259	24820	24820	22700	21660	20380	16550	4.7	11.9	2000	4000	50	4A	47600
	1438	23930	20350	18000	17810	17810	16620	3.9	11.4	2000	4000	50	4A	47600
	1672	23930	20350	18000	17810	17810	16620	3.4	10.9	2000	4000	50	4A	47600
	1794	23930	20350	18000	17810	17810	16620	3.2	10.7	2000	4000	50	4A	47600
	2022	23930	20350	18000	17810	17810	16620	2.8	10.4	2000	4000	50	4A	47600
	2523	23930	20350	18000	17810	17810	16620	2.2	9.9	2000	4000	50	4A	47600

311M L

366

49210 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
L1	4.09	49210	46590	45450	41050	30210	24540	200	*	1500	1800	—	—	58300
	5.25	47810	41400	36690	35010	29500	23960	200	*	1500	1800	—	—	58300
	6.23	36470	31040	27480	27190	27190	23670	200	*	1500	1800	—	—	58300
L2	14.0	32420	32420	32420	32420	25490	20710	115	32	1500	2500	3300	6L	58300
	16.7	49210	46590	45450	40310	24870	20200	115	38	1500	2500	3300	6L	58300
	18.0	41500	41400	36690	35010	29500	23960	115	31	1500	2500	2750	6K	58300
	21.5	47810	41400	36690	35010	23030	18700	115	37	1500	2500	2750	6K	58300
	25.5	33520	32020	32020	32020	23990	19490	115	41	1500	2500	1600	6E	58300
	27.6	47810	41400	36690	35010	28930	23490	115	41	1500	2500	2200	6G	58300
	32.7	41250	41170	36690	35010	28570	23200	115	40	1500	2500	1600	6E	58300
	38.8	36470	31040	27480	27190	27190	23670	115	37	1500	2500	1600	6E	58300
L3	50.5	32420	32420	32420	32420	25490	20710	60	26.8	1800	3800	800	5G	58300
	60.2	49210	46590	45450	40310	24870	20200	60	25.9	1800	3800	1000	5K	58300
	71.1	49210	46590	45450	40310	24870	20200	60	28.2	1800	3800	800	5G	58300
	77.3	47810	41400	36690	35010	29500	23960	60	24.8	1800	3800	800	5G	58300
	89.3	49210	46590	45450	40310	24870	20200	60	27.8	1800	3800	800	5G	58300
	104	49210	46590	45450	40310	24870	20200	60	26.4	1800	3800	800	5G	58300
	115	47810	41400	36690	35010	29500	23960	60	26.6	1800	3800	500	5C	58300
	133	47810	41400	36690	35010	29500	23960	60	25.2	1800	3800	400	5B	58300
	147	47810	41400	36690	35010	28930	23490	60	25.5	1800	3800	400	5B	58300
	161	47810	41400	36690	35010	29500	23960	60	24.0	1800	3800	400	5B	58300
	171	47810	41400	36690	35010	28930	23490	58	24.3	1800	3800	400	5B	58300
	191	33520	32020	32020	32020	23990	19490	36	22.5	1800	3800	400	5B	58300
	203	41250	41170	36690	35010	28570	23200	42	22.6	1800	3800	400	5B	58300
	245	41250	41170	36690	35010	28570	23200	35	21.6	1800	3800	400	5B	58300
	291	36470	31040	27480	27190	27190	23670	26	20.5	1800	3800	400	5B	58300



311M L

366

49210 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
L4	348	49210	46590	45450	39750	24530	19920	30	18.7	2000	4000	160	4D	58300
	410	49210	46590	45450	40310	24870	20200	28	18.6	2000	4000	160	4D	58300
	512	49210	46590	45450	40310	24870	20200	23	17.2	2000	4000	100	4B	58300
	568	47810	41400	36690	35010	29500	23960	19.9	17.3	2000	4000	100	4B	58300
	627	47810	41400	36690	35010	28930	23490	18.0	17.7	2000	4000	100	4B	58300
	825	47810	41400	36690	35010	29500	23960	13.7	15.7	2000	4000	100	4B	58300
	986	47810	41400	36690	35010	28930	23490	11.5	15.5	2000	4000	50	4A	58300
	1058	47810	41400	36690	35010	28930	23490	10.7	15.2	2000	4000	50	4A	58300
	1230	47810	41400	36690	35010	28930	23490	9.2	14.4	2000	4000	50	4A	58300
	1415	41250	41170	36690	35010	28570	23200	6.9	13.9	2000	4000	50	4A	58300
	1680	36470	31040	27480	27190	27190	23670	5.1	13.4	2000	4000	50	4A	58300
	1766	41250	41170	36690	35010	28570	23200	5.5	13.0	2000	4000	50	4A	58300
	2096	36470	31040	27480	27480	27480	23670	4.1	12.5	2000	4000	50	4A	58300

C

313M L

378

60940 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
L1	4.14	60940	57660	55630	50400	42150	34240	250	*	1000	1300	—	—	105000
	5.40	57130	48690	43150	41430	41090	33380	250	*	1000	1300	—	—	105000
	6.50	40100	34160	30260	30200	30200	30200	250	*	1000	1300	—	—	105000
L2	14.2	48640	48640	48640	48640	35280	28650	150	*	1500	2000	3300	6L	105000
	16.9	60940	57660	55630	50400	34420	27960	150	*	1500	2000	3300	6L	105000
	18.5	57130	48690	43150	41430	41090	33380	150	*	1500	2000	3300	6L	105000
	21.8	60940	57660	55630	50400	33620	27300	150	39	1500	2000	3300	6L	105000
	25.8	50810	48640	48640	48640	33200	26970	150	42	1500	2000	2200	6G	105000
	28.4	57130	48690	43150	41430	40470	32870	150	36	1500	2000	3300	6L	105000
	33.6	57130	48690	43150	41430	39970	32460	150	39	1500	2000	2200	6G	105000
	40.5	40100	34160	30260	30200	30200	30200	133	37	1500	2000	1600	6E	105000
L3	51.1	48640	48640	48640	43750	27000	21930	60	33	1800	3800	1000	5K	105000
	61.0	60940	57660	55630	49510	30550	24820	60	32	1800	3800	1000	5K	105000
	72.0	60940	57660	55630	48740	30080	24430	60	35	1800	3800	1000	5K	105000
	78.3	60940	57660	55630	50400	33620	27300	60	32	1800	3800	1000	5K	105000
	92.4	60940	57660	55630	50400	33620	27300	60	34	1800	3800	800	5G	105000
	110	50810	48640	48640	48640	33200	26970	60	31	1800	3800	800	5G	105000
	120	57130	48690	43150	41430	40470	32870	60	31	1800	3800	500	5C	105000
	135	60940	57660	55630	50400	33620	27300	60	31	1800	3800	500	5C	105000
	143	57130	48690	43150	41430	39970	32460	60	28.9	1800	3800	500	5C	105000
	151	57130	48690	43150	41430	40470	32870	60	31	1800	3800	500	5C	105000
	163	54140	54140	54140	50400	33620	27300	60	29.7	1800	3800	400	5B	105000
	176	57130	48690	43150	41430	40470	32870	60	28.9	1800	3800	400	5B	105000
	182	40100	34160	30260	30200	30200	30200	46	28.9	1800	3800	400	5B	105000
	194	50810	48640	48640	48640	33200	26970	54	27.5	1800	3800	400	5B	105000
	209	57130	48690	43150	41430	39970	32460	57	26.9	1800	3800	400	5B	105000
	252	57130	48690	43150	41430	39970	32460	47	25.6	1800	3800	400	5B	105000
	304	40100	34160	30260	30200	30200	30200	27	24.4	1800	3800	400	5B	105000
L4	394	60940	57660	55630	50400	33620	27300	30	23.6	2000	4000	260	4F	105000
	452	60940	57660	55630	47760	29470	23940	30	21.7	2000	4000	160	4D	105000
	514	57130	48690	43150	41430	40470	32870	26	22.0	2000	4000	160	4D	105000
	564	54240	54240	54240	46390	28620	23250	23	20.0	2000	4000	160	4D	105000
	633	50810	48640	48640	48640	33200	26970	19.0	20.2	2000	4000	100	4B	105000
	695	57130	48690	43150	41430	39840	32360	19.4	20.2	2000	4000	100	4B	105000
	790	50810	48640	48640	48640	33200	26970	15.2	18.8	2000	4000	100	4B	105000



313M L

378

60940 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
L4	889	57130	48690	43150	41430	39970	32460	15.2	18.4	2000	4000	100	4B	105000
	1014	57130	48690	43150	41430	40470	32870	13.3	18.0	2000	4000	100	4B	105000
	1117	50810	48640	48640	48640	33200	26970	10.8	17.0	2000	4000	50	4A	105000
	1266	57130	48690	43150	41430	40470	32870	10.7	16.8	2000	4000	50	4A	105000
	1394	50810	48640	48640	48640	33200	26970	8.6	16.0	2000	4000	50	4A	105000
	1502	57130	48690	43150	41430	39970	32460	9.0	15.9	2000	4000	50	4A	105000
	1817	57130	48690	43150	41430	39970	32460	7.4	15.1	2000	4000	50	4A	105000
	2187	40100	34160	30260	30200	30200	30200	4.3	14.7	2000	4000	50	4A	105000

314M L

390

80640 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
L1	4.25	80640	75688	75688	71136	53888	43776	260	*	500	900	—	—	115000
	5.33	73304	67496	62304	59712	52048	42280	260	*	500	900	—	—	115000
	6.20	63256	54024	47944	47400	47400	41792	260	*	500	900	—	—	115000
L2	17.4	80640	75688	75688	71136	45288	36784	175	*	1500	1800	—	—	115000
	22.3	78024	72424	72424	71136	44248	35936	175	54	1500	1800	—	—	115000
	26.5	61848	59488	59488	59488	43712	35504	175	58	1500	1800	—	—	115000
	28.0	73304	67496	62304	59712	51864	42128	175	53	1500	1800	—	—	115000
	33.2	73304	67496	62304	59712	51240	41616	175	55	1500	1800	—	—	115000
	38.6	63256	54024	47944	47400	47400	41792	175	54	1500	1800	—	—	115000
L3	62.6	80640	75688	75688	63944	39456	32048	75	54	1600	3000	1600	6E	115000
	73.9	80640	75688	75688	62952	38840	31552	75	59	1600	3000	1600	6E	115000
	92.7	80640	75688	75464	61296	37824	30720	75	56	1600	3000	1600	6E	115000
	108	80640	75688	74784	60744	37480	30448	75	52	1600	3000	1600	6E	115000
	138	78024	72424	72424	71136	44248	35936	75	50	1600	3000	1600	6E	115000
	164	61848	59488	59488	59488	43712	35504	69	45	1600	3000	1200	6C	115000
	174	73304	67496	62304	59712	51864	42128	75	47	1600	3000	1200	6C	115000
	206	73304	67496	62304	59712	51240	41616	65	42	1600	3000	900	6B	115000
	240	63256	54024	47944	47400	47400	41792	48	41	1600	3000	900	6B	115000
L4	314	80640	75688	75688	61800	38128	30976	40	41	1800	3800	400	5B	115000
	394	80640	75696	74080	60176	37128	30160	40	38	1800	3800	400	5B	115000
	458	80640	75688	73416	59632	36800	29888	37	36	1800	3800	400	5B	115000
	495	80640	75688	75464	61296	37824	30720	35	36	1800	3800	400	5B	115000
	575	73304	67496	62304	59712	43136	35040	27	34	1800	3800	400	5B	115000
	588	78024	72424	72424	71136	44248	35936	28	34	1800	3800	400	5B	115000
	668	80640	75688	74784	60744	37480	30448	26	31	1800	3800	400	5B	115000
	738	78024	72424	72424	71136	44248	35936	23	32	1800	3800	400	5B	115000
	858	78024	72424	72424	71136	44248	35936	19	30	1800	3800	400	5B	115000
	926	73304	67496	62304	59712	51864	42128	16.9	31	1800	3800	400	5B	115000
	1038	78024	72424	72424	71136	44248	35936	16.0	28.3	1800	3800	400	5B	115000
	1099	73304	67496	62304	59712	51240	41616	14.2	28.4	1800	3800	400	5B	115000
	1277	73304	67496	62304	59712	51240	41616	12.2	27.0	1800	3800	400	5B	115000
	1485	63256	54024	47944	47400	47400	41792	9.1	26.3	1800	3800	400	5B	115000
	1796	63256	54024	47944	47400	47400	41792	7.5	24.8	1800	3800	400	5B	115000



315M L

402

100800 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
L1	4.25	100800	94610	94610	88920	67360	54720	260	*	500	900	—	—	135000
	5.33	91630	84370	77880	74640	65060	52850	260	*	500	900	—	—	135000
	6.20	79070	67530	59930	59250	59250	52240	260	*	500	900	—	—	135000
L2	17.4	100800	94610	94610	88920	67360	54720	200	*	1500	1800	—	—	135000
	22.3	100800	94610	94610	88920	67360	54720	200	47	1500	1800	—	—	135000
	26.5	100800	94610	94610	88920	67360	54720	200	60	1500	1800	—	—	135000
	28.0	91630	84370	77880	74640	65060	52850	200	47	1500	1800	—	—	135000
	33.2	91630	84370	77880	74640	65060	52850	200	57	1500	1800	—	—	135000
	38.6	79070	67530	59930	59250	59250	52240	200	56	1500	1800	—	—	135000
L3	59.6	100800	94610	94610	88920	67360	54720	115	55	1500	2500	2750	6K	135000
	71.1	100800	94610	94610	88920	66430	53960	115	58	1500	2500	2200	6G	135000
	91.3	100800	94610	94610	88920	64880	52700	115	60	1500	2500	1600	6E	135000
	108	100800	94610	94610	88920	64070	52040	115	56	1500	2500	1200	6C	135000
	139	100800	94610	94610	88920	67360	54720	115	53	1500	2500	900	6B	135000
	165	100800	94610	94610	88920	67360	54720	105	50	1500	2500	900	6B	135000
	174	91630	84370	77880	74640	65060	52850	90	50	1500	2500	900	6B	135000
	207	91630	84370	77880	74640	65060	52850	76	47	1500	2500	900	6B	135000
	241	79070	67530	59930	59250	59250	52240	57	46	1500	2500	900	6B	135000
L4	302	100800	94610	94610	88920	66430	53960	60	40	1800	3800	400	5B	135000
	370	100800	94610	94610	88920	67360	54720	58	39	1800	3800	400	5B	135000
	441	100800	94610	94610	88920	66430	53960	49	37	1800	3800	400	5B	135000
	487	100800	94610	94610	88920	64880	52700	44	37	1800	3800	400	5B	135000
	533	100800	94610	94610	88920	66430	53960	40	35	1800	3800	400	5B	135000
	591	100800	94610	94610	88920	67360	54720	36	34	1800	3800	400	5B	135000
	672	100800	94610	94610	88920	64070	52040	32	33	1800	3800	400	5B	135000
	741	100800	94610	94610	88920	67360	54720	29	33	1800	3800	400	5B	135000
	862	100800	94610	94610	88920	67360	54720	25	32	1800	3800	400	5B	135000
	930	91630	84370	77880	74640	65060	52850	21	32	1800	3800	400	5B	135000
	1043	100800	94610	94610	88920	67360	54720	21	30	1800	3800	400	5B	135000
	1104	91630	84370	77880	74640	65060	52850	17.7	30	1800	3800	400	5B	135000
	1284	91630	84370	77880	74640	65060	52850	15.2	28.9	1800	3800	400	5B	135000
	1492	79070	67530	59930	59250	59250	52240	11.3	28.1	1800	3800	400	5B	135000
	1805	79070	67530	59930	59250	59250	52240	9.3	26.8	1800	3800	400	5B	135000

316M L

414

134390 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
L1	4.25	134390	126150	123700	118560	89820	72960	280	*	350	500	—	—	192000
	5.33	122190	111300	99520	99520	86750	70460	280	*	350	500	—	—	192000
L2	17.4	134390	126150	123700	118560	80680	65530	200	*	1500	1800	—	—	192000
	21.8	122190	111300	99520	99520	86750	70460	200	*	1500	1800	—	—	192000
	22.3	134390	126150	123700	118560	78790	64000	200	49	1500	1800	—	—	192000
	26.5	118110	113640	113640	113640	77820	63210	200	64	1500	1800	—	—	192000
	28.0	122190	111300	99520	99520	86750	70460	200	52	1500	1800	—	—	192000
	33.2	122190	111300	99520	99520	86750	70460	200	62	1500	1800	—	—	192000
L3	59.6	129890	126150	123700	110340	68080	55300	115	61	1500	2500	3300	6L	192000
	71.1	134390	126150	123700	107660	66430	53960	115	64	1500	2500	2750	6K	192000
	76.5	134390	126150	123700	118560	78790	64000	115	59	1500	2500	2200	6G	192000
	89.3	122190	111300	99520	99520	77870	63250	115	59	1500	2500	2200	6G	192000
	96.0	122190	111300	99520	99520	86750	70460	115	55	1500	2500	1600	6E	192000
	114	122190	111300	99520	99520	86750	70460	115	52	1500	2500	1600	6E	192000
	117	134390	126150	123700	118560	77250	62750	115	61	1500	2500	1600	6E	192000
	139	134390	126150	123700	118560	76300	61980	115	58	1500	2500	1600	6E	192000
	165	118110	113640	113640	113640	77820	63210	115	54	1500	2500	1200	6C	192000
L3	174	122190	111300	99520	99520	86750	70460	115	54	1500	2500	1200	6C	192000
	207	122190	111300	99520	99520	86750	70460	102	51	1500	2500	1200	6C	192000

C



316M L

414

134390 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
L4	215	129890	126150	123700	110340	68080	55300	60	45	1800	3800	800	5G	192000
	253	129890	126150	123700	110340	68080	55300	60	46	1800	3800	800	5G	192000
	275	134390	126150	123700	118560	78790	64000	60	43	1800	3800	630	5E	192000
	318	129890	126150	123700	110340	68080	55300	60	44	1800	3800	630	5E	192000
	346	122190	111300	99520	99520	86750	70460	60	40	1800	3800	500	5C	192000
	399	122190	111300	99520	99520	79810	64830	60	42	1800	3800	400	5B	192000
	447	129890	126150	123700	107360	66240	53810	60	39	1800	3800	400	5B	192000
	500	134390	126150	123700	118560	76300	61980	57	36	1800	3800	400	5B	192000
	563	118110	113640	113640	113640	77820	63210	45	38	1800	3800	400	5B	192000
	628	122190	111300	99520	99520	86750	70460	41	34	1800	3800	400	5B	192000
	706	122190	111300	99520	99520	86750	70460	37	36	1800	3800	400	5B	192000
	784	122190	111300	99520	99520	86750	70460	33	36	1800	3800	400	5B	192000
	880	118110	113640	113640	113640	77820	63210	29	34	1800	3800	400	5B	192000
	1020	122190	111300	99520	99520	75110	61010	26	32	1800	3800	400	5B	192000
	1104	122190	111300	99520	99520	86750	70460	24	32	1800	3800	400	5B	192000
	1237	118110	113640	113640	113640	77820	63210	20	31	1800	3800	400	5B	192000
	1308	122190	111300	99520	99520	86750	70460	19.9	31	1800	3800	400	5B	192000
	1553	122190	111300	99520	99520	86750	70460	16.8	29.7	1800	3800	400	5B	192000

C

317M L

424

207490 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
L1	4.09	207490	196240	189230	171410	121500	98690	300	*	200	300	—	—	393000
	5.25	195640	167510	148950	142330	118660	96380	300	*	200	300	—	—	393000
	6.23	150260	128480	114130	112960	112960	95190	300	*	200	300	—	—	393000
L2	16.9	207490	196240	189230	171410	109610	89030	250	46	1000	1300	—	—	393000
	22.1	179820	166930	166930	166930	106860	86800	250	66	1000	1300	—	—	393000
	26.6	125790	121300	121300	121300	103860	84360	250	69	1000	1300	—	—	393000
	28.4	195640	167510	148950	142330	118660	96380	250	64	1000	1300	—	—	393000
	34.1	155950	155950	148950	142330	118660	96380	250	67	1000	1300	—	—	393000
	40.5	150260	128480	114130	112960	112960	95190	250	61	1000	1300	—	—	393000
L3	58.1	187760	187760	183040	148670	91740	74510	150	34	1500	2000	2750	6K	393000
	69.3	207490	196240	178590	145060	89510	72700	150	47	1500	2000	2750	6K	393000
	89.0	207490	196240	174410	141670	87410	71000	150	58	1500	2000	2750	6K	393000
	106	193690	193690	172260	139920	86340	70130	150	58	1500	2000	2200	6G	393000
	116	179820	166930	166930	166930	105230	85470	150	54	1500	2000	2200	6G	393000
	138	179820	166930	166930	166930	103930	84420	150	54	1500	2000	1600	6E	393000
	166	125790	121300	121300	121300	103860	84360	131	51	1500	2000	1200	6C	393000
	179	155950	155950	148950	142330	118660	96380	150	49	1500	2000	1200	6C	393000
	213	155950	155950	148950	142330	118660	96380	126	49	1500	2000	900	6B	393000
	252	150260	128480	114130	112960	112960	95190	102	45	1500	2000	900	6B	393000
L4	378	207500	196240	174410	141670	87410	71000	60	45	1800	3800	800	5G	393000
	449	193690	193690	172260	139920	86340	70130	60	42	1800	3800	500	5C	393000
	493	179820	166930	166930	166930	105230	85470	60	42	1800	3800	400	5B	393000
	552	207490	196240	174410	141670	87410	71000	60	41	1800	3800	400	5B	393000
	619	179820	166930	166930	166930	105230	85470	60	40	1800	3800	400	5B	393000
	719	179820	166930	166930	166930	105230	85470	53	38	1800	3800	400	5B	393000
	792	193690	193690	172260	139920	86340	70130	52	37	1800	3800	400	5B	393000
	904	155950	155950	148950	142330	118660	96380	37	36	1800	3800	400	5B	393000
	1032	179820	166930	166930	166930	103930	84420	37	34	1800	3800	400	5B	393000
	1134	155950	155950	148950	142330	118660	96380	29	35	1800	3800	400	5B	393000
	1318	155950	155950	148950	142330	118660	96380	25	33	1800	3800	400	5B	393000
	1595	155950	155950	148950	142330	118660	96380	21	32	1800	3800	400	5B	393000
	1893	150260	128480	114130	112960	112960	95190	16.9	30	1800	3800	400	5B	393000



318M L

434

297550 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
L1	4.40	297550	260520	231720	223900	160590	130440	340	*	200	300	—	—	500000
L2	18.7	297550	260520	231720	223900	160590	130440	260	131	500	900	—	—	500000
	23.5	297550	260520	231720	223900	160590	130440	260	127	500	900	—	—	500000
	27.3	264700	256140	231720	223900	160590	130440	260	123	500	900	—	—	500000
L3	76.5	297550	260520	231720	223900	160590	130440	200	58	1500	1800	3300	6L	500000
	98.2	297550	260520	231720	223900	160590	130440	200	77	1500	1800	3300	6L	500000
	117	297550	260520	231720	223900	160590	130440	200	80	1500	1800	3300	6L	500000
	123	297550	260520	231720	223900	160590	130440	200	74	1500	1800	3300	6L	500000
	146	297550	260520	231720	223900	160590	130440	200	75	1500	1800	2750	6K	500000
	170	264700	256140	231720	223900	160590	130440	200	73	1500	1800	2200	6G	500000
L4	262	297550	260520	231720	223900	160590	130440	115	69	1500	2500	1600	6E	500000
	313	297550	260520	231720	223900	160590	130440	115	70	1500	2500	1200	6C	500000
	337	297550	260520	231720	223900	160590	130440	115	66	1500	2500	1200	6C	500000
	402	297550	260520	231720	223900	160590	130440	115	69	1500	2500	900	6B	500000
	422	297550	260520	231720	223900	160590	130440	115	62	1500	2500	900	6B	500000
	477	297550	260520	231720	223900	160590	130440	111	66	1500	2500	900	6B	500000
	515	297550	260520	231720	223900	160590	130440	102	65	1500	2500	900	6B	500000
	612	297550	260520	231720	223900	160590	130440	86	62	1500	2500	900	6B	500000
	647	297550	260520	231720	223900	160590	130440	82	62	1500	2500	900	6B	500000
	726	297550	260520	231720	223900	160590	130440	73	59	1500	2500	900	6B	500000
	768	297550	260520	231720	223900	160590	130440	69	59	1500	2500	900	6B	500000
	911	297550	260520	231720	223900	160590	130440	58	56	1500	2500	900	6B	500000
	1059	264700	256140	231720	223900	160590	130440	44	54	1500	2500	900	6B	500000

319 L

444

471190 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
L1	4.88	471190	383900	311830	253280	156280	126940	380	*	200	300	—	—	680000
	5.77	356270	305830	272430	249240	153790	124910	380	*	200	300	—	—	680000
L2	20.7	471190	383900	311830	253280	156280	126940	260	165	500	900	—	—	680000
	24.5	356270	305830	272430	249240	153790	124910	260	157	500	900	—	—	680000
	26.0	471190	383900	311830	253280	156280	126940	260	162	500	900	—	—	680000
	30.8	356270	305830	272430	249240	153790	124910	260	155	500	900	—	—	680000
	35.8	336430	305830	272430	249240	153790	124910	260	155	500	900	—	—	680000
L3	84.8	471190	383900	311830	253280	156280	126940	200	85	1500	1800	—	—	680000
	100	356270	305830	272430	249240	153790	124910	200	84	1500	1800	—	—	680000
	109	471190	383900	311830	253280	156280	126940	200	106	1500	1800	—	—	680000
	126	356270	305830	272430	249240	153790	124910	200	85	1500	1800	—	—	680000
	129	443030	383900	311830	253280	156280	126940	200	108	1500	1800	—	—	680000
	137	471190	383900	311830	253280	156280	126940	200	102	1500	1800	—	—	680000
	162	356270	305830	272430	249240	153790	124910	200	98	1500	1800	—	—	680000
	188	288420	284000	283990	253280	156280	126940	200	97	1500	1800	—	—	680000
	192	356270	305830	272430	249240	153790	124910	200	98	1500	1800	—	—	680000
	223	336430	305830	272430	249240	153790	124910	200	94	1500	1800	—	—	680000
L4	291	471190	383900	311830	253280	156280	126940	115	92	1500	2500	2200	6G	680000
	347	471190	383900	311830	253280	156280	126940	115	91	1500	2500	2200	6G	680000
	410	356270	305830	272430	249240	153790	124910	115	89	1500	2500	1200	6C	680000
	445	471190	383900	311830	253280	156280	126940	115	89	1500	2500	2200	6G	680000
	515	356270	305830	272430	249240	153790	124910	115	84	1500	2500	900	6B	680000
	528	406490	383900	311830	253280	156280	126940	115	83	1500	2500	900	6B	680000
	558	471190	383900	311830	253280	156280	126940	115	84	1500	2500	900	6B	680000
	571	443030	383900	311830	253280	156280	126940	115	82	1500	2500	900	6B	680000
	625	356270	305830	272430	249240	153790	124910	101	82	1500	2500	900	6B	680000
	678	433020	383900	311830	253280	156280	126940	113	78	1500	2500	900	6B	680000

C



319 L

444

471190 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
L4	717	471190	383900	311830	253280	156280	126940	115	79	1500	2500	900	6B	680000
	802	356270	305830	272430	249240	153790	124910	79	78	1500	2500	900	6B	680000
	850	438750	383900	311830	253280	156280	126940	92	75	1500	2500	900	6B	680000
	912	336430	305830	272430	249240	153790	124910	65	71	1500	2500	900	6B	680000
	1007	356270	305830	272430	249240	153790	124910	63	72	1500	2500	900	6B	680000
	1195	356270	305830	272430	249240	153790	124910	53	68	1500	2500	900	6B	680000
	1389	336430	305830	272430	249240	153790	124910	43	66	1500	2500	900	6B	680000

321 L

454

655740 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
L1	4.44	655740	517290	420170	341290	210580	171050	540	*	200	300	—	—	934000
L2	18.2	655740	517290	420170	341290	210580	171050	300	*	200	300	—	—	934000
	23.3	655740	517290	420170	341290	210580	172000	300	*	200	300	—	—	934000
	27.7	536350	517290	420170	341290	210580	171050	300	*	200	300	—	—	934000
L3	75.3	655740	517290	420170	341290	210580	171050	250	132	1000	1200	—	—	934000
	98.2	655740	517290	420170	341290	210580	171050	250	135	1000	1200	—	—	934000
	118	655740	517290	420170	341290	210580	171050	250	132	1000	1200	—	—	934000
	126	655740	517290	420170	341290	210580	172000	250	127	1000	1200	—	—	934000
	152	655740	517290	420170	341290	210580	172000	250	125	1000	1200	—	—	934000
	180	536350	517290	420170	341290	210580	171050	250	115	1000	1200	—	—	934000
L4	258	655740	517290	420170	341290	210580	171050	150	101	1500	2000	2200	6G	934000
	308	655740	517290	420170	341290	210580	171050	150	105	1500	2000	2200	6G	934000
	395	655740	517290	420170	341290	210580	171050	150	107	1500	2000	2200	6G	934000
	469	655740	517290	420170	341290	210580	171050	150	103	1500	2000	1600	6E	934000
	515	655740	517290	420170	341290	210580	171050	150	98	1500	2000	1600	6E	934000
	612	655740	517290	420170	341290	210580	171050	150	95	1500	2000	1200	6C	934000
	736	655740	517290	420170	341290	210580	171050	130	90	1500	2000	900	6B	934000
	796	655740	517290	420170	341290	210580	172000	120	88	1500	2000	900	6B	934000
	945	655740	517290	420170	341290	210580	172000	101	86	1500	2000	900	6B	934000
	1122	536350	517290	420170	341290	210580	171050	79	81	1500	2000	900	6B	934000

323 L

464

890310 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
L1	4.60	890310	829940	742050	602740	371910	302080	850	*	150	250	—	—	1580000
L2	19.6	890310	829940	742050	602740	371910	302080	380	*	200	300	—	—	1580000
	22.4	890310	829940	742050	602740	371910	302080	380	*	200	300	—	—	1580000
	26.5	890310	829940	742050	602740	371910	302080	380	*	200	300	—	—	1580000
	33.1	890310	829940	742050	602740	371910	302080	380	*	200	300	—	—	1580000
L3	83.3	890310	829940	742050	602740	371910	302080	260	179	500	800	—	—	1580000
	105	890310	829940	742050	602740	371910	302080	260	167	500	800	—	—	1580000
	113	890310	829940	742050	602740	371910	302080	260	157	500	800	—	—	1580000
	120	890310	829940	742050	602740	371910	302080	260	155	500	800	—	—	1580000
	142	890310	829940	742050	602740	371910	302080	260	149	500	800	—	—	1580000
	165	890310	829940	742050	602740	371910	302080	260	144	500	800	—	—	1580000
	205	890310	829940	742050	602740	371910	302080	210	135	500	800	—	—	1580000
L4	341	890310	829940	742050	602740	371910	302080	200	97	1500	1800	3300	6L	1580000
	390	890310	829940	742050	602740	371910	302080	200	93	1500	1800	3300	6L	1580000



323 L

464

890310 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
L4	438	890310	829940	742050	602740	371910	302080	200	109	1500	1800	3300	6L	1580000
	500	890310	829940	742050	602740	371910	302080	200	102	1500	1800	3300	6L	1580000
	569	890310	829940	742050	602740	371910	302080	200	87	1500	1800	2750	6K	1580000
	628	890310	829940	742050	602740	371910	302080	200	96	1500	1800	2750	6K	1580000
	703	890310	829940	742050	602740	371910	302080	197	99	1500	1800	2750	6K	1580000
	758	890310	829940	742050	602740	371910	302080	182	97	1500	1800	2750	6K	1580000
	882	890310	829940	742050	602740	371910	302080	157	92	1500	1800	2750	6K	1580000
	1025	890310	829940	742050	602740	371910	302080	135	89	1500	1800	2750	6K	1580000
	1101	890310	829940	742050	602740	371910	302080	126	88	1500	1800	2750	6K	1580000
	1280	890310	829940	742050	602740	371910	302080	108	85	1500	1800	2750	6K	1580000

325 L

468

1286700 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
L1	4.60	1286700	1166950	947860	769900	475050	385860	1050	*	120	250	—	—	2000000
L2	19.6	1286600	1104050	896760	729000	449450	365060	380	*	200	300	—	—	2000000
	22.4	1286700	1083740	880270	715000	441180	358350	380	*	200	300	—	—	2000000
	26.5	1286700	1066430	866210	703580	434130	352630	380	*	200	300	—	—	2000000
	33.1	963170	963170	845000	686160	423380	343890	380	*	200	300	—	—	2000000
L3	83.3	1286600	1104050	896760	728400	449450	365060	260	206	500	800	—	—	2000000
	105	1286600	1104050	896760	728400	449450	365060	260	192	500	800	—	—	2000000
	113	1286700	1066430	866210	703580	434130	352630	260	181	500	800	—	—	2000000
	120	1286700	1083740	880270	715000	441180	358350	260	177	500	800	—	—	2000000
	142	1286700	1066430	866210	703580	434130	352630	260	170	500	800	—	—	2000000
	165	1286700	1066430	866210	703580	434130	352630	260	164	500	800	—	—	2000000
	205	963170	963170	845000	686160	423380	343890	226	154	500	800	—	—	2000000
L4	341	1286600	1104050	896760	728400	449450	365060	200	120	1500	1800	3300	6L	2000000
	390	1286700	1083740	880270	715000	441180	358350	200	113	1500	1800	3300	6L	2000000
	438	1286600	1104050	896760	728400	449450	365060	200	128	1500	1800	3300	6L	2000000
	500	1286700	1083740	880270	715000	441180	358350	200	120	1500	1800	3300	6L	2000000
	569	1286700	1083740	880270	715000	441180	358350	200	105	1500	1800	3300	6L	2000000
	628	1286700	1083740	880270	715000	441180	358350	200	113	1500	1800	3300	6L	2000000
	703	1286700	1066430	866210	703580	434130	352630	200	115	1500	1800	3300	6L	2000000
	758	1286600	1104050	896760	728400	449450	365060	200	113	1500	1800	2750	6K	2000000
	882	1286700	1066430	866210	703580	434130	352630	200	108	1500	1800	2750	6K	2000000
	1025	1286700	1066430	866210	703580	434130	352630	193	104	1500	1800	2750	6K	2000000
	1101	963170	963170	845120	686350	423550	343890	135	102	1500	1800	2750	6K	2000000
	1280	963170	963170	845120	686350	423550	343890	116	99	1500	1800	2750	6K	2000000

C



C

25.8 RATING CHARTS FOR RIGHT ANGLE UNITS 300M R

Reading the rating chart.



* BONFIGLIOLI TECHNICAL SERVICE

Rated hydraulic brake torque lower than applicable torque

1	Reference torque
2	Number of reduction stages (right-angled gear unit)
3	Gear ratio
4	Gearbox rated output torque based on: - service factor f_S=1 - $n_2 \cdot h$ indicated
5	Maximum power transmitted to the input shaft
6	Gearbox thermal capacity
7	Input angular speed for continuous duty
8	Maximum input angular speed for intermittent duty 20% based 60 min running
9	Rated brake torque (Hydraulic brake)
10	Negative multidisc hydraulic brake
11	Maximum output torque at gearbox
12	Page where dimensions can be sorted from

C



300 R

264

1250 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
R2	7.13	760	730	730	730	730	730	15.0	12.3	2000	4000	160	4D	2000
	8.74	1250	1070	950	860	840	720	15.0	12.3	2000	4000	160	4D	2400
	11.8	860	730	650	650	650	630	12.2	10.1	2000	4000	100	4B	2400
	14.8	700	600	550	550	550	510	8.3	8.8	2000	4000	100	4B	2400
	18.5	460	390	370	370	370	370	4.5	8.4	2000	4000	100	4B	2400
R3	24.8	760	730	730	730	730	730	6.2	7.8	2000	4000	50	4A	2000
	30.4	1250	1070	950	860	840	720	6.6	7.8	2000	4000	50	4A	2400
	37.3	1250	1070	950	860	840	720	5.5	7.9	2000	4000	50	4A	2400
	41.2	860	730	650	650	650	630	3.6	6.9	2000	4000	50	4A	2400
	50.4	1250	1070	950	860	840	720	4.3	7.1	2000	4000	50	4A	2400
	62.9	1250	1070	950	860	840	720	3.5	6.5	2000	4000	50	4A	2400
	68.2	860	730	650	650	650	630	2.4	6.3	2000	4000	50	4A	2400
	78.7	1250	1070	950	860	840	720	2.9	6.2	2000	4000	50	4A	2400
	85.2	860	730	650	650	650	630	2.0	5.8	2000	4000	50	4A	2400
	106	860	730	650	650	650	630	1.7	5.6	2000	4000	50	4A	2400
	133	700	600	550	550	550	510	1.2	5.2	2000	4000	50	4A	2400
R4	106	1250	1070	950	860	840	720	2.2	5.7	2000	4000	50	4A	2400
	130	1250	1070	950	860	840	720	1.8	5.7	2000	4000	50	4A	2400
	143	860	730	650	650	650	630	1.4	5.1	2000	4000	50	4A	2400
	159	1250	1070	950	860	840	720	1.5	5.7	2000	4000	50	4A	2400
	175	1250	1070	950	860	840	720	1.3	5.3	2000	4000	50	4A	2400
	215	1250	1070	950	860	840	720	1.1	5.3	2000	4000	50	4A	2400
	237	860	730	650	650	650	630	0.86	4.9	2000	4000	50	4A	2400
	268	1250	1070	950	860	840	720	0.88	5.0	2000	4000	50	4A	2400
	291	1250	1070	950	860	840	720	0.81	4.8	2000	4000	50	4A	2400
	363	1250	1070	950	860	840	720	0.65	4.6	2000	4000	50	4A	2400
	394	860	730	650	650	650	630	0.52	4.5	2000	4000	50	4A	2400
	453	1250	1070	950	860	840	720	0.52	4.3	2000	4000	50	4A	2400
	491	860	730	650	650	650	630	0.41	4.3	2000	4000	50	4A	2400
	613	860	730	650	650	650	630	0.33	4.1	2000	4000	50	4A	2400
	766	860	730	650	650	650	630	0.27	4.0	2000	4000	50	4A	2400

301 R

274

2060 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
R2	7.13	1490	1430	1430	1430	1430	1300	15.0	13.9	2000	4000	260	4F	3200
	8.74	2060	2060	1890	1730	1580	1280	15.0	14.4	2000	4000	330	4H	3200
	11.8	1720	1460	1300	1300	1300	1240	15.0	12.2	2000	4000	260	4F	3200
	14.8	1150	1150	1150	1150	1150	940	15.0	10.7	2000	4000	160	4D	3200
	18.5	920	780	740	740	740	740	8.0	10.1	2000	4000	160	4D	3200
R3	24.8	1490	1430	1430	1430	1430	1300	12.4	8.9	2000	4000	100	4B	3400
	30.4	2460	2140	1900	1730	1580	1280	13.1	9.0	2000	4000	100	4B	3400
	37.3	2460	2140	1900	1730	1580	1280	10.8	9.0	2000	4000	100	4B	3400
	41.2	1720	1460	1300	1300	1300	1240	7.3	7.9	2000	4000	100	4B	3400
	50.4	2460	2140	1900	1730	1580	1280	8.4	8.0	2000	4000	100	4B	3400
	62.9	2000	2000	1830	1730	1580	1280	7.0	7.3	2000	4000	50	4A	3400
	68.2	1720	1460	1300	1300	1300	1240	4.8	7.1	2000	4000	50	4A	3400
	78.7	1600	1600	1600	1600	1530	1280	5.8	7.0	2000	4000	50	4A	3400
	85.2	1720	1460	1300	1300	1300	1240	4.0	6.6	2000	4000	50	4A	3400
	106	1720	1460	1300	1300	1300	1240	3.3	6.3	2000	4000	50	4A	3400
	133	1150	1150	1150	1150	1150	940	2.0	5.8	2000	4000	50	4A	3400
R4	106	2460	2140	1900	1730	1580	1280	4.5	6.3	2000	4000	50	4A	3400
	130	2460	2140	1900	1730	1580	1280	3.6	6.3	2000	4000	50	4A	3400
	143	1720	1460	1300	1300	1300	1240	2.7	5.8	2000	4000	50	4A	3400
	159	2460	2140	1900	1730	1580	1280	3.0	6.3	2000	4000	50	4A	3400

C



301 R

274

2060 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
R4	175	2460	2140	1900	1730	1580	1280	2.7	5.9	2000	4000	50	4A	3400
	215	2460	2140	1900	1730	1580	1280	2.2	5.8	2000	4000	50	4A	3400
	237	1720	1460	1300	1300	1300	1240	1.7	5.3	2000	4000	50	4A	3400
	268	2460	2140	1900	1730	1580	1280	1.8	5.5	2000	4000	50	4A	3400
	291	2460	2140	1900	1730	1580	1280	1.6	5.3	2000	4000	50	4A	3400
	363	2460	2140	1900	1730	1580	1280	1.3	5.0	2000	4000	50	4A	3400
	394	1720	1460	1300	1300	1300	1240	1.0	4.9	2000	4000	50	4A	3400
	453	2000	2000	1830	1730	1580	1280	1.0	4.7	2000	4000	50	4A	3400
	491	1720	1460	1300	1300	1300	1240	0.82	4.7	2000	4000	50	4A	3400
	613	1720	1460	1300	1300	1300	1240	0.66	4.4	2000	4000	50	4A	3400
	766	1720	1460	1300	1300	1300	1240	0.52	4.3	2000	4000	50	4A	3400

303 R

284

2970 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
R2	9.23	2410	2310	2310	2310	2310	1940	35	18.1	1800	3800	330	4H	5200
	10.9	2970	2810	2810	2650	2570	2090	35	18.3	1800	3800	330	4H	5200
	13.7	2850	2520	2230	2200	2140	2030	32	16.3	1800	3800	260	4F	5200
	15.9	2440	2080	1840	1820	1820	1820	23	14.4	1800	3800	260	4F	5200
	19.2	2000	1750	1650	1650	1650	1500	17.2	13.1	1800	3800	160	4D	5200
	24.8	1050	900	860	860	860	860	7.0	11.2	1800	3800	160	4D	5200
R3	25.7	2410	2310	2310	2310	2130	1730	15.0	10.6	2.000	4.000	160	4D	5200
	31.5	2410	2310	2310	2310	2100	1700	15.0	10.6	2.000	4.000	100	4B	5200
	37.1	2970	2810	2810	2650	2350	1910	15.0	10.7	2.000	4.000	100	4B	5200
	42.6	2410	2210	2210	2210	2030	1650	11.6	9.3	2.000	4.000	100	4B	5200
	46.6	2850	2520	2230	2200	2140	2030	11.2	10.0	2.000	4.000	100	4B	5200
	50.3	2770	2700	2650	2620	2280	1850	12.2	9.3	2.000	4.000	100	4B	5200
	54.2	2440	2080	1840	1820	1820	1820	8.1	9.2	2.000	4.000	100	4B	5200
	63.1	2850	2520	2230	2200	2140	2030	8.7	8.8	2.000	4.000	100	4B	5200
	73.3	2440	2080	1840	1820	1820	1820	6.2	8.2	2.000	4.000	50	4A	5200
	78.7	2850	2450	2230	2200	2140	2030	7.1	8.0	2.000	4.000	50	4A	5200
	91.5	2440	2080	1840	1820	1820	1820	5.2	7.5	2.000	4.000	50	4A	5200
	114	2300	2080	1840	1820	1820	1820	4.3	7.2	2.000	4.000	50	4A	5200
R4	129	2970	2810	2810	2650	2390	1940	5.1	7.2	2.000	4.000	50	4A	5200
	148	2410	2310	2310	2310	2130	1730	3.6	6.5	2.000	4.000	50	4A	5200
	158	2970	2810	2810	2650	2350	1910	4.3	7.1	2.000	4.000	50	4A	5200
	185	2410	2310	2310	2310	2130	1730	2.9	6.1	2.000	4.000	50	4A	5200
	214	2970	2810	2810	2650	2350	1910	3.2	6.5	2.000	4.000	50	4A	5200
	231	2440	2080	1840	1820	1820	1820	2.4	6.3	2.000	4.000	50	4A	5200
	255	2440	2080	1840	1820	1820	1820	2.1	5.9	2.000	4.000	50	4A	5200
	290	2770	2700	2650	2620	2280	1850	2.2	5.9	2.000	4.000	50	4A	5200
	313	2440	2080	1840	1820	1820	1820	1.7	5.9	2.000	4.000	50	4A	5200
	336	2850	2520	2230	2200	2140	2030	2.0	5.8	2.000	4.000	50	4A	5200
	364	2850	2520	2230	2200	2140	2030	1.9	5.7	2.000	4.000	50	4A	5200
	390	2440	2080	1840	1820	1820	1820	1.4	5.5	2.000	4.000	50	4A	5200
	452	2250	2250	2250	2250	1830	1800	1.2	5.2	2.000	4.000	50	4A	5200
	528	2440	2080	1840	1820	1820	1820	1.0	5.1	2.000	4.000	50	4A	5200
	567	2850	2450	2230	2200	2140	2030	1.2	5.0	2.000	4.000	50	4A	5200
	659	2440	2080	1840	1820	1820	1820	0.83	4.7	2.000	4.000	50	4A	5200
	797	2000	1750	1650	1650	1650	1500	0.59	4.6	2.000	4.000	50	4A	5200
	824	2440	2080	1840	1820	1820	1820	0.66	4.6	2.000	4.000	50	4A	5200

C



304 R

296

3960 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
R2	9.23	3710	3520	3500	3220	2390	1940	35	18.0	1800	3800	330	4H	6600
	10.9	3960	3750	3690	3540	2680	2180	35	18.6	1800	3800	330	4H	6600
	13.7	3740	3190	2850	2850	2850	2560	35	16.7	1800	3800	260	4F	6600
	16.8	3000	2560	2390	2390	2390	2390	28	13.8	1800	3800	260	4F	6600
R3	25.7	3710	3520	3500	3440	3080	2830	15.0	10.8	2.000	4.000	160	4D	7300
	31.5	3710	3520	3500	3440	3080	2830	15.0	10.9	2.000	4.000	100	4B	7300
	37.1	3960	3750	3690	3540	3430	2780	15.0	11.0	2.000	4.000	100	4B	7300
	42.6	3710	3520	3500	3440	3120	2830	15.0	9.7	2.000	4.000	100	4B	7300
	46.6	3740	3190	2850	2850	2850	2710	14.2	10.3	2.000	4.000	100	4B	7300
	50.3	3960	3750	3690	3540	3430	2780	15.0	9.8	2.000	4.000	100	4B	7300
	63.1	3740	3190	2850	2850	2850	2710	10.9	9.2	2.000	4.000	100	4B	7300
	78.7	3740	3190	2850	2850	2850	2710	9.0	8.5	2.000	4.000	100	4B	7300
	97.0	3010	2560	2390	2390	2390	2390	5.9	7.6	2.000	4.000	50	4A	7300
	121	3010	2560	2390	2390	2390	2390	4.9	7.4	2.000	4.000	50	4A	7300
R4	89.4	3710	3520	3500	3440	3120	2830	9.4	7.4	2.000	4.000	50	4A	7300
	109	3710	3520	3500	3440	3120	2830	7.8	7.4	2.000	4.000	50	4A	7300
	129	3960	3750	3690	3540	3430	2780	7.1	7.5	2.000	4.000	50	4A	7300
	148	3710	3520	3500	3440	3120	2830	5.9	6.7	2.000	4.000	50	4A	7300
	158	3960	3750	3690	3540	3430	2780	5.9	7.5	2.000	4.000	50	4A	7300
	185	3710	3520	3500	3440	3080	2830	4.7	6.2	2.000	4.000	50	4A	7300
	214	3960	3750	3690	3540	3430	2780	4.4	6.8	2.000	4.000	50	4A	7300
	227	3710	3520	3500	3440	3120	2830	3.9	6.3	2.000	4.000	50	4A	7300
	267	3960	3750	3690	3540	3430	2780	3.5	6.3	2.000	4.000	50	4A	7300
	290	3960	3750	3690	3540	3430	2780	3.2	6.2	2.000	4.000	50	4A	7300
	307	3710	3520	3500	3440	3120	2830	2.9	5.8	2.000	4.000	50	4A	7300
	338	3010	2560	2390	2390	2390	2390	1.9	5.6	2.000	4.000	50	4A	7300
	364	3740	3190	2850	2850	2850	2710	2.3	5.9	2.000	4.000	50	4A	7300
	414	3010	2560	2390	2390	2390	2390	1.6	5.5	2.000	4.000	50	4A	7300
	452	3960	3710	3660	3540	3430	2780	2.1	5.4	2.000	4.000	50	4A	7300
	560	3010	2560	2390	2390	2390	2390	1.2	5.1	2.000	4.000	50	4A	7300
	699	3010	2560	2390	2390	2390	2390	0.93	4.9	2.000	4.000	50	4A	7300

305 R

308

5600 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
R2	9.23	4650	4050	4000	3870	2390	1940	35	17.8	1800	3800	440	4L	7700
	10.9	5300	4720	4720	4350	2680	2180	35	18.5	1800	3800	440	4L	7700
	13.7	5600	5040	4470	4280	3150	2560	35	17.0	1800	3800	440	4L	7700
	15.9	4690	4000	3600	3600	3500	2840	35	15.1	1800	3800	330	4H	7700
	19.2	3800	3300	3100	3100	3000	2790	32	14.0	1800	3800	260	4F	7700
R3	25.7	4680	4490	4490	4490	3800	3090	15.0	10.9	2000	4000	260	4F	8800
	31.5	4700	4490	4490	4490	3750	3040	15.0	11.2	2000	4000	260	4F	8800
	37.1	5800	5500	5480	5300	4210	3420	15.0	11.3	2000	4000	260	4F	8800
	42.6	4700	4450	4430	4430	3630	2950	15.0	10.0	2000	4000	160	4D	8800
	46.6	5600	5040	4470	4400	4280	3490	15.0	10.6	2000	4000	160	4D	8800
	50.3	5530	5350	5300	5230	4070	3310	15.0	10.0	2000	4000	160	4D	8800
	54.2	4690	4000	3600	3600	3550	3460	15.0	9.8	2000	4000	100	4B	8800
	63.1	5600	5040	4470	4400	4280	3490	15.0	9.4	2000	4000	100	4B	8800
	73.3	4690	4000	3600	3600	3550	3460	12.3	8.8	2000	4000	100	4B	8800
	78.7	5600	4900	4470	4400	4280	3490	14.3	8.7	2000	4000	100	4B	8800
	91.5	4690	4000	3600	3600	3550	3460	10.2	8.1	2000	4000	100	4B	8800
	114	4430	4000	3600	3600	3500	3460	8.6	7.9	2000	4000	50	4A	8800
R4	129	5800	5480	5480	5300	4270	3470	10.3	7.6	2000	4000	50	4A	8800
	148	4700	4490	4490	4490	3800	3090	7.4	6.9	2000	4000	50	4A	8800
	158	5800	5500	5480	5300	4210	3420	8.6	7.6	2000	4000	50	4A	8800



305 R

308

5600 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
R4	185	4700	4490	4490	4490	3800	3090	6.0	6.4	2000	4000	50	4A	8800
	214	5800	5500	5480	5300	4210	3420	6.4	6.9	2000	4000	50	4A	8800
	231	4690	4000	3600	3600	3550	3460	4.7	6.8	2000	4000	50	4A	8800
	255	4690	4000	3600	3600	3550	3460	4.3	6.3	2000	4000	50	4A	8800
	290	5530	5400	5300	5230	4070	3310	4.5	6.3	2000	4000	50	4A	8800
	313	4690	4000	3600	3600	3550	3460	3.5	6.2	2000	4000	50	4A	8800
	336	5600	5040	4470	4400	4280	3490	3.9	6.1	2000	4000	50	4A	8800
	364	5600	5040	4470	4400	4280	3490	3.6	6.0	2000	4000	50	4A	8800
	390	4690	4000	3600	3600	3550	3460	2.8	5.8	2000	4000	50	4A	8800
	452	4750	4750	4750	4750	3660	3210	2.5	5.5	2000	4000	50	4A	8800
	528	4690	4000	3600	3600	3550	3460	2.1	5.4	2000	4000	50	4A	8800
	567	5600	4900	4470	4400	4280	3490	2.3	5.3	2000	4000	50	4A	8800
	659	4690	4000	3600	3600	3550	3460	1.7	5.0	2000	4000	50	4A	8800
	797	3800	3300	3100	3100	3000	2790	1.1	4.8	2000	4000	50	4A	8800
	824	4690	4000	3600	3600	3550	3460	1.3	4.8	2000	4000	50	4A	8800

306 R

320

7300 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
R2	9.23	4650	4050	4000	3870	2390	1940	35	18.8	1800	3800	440	4L	12000
	10.9	5300	4720	4720	4350	2680	2180	35	19.9	1800	3800	440	4L	12000
	13.7	6500	5920	5920	5100	3150	2560	35	18.2	1800	3800	440	4L	12000
	15.9	7300	6890	6530	5670	3500	2840	35	16.3	1800	3800	440	4L	12000
	19.2	7000	5900	5500	5400	3990	3240	35	15.2	1800	3800	400	4K	12000
R3	33.2	8020	8020	8020	8020	5680	4620	35	14.3	2000	4000	260	4F	14900
	39.2	9770	9340	9340	9300	6110	4960	35	14.6	2000	4000	260	4F	14900
	46.3	10420	9850	9850	9600	6860	5570	35	14.8	2000	4000	260	4F	14900
	58.1	9560	9100	9100	9100	6680	5430	35	13.6	2000	4000	260	4F	14900
	67.5	7890	7590	7590	7590	6620	5380	25	12.4	2000	4000	260	4F	14900
	72.9	10080	9350	8300	7950	6810	5530	27	12.7	2000	4000	160	4D	14900
	84.7	9540	9350	8300	7950	6810	5530	23	11.6	2000	4000	160	4D	14900
	98.5	8630	7370	6530	6500	6460	5480	17.7	10.8	2000	4000	100	4B	14900
	119	8500	7370	6530	6500	6460	5480	15.2	10.1	2000	4000	100	4B	14900
	144	7000	5900	5500	5500	5040	5040	10.7	9.7	2000	4000	100	4B	14900
R4	158	10420	9850	9850	9600	6860	5570	14.9	9.9	2000	4000	100	4B	14900
	168	8320	7700	7700	7530	5950	4830	11.3	9.3	2000	4000	100	4B	14900
	181	9450	9450	9450	9450	6970	5660	11.6	8.9	2000	4000	100	4B	14900
	214	10420	9850	9850	9600	6860	5570	11.1	8.9	2000	4000	50	4A	14900
	230	7890	7590	7590	7590	6620	5380	7.7	8.8	2000	4000	50	4A	14900
	249	10080	9350	8300	7950	6810	5530	9.0	8.9	2000	4000	50	4A	14900
	289	9540	9350	8300	7950	6810	5530	7.6	8.3	2000	4000	50	4A	14900
	312	7890	7590	7590	7590	6620	5380	5.7	7.9	2000	4000	50	4A	14900
	389	8500	7590	7590	7590	6620	5380	5.2	7.3	2000	4000	50	4A	14900
	420	10080	9350	8300	7950	6810	5530	5.4	7.4	2000	4000	50	4A	14900
	455	8630	7370	6530	6500	6460	5480	4.4	7.2	2000	4000	50	4A	14900
	488	9540	9350	8300	7950	6810	5530	4.5	7.0	2000	4000	50	4A	14900
	550	8500	7370	6530	6500	6460	5480	3.7	6.8	2000	4000	50	4A	14900
	590	9500	8500	7800	7800	6810	5530	3.8	6.7	2000	4000	50	4A	14900
	665	7000	5900	5500	5500	5040	5040	2.5	6.5	2000	4000	50	4A	14900
	830	7000	5900	5500	5500	5040	5040	2.0	6.1	2000	4000	50	4A	14900

C



307 R

332

14000 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
R2	13.0	9000	8500	8270	7960	6570	5340	85	*	1800	3800	1000	5K	18600
	15.5	11400	10690	9630	9520	7440	6040	85	*	1800	3800	1000	5K	21000
	19.8	14000	12700	11300	10790	8850	7190	85	*	1800	3800	800	5G	21000
	23.5	11000	9600	8700	8700	8240	7490	74	*	1800	3800	500	5C	21000
R3	31.6	9000	9000	9000	8300	5490	4460	35	17.3	2000	4000	400	4K	18600
	37.7	15680	14890	12400	10070	6210	5050	35	16.6	2000	4000	440	4L	21000
	44.6	15680	14890	13930	11310	6980	5670	35	16.8	2000	4000	400	4K	21000
	55.9	15680	14890	14890	13260	8180	6650	35	15.8	2000	4000	330	4H	21000
	65.0	14670	14010	14010	13510	9090	7380	35	14.6	2000	4000	260	4F	21000
	71.8	14840	12700	11300	10790	9340	7590	35	15.2	2000	4000	260	4F	21000
	78.6	12300	12300	12300	12300	9560	7770	35	13.8	2000	4000	260	4F	21000
	83.4	14840	12700	11300	10790	9340	7590	33	14.1	2000	4000	260	4F	21000
	99.0	11000	9600	8700	8700	8240	7490	23	13.1	2000	4000	160	4D	21000
	120	11000	9600	8700	8700	8240	7490	19.9	12.4	2000	4000	160	4D	21000
R4	152	15680	14890	14890	13510	9560	7770	15.0	11.9	2000	4000	100	4B	21000
	165	14840	12700	11300	10790	9340	7590	15.0	11.5	2000	4000	100	4B	21000
	191	15680	14890	14890	13510	9560	7770	15.0	11.2	2000	4000	100	4B	21000
	206	15680	14890	14890	13510	9560	7770	15.0	10.8	2000	4000	100	4B	21000
	232	14840	12700	11300	10790	9340	7590	14.3	10.3	2000	4000	100	4B	21000
	258	15680	14890	14890	13510	9560	7770	13.8	10.2	2000	4000	100	4B	21000
	284	14840	12700	11300	10790	9340	7590	11.6	10.2	2000	4000	100	4B	21000
	300	15000	14010	14010	13510	9560	7770	11.8	9.6	2000	4000	100	4B	21000
	331	14840	12700	11300	10790	9340	7590	10.0	9.9	2000	4000	50	4A	21000
	363	12300	12300	12300	12300	9560	7770	8.0	9.1	2000	4000	50	4A	21000
	413	14840	12700	11300	10790	9340	7590	8.0	9.3	2000	4000	50	4A	21000
	453	15000	13800	12900	12500	9560	7770	7.8	8.5	2000	4000	50	4A	21000
	490	11000	9600	8700	8700	8240	7490	5.3	8.7	2000	4000	50	4A	21000
	581	14330	12710	11300	10790	9340	7590	5.7	8.3	2000	4000	50	4A	21000
	690	11000	9600	8700	8700	8240	7490	3.8	7.9	2000	4000	50	4A	21000

309 R

344

16460 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
R2	13.0	9800	9120	8270	7960	6570	5340	85	*	1800	3800	1000	5K	27400
	15.5	11400	10690	9630	9520	7440	6040	85	*	1800	3800	1000	5K	27400
	19.8	14000	13270	12270	12270	8850	7190	85	*	1800	3800	1000	5K	27400
	23.5	16460	14070	12500	12370	9980	8110	85	*	1800	3800	800	5G	27400
R3	31.6	12800	12310	10960	8900	5490	4460	35	23.7	2000	4000	440	4L	27900
	37.7	15830	15260	12400	10070	6210	5050	35	23.0	2000	4000	440	4L	29000
	44.6	18670	17150	13930	11310	6980	5670	35	23.3	2000	4000	400	4K	29000
	55.9	18510	17140	16330	13260	8180	6650	35	21.8	2000	4000	400	4K	29000
	65.0	14670	14300	14300	14010	9090	7380	35	19.9	2000	4000	260	4F	29000
	71.8	21980	19060	16940	15790	9740	7910	35	21.0	2000	4000	330	4H	29000
	83.4	18300	18100	16940	16190	10830	8790	35	19.3	2000	4000	260	4F	29000
	99.0	17000	14400	13000	13000	12210	9910	35	18.0	2000	4000	260	4F	29000
	120	17000	14400	13000	13000	12370	10280	30	16.9	2000	4000	160	4D	29000
R4	152	21620	21260	21260	18580	11460	9310	15.0	15.8	2000	4000	160	4D	29000
	165	21980	19060	16940	16190	12810	10410	15.0	15.4	2000	4000	160	4D	29000
	191	18510	17500	17500	17140	11160	9070	15.0	14.9	2000	4000	160	4D	29000
	206	21620	21260	21260	18580	11460	9310	15.0	14.2	2000	4000	160	4D	29000
	232	18300	18100	16940	16190	12810	10410	15.0	13.7	2000	4000	100	4B	29000
	258	18510	17500	17500	17140	11160	9070	15.0	13.4	2000	4000	100	4B	29000
	284	18300	18100	16940	16190	12810	10410	15.0	13.6	2000	4000	100	4B	29000
	331	21980	19060	16940	16190	12810	10410	15.0	13.1	2000	4000	100	4B	29000
	374	14670	14300	14300	14010	11060	8990	9.2	11.7	2000	4000	100	4B	29000



309 R

344

16460 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
R4	413	21980	19060	16940	16190	12810	10410	12.0	12.1	2000	4000	100	4B	29000
	457	17000	14400	13000	13000	12370	10280	8.8	11.7	2000	4000	50	4A	29000
	490	17000	14400	13000	13000	12370	10280	8.2	11.5	2000	4000	50	4A	29000
	581	15800	15800	15800	15000	12810	10410	6.4	10.9	2000	4000	50	4A	29000
	690	17000	14400	13000	13000	12370	10280	5.8	10.4	2000	4000	50	4A	29000

310M R

356

33640 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
R2	12.0	24880	24320	24320	24320	15600	12670	130	*	1500	2500	3300	6L	47600
	15.4	30110	25640	22700	21660	18580	15090	130	*	1500	2500	2750	6K	47600
	18.3	23930	20350	18000	17810	17810	16620	130	*	1500	2500	2200	6G	47600
	16.6	33640	31900	29360	26500	17870	14510	130	*	1500	2500	2750	6K	47600
	21.3	30110	25640	22700	21660	20710	16820	130	*	1500	2500	2750	6K	47600
	25.3	23930	20350	18000	17810	17810	16620	118	*	1500	2500	2200	6G	47600
R3	37.7	15800	14860	12070	9800	6050	4910	35	27.7	1800	3800	440	4L	47600
	44.6	18640	16690	13550	11010	6790	5520	35	28.4	1800	3800	440	4L	47600
	55.9	23360	19570	15890	12910	7960	6470	35	26.6	1800	3800	440	4L	47600
	65.0	26060	21740	17660	14340	8850	7190	35	24.6	1800	3800	440	4L	47600
	71.8	29930	23300	18920	15370	9480	7700	35	25.4	1800	3800	440	4L	47600
	78.6	19480	19330	19330	16390	10110	8210	35	23.2	1800	3800	330	4H	47600
	83.4	30110	25640	21030	17080	10540	8560	35	23.6	1800	3800	400	4K	47600
	99.0	23930	20350	18000	17810	11880	9650	35	21.4	1800	3800	330	4H	47600
	120	23930	20350	18000	17810	13580	11030	35	20.4	1800	3800	260	4F	47600
R4	136	30730	30730	28700	23310	14380	11680	35	20.0	2000	4000	260	4F	47600
	160	33640	31900	29360	25750	15890	12910	35	20.9	2000	4000	260	4F	47600
	189	33640	31900	29360	26500	17850	14500	35	21.0	2000	4000	260	4F	47600
	206	30110	25640	22700	21660	18920	15370	35	20.1	2000	4000	260	4F	47600
	238	33640	31900	29360	26500	17380	14110	33	19.6	2000	4000	160	4D	47600
	258	30110	25640	22700	21660	18420	14960	28	18.8	2000	4000	160	4D	47600
	276	28060	28070	28070	26500	17220	13990	24	18.2	2000	4000	160	4D	47600
	305	30110	25640	22700	21660	20710	16820	23	18.9	2000	4000	160	4D	47600
	347	33170	30650	29360	26500	17700	14380	22.6	17.2	2000	4000	160	4D	47600
	383	30110	25640	22700	21660	20710	16820	18.6	17.7	2000	4000	100	4B	47600
	454	23930	20350	18000	17810	17810	16620	12.5	16.3	2000	4000	100	4B	47600
	517	30110	25640	22700	21660	20710	16820	13.8	15.6	2000	4000	100	4B	47600
	590	19480	19330	19330	19330	17120	13900	7.8	14.6	2000	4000	50	4A	47600
	639	23930	20350	18000	17810	17810	16620	8.9	14.5	2000	4000	50	4A	47600
	757	24820	24820	22700	21660	20380	16550	7.8	14.1	2000	4000	50	4A	47600
	898	23930	20350	18000	17810	17810	16620	6.3	13.2	2000	4000	50	4A	47600

311M R

368

49210 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
R2	12.0	24880	24320	24320	24320	15600	12670	150	*	1500	2500	3300	6L	58300
	15.4	31190	31190	31190	30110	18580	15090	150	*	1500	2500	3300	6L	58300
	18.3	36470	31040	27480	27190	20950	17020	150	*	1500	2500	2750	6K	58300
	16.6	45390	43900	35650	28960	17870	14510	150	*	1500	2500	3300	6L	58300
	21.3	47810	41400	36690	34490	21280	17280	150	*	1500	2500	2750	6K	58300
	25.3	36470	31040	27480	27190	23990	19490	150	*	1500	2500	2200	6G	58300

C



311M R

368

49210 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
R3	53.0	32410	32420	32420	27690	17090	13880	85	24.0	2000	4000	800	5G	58300
	63.2	41360	39670	38580	31340	19340	15710	85	23.5	2000	4000	800	5G	58300
	68.0	41500	41400	36690	32980	20350	16530	85	23.4	2000	4000	800	5G	58300
	81.1	47810	41400	36690	35010	23030	18700	85	22.7	2000	4000	800	5G	58300
	96.3	33520	32020	32020	32020	23990	19490	77	21.8	2000	4000	500	5C	58300
	104	47810	41400	36690	35010	27420	22270	85	22.3	2000	4000	500	5C	58300
	124	41250	41170	36690	35010	28570	23200	77	21.1	2000	4000	400	5B	58300
	147	36470	31040	27480	27190	27190	23670	55	20.2	2000	4000	400	5B	58300
R4	154	49210	38650	31380	25490	15730	12780	35	23.8	2000	4000	440	4L	58300
	182	49210	43410	35250	28630	17670	14350	35	23.8	2000	4000	330	4H	58300
	198	47810	41400	36690	30360	18730	15220	35	22.8	2000	4000	260	4F	58300
	229	49210	46590	41340	33570	20710	16830	35	22.5	2000	4000	260	4F	58300
	266	49210	46590	45450	37310	23010	18700	35	21.0	2000	4000	260	4F	58300
	294	47810	41400	36690	35010	24670	20040	35	21.6	2000	4000	160	4D	58300
	341	47810	41400	36690	35010	27410	22260	33	20.3	2000	4000	160	4D	58300
	413	47810	41400	36690	35010	29500	23960	27	19.2	2000	4000	160	4D	58300
	438	47810	41400	36690	35010	28930	23490	26	19.6	2000	4000	160	4D	58300
	490	33520	32020	32020	32020	23990	19490	16.2	18.1	2000	4000	100	4B	58300
	520	41250	41170	36690	35010	28570	23200	18.8	18.5	2000	4000	100	4B	58300
	629	41250	41170	36690	35010	28570	23200	15.5	17.5	2000	4000	100	4B	58300
	746	36470	31040	27480	27190	27190	23670	11.6	16.8	2000	4000	100	4B	58300

C

313M R

380

60940 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
R2	12.2	25160	24620	24620	24620	15740	12790	150	*	1500	2500	3300	6L	86300
	15.9	32070	32070	32070	30710	18950	15390	150	*	1500	2500	3300	6L	86300
	19.1	38580	34160	30260	30200	21580	17530	150	*	1500	2500	3300	6L	86300
	16.8	45900	44290	35970	29210	18030	14640	150	*	1500	2500	3300	6L	105000
	22.0	57130	48700	43150	35170	21700	17630	150	*	1500	2500	3300	6L	105000
	26.4	40100	34160	30260	30200	24710	20070	150	*	1500	2500	2750	6K	105000
R3	53.7	35830	33520	33520	27940	17240	14000	85	28.9	1800	3800	800	5G	105000
	64.0	41820	40180	38930	31620	19510	15850	85	28.6	1800	3800	800	5G	105000
	69.9	45180	44000	41410	33630	20750	16860	85	27.2	1800	3800	800	5G	105000
	82.2	52030	51920	46350	37650	23230	18870	85	28.2	1800	3800	800	5G	105000
	97.5	50810	48640	48640	42450	26190	21270	85	26.7	1800	3800	630	5E	105000
	107	57130	48700	43150	41440	27970	22720	85	26.3	1800	3800	630	5E	105000
	127	57130	48700	43150	41440	31530	25610	85	24.9	1800	3800	500	5C	105000
	153	40100	34160	30260	30200	30200	29160	53	23.9	1800	3800	400	5B	105000
R4	185	57650	43780	35560	28890	17820	14480	35	29.1	2000	4000	400	4K	105000
	201	60940	46420	37700	30630	18900	15350	35	28.0	2000	4000	400	4K	105000
	237	60940	52150	42350	34400	21230	17240	35	28.0	2000	4000	260	4F	105000
	281	50810	48640	47760	38780	23930	19440	35	26.1	2000	4000	260	4F	105000
	309	57130	48700	43150	41420	25550	20760	35	26.0	2000	4000	260	4F	105000
	346	60940	57660	55180	44810	27650	22460	35	24.4	2000	4000	260	4F	105000
	387	57130	48700	43150	41440	29970	24340	35	24.4	2000	4000	160	4D	105000
	450	57130	48700	43150	41440	33300	27040	30	22.9	2000	4000	160	4D	105000
	496	50810	48640	48640	48640	33200	26970	24	21.6	2000	4000	160	4D	105000
	535	57130	48700	43150	41440	37540	30490	25	21.6	2000	4000	160	4D	105000
	647	57130	48700	43150	41440	39970	32460	21	20.4	2000	4000	100	4B	105000
	778	40100	34160	30260	30200	30200	30200	12.2	19.6	2000	4000	100	4B	105000



314M R

392

80640 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
R3	51.1	79616	75696	66528	54032	33344	27080	130	42	1500	2500	2200	6G	115000
	65.5	78024	72432	72432	64352	39704	32248	130	42	1500	2500	2200	6G	115000
	77.8	61848	59496	59488	59488	43712	35504	130	39	1500	2500	2200	6G	115000
	82.3	73312	67496	62304	59720	46544	37808	130	40	1500	2500	2200	6G	115000
	97.6	73304	67496	62304	59720	51240	41616	126	37	1500	2500	2200	6G	115000
	113	63256	54024	47944	47400	47400	41792	93	36	1500	2500	2200	6G	115000
	70.7	80640	75696	75696	61888	38176	31016	130	42	1500	2500	2200	6G	115000
	90.7	78016	72432	72432	71136	44248	35936	130	41	1500	2500	3300	6L	115000
	108	61848	59496	59488	59488	43712	35504	98	37	1500	2500	2750	6K	115000
	114	73312	67496	62304	59720	51864	42128	109	38	1500	2500	2750	6K	115000
	135	73304	67496	62304	59720	51240	41616	93	35	1500	2500	2200	6G	115000
	157	63256	54024	47944	47400	47400	41792	69	35	1500	2500	2200	6G	115000
R4	160	52250	39680	32230	26180	16160	13120	35	45	1800	3800	440	4L	115000
	189	58690	44570	36200	29410	18150	14740	35	45	1800	3800	440	4L	115000
	238	68810	52250	42440	34470	21270	17280	35	42	1800	3800	400	4K	115000
	276	76460	58060	47160	38310	23640	19200	35	39	1800	3800	400	4K	115000
	354	91050	69130	56160	45620	28150	22870	35	37	1800	3800	400	4K	115000
	421	77310	74370	63340	51430	31730	25780	31	34	1800	3800	330	4H	115000
	445	73312	64864	52664	42784	26400	21448	35	35	1800	3800	400	4K	115000
	528	73312	67496	59400	48232	29760	24176	30	33	1800	3800	330	4H	115000
	614	63256	54024	47944	47400	33080	26864	22	32	1800	3800	260	4F	115000

C

315M R

404

100800 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
R3	51.1	99510	94620	83160	67540	41680	33850	150	42	1500	2500	2750	6K	135000
	65.5	100800	94620	94620	80440	49630	40310	150	42	1500	2500	2200	6G	135000
	77.8	100800	94620	94620	88920	55960	45450	150	40	1500	2500	2200	6G	135000
	82.3	91640	84370	77880	74650	58180	47260	150	39	1500	2500	1600	6E	135000
	97.6	91640	84370	77880	74650	65060	52850	150	38	1500	2500	1600	6E	135000
	113	79070	67530	59930	59250	59250	52240	116	37	1500	2500	900	6B	135000
	70.7	100800	94620	94620	77360	47720	38770	150	42	1500	2500	2200	6G	135000
	90.7	100800	94620	94620	88920	56840	46170	150	41	1500	2500	1600	6E	135000
	108	100800	94620	94620	88920	64090	52050	150	39	1500	2500	1600	6E	135000
	114	91630	84370	77880	74650	65060	52850	136	38	1500	2500	1200	6C	135000
	135	91630	84370	77880	74650	65060	52850	116	36	1500	2500	1200	6C	135000
	157	79070	67530	59930	59250	59250	52240	87	35	1500	2500	900	6B	135000
R4	225	100800	94620	91070	73970	45640	37070	90	37	1800	3800	630	5E	135000
	269	100800	94620	94620	83700	51650	41950	80	36	1800	3800	500	5C	135000
	345	100800	94620	94620	88920	61500	49960	62	35	1800	3800	400	5B	135000
	409	100800	94620	94620	88920	64070	52040	52	33	1800	3800	400	5B	135000
	525	100800	94620	94620	88920	67360	54720	41	31	1800	3800	400	5B	135000
	623	100800	94620	94620	88920	67360	54720	34	30	1800	3800	400	5B	135000
	659	91640	84370	77880	74650	65060	52850	30	30	1800	3800	400	5B	135000
	782	91640	84370	77880	74650	65060	52850	25	28.9	1800	3800	400	5B	135000
	909	79070	67530	59930	59250	59250	52240	18.5	28.4	1800	3800	400	5B	135000



316M R

416

134390 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
R3	51.1	99520	99520	83160	67540	41680	33850	150	46	1500	2500	2750	6K	192000
	64.1	122190	111300	97490	79180	48860	39690	150	45	1500	2500	2750	6K	192000
	65.5	127370	121920	99020	80430	49630	40310	150	47	1500	2500	2750	6K	192000
	77.8	118110	113650	111640	90670	55950	45450	150	45	1500	2500	2200	6G	192000
	82.3	122180	111300	99530	94300	58180	47260	150	44	1500	2500	2200	6G	192000
	97.6	122180	111300	99530	99530	65600	53280	150	42	1500	2500	2200	6G	192000
	70.7	134400	117260	95220	77340	47720	38770	150	47	1500	2500	2200	6G	192000
	88.7	122190	111300	99530	90690	55950	45450	150	44	1500	2500	2200	6G	192000
	90.7	134400	126160	113420	92100	56830	46170	150	46	1500	2500	2200	6G	192000
	108	118110	113650	113640	103860	64070	52050	150	43	1500	2500	1600	6E	192000
	114	122190	111300	99530	99530	66640	54120	150	43	1500	2500	1600	6E	192000
	135	122190	111300	99530	99530	75130	61020	150	41	1500	2500	1600	6E	192000
R4	225	129890	112120	91060	73970	45640	37070	85	40	1800	3800	800	5G	192000
	269	134400	126160	103050	83700	51650	41950	85	39	1800	3800	630	5E	192000
	289	134400	126160	108440	88080	54350	44150	85	39	1800	3800	630	5E	192000
	337	122180	111300	99530	98120	60540	49180	77	37	1800	3800	500	5C	192000
	363	122190	111300	99530	99530	63710	51750	72	37	1800	3800	400	5B	192000
	430	122190	111300	99530	99530	71830	58340	60	35	1800	3800	400	5B	192000
	443	134400	126160	123700	118580	73240	59490	65	36	1800	3800	400	5B	192000
	525	134400	126160	123700	118580	76300	61980	54	34	1800	3800	400	5B	192000
	623	118110	113650	113640	113640	77820	63210	40	32	1800	3800	400	5B	192000
	659	122180	111300	99530	99530	86750	70460	39	32	1800	3800	400	5B	192000
	782	122190	111300	99530	99530	86750	70460	33	31	1800	3800	400	5B	192000

C

317M R

426

207490 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min^{-1}]	[min^{-1}]	[Nm]		[Nm]
R3	49.8	97030	97030	81690	66340	40940	33250	150	47	1500	2500	2750	6K	393000
	64.9	126120	121070	98330	79870	49280	40030	150	48	1500	2500	2750	6K	393000
	78.1	125800	121300	111970	90940	56110	45580	150	48	1500	2500	2750	6K	393000
	83.3	161300	144170	117090	95110	58690	47670	150	47	1500	2500	2750	6K	393000
	100	155950	155950	133340	108290	66820	54280	150	46	1500	2500	2200	6G	393000
	119	150260	128480	114130	112960	75340	61190	150	43	1500	2500	1600	6E	393000
	68.9	151620	115150	93530	75970	46880	38080	150	50	1500	2500	2750	6K	393000
	89.8	179830	138660	112600	91460	56440	45850	150	48	1500	2500	2750	6K	393000
	108	125790	121300	121300	104160	64260	52200	150	46	1500	2500	2200	6G	393000
	115	195640	165120	134080	108910	67200	54600	150	46	1500	2500	2200	6G	393000
	139	155940	155950	148950	124040	76520	62160	150	44	1500	2500	1600	6E	393000
	165	150260	128480	114130	112960	86290	70080	150	41	1500	2500	1200	6C	393000
R4	220	138860	110130	89450	72660	44830	36420	90	42	1800	3800	800	5G	393000
	262	164050	124620	101220	82220	50730	41210	90	41	1800	3800	800	5G	393000
	336	195360	148400	120540	97910	60410	49070	90	40	1800	3800	800	5G	393000
	399	193680	167310	135890	110380	68110	55320	90	38	1800	3800	630	5E	393000
	438	179830	166930	145110	117860	72730	59070	87	38	1800	3800	500	5C	393000
	520	179830	166930	163600	132870	81990	66600	74	36	1800	3800	400	5B	393000
	626	125790	121300	121300	121300	93360	75830	43	34	1800	3800	400	5B	393000
	677	155950	155950	148950	142350	98610	80090	49	35	1800	3800	400	5B	393000
	803	155940	155950	148950	142350	111170	90300	41	33	1800	3800	400	5B	393000
	953	150260	128480	114130	112960	112960	95190	34	32	1800	3800	400	5B	393000



318M R

436

297550 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
R4	225	297550	260540	227590	184830	114050	92650	150	62	1500	2500	1600	6E	500000
	288	297550	260540	231740	220140	135810	110320	150	60	1500	2500	1600	6E	500000
	342	297540	260540	231740	223920	153140	124380	150	58	1500	2500	1200	6C	500000
	362	297550	260540	231740	223920	159240	129330	146	58	1500	2500	1200	6C	500000
	430	297550	260540	231740	223920	160590	130440	123	55	1500	2500	900	6B	500000
	499	264710	256160	231740	223920	160590	130440	94	53	1500	2500	900	6B	500000
	311	297550	260540	231740	211740	130610	106110	150	61	1500	2500	1200	6C	500000
	399	297530	260540	231740	223920	155590	126360	132	58	1500	2500	900	6B	500000
	474	297550	260540	231740	223920	160590	130440	111	55	1500	2500	900	6B	500000
	501	297550	260540	231740	223920	160590	130440	105	55	1500	2500	900	6B	500000
	595	297550	260540	231740	223920	160590	130440	89	53	1500	2500	900	6B	500000
	691	264710	256160	231740	223920	160590	130440	68	50	1500	2500	900	6B	500000

319 R

446

471190 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
R4	249	396290	300980	244480	198580	122540	99540	150	85	1500	2500	2200	6G	680000
	320	471190	358410	291120	236470	145920	118530	150	82	1500	2500	2200	6G	680000
	379	443030	383900	311830	253280	156280	126940	150	76	1500	2500	1600	6E	680000
	401	471180	383900	311830	253280	156280	126940	150	78	1500	2500	1600	6E	680000
	475	356250	305810	272430	249240	153790	124910	133	74	1500	2500	1200	6C	680000
	563	356280	305810	272430	249240	153790	124910	112	72	1500	2500	900	6B	680000
	655	336410	305810	272430	249240	153790	124910	91	69	1500	2500	900	6B	680000
	345	453930	344660	279970	227410	140330	114010	150	82	1500	2500	1600	6E	680000
	442	471160	383900	311830	253280	156280	126940	150	78	1500	2500	1600	6E	680000
	525	443030	383900	311830	253280	156280	126940	150	72	1500	2500	1200	6C	680000
	555	471190	383900	311830	253280	156280	126940	150	74	1500	2500	900	6B	680000
	657	356250	305810	272430	249240	153790	124910	96	71	1500	2500	900	6B	680000
	780	356280	305810	272430	249240	153790	124910	81	68	1500	2500	900	6B	680000
	906	336410	305810	272430	249240	153790	124910	66	64	1500	2500	900	6B	680000

321 R

456

655200 Nm

	i	M_{n2} [Nm]						P_1	P_{TB}	n_1	n_{1max}	M_b		M_{2max}
		$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$	$n_2 \cdot h$							
	1:	10000	25000	50000	100000	500000	1000000	[kW]	[kW]	[min-1]	[min-1]	[Nm]		[Nm]
R4	221	374000	281300	226400	181800	111130	90320	150	113	1500	2500	2750	6K	934000
	288	447500	340100	268500	216800	133790	108740	150	106	1500	2500	2200	6G	934000
	347	506300	377100	307000	247800	152340	123900	150	101	1500	2500	2200	6G	934000
	370	528500	402100	317800	264200	159330	129500	150	101	1500	2500	2200	6G	934000
	446	587310	445420	366500	293970	181430	147460	150	97	1500	2500	2200	6G	934000
	529	536350	503040	410200	331430	204550	166260	150	91	1500	2500	1600	6E	934000
	306	401340	304660	247480	201030	124050	100790	150	110	1500	2500	2200	6G	934000
	399	483180	366770	297930	242020	149350	121350	150	101	1500	2500	2200	6G	934000
	481	550170	417600	339230	275560	170050	138170	132	96	1500	2500	1200	6C	934000
	512	575410	436760	354790	288200	177850	144510	125	97	1500	2500	1200	6C	934000
	617	655200	497290	403960	328150	202500	164540	120	92	1500	2500	1200	6C	934000
	732	536360	517290	420170	341290	210580	171050	113	86	1500	2500	900	6B	934000

C

26 DIMENSIONS

300 L

	Hydraulic motor MG							487			Kg
cm³	050	080	100	125	160	200	250				
	M1							M2	M3	M4	
300 L1	162	167	171	175	181	–	–	113	60	1/4G	14
300 L2	162	167	171	–	–	–	–	113	60	1/4G	14



	L				Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
300 L1	80	86	115	80	18	23	20	16
300 L2	133	139	168	133	22	27	24	20
300 L3	186	192	221	186	26	31	28	24
300 L4	239	245	274	239	30	35	32	28

	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
300 L1	137.5	24	6	158	38	7	37	A	477	105	65	1/4 G	4	A	10
300 L2	137.5	24	6	158	38	7	37	A		105	65	1/4 G	4	A	10
300 L3	137.5	24	6	158	38	7	37	A		105	65	1/4 G	4	A	10
300 L4	137.5	24	6	158	38	7	37	A		105	65	1/4 G	4	A	10

300 L



FP — M_{2max} = 1300 Nm

	P71		P80		P90		P100		P112		P132	
	E	P	E	P	E	P	E	P	E	P	E	P
300 L1	65	160	84	200	84	200	94	250	94	250	114	300
300 L2	65	160	84	200	84	200	94	250	94	250	114	300
300 L3	65	160	84	200	84	200	94	250	94	250	114	300
300 L4	65	160	84	200	84	200	94	250	94	250	114	300

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
300 L1	253	314	138	324	399	156	357	447	195	401	493	195	460	559	258
300 L2	253	314	138	324	399	156	357	447	195	401	493	195	460	559	258
300 L3	253	314	138	324	399	156	357	447	195	401	493	195	460	559	258
300 L4	253	314	138	324	399	156	357	447	195	401	493	195	460	559	258

300 R

	Hydraulic motor							487			Kg
	MG										
cm³	050	080	100	125	160	200	250				
	M1							M2	M3	M4	
300 R2	162	167	171	–	–	–	–	113	60	1/4G	14



	R				R1	Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK		MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
300 R2	172	178	207	172	122	32	37	34	30
300 R3	225	231	260	225	122	36	41	38	34
300 R4	278	284	313	278	122	40	45	42	38

	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
300 R2	137.5	24	6	158	38	7	37	A		105	65	1/4 G	4	A	10
300 R3	137.5	24	6	158	38	7	37	A		105	65	1/4 G	4	A	10
300 R4	137.5	24	6	158	38	7	37	A	477	105	65	1/4 G	4	A	10

300 R

















FP M_{2max} = 1300 Nm

	P71		P80		P90		P100		P112		P132	
	E	P	E	P	E	P	E	P	E	P	E	P
300 R2	65	160	84	200	84	200	94	250	94	250	114	300
300 R3	65	160	84	200	84	200	94	250	94	250	114	300
300 R4	65	160	84	200	84	200	94	250	94	250	114	300

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
300 R2	253	314	138	372	444	156	405	495	195	437	529	195	508	607	258
300 R3	253	314	138	372	444	156	405	495	195	437	529	195	–	–	–
300 R4	253	314	138	372	444	156	405	495	195	–	–	–	–	–	–

3/V 00 L3



FP M_{2max} = 1300 Nm

	L				Kg				P63	P71	P80
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	P	P	P
3/V 00 L3	255	261	290	255	25	30	27	23	140	160	200

3/A 00 L2



FP	M_{2max} = 1300 Nm

	L				Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
3/A 00 L2	193	199	228	193	38	43	40	36

	P63		P71		P80		P90		P100		S1/S10+ME1/MXN10			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L		
	L2	P	L2	P	L2	P	L2	P	L2	P	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y
3/A 00 L2	212.5	140	212.5	160	232	200	232	200	242	250	396.5	455.5	138	440.5	498	156	471.5	561.5	195	515.5	607.5	195



300 L | 300 R | 3/V 00 L3 | 3/A 00 L2

MC





PC



HC





MZ | HZ



FZ



FP





FDK



FP	M_{2max} = 1300 Nm



300 L | 300 R | 3/V 00 L3 | 3/A 00 L2

Flange

W0A







Material: Steel C40

Pinions

P...





$\alpha = 20°$

	m	z	x	dp	di	de	H	A	B	C	Material
PBE	4.5	14	0.507	63	56	75.5	55	—	—	—	Steel 39NiCrMo3 hardened and tempered
PCE	5	14	0.500	70	62.5	84.8	65	—	10	53	
PDC	6	12	0.250	72	61	84.8	59	14	4	54	
PDE	6	14	0.500	84	73	99.6	65	—	10	54	

Sleeve coupling

M0A





Material: Steel 16CrNi4

Splined bars

B0A



Material: Case hardening steel 18NiCrMo5 UNI 5331
must be case hardened 50-55 HRC

Shrink disc

G0A







300 L 300 R



		V	V1	V2	V4	V5	A	B	F	L	S	D	U
300 L1	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
300 L2	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
300 L3	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
300 L4	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
300 R2-R3-R4	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28

300 L 300 R



		C	D1	D2	D3	D4	D5	D6	L1	L2	L3	L4	L5	L6	S	S1	Input
300 L1	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	53	18	45°	45°	A
300 L2	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	106	18	45°	45°	A
300 L3	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	159	18	45°	45°	A
300 L4	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	212	18	45°	45°	A
300 R2-R3-R4	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	37	18	45°	45°	A

3/V 00 L3





	D1 h6	L3	L4	L6	L7	L8	d
3/V 00 L3_HS	16	65	40	16	5	18	M6

3/A 00 L2





	D1 h6	L3	L4	L6	L7	L8	d
3/A 00 L2_HS	16	179	40	16	5	18	M6

Permissible radial and axial loads on output shaft with $Fh_2 : n_2 \cdot h = 100000$





	An2 (+)	An2 (-)
MZ - MC PZ - PC	9200	6900
HZ - HC	20000	20000



	Rn2	An2 (+/-)
FZ	3713	3713

		$Fh_2 = n_2 \cdot h$	10000	25000	50000	100000	500000	1000000
Load corrective factor fh_2 on shafts	fh_2	FZ	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
		MZ - MC - PZ - PC	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
		HZ - HC	**1.27**	**1.27**	**1.26**	**1.00**	**0.62**	**0.50**

Permissible radial loads on input shaft with $Fh_1 : n_1 \cdot h = 250000$





Load corrective factor fh_1 on shafts	$Fh_1 = n_1 \cdot h$	250000	500000	1000000	2000000	5000000	10000000
	fh_1	**1**	**0.79**	**0.63**	**0.50**	**0.37**	**0.29**

301 L



	Hydraulic motor MG							487			Kg
cm³	050	080	100	125	160	200	250				
	M1							M2	M3	M4	
301 L1	–	167	171	175	181	188	197	113	60	1/4G	14
301 L2	162	167	171	175	181	–	–	113	60	1/4G	14

	L				Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
301 L1	92	132	126	92	21	26	23	19
301 L2	145	185	176	145	25	30	27	23
301 L3	198	238	232	198	29	34	31	27
301 L4	251	291	285	251	33	38	35	31

	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
301 L1	137.5	24	6	158	38	7	37	A	477	105	65	1/4 G	4	A	10
301 L2	137.5	24	6	158	38	7	37	A		105	65	1/4 G	4	A	10
301 L3	137.5	24	6	158	38	7	37	A		105	65	1/4 G	4	A	10
301 L4	137.5	24	6	158	38	7	37	A		105	65	1/4 G	4	A	10

301 L



FP M_{2max} = 2400 Nm

	P71		P80		P90		P100		P112		P132	
	E	P	E	P	E	P	E	P	E	P	E	P
301 L1	65	160	84	200	84	200	94	250	94	250	114	300
301 L2	65	160	84	200	84	200	94	250	94	250	114	300
301 L3	65	160	84	200	84	200	94	250	94	250	114	300
301 L4	65	160	84	200	84	200	94	250	94	250	114	300

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
301 L1	253	314	138	324	396	156	357	447	195	401	493	195	460	559	258
301 L2	253	314	138	324	396	156	357	447	195	401	493	195	460	559	258
301 L3	253	314	138	324	396	156	357	447	195	401	493	195	460	559	258
301 L4	253	314	138	324	396	156	357	447	195	401	493	195	460	559	258

301 R

	Hydraulic motor							487			Kg
	MG										
cm³	050	080	100	125	160	200	250				
	M1							M2	M3	M4	
301 R2	162	167	171	175	181	–	–	113	60	1/4G	14



	R				R1	Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK		MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
301 R2	184	225	219	184	122	35	42	37	33
301 R3	237	278	272	237	122	39	46	41	37
301 R4	290	331	325	290	122	43	50	45	41

	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
301 R2	137.5	24	6	158	38	7	37	A		105	65	1/4 G	4	A	10
301 R3	137.5	24	6	158	38	7	37	A		105	65	1/4 G	4	A	10
301 R4	137.5	24	6	158	38	7	37	A	477	105	65	1/4 G	4	A	10

301 R



FP M_{2max} = 2400 Nm

	P71		P80		P90		P100		P112		P132	
	E	P	E	P	E	P	E	P	E	P	E	P
301 R2	65	160	84	200	84	200	94	250	94	250	114	300
301 R3	65	160	84	200	84	200	94	250	94	250	114	300
301 R4	65	160	84	200	84	200	94	250	94	250	114	300

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
301 R2	253	314	138	372	444	156	405	495	195	449	541	195	508	607	258
301 R3	253	314	138	372	444	156	405	495	195	449	541	195	—	—	—
301 R4	253	314	138	372	444	156	405	495	195	—	—	—	—	—	—

3/V 01 L3



FP M_{2max} = 2400 Nm

	L				Kg				P63	P71	P80
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	P	P	P
3/V 01 L3	267	308	302	267	28	35	30	26	140	160	200

3/A 01 L2



FP M_{2max} = 2400 Nm

	L				Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
3/A 01 L2	202	208	237	202	40	46	43	40

	P63		P71		P80		P90		P100		S1/S10+ME1/MXN10			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L		
	L2	P	L2	P	L2	P	L2	P	L2	P	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y
3/A 01 L2	226	140	226	160	245.5	200	245.5	200	255.5	250	410	469	138	454	526	156	485	575	195	429	621	195



301 L | 301 R | 3/V 01 L3 | 3/A 01 L2























FP	M_{2max} = 2400 Nm



301 L | 301 R | 3/V 01 L3 | 3/A 01 L2

Flange

W0A







Material: Steel C40

Pinions

P...





$\alpha = 20°$

	m	z	x	dp	di	de	H	A	B	C	Material
PBE	4.5	14	0.507	63	56	75.5	55	—	—	—	Steel 39NiCrMo3 hardened and tempered
PCE	5	14	0.500	70	62.5	84.8	65	—	10	53	
PDC	6	12	0.250	72	61	84.8	59	14	4	54	
PDE	6	14	0.500	84	73	99.6	65	—	10	54	

Sleeve coupling

M0A





Material: Steel 16CrNi4

Splined bars

B0A



Material: Case hardening steel 18NiCrMo5 UNI 5331
must be case hardened 50-55 HRC

Shrink disc

G0A







301 L 301 R



		V	V1	V2	V4	V5	A	B	F	L	S	D	U
301 L1	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
301 L2	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
301 L3	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
301 L4	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
301 R2-R3-R4	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28

301 L 301 R



		C	D1	D2	D3	D4	D5	D6	L1	L2	L3	L4	L5	L6	S	S1	Input
301 L1	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	65	18	45°	45°	A
301 L2	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	118	18	45°	45°	A
301 L3	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	171	18	45°	45°	A
301 L4	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	224	18	45°	45°	A
301 R2-R3-R4	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	37	18	45°	45°	A

3/V 01 L3





	D1 h6	L3	L4	L6	L7	L8	d
3/V 01 L3_HS	16	65	40	16	5	18	M6

3/A 01 L2





	D1 h6	L3	L4	L6	L7	L8	d
3/A 01 L2_HS	19	235.5	40	16	6	21.5	M6

301 L | 301 R | 3/V 01 L3 | 3/A 01 L2

Permissible radial and axial loads on output shaft with $Fh_2 : n_2 \cdot h = 100000$





	An_2 (+)	An_2 (-)
MZ - MC	9200	6900
HZ - HC PZ - PC	20000	20000



	Rn_2	An_2 (+/-)
FZ	3713	3713

Load corrective factor fh_2 on shafts	$Fh_2 = n_2 \cdot h$	10000	25000	50000	100000	500000	1000000
	fh_2 FZ	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
	fh_2 MZ - MC	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
	fh_2 HZ - HC - PZ - PC	**1.27**	**1.27**	**1.26**	**1.00**	**0.62**	**0.50**

Permissible radial loads on input shaft with $Fh_1 : n_1 \cdot h = 250000$





Load corrective factor fh_1 on shafts	$Fh_1 = n_1 \cdot h$	250000	500000	1000000	2000000	5000000	10000000
	fh_1	**1**	**0.79**	**0.63**	**0.50**	**0.37**	**0.29**

303 L

	Hydraulic motor							487			Kg
	MG										
cm³	050	080	100	125	160	200	250				
	M1							M2	M3	M4	
303 L1	–	–	–	–	203	210	219	135	77	1/4G	20
303 L2	162	167	171	175	181	188	–	113	60	1/4G	14



	L				Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
303 L1	125	165	150	125	31	40	35	31
303 L2	178	218	203	178	35	44	39	35
303 L3	231	271	256	231	39	48	43	39
303 L4	284	324	309	284	43	52	47	43

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
303 L1	239	48	15	—	—	—	276	48	17	—	—	—	37	A		145	95	1/4 G	5	A	16
303 L2	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A		105	65	1/4 G	4	A	10
303 L3	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A	477	105	65	1/4 G	4	A	10
303 L4	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A		105	65	1/4 G	4	A	10

303 L



	PF 160		PF 180		PF 200		PF225	
	E1	P1	E1	P1	E1	P1	E1	P1
303 L1*	165	400	165	400	195	400	195	450
303 L2	165	400	165	400	—	—	—	—
303 L3	165	400	165	400	—	—	—	—

(*): contact Bonfiglioli technical service
NOTE: For R design contact Bonfiglioli Technical service

FP — M_{2max} = 5200 Nm

	P71		P80		P90		P100		P112		P132		P160		P180		P200	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
303 L1	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400
303 L2	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—
303 L3	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—
303 L4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4			S5+ME5S/MX5S			S5+ ME5L/MX5L		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
303 L1	—	—	—	—	—	—	—	—	—	—	—	—	460	559	258	552	692.5	310	596	736.5	310
303 L2	253	314	138	324	396	156	357	447	195	401	493	195	460	559	258	—	—	—	—	—	—
303 L3	253	314	138	324	396	156	357	447	195	401	493	195	460	559	258	—	—	—	—	—	—
303 L4	253	314	138	324	396	156	357	447	195	401	493	195	460	559	258	—	—	—	—	—	—

303 R

	Hydraulic motor							487			Kg
	MG										
cm³	050	080	100	125	160	200	250				
	M1							M2	M3	M4	
303 R2	162	167	171	175	181	188	—	113	60	1/4G	14







	R				R1	Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK		MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
303 R2	217	257	242	217	140	51	60	55	51
303 R3	270	310	295	270	122	49	58	53	49
303 R4	323	363	348	323	122	53	62	57	53

	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
303 R2	137.5	24	6	158	38	7	37	A		105	65	1/4 G	4	A	10
303 R3	137.5	24	6	158	38	7	37	A		105	65	1/4 G	4	A	10
303 R4	137.5	24	6	158	38	7	37	A	477	105	65	1/4 G	4	A	10

303 R

















FP | M_{2max} = 5200 Nm

	P71		P80		P90		P100		P112		P132	
	E	P	E	P	E	P	E	P	E	P	E	P
303 R2	65	160	84	200	84	200	94	250	94	250	114	300
303 R3	65	160	84	200	84	200	94	250	94	250	114	300
303 R4	65	160	84	200	84	200	94	250	94	250	114	300

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
303 R2	—	—	—	372	444	156	405	495	195	449	541	195	508	607	258
303 R3	253	314	138	372	444	156	405	495	195	449	541	195	—	—	—
303 R4	253	314	138	372	444	156	405	495	195	449	541	195	—	—	—

3/V 03 L3



PC



PZ





MC



MZ





HC



HZ





FP



FZ



FDK



FP M_{2max} = 5200 Nm

	L				Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
3/V 03 L3	270	330	315	270	43	51	45	41

	P71	P80	P90	S1+M1			S2+ME2S/MX2S		
	P	P	P	L1	L1f	Y	L1	L1f	Y
3/V 03 L3	160	200	200	289	350	138	351	—	156

3/A 03 L2



FP M_{2max} = 5200 Nm

	L				Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
3/A 03 L2	225	285	270	225	63	71	65	60

	P63		P71		P80		P90		P100		P112		S1/S10+ME1/MXN10			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L		
	L2	P	L2	P	L2	P	L2	P	L2	P	L2	P	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y
3/A 03 L2	243	140	243	160	262	200	262	200	272	250	272	250	427	486	138	471	543	156	502	592	195	546	638	195



303 L | 303 R | 3/V 03 L3 | 3/A 03 L2

MC HC





PC



MZ HZ





FZ



FP





FDK



FP	M_{2max} = 5200 Nm



303 L | 303 R | 3/V 03 L3 | 3/A 03 L2

Flange

W0A







Material: Steel C40

Pinions

P...





α = 20°

	m	z	x	dp	di	de	H	A	B	C	Material
PCL1	5	19	—	95	82	104	77	12	9	72	Steel 39NiCrMo3 hardened and tempered
PCL2	5	19	—	95	82	104	68	—	—	—	
PCM	5	20	—	100	87.5	110	68	18	—	—	Steel 18NiCrMo5 case hardened
PCP	5	22	—	110	97.5	120	68	18	—	—	
PDE	6	14	0.500	84	75	99.6	68	—	—	—	Steel 39NiCrMo3 hardened and tempered
PDI	6	18	0.500	108	99	123.6	68	—	—	—	
PDM	6	20	0.833	120	115	140	68	—	—	—	
PFD	8	13	0.675	104	95	127.6	68	—	—	—	Steel 18NiCrMo5 case hardened
PFE1	8	14	—	112	92	126	68	—	—	—	
PFE2	8	14	—	112	92	126	80	—	12	72	
PFF	8	15	—	120	100	136	68	—	—	—	Steel 39NiCrMo3 hardened and tempered
PFP	8	22	—	176	156	190	77	12	10	71	
PHG	10	16	0.500	160	145	188	75	—	7	72	

Sleeve coupling

M0A





Material: Steel 16CrNi4

Splined bars

B0A



Material: Case hardening steel 18NiCrMo5 UNI 5331
must be case hardened 50-55 HRC

Shrink disc

G0A







303 L 303 R



V_ _



FV_ _

		V	V1	V2	V4	V5	A	B	F	L	S	D	U
303 L1	**V05B**	239	48	82	155	245	14	9	51.5	70	6	M16	36
	FV05B	276	48	82	219.5	244	14	9	51.5	70	6	M16	36
303 L2	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
303 L3	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
303 L4	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
303 R2-R3-R4	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28

303 L 303 R





		C	D1	D2	D3	D4	D5	D6	L1	L2	L3	L4	L5	L6	S	S1	Input
303 L1	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	—	18	45°	45°	A
303 L2	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	53	18	45°	45°	A
303 L3	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	106	18	45°	45°	A
303 L4	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	159	18	45°	45°	A
303 R2-R3-R4	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	37	18	45°	45°	A

3/V 03 L3





	D1 h6	L3	L4	L6	L7	L8	d
3/V 03 L3_HS	18	110.5	40	16	6	20.5	M6

3/A 03 L2







	D1 h6	L3	L4	L6	L7	L8	d
3/A 03 L2_HS	19	252.5	40	16	6	21.5	M6

303 L | 303 R | 3/V 03 L3 | 3/A 03 L2

Permissible radial and axial loads on output shaft with $Fh_2 : n_2 \cdot h = 100000$





	An2 (+)	An2 (-)
MZ - MC	25300	20240
HZ - HC PZ - PC	27500	22000



	Rn2	An2 (+/-)
FZ	11140	11604

	$Fh_2 = n_2 \cdot h$	10000	25000	50000	100000	500000	1000000
Load corrective factor fh_2 on shafts	FZ	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
	fh_2 MZ - MC	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
	HZ - HC - PZ - PC	**1.48**	**1.48**	**1.23**	**1.00**	**0.62**	**0.50**

Permissible radial loads on input shaft with $Fh_1 : n_1 \cdot h = 250000$





	$Fh_1 = n_1 \cdot h$	250000	500000	1000000	2000000	5000000	10000000
Load corrective factor fh_1 on shafts	fh_1	**1**	**0.79**	**0.63**	**0.50**	**0.37**	**0.29**

303 VK



	PF 160		PF 180		PF 200		PF225	
	E1	P1	E1	P1	E1	P1	E1	P1
303 L1	165	400	165	400	195	400	195	450
303 L2	165	400	165	400	—	—	—	—
303 L3	165	400	165	400	—	—	—	—

NOTE: For R design contact Bonfiglioli Technical service

	L	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	P71		P80		P90		P100		P112		P132		P160		P180		P200	
															E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
303 L1	51	65	239	48	15	—	—	—	276	48	17	—	—	—	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400
303 L2	104	70	137.5	24	6	158	38	7	—	—	—	—	—	—	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—
303 L3	157	73	137.5	24	6	158	38	7	—	—	—	—	—	—	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—
303 L4	210	77	137.5	24	6	158	38	7	—	—	—	—	—	—	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—

	S1+M1			S2+ME2S			S3+ME3S			S3+ME3L			S4+ME4/MX4			S5+ME5S/MX5S			S5+ME5L/MX5L		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
303 L1	—	—	—	—	—	—	—	—	—	—	—	—	460	559	258	552	692.5	310	596	736.5	310
303 L2	253	314	138	280	350	156	325	421	195	357	448	195	460	559	258	—	—	—	—	—	—
303 L3	253	314	138	280	350	156	325	421	195	357	448	195	460	559	258	—	—	—	—	—	—
303 L4	253	314	138	280	350	156	325	421	195	357	448	195	460	559	258	—	—	—	—	—	—

	R	R1	Kg	V	V1	Kg	V	V1	Kg	P71		P80		P90		P100		P112		P132	
										E	P	E	P	E	P	E	P	E	P	E	P
303 R2	143	140	85	137.5	24	6	158	38	7	65	160	84	200	84	200	94	250	94	250	114	300
303 R3	196	122	83	137.5	24	6	158	38	7	65	160	84	200	84	200	94	250	94	250	114	300
303 R4	249	122	87	137.5	24	6	158	38	7	65	160	84	200	84	200	94	250	94	250	114	300

	S1+ M1			S2+ ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
303 R2	—	—	—	372	444	156	405	495	195	449	541	195	508	607	258
303 R3	253	314	138	372	444	156	405	495	195	449	541	195	—	—	—
303 R4	253	314	138	372	444	156	405	495	195	449	541	195	—	—	—

303 VK

The diagram below allows the calculation of permitted overhung load R_{x2} on the output shaft of gearbox, with radial force applying at a distance x from shaft shoulder.
The curves are relevant to value resulting from the relationship of trust load A_{n2} to radial load R_{n2}, based on n_2 = 10 min^{-1} and 10000 hrs theoretical lifetime.



304 L



	Hydraulic motor							487			Kg
	MG										
cm³	050	080	100	125	160	200	250				
	M1							M2	M3	M4	
304 L1	–	–	–	–	203	210	219	135	77	1/4G	20
304 L2	162	167	171	175	181	188	–	113	60	1/4G	14

	L				Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
304 L1	125	165	150	125	31	40	35	31
304 L2	190	230	215	190	38	47	42	38
304 L3	243	283	268	243	42	51	46	42
304 L4	296	336	321	296	46	55	50	46

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
304 L1	239	48	15	—	—	—	276	48	17	—	—	—	37	A		145	95	1/4 G	5	A	16
304 L2	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A		105	65	1/4 G	4	A	10
304 L3	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A	477	105	65	1/4 G	4	A	10
304 L4	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A		105	65	1/4 G	4	A	10

304 L



	PF 160		PF 180		PF 200		PF225	
	E1	P1	E1	P1	E1	P1	E1	P1
304 L1*	165	400	165	400	195	400	195	450
304 L2	165	400	165	400	—	—	—	—
304 L3	165	400	165	400	—	—	—	—

FP M_{2max} = 7300 Nm

(*): contact Bonfiglioli technical service
NOTE: For R design contact Bonfiglioli Technical service

	P71		P80		P90		P100		P112		P132		P160		P180		P200	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
304 L1	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400
304 L2	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—
304 L3	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—
304 L4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4			S5+ME5S/MX5S			S5+ME5L/MX5L		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
304 L1	—	—	—	—	—	—	—	—	—	—	—	—	460	559	258	552	692.5	310	596	736.5	310
304 L2	253	314	138	324	396	156	357	447	195	461	553	195	460	559	258	—	—	—	—	—	—
304 L3	253	314	138	324	396	156	357	447	195	461	553	195	460	559	258	—	—	—	—	—	—
304 L4	253	314	138	324	396	156	357	447	195	461	553	195	460	559	258	—	—	—	—	—	—



304 R

	Hydraulic motor							487			Kg
	MG										
cm³	050	080	100	125	160	200	250				
	M1							M2	M3	M4	
304 R2	162	167	171	175	181	188	—	113	60	1/4G	14



	R				R1	Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK		MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
304 R2	217	257	242	217	140	51	60	55	51
304 R3	282	322	307	282	122	52	61	56	52
304 R4	335	375	360	335	122	56	65	60	56

	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
304 R2	137.5	24	6	158	38	7	37	A		105	65	1/4 G	4	A	10
304 R3	137.5	24	6	158	38	7	37	A		105	65	1/4 G	4	A	10
304 R4	137.5	24	6	158	38	7	37	A	477	105	65	1/4 G	4	A	10

304 R













FP M_{2max} = 7300 Nm

	P71		P80		P90		P100		P112		P132	
	E	P	E	P	E	P	E	P	E	P	E	P
304 R2	65	160	84	200	84	200	94	250	94	250	114	300
304 R3	65	160	84	200	84	200	94	250	94	250	114	300
304 R4	65	160	84	200	84	200	94	250	94	250	114	300

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
304 R2	-	-	-	372	444	156	373	463	195	405	497	195	508	607	258
304 R3	253	314	138	372	444	156	373	463	195	405	497	195	—	—	—
304 R4	253	314	138	372	444	156	373	463	195	405	497	195	—	—	—

3/V 04 L3



FP M_{2max} = 7300 Nm

	L				Kg				P71	P80	P90	P100	P112
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	P	P	P	P	P
3/V 04 L3	305	345	330	305	47	56	51	47	160	200	200	250	250

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L		
	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y
3/V 04 L3	308	369	138	377	449	156	408	498	193	452	544	193

3/A 04 L2



FP M_{2max} = 7300 Nm

	L				Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
3/A 04 L2	258	298	283	258	80	95	90	80

	P63		P71		P80		P90		P100		P112		P132	
	L2	P	L2	P	L2	P	L2	P	L2	P	L2	P	L2	P
3/A 04 L2	263	140	263	160	282.5	200	282.5	200	292.5	250	292.5	250	329	457

	S1+ME1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4		
	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y
3/A 04 L2	306	327	138	491	563	156	522	580	195	566	658	195	665	764	258



304 L | 304 R | 3/V 04 L3 | 3/A 04 L2

MC HC



PC



MZ HZ



FZ



FP





FDK



FP	M_{2max} = 7300 Nm



304 L | 304 R | 3/V 04 L3 | 3/A 04 L2

Flange

W0A





Material: Steel C40

Pinions

P...





$\alpha = 20°$

	m	z	x	dp	di	de	H	A	B	C	Material
PCL1	5	19	—	95	82	104	77	12	9	72	Steel 39NiCrMo3 hardened and tempered
PCL2	5	19	—	95	82	104	68	—	—	—	
PCM	5	20	—	100	87.5	110	68	18	—	—	Steel 18NiCrMo5 case hardened
PCP	5	22	—	110	97.5	120	68	18	—	—	
PDE	6	14	0.500	84	75	99.6	68	—	—	—	Steel 39NiCrMo3 hardened and tempered
PDI	6	18	0.500	108	99	123.6	68	—	—	—	
PDM	6	20	0.833	120	115	140	68	—	—	—	
PFD	8	13	0.675	104	95	127.6	68	—	—	—	Steel 18NiCrMo5 case hardened
PFE1	8	14	—	112	92	126	68	—	—	—	
PFE2	8	14	—	112	92	126	80	—	12	72	
PFF	8	15	—	120	100	136	68	—	—	—	Steel 39NiCrMo3 hardened and tempered
PFP	8	22	—	176	156	190	77	12	10	71	
PHG	10	16	0.500	160	145	188	75	—	7	72	

Sleeve coupling

M0A





Material: Steel 16CrNi4

Splined bars

B0A



Material: Case hardening steel 18NiCrMo5 UNI 5331
must be case hardened 50-55 HRC

Shrink disc

G0A







304 L 304 R



V_ _



FV_ _

		V	V1	V2	V4	V5	A	B	F	L	S	D	U
304 L1	**V05B**	239	48	82	155	245	14	9	51.5	70	6	M16	36
	FV05B	276	48	82	219.5	244	14	9	51.5	70	6	M16	36
304 L2	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
304 L3	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
304 L4	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
304 R2-R3-R4	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28

304 L 304 R





		C	D1	D2	D3	D4	D5	D6	L1	L2	L3	L4	L5	L6	S	S1	Input
304 L1	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	—	18	45°	45°	A
304 L2	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	65	18	45°	45°	A
304 L3	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	118	18	45°	45°	A
304 L4	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	171	18	45°	45°	A
304 R2-R3-R4	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	37	18	45°	45°	A

3/V 04 L3





	D1 h6	L3	L4	L6	L7	L8	d
3/V 04 L3_HS	19	128	40	16	6	21.5	M6

3/A 04 L2





	D1 h6	L3	L4	L6	L7	L8	d
3/A 04 L2_HS	24	302	50	19	8	27	M8

304 L | 304 R | 3/V 04 L3 | 3/A 04 L2

Permissible radial and axial loads on output shaft with $Fh_2 : n_2 \cdot h = 100000$



	An2 (+)	An2 (-)
MZ - MC	25300	20240
HZ - HC PZ - PC	27500	22000

	Rn2	An2 (+/-)
FZ	11140	11604

Load corrective factor fh_2 on shafts	$Fh_2 = n_2 \cdot h$		10000	25000	50000	100000	500000	1000000
	fh_2	FZ	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
		MZ - MC	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
		HZ - HC - PZ - PC	**1.48**	**1.48**	**1.23**	**1.00**	**0.62**	**0.50**

Permissible radial loads on input shaft with $Fh_1 : n_1 \cdot h = 250000$



Load corrective factor fh_1 on shafts	$Fh_1 = n_1 \cdot h$	250000	500000	1000000	2000000	5000000	10000000
	fh_1	**1**	**0.79**	**0.63**	**0.50**	**0.37**	**0.29**

304 VK



	PF 160		PF 180		PF 200		PF225	
	E1	P1	E1	P1	E1	P1	E1	P1
304 L1	165	400	165	400	195	400	195	450
304 L2	165	400	165	400	—	—	—	—
304 L3	165	400	165	400	—	—	—	—

NOTE: For R design contact Bonfiglioli Technical service

	L	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	P71		P80		P90		P100		P112		P132		P160		P180		P200	
															E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
304 L1	51	65	239	48	15	—	—	—	276	48	17	—	—	—	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400
304 L2	116	73	137.5	24	6	158	38	7	—	—	—	—	—	—	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—
304 L3	169	76	137.5	24	6	158	38	7	—	—	—	—	—	—	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—
304 L4	222	80	137.5	24	6	158	38	7	—	—	—	—	—	—	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4			S5+ME5S/MX5S			S5+ME5L/MX5L		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
304 L1	—	—	—	—	—	—	—	—	—	—	—	—	460	559	258	552	692.5	310	596	736.5	310
304 L2	253	314	138	324	396	156	357	447	195	401	493	195	460	559	258	—	—	—	—	—	—
304 L3	253	314	138	324	396	156	357	447	195	401	493	195	460	559	258	—	—	—	—	—	—
304 L4	253	314	138	324	396	156	357	447	195	401	493	195	460	559	258	—	—	—	—	—	—

	R	R1	Kg	V	V1	Kg	V	V1	Kg	P71		P80		P90		P100		P112		P132	
										E	P	E	P	E	P	E	P	E	P	E	P
304 R2	143	140	85	137.5	24	6	158	38	7	65	160	84	200	84	200	94	250	94	250	114	300
304 R3	208	122	86	137.5	24	6	158	38	7	65	160	84	200	84	200	94	250	94	250	114	300
304 R4	261	122	90	137.5	24	6	158	38	7	65	160	84	200	84	200	94	250	94	250	114	300

	S1+ME1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
304 R2	—	—	—	372	444	156	405	495	195	449	541	195	508	607	258
304 R3	253	314	138	372	444	156	405	495	195	449	541	195	—	—	—
304 R4	253	314	138	372	444	156	405	495	195	449	541	195	—	—	—

304 VK

The diagram below allows the calculation of permitted overhung load R_{x2} on the output shaft of gearbox, with radial force applying at a distance x from shaft shoulder.
The curves are relevant to value resulting from the relationship of trust load A_{n2} to radial load R_{n2}, based on n_2 = 10 min^{-1} and 10000 hrs theoretical lifetime.



305 L

	Hydraulic motor MG							487			Kg
cm³	050	080	100	125	160	200	250				
	M1							M2	M3	M4	
305 L1	–	–	–	–	203	210	219	135	77	1/4G	20
305 L2	162	167	171	175	181	188	–	113	60	1/4G	14



	L				Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
305 L1	143	183	168	143	36	45	40	36
305 L2	208	248	233	208	43	52	47	43
305 L3	261	301	286	261	47	56	51	47
305 L4	314	354	339	314	51	60	55	51

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
305 L1	239	48	15	—	—	—	276	48	17	—	—	—	37	A		145	95	1/4 G	5	A	16
305 L2	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A		105	65	1/4 G	4	A	10
305 L3	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A	477	105	65	1/4 G	4	A	10
305 L4	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A		105	65	1/4 G	4	A	10

305 L



	PF 160		PF 180		PF 200		PF225	
	E1	P1	E1	P1	E1	P1	E1	P1
305 L1*	165	400	165	400	195	400	195	450
305 L2	165	400	165	400	—	—	—	—
305 L3	165	400	165	400	—	—	—	—

(*): contact Bonfiglioli technical service
NOTE: For R design contact Bonfiglioli Technical service

FP — M_{2max} = 7500 Nm

	P71		P80		P90		P100		P112		P132		P160		P180		P200	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
305 L1	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400
305 L2	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—
305 L3	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—
305 L4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4			S5+ME5S/MX5S			S5+ME5L/MX5L		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
305 L1	—	—	—	—	—	—	—	—	—	—	—	—	460	559	258	574	714.5	310	552	692.5	310
305 L2	—	—	—	324	396	156	357	447	195	401	493	195	460	559	258	—	—	—	—	—	—
305 L3	253	314	138	324	396	156	357	447	195	401	493	195	460	559	258	—	—	—	—	—	—
305 L4	253	314	138	324	396	156	357	447	195	401	493	195	460	559	258	—	—	—	—	—	—

305 R

	Hydraulic motor							487			Kg
	MG										
cm³	050	080	100	125	160	200	250				
	M1							M2	M3	M4	
305 R2	162	167	171	175	181	188	—	113	60	1/4G	14







	R				R1	Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK		MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
305 R2	235	375	260	235	140	56	65	60	56
305 R3	300	340	325	300	122	57	66	61	57
305 R4	353	393	378	353	122	61	70	65	61

	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
305 R2	137.5	24	6	158	38	7	37	A		105	65	1/4 G	4	A	10
305 R3	137.5	24	6	158	38	7	37	A		105	65	1/4 G	4	A	10
305 R4	137.5	24	6	158	38	7	37	A	477	105	65	1/4 G	4	A	10

305 R













FP M_{2max} = 7500 Nm

	P71		P80		P90		P100		P112		P132	
	E	P	E	P	E	P	E	P	E	P	E	P
305 R2	65	160	84	200	84	200	94	250	94	250	114	300
305 R3	65	160	84	200	84	200	94	250	94	250	114	300
305 R4	65	160	84	200	84	200	94	250	94	250	114	300

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
305 R2	—	—	—	372	444	156	405	495	195	449	541	195	508	607	258
305 R3	253	314	138	372	444	156	405	495	195	449	541	195	508	607	258
305 R4	253	314	138	372	444	156	405	495	195	449	541	195	508	607	258

3/V 05 L3



FP M_{2max} = 7500 Nm

	L				Kg				P71	P80	P90	P100	P112
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	P	P	P	P	P
3/V 05 L3	323	363	348	323	51	60	55	51	160	200	200	250	250

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L		
	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y
3/V 05 L3	308	369	138	376	448	156	408	498	193	452	544	193

3/A 05 L2



FP M_{2max} = 7500 Nm

	L				Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
3/A 05 L2	276	316	301	276	90	105	100	90

	P63		P71		P80		P90		P100		P112		P132	
	L2	P	L2	P	L2	P	L2	P	L2	P	L2	P	L2	P
3/A 05 L2	263	140	263	160	282.5	200	282.5	200	292.5	250	292.5	250	329	457

	S1+ME1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4		
	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y
3/A 05 L2	418	479	138	491	563	156	522	580	195	566	658	195	665	764	258



305 L | 305 R | 3/V 05 L3 | 3/A 05 L2

MC HC



PC



MZ HZ



FZ



FP





FDK



FP	M_{2max} = 7500 Nm



305 L | 305 R | 3/V 05 L3 | 3/A 05 L2

Flange

W0A





Material: Steel C40

Pinions

P...





$\alpha = 20°$

	m	z	x	dp	di	de	H	A	B	C	Material
PCL1	5	19	—	95	82	104	77	12	9	72	Steel 39NiCrMo3 hardened and tempered
PCL2	5	19	—	95	82	104	68	—	—	—	
PCM	5	20	—	100	87.5	110	68	18	—	—	Steel 18NiCrMo5 case hardened
PCP	5	22	—	110	97.5	120	68	18	—	—	
PDE	6	14	0.500	84	75	99.6	68	—	—	—	Steel 39NiCrMo3 hardened and tempered
PDI	6	18	0.500	108	99	123.6	68	—	—	—	
PDM	6	20	0.833	120	115	140	68	—	—	—	
PFD	8	13	0.675	104	95	127.6	68	—	—	—	Steel 18NiCrMo5 case hardened
PFE1	8	14	—	112	92	126	68	—	—	—	
PFE2	8	14	—	112	92	126	80	—	12	72	
PFF	8	15	—	120	100	136	68	—	—	—	Steel 39NiCrMo3 hardened and tempered
PFP	8	22	—	176	156	190	77	12	10	71	
PHG	10	16	0.500	160	145	188	75	—	7	72	

Sleeve coupling

M0A





Material: Steel 16CrNi4

Splined bars

B0A



Material: Case hardening steel 18NiCrMo5 UNI 5331
must be case hardened 50-55 HRC

Shrink disc

G0A







305 L 305 R



V_ _



FV_ _

		V	V1	V2	V4	V5	A	B	F	L	S	D	U
305 L1	**V05B**	239	48	82	155	245	14	9	51.5	70	6	M16	36
	FV05B	276	48	82	219.5	244	14	9	51.5	70	6	M16	36
305 L2	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
305 L3	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
305 L4	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
305 R2-R3-R4	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28

305 L 305 R





		C	D1	D2	D3	D4	D5	D6	L1	L2	L3	L4	L5	L6	S	S1	Input
305 L1	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	—	18	45°	45°	A
305 L2	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	65	18	45°	45°	A
305 L3	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	118	18	45°	45°	A
305 L4	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	171	18	45°	45°	A
305 R2-R3-R4	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	37	18	45°	45°	A

3/V 05 L3





	D1 h6	L3	L4	L6	L7	L8	d
3/V 05 L3_HS	19	128	40	16	6	21.5	M6

3/A 05 L2





	D1 h6	L3	L4	L6	L7	L8	d
3/A 05 L2_HS	24	302	50	19	8	27	M8

305 L | 305 R | 3/V 05 L3 | 3/A 05 L2

Permissible radial and axial loads on output shaft with $Fh_2 : n_2 \cdot h = 100000$



	An2 (+)	An2 (-)
MZ - MC	25300	20240
HZ - HC PZ - PC	27500	22000

	Rn2	An2 (+/-)
FZ	11140	11604

	$Fh_2 = n_2 \cdot h$		10000	25000	50000	100000	500000	1000000
Load corrective factor fh_2 on shafts	fh_2	FZ	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
		MZ - MC	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
		HZ - HC - PZ - PC	**1.48**	**1.48**	**1.23**	**1.00**	**0.62**	**0.50**

Permissible radial loads on input shaft with $Fh_1 : n_1 \cdot h = 250000$





Load corrective factor fh_1 on shafts	$Fh_1 = n_1 \cdot h$	250000	500000	1000000	2000000	5000000	10000000
	fh_1	**1**	**0.79**	**0.63**	**0.50**	**0.37**	**0.29**

305 VK



305 L_VK

305 R_VK

	PF 160		PF 180		PF 200		PF225	
	E1	P1	E1	P1	E1	P1	E1	P1
305 L1	165	400	165	400	195	400	195	450
305 L2	165	400	165	400	—	—	—	—
305 L3	165	400	165	400	—	—	—	—

NOTE: For R design contact Bonfiglioli Technical service

	L	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	P71		P80		P90		P100		P112		P132		P160		P180		P200	
															E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
305 L1	69	70	239	48	15	—	—	—	276	48	17	—	—	—	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400
305 L2	134	77	137.5	24	6	158	38	7	—	—	—	—	—	—	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—
305 L3	187	81	137.5	24	6	158	38	7	—	—	—	—	—	—	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—
305 L4	240	85	137.5	24	6	158	38	7	—	—	—	—	—	—	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4			S5+ME5S/MX5S			S5+ME5L/MX5L		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
305 L1	—	—	—	—	—	—	—	—	—	—	—	—	460	559	258	552	692.5	310	596	736.5	310
305 L2	—	—	—	324	396	156	357	447	195	401	493	195	460	559	258	—	—	—	—	—	—
305 L3	253	314	138	324	396	156	357	447	195	401	493	195	460	559	258	—	—	—	—	—	—
305 L4	253	314	138	324	396	156	357	447	195	401	493	195	460	559	258	—	—	—	—	—	—

	R	R1	Kg	V	V1	Kg	V	V1	Kg	P71		P80		P90		P100		P112		P132	
										E	P	E	P	E	P	E	P	E	P	E	P
305 R2	161	140	90	137.5	24	6	158	38	7	65	160	84	200	84	200	94	250	94	250	114	300
305 R3	226	122	92	137.5	24	6	158	38	7	65	160	84	200	84	200	94	250	94	250	114	300
305 R4	279	122	95	137.5	24	6	158	38	7	65	160	84	200	84	200	94	250	94	250	114	300

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
305 R2	—	—	—	372	444	156	405	495	195	449	541	195	508	607	258
305 R3	253	314	138	372	444	156	405	495	195	449	541	195	508	607	258
305 R4	253	314	138	372	444	156	405	495	195	449	541	195	508	607	258

305 VK

The diagram below allows the calculation of permitted overhung load R_{x2} on the output shaft of gearbox, with radial force applying at a distance x from shaft shoulder.
The curves are relevant to value resulting from the relationship of trust load A_{n2} to radial load R_{n2}, based on n_2 = 10 min^{-1} and 10000 hrs theoretical lifetime.



306 L



	Hydraulic motor							487			Kg
	MG										
cm³	050	080	100	125	160	200	250				
	M1							M2	M3	M4	
306 L2	–	–	–	–	203	210	219	135	77	1/4G	20

	L				Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
306 L1	160	235	195	160	65	85	70	65
306 L2	225	300	260	225	74	95	79	74
306 L3	278	353	313	278	78	98	83	78
306 L4	331	406	366	331	82	103	87	82

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
306 L1	307	60	23	—	—	—	357	60	28	—	—	—	45	B		195	147	1/4 G	6	B	28
306 L2	239	48	15	—	—	—	276	48	17	—	—	—	37	A		145	95	1/4 G	5	A	16
306 L3	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A	477	105	65	1/4 G	4	A	10
306 L4	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A		105	65	1/4 G	4	A	10

306 L



	PF 160		PF 180		PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1	E1	P1	E1	P1
306 L1*	—	—	167	390	197	400	197	450	207	550
306 L2	165	400	165	400	195	400	195	450	—	—
306 L3	165	400	165	400	—	—	—	—	—	—

(*) Contact Bonfiglioli's Technical Service

NOTE: For R design contact Bonfiglioli Technical service

FP M_{2max} = 12000 Nm

	P71		P80		P90		P100		P112		P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
306 L1	—	—	—	—	—	—	—	—	—	—	—	—	144	350	153	350	183	400	212	450	193	550
306 L2	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400	—	—	—	—
306 L3	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—
306 L4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—

	S1+M1			S2+ME2S/MX5S			S3+ME3S/MX5S			S3+ME3L/MX5S			S4+ME4/MX4			S5+ME5S/MX5S			S5+ME5L/MX5L		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
306 L1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
306 L2	—	—	—	—	—	—	—	—	—	—	—	—	460	559	258	552	692.5	310	596	736.5	310
306 L3	253	314	138	324	396	156	357	447	195	401	493	195	460	559	258	—	—	—	—	—	—
306 L4	253	314	138	324	396	156	357	447	195	401	493	195	460	559	258	—	—	—	—	—	—

306 R

	Hydraulic motor							487			Kg
	MG										
cm³	050	080	100	125	160	200	250				
	M1							M2	M3	M4	
306 R2	–	167	171	175	181	188	197	113	60	1/4G	14
306 R3	162	167	171	175	181	–	–	113	60	1/4G	14







	R				R1	Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK		MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
306 R2	297	372	332	297	140	89	105	94	89
306 R3	317	392	352	317	140	85	100	90	85
306 R4	370	445	405	370	122	79	95	84	79

	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
306 R2	137.5	24	6	158	38	7	37	A		105	65	1/4 G	4	A	10
306 R3	137.5	24	6	158	38	7	37	A		105	65	1/4 G	4	A	10
306 R4	137.5	24	6	158	38	7	37	A	477	105	65	1/4 G	4	A	10

306 R



FP M_{2max} = 12000 Nm

	P71		P80		P90		P100		P112		P132		P160	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P
306 R2	65	160	84	200	84	200	94	250	94	250	114	300	144	350
306 R3	65	160	84	200	84	200	94	250	94	250	114	300	144	350
306 R4	65	160	84	200	84	200	94	250	94	250	114	300	144	350

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
306 R2	—	—	—	372	444	156	405	495	195	449	541	195	508	607	258
306 R3	253	314	138	372	444	156	405	495	195	449	541	195	508	607	258
306 R4	253	314	138	372	444	156	405	495	195	449	541	195	508	607	258

3/V 06 L3



FP M_{2max} = 12000 Nm

	L				Kg				P71	P80	P90	P100	P112
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	P	P	P	P	P
3/V 06 L3	370	445	405	370	80	111	95	80	160	200	200	250	250

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L		
	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y
3/V 06 L3	324	385	138	393	465	156	424	514	193	468	560	193

3/A 06 L2



FP M_{2max} = 12000 Nm

	L				Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
3/A 06 L2	340	415	375	340	140	170	150	140

	P63		P71		P80		P90		P100		P112		P132		P160		P180	
	L2	P	L2	P	L2	P	L2	P	L2	P	L2	P	L2	P	L2	P	L2	P
3/A 06 L2	314.5	140	314.5	160	334	200	334	200	344	250	344	250	380.5	300	431	350	431	350

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4		
	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y
3/A 06 L2	469.5	530.5	138	542.5	614.5	156	573.5	663.5	195	617.5	709.5	195	716.5	815.5	258

306 L | 306 R | 3/V 06 L3 | 3/A 06 L2

MC HC



PC



MZ HZ





FZ



FP





FDK



FP	M_{2max} = 12000 Nm



306 L | 306 R | 3/V 06 L3 | 3/A 06 L2

Flange

W0A





Material: Steel C40

Pinions

P...





$\alpha = 20°$

	m	z	x	dp	di	de	H	A	B	C	Material
PFF1	8	15	—	120	100	134	90	—	—	—	Steel 39NiCrMo3 hardened and tempered
PFF2	8	15	0.500	120	108	141	90	—	—	—	
PHB	10	11	0.500	110	95	136	90	10	—	—	
PHC1	10	12	0.450	120	104	145	90	—	—	—	
PHC2	10	12	0.320	120	100	144.2	90	—	—	—	
PHC3	10	12	0.350	120	101	144	90	—	—	—	
PHD1	10	13	0.950	130	124	165	90	—	—	—	
PHD2	10	13	0.500	130	115	159	90	—	—	—	
PHE1	10	14	—	140	115	160	90	—	—	—	
PHE2	10	14	0.500	140	125	166	90	—	—	—	Steel 18NiCrMo5 case hardened
PHF	10	15	—	150	127	167	90	24	—	—	Steel 39NiCrMo3 hardened and tempered
PHH	10	17	0.480	170	154	197.5	90	10	—	—	
PHM	10	20	—	200	175	220	90	10	—	—	Steel 18NiCrMo5 case hardened

Sleeve coupling

M0A





Material: Steel 16CrNi4

Splined bars

B0A



Material: Case hardening steel 18NiCrMo5 UNI 5331
must be case hardening 50-55 HRC

Shrink disc

G0A







306 L 306 R



V_ _



FV_ _

		V	V1	V2	V4	V5	A	B	F	L	S	D	U
306 L1	**V06B**	307	60	105	155	292	18	11	64	90	7.5	M16	36
	FV06B	357	60	105	309	292	18	11	64	90	7.5	M16	36
306 L2	**V05B**	239	48	82	155	245	14	9	51.5	70	6	M16	36
	FV05B	276	48	82	219.5	244	14	9	51.5	70	6	M16	36
306 L3	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
306 L4	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
306 R2-R3-R4	**V01A**	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28

306 L 306 R







		C	D1	D2	D3	D4	D5	D6	L1	L2	L3	L4	L5	L6	S	S1	Input
306 L1	**V9AB**	45	58x53 DIN5482	195	236 H7	222	M10 n°12	—	4	18	11	22	—	—	45°	22.5°	B
306 L2	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	—	4	18	9	18	—	—	45°	45°	A
306 L3	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	53	18	45°	45°	A
306 L4	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	106	18	45°	45°	A
306 R2-R3-R4	**V9AA**	37	40x36 DIN5482	140	178 H7	165	M10 n°8	11	4	—	9	18	37	18	45°	45°	A

3/V 06 L3





	D1 h6	L3	L4	L6	L7	L8	d
3/V 06 L3_HS	25	144	50	19	8	28	M8

3/A 06 L2







	D1 h6	L3	L4	L6	L7	L8	d
3/A 06 L2_HS	24	354	50	19	8	27	M8

306 L | 306 R | 3/V 06 L3 | 3/A 06 L2

Permissible radial and axial loads on output shaft with $Fh_2 : n_2 \cdot h = 100000$





	An2 (+)	An2 (-)
MZ - MC	32200	20240
HZ - HC PZ - PC	60000	30000



	Rn2	An2 (+/-)
FZ	16246	16246

Load corrective factor fh_2 on shafts	$Fh_2 = n_2 \cdot h$		10000	25000	50000	100000	500000	1000000
	fh_2	FZ	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
		MZ - MC	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
		HZ - HC - PZ - PC	**1.34**	**1.34**	**1.23**	**1.00**	**0.62**	**0.50**

Permissible radial loads on input shaft with $Fh_1 : n_1 \cdot h = 250000$





Load corrective factor fh_1 on shafts	$Fh_1 = n_1 \cdot h$	250000	500000	1000000	2000000	5000000	10000000
	fh_1	**1**	**0.79**	**0.63**	**0.50**	**0.37**	**0.29**

306 VK



306 L_VK

306 R_VK

	PF 160		PF 180		PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1	E1	P1	E1	P1
306 L1	—	—	167	390	197	400	197	450	207	550
306 L2	165	400	165	400	195	400	195	450	—	—
306 L3	165	400	165	400	—	—	—	—	—	—

NOTE: For R design contact Bonfiglioli Technical service

	L	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	P71		P80		P90		P100		P112		P132		P160		P180		P200		P225		P250	
															E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
306 L1	75	110	307	60	23	—	—	—	357	60	28	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	144	350	153	350	183	400	212	450	193	550
306 L2	140	120	239	48	15	—	—	—	276	48	17	—	—	—	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400	—	—	—	—
306 L3	193	125	137.5	24	6	158	38	7	—	—	—	—	—	—	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—
306 L4	246	130	137.5	24	6	158	38	7	—	—	—	—	—	—	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4			S5+ME5S/MX5S			S5+ME5L/MX5L		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
306 L1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
306 L2	—	—	—	—	—	—	—	—	—	—	—	—	460	559	258	552	692.5	310	596	736.5	310
306 L3	253	314	138	324	396	156	357	447	195	401	493	195	460	559	258	—	—	—	—	—	—
306 L4	253	314	138	324	396	156	357	447	195	401	493	195	460	559	258	—	—	—	—	—	—

	R	R1	Kg	V	V1	Kg	V	V1	Kg	P71		P80		P90		P100		P112		P132		P160	
										E	P	E	P	E	P	E	P	E	P	E	P	E	P
306 R2	212	140	90	137.5	24	6	158	38	7	65	160	84	200	84	200	94	250	94	250	114	300	144	350
306 R3	232	140	92	137.5	24	6	158	38	7	65	160	84	200	84	200	94	250	94	250	114	300	144	350
306 R4	285	122	95	137.5	24	6	158	38	7	65	160	84	200	84	200	94	250	94	250	114	300	144	350

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
306 R2	—	—	—	372	444	156	405	495	195	449	541	195	508	607	258
306 R3	253	314	138	372	444	156	405	495	195	449	541	195	508	607	258
306 R4	253	314	138	372	444	156	405	495	195	449	541	195	508	607	258

306 VK

The diagram below allows the calculation of permitted overhung load R_{x2} on the output shaft of gearbox, with radial force applying at a distance x from shaft shoulder.
The curves are relevant to value resulting from the relationship of trust load A_{n2} to radial load R_{n2}, based on n_2 = 10 min^{-1} and 10000 hrs theoretical lifetime.





307 L



	Hydraulic motor							487			Kg
	MG										
cm³	050	080	100	125	160	200	250				
	M1							M2	M3	M4	
307 L2	–	–	–	–	203	210	219	135	77	1/4G	20

	L				Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
307 L1	165	246	210	165	85	120	105	85
307 L2	254	335	299	254	97	132	117	97
307 L3	319	400	364	319	104	139	124	104
307 L4	372	453	417	372	108	143	128	108

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
307 L1	315	80	35	313	60	28	375	80	48	363	60	34	51	B		201	153	1/4 G	6	B	28
307 L2	239	48	15	—	—	—	276	48	17	—	—	—	37	A		145	95	1/4 G	5	A	16
307 L3	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A	477	105	65	1/4 G	4	A	10
307 L4	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A		105	65	1/4 G	4	A	10

307 L



	PF 160		PF 180		PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1	E1	P1	E1	P1
307 L1*	—	—	—	—	197	530	227	530	227	550
307 L2	165	400	165	400	195	400	195	450	—	—
307 L3	165	400	165	400	—	—	—	—	—	—
307 L4	165	400	165	400	—	—	—	—	—	—

(*): contact Bonfiglioli technical service
NOTE: For R design contact Bonfiglioli Technical service

FP M_{2max} = 18200 Nm

	P71		P80		P90		P100		P112		P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
307 L1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	195	350	186	400	216	450	215	550
307 L2	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400	—	—	—	—
307 L3	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—
307 L4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4			S5+ME5S/MX5S			S5+ME5L/MX5L		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
307 L1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
307 L2	—	—	—	—	—	—	—	—	—	—	—	—	460	559	258	552	692.5	310	596	736.5	310
307 L3	—	—	—	324	396	156	357	447	195	401	493	195	460	559	258	—	—	—	—	—	—
307 L4	253	314	138	324	396	156	357	447	195	401	493	195	460	559	258	—	—	—	—	—	—

307 R

	Hydraulic motor							487			Kg
	MG										
cm³	050	080	100	125	160	200	250				
	M1							M2	M3	M4	
307 R2	—	—	171	175	181	188	197	113	60	1/4G	14
307 R3	—	167	171	175	181	188	197	113	60	1/4G	14







	R				R1	R2	Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK			MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
307 R2	284	365	329	284	225	245	135	170	155	135
307 R3	346	427	391	346	140	186	117	152	137	117
307 R4	411	492	456	411	122	186	118	153	138	118

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
307 R2	239	48	15	—	—	—	276	48	17	—	—	—	37	A		145	95	1/4 G	5	A	16
307 R3	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A		105	65	1/4 G	4	A	10
307 R4	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A	477	105	65	1/4 G	4	A	10

307 R





HZ



HC





FZ



FP



FDK



FP M_{2max} = 18200 Nm

	P71		P80		P90		P100		P112		P132		P160		P180		P200	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
307 R2	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400
307 R3	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—
307 R4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4			S5+ME5S/MX5S			S5+ME5L/MX5L		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
307 R2	—	—	—	—	—	—	—	—	—	—	—	—	508	607	258	552	692.5	310	596	736.5	310
307 R3	253	314	138	372	444	156	405	495	195	449	541	195	508	607	258	—	—	—	—	—	—
307 R4	253	314	138	372	444	156	405	495	195	449	541	195	508	607	258	—	—	—	—	—	—

3/V 07 L3





























FP M_{2max} = 18200 Nm

	L				Kg				P80	P90	P100	P112
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	P	P	P	P
3/V 07 L3	414	495	459	414	130	165	150	130	200	200	250	250

	S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L		
	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y
3/V 07 L3	408	480	156	439	529	195	483	575	195

3/A 07 L2



FP M_{2max} = 18200 Nm

	L				Kg			
	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK	MC - MZ	PC - PZ	HC - HZ	FP - FZ - FDK
3/A 07 L2	336	417	381	336	200	230	210	200

	P80		P90		P100		P112		P132		P160		P180	
	L2	P	L2	P	L2	P	L2	P	L2	P	L2	P	L2	P
3/A 07 L2	371	200	371	200	381	250	381	250	416.5	300	468	350	468	350

	S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4			S5+ME5S/MX5S			S5+ME5L/MX5L		
	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y
3/A 07 L2	579.5	651.5	156	610.5	700.5	195	654.5	746.5	195	753.5	852.5	258	970	1110.5	310	1014	1154.5	310



307 L | 307 R | 3/V 07 L3 | 3/A 07 L2

MC **HC**



PC



MZ **HZ**





FZ



FP





FDK



FP	M_{2max} = 18200 Nm



307 L | 307 R | 3/V 07 L3 | 3/A 07 L2

Flange

W0A





Material: Steel C40

Pinions

P...





$\alpha = 20°$

	m	z	x	dp	di	de	H	A	B	C	Material
PFG	8	16	0.500	128	117	149.5	90	—	—	—	Steel 39NiCrMo3 hardened and tempered
PHC	10	12	0.450	120	104	145	90	—	—	—	
PHE	10	14	0.320	140	121	165	116	13	26	95	
PHF	10	15	0.150	150	130	171.5	107	20	17	100	
PHG	10	16	0.500	160	145	186	90	—	—	—	Steel 18NiCrMo5 case hardened
PHH1	10	17	—	170	145	189	90	—	—	—	
PHH2	10	17	0.500	170	154	198	90	—	—	—	
PLD	12	13	0.500	156	138	192	102	—	12	95	Steel 39NiCrMo3 hardened and tempered
PLE	12	14	0.500	168	150	199.2	90	—	—	—	
PLI	12	18	0.500	216	198	249.6	107	7	17	95	
PLT	12	26	—	312	282	336	90	10	—	—	Steel 18NiCrMo5 case hardened

Sleeve coupling

M0A





Material: Steel 16CrNi4

Splined bars

B0A



Material: Case hardening steel 18NiCrMo5 UNI 5331
must be case hardened 50-55 HRC

Shrink disc

G0A







307 L 307 R



V_ _



FV_ _



		V	V1	V2	V4	V5	A	B	F	L	S	D	U
307 L1	V07B	315	80	130	200	345	22	14	85	110	10	M16	36
	FV07B	375	80	130	347.5	348	22	14	85	110	10	M16	36
	V07A	313	60	105	155	345	18	11	64	90	7.5	M16	36
	FV07A	363	60	105	309	348	18	11	64	90	7.5	M16	36
307 L2	V05B	239	48	82	155	245	14	9	51.5	70	6	M16	36
	FV05B	276	48	82	219.5	244	14	9	51.5	70	6	M16	36
307 L3	V01A	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
307 L4	V01A	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
307 R2	V05B	239	48	82	155	245	14	9	51.5	70	6	M16	36
	FV05B	276	48	82	219.5	244	14	9	51.5	70	6	M16	36
307 R3-R4	V01A	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28

307 L 307 R







		C	D1	D2	D3	D4	D5	D6	L1	L2	L3	L4	L5	L6	S	S1	Input
307 L1	V9AB	51	58x53 DIN 5482	195	236 H7	222	M10 n°12	—	4	18	11	22	—	—	45°	22.5°	B
307 L2	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	—	4	18	9	18	—	—	45°	45°	A
307 L3	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	11	4	—	9	18	65	18	45°	45°	A
307 L4	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	11	4	—	9	18	118	18	45°	45°	A
307 R2	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	11	4	18	9	18	—	—	45°	45°	A
307 R3-R4	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	11	4	—	9	18	37	18	45°	45°	A

3/V 07 L3





	D1 h6	L3	L4	L6	L7	L8	d
3/V 07 L3_HS	25	168	60	19	8	28	M8

3/A 07 L2







	D1 h6	L3	L4	L6	L7	L8	d
3/A 07 L2_HS	28	409	60	22	8	31	M10

307 L | 307 R | 3/V 07 L3 | 3/A 07 L2

Permissible radial and axial loads on output shaft with $Fh_2 : n_2 \cdot h = 100000$



	An2 (+)	An2 (-)
MZ - MC	41400	23000
HZ - HC PZ - PC	80000	40000

	Rn2	An2 (+/-)
FZ	20887	20887

	$Fh_2 = n_2 \cdot h$		10000	25000	50000	100000	500000	1000000
Load corrective factor fh_2 on shafts	fh_2	FZ	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
		MZ - MC	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
		HZ - HC - PZ - PC	**1.49**	**1.49**	**1.23**	**1.00**	**0.62**	**0.50**

Permissible radial loads on input shaft with $Fh_1 : n_1 \cdot h = 250000$



Load corrective factor fh_1 on shafts	$Fh_1 = n_1 \cdot h$	250000	500000	1000000	2000000	5000000	10000000
	fh_1	**1**	**0.79**	**0.63**	**0.50**	**0.37**	**0.29**

307 VK



307 L_VK

307 R_VK

	PF 160		PF 180		PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1	E1	P1	E1	P1
307 L1	—	—	—	—	197	530	227	530	227	550
307 L2	165	400	165	400	195	400	195	450	—	—
307 L3	165	400	165	400	—	—	—	—	—	—
307 L4	165	400	165	400	—	—	—	—	—	—

NOTE: For R design contact Bonfiglioli Technical service

	L	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	P71		P80		P90		P100		P112		P132		P160		P180		P200		P225		P250	
															E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
307 L1	80	145	315	80	35	313	60	28	375	80	48	363	60	34	—	—	—	—	—	—	—	—	—	—	—	—	—	—	195	350	186	400	216	450	215	550
307 L2	169	160	239	48	15	—	—	—	276	48	17	—	—	—	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400	—	—	—	—
307 L3	234	170	137.5	24	6	158	38	7	—	—	—	—	—	—	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—
307 L4	287	175	137.5	24	6	158	38	7	—	—	—	—	—	—	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4			S5+ME5S/MX5S			S5+ME5L/MX5L		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
307 L1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
307 L2	—	—	—	—	—	—	—	—	—	—	—	—	460	559	258	552	692.5	310	596	736.5	310
307 L3	—	—	—	324	396	156	357	447	195	401	493	195	460	559	258	—	—	—	—	—	—
307 L4	253	314	138	324	396	156	357	447	195	401	493	195	460	559	258	—	—	—	—	—	—

	R	R1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	P71		P80		P90		P100		P112		P132		P160		P180		P200	
																E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
307 R2	199	225	180	239	48	15	—	—	—	276	48	17	—	—	—	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400
307 R3	261	140	170	137.5	24	6	158	38	7	—	—	—	—	—	—	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—
307 R4	326	122	175	137.5	24	6	158	38	7	—	—	—	—	—	—	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—

	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L			S4+ME4/MX4			S5+ME5S/MX5S			S5+ME5L/MX5L		
	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1	X1	X2	Y1
307 R2	—	—	—	—	—	—	—	—	—	—	—	—	508	607	258	552	692.5	310	596	736.5	310
307 R3	253	314	138	372	444	156	405	495	195	449	541	195	508	607	258	—	—	—	—	—	—
307 R4	253	314	138	372	444	156	405	495	195	449	541	195	508	607	258	—	—	—	—	—	—

307 VK

The diagram below allows the calculation of permitted overhung load R_{x2} on the output shaft of gearbox, with radial force applying at a distance x from shaft shoulder.
The curves are relevant to value resulting from the relationship of trust load A_{n2} to radial load R_{n2}, based on n_2 = 10 min^{-1} and 10000 hrs theoretical lifetime.



309 L



	L				Kg			
	PC - PZ	HC - HZ	FZ	FP - FDK	PC - PZ	HC - HZ	FZ	FP - FDK
309 L1	267	126	99	101	130	115	95	100
309 L2	356	215	188	190	142	127	107	112
309 L3	421	280	253	255	149	134	114	119
309 L4	474	333	306	308	153	138	118	123

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
309 L1	315	80	35	313	60	28	375	80	48	363	60	34	51	B		201	153	1/4 G	6	B	28
309 L2	239	48	15	—	—	—	276	48	17	—	—	—	37	A		145	95	1/4 G	5	A	16
309 L3	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A	477	105	65	1/4 G	4	A	10
309 L4	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A		105	65	1/4 G	4	A	10

309 L



	PF 160		PF 180		PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1	E1	P1	E1	P1
309 L1*	—	—	—	—	197	530	227	530	227	550
309 L2	165	400	165	400	195	400	195	450	—	—
309 L3	165	400	165	400	—	—	—	—	—	—
309 L4	165	400	165	400	—	—	—	—	—	—

FP M_{2max} = 29000 Nm

(*): contact Bonfiglioli technical service
NOTE: For R design contact Bonfiglioli Technical service

	P71		P80		P90		P100		P112		P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
309 L1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	195	350	186	400	216	450	216	550
309 L2	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400	—	—	—	—
309 L3	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—
309 L4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—

309 R



	R				R1	R2	R3			Kg			
	PC-PZ	HC-HZ	FZ	FP - FDK			HC-HZ	FZ	FP	PC-PZ	HC-HZ	FZ	FP - FDK
309 R2	386	245	218	220	225	245	168	141	143	180	165	145	150
309 R3	448	307	280	282	140	186	144	117	119	162	147	127	132
309 R4	513	372	345	347	122	186	144	117	119	163	148	128	133

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
309 R2	239	48	15	—	—	—	276	48	17	—	—	—	37	A		145	95	1/4 G	5	A	16
309 R3	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A		105	65	1/4 G	4	A	10
309 R4	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A	477	105	65	1/4 G	4	A	10

309 R



FP M_{2max} = 29000 Nm

	P71		P80		P90		P100		P112		P132		P160		P180		P200	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
309 R2	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400
309 R3	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—
309 R4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—

3/V 09 L3



PC



HZ PZ





HC





FP





FZ



FDK



FP M_{2max} = 29000 Nm

	L				Kg				P100	P112	P132	P160
	PC - PZ	HC - HZ	FZ	FP - FDK	PC - PZ	HC - HZ	FZ	FP - FDK	P	P	P	P
3/V 09 L3	530	389	362	364	202	187	167	172	250	250	300	350





309 L | 309 R | 3/V 09 L3

HC





PC



HZ





FZ



FP



FDK





FP	M_{2max} = 29000 Nm



309 L | 309 R | 3/V 09 L3

Flange

W0A







Material: Steel C40

Pinions

P...





$\alpha = 20°$

	m	z	x	dp	di	de	H	A	B	C	Material
PFG	8	16	0.500	128	117	149.5	90	—	—	—	Steel 39NiCrMo3 hardened and tempered
PHC	10	12	0.450	120	104	145	90	—	—	—	
PHE	10	14	0.320	140	121	165	116	13	26	95	
PHF	10	15	0.150	150	130	171.5	107	20	17	100	
PHG	10	16	0.500	160	145	186	90	—	—	—	Steel 18NiCrMo5 case hardened
PHH1	10	17	—	170	145	189	90	—	—	—	
PHH2	10	17	0.500	170	154	198	90	—	—	—	
PLD	12	13	0.500	156	138	192	102	—	12	95	Steel 39NiCrMo3 hardened and tempered
PLE	12	14	0.500	168	150	199.2	90	—	—	—	
PLI	12	18	0.500	216	198	249.6	107	7	17	95	
PLT	12	26	—	312	282	336	90	10	—	—	Steel 18NiCrMo5 case hardened

Sleeve coupling

M0A





Material: Steel 16CrNi4

Splined bars

B0A



Material: Case hardening steel 18NiCrMo5 UNI 5331
must be case hardened 50-55 HRC

Shrink disc

G0A







309 L 309 R



V_ _



FV_ _



		V	V1	V2	V4	V5	A	B	F	L	S	D	U
309 L1	V07B	315	80	130	200	345	22	14	85	110	10	M16	36
	FV07B	375	80	130	347.5	348	22	14	85	110	10	M16	36
	V07A	313	60	105	155	345	18	11	64	90	7.5	M16	36
	FV07A	363	60	105	309	348	18	11	64	90	7.5	M16	36
309 L2	V05B	239	48	82	155	245	14	9	51.5	70	6	M16	36
	FV05B	276	48	82	219.5	244	14	9	51.5	70	6	M16	36
309 L3	V01A	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
309 L4	V01A	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
309 R2	V05B	239	48	82	155	245	14	9	51.5	70	6	M16	36
	FV05B	276	48	82	219.5	244	14	9	51.5	70	6	M16	36
309 R3-R4	V01A	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28

309 L 309 R







		C	D1	D2	D3	D4	D5	D6	L1	L2	L3	L4	L5	L6	S	S1	Input
309 L1	V9AB	51	58x53 DIN 5482	195	236 H7	222	M10 n°12	—	4	18	11	22	—	—	45°	22.5°	B
309 L2	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	—	4	18	9	18	—	—	45°	45°	A
309 L3	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	11	4	—	9	18	65	18	45°	45°	A
309 L4	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	11	4	—	9	18	118	18	45°	45°	A
309 R2	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	11	4	18	9	18	—	—	45°	45°	A
309 R3-R4	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	11	4	—	9	18	37	18	45°	45°	A

3/V 09 L3





	D1 h6	L3	L4	L6	L7	L8	d
3/V 09 L3_HS	35	185	65	20	10	38	M8

309 L | 309 R | 3/V 09 L3

Permissible radial and axial loads on output shaft with $Fh_2 : n_2 \cdot h = 100000$





	An_2 (+)	An_2 (-)
HZ - HC PZ - PC	80000	40000



	Rn_2	An_2 (+/-)
FZ	16710	17174

Load corrective factor fh_2 on shafts	$Fh_2 = n_2 \cdot h$	10000	25000	50000	100000	500000	1000000
	FZ	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
fh_2	**HZ - HC - PZ - PC**	**1.49**	**1.49**	**1.23**	**1.00**	**0.62**	**0.50**

Permissible radial loads on input shaft with $Fh_1 : n_1 \cdot h = 250000$





Load corrective factor fh_1 on shafts	$Fh_1 = n_1 \cdot h$	250000	500000	1000000	2000000	5000000	10000000
	fh_1	**1**	**0.79**	**0.63**	**0.50**	**0.37**	**0.29**

309 VK



309 L_VK

309 R_VK

	PF 160		PF 180		PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1	E1	P1	E1	P1
309 L1	—	—	—	—	197	530	227	530	227	550
309 L2	165	400	165	400	195	400	195	450	—	—
309 L3	165	400	165	400	—	—	—	—	—	—
309 L4	165	400	165	400	—	—	—	—	—	—

NOTE: For R design contact Bonfiglioli Technical service

	L	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg
309 L1	102	165	315	80	35	313	60	28	375	80	48	363	60	34
309 L2	191	180	239	48	15	—	—	—	276	48	17	—	—	—
309 L3	256	190	137.5	24	6	158	38	7	—	—	—	—	—	—
309 L4	309	195	137.5	24	6	158	38	7	—	—	—	—	—	—

	P71		P80		P90		P100		P112		P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
309 L1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	195	350	186	400	216	450	216	450
309 L2	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400	—	—	—	—
309 L3	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—
309 L4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—

	R	R1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg
309 R2	221	225	200	239	48	15	—	—	—	276	48	17	—	—	—
309 R3	283	140	190	137.5	24	6	158	38	7	—	—	—	—	—	—
309 R4	348	122	195	137.5	24	6	158	38	7	—	—	—	—	—	—

	P71		P80		P90		P100		P112		P132		P160		P180		P200	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
309 R2	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400
309 R3	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—
309 R4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—

309 VK

The diagram below allows the calculation of permitted overhung load R_{x2} on the output shaft of gearbox, with radial force applying at a distance x from shaft shoulder.
The curves are relevant to value resulting from the relationship of trust load A_{n2} to radial load R_{n2}, based on n_2 = 10 min^{-1} and 10000 hrs theoretical lifetime.



310M L



	L				Kg			
	PC - PZ	HC - HZ	FZ	FP - FDK	PC - PZ	HC - HZ	FZ	FP - FDK
310M L1	288	108	88	88	155	135	110	115
310M L2	424	244	224	224	185	165	140	145
310M L3	489	309	289	289	194	174	149	154
310M L4	542	362	342	342	198	178	153	158

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
310M L1	377	80	50	—	—	—	457	80	63	—	—	—	88	C		—	—	—	—	—	—
310M L2	307	60	23	—	—	—	357	60	28	—	—	—	45	B		195	147	1/4 G	6	B	28
310M L3	239	48	15	—	—	—	276	48	17	—	—	—	37	A		145	95	1/4 G	5	A	16
310M L4	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A	477	105	65	1/4 G	4	A	10

310M L



	PF 160		PF 180		PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1	E1	P1	E1	P1
310M L1*	—	—	—	—	—	—	254	550	254	550
310M L2	—	—	167	390	197	400	197	450	207	550
310M L3	165	400	165	400	195	400	195	450	—	—
310M L4	165	400	165	400	—	—	—	—	—	—

FP M_{2max} = 44000 Nm

(*) Contact Bonfiglioli's Technical Service

NOTE: For R design contact Bonfiglioli Technical service

	P71		P80		P90		P100		P112		P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
310M L1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	271	400	301	450	281	550
310M L2	—	—	—	—	—	—	—	—	—	—	—	—	152	350	153	350	183	400	212	450	193	550
310M L3	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400	—	—	—	—
310M L4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—

310M R



	R				R1	R2	R4	Kg			
	PC-PZ	HC-HZ	FZ	FP - FDK				PC-PZ	HC-HZ	FZ	FP - FDK
310M R2 (B)	495	315	295	295	345	292	400	280	260	240	250
310M R2 (C)	513	333	313	313	390	292	480	300	280	260	270
310M R3	561	381	361	361	140	186	244	209	189	164	169
310M R4	581	401	381	381	140	186	244	214	194	169	174

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
310M R2 (B)	307	60	23	—	—	—	357	60	28	—	—	—	45	B		195	147	1/4 G	6	B	28
310M R2 (C)	307	60	23	—	—	—	357	60	28	—	—	—	45	B		195	147	1/4 G	6	B	28
310M R3	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A		145	95	1/4 G	4	A	16
310M R4	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A	477	105	65	1/4 G	4	A	10

310M R













Only for configuration:

R2



For mounting the gear-box only use stud bolts

HZ HC

FZ FP

FP M_{2max} = 44000 Nm

	P71		P80		P90		P100		P112		P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
310M R2 (B)	—	—	—	—	—	—	—	—	—	—	—	—	152	350	152	350	182	400	212	450	—	—
310M R2 (C)	—	—	—	—	—	—	—	—	—	—	—	—	152	350	152	350	182	400	212	450	193	550
310M R3	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—
310M R4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—

3/V 10M L3



PC



HZ PZ





HC







FP



FZ



FDK



FP | M_{2max} = 44000 Nm

	L				Kg				P71	P80	P90	P100	P112	P132	P160
	PC - PZ	HC - HZ	FZ	FP - FDK	PC - PZ	HC - HZ	FZ	FP - FDK	P	P	P	P	P	P	P
3/V 10M L3	608	428	408	408	245	225	200	205	—	—	—	250	250	300	300

3/V 10M L4

PC





HZ PZ



HC





FP





FZ



FDK



FP M_{2max} = 44000 Nm

	L				Kg			
	PC - PZ	HC - HZ	FZ	FP	PC - PZ	HC - HZ	FZ	FP - FDK
3/V 10M L4	634	454	434	434	210	190	165	170

	P71	P80	P90	P100	P112	S1+M1			S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L		
	P	P	P	P	P	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y
3/V 10M L4	160	200	200	250	250	324	385	138	393	465	156	424	514	193	468	560	193



310M L | 310M R | 3/V 10M L

HC



PC



HZ



FZ



FP





FDK



FP	M_{2max} = 44000 Nm

310M L | 310M R | 3/V 10M L

Flange

W0A







Material: Steel C40

Pinions

P...





$\alpha = 20°$

	m	z	x	dp	di	de	H	A	B	C	Material
PLQ	12	23	—	276	246	300	110	—	—	—	Steel 18NiCrMo5 case hardened
PPD	16	13	0.500	208	184	252.5	145	—	35	116	Steel 39NiCrMo3 hardened and tempered
PPF	16	15	0.450	240	215	280	125	—	15	120	

Sleeve coupling

M0A





Material: Steel 16CrNi4

Splined bars

B0A



Material: Case hardening steel 18NiCrMo5 UNI 5331
must be case hardened 50-55 HRC

Shrink disc

G0A







310M L 310M R



V_ _



FV_ _

		V	V1	V2	V4	V5	A	B	F	L	S	D	U
310M L1	V10B	377	80	130	200	400	22	14	85	110	10	M16	36
	FV10B	457	80	130	347.5	400	22	14	85	110	10	M16	36
310M L2	V06B	307	60	105	155	292	18	11	64	90	7.5	M16	36
	FV06B	357	60	105	309	292	18	11	64	90	7.5	M16	36
310M L3	V05B	239	48	82	155	245	14	9	51.5	70	6	M16	36
	FV05B	276	48	82	219.5	244	14	9	51.5	70	6	M16	36
310M L4	V01A	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
310M R2 (B) (C)	V06B	307	60	105	155	292	18	11	64	90	7.5	M16	36
	FV06B	357	60	105	309	292	18	11	64	90	7.5	M16	36
310M R3-R4	V01A	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28

310M L 310M R







		C	D1	D2	D3	D4	D5	D6	L1	L2	L3	L4	L5	L6	S	S1	Input
310M L1	V9AC	88	70x64 DIN 5482	200	282 H7	266	M12 n°12	—	4	22	11	32	—	—	45°	45°	C
310M L2	V9AB	45	58x53 DIN 5482	195	236 H7	222	M10 n°12	—	4	18	11	22	—	—	45°	22.5°	B
310M L3	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	—	4	18	9	18	—	—	45°	45°	A
310M L4	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	11	4	—	9	18	53	18	45°	45°	A
310M R2 (B) (C)	V9AB	45	58x53 DIN 5482	195	236 H7	222	M10 n°12	—	4	18	11	22	—	—	45°	22.5°	B
310M R3-R4	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	11	4	—	9	18	37	18	45°	45°	A

3/V 10M L





	D1 h6	L3	L4	L6	L7	L8	d
3/V 10M L3_HS	35	185	65	20	10	38	M8
3/V 10M L4_HS	25	144	50	19	8	28	M8

310M L 310M R 3/V 10M L

Permissible radial and axial loads on output shaft with $Fh_2 : n_2 \cdot h = 100000$



	An2 (+)	An2 (-)
HZ - HC PZ - PC	85000	50000

	Rn2	An2 (+/-)
FZ	30170	24136

Load corrective factor fh_2 on shafts	$Fh_2 = n_2 \cdot h$	10000	25000	50000	100000	500000	1000000
	fh_2 FZ	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
	fh_2 HZ - HC - PZ - PC	**1.27**	**1.27**	**1.23**	**1.00**	**0.62**	**0.50**

Permissible radial loads on input shaft with $Fh_1 : n_1 \cdot h = 250000$



Load corrective factor fh_1 on shafts	$Fh_1 = n_1 \cdot h$	250000	500000	1000000	2000000	5000000	10000000
	fh_1	**1**	**0.79**	**0.63**	**0.50**	**0.37**	**0.29**

310M VK



310M L_VK

310M R_VK

	PF 160		PF 180		PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1	E1	P1	E1	P1
310M L1	—	—	—	—	—	—	254	550	254	550
310M L2	—	—	167	390	197	400	197	450	207	550
310M L3	165	400	165	400	195	400	195	450	—	—
310M L4	165	400	165	400	—	—	—	—	—	—

NOTE: For R design contact Bonfiglioli Technical service

	L	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg
310M L1	107	200	377	80	50	—	—	—	457	80	63	—	—	—
310M L2	243	230	307	60	23	—	—	—	357	60	28	—	—	—
310M L3	308	240	239	48	15	—	—	—	276	48	17	—	—	—
310M L4	361	245	137.5	24	6	158	38	7	—	—	—	—	—	—

	P71		P80		P90		P100		P112		P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
310M L1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	271	400	301	450	281	550
310M L2	—	—	—	—	—	—	—	—	—	—	—	—	152	350	153	350	183	400	212	450	193	550
310M L3	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400	—	—	—	—
310M L4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—

	R	R1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg
310M R2 (B)	315	345	320	307	60	23	—	—	—	357	60	28	—	—	—
310M R2 (C)	333	390	340	307	60	23	—	—	—	357	60	28	—	—	—
310M R3	380	140	250	137.5	24	6	158	38	7	—	—	—	—	—	—
310M R4	400	140	260	137.5	24	6	158	38	7	—	—	—	—	—	—

	P71		P80		P90		P100		P112		P132		P160		P180		P200		P225	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
310M R2 (B)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	152	350	182	400	212	450
310M R2 (C)	—	—	—	—	—	—	—	—	—	—	114	300	152	350	152	350	182	400	212	450
310M R3	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—
310M R4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—

310M VK

The diagram below allows the calculation of permitted overhung load R_{x2} on the output shaft of gearbox, with radial force applying at a distance x from shaft shoulder.
The curves are relevant to value resulting from the relationship of trust load A_{n2} to radial load R_{n2}, based on n_2 = 10 min^{-1} and 10000 hrs theoretical lifetime.



311M L



	L				Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP	PC - PZ	HC - HZ	FZ - FZP	FP
311M L1	325	115	115	115	250	180	160	170
311M L2	458	248	248	248	295	225	205	215
311M L3	547	337	337	337	307	237	217	227
311M L4	612	402	402	402	314	244	224	234

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
311M L1	348	80	55	—	—	—	456	80	85	—	—	—	81	D		—	—	—	—	—	—
311M L2	315	80	35	313	60	28	375	80	48	363	60	34	51	B		201	153	1/4 G	6	B	28
311M L3	239	48	15	—	—	—	276	48	17	—	—	—	37	A		145	95	1/4 G	5	A	16
311M L4	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A	477	105	65	1/4 G	4	A	10

311M L



	PF 160		PF 180		PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1	E1	P1	E1	P1
311M L1*	—	—	—	—	—	—	250	580	250	580
311M L2	—	—	—	—	197	530	227	530	227	550
311M L3	165	400	165	400	195	400	195	450	—	—
311M L4	165	400	165	400	—	—	—	—	—	—

(*) Contact Bonfiglioli's Technical Service
NOTE: For R design contact Bonfiglioli Technical service

* For dimensions refer to page 356

FZB	**M_{2max} = 66900 Nm**
FP	**M_{2max} = 55000 Nm**

	P71		P80		P90		P100		P112		P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
311M L1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	267	400	297	450	297	550
311M L2	—	—	—	—	—	—	—	—	—	—	—	—	—	—	195	350	186	400	216	450	216	550
311M L3	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400	—	—	—	—
311M L4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—

311M R



	R				R1	R2	R4	Kg			
	PC-PZ	HC-HZ	FZ - FZP	FP				PC-PZ	HC-HZ	FZ - FZP	FP
311M R2 (B)	550	340	340	340	345	292	400	380	310	290	300
311M R2 (C)	550	340	340	340	390	292	480	390	320	300	310
311M R3	577	367	367	367	225	245	375	345	275	255	265
311M R4	639	429	429	429	140	186	244	327	257	237	247

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
311M R2 (B)	307	60	23	—	—	—	357	60	28	—	—	—	45	B		195	147	1/4 G	6	B	28
311M R2 (C)	307	60	23	—	—	—	357	60	28	—	—	—	45	B		195	147	1/4 G	6	B	28
311M R3	239	48	15	—	—	—	276	48	17	—	—	—	37	A		145	95	1/4 G	5	A	16
311M R4	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A	477	105	65	1/4 G	4	A	10

311M R



FZB	M_{2max} = 66900 Nm	
FP	M_{2max} = 55000 Nm	

* For dimensions refer to page 356

	P71		P80		P90		P100		P112		P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
311M R2 (B)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	152	350	182	400	212	450	193	550
311M R2 (C)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	152	350	182	400	212	450	193	550
311M R3	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400	—	—	—	—
311M R4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—

3/V 11M L3



















* For dimensions refer to page 356

FZB	**M_{2max} = 66900 Nm**
FP	**M_{2max} = 55000 Nm**

	L				Kg				P80	P90	P100	P112	P132	P160	P180
	PC - PZ	HC - HZ	FZ - FZP	FP	PC - PZ	HC - HZ	FZ - FZP	FP	P	P	P	P	P	P	P
3/V 11M L3	659	449	449	449	390	320	300	310	—	—	250	250	300	350	350

3/V 11M L4



PC



HZ PZ





HC



FP





FZ
FZB



FZP





FZB M_{2max} = 66900 Nm

FP M_{2max} = 55000 Nm

* For dimensions refer to page 356

	L				Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP	PC - PZ	HC - HZ	FZ - FZP	FP
3/V 11M L4	707	497	497	497	340	270	250	260

	P80	P90	P100	P112	S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L		
	P	P	P	P	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y
3/V 11M L4	200	200	250	250	408	480	156	439	529	193	483	575	193



311M L 311M R 3/V 11M L

HC



PC



HZ



FZ



FZB



FP



FZP



FZB	M_{2max} = 66900 Nm
FP	M_{2max} = 55000 Nm

311M L 311M R 3/V 11M L

Flange

W0A







Material: Steel C40

Pinions

P...





$\alpha = 20°$

	m	z	x	dp	di	de	H	A	B	C	Material
PLQ	12	23	—	276	246	300	110	—	—	—	Steel 18NiCrMo5 case hardened
PPD	16	13	0.500	208	184	252.5	145	—	35	116	Steel 39NiCrMo3 hardened and tempered
PPF	16	15	0.450	240	215	280	125	—	15	120	

Sleeve coupling

M0A





Material: Steel 16CrNi4

Splined bars

B0A



Material: Case hardening steel 18NiCrMo5 UNI 5331
must be case hardened 50-55 HRC

Shrink disc

G0A







311M L 311M R



V_ _



FV_ _



		V	V1	V2	V4	V5	A	B	F	L	S	D	U
311M L1	V11B	348	80	130	200	428	22	14	85	110	10	M16	36
	FV11B	456	80	130	347.5	428	22	14	85	110	10	M16	36
311M L2	V07B	315	80	130	200	345	22	14	85	110	10	M16	36
	FV07B	375	80	130	347.5	348	22	14	85	110	10	M16	36
	V07A	313	60	105	155	345	18	11	64	90	7.5	M16	36
	FV07A	363	60	105	309	348	18	11	64	90	7.5	M16	36
311M L3	V05B	239	48	82	155	245	14	9	51.5	70	6	M16	36
	FV05B	276	48	82	219.5	244	14	9	51.5	70	6	M16	36
311M L4	V01A	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
311M R2 (B)(C)	V06B	307	60	105	155	292	18	11	64	90	7.5	M16	36
	FV06B	357	60	105	309	292	18	11	64	90	7.5	M16	36
311M R3	V05B	239	48	82	155	245	14	9	51.5	70	6	M16	36
	FV05B	276	48	82	219.5	244	14	9	51.5	70	6	M16	36
311M R4	V01A	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28

311M L 311M R







		C	D1	D2	D3	D4	D5	D6	L1	L2	L3	L4	L5	L6	S	S1	Input
311M L1	V9AD	81	80x74 DIN 5482	270	335 H7	314	M16 n°8	—	5	30	8.5	40	—	—	60°	30°	D
311M L2	V9AB	51	58x53 DIN 5482	195	236 H7	222	M10 n°12	—	4	18	11	22	—	—	45°	22.5°	B
311M L3	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	—	4	18	9	18	—	—	45°	45°	A
311M L4	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	11	4	—	9	18	65	18	45°	45°	A
311M R3	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	11	4	18	9	18	—	—	45°	45°	A
311M R2 (B) (C)	V9AB	45	58x53 DIN 5482	195	236 H7	222	M10 n°12	—	4	18	11	22	—	—	45°	22.5°	B
311M R4	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	11	4	—	9	18	37	18	45°	45°	A

3/V 11M L





	D1 h6	L3	L4	L6	L7	L8	d
3/V 11M L3_HS	40	214.5	70	20	12	43	M8
3/V 11M L4_HS	25	168	60	19	8	28	M8

311M L 311M R 3/V 11M L

Permissible radial and axial loads on output shaft with $Fh_2 : n_2 \cdot h = 100000$





	An2 (+)	An2 (-)
HZ - HC PZ - PC	100000	70000



	Rn2	An2 (+/-)
FZ	30170	27850

	$Fh_2 = n_2 \cdot h$		10000	25000	50000	100000	500000	1000000
Load corrective factor fh_2 on shafts	fh_2	FZ	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
		HC - PC	**1.93**	**1.52**	**1.23**	**1.00**	**0.62**	**0.50**
		HZ - PZ	**1.24**	**1.00**	**1.00**	**1.00**	**0.62**	**0.50**

Permissible radial loads on input shaft with $Fh_1 : n_1 \cdot h = 250000$





Load corrective factor fh_1 on shafts	$Fh_1 = n_1 \cdot h$	250000	500000	1000000	2000000	5000000	10000000
	fh_1	**1**	**0.79**	**0.63**	**0.50**	**0.37**	**0.29**

311M VK



311M L_VK

311M R_VK

	PF 160		PF 180		PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1	E1	P1	E1	P1
311M L1	—	—	—	—	—	—	250	580	250	580
311M L2	—	—	—	—	197	530	227	530	227	550
311M L3	165	400	165	400	195	400	195	450	—	—
311M L4	165	400	165	400	—	—	—	—	—	—

NOTE: For R design contact Bonfiglioli Technical service

	L	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg
311M L1	129	295	348	80	55	—	—	—	456	80	85	—	—	—
311M L2	262	340	315	80	35	313	60	28	375	80	48	363	60	34
311M L3	351	350	239	48	15	—	—	—	276	48	17	—	—	—
311M L4	416	360	137.5	24	6	158	38	7	—	—	—	—	—	—

	P71		P80		P90		P100		P112		P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
311M L1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	267	400	297	450	297	550
311M L2	—	—	—	—	—	—	—	—	—	—	—	—	—	—	195	350	186	400	216	450	216	550
311M L3	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400	—	—	—	—
311M L4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—

	R	R1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg
311M R2 (B)	354	345	420	307	60	23	—	—	—	357	60	28	—	—	—
311M R2 (C)	354	390	430	307	60	23	—	—	—	357	60	28	—	—	—
311M R3	381	225	385	239	48	15	—	—	—	276	48	17	—	—	—
311M R4	443	140	360	137.5	24	6	158	38	7	—	—	—	—	—	—

	P71		P80		P90		P100		P112		P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
311M R2 (B)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	152	350	182	400	212	450	193	550
311M R2 (C)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	152	350	182	400	212	450	193	550
311M R3	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400	—	—	—	—
311M R4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—

311M VK

The diagram below allows the calculation of permitted overhung load R_{x2} on the output shaft of gearbox, with radial force applying at a distance x from shaft shoulder.
The curves are relevant to value resulting from the relationship of trust load A_{n2} to radial load R_{n2}, based on n_2 = 10 min^{-1} and 10000 hrs theoretical lifetime.



313M L



	L				Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP	PC - PZ	HC - HZ	FZ - FZP	FP
313M L1	381	154	154	154	320	230	200	200
313M L2	531	304	304	304	380	290	260	280
313M L3	620	393	393	393	392	302	272	292
313M L4	685	458	458	458	399	309	279	299

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
313M L1	343	80	55	—	—	—	451	80	71	—	—	—	76	D		—	—	—	—	—	—
313M L2	315	80	35	313	60	28	375	80	48	363	60	34	51	B		201	153	1/4 G	6	B	28
313M L3	239	48	15	—	—	—	276	48	17	—	—	—	37	A		145	95	1/4 G	5	A	16
313M L4	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A	477	105	65	1/4 G	4	A	10

313M L



	PF 160		PF 180		PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1	E1	P1	E1	P1
313M L2	—	—	—	—	197	530	227	530	227	550
313M L3	165	400	165	400	195	400	195	450	—	—
313M L4	165	400	165	400	—	—	—	—	—	—

NOTE: For R design contact Bonfiglioli Technical service

* For dimensions refer to page 368

FP M_{2max} = 79000 Nm

	P71		P80		P90		P100		P112		P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
313M L2	—	—	—	—	—	—	—	—	—	—	—	—	—	—	195	350	186	400	216	450	216	550
313M L3	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400	—	—	—	—
313M L4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—

313M R



	R				R1	R2	R3			R4	Kg			
	PC-PZ	HC-HZ	FZ - FZP	FP			HC-HZ	FZ	FP		PC-PZ	HC-HZ	FZ - FZP	FP
313M R2 (B)	611	384	384	384	345	292	199	199	199	400	450	360	330	350
313M R2 (C)	611	384	384	384	390	292	168	168	168	480	460	370	340	360
313M R3	650	423	423	423	225	245	169	169	169	345	430	340	310	330
313M R4	712	485	485	485	140	186	169	169	169	244	412	322	292	312

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
313M R2 (B)	307	60	23	—	—	—	357	60	28	—	—	—	45	B		195	147	1/4 G	6	B	28
313M R2 (C)	307	60	23	—	—	—	357	60	28	—	—	—	45	B		195	147	1/4 G	6	B	28
313M R3	239	48	15	—	—	—	276	48	17	—	—	—	37	A		145	95	1/4 G	5	A	16
313M R4	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A	477	105	65	1/4 G	4	A	10

313M R



FP M_{2max} = 79000 Nm

* For dimensions refer to page 368

	P71		P80		P90		P100		P112		P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
313M R2 (B)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	152	350	182	400	212	450	193	550
313M R2 (C)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	152	350	182	400	212	450	193	550
313M R3	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400	—	—	—	—
313M R4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—

3/V 13M L3









PC



HZ **PZ**



HC



FP



FZ
FZB



FZP



* For dimensions refer to page 368

FP | **M_{2max} = 79000 Nm**

	L				Kg				P80	P90	P100	P112	P132	P160	P180
	PC - PZ	HC - HZ	FZ - FZP	FP	PC - PZ	HC - HZ	FZ - FZP	FP	P	P	P	P	P	P	P
3/V 13M L3	732	505	505	505	475	385	355	375	—	—	250	250	300	350	350

3/V 13M L4



PC



HZ PZ





HC



FP





FZ
FZB



FZP





FP | M_{2max} = 79000 Nm

* For dimensions refer to page 368

	L				Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP	PC - PZ	HC - HZ	FZ - FZP	FP
3/V 13M L4	780	553	553	553	425	335	305	325

	P80	P90	P100	P112	P132	S2+ME2S/MX2S			S3+ME3S/MX3S			S3+ME3L/MX3L		
	P	P	P	P	P	L1	L1f	Y	L1	L1f	Y	L1	L1f	Y
3/V 13M L4	200	200	250	250	300	408	480	156	439	529	193	483	575	193



313M L 313M R 3/V 13M L

HC



PC



HZ



FZ



FZB



FP



FZP



FP	M_{2max} = 79000 Nm

313M L 313M R 3/V 13M L

Flange

W0A







Material: Steel C40

Pinions

P...





$\alpha = 20°$

	m	z	x	dp	di	de	H	A	B	C	Material
PPH	16	17	0.500	272	247	315	135	—	5	136	Steel 39NiCrMo3 hardened and tempered
PRI	18	18	0.333	324	294	365	140	—	10	140	

Sleeve coupling

M0A





Material: Steel 16CrNi4

Splined bars

B0A



Material: Case hardening steel 18NiCrMo5 UNI 5331
must be case hardened 50-55 HRC

Shrink disc

G0A







313M L 313M R



V_ _



FV_ _



		V	V1	V2	V4	V5	A	B	F	L	S	D	U
313M L1	V11B	343	80	130	200	445	22	14	85	110	10	M16	36
	FV11B	451	80	130	347.5	445	22	14	85	110	10	M16	36
313M L2	V07B	315	80	130	200	345	22	14	85	110	10	M16	36
	FV07B	375	80	130	347.5	348	22	14	85	110	10	M16	36
	V07A	313	60	105	155	345	18	11	64	90	7.5	M16	36
	FV07A	363	60	105	309	348	18	11	64	90	7.5	M16	36
313M L3	V05B	239	48	82	155	245	14	9	51.5	70	6	M16	36
	FV05B	276	48	82	219.5	244	14	9	51.5	70	6	M16	36
313M L4	V01A	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28
313M R2 (B) (C)	V06B	307	60	105	155	292	18	11	64	90	7.5	M16	36
	FV06B	357	60	105	309	292	18	11	64	90	7.5	M16	36
313M R3	V05B	239	48	82	155	245	14	9	51.5	70	6	M16	36
	FV05B	276	48	82	219.5	244	14	9	51.5	70	6	M16	36
313M R4	V01A	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28

313M L 313M R







		C	D1	D2	D3	D4	D5	D6	L1	L2	L3	L4	L5	L6	S	S1	Input
313M L1	V9AD	75	80x74 DIN 5482	270	335 H7	314	M16 n°8	—	5	30	8.5	40	—	—	60°	30°	D
313M L2	V9AB	51	58x53 DIN 5482	195	236 H7	222	M10 n°12	—	4	18	11	22	—	—	45°	22.5°	B
313M L3	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	—	4	18	9	18	—	—	45°	45°	A
313M L4	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	11	4	—	9	18	65	18	45°	45°	A
313M R3	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	11	4	18	9	18	—	—	45°	45°	A
313M R2 (B) (C)	V9AB	45	58x53 DIN 5482	195	236 H7	222	M10 n°12	—	4	18	11	22	—	—	45°	22.5°	B
313M R4	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	11	4	—	9	18	37	18	45°	45°	A

3/V 13M L





	D1 h6	L3	L4	L6	L7	L8	d
3/V 13M L3_HS	40	214.5	70	20	12	43	M8
3/V 13M L4_HS	25	168	60	19	8	28	M8

313M L 313M R 3/V 13M L

Permissible radial and axial loads on output shaft with $Fh_2 : n_2 \cdot h = 100000$





	An2 (+)	An2 (-)
HZ - HC PZ - PC	125000	80000



	Rn2	An2 (+/-)
FZ	37133	34812

Load corrective factor fh_2 on shafts	$Fh_2 = n_2 \cdot h$		10000	25000	50000	100000	500000	1000000
	fh_2	FZ	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
		HZ - HC - PZ - PC	**1.32**	**1.20**	**1.20**	**1.00**	**0.62**	**0.50**

Permissible radial loads on input shaft with $Fh_1 : n_1 \cdot h = 250000$





Load corrective factor fh_1 on shafts	$Fh_1 = n_1 \cdot h$	250000	500000	1000000	2000000	5000000	10000000
	fh_1	**1**	**0.79**	**0.63**	**0.50**	**0.37**	**0.29**

313M VK



313M L_VK

313M R_VK

	PF 160		PF 180		PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1	E1	P1	E1	P1
313M L2	—	—	—	—	197	530	227	530	227	550
313M L3	165	400	165	400	195	400	195	450	—	—
313M L4	165	400	165	400	—	—	—	—	—	—

NOTE: For R design contact Bonfiglioli Technical service

	L	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg
313M L1	158	380	343	80	55	—	—	—	451	80	71	—	—	—
313M L2	308	440	315	80	35	313	60	28	375	80	48	363	60	34
313M L3	397	450	239	48	15	—	—	—	276	48	17	—	—	—
313M L4	462	460	137.5	24	6	158	38	7	—	—	—	—	—	—

	P71		P80		P90		P100		P112		P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
313M L2	—	—	—	—	—	—	—	—	—	—	—	—	—	—	195	350	186	400	216	450	216	550
313M L3	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400	—	—	—	—
313M L4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—

	R	R1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg
313M R2 (B)	388	345	510	307	60	23	—	—	—	357	60	28	—	—	—
313M R2 (C)	388	390	520	307	60	23	—	—	—	357	60	28	—	—	—
313M R3	427	225	490	239	48	15	—	—	—	—	—	—	—	—	—
313M R4	489	140	470	137.5	24	6	158	38	7	—	—	—	—	—	—

	P71		P80		P90		P100		P112		P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
313M R2 (B)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	152	350	182	400	212	450	193	550
313M R2 (C)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	152	350	182	400	212	450	193	550
313M R3	—	—	—	—	—	—	—	—	—	—	114	300	144	350	144	350	174	400	—	—	—	—
313M R4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—

313M VK

The diagram below allows the calculation of permitted overhung load R_{x2} on the output shaft of gearbox, with radial force applying at a distance x from shaft shoulder.
The curves are relevant to value resulting from the relationship of trust load A_{n2} to radial load R_{n2}, based on n_2 = 10 min^{-1} and 10000 hrs theoretical lifetime.



314M L



	L				Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP	PC - PZ	HC - HZ	FZ - FZP	FP
314M L1	453	174	174	174	500	370	280	330
314M L2	641	362	362	362	545	415	325	375
314M L3	777	498	498	498	590	460	370	420
314M L4	842	563	563	563	600	470	380	430

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
314M L1	—	—	—	—	—	—	—	—	—	—	—	—	120	L		—	—	—	—	—	—
314M L2	377	80	50	—	—	—	457	80	63	—	—	—	88	C		195	147	1/4 G	6	B	28
314M L3	307	60	23	—	—	—	357	60	28	—	—	—	45	B	477	145	95	1/4 G	5	B	16
314M L4	239	48	15	—	—	—	276	48	17	—	—	—	37	A		105	65	1/4 G	5	A	10

314M L



	PF 160		PF 180		PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1	E1	P1	E1	P1
314M L2	—	—	—	—	—	—	254	550	254	550
314M L3	—	—	167	390	197	400	197	450	207	550
314M L4	165	400	165	400	195	400	197	450	—	—

NOTE: For R design contact Bonfiglioli Technical service

FP M_{2max} = 115000 Nm

	P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P
314M L2	—	—	—	—	—	—	271	400	301	450	281	550
314M L3	—	—	153	350	153	350	183	400	213	450	193	550
314M L4	114	300	144	350	144	350	174	400	—	—	—	—

314M R



	R				R1	R2	R4	Kg			
	PC-PZ	HC-HZ	FZ - FZP	FP				PC-PZ	HC-HZ	FZ - FZP	FP
314M R3 (B)	848	569	569	569	345	292	400	720	590	500	550
314M R3 (C)	856	587	587	587	390	292	480	730	600	510	560
314M R4	914	635	635	635	140	186	244	680	550	460	510

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
314M R3 (B)	307	60	23	—	—	—	357	60	28	—	—	—	45	B		195	147	1/4 G	6	B	28
314M R3 (C)	307	60	23	—	—	—	357	60	28	—	—	—	45	B		195	147	1/4 G	6	B	28
314M R4	137.5	24	6	158	38	7	—	—	—	—	—	—	37	A	477	105	65	1/4 G	4	A	10

314M R









FP M_{2max} = 115000 Nm

	P71		P80		P90		P100		P112		P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
314M R3 (B)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	152	350	182	400	212	450	193	550
314M R3 (C)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	152	350	182	400	212	450	193	550
314M R4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—

3/V 14M L3



FP M_{2max} = 115000 Nm

	L				L1	L2	D1	L3	L4	Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP						PC - PZ	HC - HZ	FZ - FZP	FP
3/V 14M L3	920	641	641	641	185	217	40	214.5	70	665	535	445	495

	P100	P112	P132		P160		P180	
	P	P	L2	P	L2	P	L2	P
3/V 14M L3	250	250	—	300	—	350	—	350

3/V 14M L4



FP M_{2max} = 115000 Nm

	L				L1	L2	D1	L3	L4	Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP						PC - PZ	HC - HZ	FZ - FZP	FP
3/V 14M L4	961	682	682	682	150	190	35	185	65	690	560	470	520

	P100	P112	P132		P160		P180	
	P	P	L2	P	L2	P	L2	P
3/V 14M L4	250	250	—	300	—	350	—	—



314M L 314M R 3/V 14M L

HC



PC



HZ



FZ



FP



FZP



FP	M_{2max} = 115000 Nm



314M L | 314M R | 3/V 14M L

Flange

W0A





Material: Steel C40

Pinions

P...





α = 20°

	m	z	x	dp	di	de	H	A	B	C	Material
PRG1	18	16	0.500	288	261	342	160	—	10	166	Steel 18NiCrMo5 case hardened
PRG2	18	16	0.617	288	271	339	150	30	—	—	Steel 39NiCrMo3 hardened and tempered

Sleeve coupling

M0A





Material: Steel 16CrNi4

Splined bars

B0A





Material: Case hardening steel 18NiCrMo5 UNI 5331
must be case hardened 50-55 HRC

Shrink disc

G0A







314M L 314M R



V_ _



FV_ _

		V	V1	V2	V4	V5	A	B	F	L	S	D	U
314M L2	V10B	377	80	130	200	400	22	14	85	110	10	M16	36
	FV10B	457	80	130	347.5	400	22	14	85	110	10	M16	36
314M L3	V06B	307	60	105	155	292	18	11	64	90	7.5	M16	36
	FV06B	357	60	105	309	292	18	11	64	90	7.5	M16	36
314M L4	V05B	239	48	82	155	245	14	9	51.5	70	6	M16	36
	FV05B	276	48	82	219.5	244	14	9	51.5	70	6	M16	36
314M R3 (B) (C)	V06B	307	60	105	155	292	18	11	64	90	7.5	M16	36
	FV06B	357	60	105	309	292	18	11	64	90	7.5	M16	36
314M R4	V01A	137.5	24	36	120	186	8	7	27	30	3	M8	19
	V01B	158	38	58	120	186	10	8	41	50	4	M12	28

314M L 314M R







		C	D1	D2	D3	D4	D5	D6	L1	L2	L3	L4	L5	L6	S	S1	Input
314M L1	V9AL	120	100x94 DIN 5482	295	336 H7	370	M16 n°15	—	8	21	13	55	—	—	24°	24°	L
314M L2	V9AC	88	70x64 DIN 5482	200	282 H7	266	M12 n°12	—	4	22	11	32	—	—	45°	45°	C
314M L3	V9AB	45	58x53 DIN 5482	195	236 H7	222	M10 n°12	—	4	18	11	22	—	—	45°	22.5°	B
314M L4	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	—	4	18	9	18	—	—	45°	45°	A
314M R3 (B) (C)	V9AB	45	58x53 DIN 5482	195	236 H7	222	M10 n°12	—	4	18	11	22	—	—	45°	22.5°	B
314M R4	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	11	4	—	9	18	37	18	45°	45°	A

3/V 14M L





	D1 h6	L3	L4	L6	L7	L8	d
3/V 14M L3_HS	40	214.5	70	20	12	43	M8
3/V 14M L4_HS	35	185	65	20	10	38	M8

314M L 314M R 3/V 14M L

Permissible radial and axial loads on output shaft with $Fh_2 : n_2 \cdot h = 100000$





	An2 (+)	An2 (-)
HZ - HC PZ - PC	140000	105000



	Rn2	An2 (+/-)
FZ	41774	41774

Load corrective factor fh_2 on shafts	$Fh_2 = n_2 \cdot h$		10000	25000	50000	100000	500000	1000000
	fh_2	FZ	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
		HZ - HC - PZ - PC	**2.00**	**1.52**	**1.23**	**1.00**	**0.62**	**0.50**

Permissible radial loads on input shaft with $Fh_1 : n_1 \cdot h = 250000$





Load corrective factor fh_1 on shafts	$Fh_1 = n_1 \cdot h$	250000	500000	1000000	2000000	5000000	10000000
	fh_1	**1**	**0.79**	**0.63**	**0.50**	**0.37**	**0.29**

314M VK



314M L_VK

314M R_VK

	PF 160		PF 180		PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1	E1	P1	E1	P1
314M L2	—	—	—	—	—	—	254	550	254	550
314M L3	—	—	167	390	197	400	197	450	207	550
314M L4	165	400	165	400	195	400	197	450	—	—

NOTE: For R design contact Bonfiglioli Technical service

	L	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	P132		P160		P180		P200		P225		P250	
															E	P	E	P	E	P	E	P	E	P	E	P
314M L2	386	650	348	80	55	—	—	—	457	80	63	—	—	—	—	—	—	—	—	—	271	400	301	450	281	550
314M L3	519	700	315	80	35	313	60	28	357	60	28	—	—	—	—	—	153	350	153	350	183	400	213	450	193	550
314M L4	608	710	239	48	15	—	—	—	276	48	17	—	—	—	114	300	144	350	144	350	174	400	—	—	—	—

	R	R1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg
314M R3 (B)	611	345	720	307	60	23	—	—	—	357	60	28	—	—	—
314M R3 (C)	611	390	730	307	60	23	—	—	—	357	60	28	—	—	—
314M R4	638	225	690	137.5	24	6	158	38	7	—	—	—	—	—	—

	P71		P80		P90		P100		P112		P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P	E	P
314M R3 (B)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	152	350	182	400	212	450	193	550
314M R3 (C)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	152	350	182	400	212	450	193	550
314M R4	65	160	84	200	84	200	94	250	94	250	114	300	144	350	—	—	—	—	—	—	—	—

314M VK

The diagram below allows the calculation of permitted overhung load R_{x2} on the output shaft of gearbox, with radial force applying at a distance x from shaft shoulder.
The curves are relevant to value resulting from the relationship of trust load A_{n2} to radial load R_{n2}, based on n_2 = 10 min^{-1} and 10000 hrs theoretical lifetime.





315M L



	L				Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP	PC - PZ	HC - HZ	FZ - FZP	FP
315M L1	453	174	174	174	500	370	280	330
315M L2	665	386	386	386	585	455	365	415
315M L3	798	519	519	519	630	500	410	460
315M L4	887	608	608	608	642	512	422	472

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
315M L1	556	120	125	—	—	—	—	—	—	—	—	—	116	E		—	—	—	—	—	—
315M L2	348	80	55	—	—	—	456	80	85	—	—	—	81	D		232	185	1/4 G	6	B	35
315M L3	315	80	35	313	60	28	375	80	48	363	60	34	51	B	477	201	153	1/4 G	6	B	28
315M L4	239	48	15	—	—	—	276	48	17	—	—	—	37	A		145	95	1/4 G	5	A	16

315M L



	PF 160		PF 180		PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1	E1	P1	E1	P1
315M L2	—	—	—	—	—	—	250	580	250	580
315M L3	—	—	—	—	197	530	227	530	227	550
315M L4	165	400	165	400	195	400	195	450	—	—

NOTE: For R design contact Bonfiglioli Technical service

FP M_{2max} = 135000 Nm

	P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P
315M L2	—	—	—	—	—	—	267	400	297	450	297	550
315M L3	—	—	—	—	195	350	186	400	216	450	215	550
315M L4	114	300	144	350	144	350	174	400	—	—	—	—

315M R



	R				R1	R2	R4	Kg			
	PC-PZ	HC-HZ	FZ - FZP	FP				PC-PZ	HC-HZ	FZ - FZP	FP
315M R3 (B)	890	611	611	611	345	292	400	720	590	500	550
315M R3 (C)	890	611	611	611	390	292	480	730	600	510	560
315M R4	917	638	638	638	225	245	345	680	550	460	510

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
315M R3 (B)	307	60	23	—	—	—	357	60	28	—	—	—	45	B		195	147	1/4 G	6	B	28
315M R3 (C)	307	60	23	—	—	—	357	60	28	—	—	—	45	B		195	147	1/4 G	6	B	28
315M R4	239	48	15	—	—	—	276	48	17	—	—	—	37	A	477	145	95	1/4 G	5	A	16

315M R









FP M_{2max} = 135000 Nm

	P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P
315M R3 (B)	—	—	—	—	152	350	182	400	212	450	193	550
315M R3 (C)	—	—	—	—	152	350	182	400	212	450	193	550
315M R4	114	300	144	350	144	350	174	400	—	—	—	—

3/V 15M L3



FP M_{2max} = 135000 Nm

	L				L1	L2	D1	L3	L4	Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP						PC - PZ	HC - HZ	FZ - FZP	FP
3/V 15M L3	885	606	606	606	210	—	48	230	110	800	670	575	625

	P100	P112	P132		P160		P180		P200		P225	
	P	P	L2	P	L2	P	L2	P	L2	P	L2	P
3/V 15M L3	—	—	485	300	460	350	460	350	485	400	490	450

3/V 15M L4



FP M_{2max} = 135000 Nm

	L				L1	L2	D1	L3	L4	Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP						PC - PZ	HC - HZ	FZ - FZP	FP
3/V 15M L4	989	710	710	710	150	190	35	185	65	690	560	470	520

	P100	P112	P132		P160		P180		P200		P225	
	P	P	L2	P	L2	P	L2	P	L2	P	L2	P
3/V 15M L4	250	250	—	300	—	350	—	—	—	—	—	—



315M L | 315M R | 3/V 15M L

HC



PC



HZ



FZ



FP



FZP



FP	M_{2max} = 135000 Nm



315M L | 315M R | 3/V 15M L

Flange

W0A





Material: Steel C40

Pinions

P...





$\alpha = 20°$

	m	z	x	dp	di	de	H	A	B	C	Material
PRG1	18	16	0.500	288	261	342	160	—	10	166	Steel 18NiCrMo5 case hardened
PRG2	18	16	0.617	288	271	339	150	30	—	—	Steel 39NiCrMo3 hardened and tempered

Sleeve coupling

M0A





Material: Steel 16CrNi4

Splined bars

B0A





Material: Case hardening steel 18NiCrMo5 UNI 5331
must be case hardened 50-55 HRC

Shrink disc

G0A







315M L 315M R



V_ _



FV_ _



		V	V1	V2	V4	V5	A	B	F	L	S	D	U
315M L1	**V15B**	556	120	210	230	542	32	18	127	180	15	M24	50
315M L2	**V11B**	348	80	130	200	418	22	14	85	110	10	M16	36
	FV11B	456	80	130	347.5	428	22	14	85	110	10	M16	36
315M L3	**V07B**	315	80	130	200	345	22	14	85	110	10	M16	36
	FV07B	375	80	130	347.5	348	22	14	85	110	10	M16	36
	V07A	313	60	105	155	345	18	11	64	90	7.5	M16	36
	FV07A	363	60	105	309	348	18	11	64	90	7.5	M16	36
315M L4	**V05B**	239	48	82	155	245	14	9	51.5	70	6	M16	36
	FV05B	276	48	82	219.5	244	14	9	51.5	70	6	M16	36
315M R3 (B) (C)	**V06B**	307	60	105	155	292	18	11	64	90	7.5	M16	36
	FV06B	357	60	105	309	292	18	11	64	90	7.5	M16	36
315M R4	**V05B**	239	48	82	155	245	14	9	51.5	70	6	M16	36
	FV05B	276	48	82	219.5	244	14	9	51.5	70	6	M16	36

315M L 315M R







		C	D1	D2	D3	D4	D5	D6	L1	L2	L3	L4	L5	L6	S	S1	Input
315M L1	**V9AE**	116	100x94 DIN 5482	340	412 H7	390	M16 n°18	—	7	30	8	55	—	—	20°	20°	E
315M L2	**V9AD**	81	80x74 DIN 5482	270	335 H7	314	M16 n°8	—	5	30	8.5	40	—	—	60°	30°	D
315M L3	**V9AB**	51	58x53 DIN 5482	195	236 H7	222	M10 n°12	—	4	18	11	22	—	—	45°	22.5°	B
315M L4	**V9AA**	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	—	4	18	9	18	—	—	45°	45°	A
315M R4	**V9AA**	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	11	4	18	9	18	—	—	45°	45°	A
315M R3 (B) (C)	**V9AB**	45	58x53 DIN 5482	195	236 H7	222	M10 n°12	—	4	18	11	22	—	—	45°	22.5°	B

3/V 15M L





	D1 h6	L3	L4	L6	L7	L8	d
3/V 15M L3_HS	48	230	110	40	14	51.5	M16
3/V 15M L4_HS	35	185	65	20	10	38	M8

315M L 315M R 3/V 15M L

Permissible radial and axial loads on output shaft with $Fh_2 : n_2 \cdot h = 100000$





	An2 (+)	An2 (-)
HZ - HC PZ - PC	140000	105000



	Rn2	An2 (+/-)
FZ	41774	41774

Load corrective factor fh_2 on shafts	$Fh_2 = n_2 \cdot h$		10000	25000	50000	100000	500000	1000000
	fh_2	FZ	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
		HZ - HC - PZ - PC	**2.00**	**1.52**	**1.23**	**1.00**	**0.62**	**0.50**

Permissible radial loads on input shaft with $Fh_1 : n_1 \cdot h = 250000$





Load corrective factor fh_1 on shafts	$Fh_1 = n_1 \cdot h$	250000	500000	1000000	2000000	5000000	10000000
	fh_1	**1**	**0.79**	**0.63**	**0.50**	**0.37**	**0.29**

315M VK



315M L_VK

315M R_VK

	PF 160		PF 180		PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1	E1	P1	E1	P1
315M L2	—	—	—	—	—	—	250	580	250	580
315M L3	—	—	—	—	197	530	227	530	227	550
315M L4	165	400	165	400	195	400	195	450	—	—

NOTE: For R design contact Bonfiglioli Technical service

	L	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	P132		P160		P180		P200		P225		P250	
															E	P	E	P	E	P	E	P	E	P	E	P
315M L2	386	650	348	80	55	—	—	—	456	80	85	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
315M L3	519	700	315	80	35	313	60	28	375	80	48	363	60	34	—	—	—	—	195	350	186	400	216	450	215	550
315M L4	608	710	239	48	15	—	—	—	276	48	17	—	—	—	114	300	144	350	144	350	174	400	—	—	—	—

	R	R1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	P132		P160		P180		P200		P225		P250	
																E	P	E	P	E	P	E	P	E	P	E	P
315M R3 (B)	611	345	720	307	60	23	—	—	—	357	60	28	—	—	—	—	—	—	—	152	350	182	400	212	450	193	550
315M R3 (C)	611	390	730	307	60	23	—	—	—	357	60	28	—	—	—		—	—	—	152	350	182	400	212	450	193	550
315M R4	638	225	690	239	48	15	—	—	—	276	48	17	—	—	—	114	300	144	350	144	350	174	400	—	—	—	—

315M VK

The diagram below allows the calculation of permitted overhung load R_{x2} on the output shaft of gearbox, with radial force applying at a distance x from shaft shoulder.
The curves are relevant to value resulting from the relationship of trust load A_{n2} to radial load R_{n2}, based on n_2 = 10 min^{-1} and 10000 hrs theoretical lifetime.



316M L



	L				Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP	PC - PZ	HC - HZ	FZ - FZP	FP
316M L1	289	179	179	179	700	500	430	450
316M L2	541	431	431	431	790	590	520	540
316M L3	674	564	564	564	840	640	570	590
316M L4	763	653	653	653	860	660	590	610

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
316M L1	—	—	—	—	—	—	—	—	—	—	—	—	156	E		—	—	—	—	—	—
316M L2	348	80	55	—	—	—	456	80	85	—	—	—	81	D		—	—	—	—	—	—
316M L3	315	80	35	313	60	28	375	80	48	363	60	34	51	B	477	201	153	1/4 G	6	B	28
316M L4	239	48	15	—	—	—	276	48	17	—	—	—	37	A		145	95	1/4 G	5	A	16

316M L



	PF 160		PF 180		PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1	E1	P1	E1	P1
316M L2	—	—	—	—	—	—	250	580	250	580
316M L3	—	—	—	—	197	530	227	530	227	550
316M L4	165	400	165	400	195	400	195	450	—	—

NOTE: For R design contact Bonfiglioli Technical service

FP	M_{2max} = 178000 Nm

	P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P
316M L2	—	—	—	—	—	—	267	400	297	450	297	550
316M L3	—	—	—	—	195	350	186	400	216	450	215	550
316M L4	114	300	144	350	144	350	174	400	—	—	—	—

316M R



	R				R1	R2	R4	Kg			
	PC-PZ	HC-HZ	FZ - FZP	FP				PC-PZ	HC-HZ	FZ - FZP	FP
316M R3 (B)	766	656	656	656	345	292	400	910	710	640	660
316M R3 (C)	766	656	656	656	390	292	480	920	720	650	670
316M R4	793	683	683	683	225	245	345	890	690	620	640

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
316M R3 (B)	307	60	23	—	—	—	357	60	28	—	—	—	45	B		195	147	1/4 G	6	B	28
316M R3 (C)	307	60	23	—	—	—	357	60	28	—	—	—	45	B		195	147	1/4 G	6	B	28
316M R4	239	48	15	—	—	—	276	48	17	—	—	—	37	A	477	145	95	1/4 G	5	A	16

316M R









FP M_{2max} = 178000 Nm

	P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P
316M R3 (B)	—	—	—	—	152	350	182	400	212	450	193	550
316M R3 (C)	—	—	—	—	152	350	182	400	212	450	193	550
316M R4	114	300	144	350	144	350	174	400	—	—	—	—

3/V 16M L3





FP M_{2max} = 178000 Nm

	L				L1	D1	L3	L4	Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP					PC - PZ	HC - HZ	FZ - FZP	FP
3/V 16M L3	812	702	702	702	250	55	274	110	1100	900	830	850

	P132		P160		P180		P200		P225	
	L2	P	L2	P	L2	P	L2	P	L2	P
3/V 16M L3	531	300	506	350	506	350	531	400	536	450

3/V 16M L4



FP M_{2max} = 178000 Nm

	L				L1	D1	L3	L4	Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP					PC - PZ	HC - HZ	FZ - FZP	FP
3/V 16M L4	865	755	755	755	150	35	185	65	900	700	630	650

	P100		P112		P132		P160	
	L2	P	L2	P	L2	P	L2	P
3/V 16M L4	190	250	190	250	190	300	190	350



316M L 316M R 3/V 16M L

HC



PC



HZ



FZ



FP



FZP



FP | M_{2max} = 178000 Nm

Flange

W0A





Material: Steel C40

Sleeve coupling

M0A





Material: Steel C40

Splined bars

B0A



Material: Case hardening steel 18NiCrMo5 UNI 5331
must be case hardened 50-55 HRC

Shrink disc

G0A







316M L 316M R



V_ _



FV_ _



		V	V1	V2	V4	V5	A	B	F	L	S	D	U
316M L2	V11B	348	80	130	200	418	22	14	85	110	10	M16	36
	FV11B	456	80	130	347.5	428	22	14	85	110	10	M16	36
316M L3	V07B	315	80	130	200	345	22	14	85	110	10	M16	36
	FV07B	375	80	130	347.5	348	22	14	85	110	10	M16	36
	V07A	313	60	105	155	345	18	11	64	90	7.5	M16	36
	FV07A	363	60	105	309	348	18	11	64	90	7.5	M16	36
316M L4	V05B	239	48	82	155	245	14	9	51.5	70	6	M16	36
	FV05B	276	48	82	219.5	244	14	9	51.5	70	6	M16	36
316M R3 (B) (C)	V06B	307	60	105	155	292	18	11	64	90	7.5	M16	36
	FV06B	357	60	105	309	292	18	11	64	90	7.5	M16	36
316M R4	V05B	239	48	82	155	245	14	9	51.5	70	6	M16	36
	FV05B	276	48	82	219.5	244	14	9	51.5	70	6	M16	36

316M L 316M R







		C	D1	D2	D3	D4	D5	D6	L1	L2	L3	L4	L5	L6	S	S1	Input
316M L1	V9AE	116	100x94 DIN 5482	340	412 H7	390	M16 n° 18	—	7	30	8	55	—	—	20°	20°	E
316M L2	V9AD	81	80x74 DIN 5482	270	335 H7	314	M16 n° 8	—	5	30	8.5	40	—	—	60°	30°	D
316M L3	V9AB	51	58x53 DIN 5482	195	236 H7	222	M10 n° 12	—	4	18	11	22	—	—	45°	22.5°	B
316M L4	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n° 8	—	4	18	9	18	—	—	45°	45°	A
316M R3 (B) (C)	V9AB	45	58x53 DIN 5482	195	236 H7	222	M10° 12	—	4	18	11	22	—	—	45°	22.5°	B
316M R4	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n° 8	11	4	18	9	18	—	—	45°	45°	A

3/V 16M L





	D1 h6	L3	L4	L6	L7	L8	d
3/V 16M L3_HS	55	274	110	40	16	59	M16
3/V 16M L4_HS	35	185	65	20	10	38	M8

316M L 316M R 3/V 16M L

Permissible radial and axial loads on output shaft with $Fh_2 : n_2 \cdot h = 100000$





	An2 (+)	An2 (-)
HZ - HC PZ - PC	180000	150000



	Rn2	An2 (+/-)
FZ	69624	69624

	Fh2 = n2 · h	10000	25000	50000	100000	500000	1000000
Load corrective factor fh_2 on shafts	FZ	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
	HC - PC	**1.16**	**1.00**	**1.00**	**1.00**	**0.62**	**0.50**
	HZ - PZ	**1.19**	**1.02**	**1.02**	**1.00**	**0.62**	**0.50**

Permissible radial loads on input shaft with $Fh_1 : n_1 \cdot h = 250000$





	Fh1 = n1 · h	250000	500000	1000000	2000000	5000000	10000000
Load corrective factor fh_1 on shafts	fh_1	**1**	**0.79**	**0.63**	**0.50**	**0.37**	**0.29**

317M L



	L				Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP	PC - PZ	HC - HZ	FZ - FZP	FP
317M L1	315	163	163	163	950	800	750	800
317M L2	624	472	472	472	1080	930	880	930
317M L3	774	622	622	622	1140	990	940	990
317M L4	862	710	710	710	1152	1000	952	1000

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
317M L1	—	—	—	—	—	—	—	—	—	—	—	—	181	F		—	—	—	—	—	—
317M L2	343	80	55	—	—	—	451	80	71	—	—	—	75	D		—	—	—	—	—	—
317M L3	315	80	35	313	60	28	375	80	48	363	60	34	51	B	477	201	153	1/4 G	6	B	28
317M L4	239	48	15	—	—	—	276	48	17	—	—	—	37	A		145	95	1/4 G	5	A	16

317M L



	PF 160		PF 180		PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1	E1	P1	E1	P1
317M L3	—	—	—	—	197	530	227	530	227	550
317M L4	165	400	165	400	195	400	195	450	—	—

NOTE: For R design contact Bonfiglioli Technical service

FP M_{2max} = 242000 Nm

	P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P
317M L3	—	—	—	—	196	350	186	400	216	450	216	550
317M L4	114	300	144	350	144	350	174	400	—	—	—	—



317M R



	R				R1	R2	R4	Kg			
	PC-PZ	HC-HZ	FZ - FZP	FP				PC-PZ	HC-HZ	FZ - FZP	FP
317M R3 (B)	853	701	701	701	345	292	400	1210	1060	1010	1060
317M R3 (C)	853	701	701	701	390	292	480	1220	1070	1020	1070
317M R4	892	740	740	740	225	245	345	1190	1040	990	1040

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
317M R3 (B)	307	60	23	—	—	—	357	60	28	—	—	—	45	B		195	147	1/4 G	6	B	28
317M R3 (C)	307	60	23	—	—	—	357	60	28	—	—	—	45	B		195	147	1/4 G	6	B	28
317M R4	239	48	15	—	—	—	276	48	17	—	—	—	37	A	477	105	65	1/4 G	4	A	10

317M R













FP M_{2max} = 242000 Nm

	P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P
317M R3 (B)	—	—	—	—	152	350	182	400	212	450	193	550
317M R3 (C)	—	—	—	—	152	350	182	400	212	450	193	550
317M R4	114	300	144	350	144	350	174	400	—	—	—	—

3/V 17M L3





















FP M_{2max} = 242000 Nm

	L				L1	D1	L3	L4	Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP					PC - PZ	HC - HZ	FZ - FZP	FP
3/V 17M L3	894	745	745	745	250	55	276	110	1400	1250	1200	1250

	P132		P160		P180		P200		P225	
	L2	P	L2	P	L2	P	L2	P	L2	P
3/V 17M L3	531	300	506	350	506	350	531	400	536	450

3/V 17M L4





















FP M_{2max} = 242000 Nm

	L				L1	D1	L3	L4	Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP					PC - PZ	HC - HZ	FZ - FZP	FP
3/V 17M L4	975	823	823	823	185.4	40	214.5	70	1250	1090	1040	1090

	P100	P112	P132		P160		P180	
	P	P	L2	P	L2	P	L2	P
3/V 17M L4	250	250	217	300	217	350	217	350

317M L 317M R 3/V 17M L

HC



PC



HZ



FZ



FP



FZP



FP	M_{2max} = 242000 Nm

Flange

W0A







Material: Steel C40

Sleeve coupling

M0A





Material: Steel 16CrNi4

Shrink disc

G0A







317M L 317M R



V_ _



FV_ _



		V	V1	V2	V4	V5	A	B	F	L	S	D	U
317M L2	V11B	343	80	130	200	445	22	14	85	110	10	M16	36
	FV11B	451	80	130	347.5	445	22	14	85	110	10	M16	36
317M L3	V07B	315	80	130	200	345	22	14	85	110	10	M16	36
	FV07B	375	80	130	347.5	348	22	14	85	110	10	M16	36
	V07A	313	60	105	155	345	18	11	64	90	7.5	M16	36
	FV07A	363	60	105	309	348	18	11	64	90	7.5	M16	36
317M L4	V05B	239	48	82	155	245	14	9	51.5	70	6	M16	36
	FV05B	276	48	82	219.5	244	14	9	51.5	70	6	M16	36
317M R3 (B) (C)	V06B	307	60	105	155	292	18	11	64	90	7.5	M16	40
	FV06B	357	60	105	309	292	18	11	64	90	7.5	M16	36
317M R4	V05B	239	48	82	155	245	14	9	51.5	70	6	M16	36
	FV05B	276	48	82	219.5	244	14	9	51.5	70	6	M16	36

317M L 317M R







		C	D1	D2	D3	D4	D5	D6	L1	L2	L3	L4	L5	L6	S	S1	Input
317M L1	V9AF	181	120x3 DIN 5480	365	390 g7	415	M16 n°36	—	4	30	3	65	—	—	20°	20°	F
317M L2	V9AD	75	80x74 DIN 5482	270	335 H7	314	M16 n°8	—	5	30	8.5	40	—	—	60°	30°	D
317M L3	V9AB	51	58x53 DIN 5482	195	236 H7	222	M10 n°12	—	4	18	11	22	—	—	45°	22.5°	B
317M L4	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	—	4	18	9	18	—	—	45°	45°	A
317M R4	V9AA	37	40x36 DIN 5482	140	178 H7	165	M10 n°8	11	4	18	9	18	—	—	45°	45°	A
317M R3 (B) (C)	V9AB	45	58x53 DIN 5482	195	236 H7	222	M10 n°12	—	4	18	11	22	—	—	45°	22.5°	B

3/V 17M L





	D1 h6	L3	L4	L6	L7	L8	d
3/V 17M L3_HS	55	276	110	40	16	59	M16
3/V 17M L4_HS	40	214.5	70	20	12	43	M8

317M L 317M R 3/V 17M L

Permissible radial and axial loads on output shaft with $Fh_2 : n_2 \cdot h = 100000$



	An2 (+)	An2 (-)
HZ - HC PZ - PC	180000	150000



	Rn2	An2 (+/-)
FZ	69624	69624

Load corrective factor fh_2 on shafts	$Fh_2 = n_2 \cdot h$		10000	25000	50000	100000	500000	1000000
	fh_2	FZ	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
		HZ - HC - PZ - PC	**1.50**	**1.50**	**1.23**	**1.00**	**0.62**	**0.50**

Permissible radial loads on input shaft with $Fh_1 : n_1 \cdot h = 250000$





Load corrective factor fh_1 on shafts	$Fh_1 = n_1 \cdot h$	250000	500000	1000000	2000000	5000000	10000000
	fh_1	**1**	**0.79**	**0.63**	**0.50**	**0.37**	**0.29**

318M L



	L				Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP	PC - PZ	HC - HZ	FZ - FZP	FP
318M L1	332	202	202	202	1250	950	800	830
318M L2	677	547	547	547	1500	1200	1050	1080
318M L3	889	759	759	759	1600	1300	1150	1180
318M L4	1022	892	892	892	1650	1350	1200	1230

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
318M L1	—	—	—	—	—	—	—	—	—	—	—	—	208	G		—	—	—	—	—	—
318M L2	556	120	125	—	—	—	—	—	—	—	—	—	116	E		—	—	—	—	—	—
318M L3	348	80	55	—	—	—	456	80	85	—	—	—	81	D	477	232	185	1/4 G	6	B	28
318M L4	315	80	35	313	60	28	375	80	48	363	60	34	51	B		201	153	1/4 G	6	B	28

318M L



	PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1
318M L3	—	—	250	580	250	580
318M L4	197	530	227	530	227	550

NOTE: For R design contact Bonfiglioli Technical service

FP M_{2max} = 322000 Nm

	P180		P200		P225		P250	
	E	P	E	P	E	P	E	P
318M L3	—	—	267	400	297	450	297	550
318M L4	195	350	186	400	216	450	215	550

318M R



	R				R1	R2	R4	Kg			
	PC-PZ	HC-HZ	FZ - FZP	FP				PC-PZ	HC-HZ	FZ - FZP	FP
318M R4 (B)	1115	985	985	985	345	292	400	1720	1420	1270	1300
318M R4 (C)	1115	985	985	985	390	292	480	1730	1430	1280	1310

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
318M R4 (B)	307	60	23	—	—	—	357	60	28	—	—	—	45	B	477	195	147	1/4 G	6	B	28
318M R4 (C)	307	60	23	—	—	—	357	60	28	—	—	—	45	B		195	147	1/4 G	6	B	28

318M R









FP M_{2max} = 322000 Nm

	P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P
318M R4 (B)	—	—	—	—	152	350	182	400	212	450	193	550
318M R4 (C)	—	—	—	—	152	350	182	400	212	450	193	550

3/V 18M L4



FP M_{2max} = 322000 Nm

	L				L1	D1	L3	L4	Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP					PC - PZ	HC - HZ	FZ - FZP	FP
3/V 18M L4	1114	984	984	984	210	48	230	110	1810	1510	1360	1390

	P132		P160		P180		P200		P225	
	L2	P	L2	P	L2	P	L2	P	L2	P
3/V 18M L4	485	300	460	350	460	350	485	400	490	450



318M L 318M R 3/V 18M L4

HC



PC



HZ



FZ



FP



FZP



FP M_{2max} = 322000 Nm

Flange

W0A



Material: Steel C40

Sleeve coupling

M0A



Material: Steel C40

Shrink disc

G0A





318M L 318M R





		V	V1	V2	V4	V5	A	B	F	L	S	D	U
318M L2	**V15B**	556	120	210	230	542	32	18	127	180	15	M24	50
318M L3	**V11B**	348	80	130	200	428	22	14	85	110	10	M16	36
	FV11B	456	80	130	347.5	428	22	14	85	110	10	M16	36
318M L4	**V07B**	315	80	130	200	345	22	14	85	110	10	M16	36
	FV07B	375	80	130	347.5	348	22	14	85	110	10	M16	36
	V07A	313	60	105	155	345	18	11	64	90	7.5	M16	36
	FV07A	363	60	105	309	348	18	11	64	90	7.5	M16	36
318M R4 (B) (C)	**V06B**	307	60	105	155	292	18	11	64	90	7.5	M16	36
	FV06B	357	60	105	309	292	18	11	64	90	7.5	M16	36

318M L 318M R







		C	D1	D2	D3	D4	D5	D6	L1	L2	L3	L4	L5	L6	S	S1	Input
318M L1	Please consult Bonfiglioli Technical Service																
318M L2	**V9AE**	116	100x94 DIN 5482	340	412 H7	390	M16 n° 18	—	7	30	8	55	—	—	20°	20°	E
318M L3	**V9AD**	81	80x74 DIN 5482	270	335 H7	314	M16 n° 8	—	5	30	8.5	40	—	—	60°	30°	D
318M L4	**V9AB**	51	58x53 DIN 5482	195	236 H7	222	M16 n° 12	—	4	18	11	22	—	—	45°	22.5°	B
318M R4 (B) (C)	**V9AB**	45	58x53 DIN 5482	195	236 H7	222	M10 n° 10	—	4	18	11	22	—	—	45°	22.5°	B

3/V 18M L4





	D1 h6	L3	L4	L6	L7	L8	d
3/V 18M L4_HS	48	230	110	40	14	51.5	M16

318M L 318M R 3/V 18M L4

Permissible radial and axial loads on output shaft with $Fh_2 : n_2 \cdot h = 100000$





	An2 (+)	An2 (-)
HZ - HC PZ - PC	250000	225000



	Rn2	An2 (+/-)
FZ	92832	92832

	Fh2 = n2 · h	10000	25000	50000	100000	500000	1000000
Load corrective factor fh_2 on shafts	FZ	2.15	1.59	1.26	1.00	0.58	0.46
	HC - PC	1.96	1.52	1.23	1.00	0.62	0.50
	HZ - PZ	1.15	1.00	1.00	1.00	0.62	0.50

Permissible radial loads on input shaft with $Fh_1 : n_1 \cdot h = 250000$





Load corrective factor fh_1 on shafts	$Fh_1 = n_1 \cdot h$	250000	500000	1000000	2000000	5000000	10000000
	fh_1	1	0.79	0.63	0.50	0.37	0.29

319 L



	L				Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP	PC - PZ	HC - HZ	FZ - FZP	FP
319 L1	395	185	185	185	2100	1800	1700	1700
319 L2	778	568	568	568	2350	2050	1950	1950
319 L3	990	780	780	780	2435	2135	2035	2035
319 L4	1123	913	913	913	2480	2180	2080	2080

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
319 L1	—	—	—	—	—	—	—	—	—	—	—	—	245	G		—	—	—	—	—	—
319 L2	556	120	125	—	—	—	—	—	—	—	—	—	116	E		—	—	—	—	—	—
319 L3	348	80	55	—	—	—	456	80	85	—	—	—	81	D	477	232	185	1/4 G	6	B	28
319 L4	315	80	35	313	60	28	375	80	48	363	60	34	51	B		201	153	1/4 G	6	B	28

319 L



	PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1
319 L3	—	—	250	580	250	580
319 L4	197	530	227	530	227	550

NOTE: For R design contact Bonfiglioli Technical service

FP M_{2max} = 480000 Nm

	P180		P200		P225		P250	
	E	P	E	P	E	P	E	P
319 L3	—	—	267	400	297	450	297	550
319 L4	195	350	186	400	216	450	216	550

319 R



	R				R1	R2	R4	Kg			
	PC-PZ	HC-HZ	FZ - FZP	FP				PC-PZ	HC-HZ	FZ - FZP	FP
319 R4 (B)	1215	1005	1005	1005	345	292	400	2560	2260	2160	2160
319 R4 (C)	1215	1005	1005	1005	390	292	480	2580	2280	2180	2180

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
319 R4 (B)	307	60	23	—	—	—	357	60	28	—	—	—	45	B	477	195	147	1/4 G	6	B	28
319 R4 (C)	307	60	23	—	—	—	357	60	28	—	—	—	45	B		195	147	1/4 G	6	B	28

319 R













FP M_{2max} = 480000 Nm

	P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P
319 R4 (B)	—	—	—	—	152	350	182	400	212	450	193	550
319 R4 (C)	—	—	—	—	152	350	182	400	212	450	193	550

3/V 19 L4



FP M_{2max} = 480000 Nm

	L				L1	D1	L3	L4	Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP					PC - PZ	HC - HZ	FZ - FZP	FP
3/V 19 L4	1210	1000	1000	1000	210	48	230	110	2650	2350	2250	2250

	P132		P160		P180		P200		P225	
	L2	P	L2	P	L2	P	L2	P	L2	P
3/V 19 L4	485	300	460	350	460	350	485	400	490	450





319 L | 319 R | 3/V 19 L4

HC



PC



HZ





FZ



FP



FZP



FP | M_{2max} = 480000 Nm



319 L | 319 R | 3/V 19 L4

Flange

W0A







Material: Steel C40

Sleeve coupling

M0A





Material: Steel 16CrNi4

Shrink disc

G0A







319 L 319 R



V_ _



FV_ _

		V	V1	V2	V4	V5	A	B	F	L	S	D	U
319 L2	**V15B**	556	120	210	230	542	32	18	127	180	15	M24	50
319 L3	**V11B**	348	80	130	200	428	22	14	85	110	10	M16	36
	FV11B	456	80	130	347.5	428	22	14	85	110	10	M16	36
319 L4	**V07B**	315	80	130	200	345	22	14	85	110	10	M16	36
	FV07B	375	80	130	347.5	348	22	14	85	110	10	M16	36
	V07A	313	60	105	155	345	18	11	64	90	7.5	M16	36
	FV07A	363	60	105	309	348	18	11	64	90	7.5	M16	36
319 R4 (B) (C)	**V06B**	307	60	105	155	292	18	11	64	90	7.5	M16	36
	FV06B	357	60	105	309	292	18	11	64	90	7.5	M16	36

319 L 319 R







		C	D1	D2	D3	D4	D5	D6	L1	L2	L3	L4	L5	L6	S	S1	Input
319 L1	**V9AG**	245	150x5x28 DIN 5480	444	474 g7	503	M20 n°20	20	5	40	20	82	—	—	30°	15°	G
319 L2	**V9AE**	116	100x94 DIN 5482	340	412 H7	390	M16 n°18	—	7	30	8	55	—	—	20°	20°	E
319 L3	**V9AD**	81	80x74 DIN 5482	270	335 H7	314	M16 n°8	—	5	30	8.5	40	—	—	60°	30°	D
319 L4	**V9AB**	51	58x53 DIN 5482	195	236 H7	222	M10 n°12	—	4	18	11	22	—	—	45°	22.5°	B
319 R4	**V9AA**	37	40x36 DIN 5482	140	178 H7	165	M12 n°8	11	4	18	9	18	—	—	45°	45°	A
319 R4 (B) (C)	**V9AB**	45	58x53 DIN 5482	195	236 H7	222	M10 n°12	—	4	18	11	22	—	—	45°	22.5°	B

3/V 19 L4





	D1 h6	L3	L4	L6	L7	L8	d
3/V 19 L4_HS	48	230	110	40	14	51.5	M16

319 L | 319 R | 3/V 19 L4

Permissible radial and axial loads on output shaft with $Fh_2 : n_2 \cdot h = 100000$



	An2 (+)	An2 (-)
HZ - HC PZ - PC	250000	225000



	Rn2	An2 (+/-)
FZ	92832	92832

Load corrective factor fh_2 on shafts	$Fh_2 = n_2 \cdot h$		10000	25000	50000	100000	500000	1000000
	fh_2	FZ	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
		HZ - HC - PZ - PC	**1.75**	**1.52**	**1.23**	**1.00**	**0.62**	**0.50**

Permissible radial loads on input shaft with $Fh_1 : n_1 \cdot h = 250000$





Load corrective factor fh_1 on shafts	$Fh_1 = n_1 \cdot h$	250000	500000	1000000	2000000	5000000	10000000
	fh_1	**1**	**0.79**	**0.63**	**0.50**	**0.37**	**0.29**

321 L



	L				Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP	PC - PZ	HC - HZ	FZ - FZP	FP
321 L2	795	595	595	595	3000	2700	2600	2600
321 L3	1104	904	904	904	3120	2820	2720	2720
321 L4	1253	1053	1053	1053	3180	2880	2780	2780

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
321 L2	—	—	—	—	—	—	—	—	—	—	—	—	181	F		—	—	—	—	—	—
321 L3	343	80	55	—	—	—	451	80	71	—	—	—	75	D		—	—	—	—	—	—
321 L4	315	80	35	313	60	28	375	80	48	363	60	34	51	B	477	201	153	1/4 G	6	B	28

321 L



	PF 200		PF225		PF 250	
	E1	P1	E1	P1	E1	P1
321 L4	197	530	227	530	227	550

NOTE: For R design contact Bonfiglioli Technical service

FP M_{2max} = 720000 Nm

	P180		P200		P225		P250	
	E	P	E	P	E	P	E	P
321 L4	195	350	186	400	216	450	216	550

321 R



	R				R1	R2	R4	Kg			
	PC-PZ	HC-HZ	FZ - FZP	FP				PC-PZ	HC-HZ	FZ - FZP	FP
321 R4 (B)	1334	1134	1134	1134	345	292	400	3250	2950	2850	2850
321 R4 (C)	1334	1134	1134	1134	390	292	480	3260	2960	2860	2860

	V	V1	Kg	V	V1	Kg	V	V1	Kg	V	V1	Kg	C	Input	I	F	F1	F2	Type	Input	Kg
321 R4 (B)	307	60	23	—	—	—	357	60	28	—	—	—	45	B	477	195	147	1/4 G	6	B	28
321 R4 (C)	307	60	23	—	—	—	357	60	28	—	—	—	45	B		195	147	1/4 G	6	B	28

321 R









FP M_{2max} = 720000 Nm

	P132		P160		P180		P200		P225		P250	
	E	P	E	P	E	P	E	P	E	P	E	P
321 R4 (B)	—	—	—	—	152	350	182	400	212	450	193	550
321 R4 (C)	—	—	—	—	152	350	182	400	212	450	193	550

3/V 21 L4



PC



HZ PZ





HC





FP





FZ





FZP



FP | M_{2max} = 720000 Nm

	L				L1	L2	D1	L3	L4	Kg			
	PC - PZ	HC - HZ	FZ - FZP	FP						PC - PZ	HC - HZ	FZ - FZP	FP
3/V 21 L4	1374	1174	1174	1174	250	—	55	276	110	3430	3130	3030	3030

	P132		P160		P180		P200		P225	
	L2	P	L2	P	L2	P	L2	P	L2	P
3/V 21 L4	531	300	506	350	506	350	531	400	536	450



321 L | 321 R | 3/V 21 L4

HC



PC



HZ



FZ



FP



FZP



FP | M_{2max} = 720000 Nm

Flange

W0A







Material: Steel C40

Shrink disc

G0A







321 L 321 R



V_ _



FV_ _



		V	V1	V2	V4	V5	A	B	F	L	S	D	U
321 L3	V11B	343	80	130	200	445	22	14	85	110	10	M16	36
	FV11B	451	80	130	347.5	445	22	14	85	110	10	M16	36
321 L4	V07B	315	80	130	200	345	22	14	85	110	10	M16	36
	FV07B	375	80	130	347.5	348	22	14	85	110	10	M16	36
	V07A	313	60	105	155	345	18	11	64	90	7.5	M16	36
	FV07A	363	60	105	309	348	18	11	64	90	7.5	M16	36
321 R4 (B) (C)	V06B	307	60	105	155	292	18	11	64	90	7.5	M16	36
	FV06B	357	60	105	309	292	18	11	64	90	7.5	M16	36

321 L 321 R







		C	D1	D2	D3	D4	D5	D6	L1	L2	L3	L4	L5	L6	S	S1	Input
321 L1	Please consult Bonfiglioli Technical Service																
321 L2	V9AF	181	120x3 DIN 5480	365	390 f7	415	M16 n°18	—	4	30	3	65	—	—	20°	20°	F
321 L3	V9AD	75	80x74 DIN 5482	270	335 H7	314	M16 n°8	—	5	30	8.5	40	—	—	60°	30°	D
321 L4	V9AB	51	58x53 DIN 5482	195	236 H7	222	M10 n°12	—	4	18	11	22	—	—	45°	22.5°	B
321 R4 (B) (C)	V9AB	45	58x53 DIN 5482	195	236 H7	222	M10 n°12	—	4	18	11	22	—	—	45°	22.5°	B

3/V 21 L4





	D1 h6	L3	L4	L6	L7	L8	d
3/V 21 L4_HS	55	276	110	40	16	59	M16

321 L | 321 R | 3/V 21 L4

Permissible radial and axial loads on output shaft with $Fh_2 : n_2 \cdot h = 100000$





	An_2 (+)	An_2 (-)
HZ - HC PZ - PC	90000	120000



	Rn_2	An_2 (+/-)
FZ	556991	83549

Load corrective factor fh_2 on shafts	$Fh_2 = n_2 \cdot h$	10000	25000	50000	100000	500000	1000000
	fh_2 FZ	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**
	fh_2 HZ - HC - PZ - PC	**1.54**	**1.35**	**1.23**	**1.00**	**0.62**	**0.50**

Permissible radial loads on input shaft with $Fh_1 : n_1 \cdot h = 250000$





Load corrective factor fh_1 on shafts	$Fh_1 = n_1 \cdot h$	250000	500000	1000000	2000000	5000000	10000000
	fh_1	**1**	**0.79**	**0.63**	**0.50**	**0.37**	**0.29**

323 L



FP M_{2max} = 1580000 Nm

	PF225		PF 250	
	E1	P1	E1	P1
323 L4	250	580	250	580

NOTE: For R design contact Bonfiglioli Technical service

	L		Kg							
	FZ - FZP	FP	FZ - FZP	FP	V	V1	Kg	V	V1	Kg
323 L1	Please consult Bonfiglioli Technical Service									
323 L2	666	666	4450	4550	—	—	—	—	—	—
323 L3	1049	1049	4750	4850	556	120	125	—	—	—
323 L4	1261	1261	4900	5000	315	80	35	456	80	85

										P200		P225		P250	
	C	Input	I	F	F1	F2	Type	Input	Kg	E	P	E	P	E	P
323 L1	—	—		—	—	—	—	—	—	—	—	—	—	—	—
323 L2	245	G		—	—	—	—	—	—	—	—	—	—	—	—
323 L3	116	E		—	—	—	—	—	—	—	—	—	—	—	—
323 L4	81	D	477	201	48	1/4 G	6	B	22	267	400	297	450	297	550

323 L

FZ



FZP



FP



Shrink disc

G0A





FP M_{2max} = 1580000 Nm

323 L



V_ _



FV_ _



		V	V1	V2	V4	V5	A	B	F	L	S	D	U
323 L3	**V15B**	556	120	210	230	542	32	18	127	180	15	M24	50
323 L4	**V11B**	343	80	130	200	445	22	14	85	110	10	M16	36
	FV11B	451	80	130	347.5	445	22	14	85	110	10	M16	36

323 L







		C	D1	D2	D3	D4	D5	D6	L1	L2	L3	L4	L5	L6	S	S1	Input
323 L1	Please consult Bonfiglioli Technical Service																
323 L2	**V9AG**	245	150x5x28 DIN 5480	444	474 g7	503	M20 n°20	20	5	40	20	82	—	—	30°	15°	G
323 L3	**V9AE**	116	100x94 DIN 5482	340	412 H7	390	M16 n°18	—	7	30	8	55	—	—	20°	20°	E
323 L4	**V9AD**	81	80x74 DIN 5482	270	335 H7	314	M16 n°8	—	5	30	8.5	40	—	—	60°	30°	D

323 L

Permissible radial and axial loads on output shaft with $Fh_2 : n_2 \cdot h = 100000$



	Rn_2	An_2 (+)	An_2 (-)
FZ	510575	174060	69624

Load corrective factor fh_2 on shafts	$Fh_2 = n_2 \cdot h$		10000	25000	50000	100000	500000	1000000
	fh_2	**FZ**	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**

Permissible radial loads on input shaft with $Fh_1 : n_1 \cdot h = 250000$





Load corrective factor fh_1 on shafts	$Fh_1 = n_1 \cdot h$	250000	500000	1000000	2000000	5000000	10000000
	fh_1	**1**	**0.79**	**0.63**	**0.50**	**0.37**	**0.29**

325 L



FP M_{2max} = 2000000 Nm

	PF225		PF 250	
	E1	P1	E1	P1
325 L4	250	580	250	580

NOTE: For R design contact Bonfiglioli Technical service

	L		Kg							
	FZ - FZP	FP	FZ - FZP	FP	V	V1	Kg	V	V1	Kg
325 L1	Please consult Bonfiglioli Technical Service									
325 L2	698	698	5700	5900	—	—	—	—	—	—
325 L3	1081	1081	6000	6200	556	120	125	—	—	—
325 L4	1293	1293	6150	6350	315	80	35	456	80	85

										P200		P225		P250	
	C	Input	I	F	F1	F2	Type	Input	Kg	E	P	E	P	E	P
325 L1	—	—		—	—	—	—	—	—	—	—	—	—	—	—
325 L2	245	G		—	—	—	—	—	—	—	—	—	—	—	—
325 L3	116	E	477	—	—	—	—	—	—	—	—	—	—	—	—
325 L4	81	D		201	48	1/4 G	6	B	22	267	400	297	450	297	550

325 L

FZ



FP



FZP



Shrink disc



G0A



FP M_{2max} = 2000000 Nm

325 L



		V	V1	V2	V4	V5	A	B	F	L	S	D	U
325 L3	**V15B**	556	120	210	230	542	32	18	127	180	15	M24	50
325 L4	**V11B**	343	80	130	200	445	22	14	85	110	10	M16	36
	FV11B	451	80	130	347.5	445	22	14	85	110	10	M16	36

325 L



		C	D1	D2	D3	D4	D5	D6	L1	L2	L3	L4	L5	L6	S	S1	Input
325 L1	Please consult Bonfiglioli Technical Service																
325 L2	**V9AG**	245	150x5x28 DIN 5480	444	474 g7	503	M20 n°20	20	5	40	20	82	—	—	30°	15°	G
325 L3	**V9AE**	116	100x94 DIN 5482	340	412 H7	390	M16 n°18	—	7	30	8	55	—	—	20°	20°	E
325 L4	**V9AD**	81	80x74 DIN 5482	270	335 H7	314	M16 n°8	—	5	30	8.5	40	—	—	60°	30°	D

325 L

Permissible radial and axial loads on output shaft with $Fh_2 : n_2 \cdot h = 100000$



	Rn_2	An_2 (+)	An_2 (-)
FZ	510575	174060	69624

Load corrective factor fh_2 on shafts	$Fh_2 = n_2 \cdot h$		10000	25000	50000	100000	500000	1000000
	fh_2	**FZ**	**2.15**	**1.59**	**1.26**	**1.00**	**0.58**	**0.46**

Permissible radial loads on input shaft with $Fh_1 : n_1 \cdot h = 250000$





Load corrective factor fh_1 on shafts	$Fh_1 = n_1 \cdot h$	250000	500000	1000000	2000000	5000000	10000000
	fh_1	**1**	**0.79**	**0.63**	**0.50**	**0.37**	**0.29**

CUSTOMER'S SHAFT

FP



	A Ø H7 - g6 [mm]	B Ø H7 - g6 [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]	Shaft material
300	42	35	1.6	2	2	18	38	Suggested material: Steel with tensile strength $\sigma_R \geq 700MPa$
301	52	35	1.6	2	2	18	38	
303 - 304 - 305	75	65	1.6	2	2	30	65	
306	90	75	1.6	3	3	55	85	
307	100	85	1.6	3	3	40	95	
309	120	—	1.6	—	3	—	140	
310M	130	—	1.6	—	3	—	155	
311M	135	—	1.6	—	3	—	150	
313M	140	130	2	3	3	45	150	
314M	180	160	1.6	3	3	50	200	
315M	180	160	1.6	3	3	50	200	
316M	180	165	1.6	3	3	90	180	
317M	200	—	1.6	—	3	—	250	
318M	220	200	2	3	3	130	180	
319	280	—	2	—	3	—	300	
321	320	—	2	—	3	—	300	
323	410	—	2	—	3	—	250	
325	450	—	2	—	3	—	300	

FDK



	A	B	A1	A2	C	Shaft material	Keyways dimensions		b	t_1	E	F	R
	Ø shaft	Length					Keyways UNI 6604 / DIN 6885				Chamfer dimensions		Fillets
	[mm]	[mm]	[mm]	[mm]	[mm]	Suggested material: Steel with tensile strength $\sigma_R \geq 900$MPa	—	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]
300	35 g6	64	35	39	4		N°2 x 120°	10x8x50	10 H8	Dimension according to UNI6604 / DIN 6885 standard.	1 x 45°	0.5 x 45°	(*)
301	35 g6	64	35	43	5		N°2 x 120°	10x8x50	10 H8		1 x 45°	0.5 x 45°	0.5
303 - 304 - 305	65 g6	95	65	75	6		N°2 x 120°	18x11x80	18 H8		1 x 45°	0.5 x 45°	0.8
306	80 g6	116	80	92	7		N°2 x 120°	22x14x100	22 H8		1 x 45°	0.5 x 45°	0.8
307	90 g6	141	90	102	8		N°2 x 120°	25x14x125	25 H8		2 x 45°	1 x 45°	0.8
309	120 g6	128	120	136	10		N°2 x 120°	32x18x110	32 H8		2 x 45°	1 x 45°	1.6
310M	130 g6	138	130	146	10		N°2 x 120°	32x18x120	32 H8		2 x 45°	1 x 45°	1.6

(*) Relief groove (UNI 4386 - 75 E0.6x0.3)

FZP



	A	B	C	Shaft material	D	E	F	G	H	K	J	L	M	N	O	P	Q	R	DC*
	Splined shaft DIN 5480	Ø H7 - g6	Relief groove diameter																
	[mm]	[mm]	[mm]		[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]
311M	120x3x38	108	112	Suggested material: Steel with tensile strength $\sigma_R \geq 900MPa$	124	112	124	19	69	9	70	18,5	6	1	1.6	—	—	1.6	60
313M	140x5x26	110	132		142	132	142	26	83	18	84	30	6	1	2	—	—	3	60
314M	150x5x28	136	136		152	136	152	16	103	8	104	20	8	1	2	—	—	1.6	60
315M	150x5x28	136	136		152	136	152	16	103	8	104	20	8	1	2	—	—	1.6	60
316M	170x5x32	150	154		172	154	172	30	113	20	114	45	9	1	3	—	—	3	60
317M	200x5x38	187	186		202	192	202	16	100	19	101	33	9	1	3.5	130	10	1.6	60
318M	210x5x40	190	194		212	194	212	27	133	20	134	45	9	2	3	—	—	3	60
319	260x5x50	248	243		265	243	265	29	144	20	145	40	11	2	3	—	—	3	60
321	300x8x36	282	281		305	281	305	25	158	25	159	50	12	2	3	—	—	3	70
323	400x8x48	360	381		405	381	405	35	254	26	256	53,5	12	2	4	—	—	5	70
325	450x8x55	410	431		455	431	455	34	272	24	274	66	12	2	4	—	—	5	70

* Max cutter diameter

TORQUE ARM

	L1 [mm]	L2 [mm]
300	300	450
301	580	
303	350	500
304		
305	370	
306	410	600
307	490	700
309	600	900
310M	1030	1000
311M	800	1100
313M	900	1200
314M	1100	1400
315M		
316M	1280	1500
317M	1300	1600
318M	1900	1800
319	1500	2000
321	1500	
323	1750	3000
325	2050	3200



NOTE: Drawings for illustration purpose only

Suggested material: S275JR - UNI EN 10025 or S355JR - UNI EN 10025.

TORQUE ARM KIT FOR FP VERSIONS

If requested, it's possible to install a specific "Torque arm" Kit on 300M series gearboxes. For detailed information please contact our Technical Service .

	L1 [mm]	i [mm]
300	300	55
301	580	
303	350	80
304		
305	370	
306	410	115
307	490	
309	600	
310M	1030	135
311M	800	155
313M	900	160
314M	1100	200
315M		
316M	1280	210
317M	1300	240
318M	1900	280
319	1500	320
321	1500	360
323	1750	400
325	2050	440



NOTE: Draw for illustration purpose only

Suggested material: S275JR - UNI EN 10025 or S355JR - UNI EN 10025.



NEGATIVE MULTIDISC BRAKE AND HYDRAULIC MOTORS

H1 SYMBOLS AND UNITS OF MEASURE

Symbols	Units of Measure	Description
V	[cm^3]	Rot. displacement
p	[bar]	Pressure
pA. pB	[bar]	Pressure in A and B connections
Q	[l/min]	Flow rate
ηt		Efficiency
ηmh		Hydraulic-mechanical efficiency

Symbols	Units of Measure	Description
ηv		Volumetric efficiency
n	[min^{-1}]	Angular speed
M	[Nm]	Actual torque onto the motor shaft
cont		General value, for continuous duty
int		General value, intermittent duty

H2 NEGATIVE MULTIDISC BRAKE

DESCRIPTION

TRASMITAL's fail-safe parking brake is an oil immersed multidisc unit on the input side of the gearbox. The brake is operated when there is no hydraulic pressure and is released when the minimum release pressure is applied.
Use of parking brake is necessary whenever the driven system must be kept at standstill even under external forces and/or torques.

Applications:

- winches
- slewing drives
- parking brake on mobile equipment
- general industrial applications



H2.1 Brake technical data

(A 31)

		Type																	
		4.							5.					6.					
		A	B	D	F	H	K	L	B	C	E	G	K	B	C	E	G	K	L
Static braking torque Mb	Nm ±10%	50	100	160	260	330	400	440	400	500	630	800	1000	900	1200	1600	2200	2750	3300
Min. opening pressure	bar	10	20	30	20	25	30	34	20	27	20	26	32	16	21	28	21	27	32
Max. operating pressure	bar	320																	
Oil volume for brake release	cm^3	6.65	6.65	6.65	6.65	6.65	6.65	6.65	13.96	13.96	13.96	13.96	13.96	37.2	37.2	37.2	37.2	37.2	37.2

H3 INPUTS FOR HYDRAULIC MOTORS

The available motor adaptors and motor sizes are shown in the following pages.
The standard orientations (A) of the motor flanges are shown in the following scheme, taking into consideration the input side of the gearbox.



Identification codes of other arrangements:

B: + 90° (clockwise)
C: + 180° (clockwise)
D: + 270° (clockwise)





		SAE Standard J744c											
		SAE A 16/32 z9	SAE A ø15,875	SAE B 16/32 z13	SAE B ø22,2	SAE BB 16/32 z15	SAE BB ø25,4	SAE C 12/24 z14	SAE C ø31,7	SAE CC 12/24 z17	SAE C ø38,1	SAE D 8/16 z13	SAE E 8/16 z13
		S5AM	S5AN	S5BA	S5BB	S5BM	S5BN	S5CA	S5CB	S5CP	S5CQ	S5DA	S5EA
	CODE	I											
300	L1-L2-L3-L4	42	42	52	52	52	52	64	64	80	80	81	
	R2-R3-R4	42	42	52	52	52	52	64	64	80	80	81	
301	L1-L2-L3-L4	42	42	52	52	52	52	64	64	80	80	81	
	R2-R3-R4	42	42	52	52	52	52	64	64	80	80	81	
303	L1	42	42	52	52	52	52	64	64	80	80	81	
	L2-L3-L4	42	42	52	52	52	52	64	64	80	80	81	
	R2-R3-R4	42	42	52	52	52	52	64	64	80	80	81	
304	L1	42	42	52	52	52	52	64	64	80	80	81	
	L2-L3-L4	42	42	52	52	52	52	64	64	80	80	81	
	R2-R3-R4	42	42	52	52	52	52	64	64	80	80	81	
305	L1	42	42	52	52	52	52	64	64	80	80	81	
	L2-L3-L4	42	42	52	52	52	52	64	64	80	80	81	
	R2-R3-R4	42	42	52	52	52	52	64	64	80	80	81	
306	L1											101	113
	L2	42	42	52	52	52	52	64	64	80	80	81	
	L3-L4	42	42	52	52	52	52	64	64	80	80	81	
	R2-R3-R4	42	42	52	52	52	52	64	64	80	80	81	
307	L1											101	113
	L2	42	42	52	52	52	52	64	64	80	80	81	
	L3-L4	42	42	52	52	52	52	64	64	80	80	81	
	R2	42	42	52	52	52	52	64	64	80	80	81	
	R3-R4	42	42	52	52	52	52	64	64	80	80	81	
309	L1											101	113
	L2	42	42	52	52	52	52	64	64	80	80	81	
	L3-L4	42	42	52	52	52	52	64	64	80	80	81	
	R2	42	42	52	52	52	52	64	64	80	80	81	
	R3-R4	42	42	52	52	52	52	64	64	80	80	81	
310M	L1											146	158
	L2											101	113
	L3	42	42	52	52	52	52	64	64	80	80	81	
	L4	42	42	52	52	52	52	64	64	80	80	81	
	R2(B)-R2(C)											101	113
	R3-R4	42	42	52	52	52	52	64	64	80	80	81	
311M	L1												
	L2											101	113
	L3	42	42	52	52	52	52	64	64	80	80	81	
	L4	42	42	52	52	52	52	64	64	80	80	81	
	R2(B)-R2(C)											101	113
	R3-R4	42	42	52	52	52	52	64	64	80	80	81	
313M	L1												
	L2											101	113
	L3	42	42	52	52	52	52	64	64	80	80	81	
	L4	42	42	52	52	52	52	64	64	80	80	81	
	R2(B)-R2(C)											101	113
	R3-R4	42	42	52	52	52	52	64	64	80	80	81	
314M	L1												
	L2											146	113
	L3	42	42	52	52	52	52	64	64	80	80	81	
	L4	42	42	52	52	52	52	64	64	80	80	81	
	R3(B)-R3(C)											101	113
	R4	42	42	52	52	52	52	64	64	80	80	81	
315M	L1												
	L2												
	L3											101	113
	L4	42	42	52	52	52	52	64	64	80	80	81	
	R3(B)-R3(C)											101	113
	R4	42	42	52	52	52	52	64	64	80	80	81	
316M	L1												
	L2												
	L3											101	113
	L4	42	42	52	52	52	52	64	64	80	80	81	
	R3(B)-R3(C)											101	113
	R4	42	42	52	52	52	52	64	64	80	80	81	
317M	L1												
	L2												
	L3											101	113
	L4	42	42	52	52	52	52	64	64	80	80	81	
	R3(B)-R3(C)											101	113
	R4	42	42	52	52	52	52	64	64	80	80	81	
318M	L1												
	L2												
	L3												
	L4											101	113
	R4(B)-R4(C)											101	113
319	L1												
	L2												
	L3												
	L4											101	113
	R4(B)-R4(C)											101	113
321	L1												
	L2												
	L3												
	L4											101	113
	R4(B)-R4(C)											101	113
323	L1												
	L2												
	L3												
	L4												

* For gear units supplied with a 6" brake





		CALZONI								CHAR-LYNN (EATON)								
		CALZONI MR190 N z8	CALZONI MR300 N z8	CALZONI MRP300 N z8	CALZONI MR450 N z8	CALZONI MR700 N z8	CALZONI MR1100 N z8	CALZONI MR1800 N z10	CALZONI MR2800 N z10	SERIE 2000 SAE A 1" 6B	SERIE 2000 SAE A ø25,4	SERIE 2000 SAE A ø32	SERIE 2000 SAE A 12/24 z14	SERIE 2000 BEARINGLESS 1 2/24 z12	SERIE 4000 SAE B ø31,75	SERIE 4000 SAE C 12/24 z17	SERIE 6000 SAE C ø38,1	SERIE 6000 SAE C 12/24 z17
	CODE	C0AA	C0AD	C0BL	C0AG	C0AL	C0AP	C0AS	C0AV	S5AQ	S5AS	D0AG	D0AH	E2AA	S5BP	S5CP	S5CQ	S5CP
300	L1-L2-L3-L4	64	78	78						42	42	64	64	52	68	80	80	80
	R2-R3-R4	64	78	78						42	42	64	64	52	68	80	80	80
301	L1-L2-L3-L4	64	78	78						42	42	64	64	52	68	80	80	80
	R2-R3-R4	64	78	78						42	42	64	64	52	68	80	80	80
303	L1	64	78	78						42	42	64	64	52	68	80	80	80
	L2-L3-L4	64	78	78						42	42	64	64	52	68	80	80	80
	R2-R3-R4	64	78	78						42	42	64	64	52	68	80	80	80
304	L1	64	78	78						42	42	64	64	52	68	80	80	80
	L2-L3-L4	64	78	78						42	42	64	64	52	68	80	80	80
	R2-R3-R4	64	78	78						42	42	64	64	52	68	80	80	80
305	L1	64	78	78						42	42	64	64	52	68	80	80	80
	L2-L3-L4	64	78	78						42	42	64	64	52	68	80	80	80
	R2-R3-R4	64	78	78						42	42	64	64	52	68	80	80	80
306	L1				98	102	133											
	L2	64	78	78						42	42	64	64	52	68	80	80	80
	L3-L4	64	78	78						42	42	64	64	52	68	80	80	80
	R2-R3-R4	64	78	78						42	42	64	64	52	68	80	80	80
307	L1				98	102	133											
	L2	64	78	78						42	42	64	64	52	68	80	80	80
	L3-L4	64	78	78						42	42	64	64	52	68	80	80	80
	R2	64	78	78						42	42	64	64	52	68	80	80	80
	R3-R4	64	78	78						42	42	64	64	52	68	80	80	80
309	L1				98	102	133											
	L2	64	78	78						42	42	64	64	52	68	80	80	80
	L3-L4	64	78	78						42	42	64	64	52	68	80	80	80
	R2	64	78	78						42	42	64	64	52	68	80	80	80
	R3-R4	64	78	78						42	42	64	64	52	68	80	80	80
310M	L1				143	147	178											
	L2				98	102	133											
	L3	64	78	78						42	42	64	64	52	68	80	80	80
	L4	64	78	78						42	42	64	64	52	68	80	80	80
	R2(B)-R2(C)				98	102	133											
	R3-R4	64	78	78						42	42	64	64	52	68	80	80	80
311M	L1					130	130	165	200									
	L2				98	102	133											
	L3	64	78	78						42	42	64	64	52	68	80	80	80
	L4	64	78	78						42	42	64	64	52	68	80	80	80
	R2(B)-R2(C)				98	102	133											
	R3-R4	64	78	78						42	42	64	64	52	68	80	80	80
313M	L1					130	130	165	200									
	L2				98	102	133											
	L3	64	78	78						42	42	64	64	52	68	80	80	80
	L4	64	78	78						42	42	64	64	52	68	80	80	80
	R2(B)-R2(C)				98	102	133											
	R3-R4	64	78	78						42	42	64	64	52	68	80	80	80
314M	L1																	
	L2				98	102	133											
	L3	64	78	78						42	42	64	64	52	68	80	80	80
	L4	64	78	78						42	42	64	64	52	68	80	80	80
	R3(B)-R3(C)				98	102	133											
	R4	64	78	78						42	42	64	64	52	68	80	80	80
315M	L1																	
	L2					130	130	165	200									
	L3				98	102	133											
	L4	64	78	78						42	42	64	64	52	68	80	80	80
	R3(B)-R3(C)				98	102	133											
	R4	64	78	78						42	42	64	64	52	68	80	80	80
316M	L1																	
	L2					130	130	165	200									
	L3				98	102	133											
	L4	64	78	78						42	42	64	64	52	68	80	80	80
	R3(B)-R3(C)				98	102	133											
	R4	64	78	78						42	42	64	64	52	68	80	80	80
317M	L1																	
	L2					130	130	165	200									
	L3				98	102	133											
	L4	64	78	78						42	42	64	64	52	68	80	80	80
	R3(B)-R3(C)				98	102	133											
	R4	64	78	78						42	42	64	64	52	68	80	80	80
318M	L1																	
	L2																	
	L3					130	130	165	200									
	L4				98	102	133											
	R4(B)-R4(C)				98	102	133											
319	L1																	
	L2																	
	L3					130	130	165	200									
	L4				98	102	133											
	R4(B)-R4(C)				98	102	133											
321	L1																	
	L2																	
	L3					130	130	165	200									
	L4				98	102	133											
	R4(B)-R4(C)				98	102	133											
323	L1																	
	L2																	
	L3																	
	L4					130/102(*)	130/133(*)	165	200									

* For gear units supplied with a 6" brake





		SAUER DANFOSS (orbit)									DENISON Hydraulics							
		OMP-OMR 50/315 ø25	OMP-OMR 50/315 SAE 1" 6B	OMS 80/315 ø32	OMS 80/315 12/24 z14	OMSS 80/315 12/24 z12	OMT 160/400 ø40	OMT 160/400 12/24 z17	OMTS 160/400 12/24 z16	OMVS 315/800 10/20 z16	M6-M7-M8 "3** 12/24 z14	M11-M14 "3** 8/16 z13	M3 B 16/32 z9	M4C-M4SC 16/32 z13	M4D-M4SD 12/24 z14	M4DC-M4S DC 12/24 z14	M4E-M4SE 12/24 z14	M5BS 16/32 z13
		S5AP	S5AQ	D0AG	D0AH	D0AL	D0AM	D0AN	D0AQ	D0AU	S5CA	S5EA	S5AM	S5BA	S5CA	S5CA	S5CA	S5BA
	CODE									I								
300	L1-L2-L3-L4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	R2-R3-R4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
301	L1-L2-L3-L4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	R2-R3-R4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
303	L1	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	L2-L3-L4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	R2-R3-R4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
304	L1	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	L2-L3-L4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	R2-R3-R4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
305	L1	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	L2-L3-L4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	R2-R3-R4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
306	L1									70		113						
	L2	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	L3-L4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	R2-R3-R4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
307	L1									70		113						
	L2	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	L3-L4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	R2	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	R3-R4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
309	L1									70		113						
	L2	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	L3-L4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	R2	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	R3-R4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
310M	L1									115		158						
	L2									70		113						
	L3	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	L4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	R2(B)-R2(C)									70		113						
	R3-R4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
311M	L1																	
	L2									70		113						
	L3	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	L4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	R2(B)-R2(C)									70		113						
	R3-R4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
313M	L1																	
	L2									70		113						
	L3	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	L4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	R2(B)-R2(C)									70		113						
	R3-R4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
314M	L1																	
	L2									70		113						
	L3	42	42	64	64	37		112	57		64		42	52	64	64	64	52
	L4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	R3(B)-R3(C)									70		113						
	R4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
315M	L1																	
	L2																	
	L3									70		113						
	L4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	R3(B)-R3(C)									70		113						
	R4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
316M	L1																	
	L2																	
	L3									70		113						
	L4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	R3(B)-R3(C)									70		113						
	R4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
317M	L1																	
	L2																	
	L3									70		113						
	L4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
	R3(B)-R3(C)									70		113						
	R4	42	42	64	64	37	112	112	57		64		42	52	64	64	64	52
318M	L1																	
	L2																	
	L3																	
	L4									70		113						
	R4(B)-R4(C)									70		113						
319	L1																	
	L2																	
	L3																	
	L4									70		113						
	R4(B)-R4(C)									70		113						
321	L1																	
	L2																	
	L3																	
	L4									70		113						
	R4(B)-R4(C)									70		113						
323	L1																	
	L2																	
	L3																	
	L4																	

* For gear units supplied with a 6" brake



		LINDE							
		MMF 43 16/32 z15	MMF 63 12/24 z14	HMF 28-35-02 16/32 z15	HMF 50-02 16/32 z21	HMF-HMV 75-02 16/32 z21	HMF-HMV 105-02 16/32 z23	HMF-HMV 135-02 16/32 z27	BMF-BMV 186 50x2 Z24
		S5BM	S5CA	S5BM	S5CE	S5CE	S5CD	S5DC	I5AF
	CODE	I							
300	L1-L2-L3-L4	52	64	52	64	64	64	81	
	R2-R3-R4	52	64	52	64	64	64	81	
301	L1-L2-L3-L4	52	64	52	64	64	64	81	
	R2-R3-R4	52	64	52	64	64	64	81	
303	L1	52	64	52	64	64	64	81	
	L2-L3-L4	52	64	52	64	64	64	81	
	R2-R3-R4	52	64	52	64	64	64	81	
304	L1	52	64	52	64	64	64	81	
	L2-L3-L4	52	64	52	64	64	64	81	
	R2-R3-R4	52	64	52	64	64	64	81	
305	L1	52	64	52	64	64	64	81	
	L2-L3-L4	52	64	52	64	64	64	81	
	R2-R3-R4	52	64	52	64	64	64	81	
306	L1							101	121
	L2	52	64	52	64	64	64	81	
	L3-L4	52	64	52	64	64	64	81	
	R2-R3-R4	52	64	52	64	64	64	81	
307	L1							101	121
	L2	52	64	52	64	64	64	81	
	L3-L4	52	64	52	64	64	64	81	
	R2	52	64	52	64	64	64	81	
	R3-R4	52	64	52	64	64	64	81	
309	L1							101	121
	L2	52	64	52	64	64	64	81	
	L3-L4	52	64	52	64	64	64	81	
	R2	52	64	52	64	64	64	81	
	R3-R4	52	64	52	64	64	64	81	
310M	L1							146	166
	L2							101	121
	L3	52	64	52	64	64	64	81	
	L4	52	64	52	64	64	64	81	
	R2(B)-R2(C)							101	121
	R3-R4	52	64	52	64	64	64	81	
311M	L1								
	L2							101	121
	L3	52	64	52	64	64	64	81	
	L4	52	64	52	64	64	64	81	
	R2(B)-R2(C)							101	121
	R3-R4	52	64	52	64	64	64	81	
313M	L1								
	L2							101	121
	L3	52	64	52	64	64	64	81	
	L4	52	64	52	64	64	64	81	
	R2(B)-R2(C)							101	121
	R3-R4	52	64	52	64	64	64	81	
314M	L1								
	L2							101	121
	L3	52	64	52	64	64	64	81	
	L4	52	64	52	64	64	64	81	
	R3(B)-R3(C)							101	121
	R4	52	64	52	64	64	64	81	
315M	L1								
	L2								
	L3							101	121
	L4	52	64	52	64	64	64	81	
	R3(B)-R3(C)							101	121
	R4	52	64	52	64	64	64	81	
316M	L1								
	L2								
	L3							101	121
	L4	52	64	52	64	64	64	81	
	R3(B)-R3(C)							101	121
	R4	52	64	52	64	64	64	81	
317M	L1								
	L2								
	L3							101	121
	L4	52	64	52	64	64	64	81	
	R3(B)-R3(C)							101	121
	R4	52	64	52	64	64	64	81	
318M	L1								
	L2								
	L3								
	L4							101	121
	R4(B)-R4(C)							101	121
319	L1								
	L2								
	L3								
	L4							101	121
	R4(B)-R4(C)							101	121
321	L1								
	L2								
	L3								
	L4							101	121
	R4(B)-R4(C)							101	121
323	L1								
	L2								
	L3								
	L4								

* For gear units supplied with a 6" brake





		BRUENINGHAUS HYDROMATIK (BOSCH REXROTH)															
		A2FM10-12-16 25x1,25 z18	A2FM23-28-32 A6VM 28 30x2 z14	A2FM23-28 ø25	A2FM45 32x2 z14	A2FM45-56 30x2 z14	A2FM56-63 A6VM55 35x2 z16	A2FM80-90 A6VM80 40x2 z18	A2FM80 35x2 z16	A2FM107-125 A6VM107 45x2 z21	A2FM107 A6VM107 40x2 z18	A2FM160-180 A6VM160 50x2 z24	A2FM160 A6VM160 45x2 z21	A2FM200 A6VM200 50x2 z24	A6VM250 50x2 z24	A2FM250 50x2 z24	A10FM45.30W A10VM63 16/32 z15
	CODE	H0AA	H0AE	H0AH	H0AI	H0BA	H0BC	H0BG	H0BI	H0CA	H0CC	H0CE	H0CG	H0CI	H0DA	H0DE	S5BM
		I															
300	L1-L2-L3-L4	42	52	52	64	64	64	75	75	101	101		101				52
	R2-R3-R4	42	52	52	64	64	64	75	75	101	101		101				52
301	L1-L2-L3-L4	42	52	52	64	64	64	75	75	101	101		101				52
	R2-R3-R4	42	52	52	64	64	64	75	75	101	101		101				52
303	L1	42	52	52	64	64	64	75	75	101	101		101				52
	L2-L3-L4	42	52	52	64	64	64	75	75	101	101		101				52
	R2-R3-R4	42	52	52	64	64	64	75	75	101	101		101				52
304	L1	42	52	52	64	64	64	75	75	101	101		101				52
	L2-L3-L4	42	52	52	64	64	64	75	75	101	101		101				52
	R2-R3-R4	42	52	52	64	64	64	75	75	101	101		101				52
305	L1	42	52	52	64	64	64	75	75	101	101		101				52
	L2-L3-L4	42	52	52	64	64	64	75	75	101	101		101				52
	R2-R3-R4	42	52	52	64	64	64	75	75	101	101		101				52
306	L1											101	101	101	113	113	
	L2	42	52	52	64	64	64	75	75	101	101		101				52
	L3-L4	42	52	52	64	64	64	75	75	101	101		101				52
	R2-R3-R4	42	52	52	64	64	64	75	75	101	101		101				52
307	L1											101	101	101	113	113	
	L2	42	52	52	64	64	64	75	75	101	101		101				52
	L3-L4	42	52	52	64	64	64	75	75	101	101		101				52
	R2	42	52	52	64	64	64	75	75	101	101		101				52
	R3-R4	42	52	52	64	64	64	75	75	101	101		101				52
309	L1											101	101	101	113	113	
	L2	42	52	52	64	64	64	75	75	101	101		101				52
	L3-L4	42	52	52	64	64	64	75	75	101	101		101				52
	R2	42	52	52	64	64	64	75	75	101	101		101				52
	R3-R4	42	52	52	64	64	64	75	75	101	101		101				52
310M	L1											146	146	146	158	158	
	L2											101	101	101	113	113	
	L3	42	52	52	64	64	64	75	75	101	101		101				52
	L4	42	52	52	64	64	64	75	75	101	101		101				52
	R2(B)-R2(C)											101	101	101	113	113	
	R3-R4	42	52	52	64	64	64	75	75	101	101		101				52
311M	L1																
	L2											101	101	101	113	113	
	L3	42	52	52	64	64	64	75	75	101	101		101				52
	L4	42	52	52	64	64	64	75	75	101	101		101				52
	R2(B)-R2(C)											101	101	101	113	113	
	R3-R4	42	52	52	64	64	64	75	75	101	101		101				52
313M	L1																
	L2											101	101	101	113	113	
	L3	42	52	52	64	64	64	75	75	101	101		101				52
	L4	42	52	52	64	64	64	75	75	101	101		101				52
	R2(B)-R2(C)											101	101	101	113	113	
	R3-R4	42	52	52	64	64	64	75	75	101	101		101				52
314M	L1																
	L2											101	101	101	113	113	
	L3	42	52	52	64	64	64	75	75	101	101		101		113		52
	L4	42	52	52	64	64	64	75	75	101	101		101				52
	R3(B)-R3(C)											101	101	101	113	113	
	R4	42	52	52	64	64	64	75	75	101	101		101				52
315M	L1																
	L2																
	L3											101	101	101	113	113	
	L4	42	52	52	64	64	64	75	75	101	101		101				52
	R3(B)-R3(C)											101	101	101	113	113	
	R4	42	52	52	64	64	64	75	75	101	101		101				52
316M	L1																
	L2																
	L3											101	101	101	113	113	
	L4	42	52	52	64	64	64	75	75	101	101		101				52
	R3(B)-R3(C)											101	101	101	113	113	
	R4	42	52	52	64	64	64	75	75	101	101		101				52
317M	L1																
	L2																
	L3											101	101	101	113	113	
	L4	42	52	52	64	64	64	75	75	101	101		101				52
	R3(B)-R3(C)											101	101	101	113	113	
	R4	42	52	52	64	64	64	75	75	101	101		101				52
318M	L1																
	L2																
	L3																
	L4											101	101	101	113	113	
	R4(B)-R4(C)											101	101	101	113	113	
319	L1																
	L2																
	L3																
	L4											101	101	101	113	113	
	R4(B)-R4(C)											101	101	101	113	113	
321	L1																
	L2																
	L3																
	L4											101	101	101	113	113	
	R4(B)-R4(C)											101	101	101	113	113	
323	L1																
	L2																
	L3																
	L4																

* For gear units supplied with a 6" brake



		SAI							KAWASAKI STAFFA	
		GM05 UNI 8953	GM1 UNI 8953	GM1/P1/S1 35x2 z16	GM2 UNI 8953	GM3 UNI 8953	GM4/GM5 UNI 8953	SAI L7 (9) N80x3 z25	B030 z17	B045 z17
		S2BA	S2AB	S2CE	S2AF	S2DN	S2BF	S2BH	S1AB	S1AC
	CODE	I								
300	L1-L2-L3-L4	73	37	57						
	R2-R3-R4	73	37	57						
301	L1-L2-L3-L4	73	37	57						
	R2-R3-R4	73	37	57						
303	L1	73	37	57						
	L2-L3-L4	73	37	57						
	R2-R3-R4	73	37	57						
304	L1	73	37	57						
	L2-L3-L4	73	37	57						
	R2-R3-R4	73	37	57						
305	L1	73	37	57						
	L2-L3-L4	73	37	57						
	R2-R3-R4	73	37	57						
306	L1		74		98	98	105		135	140
	L2	73	37	57						
	L3-L4	73	37	57						
	R2-R3-R4	73	37	57						
307	L1		74		98	98	105		135	140
	L2	73	37	57						
	L3-L4	73	37	57						
	R2	73	37	57						
	R3-R4	73	37	57						
309	L1		74		98	98	105		135	140
	L2	73	37	57						
	L3-L4	73	37	57						
	R2	73	37	57						
	R3-R4	73	37	57						
310M	L1		119		143	143	156		180	185
	L2		74		98	98	105		135	140
	L3	73	37	57						
	L4	73	37	57						
	R2(B)-R2(C)		74		98	98	105		135	140
	R3-R4	73	37	57						
311M	L1				149		156	90		
	L2		74		98	98	105		135	140
	L3	73	37	57						
	L4	73	37	57						
	R2(B)-R2(C)		74		98	98	105		135	140
	R3-R4	73	37	57						
313M	L1				149		156	90		
	L2		74		98	98	105		135	140
	L3	73	37	57						
	L4	73	37	57						
	R2(B)-R2(C)		74		98	98	105		135	140
	R3-R4	73	37	57						
314M	L1									
	L2		74		98	98	105		135	140
	L3	73	37	57						
	L4	73	37	57						
	R3(B)-R3(C)		74		98	98	105		135	140
	R4	73	37	57						
315M	L1									
	L2				149		156	90		
	L3		74		98	98	105		135	140
	L4	73	37	57						
	R3(B)-R3(C)		74		98	98	105		135	140
	R4	73	37	57						
316M	L1									
	L2				149		156	90		
	L3		74		98	98	105		135	140
	L4	73	37	57						
	R3(B)-R3(C)		74		98	98	105		135	140
	R4	73	37	57						
317M	L1									
	L2				149		156	90		
	L3		74		98	98	105		135	140
	L4	73	37	57						
	R3(B)-R3(C)		74		98	98	105		135	140
	R4	73	37	57						
318M	L1									
	L2									
	L3				149		156	90		
	L4		74		98	98	105		135	140
	R4(B)-R4(C)		74		98	98	105		135	140
319	L1									
	L2									
	L3				149		156	90		
	L4		74		98	98	105		135	140
	R4(B)-R4(C)		74		98	98	105		135	140
321	L1									
	L2									
	L3				149		156	90		
	L4		74		98	98	105		135	140
	R4(B)-R4(C)		74		98	98	105		135	140
323	L1									
	L2									
	L3									
	L4				149/ 98 (*)		156/ 105 (*)	90		

* For gear units supplied with a 6" brake





		SAUER DANFOSS (piston)														
		OMF-SMF-OMV -SMV 1-038 16/32 z13	SMF 2/033-052-070 16/32 z21	SMF 2/089 16/32 z23	SMF 2/119 16/32 z27	SMF 2/166-227 16/32 z27	SMF 4/023 90M042 16/32 z13	SMF 4/046 90M042 16/32 z15	90 M055 16/32 z21	90 M075-M100 16/32 z23	90 M130 16/32 z27	51 V 060 12/24 z14	51 V 080 12/24 z14	51 V 110 8/16 z13	51 V 160 8/16 z13	51 V 250 8/16 z15
		S5BA	S5CE	S5CD	S5DC	S5EC	S5BA	S5BM	S5CE	S5CD	S5DC	S5CA	S5CA	S5DA	S5DA	S5ED
	CODE								I							
300	L1-L2-L3-L4	52	64	64	81		52	52	64	64	81	64	64	81	81	
	R2-R3-R4	52	64	64	81		52	52	64	64	81	64	64	81	81	
301	L1-L2-L3-L4	52	64	64	81		52	52	64	64	81	64	64	81	81	
	R2-R3-R4	52	64	64	81		52	52	64	64	81	64	64	81	81	
303	L1	52	64	64	81		52	52	64	64	81	64	64	81	81	
	L2-L3-L4	52	64	64	81		52	52	64	64	81	64	64	81	81	
	R2-R3-R4	52	64	64	81		52	52	64	64	81	64	64	81	81	
304	L1	52	64	64	81		52	52	64	64	81	64	64	81	81	
	L2-L3-L4	52	64	64	81		52	52	64	64	81	64	64	81	81	
	R2-R3-R4	52	64	64	81		52	52	64	64	81	64	64	81	81	
305	L1	52	64	64	81		52	52	64	64	81	64	64	81	81	
	L2-L3-L4	52	64	64	81		52	52	64	64	81	64	64	81	81	
	R2-R3-R4	52	64	64	81		52	52	64	64	81	64	64	81	81	
306	L1				101	113					101			101	101	113
	L2	52	64	64	81		52	52	64	64	81	64	64	81	81	
	L3-L4	52	64	64	81		52	52	64	64	81	64	64	81	81	
	R2-R3-R4	52	64	64	81		52	52	64	64	81	64	64	81	81	
307	L1				101	113					101			101	101	113
	L2	52	64	64	81		52	52	64	64	81	64	64	81	81	
	L3-L4	52	64	64	81		52	52	64	64	81	64	64	81	81	
	R2	52	64	64	81		52	52	64	64	81	64	64	81	81	
	R3-R4	52	64	64	81		52	52	64	64	81	64	64	81	81	
309	L1				101	113					101			101	101	113
	L2	52	64	64	81		52	52	64	64	81	64	64	81	81	
	L3-L4	52	64	64	81		52	52	64	64	81	64	64	81	81	
	R2	52	64	64	81		52	52	64	64	81	64	64	81	81	
	R3-R4	52	64	64	81		52	52	64	64	81	64	64	81	81	
310M	L1				146	158					146			146	146	158
	L2				101	113					101			101	101	113
	L3	52	64	64	81		52	52	64	64	81	64	64	81	81	
	L4	52	64	64	81		52	52	64	64	81	64	64	81	81	
	R2(B)-R2(C)				101	113					101			101	101	113
	R3-R4	52	64	64	81		52	52	64	64	81	64	64	81	81	
311M	L1															
	L2				101	113					101			101	101	113
	L3	52	64	64	81		52	52	64	64	81	64	64	81	81	
	L4	52	64	64	81		52	52	64	64	81	64	64	81	81	
	R2(B)-R2(C)				101	113					101			101	101	113
	R3-R4	52	64	64	81		52	52	64	64	81	64	64	81	81	
313M	L1															
	L2				101	113					101			101	101	113
	L3	52	64	64	81		52	52	64	64	81	64	64	81	81	
	L4	52	64	64	81		52	52	64	64	81	64	64	81	81	
	R2(B)-R2(C)				101	113					101			101	101	113
	R3-R4	52	64	64	81		52	52	64	64	81	64	64	81	81	
314M	L1															
	L2				101	113					101			101	101	113
	L3	52	64	64	81		52	52	64	64	81	64	64	81	81	
	L4	52	64	64	81		52	52	64	64	81	64	64	81	81	
	R3(B)-R3(C)				101	113					101			101	101	113
	R4	52	64	64	81		52	52	64	64	81	64	64	81	81	
315M	L1															
	L2															
	L3				101	113					101			101	101	113
	L4	52	64	64	81		52	52	64	64	81	64	64	81	81	
	R3(B)-R3(C)				101	113					101			101	101	113
	R4	52	64	64	81		52	52	64	64	81	64	64	81	81	
316M	L1															
	L2															
	L3				101	113					101			101	101	113
	L4	52	64	64	81		52	52	64	64	81	64	64	81	81	
	R3(B)-R3(C)				101	113					101			101	101	113
	R4	52	64	64	81		52	52	64	64	81	64	64	81	81	
317M	L1															
	L2															
	L3				101	113					101			101	101	113
	L4	52	64	64	81		52	52	64	64	81	64	64	81	81	
	R3(B)-R3(C)				101	113					101			101	101	113
	R4	52	64	64	81		52	52	64	64	81	64	64	81	81	
318M	L1															
	L2															
	L3															
	L4				101	113					101			101	101	113
	R4(B)-R4(C)				101	113					101			101	101	113
319	L1															
	L2															
	L3															
	L4				101	113					101			101	101	113
	R4(B)-R4(C)				101	113					101			101	101	113
321	L1															
	L2															
	L3															
	L4				101	113					101			101	101	113
	R4(B)-R4(C)				101	113					101			101	101	113
323	L1															
	L2															
	L3															
	L4															

* For gear units supplied with a 6" brake



		TRW-TORQMOTOR (PARKER)					VICKERS (EATON)				WHITE				
		MAG 04-32 SAE 1" 6B	MAF 06-40 SAE 1" 6B	MAB 06-32 SAE 1" 6B	MAB 06-32 SAE A ø25	MAE 10-68 SAE 1" 6B	MFE 19 16/32 z15	25M**A11 16/32 z13	35-45 M**A11 12/24 z14	50 M**A11 8/16 z13	HS 02-15 SAE A ø25	HS 02-15 SAE A 1" 6B	RS 08-24 SAE A ø25	RS 08-24 SAE A 1" 6B	REO 06-45 SAE A 1" 6B
		S5AQ	S5AQ	S5AQ	S5AP	S5AQ	S5BM	S5BA	S5CA	S5DA	S5AP	S5AQ	S5AP	S5AQ	S5AP
	CODE	I													
300	L1-L2-L3-L4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	R2-R3-R4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
301	L1-L2-L3-L4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	R2-R3-R4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
303	L1	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	L2-L3-L4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	R2-R3-R4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
304	L1	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	L2-L3-L4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	R2-R3-R4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
305	L1	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	L2-L3-L4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	R2-R3-R4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
306	L1									101					
	L2	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	L3-L4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	R2-R3-R4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
307	L1									101					
	L2	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	L3-L4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	R2	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	R3-R4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
309	L1									101					
	L2	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	L3-L4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	R2	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	R3-R4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
310M	L1									146					
	L2									101					
	L3	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	L4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	R2(B)-R2(C)									101					
	R3-R4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
311M	L1														
	L2									101					
	L3	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	L4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	R2(B)-R2(C)									101					
	R3-R4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
313M	L1														
	L2									101					
	L3	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	L4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	R2(B)-R2(C)									101					
	R3-R4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
314M	L1														
	L2									101					
	L3	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	L4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	R3(B)-R3(C)									101					
	R4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
315M	L1														
	L2														
	L3									101					
	L4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	R3(B)-R3(C)									101					
	R4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
316M	L1														
	L2														
	L3									101					
	L4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	R3(B)-R3(C)									101					
	R4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
317M	L1														
	L2														
	L3									101					
	L4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
	R3(B)-R3(C)									101					
	R4	42	42	42	42	42	52	52	64	81	42	42	42	42	42
318M	L1														
	L2														
	L3														
	L4									101					
	R4(B)-R4(C)									101					
319	L1														
	L2														
	L3														
	L4									101					
	R4(B)-R4(C)									101					
321	L1														
	L2														
	L3														
	L4									101					
	R4(B)-R4(C)									101					
323	L1														
	L2														
	L3														
	L4														

* For gear units supplied with a 6" brake





		VOAC (PARKER)																		
		F11-5 CK ø18	F11-10 CK ø20	F11-19 CK ø25	F11-19 CD 25x1,25 z18	F12-30 MF*I*D 30x2 z14	F12-40 MF*I*D 32x2 z14	F12-60 MF*I*D 35x2 z16	F12-80 MF*I*D 40x2 z18	F12-110 MF*I*D 45x2 z21	F11-150/250 S+S 8/16 z13	V12 060 I*D 35x2 z16	V12 060 S*S 12/24 z14	V12 080 N*D 40x2 z18	V12 080 S*S 12/24 z14	V12 110 I*D 45x2 z21	V12 110 S*S 8/16 z13	V12 160 S*S 8/16 z13	V12 160 N*C 45x2 z21
		V0AA	V0AC	V0AE	V0AG	H0AE	H0AI	H0BC	H0BG	H0CA	S5DA	H0BC	S5CA	H0BG	S5CA	H0CA	S5DA	S5DA	H0CG
	CODE	I																	
300	L1-L2-L3-L4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	R2-R3-R4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
301	L1-L2-L3-L4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	R2-R3-R4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
303	L1	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	L2-L3-L4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	R2-R3-R4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
304	L1	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	L2-L3-L4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	R2-R3-R4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
305	L1	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	L2-L3-L4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	R2-R3-R4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
306	L1										101						101	101	
	L2	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	L3-L4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	R2-R3-R4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
307	L1										101						101	101	
	L2	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	L3-L4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	R2	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	R3-R4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
309	L1										101						101	101	
	L2	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	L3-L4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	R2	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	R3-R4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
310M	L1										146						146	146	
	L2										101						101	101	
	L3	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	L4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	R2(B)-R2(C)										101						101	101	
	R3-R4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
311M	L1																		
	L2										101						101	101	
	L3	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	L4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	R2(B)-R2(C)										101						101	101	
	R3-R4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
313M	L1																		
	L2										101						101	101	
	L3	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	L4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	R2(B)-R2(C)										101						101	101	
	R3-R4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
314M	L1																		
	L2										101						101	101	
	L3	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	L4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	R3(B)-R3(C)										101						101	101	
	R4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
315M	L1																		
	L2																		
	L3										101						101	101	
	L4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	R3(B)-R3(C)										101						101	101	
	R4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
316M	L1																		
	L2																		
	L3										101						101	101	
	L4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	R3(B)-R3(C)										101						101	101	
	R4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
317M	L1																		
	L2																		
	L3										101						101	101	
	L4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
	R3(B)-R3(C)										101						101	101	
	R4	64	52	53	53	52	64	64	75	101	81	64	64	75	64	101	81	81	101
318M	L1																		
	L2																		
	L3																		
	L4										101						101	101	
	R4(B)-R4(C)										101						101	101	
319	L1																		
	L2																		
	L3																		
	L4										101						101	101	
	R4(B)-R4(C)										101						101	101	
321	L1																		
	L2																		
	L3																		
	L4										101						101	101	
	R4(B)-R4(C)										101						101	101	
323	L1																		
	L2																		
	L3																		
	L4																		

* For gear units supplied with a 6" brake

H4 HYDRAULIC MOTORS

GENERAL FEATURES

Gearboxes belonging to the series 300M can be supplied complete with MG hydraulic motors manufactured by BONFIGLIOLI TRASMITAL. These motors were designed to provide compact and energy efficient gearmotors.
Before ordering, you should consult with the Technical Service Bonfiglioli.



H4.1 MG hydraulic motors

Design characteristics:

- Orbit system with GEROLER® rollers between rotor and stator
- Distributor on output shaft
- Displacements from 50 to 250 cm^3
- Max. pressure 175 bar
- Max. flow rate 48 lt/min
- High efficiency
- Hydraulic brake can be included in the motor overall dimensions
- Inner brake directly controlled by the motor with no valves or outer circuits required.

H5 TECHNICAL FEATURES

H5.1 Displacement V [cm^3]

Geometrical volume produced as a result of each motor rotation corresponding to the theoretical volume of hydraulic oil necessary for a rotation of the driving shaft

H5.2 Pressure p [bar]

Hydraulic pressure applied to the motor when running.

H5.3 Flow rate Q [l / min]

Hydraulic oil flow through the motor when running.

H5.4 Efficiency η_t

Total efficiency of the hydraulic motor given by:

$$\eta_t = \eta mh \times \eta v \quad (38)$$



H5.5 Mechanical-hydraulic efficiency ηmh

This is the ratio of actual torque to theoretical torque at the driving shaft. Value depending on inner losses due to mechanical friction as well as hydraulic fluid pressure losses, calculated as follows:

$$\eta mh = \frac{2\pi \times 10 \times M}{(pA - pB) \times V} \quad (39)$$

H5.6 Hydraulic efficiency ηv

This is the ratio of motor actual speed to motor theoretical speed. Value depending on the motor inner blow-by between high and low pressure volumes. This value is given by the following formula:

$$\eta v = \frac{n \times V}{Q \times 1000} \quad (40)$$

H5.7 Angular speed n [min-1]

Hydraulic motor rotation speed. Value resulting from the following formula:

$$n = \frac{Q \times 1000}{V} \times \eta v \quad (41)$$

H5.8 Torque M [Nm]

Actual torque transmitted by the hydraulic motor. Value given by the following formula:

$$M = \frac{(p\,A - p\,B) \times V}{2\pi \times 10} \times \eta mh \quad (42)$$

H6 DESIGNATION

MG 050 SD_R P010

PORTS

P010 = oil ports on motor housing direct — with brake



without brake



B02P = oil ports with valve brake pilot — with brake



CONSTRUCTIVE SERIES

DISPLACEMENT

050	51.60	cm³	**160**	159.60	cm³
080	80.30	cm³	**200**	199.80	cm³
100	99.80	cm³	**250**	249.30	cm³
125	125.70	cm³			

ORBIT MOTOR TYPE MG

H7 DISPLACEMENT SELECTION

Displacement V of the hydraulic motor should be selected together with the gearbox.

Once the output torque and speed n_2 for the gearbox M_{r2} is known, proceed as follows:

Define the control pressure value pA-pB ≤ 175 bar for the motor.

Calculate the gearbox displacement value called Veq with the following formula:

$$Veq = \frac{2\pi \times 10 \times M_{r2}}{(pA - pB) \times \eta mh \times \eta d} \ [cm^3] \quad (43)$$

where ηmh, for example, is equal to 0.85;
η_d: gearbox dynamic efficiency, consider 0.94.

Calculate the value for flow rate Q, necessary for feeding the hydraulic motor, with the following formula:

$$Q = \frac{n_2 \times Veq}{1000 \times \eta v} \ [l/min] \quad (44)$$

where ηv, for example, is equal to 0.90.

− Select the gearbox size with M_{r2} and n_2.

− Look up the diagram (A23) for the gearmotor with equivalent displacement value Veq and select:
- a motor that fulfils the p int. and Q requirements and at the same time.
- the indicative value of reduction ratio i. Please consider that ratio should be obtained with as few reduction stages as possible, to save on gearmotor costs and contain dimensions.

Once you have determined the value of M_2 and the indicative value of i, select the gearbox and check your selection as indicated in chapt. 14.5.

H8 CHECKING

Check that pressure, efficiency and flow rate values correspond with values indicated in Table (A33 and A34) on motor technical features.

H9 TECHNICAL DATA MG MOTORS

(A 32)



(A 33)





(A 34)

MG 100 SD_H



MG 125 SD_H



MG 160 SD_H



MG 200 SD_H



MG 250 SD_H



MG-**P010



PORTS

A - B = 3/8” G 19TPI
T = 1/8” G 28TPI
X = 1/4 G 19TPI

MG-**B02P



(A 35)

Suitable gearbox	Motor							Execution		
	MG 050	MG 080	MG 100	MG 125	MG 160	MG 200	MG 250	P010		B02P
	M1							M2	M3	M5
300 L1 - L2 - R2	162	167	171	175	181			113	60	143
301 L1 - L2 - R2	162	167	171	175	181	188	197	113	60	143
303 L1					203	210	219	135	77	165
303 L2 - R2	162	167	171	175	181	188	197	113	60	143
304 L1				197	203	210	219	135	77	165
304 L2 - R2	162	167	171	175	181	188	197	113	60	143
305 L1					203	210	219	135	77	165
305 L2 - R2	162	167	171	175	181	188	197	113	60	143
306 L2					203	210	219	135	77	165
306 R2 - R3	162	167	171	175	181	188	197	113	60	143
307 L2					203	210	219	135	77	165
307 R2 - R3	162	167	171	175	181	188	197	113	60	143

H11 TECHNICAL DATABRAKES FOR MG MOTORS

(A 36)

		Brake TYPE 3				Brake TYPE 4			
		3E	**3I**	**3L**	**3N**	**4K**	**4N**	**4R**	**4U**
Brake torque Mf	Nm]	120	200	280	350	260	320	430	620
Min. opening pressure	[bar]	16	28	28	35	25	30	24	34
Max. operating pressure	[bar]	200							
Oil volume for brake release	[cc]	6.43	6.43	6.43	6.43	6.65	6.65	6.65	6.65

(A 37)

Suitable gearbox	Motor													
	MG 050		**MG 080**		**MG 100**		**MG 125**		**MG 160**		**MG 200**		**MG 250**	
	Mf [Nm]		Mf [Nm]		Mf [Nm]		Mf [Nm]		Mf [Nm]		Mf [Nm]		Mf [Nm]	
300 L1 - L2	120	**3E**	200	**3I**	280	**3L**	350	**3N**	350	**3N**				
300 R2	120	**3E**	200	**3I**	280	**3L**								
301 L1 - L2			200	**3I**	280	**3L**	350	**3N**	350	**3N**	350	**3N**	350	**3N**
301 R2	120	**3E**	200	**3I**	280	**3L**	350	**3N**	350	**3N**				
303 L1									430	**4R**	430	**4R**	430	**4R**
303 L2	120	**3E**	200	**3I**	280	**3L**	350	**3N**	350	**3N**	350	**3N**		
303 R2	120	**3E**	200	**3I**	280	**3L**	350	**3N**	350	**3N**	350	**3N**		
304 L1							350	**3N**	430	**4R**	430	**4R**	430	**4R**
304 L2	120	**3E**	200	**3I**	280	**3L**	350	**3N**	350	**3N**	350	**3N**		
304 R2	120	**3E**	200	**3I**	280	**3L**	350	**3N**	350	**3N**	350	**3N**		
305 L1									430	**4R**	430	**4R**	430	**4R**
305 L2	120	**3E**	200	**3I**	280	**3L**	350	**3N**	350	**3N**	350	**3N**		
305 R2	120	**3E**	200	**3I**	280	**3L**	350	**3N**	350	**3N**	350	**3N**		
306 L2			260	**4K**	260	**4K**	430	**4R**	430	**4R**	430	**4R**	430	**4R**
306 R2 - R3			200	**3I**	280	**3L**	350	**3N**	350	**3N**	350	**3N**		
307 L2					260	**4K**	430	**4R**	430	**4R**	430	**4R**	430	**4R**
307 R2 - R3			200	**3I**	280	**3L**	350	**3N**	350	**3N**	350	**3N**	350	**3N**

H12 INSTALLATION

Further to standards on gearbox installation, refer to chapter 15, comply with the following hydraulic motor installation instructions.

a) Connection to the hydraulic circuit

Motors can be connected either to closed or open circuits.
In case of an open circuit, solenoid valve or control distributor can be of the closed or open center type.

The hydraulic motor delivery side should always have a max. pressure valve set to a value not exceeding the p_{int} value allowed for the hydraulic motor. See hydraulic diagrams (A29).

(A 38)

CLOSED LOOP CIRCUIT



OPEN LOOP CIRCUIT



RV = Max pressure valve set to a pRV < pmax

If not possible, because the circuits control other devices needing a higher pressure and/or a closed center control valve is fitted and the motor controls parts with a high moment of inertia, max. pressure secondary valves should be as close as possible to the motor. See diagram (A39).

(A 39)



RV = Max pressure secondary valve set to a pRV < pmax

b) Connecting drain port T

These motors have a 1/8" G drain hole in the centre of the cover. The motor is supplied with the port closed by a metal plug (see figure below).

(A 40)



1) If the drain port is connected up, pressure at the shaft seal is always equal to the pressure in the drain line.

2) if a closed drainage system is used, the pressure on the shaft oil seal will be equal to the average value between the inlet and outlet pressures.

$$P_{seal} = \frac{P_{in} + P_{out}}{2}$$

The maximum values for pressure acceptable for the seal are given in the following figure (for continuous and intermittent operating conditions).

(A 41)



The drain port must always be connected up when more motors are operated in series.

c) Brake control

For gearmotors equipped with brakes, there are two motor versions available, i.e. the B02P or P010 executions.
In the B02P version, the motor has an in-built, direct brake control system. In the P010 version, an auxiliary branching is required to control the brake. See the following diagram.

(A 42)

OPEN LOOP CIRCUIT **CLOSED LOOP CIRCUIT**

Control valve open centre type Control valve closed centre type



d) Hydraulic oil

Use hydraulic mineral oil with viscosity ISO VG 46 (46 Cst at t = 40°C).
It is recommended the oil temperature should be between +30°C and +70°C.

e) Oil filtering

For reliable motor operation and long life, it is important that the hydraulic circuit has a filter for a proper oil filtering according to the following degree:

degree 9 NAS 1638
degree 6 SAE
degree 18/15 SO DIS 4406



PLANETARY GEARBOX SERIES 300M ATEX CONFIGURATION

A1 SCOPE OF DOCUMENT

This Technical Bulletin serves as an aid for the selection of 300M series planetary gear units intended for installation in explosion risk areas, classified according to Directive 1999/92/EC.

This Technical Bulletin is an integral part of the 300M series, and subsequent revisions, and has the following scope:
• describes the **constructional characteristics** of the reducers comply with the directive 2014/34/EU, where these differ from those of standard construction gear units - See section A4.2.
• specifies the **selection criteria** approved by the manufacturer that said gear units operate keeping the minimum security requirements required by the Directive 2014/34/EU - See section A4.4.

A2 INTRODUCTION TO THE ATEX DIRECTIVES

Under the provisions of Directive 2014/34/EU, an explosive atmosphere is defined as a mixture:
a) of **flammable substances**, whether gas, vapour, mist or dust;
b) with **air;**
c) in certain **atmospheric conditions**;
d) in which, following ignition, combustion spreads to the entire unburned mixture (note that in the case of dust, the entire quantity of dust is not always completely burnt after combustion).
An atmosphere which may potentially be transformed into an explosive atmosphere due to operating and/or ambient conditions is defined as a **potentially explosive atmosphere**. The products governed by Directive 2014/34/EU are intended for use only in a potentially explosive atmosphere defined in this way.

European harmonised ATEX standards
The European Union has issued two harmonisation guidelines in the area of health and safety. Directive 2014/34/EU stipulates the minimum safety requirements for products intended for use in explosion risk areas within the member countries of the European Union. The directive also assigns such equipment to **categories**, which are defined by the directive itself.
Directive 1999/92/EC defines the minimum health and safety requirements for the workplace, for working conditions and for the handling of products and materials in explosion risk areas. The directive also divides the workplace into zones and defines the criteria for the application of product **categories** in said **zones.**
The following table describes the **zones** into which the user of a plant, in which an explosive atmosphere may occur, is required to divide the equipment application areas.

Zones		Formation frequency of a potentially explosive atmosphere	Type of danger
Gaseous atmosphere G	Dusty atmosphere D		
0	20	Present continuously or for long periods	Permanent
1	21	Likely to occur in normal operation occasionally	Potential
2	22	Not likely to occur in normal operation but if it does occur will persist for short period only	Minimal



BONFIGLIOLI RIDUTTORI gear units selected in this catalogue are marked for installation in zones 1, 21, as highlighted in light gray in the above table and are also suitable for installation in areas with a lower level of protection (zones 2 and 22).
Starting from July 1, 2003, the Atex Directives apply throughout the European Union, and replace the divergent laws currently in force at national and European level in the field of explosive atmospheres.
The directives apply to mechanical, hydraulic and pneumatic equipment.

Levels of protection for the various categories of equipment
The various categories of equipment must be able to operate in conformity with the Manufacturer's operational specifications, at certain defined levels of protection.

Protection level	Category		Type of protection	Operating conditions
	Group I	Group II		
Very high	M1		Two independent means of protection or safety capable of operating even when two independent faults occur	The equipment remains powered and operational even in the presence of an explosive atmosphere
Very high		1	Two independent means of protection or safety capable of operating even when two independent faults occur	The equipment remains powered and operational in zones 0, 1, 2 (G) and/or zones 20, 21, 22 (D)
High	M2		Protection suitable for normal operation and heavy duty conditions	Power to the equipment is shut off in the presence of a potentially explosive atmosphere
High		2	Protection suitable for normal operation and frequent faults or equipment in which malfunction is normal.	The equipment remains powered and operational in zones 1, 2 (G) and/or zones 21, 22 (D)
Normal		3	Protection suitable for normal operation	The equipment remains powered and operational in zones 2 (G) and/or 22 (D)

Definition of groups (EN 1127-1)
Group I Applies to equipment intended for use underground in parts of mines and those parts of surface installations of such mines, liable to be endangered by firedamp and/or combustible dust.
Group II Applies to equipment intended for use in other places liable to be endangered by explosive atmospheres.

The areas highlighted in grey indicate the only categories in which BONFIGLIOLI RIDUTTORI products may be used. BONFIGLIOLI RIDUTTORI products may not therefore be installed in mines, classified in **Group I**. To summarise, the classification of equipment into groups, categories and zones is illustrated in the table below, where the availability of BONFIGLIOLI RIDUTTORI products is highlighted in grey.

Group	I mines, firedamp		II other potentially explosive areas (gas, dust)					
Category	M1	M2	1		2		3	
Atmosphere(1)			G	D	G	D	G	D
Zone			0	20	1	21	2	22
Type of protection gear unit(2)					Ex h Gb	Ex h Db	Ex h Gc	Ex h Dc

(1) **G** = gas **D** = dust
(2) as per 80079-36 and EN 80079-37

A3 USE, INSTALLATION AND MAINTENANCE

The instructions for safe storage, handling and use of the product are given in the unit's User, Installation and Service Manual.
This document must be kept in a suitable place, in the vicinity of the installed gear unit, as a reference for all persons authorised to work with or on the product throughout its service life.

The Manufacturer reserves the right to modify, supplement or improve the Manual, in the interests of the User.

A4 PECULIARITIES OF 300M SERIES GEAR UNITS COMPLIANT WITH DIRECTIVE ATEX

A4.1 PRODUCT AVAILABILITY

Frame sizes : 300 to 325.

	3...L		3...R	
Configurations	300...309, 310M...318M, 319	L 1	-	- -
	300...309, 310M...318M, 319...321	L 2	300...306	R 2
	300...309, 310M...318M, 319...321	L 3	300...309, 310M...317M	R 3
	300...309, 310M...318M, 319...325	L 4	300...309, 310M...318M, 319...321	R 4

Versions	Foot mount		Flange mount			Shaft mount			Agitator (vertical)
									
	PC	PZ	MC/HC	MZ/HZ	FZ	FP	FDK	FZP	VK

Inputs			
	P(IEC)	 V_	Hydraulic motor connecting BONFIGLIOLI TECHNICAL SERVICE
			Standard negative multidisc brake **6** = Type: **4, 5, 6** **A** = Braking torque: **A, B, C, ...** BONFIGLIOLI TECHNICAL SERVICE

NOTE:
- With the negative multi disc brake, you must always ensure a minimum pressure for opening the discs. This must be 20% higher than that of the table of the brakes.
- The pressure max. of brake control must not exceed 50 bar.

Accessories					
					
	P ...	B0A	M0A	G0A	W0A

A4.2 CONSTRUCTIONAL CHARACTERISTICS

• Only synthetic lubricants are used.
• Only VITON® gaskets are used.
• Oil seals are equipped with dust lips.
• Vent plugs are equipped with valves with anti-intrusion springs, to prevent contamination of the lubricant by solid particles.
• Oil filler, drain and level plugs are made from steel and equipped with aluminium lock washers.
• No external metal moving parts in contact with other parts.
• No plastic parts prone to accumulating static charges; if present, such parts are shielded.
• Each gear unit is supplied with an installation drawing indicating the following information:
- main technical characteristics
- installation specifications
- location of oil plugs for the specified mounting position
- lubrication instructions
• The units are fitted with an additional nameplate specifying the product category. For example:



A Manufacturer
B Product identification
C Product code
D Reduction ratio
E Serial number
F Date of manufacture
G Client product code
H Specific symbols of Atex marking

A4.3 OPERATIONAL CHARACTERISTICS

For installation in zones 21 and 22, the Customer must set out and implement a specific cleaning schedule for the unit's surfaces and recesses to prevent build ups of dust exceeding 5 mm in depth.



A4.4 SELECTING THE PRODUCT

The gear unit and gearmotor selection procedure is identical to that given in the 300M Series, and any future revisions thereof.
The following chapters contain variations to the procedure given in the catalogue, and subsequent revisions thereof as regards the selection of products compliant with 2014/34/EU, which supersede the procedure specified in the catalogue for units intended for installation in areas without risk of explosion.
These variations primarily affect the following:
• Application of an adjusting factor to the thermal capacity.
• Application of a service factor « f_s » with a greater safety margin.

- Thermal power « P_T » [kW]
Refer to section 14.5 “VERIFICATION” about calculation of the correct P_T value.

Only for L1 Atex configuration, the reference P_T value are listed in the table below. The are valid for:
- Maximum input speed as written
- Ambient temperature 40°C
- Horizontal mounting position
- Installation in large area (air speed > 1.4 m/s)
- Intermittent duty 20% based 60 min running

Please refer to Bonfiglioli Tecnical Service for other type of application.

L1	**P_{TB}** [kW] @ 20% intermittent duty	**$n_{1\ max}$** [min^{-1}] @ L1 ATEX
300	14	1000
301	16	
303	20	700
304	25	
305	25	
306	27	500
307	35	
309	35	
310M	37	400
311M	40	
313M	42	
314M	45	300
315M	45	
316M	45	
317M	55	200
318M	60	
319	70	

- Service factor in Atex gearboxes with Negative multidisc brake





		POS O, Q, T, V Input speed [rpm] 100 200 300 400 500 600 700 800 900 1000 1100 1200 1300 1400 1500 1600 1700 1800
300	**L1**	85%
	L2	85% 70%
	L3	85% 70%
	L4	85% 70%
301	**L1**	85%
	L2	85% 70%
	L3	85% 70%
	L4	85% 70%
303	**L1**	60%
	L2	85% 70%
	L3	85% 70%
	L4	85% 70%
305	**L1**	60%
	L2	85% 70%
	L3	85% 70%
	L4	85% 70%
306	**L1**	50%
	L2	60% 40%
	L3	85% 70%
	L4	85% 70%
307	**L1**	50%
	L2	60% 40%
	L3	85% 70%
	L4	85% 70%
309	**L1**	50%
	L2	60% 40%
	L3	85% 70%
	L4	85% 70%
310M	**L1**	no brake
	L2	50% 15% 10%
	L3	60% 40%
	L4	85% 70%
311M	**L1**	no brake
	L2	50% 15% 10%
	L3	60% 40%
	L4	85% 70%
313M	**L1**	no brake
	L2	50% 15% 10%
	L3	60% 40%
	L4	85% 70%
315M	**L1**	no brake
	L2	
	L3	50% 15% 10%
	L4	60% 40%
316M	**L1**	no brake
	L2	
	L3	50% 15% 10%
	L4	60% 40%
317M	**L1**	no brake
	L2	
	L3	50% 15% 10%
	L4	60% 40%
318M	**L1**	no brake
	L2	
	L3	50% 15% 10%
	L4	60% 40%
319	**L1**	no brake
	L2	no brake
	L3	50%
	L4	50% 15% 10%
321	**L1**	no brake
	L2	no brake
	L3	no brake
	L4	50% 15% 10%

Unusable speed



		POS B0, B2, I0, I2, J0, J2, M1, M3, P, R, U, W Input speed [rpm]																	
		100	200	300	400	500	600	700	800	900	1000	1100	1200	1300	1400	1500	1600	1700	1800
300	**R2**	85%									70%								
	R3	85%									70%								
	R4	85%									70%								
301	**R2**	85%									70%								
	R3	85%									70%								
	R4	85%									70%								
303	**R2**	85%									70%								
	R3	85%									70%								
	R4	85%									70%								
305	**R2**	85%									70%								
	R3	85%									70%								
	R4	85%									70%								
306	**R2**	85%									70%								
	R3	85%									70%								
	R4	85%									70%								
307	**R2**	60%														40%			
	R3	85%									70%								
	R4	85%									70%								
309	**R2**	60%														40%			
	R3	85%									70%								
	R4	85%									70%								
310M	**R2 (A)**	60%														40%			
	R2 (B)	50%							15%					10%					
	R3	85%									70%								
	R4	85%									70%								
311M	**R2 (A)**	60%														40%			
	R2 (B)	50%							15%					10%					
	R2 (C)	50%							15%					10%					
	R3	60%														40%			
	R4	85%									70%								
313M	**R2 (A)**	60%																	
	R2 (B)	50%							15%					10%					
	R2 (C)	50%							15%					10%					
	R3	60%														40%			
	R4	85%									70%								
315M	**R3 (A)**	60%																	
	R3 (B)	50%							15%					10%					
	R3 (C)	50%							15%					10%					
	R4	60%														40%			
316M	**R3 (B)**	50%							15%					10%					
	R3 (C)	50%							15%					10%					
	R4	60%														40%			
317M	**R3 (A)**	60%																	
	R3 (B)	50%							15%					10%					
	R3 (C)	50%							15%					10%					
	R4	60%														40%			
318M	**R4 (B)**	50%							15%					10%					
	R4 (C)	50%							15%					10%					
319	**R4 (B)**	60%																	
	R4 (C)	50%							15%					10%					
	R4 (C)	50%							15%					10%					
321	**R4 (B)**	60%																	
	R4 (C)	50%							15%					10%					
	R4 (C)	50%							15%					10%					

Unusable speed



		POS B1, B3, I1, I3, J1, J3, M0, M2 Input speed [rpm]																
		100	200	300	400	500	600	700	800	900	1000	1100	1200	1300	1400	1500	1600	1700	1800
300	**R2**	85%																	
	R3	85%																	
	R4	85%																	
301	**R2**	85%																	
	R3	85%																	
	R4	85%																	
303	**R2**	85%																	
	R3	85%																	
	R4	85%																	
305	**R2**	85%																	
	R3	85%																	
	R4	85%																	
306	**R2**	85%																	
	R3	85%																	
	R4	85%																	
307	**R2**	85%														75%			
	R3	85%																	
	R4	85%																	
309	**R2**	85%														75%			
	R3	85%																	
	R4	85%																	
310M	**R2 (A)**	85%														75%			
	R2 (B)	85%																	
	R3	85%																	
	R4	85%																	
311M	**R2 (A)**	85%														75%			
	R2 (B)	85%																	
	R2 (C)	85%																	
	R3	85%														75%			
	R4	85%																	
313M	**R2 (A)**	60%																	
	R2 (B)	85%																	
	R2 (C)	85%																	
	R3	85%														75%			
	R4	85%																	
315M	**R3 (A)**	60%																	
	R3 (B)	85%																	
	R3 (C)	85%																	
	R4	85%														75%			
316M	**R3 (B)**	85%																	
	R3 (C)	85%																	
	R4	85%														75%			
317M	**R3 (A)**	85%																	
	R3 (B)	85%																	
	R3 (C)	85%																	
	R4	85%														75%			
318M	**R4 (B)**	85%																	
	R4 (C)	85%																	
319	**R4 (B)**	60%																	
	R4 (C)	85%																	
	R4 (C)	85%																	
321	**R4 (B)**	85%																	
	R4 (C)	85%																	
	R4 (C)	85%																	

Unusable speed



- Service factor « f_s »

Service factor « f_s »						
Duty	Starts / hour	Accumulated operating hours (h)				
		≤ 5000	10000	15000	25000	50000
		Daily operating hours (h)				
	z	h < 4	4 < h < 8	8 < h < 12	12 < h < 16	16 < h < 24
Uniform load	Z < 10	1.10	1.10	1.15	1.30	1.60
	10 < Z < 30	1.10	1.15	1.30	1.50	1.80
	30 < Z < 100	1.10	1.25	1.45	1.60	2.00
Moderate shock load	Z < 10	1.10	1.25	1.45	1.60	2.00
	10 < Z < 30	1.10	1.40	1.60	1.80	2.20
	30 < Z < 100	1.20	1.50	1.70	2.00	2.40
Heavy shock load	Z < 10	1.20	1.50	1.70	2.00	2.40
	10 < Z < 30	1.30	1.60	1.80	2.10	2.60
	30 < Z < 100	1.40	1.75	2.00	2.30	2.80

A5 ORDERING NUMBERS

A5.1 DESIGNATION OF IN-LINE (300M L) AND RIGHT ANGLE (300M R) GEAR UNITS

3 | 11M | L | 2 | 16.7 | HZ

OUTPUT VERSION


MZ: Splined male shaft


MC: Solid keyed shaft


HZ: Heavy duty splined male shaft


HC: Heavy duty solid keyed shaft


PZ: Foot base with splined shaft


PC: Foot base with solid keyed shaft


FZ / FZB: Hollow splined shaft


VK: Reinforced output with heavy duty keyed shaft for stirrers and mixer


FP: Hollow shaft for shrink disc


FDK: Hollow shaft with double keyway


FZP: Hollow splined shaft with axial blockage device (recommended for shaft mounted installation)

GEAR RATIO
Fill in the value of the gear ratio (including point and decimals) as listed in the selection charts
Ex.: 1/44.6 = 44.6 1/131 = 131

REDUCTIONS
1 - 2 - 3 - 4

DESIGN
L = In line



R = Right angle



GEARBOX FRAME SIZE

00 = 300	**06** = 306	**11M** = 311M	**17M** = 317M	**23** = 323
01 = 301	**07** = 307	**13M** = 313M	**18M** = 318M	**25** = 325
03 = 303	**09** = 309	**15M** = 315M	**19** = 319	
05 = 305	**10M** = 310M	**16M** = 316M	**21** = 321	

SERIES



- **V11B** **A** **A** **W0A** **EX** **...**

OPTIONS

INPUT SHAFT PREFERENTIAL DIRECTION OF ROTATION
(applicable to angle gear units only)

RA = counterclockwise
RO = clockwise



CONFIGURATION COMPLIANT WITH THE OLD DIRECTIVE 94/9/EC AND AT THE NEW DIRECTIVE 2014/34/EU.

OUTPUT FITTINGS



P... = Pinions



B0A = Splined bar

M0A = Sleeve coupling



G0A = Shrink disc

W0A = Flange

MOTOR FLANGE ORIENTATION

MOUNTING POSITION

In mounting positions featuring a vertical output shaft, the gearbox will be equipped with an expansion tank.
Please request the installation drawing to Bonfiglioli's Technical Service.



INPUT

Input keyed shaft

	V01A	V01B	V05B	V06B	V07A	V07B	V10B	V11B	V15B
diam.	Ø24	Ø38	Ø48	Ø60	Ø60	Ø80	Ø80	Ø80	Ø120



Electric motor connection **P** + motor size (80,90,100,132,160, ...)



Hydraulic Motor connection
BONFIGLIOLI TECHNICAL SERVICE

ONLY WITH HYDRAULIC MOTOR ADAPTOR



Standard negative multidisc brake
6 = Type: **4, 5, 6**
A = Braking torque: **A, B, C, ...**

Negative multidisc brake for MG hydraulic motor
SF = Without brake



A6 DECLARATION OF CONFORMITY

The Declaration of Conformity, is the document which attests to the conformity of the product to Directive 2014/34/EU.
The validity of the Declaration is bound to observance of the instructions given in the User, Installation and Service Manual for safe use of the product throughout its service life.
This can be downloaded from www.bonfiglioli.com where the manual is available in PDF format in a number of languages.
The instructions regarding ambient conditions are of particular importance inasmuch as failure to observe them during operation of the product renders the certificate null and void. In case of doubt regarding the validity of the certificate of conformity, contact the BONFIGLIOLI RIDUTTORI technical department.





ELECTRIC MOTORS

M1 SYMBOLS AND UNITS OF MEASUREMENT

Symbols	Units of Measure	Description
$\cos\varphi$	–	Power factor
η	–	Efficiency
f_m	–	Power adjusting factor
I	–	Cyclic duration factor
I_N	[A]	Rated current
I_S	[A]	Locked rotor current
J_C	[Kgm^2]	Load moment of inertia
J_M	[Kgm^2]	Moment of inertia
K_c	–	Torque factor
K_d	–	Load factor
K_J	–	Inertia factor
M_A	[Nm]	Mean breakaway torque
M_B	[Nm]	Brake torque
M_N	[Nm]	Rated torque
M_L	[Nm]	Counter-torque during acceleration
M_S	[Nm]	Starting torque

Symbols	Units of Measure	Description
n	[min^{-1}]	Rated speed
P_B	[W]	Power drawn by the brake at 20°C
P_n	[kW]	Motor rated power
P_r	[kW]	Required power
t_1	[ms]	Brake response time with one-way rectifier
t_{1s}	[ms]	Brake response time with electronic-controlled rectifier
t_2	[ms]	Brake reaction time with a.c. disconnect
t_{2c}	[ms]	Brake reaction time with a.c. and d.c. disconnect
t_a	[°C]	Ambient temperature
t_f	[min]	Work time at constant load
t_r	[min]	Rest time
W	[J]	Braking work between service interval
W_{max}	[J]	Maximum brake work for each braking
Z	[1/h]	Permissible starting frequency, loaded
Z_0	[1/h]	Max. permissible unloaded starting frequency (I = 50%)

Efficiency classes and test methods

Efficiency classes characterise the efficiency with which an electric motor converts electrical energy into mechanical energy. In Europe, the energy efficiency of low voltage electric motors used to be classified using the voluntary Eff1/Eff2/Eff3 system. Outside Europe, other countries used to apply their own national systems, often very different to the European system. This uncertainty in standards led manufacturers to develop a harmonised international standard, and push for the issue of IEC (International Electrotechnical Commission) standard IEC 60034-30-1, “Efficiency classes of single-speed, three-phase, cage-induction motors (IE code)”.

This new standard:
- defines new classes of efficiency
- IE1 (standard efficiency)
- IE2 (high efficiency)
- IE3 (premium efficiency)
- provides a common, international reference system for the classification of electric motors
- and for national legislation
- introduces a new efficiency measurement method in conformity with standard IEC 60034-1-2:2007

The following table shows the correspondence among the main classes.





European Commission regulation 640/2009

IEC standard 60034-30-1 establishes technical guidelines for efficiency classification but does not impose any legal requirements for the adoption of any particular efficiency class. These are laid down by European Directives and national laws.

The EC Regulation applying Directive 2005/32/EC was adopted on the 22nd July 2009. This establishes the legal requirements and eco-compatible design criteria for electric motors, and imposes minimum efficiency limits according to the following schedule:

▪ **16/06/2011:** Electric motors must have a minimum efficiency level equivalent to class **IE2**

▪ **01/01/2015**: Electric motors with a rated power output between 7.5 kW and 375 kW must have a minimum efficiency level corresponding to **IE3**, or to **IE2** if controlled by an inverter.

▪ **01/01/2017:** Electric motors with a rated power output between 0.75 kW and 375 kW must have a minimum efficiency level corresponding to **IE3**, or to **IE2** if controlled by an inverter.

Scope and exclusions

EC Regulation 640/2009 applies to 2, 4, and 6 pole, single-speed, three-phase, 50 Hz or 60 Hz, cage-induction motors with rated outputs of 0.75 kW to 375 kW, and rated voltage up to 1000 V, designed for continuous duty (S1).

The regulation does not apply to:

- brakemotors
- motors designed to function immersed in liquid
- motors that are fully integrated in a product (like a gearbox, pump, fan), so that it is not possible
- to test the performance of the motor independently of that of the product.
- motors expressly designed to function:

▪ at altitudes above 4000 metres a.s.l.;

▪ in ambient temperatures above 60 °C;

▪ at maximum operating temperatures above 400 °C;

▪ in ambient temperatures below -30 °C (all motors) or below 0 °C (water-cooled motors);

▪ with incoming liquid coolants at temperatures below 0 °C or above 32 °C;

▪ in potentially explosive atmospheres as defined by Directive 2014/34/EU.



M3 GENERAL CHARACTERISTICS

M3.1 Production range

The asynchronous three-phase electric motors BXN, BX, BE, BN, MXN, MX, ME and M of BONFIGLIOLI RIDUTTORI's production, are available in basic design IMB5 and derived versions.
Motors are the enclosed type with outer fan and cage-tipe rotor for use in industrial environments.
Standard versions of BX-BE/MX-ME motors are 230/400V Δ/Y (400/690V Δ/Y in sizes BX-BE 160 and BX- BE 180), 50 Hz motors, with a tolerance of ±10%. Standard BN/M motors are designed to operate from a rated voltage 230/400V Δ/Y (400/690V Δ/Y for frame sizes BN 160 through BN 200) 50 Hz, with ±10% tolerance.
On the BXN/MXN motors, it is present a terminal box with 9 PIN connection + 12 wires winding that makes it easy to obtain the right voltage for most countries as standard. The Standard versions is identified as WD1 and makes it possible to obtain the following voltages/frequency (115/200/230/400V-50Hz and 132/230/265/460V-60Hz). For the BXN/MXN motors the voltage tolerance is reduced to ±5%.

M3.2 Standards

The motors described in this catalogue are manufactured to the applicable standards shown in the following table.

(F01)

Title	CEI	IEC
General requirements for rotating electrical machines	**CEI EN 60034-1**	**IEC 60034-1**
Terminal markings and direction of rotation of rotating machines	**CEI 2-8**	**IEC 60034-8**
Methods of cooling for electrical machines	**CEI EN 60034-6**	**IEC 60034-6**
Dimensions and output ratings for rotating electrical machines	**EN 50347**	**IEC 60072**
Classification of degree of protection provided by enclosures for rotating machines	**CEI EN 60034-5**	**IEC 60034-5**
Noise limits	**CEI EN 60034-9**	**IEC 60034-9**
Classification of type of construction and mounting arrangements	**CEI EN 60034-7**	**IEC 60034-7**
Rated voltage for low voltage mains power	**CEI 8-6**	**IEC 60038**
Vibration level of electric machines	**CEI EN 60034-14**	**IEC 60034-14**
Efficiency classes of single-speed, three-phase, cage-induction motors (IE code)	**CEI EN 60034-30-1**	**IEC 60034-30-1**
Standard method for determining losses and efficiency from tests	**CEI EN 60034-2-1**	**IEC 60034-2-1**

The motors also comply with foreign standards adapted to IEC 60034-1 as shown here below.

(F02)

DIN VDE 0530	Germany
BS5000 / BS4999	Great Britain
AS 1359	Australia
NBNC 51 - 101	Belgium
NEK - IEC 34	Norway
NF C 51	France
OEVE M 10	Austria
SEV 3009	Switzerland
NEN 3173	Netherlands
SS 426 01 01	Sweden

M3.3 Directives 2006/95/EC (LVD) and 2004/108/EC (EMC)

BXN, BX, BE, BN, MXN, MX, ME and M motors meet the requirements of Directives 2014/35/UE (LVD - Low Voltage Directive), the 2014/30/UE (EMC - Electromagnetic Compatibility Directive), the 2009/125/CE (ERP - Energy Related Products Directive) and 2011/65/UE (RoHS – Restriction of Hazardous Substances) and their nameplates bear the CE mark.
As for the EMC Directive, construction is in accordance with standards CEI EN 60034-1 (Rotating electrical machines Part 1: Rating and performance), CEI EN 61000-6-2 (Generic standards - Immunity for industrial environments), CEI EN 61000-6-4 (Generic standards - Emission standard for industrial environments).
Motors with FD brakes, when fitted with the suitable capacitive filter at rectifier input (option **CF**), meet the emission limits required by Standards CEI EN 61000-6-3 and CEI EN 60204-1.
The responsibility for final product safety and compliance with applicable directives rests with the manufacturer or the assembler who incorporate the motors as component parts.

UKCA mark as standard
In UK, the CE mark will be replaced by the UKCA (United Kingdom Conformity Assessed mark) mark, due to Brexit, starting from 1st January 2022. All Bonfiglioli motors are already compliant with UKCA requirements.

M3.4 EU Directive 2012/19/EU - Information on disposal

This product should not be mixed with general household waste. Disposal has to be carried out in conformity with EU Directive 2012/19/EU where established, and in accordance to national regulations.
Fulfill disposal in accordance with any other legislation in force throughout the country.

M3.5 Tolerances

As per the Norms CEI EN 60034-1, applicable the tolerances here below apply to the following quantities.

(F03)

-0.15 (1 - η) P ≤ 50kW	Efficiency
-(1 - cosφ)/6 min 0.02 max 0.07	Power factor
±20% *	Slip
+20%	Locked rotor current
-15% +25%	Locked rotor torque
-10%	Max. torque

(*) ± 30% for motors with Pn < 1 kW

M4 MOTOR DESIGNATION





MOTOR | BRAKE

BX 132SB 4 230/400-50 IP55 CLF B5 **W** **FD** 7.5 R AA SB SA 220 .....

OPTIONS

BRAKE SUPPLY

RECTIFIER TYPE
AC/DC
NB, **SB, NBR, SBR**

RELEASE LEVER ORIENTATION
AA, AB (standard)**, AC, AD**

BRAKE HAND RELEASE
R, RM

BRAKE TORQUE

BRAKE TYPE
FD (d.c. brake)
FA (a.c. brake)

TERMINAL BOX POSITION
(compact motor only)
W (default), **N**, **E**, **S**

MOTOR MOUNTING
− compact motor
IM B5 - IEC motor

INSULATION CLASS
CL F standard
CL H option

DEGREE OF PROTECTION
IP55 standard (IP56 - option)
IP54, **IP55** brake motor

VOLTAGE - FREQUENCY
(See Paragraph M7.1)

POLE NUMBER
4

MOTOR SIZE
80B ... 355 (IEC motor)
2SB ... 5LA (compact motor)

MOTOR TYPE
BX = IEC 3-phase, class IE3 **MX** = compact 3-phase, class IE3



MOTORE BRAKE

BE 90LA 4 230/400-50 IP55 CLF B5 **W** **FD** 7.5 R AA SB SA 220 .....

OPTIONS

BRAKE SUPPLY

RECTIFIER TYPE
AC/DC
NB, **SB, NBR, SBR**

RELEASE LEVER ORIENTATION
AA, AB (standard)**, AC, AD**

BRAKE HAND RELEASE
R, RM

BRAKE TORQUE

BRAKE TYPE
FD (d.c. brake)
FA (a.c. brake)

TERMINAL BOX POSITION
(compact motor only)
W (default), **N**, **E**, **S**

MOTOR MOUNTING
− compact motor
IM B5 - IEC motor

INSULATION CLASS
CL F standard
CL H option

DEGREE OF PROTECTION
IP55 standard (IP56 - option)
IP54, **IP55** brake motor

VOLTAGE - FREQUENCY
(See Paragraph M7.1)

POLE NUMBER
2, **4**, **6**

MOTOR SIZE
63A ... 180L (IEC motor)
05A ... 5L (compact motor)

MOTOR TYPE
BE = IEC 3-phase, class IE2 **ME** = compact 3-phase, class IE2



MOTOR | BRAKE

BN 90LA 4 230/400-50 IP55 CLF B5 **W** **FD** 7.5 R AA SB SA 220 .....

OPTIONS

BRAKE SUPPLY

RECTIFIER TYPE
AC/DC
NB, **SB, NBR, SBR**

RELEASE LEVER ORIENTATION
AA, AB (standard)**, AC, AD**

BRAKE HAND RELEASE
R, RM

BRAKE TORQUE

BRAKE TYPE
FD (d.c. brake)
FA (a.c. brake)

TERMINAL BOX POSITION
(compact motor only)
W (default), **N**, **E**, **S**

MOTOR MOUNTING
− compact motor
IM B5 - IEC motor

INSULATION CLASS
CL F standard
CL H option

DEGREE OF PROTECTION
IP55 standard (IP56 - option)
IP54, **IP55** brake motor

VOLTAGE - FREQUENCY
(See Paragraph M7.1)

POLE NUMBER
2, **4**, **6**, **2/4**, **2/6**, **2/8**, **2/12**, **4/6**, **4/8**

MOTOR SIZE
56A ... 200LA (IEC motor)
0B ... 5SB (compact motor)

MOTOR TYPE
BN = IEC 3-phase **M** = IEC compact 3-phase



M5 VARIANTS AND OPTIONS

M5.1 Variants

(F04)

Description		Default	Option	Page
Voltage (BN - BE - BX) ≤ 132		230/400/50		528
Voltage (BN - BE - BX) ≥ 160		400/690/50		
Voltage (BXN)		WD1		EVOX*
Protection class	BXN - BX - BE - BN - MXN - MX - ME - M	IP 55	IP 56	524
	BXN - BX - BE - BN/FA-FD MXN - MX - ME - M/FA-FD	IP 54	IP 55	
	BX_FD ≥ 200	IP 55		
	BX...K - BX... K_FDK	IP 55	IP 56	
Insulation class		CLF	CLH	535
Design version	BX - BE - BN	**B5** **B5 R**		523
	BXN	**B5**		EVOX*

Default values. * See EVOX specific catalogue

M5.2 Options

(F05)

Description	Catalogue numbers								Availability	Page
Thermal protective devices	**D3**	**K1**	**E3**	**PT1000°°**					BXN- BX - BE - BN - MXN- MX - ME - M	554
50 Hz normalized power	**PN**								BN - M	531
Feedback devices	**EN1**	**EN2**	**EN3**	**EN4**	**EN5**	**EN6**	**EN7***	**EN8***	BXN- BX - BE - BN - MX - ME - M	562-564
Anti-condensate heaters	**H1**	**NH1**							BXN- BX - BE - BN - MXN- MX - ME - M	557
Tropicalized windings	**TP**								BXN- BX - BE - BN - MXN- MX - ME - M	558
Double-extended shaft	**PS**								BXN- BX - BE - BN - MXN- MX - ME - M	558
Rotor balancing grade B	**RV**								BX - BE - BN MX - ME - M	559
External mechanical protections	**RC**	**TC*****	**EC°°**						BXN- BX - BE - BN - MXN- MX - ME - M	561
Forced ventilation	**U1**	**U2****							BX - BE - BN MX - ME - M	560
Insulated Bearings	**IB***								BX - MX	564
Certification CSA/UL	**CUS°**								BXN- BX - BE - BN - MXN- MX - ME - M	532
Bureau of Indian Standard Certification	**BIS**								BE - ME	533
China Compulsory Certification	**CCC**								BX - BE - BN MX - ME - M	533
China Energy Label	**CEL**								BX - MX	534
NBR Certification	**NBR**								BX - MX	534
EECA Ceertification	**EECA**								BX - MX	535
Plug connector	**CON**								BX - BE - BN MX - ME - M	554
Surface protection	**C_**								BXN- BX - BE - BN - MXN- MX - ME - M	565
Painting	**RAL**								BXN- BX - BE - BN - MXN- MX - ME - M	566
Certificates	**ACM**								BXN- BX - BE - BN - MXN- MX - ME - M	566
Inspection certificate	**CC**								BXN- BX - BE - BN - MXN- MX - ME - M	566
Vertical Mounting	**VM***								BX - MX	567
Backstop device	**AL**	**AR**							MX - ME - M	559
Type of duty	**S2**	**S3**	**S9**						BN - M	536
	S2-10	**S2-30**	**S2-60**	**S3=25%**	**S3=40%**		**S3=70%**		BXN - MXN	

*Only for BX ≥ 280 and BX ≥ 280K ** Only for motors BN *** Not for motors BX - MX

° Standard on BXN/MXN not an option °° Only for motors BXN/MXN



M5.3 Brake-related options

(F06)

Description	Catalogue numbers				Availability	Page
Brake torque	Refer to the specific brake type					545-548
Manual release lever	**R**	**RM**			BXN - BX - BE - BN MXN - MX - ME - M	551
Release lever orientation	**AB**	**AA**	**AC**	**AD**	BXN - BX - BE - BN MXN - MX - ME - M	552
DC brake rectifier	**NB**	**NBR°**	**SB**	**SBR°**	BXN - BX - BE - BN MXN - MX - ME - M	543
Soft-start flywheel	**F1**				BE - BN ME - M	553
Capacitive filter	**CF**				BXN - BX - BE - BN MXN - MX - ME - M	553
Brake separate power supply (*)	**...SA**	**...SD**	**DIR°°**		BXN - BX - BE - BN MXN - MX - ME - M	552
Brake functionality check	**MSW**				BX - BE - BN MX - ME - M	557
Additional cable entry for brake motors	**IC**				BN M	557

(*) Specify voltage. (°) Not for BXN/MXN (°°) Only for BXN/MXN - means "without separate power supply"

Default values.

M5.4 Example of identification nameplate for legacy motors (BX - BE - BN)



① BONFIGLIOLI Motor type
② Serial number
③ Rated voltage
④ Motor code
⑤ Type of duty: S1 Continuous duty
⑥ IE Class, Efficiency at: 4/4 - 3/4 - 2/4 load

M5.4.1 Example of identification nameplate for EVOX motors (BXN)



① Motor designation and general information
② Serial codes
③ Environment & application compliancy
④ Rated performances function of voltages/frequencies
⑤ Motor performances @ 50 Hz
⑥ Motor performances @ 60 Hz
⑦ Thermal protection and Servo ventilation information
⑧ Brake information
⑨ Certifications
⑩ Manufactory information

M6 MECHANICAL FEATURES

M6.1 Versions

EC-normalised BXN, BX, BE and BN motors are available in the design versions as indicated in the table below here after as per Standards EN 60034-7 (BX/BE), CEI EN 60034-14 (BN).
Mounting versions are:
IM B5 (basic)
IM V1, IM V3 (derived)

IM B5 design motors can be installed in positions IM V1 and IM V3; in such cases, the basic design IM B5 is indicated on the motor name plate.
In design versions with a vertically located motor and shaft downwards, it is recommended to request the drip cover (always necessary for brake motors). This facility, included in the option list should be specified when ordering as it does not come as a standard device

(F07)





For Motor BX≥200 and BX≥200K it is necessary to select VM options when vertically mounted.

If the motor will be mounted with DE facing downwards, selection of RC option is recommended. This has to be specified during the ordering phase because not present in standard motor version.

Flange output motors are also available with reduced coupling dimensions, as indicated in the table below - executions **B5R**. Their use in combination with gearboxes must be however coherent with the maximum installable power on gearboxes themselves (see chapters “Motors availability”). In case this condition is not met need to contact the Technical Service for the checking of the combination.

(F08)



	BN/BE 71	BX/BE/BN 80	BX/BE/BN 90	BX/BE/BN 100	BX/BE/BN 112	BX/BE/BN 132
	DxE - Ø					
B5R(1)	11x23 - 140	14x30 - 160	19x40 - 200	24x50 - 200	24x50 - 200	28x60 - 250

(1) flange with through holes

M6.2 Degree of protection

IP..

The following chart provides an overview of the degrees of protection available.
In addition to the degree of protection specified when ordering, motors to be installed outdoors require protection against direct sunlight and also – when they are to be installed vertically down – a drip cover to prevent the ingress of water and solid particles (option **RC**).

(F09)

		IP 54	IP 55	IP 56
BXN- BX-BE-BN	**MXN-MX-ME-M**	⛔	standard	on request
BXN-BX-BE-BN/ FD*-FA	**MXN-MX-ME-M/ FD-FA**	standard	on request	⛔
BX ≥ 200_FD BX ≥ 200K_FD		⛔	standard	⛔
BX ≥ 280K_FD		⛔	standard	on request

(*) BX ≤ 180_FD

IP	5	5

0		Not protected
1		Protected against extraneous solid bodies having Ø ≥ 50 mm
2		Protected against extraneous solid bodies having Ø ≥ 12.5 mm
3		Protected against extraneous solid bodies having Ø ≥ 2.5 mm
4		Protected against extraneous solid bodies having Ø ≥ 1.0 mm
5		Protected against dust
6		No dust ingress

0		Not protected
1		Protected against vertical water drips
2		Protected against vertical water drips inclined up to 15°
3		Protected against rain
4		Protected against water splashes
5		Protected against jets of water
6		Protected against powerful jets of water
7		Protected against the effects of temporary immersion
8		Protected against the effects of continuous immersion

M6.3 Cooling

The motors are externally ventilated (IC 411 to CEI EN 60034-6) and are equipped with a plastic fan working in both directions.
The motors must be installed allowing sufficient space between fan cowl and the nearest wall to ensure free air intake and allow access for maintenance purposes on motor and brake, if supplied.
Independent, forced air ventilation (IC 416) can be supplied on request (option **U1**).
This solution enables to increase the motor duty factor when driven by an inverter and operating at reduced speed.

M6.4 Direction of rotation

Rotation is possible in both directions. If terminals U1, V1 and W1 are connected to line phases L1,L2 and L3, clockwise rotation (looking from drive end) is obtained. For counterclockwise rotation, switch two phases.

M6.5 Noise

Noise levels, measured using the method prescribed by ISO 1680 Standards, are within the maximum levels specified by Standards CEI EN 60034-9.



M6.6 Vibrations and balancing

Rotor shafts are balanced with half key fitted and fall within the vibration class N, as per Standard CEI EN 60034-14.

M6.7 Terminal box

Legacy motors (BN/M - BE/ME - BX/MX) terminal board features 6 studs for eyelet terminal connection while EVOX BXN and MXN motors have always 9 studs as standard.
When a legacy motor have UL option active the terminal board features 9 studs execution (for US voltage “Dual Voltage”). A ground terminal is also supplied for earthing of the equipment. Terminals number and type are shown in the following table. For brake power supply, please read par. M9 (brake FD), M10 (brake FA). Brakemotors house the a.c./d.c. rectifier (factory pre-wired) inside the terminal box.
Wiring instructions are provided either in the box or in the user manual.

(F10)

		No. of terminals	Terminal threads
BXN 63 ... BXN 90	**MXN05 ... MXN25**	9	M4
BX 80, BX 90 **BE 63 ... BE 90** **BN 56 ... BN 90**	**MX2, MX3** **ME05 ... ME3** **M05 ... M2**	6	M4
BX 100 ... BX 132 **BE 100 ... BE 132** **BN 100 ... BN 160MR**	**MX3, MX4** **ME3, ME4** **M3 ... M4**	6	M5
BX 160 - BE 160 ... BE 180M **BN 160M ... BN 180M**	**ME5** **MX5 - M5**	6	M6
BX 180 - BE 180L **BN 180L ... BN 200L**	**–** **–**	6	M8
BX 200 ... BX 250 **BX 200K ... BX 250K**	**–** **–**	6	M10
BX 280 ... BX 355 **BX 280K ... BX 355K**	**–** **–**	6	M12
BX 80 ... BX 132 **BE 71 ... BE 132** **BN 63 ... BN 160MR**	**MX2 ... MX4** **ME2 ... ME4** **M05 ... M4**	9	M4
BX 160 ... BX 180 **BE 160 ... BE 180** **BN 160M ... BN 200L**	**MX5** **ME5** **M5**	9	M6

M6.8 Cable entry

The holes used to bring cables to terminal boxes use metric threads in accordance with standard EN 50262 as indicated in the table here after.

(F11)

		Cable gland and dimensions		Maximum cable diameter allowed [mm]
BXN 63	**MXN 05**	2 x M20 x 1.5	1+1 Hole on each side	13
		2 x M16 x 1.5		11
BXN 71 ... BXN 90	**MXN 10 ... MXN 25**	2 x M25 x 1.5		17
		2 x M16 x 1.5		11
BN 63 - BE 63	**M05 - ME05**	2 x M20 x 1.5	1 Hole on each side	13
BN71 ... BN90, BE71 ... BE90, BX80 ... BX90	**M1 - M2, ME1 - ME2, MX2**	2 x M25 x 1.5		17
BN100 - BN112, BE100 - BE112, BX100 - BX112	**MX3, MX4 - ME3 M3**	2 x M32 x 1.5	2 Holes on each side	21
		2 x M25 x 1.5		17
BN132 ... BN160MR, BE132, BX132	**M4, ME4, MX4**	4 x M32 x 1.5		21
BN160M ... BN200L, BE160 - BE180, BX160 - BX180	**M5, ME5, MX5**	2 x M40 x 1.5	Pivoting, 4 x 90°	28
BX 200 ... BX 355 BX 200K ... BX 355K	**–**	2 x M63 x 1.5	Pivoting, 4 x 90°	45

M6.9 Bearings

Life lubricated preloaded radial ball bearings are used, types are shown in the chart here under.
Calculated endurance lifetime L_{10h}, as per ISO 281, in unloaded condition, exceeds 40000 hrs.
DE = drive end
NDE = non drive end

(F12)

	DE	NDE	
		Without Brake	With Brake
MXN 05 - ME05 - M05	6004 2Z C3	6201 2Z C3	6201 2RS C3
MXN 10 - ME1 - M1	6004 2Z C3	6202 2Z C3	6202 2RS C3
MXN 20 - MX2 - ME2 - M2	6007 2Z C3	6204 2Z C3	6204 2RS C3
MXN 25 - MX3 - ME3 - M3	6207 2Z C3	6206 2Z C3	6206 2RS C3
MX4 - ME4 - M4	6309 2Z C3	6308 2Z C3	6308 2RS C3
MX5 - ME5 - M5	6309 2Z C3	6309 2Z C3	6309 2RS C3

	DE	NDE	
		Without Brake	With Brake
BN 56	6201 2Z C3	6201 2Z C3	–
BXN 63 - BE 63 BN 63	6201 2Z C3	6201 2Z C3	6201 2RS C3
BXN 71 - BE 71 BN 71	6202 2Z C3	6202 2Z C3	6202 2RS C3
BXN 80 - BX 80 BE 80 - BN 80	6204 2Z C3	6204 2Z C3	6204 2RS C3
BXN 90 - BX 90 BE 90 - BN 90	6205 2Z C3	6205 2Z C3	6305 2RS C3
BX 100 - BE 100 - BN 100	6206 2Z C3	6206 2Z C3	6206 2RS C3
BX 112 - BE 112 - BN 112	6306 2Z C3	6306 2Z C3	6306 2RS C3
BX 132 - BE 132 - BN 132	6308 2Z C3	6308 2Z C3	6308 2RS C3
BN 160MR	6309 2Z C3	6308 2Z C3	6308 2RS C3
BX 160M/L - BE 160M/L - BN 160M/L	6309 2Z C3	6309 2Z C3	6309 2RS C3
BN 180M	6310 2Z C3	6309 2Z C3	6309 2RS C3
BX 180M/L - BE 180M/L - BN 180L	6310 2Z C3	6310 2Z C3	6310 2RS C3

	DE	NDE	
		Without Brake	With Brake
BN 200L - BX 200 - BX 200K	6312 2Z C3 6312/C3	6310 2Z C3 6210/C3*	6310 2RS C3
BX 225 - BX 225K	6313/C3*	6212/C3*	-
BX 250 - BX 250K	6315/C3*	6213/C3*	-
BX 280 - BX 280K	6316/C3*	6316/C3*	-
BX 315 - BX 315K	6319/C3**	6316/C3**	-
BX 355 - BX 355K	6322/C3**	6316/C3**	-

*Regreasable bearings with M6x1 Greasing Device
**Regreasable bearings with M10x1 Greasing Device
Note: BX and BXN motors have high efficiency bearings



M7 ELECTRICAL CHARACTERISTICS

M7.1 Voltage

Single speed motors are provided in standard execution either for nominal voltage 230 / 400 V Δ/Y, 50 Hz, or 400 / 690 V Δ/Y, 50 Hz, with a voltage tolerance of ± 10%.
Note: Motor nominal voltage/frequency also depends on the selection of options related to energy certifications for specific markets. Table below, then, has to be intended only as a guideline, for more details on the available Voltages/Frequencies as a function of the selected certification, please refer to paragraph M7.5 - M7.10.

On all the motors, whose voltage / frequency configuration is not as indicated above, the voltage tolerance is reduced down to ± 5%.
For the operation out of the tolerance boundaries, the temperature may exceed by 10 K the limit provided by the adopted insulation class.
The motors are suitable for operation on distribution European grid with voltage complying with the pubblication IEC 60038.

(F13)

BN - M motor power supply voltages (IE1)

Single speed motors at 50Hz

Motor power supply voltage	— (CE)		CCC	CUS
	STD	FD / FA		
220/380 - 50	✗	✓	✗	✓
230/400 - 50	✓	✓	✓	✓
240/415 - 50	✗	✓	✗	✓
290/500 - 50	✓	✓	✗	✓
380/660 - 50	✗	✓	✗	✓
400/690 - 50	✓	✓	✗	✓
415/720 - 50	✗	✓	✗	✓
500/865 - 50	✓	✓	✗	✓

Double speed motors at 50Hz

Motor power supply voltage	— (CE)	CCC	CUS
380 - 50	✓	✗	✓
400 - 50	✓	✓	✓
415 - 50	✓	✗	✓
500 - 50	✓	✗	✓

Single speed motors at 60Hz

Motor power supply voltage	— (CE)		CCC	CUS
	STD	FD / FA		
208/360 - 60	✓	✓	✗	✓
220/380 - 60	✓	✓	✗	✓
230/400 - 60	✓	✓	✗	✓
255/440 - 60	✗	✓	✗	✓
265/460 - 60	✗	✓	✓	✓
280/480 - 60	✗	✓	✗	✓
330/575 - 60	✓	✓	✗	✓
380/660 - 60	✓	✓	✗	✓
400/690 - 60	✓	✓	✗	✓
440/760 - 60	✗	✓	✗	✓
460/800 - 60	✗	✓	✗	✓
480/830 - 60	✗	✓	✗	✓
575/995 - 60	✓	✓	✗	✓
220/440 - 60	✓	✓	✗	✓
230/460 - 60	✓	✓	✗	✓
240/480 - 60	✓	✓	✗	✓

Double speed motors at 60Hz

Motor power supply voltage	— (CE)	CCC	CUS
208 - 60	✓	✗	✓
220 - 60	✓	✗	✓
230 - 60	✓	✗	✓
240 - 60	✓	✗	✓
380 - 60	✓	✗	✓
400 - 60	✓	✗	✓
440 - 60	✓	✗	✓
460 - 60	✓	✗	✓
480 - 60	✓	✗	✓
575 - 60	✓	✗	✓



(F14)

BE - ME motor power supply voltages (IE2)

Single speed motors at 50Hz

Motor power supply voltage	— (CE)	CCC	BIS	CUS
220/380 - 50	✓	✗	✓	✓
230/400 - 50	✓	✓	✓	✓
240/415 - 50	✓	✗	✓	✓
290/500 - 50	✓	✗	✓	✓
380/660 - 50	✓	✗	✓	✓
400/690 - 50	✓	✗	✓	✓
415/720 - 50	✓	✗	✓	✓
500/865 - 50	✓	✗	✓	✓

Single speed motors at 60Hz

Motor power supply voltage	— (CE) STD	— (CE) FD / FA	CCC	BIS	CUS
208/360 - 60	✓	✓	✗	✗	✓
220/380 - 60	✓	✓	✗	✗	✓
230/400 - 60	✓	✓	✗	✗	✓
255/440 - 60	✓	✓	✗	✗	✓
265/460 - 60	✗	✓	✗	✗	✓
280/480 - 60	✓	✓	✗	✗	✓
330/575 - 60	✗	✓	✗	✗	✓
380/660 - 60	✓	✓	✗	✗	✓
400/690 - 60	✓	✓	✗	✗	✓
440/760 - 60	✓	✓	✗	✗	✓
460/800 - 60	✗	✓	✗	✗	✓
480/830 - 60	✓	✓	✗	✗	✓
575/995 - 60	✓	✓	✗	✗	✓
220/440 - 60	✓	✓	✗	✗	✓
230/460 - 60	✓	✓	✗	✗	✓
240/480 - 60	✓	✓	✗	✗	✓

BX - MX motor power supply voltages (IE3)

Single speed motors at 50Hz

Motor power supply voltage	— (CE)	CCC	CEL	NBR	BIS	CUS
230/400-50	✓ (1)	✗	✓ (6)	✗	✗	✗
290/500-50	✓	✗	✗	✗	✗	✗
380/660-50	✗	✗	✓ (4)	✗	✗	✗
400/690-50	✓ (2)	✗	✓ (2) (3)	✗	✗	✗

Single speed motors at 60Hz

Motor power supply voltage	— (CE) STD	— (CE) FD / FA	CCC	CEL	NBR (*)	BIS	CUS
220/380-60	✗	✗	✗	✗	✓ (3)	✗	✓
265/460-60	✗	✓ (1)	✗	✗	✗	✗	✓
330/575-60	✗	✓ (3)	✗	✗	✗	✗	✓
380/660-60	✗	✗	✗	✗	✓ (5)	✗	✓
440/760-60	✗	✗	✗	✗	✓ (4)	✗	✓
460/800-60	✗	✓ (2) (3)	✗	✗	✗	✗	✓
220/440-60	✗	✗	✗	✗	✓ (3)	✗	✓
230/460-60	✗	✗	✗	✗	✗	✗	✓

(1) only for motor size ≤132
(2) only for motor size ≥160
(3) only for motor size ≤180
(4) only for motor size ≥200
(5) only for motor size 180
(6) only for motor size ≥100



The table below shows the wiring options available.

(F15)

Number of poles			Winding connection
2	**BE 80 … BE 160, BN 63 … BN 200**	**ME2 ... ME5, M05 ... M5**	Δ / Y (²)
4	**BXN 63 ... BXN 90, BX 80 ... BX 355** **BX 200LAK ... BX 355MCK** **BE 63 … BE 180, BN 56 … BN 200**	**MXN05 ... MXN25 , MX2 ... MX5** **—** **ME05 ... ME5, M05 ... M5**	
6	**BE 90 … BE 160, BN 63 … BN 200**	**ME3 ... ME5, M05 ... M5**	
8	**BN 71 … BN 132**	**M1 ... M4**	
2/4	**BN 63 … BN 132**	**M05 ... M4**	Δ / YY (Dahlander)
2/6	**BN 71 … BN 132**	**M1 ... M4**	Y / Y (Two windings)
2/8	**BN 71 … BN 132**	**M1 ... M4**	
2/12	**BN 80 … BN 132**	**M2 ... M4**	
4/6	**BN 71 … BN 132**	**M1 ... M4**	
4/8	**BN 80 … BN 132**	**M2 ... M4**	Δ / YY (Dahlander)

(²) Motors with voltage in ratio 2 (ex. 230/460 - 60) will be equipped with a 9 pin terminal box with winding connection either Δ Δ/ Δ or YY / Y (except 6 pole BN 63 Δ / Y)

NOTE: For BXN and MXN motors refer to EVOX specific catalogue

M7.2 Frequency

Rated output power BN / M for 60 Hz operation is shown in the following diagram.

(F16)

		P_n [kW]			
		2P	**4P**	**6P**	**8P (*)**
BN 56A	**–**	–	0.07	–	–
BN 56B	**M0B**	–	0.1	–	–
BN 63A	**M05A**	0.21	0.14	0.1	–
BN 63B	**M05B**	0.3	0.21	0.14	–
BN 63C	**M05C**	0.45	0.3	–	–
BN 71A	**–**	0.45	0.3	0.21	0.1
–	**M1SC**	–	–	0.21	–
BN 71B	**M05SD**	0.65	0.45	0.3	0.14
BN 71C	**M1LA**	0.9	0.65	0.45	–
BN 80A	**–**	0.9	0.65	0.45	0.21
BN 80B	**M2SA**	1.3	0.9	0.65	0.30
BN 80C	**M2SB**	1.8	1.3	0.9	–
BN 90S		–	1.3	0.9	0.45
BN 90SA	**–**	1.8	–	–	–
BN 90SB		2.2	–	–	–
BN 90L	**M3SA**	2.5	–	1.3	0.65
BN 90LA		–	1.8	–	–
BN 90LB	**–**	–	2.2	–	–

		P_n [kW]			
		2P	**4P**	**6P**	**8P (*)**
BN 100L	**M3LA**	3.5	–	–	–
BN 100LA		–	2.5	1.8	0.9
BN 100LB	**M3LB**	4.7	3.5	2.2	1.3
BN 112M	**–**	4.7	4.7	2.5	1.8
–	**M3LC**	–	4.7	2.5	–
BN 132S	**M4SA**	–	6.5	3.5	2.5
BN 132SA		6.5	–	–	–
BN 132SB	**M4SB**	8.7	–	–	–
BN 132M	**M4LA**	11	–	–	3.5
BN 132MA		–	8.7	4.7	–
BN 132MB	**M4LB**	–	11	6.5	–
BN 160MR	**M4LC**	12.5	12.5	–	–
BN 160M	**M5SA**	–	–	8.7	–
BN 160MB	**–**	17.5	–	–	–
–	**M5SB**	17.5	17.5	–	–
BN 160L	**–**	21.5	17.5	12.5	–
–	**M5SC**	21.5	–	–	–
BN 180M	**M5LA**	24.5	21.5	–	–
BN 180L	**–**	–	25.3	17.5	–
BN 200L	**–**	–	34	–	–
BN 200LA	**–**	34	–	22	–

(*) Excluded M_ motors



BXN / BX / BE / MXN / MX / ME motors are available at 60 Hz on a 4 pole configuration only, and their power rating is the same as their 50 Hz counterpart. Double speed BN / M motors supplied at 60 Hz will have an increase of nominal power, referred to 50 Hz, equal to 15%, whereas double speed BXN / BX / BE / MXN / MX / ME motors are not available. If a nominal power rating, equal to the normalised nominal power rating at 50 Hz, was requested to be on a nameplate of a motor meant to be voltage supplied at 60 Hz, the PN option shall be specified on the motor designation. Motors normally designed for a 50 Hz frequency may be used on a 60 Hz operating grid, but the related data shall be updated according to the following table. Motors designated for 50 Hz operation show on the nameplate also the values for 60 Hz operation (excluding motors in CUS execution and brake motors). See the following table.

(F17)

	50 Hz	**60 Hz**			
	V - 50 Hz	**V** - 60 Hz	**Pn** - 60 Hz	$\mathbf{M_n}$, $\mathbf{M_a/M_n}$ - 60 Hz	**n** [min^{-1}] - 60 Hz
BXN / MXN BX / MX BE / ME	**230/400 Δ/Y**	265 - 460 Δ Y	1	0.83	1.2
	400/690 Δ/Y	460 Δ			
BN / M	**230/400 Δ/Y**	220 - 240 Δ			
		380 - 415 Y			
	400/690 Δ/Y	380 - 415 Δ			
BN / M	**230/400 Δ/Y**	265 - 280 Δ	1.15	1	1.2
		440 - 480 Y			
	400/690 Δ/Y	440 - 480 Δ			

NOTE: For BXN and MXN motors refer to EVOX specific catalogue

M7.3 Ambient temperature

Catalogue rating values are calculated for 50 Hz operation and for standard ambient conditions (temperature 40 °C; elevation ≤ 1000 m a.s.l.) as per the CEI EN 60034-1 Standards.
The motors can be used within the 40 - 60 °C temperature range with rated power output adjusted by factors given in the table below.

(F18)

Ambient temperature (°C)	40°	45°	50°	55°	60°
Permitted power as a % of rated power	100%	95%	90%	85%	80%

Should a derating factor higher than 15% apply please consult factory.

M7.4 50 HZ normalized power

PN

With this option, motor name plate includes 50 Hz normalized power information even when motor is designated for operation with 60 Hz power mains. For 60 Hz supplies along with voltages 230/460V and 575V the PN option is applied by default.

M7.5 Motors for USA and Canada

CUS

CUS option is available in NEMA Design C execution for BN, BE, M, ME motors, and NEMA Design B for BX motors, with regards to the electrical features. The BXN and MXN motors are CUS certified as standard. Motors are certified in compliance with CSA (Canadian Standard) C22.2 N° 100 and UL (Underwriters Laboratory) UL 1004-1 standards, as stated on UL file E308649.
All powers BN-BE-M-ME and BXN-MXN with powers between 0,12 and 0,55kW included motors nameplates show the below marks:

BXN/MXN >= 0,75kW and BX/MX >= 0,75kW motors nameplates show the below marks and are certified in compliance with the energy efficiency standards in effect in the USA and Canada, respectively provided by DOE (10 CFR Part 431) and NRCan (Energy Efficiency Regulations), tested according to CSA C390 standard.

BX 100 motors are available for the USA only and not for Canada, and the related marks reported on the nameplates are the following:

BX≥200K motors shows on nameplate the logo reported below and are compliant to energy efficiency regulations of USA and Canada, respectively established from DOE (10 CFR Part 431) and from NRCan (Energy Efficiency Regulations), and tested in accordance to CSA C390.

NOTES:
Starting from **June, 1st 2016**, CUS motors whose efficiency is below IE3 (i.e. “Premium Efficiency”) cannot be any longer sold in the USA and Canada, unless one or more of the following conditions apply:

- Double speed motors;
- Motors plated for a non - continuous duty (<80%);
- Motors intended to be operated through variable frequency drive only (properly equipped with “Inverter Duty Only” label, or similar).

CUS option is selectable in combination to U1 or U2 only for BX≥200K.
US power mains voltages and the corresponding rated voltages to be specified for the motor are indicated in the following table:

(F19)

Frequency	Mains voltage	V_{mot}
60 Hz	208 V	**200 V**
	240 V	**230 V**
	480 V	**460 V**
	600 V	**575 V**

BX motor with CUS option are available with the following nominal Voltage/Frequency combinations:

(F20)

	V_{mot}
BX ≤ 132	265/460 - 60 Hz
BX ≤ 180	230/460 - 60 Hz 330/575 - 60 Hz
BX ≥ 160 BX ≥ 200K	460/800 - 60 Hz

CUS option is applicable onto 50 Hz operating motors as well (motors BX, MX excluded).

M7.6 Motors certified for India

BIS

Low voltage motors ≥0.12kW manufactured or imported in India must be certified from Bureau of Indian Standard and provided with a mark certifying motor compliance to IS 12615 standard.
BE - ME motors with power up to 3.7kW included, are avaiable with the above mentioned certification and, when BIS option is selected, are provided with the nameplate reporting the following logo:

M7.7 China Compulsory Certification

CCC

Electric motors destined for sale in the People's Republic of China have to be certified under the CCC (China Compulsory Certification) system. BN/M and BE/ME motors of up to 7 Nm in rated torque are available with CCC certification and a special nameplate bearing the mark shown below:

CCC option is not currently available for IE3 motors and will be available starting from end 2021.
CCC option is not currently available for servo - ventilated motors.

M7.8 Motor certified for China (China Energy Label)

CEL

Low voltage motors ≥0.75kW manufactured or imported in China must be certified and registered by the label office and provided with an energy label certifying they meet the energy efficiency levels as defined in GB18613-2012.
BX motors with power from 30 to 355kW included are available with the above mentioned certification and, when CEL option is selected, are provided with the following sticker applyed to the motor:



BX motors with CEL option are available with the following nominal Voltage/Frequency combinations:

(F21)

	V_{mot}
BX ≥ 200	380/660 - 50 Hz

M7.9 Motors certified for Brazil

NBR

Brazilan laws regulamentates the manufacturing and importation of electric motor in the country. These have to be approved by NBR trough a declaration of the motor efficiency level at INMETRO. Motor compliant to NBR must report the declared efficiency value and have to be provided with a specific NBR nameplate and the additional mark shown in picture below.

The NBR option is available for motors:
- BX with powers from 0.75 to 22 kW included
- BX… K with powers from 30 to 355 kW included

BX motors with NBR option are available with the following nominal Voltage/Frequency combinations:

(F22)

	V_{mot}
BX90SR ... BX160	220/380 - 60 Hz 220/440 - 60 Hz
BX 180	220/380 - 60 Hz 220/440 - 60 Hz 380/660 - 60 Hz
BX ≥ 200K	440/760 - 60 HZ

M7.10 Motors certified for Australia

EECA

Electric motor covered by Australian/NewZeland's energy regulation must be listed in the national database Energyratig. Mootr with EECA option are registered in the previously mentioned database and can be sold in Australia and New Zeland.
EECA option is available for BX ... K motor with power from 30 to 355kW included.

BX motors with EECA option are available with the following nominal Voltage/Frequency combinations:

(F23)

	V_{mot}
BX ≥ 200K	400/690 - 50 Hz

M7.11 Insulation class

CL F

Bonfiglioli motors use class **F** insulating materials (enamelled wire, insulators, impregnation resins) as compare to the standard motor. In standard motors, stator windings over temperature normally stays below the 80 K limit corresponding to class B over temperature. A careful selection of insulating components makes the motors compatible with tropical climates and normal vibration. For applications involving the presence of aggressive chemicals or high humidity, contact Bonfiglioli Engineering for assistance with product selection.

CL H

Motors manufactured in insulation class **H** are available at request.
This option can be selected for motors compliant with CSA and UL standards (CUS option), only for BX≥200 and BX≥200K.
CLH can't be selected on BXN motors because are CUS standard. If necessary contact technical office.

(F25)



M7.12 Type of duty

Unless otherwise specified, catalogue motor power refers to continuous duty S1. Any operating conditions other than S1 duty must be identified in accordance with duty cycle definitions laid down in standards CEI EN 60034-1. For duty cycles S2 and S3, the power increase co-efficient reported in the following table may be used. Please note that the table provided below applies to single-speed motors. As an alternative to S1 continuous duty, one of the following values can be specified at the product configuration stage (single speed motors only): S2, S3 or S9. The motor nameplate will be marked with an increased power rating to suit the type of duty, and with specific electrical data and a duty type of S2-30 min, S3-70% or S9 respectively. For further details, contact Bonfiglioli's Technical Service. Please contact Bonfiglioli Engineering for the power increase coefficients applicable to switch-pole motors.

BN and M motors can be configured for operation at duty cycle S2(30min) and S3(70%) as standard option, Other requests which are different in terms of % or min are considered a speciality.
BXN and MXN motors can be configured as standard at S2=10min, S2=30min, S2=60min or S3=25%, S3=40%, S3=70%.

(F24)

	Type of duty						
	S2			**S3 ***			**S4 - S9**
	Duration (min)			Intermittence (I)			
	10	**30 (*)**	**60**	**25%**	**40%**	**70% (*)**	Contact us
f_m	1.35	1.15	1.05	1.25	1.15	1.1	

* Cycle duration must, in any event, be equal to or less than 10 minutes; if this time is exceeded, please contact our Technical Service.
(*) Default values from options (tab. F05).

M7.12.1 Cyclic duration factor:

$$I = \frac{t_f}{t_f + t_r} \times 100 \qquad (01)$$

t_f = work time under constant load
t_r = rest time

M7.12.2 Limited duration duty S2

This type of duty is characterized by operation at constant load for a limited time, which is shorter than the time required to reach thermal equilibrium, followed by a rest period of sufficient duration to restore ambient temperature in the motor.



M7.12.3 Periodical intermittent duty S3:

This type of duty is characterized by a sequence of identical operation cycles, each including a constant load operation period and a rest period.
For this type of duty, the starting current does not significantly influence overtemperature.



M7.13 Inverter-controlled motors

The electric motors Bonfiglioli may be used in combination with PWM inverters with rated voltage at transformer input up to 500 V.Standard motors use a phase insulating system with separators, class 2 enamelled wire and class H impregnation resins (1600V peak-to-peak voltage pulse capacity and rise edge t_s > 0.1µs at motor terminals). Typical torque/speed curves referred to S1 duty for motors with base frequency f_b = 50 Hz is are reported in the table below. Because ventilation is somewhat impaired in operation at lower frequencies (about 30 Hz), standard motors with incorporated fan (IC411) require adequate torque derating or - alternately - the addition of a separate supply fan cooling.
Above base frequency, upon reaching the maximum output voltage of the inverter, the motor enters a steady-power field of operation, and shaft torque drops with ratio ($f/_{fb}$). As motor maximum torque decreases with $(f/_{fb})^2$, the allowed overloading must be reduced progressively.

(F26)



The following table reports the mechanical speed limit for motors operating above rated frequency:

(F27)

		n [min^{-1}]		
		2p	**4p**	**6p**
≤ BE 112 - BN 112	**ME2, ME3 M05 ... M3**	5200	4000	3000
≥ BE 132 - BN 132	**ME4, ME5 M4, M5**	4500	4000	3000
BXN 63 ... BXN 90	**MXN 05 ... MXN 25**		4000	
BX 80 ... BX 180	**MX2 ... MX5**		4000	

Above rated speed, motors generate increased mechanical vibration and fan noise. Class B rotor balancing is highly recommended in these applications. Installing a separate supply fan cooling may also be advisable. Remote-controlled fan and brake (if fitted) must always be connected direct to mains power supply.

M7.14 Permissible starts per hour, Z

The rating charts of brakemotors lend the permitted number of starts Z_0, based on 50% intermittence and for unloaded operation.
The catalogue value represents the maximum number of starts per hour for the motor without exceeding the rated temperature for the insulation class F.
To give a practical example for an application characterized by inertia J_c, drawing power P_r and requiring mean torque at start-up M_L the actual number of starts per hour for the motor can be calculated approximately through the following equation:

$$Z = \frac{Z_0 \cdot K_c \cdot K_d}{K_J} \qquad (02)$$

where:

$K_J = \frac{J_m + J_c}{J_m}$	inertia factor
$K_c = \frac{M_a - M_L}{M_a}$	torque factor
$K_d =$	load factor, see the following table

(F28)



If actual starts per hour is within permitted value (Z) it may be worth checking that braking work is compatible with brake (thermal) capacity Wmax also given in tables (F38), (F41) and dependent on the number of switches (c/h).

M8 ASYNCHRONOUS BRAKE MOTORS

M8.1 Operation

Versions with incorporated brake use spring-applied DC (FD option) or AC (FA options) brakes.
All brakes are designed to provide fail-safe operation, meaning that they are applied by spring-action in the event of power failure.

(F29)



Key:
① brake disc
② disc carrier
③ pressure plate
④ brake coil
⑤ motor rear shield
⑥ brake springs

When voltage is interrupted, pressure springs push the armature plate against the brake disc. The disc becomes trapped between the armature plate and motor shield and stops the shaft from rotation.
When the coil is energized, a magnetic field strong enough to overcome spring action attracts the armature plate, so that the brake disc – which is integral with the motor shaft – is released.

M8.2 Most significant features

- High braking torques (normally $M_b \approx 2\ M_n$), braking torque adjustment.
- Steel brake disc with double friction lining (low-wear, asbestos-free lining).
- Hexagonal seat on motor shaft fan end (N.D.E.) for manual rotation (not compatible with options PS, RC, TC, U1, U2, EN1, EN2, EN3, EN4, EN5, EN6).
- Manual release lever (options **R** and **RM** for FD; option **R** for FA).
- Corrosion-proof treatment on all brake surfaces.
- Insulation class F.

M9 DC BRAKE MOTORS TYPE BXN-BX-BE-BN_FD and MXN-MX-ME-M_FD

Frame sizes: BXN 63 ... BXN 90, BX 80 ... BX 355M, BX200LAK … BX 355MCK - BE 63 ... BE 180L - BN 63 … BN 200L / MXN 05 ... MXN 25 - MX2SB ... MX5LA - ME05 ... ME5 - M05 ... M5

(F30)



IP 54

(F31)



IP 55

Direct current toroidal-coil electromagnetic brake bolted onto motor shield. Preloading springs provide axial positioning of magnet body.
Brake disc slides axially on steel hub shrunk onto motor shaft with anti-vibration device.
Brake torque factory setting is indicated in the corresponding motor rating charts. Braking torque may be modified by changing the type and/or number of springs.
At request, motors may be equipped with manual release lever with automatic return (**R**) or system for holding brake in the released position (**RM**).
See variant at paragraph “BRAKE RELEASE SYSTEMS” for available release lever locations.
FD brakes ensure excellent dynamic performance with low noise. DC brake operating characteristics may be optimized to meet application requirements by choosing from the various rectifier/power supply and wiring connection options available.
For applications involving lifting and/or high hourly energy dissipation, contact Bonfiglioli’s Technical Service.



M9.1 Degree of protection

The standard protection degree for BN - M, BE - ME, BX≤180 - MX≤5 and BXN - MXN, while for BX≥200 and BX≥200K standard protection degree is IP55.
BN - M, BE - ME, BX≤180 - MX≤5 and BXN - MXN brakemotor with a standard protection degree IP54 can be requested with a protection degtree IP55. If **IP55** is selected the following construction variants will be applied:

① V-ring at N.D.E. of motor shaft

② dust and water-proof rubber boot

③ stainless steel ring placed between motor shieldand brake disc

④ stainless steel hub

⑤ stainless steel brake disc

M9.2 FD brake power supply

A rectifier accommodated inside the terminal box feeds the DC brake coil. Wiring connection across rectifier and brake coil is performed at the factory.
Brake power supply voltage V_B is as indicated in the following table, regardless of mains frequency:

(F32)

FD brake supply voltages			
Brake power supply voltage V	FD brake		
	Power supply from the motor with rectifier	Separate power supply with rectifier	Power supply without rectifier
24	✗	✗	✓
100	✗	✗	✓
110	✗	✓	✗
115	✗	✓	✗
120	✗	✓	✗
127	✗	✓	✗
180	✗	✗	✓
208	✓	✓	✗
220	✓	✓	✗
230	✓	✓	✓
240	✓	✓	✗
255	✓	✗	✗
265	✓	✗	✗
280	✓	✗	✗
290	✓	✗	✗
330	✓	✗	✗
380	✓	✓	✗
400	✓	✓	✗
415	✓	✓	✗
440	✓	✓	✗
460	✓	✓	✗
480	✓	✓	✗
500	✓	✓	✗

NOTE: For BXN and MXN motors refer to EVOX specific catalogue

For switch-pole motors the brake power supply is compulsorily from a separate line:

The diode half-wave rectifier (VDC ≈ 0,45 x VAC) is available in versions **NB, SB, NBR** e **SBR**, as detailed in the table below:

(F33)

		brake	standard	on request
BXN 63	**MXN05**	**FD 02**	**NB** 	**SB** 
BXN 71	**MXN10**	**FD 53**		
BXN 80	**MXN20**	**FD 04**		
BXN 90	**—**	**FD 05**		
BE 63 - BN 63	**ME05 - M05**	**FD 02**	**NB** 	**SB** 
BE 71 - BN 71	**ME1 - M1**	**FD 03** **FD 53**		
BX 80 - BE 80 - BN 80	**MX2 - ME2 - M2**	**FD 04**		**SBR** 
BX 90S - BE 90S - BN 90S	**—**	**FD 14**		
BX 90L - BE 90L - BN 90L	**—**	**FD 05**		**NBR** 
BX 100 - BE 100 - BN 100	**MX3 - ME3 - M3**	**FD 15**		
—		**FD 55**	**SB** 	**SBR** 
BX 112 - BE 112 - BN 112	**—**	**FD 06S**		
BX 132 - BE 132 - BN 132 - BN 160MR	**MX4 - ME4 - M4**	**FD 56** **FD 06** **FD 07**		
BX 160 - BE 160L - BN 160L - BN 180M	**MX5 - ME5 - M5**	**FD 08**		
BX 180 - BE 180L - BN 180L - BN 200M	**—**	**FD 09**		
BX 200LA	**—**	**FD 20**	**NB** 	**SB** 
BX 225SA	**—**	**FD 25**		
BX 250M - BX 315SA	**—**	**FD 30**		
BX 315SB - BX 315SC	**—**	**FD 160**		
BX 315MA - BX 355MA	**—**	**FD 250**		
BX 355MB - BX 355MC	**—**	**FD 400**		
BX 200LAK	**—**	**FD 8**		⛔
BX 225SAK - BX 225SBK	**—**	**FD 9**		
BX 250MAK	**—**	**FD 10**		
BX 280SAK - BX 315SAK	**—**	**FD 1000**		
BX 315SBK - BX 315SCK	**—**	**FD 1600**		
BX 355SAK - BX 355MCK	**—**	**FD 2500**	⛔	

(*) $t_{2c} < t_{2r} < t_2$

For BXN motors see the “Brake section” on the EVOX catalogue.



Rectifier **SB** with electronic energizing control over-energizes the electromagnet upon power-up to cut brake release response time and then switches to normal half-wave operation once the brake has been released.

Use of the **SB** rectifier is mandatory in the event of:
- high number of operations per hour
- reduced brake release response time
- brake is exposed to extreme thermal stress

Rectifiers **NBR** or **SBR** are available for applications requiring quick brake intervention (braking condition reinstatement) response.
These rectifiers complement the **NB** and **SB** types as their electronic circuit incorporates a static switch that de-energizes the brake quickly in the event voltage is missing.
This arrangement ensures short brake release response time with no need for additional external wiring and contacts.
Optimum performance of rectifiers **NBR** and **SBR** is achieved with separate brake power supply.
Versions available: 230Vac ±10%, 400Vac ± 10%, 50/60 Hz (with power supply); 100Vdc ±10%, 180Vdc ± 10% (with SD option).



M9.3 FD brake technical specifications

The table below reports the technical specifications of DC brakes FD.

(F34)

Brake	Brake torque M_b [Nm] springs			Release		Braking		W_{max} per brake operation [J]			W	P
				t_1	$t_{1\,s}$	t_2	t_{2c}					
	6	4	2	[ms]	[ms]	[ms]	[ms]	10 s/h	100 s/h	1000 s/h	[MJ]	[W]
FD02	–	3.5	1.75	30	15	80	9	4500	1400	180	15	17
FD03	5	3.5	1.75	50	20	100	12	7000	1900	230	25	24
FD53	7.5	5	2.5	60	30	100	12					
FD04	15	10	5	80	35	140	15	10000	3100	350	30	33
FD14												
FD05	40	26	13	130	65	170	20	18000	4500	500	50	45
FD15	40	26	13	130	65	170	20					
FD06S	60	40	20	–	80	220	25	20000	4800	550	70	55
FD56	–	75	37	–	90	250	20	29000	7400	800	80	65
FD06		100	50		100	250	20					
FD07	150	100	50	–	120	200	25	40000	9300	1000	130	65
FD08*	250	200	170	–	140	350	30	60000	14000	1500	230	100
FD09**	400	300	200	–	200	450	40	70000	15000	1700	230	120
FD20	260			100	170	340	-	80000	1700	1800	-	100
FD25	400			120	195	390	-	120000	19000	2000	-	110
FD30	1000			180	210	420	-	200000	28000	2900	-	200
FD160	1600			360	245	490	-	240000	36000	2600	-	336
FD250	2500			420	343	685	-	280000	47000	3700	-	400
FD400	4000			530	455	910	-	325000	51000	4500	-	420
FD8	400			176	78	236	-	65000	7000	650	-	85
FD9	600			324	138	176	-	120000	12000	1200	-	100
FD10	800			480	194	172	-	100000	16000	2000	-	150
FD1000	1000			252	-	375	-	220000	27000	2700	-	300
FD1600	1600			366	-	498	-	230000	35000	3500	-	340
FD2500	2500			660	-	880	-	590000	61000	6100	-	530

* brake torque values obtained with 9, 7 and 6 springs, respectively

** brake torque values obtained with 12, 9 and 6 springs, respectively

t_1 = brake release time with half-wave rectifier
t_{1s} = brake release time with over-energizing rectifier
t_2 = brake engagement time with AC line interruption and separate power supply
t_{2c} = brake engagement time with AC and DC line interruption – Values for t_1, t_{1s}, t_2, t_{2c} indicated in the tab. (F34) are referred to brake set at maximum torque, medium air gap and rated voltage
W_{max} = max energy per brake operation
W = braking energy between two successive air gap adjustments
P_b = brake power absorption at 20 °C
M_b = static braking torque (±15%
s/h = starts per hour

The brake pad wear depends on the operating/ambient conditions (temperature, humidity, angular speed, specifica pressure); Therefore the declared wear rate must be considered as indicative.

M9.4 FD brake connections

On standard single-pole motors, the rectifier is connected to the motor terminal board at the factory. For switch-pole motors and where a separate brake power supply is required, connection to rectifier must comply with brake voltage VB stated in motor name plate.
Because the load is of the inductive type, brake control and DC line interruption must use contacts from the usage class AC-3 to IEC 60947-4-1.

Table (F35+F39) – Brake coil with power supply from motor terminals (DIR) and AC line interruption.
Delayed stop time t_2 and function of motor time constants.
Mandatory when soft-start/stops are required.
Table (F36+F40) – Brake coil with separate power supply (SA) and AC line interruption.
Normal stop time independent of motor.
Achieved stop times t_2 are indicated in the table (F34).
Table (F37+F41) – Brake coil with power supply from motor terminals (DIR) and AC/DC line interruption.
Quick stop with operation times t_{2c} as per table (F34).
Table (F38+F42) – Brake coil with separate power supply (SA) and AC/DC line interruption.
Stop time decreases by values t_{2c} indicated in the table (F34).

The brake may be voltage supplied directly from the motor terminal box (tab. F35-F39 and tab. F37-F41) only if the nominal voltage of the brake is the same as the smaller voltage of the motor.

(F35)



(F36)



(F37)



(F38)



For BXN and MXN motors the FD brake connection scheme is as follows:

(F39)



(F40)



(F41)



(F42)



M10 AC BRAKE MOTORS TYPE BXN-BX-BE-BN_FA and MXN-MX-ME-M_FA

Frame sizes: BXN 63 ... BXN 90, BX 80 ... BX 160L - BE 63 … BE 160L - BN 63 … BN 180M / MXN 05 ... MXN 25 - MX2SB ... MX5LA - ME05 … ME5 - M05 ... M5

(F43)



IP 54

(F44)



IP 55

Electromagnetic brake operates from three-phase alternated current power supply and is bolted onto conveyor shield. Preloading springs provide axial positioning of magnet body.
Steel brake disc slides axially on steel hub shrunk onto motor shaft with anti-vibration device.
Brake torque factory setting is indicated in the corresponding motor rating charts.
Spring preloading screws provide stepless braking torque adjustment.
Torque adjustment range is 30% $M_{bMAX} < M_b < M_{bMAX}$ (where M_{bMAX} is maximum braking torque as shown in tab. (F45).
Thanks to their high dynamic characteristics, FA brakes are ideal for heavy-duty applications as well as applications requiring frequent stop/starts and very fast response time.
Motors may be equipped with manual release lever with automatic return (R) at request. See variant at paragraph “BRAKE RELEASE SYSTEMS” for available release lever locations.
For applications involving lifting and/or high hourly energy dissipation, contact Bonfiglioli’s Technical Service.

M10.1 Degree of protection

Standard protection class is IP54.
Brake motor FA is also available in protection class **IP55**, which mandates the following variants:

① V-ring at N.D.E. of motor shaft
② dust and water-proof rubber boot
③ O-ring



M10.2 FA brake power supply

In single speed motors, power supply may be brought to the brake coil direct from the motor terminal box. As a result, brake voltage and motor voltage are the same.
Switch-pole motors and motors with separate brake power supply feature an auxiliary terminal board with 6 terminals for connection to brake line. In all cases, brake voltage indication in the designation is mandatory. The following table reports standard AC brake power supply ratings for single- and switch-pole motors:

(F45)

FA brake supply voltages		
Brake power supply voltage V	FA brake	
	Motor power supply at 50Hz	Motor power supply at 60Hz
208	✗	✓
220	✗	✓
230	✓	✓
240	✗	✓
380	✓	✓
400	✓	✓
415	✓	✗
440	✗	✓
460	✗	✓
480	✗	✓
500	✓	✗
575	✗	✓

NOTE: For BXN and MXN motors refer to EVOX specific catalogue

Special voltages are available at request.

M10.3 Technical specifications of FA brakes

(F46)

Brake	Brake torque M_b [Nm]	Release t_1 [ms]	Braking t_2 [ms]	W_{max} [J]			W [MJ]	P [VA]
				10 s/h	**100 s/h**	**1000 s/h**		
FA 02	3.5	4	20	4500	1400	180	15	60
FA 03	7.5	4	40	7000	1900	230	25	80
FA 04	15	6	60	10000	3100	350	30	110
FA 14								
FA 05	40	8	90	18000	4500	500	50	250
FA 15								
FA 06S	60	16	120	20000	4800	550	70	470
FA 06	75	16	140	29000	7400	800	80	550
FA 07	150	16	180	40000	9300	1000	130	600
FA 08	250	20	200	60000	14000	1500	230	1200

M_b = max static braking torque (±15%)
t_1 = brake release time
t_2 = brake engagement time
W_{max} = max energy per brake operation (brake thermal capacity)
W = braking energy between two successive air gap adjustments
P_b = power drawn by brake at 20° (50 Hz)
s/h = starts per hour

NOTE
Values t_1 and t_2 in the table refer to a brake set at rated torque, medium air gap and rated voltage.

The brake pad wear depends on the operating/ambient conditions (temperature, humidity, angular speed, specifica pressure); Therefore the declared wear rate must be considered as indicative.

M10.4 FA brake connections

The diagram below shows the wiring when brake is connected directly to same power supply of the motor:

(F47)



For BXN and MXN motors the FA brake connection scheme is as follows:

(F48)



Switch-pole motors and, at request, single-pole motors with separate power supply are equipped with an auxiliary terminal board with 6 terminals for brake connection.
In this version, motors feature a larger terminal box. See diagram below:

(F49)



For BXN and MXN motors the FA brake connection scheme is as follows:

(F50)



M11 BRAKE RELEASE SYSTEMS

Spring-applied brakes type FD and FA may be equipped with optional manual release devices. These are typically used for manually releasing the brake before servicing any machine or plant parts operated by the motor.

R

(F51)



A return spring brings the release lever back in the original position.

RM

(F52)



On brake motors type FD, if the option RM is specified, the release device may be locked in the ”release” position by tightening the lever until its end becomes engaged with a brake housing projection.
The availability for the various disengagement devices is charted here below:

(F53)

	R	RM
BXN_FD BX_FD BE_FD BN_FD	BXN 63 ... BXN 90 BX 80 ... BX 180 BX 200K ... BX 315K BE 63 ... BE 180 BN 63 ... BN 200	BXN 63 ... BXN 90 BX 80 ... BX 132 BE 63 ... BE 132 BN 63 ... BN 132 ⛔ FD07
MXN_FD MX_FD ME_FD M_FD	MXN05 ... MXN20 MX2 ... MX5 ME05 ... ME5 M05 ... M5	MXN05 ... MXN20 MX2 ... MX4 ME05 ... ME4 M05 ... M4LA
BXN_FA BX_FA BE_FA BN_FA	BXN 63 ... BXN 90 BX 80 ... BX 160 BE 63 ... BE 160L BN 63 ... BN 180M	⛔
MXN_FA MX_FA ME_FA M_FA	MXN05 ... MXN20 MX2 ... MX5 ME05 ... ME5 M05 ... M5	⛔

M11.1 Release lever orientation

Unless otherwise specified, the release lever is located 90° away from the terminal box – identified by letters [**AB**] in the diagram below – in a clockwise direction on both options **R** and **RM**. Alternative lever positions [**AA**], [**AC**] and [**AD**] are also possible when the corresponding option is specified:

(F54)



M11.2 Separate brake supply

DIR

Direct brake supply
The brake system is directly powered through the electric motor terminal board power supply. When a legacy motor is configured with a direct brake supply no option need to be selected, while for EVOX motors DIR option must be selected.

...SA

Separate AC brake supply
The brake coil is directly powered through an independent line, separated from the motor one.
FA-SA: the rated AC voltage must be specified. SA 230 (V AC).
FD-NB/SB-SA: the rated AC voltage which power the rectifier must be specified. E.G. SA 400 (V

...SD

Separate DC brake supply
The brake coil is directly powered with a DC current and the rectifier is not present.
The rated coil voltage must be specified, E.G. SD 24 (V DC).
Note: for BX≥200 and BX≥200K it is not possible to directly feed the brake from the motor terminal box, it is then necessary to select option SA or SD.



M12 OPTIONS

M12.1 Soft-start / stop

F1

An optional flywheel - option F1 - is available for applications requiring soft starting or stopping. The flywheel's added inertia uses up kinetic energy during starting and returns it back during braking, thus catering for more progressive and gradual shock loads. The optional flywheel is available for brake motors type BN-BE_FD and M-ME_FD with specific characteristics as detailed in the table below:

(F55)

Main data for flywheel of motore type: BN-BE_FD, M-ME_FD			
		Fly-wheel weight [Kg]	**Fly-wheel inertia** [Kgm^2]
BN 63 - BE 63	**M05 - ME05**	0.69	0.00063
BN 71 - BE 71	**M1 - ME1**	1.13	0.00135
BN 80 - BE 80	**M2 - ME2**	1.67	0.00270
BN 90 S - BN 90 L BE 90 S - BE 90 LA	**–**	2.51	0.00530
BN 100 - BE 100	**M3 - ME3**	3.48	0.00840
BN 112 - BE 112	**–**	4.82	0.01483
BN 132 S - BN 132 M BE 132 S - BE 132 M	**M4 - ME4**	6.19	0.02580

M12.2 Capacitive filter

CF

An optional capacitive filter is available for brake motors type FD only. When the suitable capacitive filter is installed upstream of the rectifier (option CF), motors comply with the emission limits required by standard EN61000-6-3:2007" Electromagnetic Compatibility – Generic Emission Standard – Part 6-3: Residential, commercial and light industrial environment".
BX≥200LA and BX≥200LAK motors comply with the emission limits required by standard EN 61000-6-3:2007 "Electromagnetic Compatibility - Generic Emission Standard - Part 6-3: residential, commercial and light industrial environment."

M12.3 Thermal protective devices

In addition to the standard protection provided by the magneto-thermal device, motors can be supplied with built-in thermal probes to protect the winding against overheating caused, by insufficient ventilation or by an intermittent duty.
This additional protection should always be specified for servoventilated motors (IC416).

M12.4 Thermistors

E3

These are semi-conductors having rapid resistance variation when they are close to the rated switch off temperature (150 °C). Variations of the R = f(T) characteristic are specified under DIN 44081, IEC 34-11 Standards. Positive temperature coefficient thermistors are normally used (also known as PTC "cold conductor resistors"). Thermistors cannot control relays directly and must be connected to a suitable disconnect device. Thus protected, three PTCs connected in series are installed in the winding, the terminals of which are located on the auxiliary terminal-board.



K1

The design characteristics of this sub-group of PTC thermistors allow them to be used as positive temperature coefficient sensors with variable resistance.
Functioning temperature range: 0°C ... +260°C.
Thermistors cannot control relays directly and must be connected to a suitable disconnect device.
Terminals (polarised) for 1 x KTY 84-130 are provided on an auxiliary terminal strip.

M12.5 Bimetallic thermostates

D3

These types of protective devices house a bimetal disk. When the rated switch off temperature (150 °C) is reached, the disk switches the contacts from their initial rest position.
As temperature falls, the disk and the contacts automatically return to rest position.
Three bimetallic thermostates connected in series are usually employed, with normally closed contacts. The terminals are located on an auxiliary terminal-board.

M12.6 Resistance thermometer

Pt1000

The resistance thermometer has a chip for a temperature sensor, the resistance of which changes in relation to temperature according to a series of reproducible basic values. The changes in resistance are transferred as changes in current.
At 0°C, the measurement resistances are adjusted to 1000 ohm for the Pt1000 and correspond to the accuracy class B (i.e. the relationship between resistance and temperature). The limit deviation is +-0,3°C, and the admissible deviations are defined in EN 60751. The Pt1000 resistance thermometer will, in the future, gradually replace the KTY84-130 temperature available today. The relationship between the temperature and the electrical resistance of conductors is utilized in the Pt1000 to measure the temperature, just like with the additional resistance thermometers described above. Pure metals undergo larger changes in resistance than alloys and have a relatively constant temperature coefficient.

M12.7 Plug connector

CON

Three types of connectors (CON 1, CON 2, CON 3) are provided; they can be mounted in two different positions: right side of terminal box cover (C1D, C2D, C3D); left side of terminal box cover (C1S, C2S, C3S).
The option CON is applicable to single speed BN and M motors (2, 4, 6, 8 poles), and BX / BE and MX / ME motors on the sizes specified on the following table. All double speed motors are excluded.
The connectors CON 1 / CON 2 are available for BX-BE/MX-ME and BN/M motors without brake and for brakemotors equipped with DC brake type FD, for the motor sizes listed below.
The male connector (with pins) is mounted on the motor, the female connector is not provided.
With CON option, the winding connection is always Y.
With option U1 “forced ventilation”, the fan unit supply is available inside the separate terminal box fixed to fan cover.
With options EN1...EN6, the encoder connection is made by a cable not connected to the motor plug connector.
The CON option is not applicable to brakemotors equipped with AC brake type FA.
The CON option is not available when at least one of the next options are selected: the U2, CUS, IC.



Specifications

(F56)

Option	CON 1
Motor size	**BX 80 ... BX 112 / MX2, MX3 / BE 63 ... BE 112 / ME05 ... ME4 BN 63 … BN 112 / M05 ... M3**
Connector view	
Type of connector	Harting Han 10ES
Housing	Han EMC 10B with 2 levers
Numbers of pins - nominal current	10 x 16A
Voltage	500 Vac
Contact connection	Screw terminals

(F57)

Option	CON 2
Motor size	**BX 80 ... BX 132 / MX2, MX3 / BE 63 ... BE 132 / ME05 ... ME4 BN 63 … BN 160MR / M05 ... M4**
Connector view	
Type of connector	Harting Han Modular
Housing	Han EMC 10B with 2 levers
Module type	Module C + Module E + Module E
Numbers of pins - nominal current	3 x 36A / 6 x 16A
Voltage	500 Vac
Contact connection	Crimping contacts

(F58)

Option	CON 3
Motor size	**BX 80 ... BX 132M / MX2, MX3 / BE 63 ... BE 132 / ME05 ... ME4 / BN 63 … BN 160MR / M05 ... M4**
Connector view	
Type of connector	Harting Han Modular
Housing	Han EMC 10B with 2 levers
Module type	Module C + Module E + Module E
Numbers of pins - nominal current	3 x 36A / 6 + 6 x 16A
Voltage	500 Vac
Contact connection	Crimping contacts

(F59)

Connector orientation



(F60)

Motors without brake dimensions



		AD (mm)	**AF** (mm)	**AH** (mm)	**LL** (mm)	**V**(*) (mm)
BE 63 - BN 63	**ME05 - M05**	136	110	45	165	4.5
BE 71 - BN 71	**ME1 - M1**	149	110	45	165	15.5
BX 80 - BE 80 - BN 80	**MX2 - ME2 - M2**	160	110	45	165	16.5
BX 90 - BE 90 - BN 90	**MX3**	162	110	45	165	31.5
BX 100 - BE 100 - BN 100	**MX3 - ME3 - M3**	171	110	45	165	37.5
BX 112 - BE 112 - BN 112	**MX4**	186	110	45	165	39
BX 132 - BE 132 - BN 132	**MX4 - ME4 - M4**	210	140	45	188	45.5
BN 160MR	**–**	210	140	45	188	161

(*) Dimension valid only for motors BX, BE and BN.

(F61)

Motors with FD brake dimensions



		AD (mm)	**AF** (mm)	**AH** (mm)	**LL** (mm)	**V**(*) (mm)
BE 63 - BN 63	**ME05 - M05**	136	110	45	165	4.5
BE 71 - BN 71	**ME1 - M1**	149	110	45	165	1.5
BX 80 - BE 80 - BN 80	**MX2 - ME2 - M2**	160	110	45	165	18.5
BX 90 - BE 90 - BN 90	**—**	162	110	45	165	39.5
BX 100 - BE 100 - BN 100	**MX3 - ME3 - M3**	171	110	45	165	63.5
BX 112 - BE 112 - BN 112	**—**	186	110	45	165	75
BX 132 - BE 132 - BN 132	**MX4 - ME4 - M4**	210	140	45	188	122
BN 160MR	**—**	210	140	45	188	161

(*) Dimension valid only for motors BN.and BX

M12.8 Control of brake operation

MSW

The microswitch can be set in order to obtain from it a signal related to the attraction/release of anchor plate, or it can be set in order to give feedback when the air gap reaches the maximum value.
MSW option is available for brakes FD03...FD09.
The microswitch is provided with three lead wires (NC, NO, COM). The next figure shown the main components of the brake equipped with microswitch.

(F62)



A: Plate f xing screws
B: Setting screws
C: Actuator control pin

M12.9 Additional cable entry for brakemotors

IC

The terminal box cover of brakemotors BN 63 ... BN 160MR - M05 ... M4L is provided with two additional cable entry M16 x 1.5 (one cable entry per side).
The terminal box cover of brakemotors BN 160 ... BN 200 - M5 is provided with an additional cable entry M16 x 1.5 next to the cable entry used for the brake.

M12.10 Anti-condensation heaters

H1 **NH1**

Where an application involves high humidity or extreme temperature fluctuation, motors may be equipped with an anti-condensate heater.
A single-phase power supply is available in the auxiliary terminal board inside the main terminal box.
Values for the absorbed power are listed here below:

(F63)

	H1	NH1
	1~ 230V ± 10% P [W]	1~ 115V ± 10% P [W]
BXN 63 ... BXN 80 **BX 80** **BE 63 ... BE 80** **BN 56 ... BN 80**	10	10
BXN 90 **BX 90 ... BX 132** **BE 90 ... BE 132MB** **BN 90 ... BN 160MR**	25	25
BX 160...BX 250 **BX 160 ... BX 250K** **BX 160, BX 180** **BE 160, BE 180** **BN 160, BN 200**	50	50
BX 280 **BX 280K**	60	60
BX 315 ... BX 355 **BX 315K ... BX 355K**	120	120

Warning!
Always remove power supply to the anti-condensante heater before operating the motor.

M12.11 Tropicalization

TP

When option **TP** is specified, motor windings receive additional protection for operation in high humidity and temperature conditions.

M12.12 Second shaft extension

PS

This option is not compatible with variants RC, TC, U1, U2, EN1, EN2, EN3, EN4, EN5, EN6, EN7, EN8.
For shaft dimensions please see motor dimensions tables.

(F64)



M12.13 Backstop device

AL **AR**

For applications where backdriving must be avoided, motors equipped with an anti run-back device can be used (available for the MX/ME and M series only). While allowing rotation in the direction required, this device operates instantaneously in case of a power failure, preventing the shaft from running back. The anti run-back device is life lubricated with special grease for this specific application. When ordering, customers should indicate the required rotation direction, AL or AR.
Never use the anti run-back device to prevent reverse rotation caused by faulty electrical connection. Table (F62) shows rated and maximum locking torques for the anti run-back devices. A diagram of the device can be seen in Table (F63). Overall dimensis are same as the corresponding brake motor. The direction of free rotation is described in the “MOTOR OPTIONS” section of specifically dedicated sections to gear units.

(F65)

	Rated locking torque [Nm]	Max. locking torque [Nm]	Release speed [min^{-1}]
ME1 - M1	6	10	750
MX2 - ME2 M2	16	27	650
MX3 - ME3 M3	54	92	520
MX4 - ME4 M4	110	205	430

(F66)



M12.14 Rotor balancing

RV

Where low noise is a priority requirement, the option RV ensures reduced vibration in accordance with vibration class B.
The table below reports effective velocity of vibration for normal (A) and B grade balancing.

(F67)

Vibration level	Angular velocity n [min^{-1}]	Limits of the vibration velocity (mm/s) **BX 80 ≤ H ≤ BX 335M ≤ BX 355MK BE 63 ≤ H ≤ BE 180L BN 56 ≤ H ≤ BN 200**
A	600 < n < 3600	1.6
B	600 < n < 3600	0.70

Values are obtained from measurements on freely suspended motor during noload operation; tolerance ±10%.



M12.15 Ventilation

Motors are cooled through outer air blow (IC 411 according to CEI EN 60034-6) and are equipped with a plastic radial fan, which operates in both directions.
Ensure that fan cover is installed at a suitable distance from the closest wall so to allow air circulation and servicing of motor and brake, if fitted.
Motor is cooled by an axial fan with independent power supply and fitted on the fan cover (IC 416 cooling system).
This version is used in case of motor driven by inverter so that steady torque operation is possible even at low speed or when high starting frequencies are needed.
Brake motors of motors with rear shaft projection (PS option) are excluded.

This variant has two different models, called **U1** and **U2**, having the same longitudinal size. Longer side of fan cover (**DL**) is specified for both models in the table below. Overall dimension can be reckoned from motor size table.

(F68)

Extra length for servoventilated motors			
		ΔL_1	ΔL_2
BE 71 - BN 71	**ME1 - M1**	93	32
BX 80	**MX2**	80	67
BE 80 - BN 80	**ME2 - M2**	125	55
BX 90	**—**	133	85
BE 90 - BN 90	**—**	133	49
BX 100	**MX3**	135	88
BE 100 - BN 100	**ME3 - M3**	119	30
BX 112	**—**	136	90
BE 112 - BN 112	**—**	130	33
BX 132	**MX4**	123	24
BE 132 - BN 132	**ME4 - M4**	160	51
BX 160 - BX 180 **BE 160 - BE 180** **BN 160 - BN 180 - BN 200**	**MX5** **ME5** **M5**	184	184
BX 200	**—**	260	260
BX 225 - BX 250	**—**	320	320
BX 280 - BX 315	**—**	430	430
BX 355	**—**	640	640

ΔL_1 = extra length to LB value of corresponding standard motor.

ΔL_2 = extra length to LB value of corresponding brake motor.

U1

Fan wiring terminals are housed in a separate terminal box.
In brake motors of size BX 132 ... BX 160 - BE 71 ... BE 160 - BN 71 ... BN 160MR, MX4, MX5 - ME05 ... ME5 - M05 ... M5 with **U1** model, the release lever cannot be positioned to AA.
This option can be selected for motors compliant with CSA and UL standards (CUS option), only for BX ≥ 200 and BX ≥ 200K.

(F69) 

		V a.c. ±10%	Hz	P [W]	I [A]
BN 71 - BE 71	**ME1 - M1**	1 ~ 230	50 / 60	22	0.12
BX 80 - BE 80 **BN 80**	**MX2 - ME2** **M2**			22	0.12
BX 90 - BE 90 **BN 90**	**–**			40	0.30
BX 100 - BE 100 **BN 100**	**MX3 - ME3** **M3**			50	0.25
BX 112 - BE 112 **BN 112**	**–**	3 ~ 230Δ / 400Y		50	0.26 / 0.15
BX 132 - BE 132 **BN 132 ... BN 160MR**	**MX4 - ME4** **M4L**			110	0.38 / 0.22
BX 160 - BE 160 **BN 160M ... BN 180M**	**MX5 - ME5** **M5**		50	180	1.25 / 0.72
BX 180 - BE 180 **BN 180L ... BN 200L**	**–**			250	1.51 / 0.87
BX 200 ... BX 250 **BX 200K ... BX 250K**	**–**	3 ~ 400Δ / 690Y		250	0.64
BX 280 ... BX 315M **BX 280K ... BX 315MK**	**–**			750	1.7
BX 315 ... BX 355S **BX 315LK ... BX 355SK**	**–**			1500	3.3
BX 355M **BX 355MK**	**–**			3000	6.1

U2

Fan terminals are wired in the motor terminal box.
The **U2** option does not apply to motors BX, BE, MX, ME and to motors with option CUS (compliant to norms CSA and UL).

(F70) 

		V a.c. ±10%	Hz	P [W]	I [A]
BN 71	**M1**	1 ~ 230	50 / 60	22	0.12
BN 80	**M2**			22	0.12
BN 90	**–**			40	0.30
BN 100	**M3**	3 ~ 230Δ / 400Y		40	0.26 / 0.09
BN 112	**–**			50	0.26 / 0.15
BN 132 ... BN 160MR	**M4L**			110	0.38 / 0.22

M12.16 Rain canopy

RC

The rain canopy protects the motor from dripping and avoids the ingress of solid bodies. It is recommended when motor is installed in a vertical position with the shaft downwards.
Relevant dimensions are indicated in the table below.
The drip cover is not compatible with variants PS, EN1, EN2, EN3, EN4, EN5, EN6.

(F71)

		AQ	ΔV	
BE 63 - BN 63	**ME05 - M05**	118	24	
BN 71 - BE 71	**ME1 - M1**	134	27	
BX 80 - BE 80 **BN 80**	**MX2 - ME2** **M2**	152	25	
BX 90 - BE 90 **BN 90**	**—**	168	30	
BX 100 - BE 100 **BN 100**	**MX3 - ME3** **M3**	190	28	
BX 112 - BE 112 **BN 112**	**—**	211	32	
BX 132 - BE 132 **BN 132 ... BN 160MR**	**MX4 - ME4** **M4**	254	32	
BX 160 - BE 160 **BN 160M ... BN 180M**	**MX5 - ME5** **M5**	302	36	
BX 180 - BE 180 **BN 180L ... BN 200L**	**—**	340	36	
BX 200	**—**	423	55	
BX 225	**—**	465	55	
BX 250	**—**	514	55	
BX 280	**—**	567	100	
BX 315	**—**	645	100	
BX 355	**—**	740	120	

For RC/TC on BXN/MXN motors see the scheme below.



M12.17 Textile canopy

TC

Option TC is a cover variant for textile industry environments, where lint may obstruct the fan grid and prevent a regular flow of cooling air.
This option is not compatible with variants EN1, EN2, EN3, EN4, EN5, EN6, PS, U1, U2.
Overall dimensions are the same as drip cover type RC.
TC option is not available for BX motors.

M12.18 Feedback units

Motors may be combined with six different types of encoders to achieve feedback circuits.
Configurations with double-extended shaft (PS) and rain canopy (RC, TC) are not compatible with encoder installation.



EN1

Incremental encoder, V_{IN} = 5 V, line-driver output RS 422.

EN2

Incremental encoder, V_{IN} = 10-30 V, line-driver output RS 422.

EN3

Incremental encoder, V_{IN} = 12-30 V, push-pull output 12-30 V

EN4

Encoder sin/cos, V_{IN} = 4.5-5.5 V, output Sinus 0.5V_{PP}.

EN5

Absolute encoder singleturn, HIPERFACE® interface, V_{IN} = 7-12 V.

EN6

Absolute encoder multiturn, HIPERFACE® interface, V_{IN} = 7-12 V.

EN7

Incremental encoder Heavy Duty, V_{IN} = 12-30 V, push-pull output 12-30 V.

EN8

Incremental encoder Heavy Duty, V_{IN} = 12-30 V, push-pull output 9-30 V.

Note: EN7 and EN8 available only for BX≥200

(F72)

		EN1	EN2	EN3	EN4	EN5	EN6	EN7	EN8
Interface		TTL/RS 422	TTL/RS 422	HTL push-pull	Sinus 0.5 VPP	HIPERFACE®	HIPERFACE®	HTL push-pull	HTL push-pull
Power supply voltage	[V]	4...6	10...30	12...30	4.4...5.5	7...12	7...12	9...30	
Output voltage	[V]	5	5	12...30	—	—	—	9...30	
No-load operating current	[mA]	120	100	100	40	80	80	80	
No. of pulses per revolution		1024							2048
Steps per revolution		—	—	—	—	15 bit	15 bit	-	-
Revolutions		—	—	—	—	—	12 bit	-	-
No. of signals		6 (A, B, Z + inverted signals)			6 (cos-, cos+, sin-, sin+, Z, $\overline{Z}$)	—	—	6	6
Max. output frequency	[kHz]	600			200			200	
Max. speed	[min^{-1}]	6000 (9000 min^{-1} for 10 s)						6000	
Temperature range	[°C]	-30 ... +100						-20 ... +85	
Protection class		IP 65						IP67	

(F73)

EN1, EN2, EN3, EN4, EN5, EN6, EN7, EN8		
		
		L4
BN 63 … BN 200	**M05 ... M5**	65
BE 63… BE180	**ME05 ... ME5L**	65
BX 80 … BX 180	**MX2 ... MX5L**	65
BX 200 … BX 280	**—**	100
BX 315 … BX 355	**—**	100

(F74)

EN_ + U1		
		
		L3
BX 160 - BE 160 BN 160M...BN 180M	**MX5 - ME5 M5**	72
BX 160 - BE 180 BN 180L...BN 200L	**–**	82
BX 160_FD BN 160M_FD...BN 180M_FD	**MX5_FD M5_FD**	35
BX 180_FD BN 180L_FD...BN 200L_FD	**–**	41
BX 200 - BX 225 - BX 250	**–**	100
BX 280 - BX 315 - BX 355	**–**	150

If the encoder device (option EN_) is specified on motors BX 80 ... BX 132 - MX2 ... MX4 - BE 63 ... BE 132 - ME05 ... ME4 - BN 71 ... BN 160MR - M1 ... M4, along with the independent fan cooling (options U1, U2), the extra length of motor is coincident with that of the correspondent U1 and U2 execution.

For EN on BXN/MXN motors see the scheme below.



M12.19 EC - Encoder canopy

EC

Option EC is a cover variant specifically made for our encoders. It protects them from impacts and may help in prolonging their productive life.





M12.20 Insulated Bearings

IB

When IB option is selected the motor is equipped with insulated bearings at drive end. This prevent early bearings failures due to high frequency circulation currents.
NOTE: This option is available only for BX ≥ 280 and BX ≥ 280K, and it is mandatory when the motor is operated through a variable speed drive.

M12.21 Vertical Mounting

VM

NOTE: This option is mandatory for BX ≥ 200 and BX ≥ 200K, when vertically mounted.
When VM is selected the motor is delivered with specific arrangements.
Furthermore, the vertical mounting position will also be reported on motor nameplate.

M12.22 Surface protection

C_

When no specific protection class is requested, the painted (ferrous) surfaces of motors are protected to at least corrosivity class C2 (UNI EN ISO 12944-2). For improved resistance to atmospheric corrosion, motors can be delivered with C3 and C4 surface protection.

(F75)

SURFACE PROTECTION	Typical environments	Maximum surface temperature	Corrosivity class according to UNI EN ISO 12944-2
C3	Urban and industrial environments with up to 100% relative humidity (medium air pollution)	120°C	C3
C4	Industrial areas, coastal areas, chemical plant, with up to 100% relative humidity (high air pollution)	120°C	C4
C5M	Coast and offshore areas with high salt content.	120°C	C5M

Motors with optional protection to class C3 or C4 are available in a choice of colours. If no specific colour is requested (see the “PAINTING” option) motors are finished in RAL 7042 for BN/M, BE/ME and BX≤180/MX and in Munsell blue 8B 4.5/3.25 for BX≥200.
Motors can also be supplied with surface protection for corrosivity class C5 according to UNI EN ISO 12944-2. Contact our Technical Service for further details.



M12.23 Painting

RAL

Gearboxes with optional protection to class C3 or C4 are available in the colours listed in the following table.

(F76)

PAINTING	Colour	RAL number
RAL7042*	Traffic Grey A	7042
RAL5010	Gentian Blue	5010
RAL9005	Jet Black	9005
RAL9006	White Aluminium	9006
RAL9010	Pure White	9010
RAL7035	Light Grey	7035
RAL7001	Silver Grey	7001
RAL5015	Sky Blue	5015
RAL7037	Dusty Grey	7037
RAL5024	Pastel Blue	5024

* BX ≥ 200 and BX ≥ 200K Motors are standardly supplied in this colour with C3 protection unless specified diffrently.

NOTE – “PAINTING” options can only be specified in conjunction with “SURFACE PROTECTION” options.

M12.24 Certificates

ACM

Certificate of compliance of motors
The document certifies the compliance of the product with the purchase order and the construction in conformity with the applicable procedures of the Bonfiglioli Quality System.

Note: Not available for BX≥200 and BX≥200K

CC

Inspection certificate
The document entails checking on order compliance, the visual inspection of external conditions and instrumental testing of the electrical characteristics in unloaded conditions. Units inspected are sampled within the shipping batch and marked individually.



M13 TABLES OF MOTORS CORRELATION

M13.1 50 Hz Motors

(F77)

2 pole							
Efficiency class		IE1	IE2	IE3	IE1	IE2	IE3
Pn [kW]	0.06						
	0.09						
	0.12						
	0.18	BN 63A 2			M 05A 2		
	0.25	BN 63B 2			M 05B 2		
	0.37	BN 71A 2			M 05C 2		
	0.55	BN 71B 2			M 1SD 2		
	0.75	BN 71C 2	BE 80A 2		M 1LA 2	ME 2SA 2	
		BN 80A 2					
	1.1	BN 80B 2	BE 80B 2		M 2SA 2	ME 2SB 2	
	1.5	BN 90SA 2	BE 90SA 2		M 2SB 2		
	1.85	BN 90SB 2					
	2.2	BN 90L 2	BE 90L 2		M 3SA 2		
	3	BN 100L 2	BE 100L 2		M 3LA 2	ME 3LB 2	
	4	BN 112M 2	BE 112M 2		M 3LB 2		
	5.5	BN 132SA 2	BE 132SA 2		M 4SA 2	ME 4SA 2	
	7.5	BN 132SB 2	BE 132SB 2		M 4SB 2	ME 4LA 2	
	9.2	BN 132M 2	BE 132MB 2		M 4LA 2	ME 4LB 2	
	11	BN 160MR 2	BE 160MA 2		M 4LC 2	ME 5SA 2	
		BN 160M 2					
	15	BN 160MB 2	BE 160MB 2		M 5SB 2	ME 5SB 2	
	18.5	BN 160L 2	BE 160L 2		M 5SC 2	ME 5LA 2	
	22	BN 180M 2			M 5LA 2		
	30	BN 200LA 2					

(F78)

4 pole									
Efficiency class		IE1	IE2	IE3		IE1	IE2	IE3	
Pn [kW]	0.06	BN 56A 4							
	0.09	BN 56B 4				M 0B 4			
	0.12	BN 63A 4	BE 63A 4		BXN 63MA 4	M 05A 4	ME 05A 4		MXN 05MA 4
	0.18	BN 63B 4	BE 63B 4		BXN 63MB 4	M 05B 4	ME 05B 4		MXN 05MB 4
	0.25	BN 63C 4				M 05C 4			
		BN 71A 4	BE 71A 4		BXN 71MA 4		ME 1SA 4		MXN 10MA 4
	0.37	BN 71B 4	BE 71B 4		BXN 71MB 4	M 1SD 4	ME 1SB 4		MXN 10MB 4
	0.55	BN 71C 4				M 1LA 4			
		BN 80A 4	BE 80A 4		BXN 80MA 4				MXN 20MA 4
	0.75	BN 80B 4	BE 80B 4	BX 80B 4	BXN 80MB 4	M 2SA 4	ME 2SB 4	MX 2SB 4	MXN 20MB 4
	1.1	BN 80C 4	BE 90S 4	BX 90S 4		M 2SB 4	ME 3SA 4	MX 3SA 4	
		BN 90S 4			BXN 90S 4				
	1.5	BN 90LA 4	BE 90LA 4	BX 90LA 4	BXN 90L 4	M 3SA 4	ME 3SB 4	MX 3SB 4	
	1.85	BN 90LB 4							
	2.2	BN 100LA 4	BE 100LA 4	BX 100LA 4		M 3LA 4	ME 3LA 4	MX 3LA 4	
	3	BN 100LB 4	BE 100LB 4	BX 100LB 4		M 3LB 4	ME 3LB 4	MX 3LB 4	
	4	BN 112M 4	BE 112M 4	BX 112M 4		M 3LC 4	ME 4SA 4	MX 4SA 4	
	5.5	BN 132S 4	BE 132S 4	BX 132SB 4		M 4SA 4	ME 4SB 4	MX 4SB 4	
	7.5	BN 132MA 4	BE 132MA 4	BX 132MA 4		M 4LA 4	ME 4LA 4	MX 4LA 4	
	9.2	BN 132MB 4	BE 132MB 4	BX 160MA 4		M 4LB 4	ME 4LB 4	MX 5SA 4	
	11	BN 160MR 4	BE 160M 4	BX 160MB 4		M 4LC 4	ME 5SA 4	MX 5SB 4	
		BN 160M 4							
	15	BN 160L 4	BE 160L 4	BX 160L 4		M 5SB 4	ME 5LA 4	MX 5LA 4	
	18.5	BN 180M 4	BE 180M 4	BX 180M 4		M 5LA 4			
	22	BN 180L 4	BE 180L 4	BX 180L 4					
	30	BN 200L 4		BX 200LA 4*					
	37			BX 225SA 4*					
	45			BX 225SB 4*					
	55			BX 250MA 4*					
	75			BX 280SA 4*					
	90			BX 280SB 4*					
	110			BX 315SA 4*					
	132			BX 315SB 4*					
	160			BX 315SC 4*					
	200			BX 315MA 4*					
	250			BX 355MA 4*					
	315			BX 355MB 4*					
	355			BX 355MC 4*					

Note: For the Australian market these motor has to be selected in the BX ... K 4 Version



(F79)

6 pole							
Efficiency class		IE1	IE2	IE3	IE1	IE2	IE3
Pn [kW]	0.06						
	0.09	BN 63A 6			M 05A 6		
	0.12	BN 63B 6			M 05B 6		
	0.18	BN 71A 6			M 1SC 6		
	0.25	BN 71B 6			M 1SD 6		
		BN 71C 6					
	0.37	BN 80A 6			M 1LA 6		
	0.55	BN 80B 6			M 2SA 6		
	0.75	BN 80C 6	BE 90S 6		M 2SB 6		
		BN 90S 6					
	1.1	BN 90L 6	BE 100M 6		M 3SA 6	ME 3LA 6	
	1.5	BN 100LA 6	BE 100LA 6		M 3LA 6	ME 3LB 6	
	1.85	BN 100LB 6			M 3LB 6		
	2.2	BN 112M 6	BE 112M 6		M 3LC 6		
	3	BN 132S 6	BE 132S 6		M 4SA 6	ME 4SB 6	
	4	BN 132MA 6	BE 132MA 6		M 4LA 6	ME 4LA 6	
	5.5	BN 132MB 6	BE 160MA 6		M 4LB 6	ME 5SA 6	
	7.5	BN 160M 6	BE 160MB 6		M 5SA 6	ME 5SB 6	
	9.2						
	11	BN 160L 6			M 5SB 6		
	15	BN 180L 6					
	18.5	BN 200LA 6					
	22						
	30						

M13.2 60 Hz Motors

(F80)

2 pole							
Efficiency class		IE1	IE2	IE3	IE1	IE2	IE3
Pn [kW]	0.06						
	0.09						
	0.12						
	0.18	BN 63A 2			M 05A 2		
	0.25	BN 63B 2			M 05B 2		
	0.37	BN 71A 2			M 05C 2		
	0.55	BN 71B 2			M 1SD 2		
	0.75	BN 71C 2			M 1LA 2		
		BN 80A 2					
	1.1	BN 80B 2			M 2SA 2		
	1.5	BN 90SA 2			M 2SB 2		
	1.85	BN 90SB 2					
	2.2	BN 90L 2			M 3SA 2		
	3	BN 100L 2			M 3LA 2		
	3.7	BN 112M 2			M 3LB 2		
	5.5	BN 132SA 2			M 4SA 2		
	7.5	BN 132SB 2			M 4SB 2		
	9.2	BN 132M 2			M 4LA 2		
	11	BN 160MR 2			M 4LC 2		
		BN 160M 2					
	15	BN 160MB 2			M 5SB 2		
	18.5	BN 160L 2			M 5SC 2		
	22	BN 180M 2			M 5LA 2		
	30	BN 200LA 2					



(F81)

4 pole									
Efficiency class		IE1	IE2	IE3		IE1	IE2	IE3	
Pn [kW]	0.06	BN 56A 4							
	0.09	BN 56B 4				M 0B 4			
	0.12	BN 63A 4	BE 63A 4		BXN 63MA 4	M 05A 4			MXN 05MA 4
	0.18	BN 63B 4	BE 63B 4		BXN 63MB 4	M 05B 4			MXN 05MB 4
	0.25	BN 63C 4				M 05C 4			
		BN 71A 4	BE 71A 4		BXN 71MA 4				MXN 10MA 4
	0.37	BN 71B 4	BE 71B 4		BXN 71MB 4	M 1SD 4			MXN 10MB 4
	0.55	BN 71C 4				M 1LA 4			
		BN 80A 4	BE 80A 4		BXN 80MA 4				MXN 20MA 4
	0.75	BN 80B 4	BE 80B 4	BX 90SR 4	BXN 80MB 4	M 2SA 4	ME 2SB 4	MX 2SB 4	MXN 20MB 4
	1.1	BN 80C 4	BE 90S 4	BX 90S 4		M 2SB 4	ME 3SA 4	MX 3SA 4	
		BN 90S 4			BXN 90S 4				
	1.5	BN 90LA 4	BE 90LA 4	BX 90LA 4	BXN 90L 4	M 3SA 4	ME 3SB 4	MX 3SB 4	
	1.85	BN 90LB 4							
	2.2	BN 100LA 4	BE 100LA 4	BX 100LA 4		M 3LA 4	ME 3LA 4	MX 3LA 4	
	3	BN 100LB 4	BE 100LB 4	BX 100LB 4		M 3LB 4	ME 3LB 4	MX 3LB 4	
	3.7	BN 112M 4	BE 112M 4	BX 112M 4		M 3LC 4	ME 4SA 4	MX 4SA 4	
	5.5	BN 132S 4	BE 132S 4	BX 132SB 4		M 4SA 4	ME 4SB 4	MX 4SB 4	
	7.5	BN 132MA 4	BE 132MA 4	BX 132MA 4		M 4LA 4	ME 4LA 4	MX 4LA 4	
	9.2	BN 132MB 4	BE 132MB 4	BX 160MA 4		M 4LB 4	ME 4LB 4	MX 5SA 4	
	11	BN 160MR 4	BE 160M 4	BX 160MB 4		M 4LC 4	ME 5SA 4	MX 5SB 4	
		BN 160M 4							
	15	BN 160L 4	BE 160L 4	BX 160L 4		M 5SB 4	ME 5LA 4	MX 5LA 4	
	18.5	BN 180M 4	BE 180M 4	BX 180M 4		M 5LA 4			
	22	BN 180L 4	BE 180L 4	BX 180L 4					
	30	BN 200L 4		BX 200LAK 4					
	37			BX 225SAK 4					
	45			BX 225SBK 4					
	55			BX 280SAK 4					
	75			BX 280SBK 4					
	90			BX 315SAK 4					
	110			BX 315SBK 4					
	132			BX 315SCK 4					
	160			BX 355SAK 4					
	200			BX 355SBK 4					
	250			BX 355SCK 4					
	315			BX 355MBK 4					
	355			BX 355MCK 4					

(F82)

6 pole							
Efficiency class		IE1	IE2	IE3	IE1	IE2	IE3
Pn [kW]	0.06						
	0.09	BN 63A 6			M 05A 6		
	0.12	BN 63B 6			M 05B 6		
	0.18	BN 71A 6			M 1SC 6		
	0.25	BN 71B 6			M 1SD 6		
		BN 71C 6					
	0.37	BN 80A 6			M 1LA 6		
	0.55	BN 80B 6			M 2SA 6		
	0.75	BN 80C 6			M 2SB 6		
		BN 90S 6					
	1.1	BN 90L 6			M 3SA 6		
	1.5	BN 100LA 6			M 3LA 6		
	1.85	BN 100LB 6			M 3LB 6		
	2.2	BN 112M 6			M 3LC 6		
	3	BN 132S 6			M 4SA 6		
	3.7	BN 132MA 6			M 4LA 6		
	5.5	BN 132MB 6			M 4LB 6		
	7.5	BN 160M 6			M 5SA 6		
	9.2						
	11	BN 160L 6			M 5SB 6		
	15	BN 180L 6					
	18.5	BN 200LA 6					
	22						
	30						



4 P	1500 min^{-1} - S1	50 Hz - IE3

CE

															d.c. brake						a.c. brake				
															FD						FA				
P_n		n	M_n	In 400V	η%			cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	KVA code	J_m x 10^{-4}	IM B5	Mod	M_b	Z_o 1/h		J_m x 10^{-4}	IM B5	Mod	M_b	Z_o 1/h	J_m x 10^{-4}	IM B5
kW		min^{-1}	Nm	A	100%	75%	50%						kgm^2	Kg		Nm	NB	SB	kgm^2	Kg		Nm		kgm^2	Kg
0.12	**BXN 63MA 4**	1407	0.8	0.47	64.8	60.3	52.5	0.58	3.4	2.9	1.7	H	1.82	4.6	**FD 02**	1.8	8900	11000	2.4	6.3	**FA 02**	1.8	11000	2.4	6.1
0.18	**BXN 63MB 4**	1373	1.3	0.61	69.9	68.8	63.3	0.61	3.5	3.1	1.8	G	2.92	5.7	**FD 02**	3.5	7000	9000	3.5	7.4	**FA 02**	3.5	9000	3.5	7.2
0.25	**BXN 71MA 4**	1388	1.7	0.67	73.5	72.8	67.9	0.74	4.8	1.6	2.4	H	6.28	6.5	**FD 53**	5	5700	8100	7.4	9.2	**FA 03**	5	8100	7.4	8.9
0.37	**BXN 71MB 4**	1429	2.5	1.05	77.3	76.0	70.8	0.66	6.3	2.6	2.5	L	9.70	8.3	**FD 53**	5	6400	9900	10.8	11.0	**FA 03**	5	9900	10.8	10.7
0.55	**BXN 80MA 4**	1447	3.6	1.31	80.8	80.9	77.4	0.75	6.1	1.9	1.6	J	17.78	10.7	**FD 04**	10	2500	5200	19.8	14.6	**FA 04**	10	5200	19.8	14.5
0.75	**BXN 80MB 4**	1451	4.9	1.63	82.5	85.1	82.5	0.78	7.4	2.4	2.0	K	28.89	14.4	**FD 04**	15	2000	4100	30.8	18.3	**FA 04**	15	4100	30.8	18.2
1.1	**BXN 90S 4**	1448	7.3	2.38	84.1	85.9	83.5	0.78	7.3	2.4	3.4	J	31.76	15.6	**FD 05**	26	2800	6600	35.8	21.6	**FA 05**	26	6600	35.8	22.3
1.5	**BXN 90L 4**	1441	9.9	3.44	85.3	84.3	81.7	0.75	6.7	2.6	2.4	J	34.96	16.6	**FD 05**	26	1400	3100	39.1	22.6	**FA 05**	26	3100	39.1	23.3

Note: for more details on the available energy certifications look at the catalog's dedicated section.

4 P	1500 min^{-1} - S1	50 Hz - IE3

CE

															d.c. brake						a.c. brake				
															FD						FA				
P_n		n	M_n	In 400V	η%			cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	KVA code	J_m x 10^{-4}	IM B5	Mod	M_b	Z_O 1/h		J_m x 10^{-4}	IM B5	Mod	M_b	Z_O 1/h	J_m x 10^{-4}	IM B5
kW		min^{-1}	Nm	A	100%	75%	50%						kgm^2	Kg		Nm	NB	SB	kgm^2	Kg		Nm		kgm^2	Kg
0.12	**MXN 05MA 4**	1407	0.8	0.47	64.8	60.3	52.5	0.58	3.4	2.9	1.7	H	1.82	4.6	**FD 02**	1.8	8900	11000	2.4	6.3	**FA 02**	1.8	11000	2.4	6.1
0.18	**MXN 05MB 4**	1373	1.3	0.61	69.9	68.8	63.3	0.61	3.5	3.1	1.8	G	2.92	5.7	**FD 02**	3.5	7000	9000	3.5	7.4	**FA 02**	3.5	9000	3.5	7.2
0.25	**MXN 10MA 4**	1388	1.7	0.67	73.5	72.8	67.9	0.74	4.8	1.6	2.4	H	6.28	6.5	**FD 53**	5	5700	8100	7.4	9.2	**FA 03**	5	8100	7.4	8.9
0.37	**MXN 10MB 4**	1429	2.5	1.05	77.3	76.0	70.8	0.66	6.3	2.6	2.5	L	9.70	8.3	**FD 53**	5	6400	9900	10.8	11.0	**FA 03**	5	9900	10.8	10.7
0.55	**MXN 20MA 4**	1447	3.6	1.31	80.8	80.9	77.4	0.75	6.1	1.9	1.6	J	17.78	10.7	**FD 04**	10	2500	5200	19.8	14.6	**FA 04**	10	5200	19.8	14.5
0.75	**MXN 20MB 4**	1451	4.9	1.63	82.5	85.1	82.5	0.78	7.4	2.4	2.0	K	28.89	14.4	**FD 04**	15	2000	4100	30.8	18.3	**FA 04**	15	4100	30.8	18.2

Note: for more details on the available energy certifications look at the catalog's dedicated section.



M15 MOTORS DIMENSIONS BXN-MXN

BXN - IM B5 - CE CUS/UKCA



	Shaft					Housing						Motor							
	D DA	**E EA**	**DB**	**GA GC**	**F FA**	**M**	**N**	**P**	**S**	**T**	**LA**	**AC**	**L**	**LB**	**LC**	**AD**	**AF**	**LL**	**V**
BXN 63	11 9(1)	23 20(1)	M4 M3(1)	12.5 10.2(1)	4 3(1)	115	95	140	9.5	3	9	122	281	258	301	136	112	165	37
BXN 71	14 11(1)	30 23(1)	M5 M4(1)	16 12.5(1)	5 4(1)	130	110	160		3.5		138	292	262	315	138			34
BXN 80	19 14(1)	40 30(1)	M6 M5(1)	21.5 16(1)	6 5(1)	165	130	200	11.5		10	158	346	306	376	148			40
BXN 90	24 19(1)	50 40(1)	M8 M6(1)	27 21.5(1)	8 6(1)							177	365	315	405	170		170	43

N.B.: 1) These values refer to the rear shaft end (PS).

BXN - IM B5 - FD/FA - CE - CUS/UKCA



	Shaft					Housing						Motor								R	
	D DA	**E EA**	**DB**	**GA GC**	**F FA**	**M**	**N**	**P**	**S**	**T**	**LA**	**AC**	**L**	**LB**	**LC**	**AD**	**AF**	**LL**	**V**	**FD**	**FA**
BXN 63	11 9(1)	23 20(1)	M4 M3(1)	12.5 10.2(1)	4 3(1)	115	95	140	9.5	3	9	122	328	305	352	136	112	165	37	96	116
BXN 71	14 11(1)	30 23(1)	M5 M4(1)	16 12.5(1)	5 4(1)	130	110	160		3.5		138	351	321	380	138			34	103	121
BXN 80	19 14(1)	40 30(1)	M6 M5 1)	21.5 16(1)	6 5(1)	165	130	200	11.5		10	158	417	377	448	148			40	129	131
BXN 90	24 19(1)	50 40(1)	M8 M6(1)	27 21.5(1)	8 6(1)							177	433	383	451	170		170	43	160	160

N.B.: 1) These values refer to the rear shaft end (PS).



MXN



	Rear shaft end					Motor						
	DA	**EA**	**DB**	**FA**	**GC**	**AC**	**LB**	**LC**	**AF**	**LL**	**J**	**AD**
MXN 05	9	20	M3	3	10.2	123	211.5	231.5	112	165	9.5	136
MXN 10	11	23	M4	4	12.5	138	216	239	112	165	11.5	137
MXN 20	14	30	M5	5	16	158	255.5	285.5	112	165	10.5	146

MXN_FD/FA



	Rear shaft end					Motor								
	DA	EA	DB	FA	GC	AC	LB	LC	AF	LL	J	AD	R	
													FD	FA
MXN 05	9	20	M3	3	10.2	122	211.5	258.5	112	165	9.5	136	96	116
MXN 10	11	23	M4	4	12.5	138	216	275	112	165	11.5	138	103	121
MXN 20	14	30	M5	5	16	158	255.5	326.5	112	165	10.5	148	129	131



4 P	1500 min^{-1} - S1	50 Hz - IE3

CE

															d.c. brake				a.c. brake			
															FD				FA			
P_n kW		n min^{-1}	M_n Nm	In 400V A	η% 100%	η% 75%	η% 50%	cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	KVA code	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	J_m x 10^{-4} kgm^2	IM B5 Kg
0.75	**BX 80B 4**	1425	5.0	1.61	82.5	83.9	83.2	0.81	6.5	2.0	1.8	J	35	16	**FD 04**	15	37	19.9	**FA 04**	15	37	19.8
1.1	**BX 90S 4**	1425	7.4	2.44	84.1	84.1	82.0	0.77	6.9	3.4	2.2	J	27	16	**FD 14**	15	29	20.2	**FA 14**	15	29	20.1
1.5	**BX 90LA 4**	1420	10.1	3.3	85.3	86.2	84.9	0.78	6.3	3.1	1.9	J	31	17	**FD 05**	26	35	23	**FA 05**	26	35	23.7
2.2	**BX 100LA 4**	1445	14.5	5.1	86.7	86.2	84.0	0.72	7.2	3.6	2.4	K	58	24	**FD 15**	40	62	31	**FA 15**	40	62	31
3	**BX 100LB 4**	1445	19.8	6.7	87.7	87.7	86.0	0.74	7.6	3.9	2.6	K	73	29	**FD 15**	40	77	36	**FA 15**	40	77	36
4	**BX 112M 4**	1445	26	8.1	88.6	88.9	87.6	0.8	8.1	3.8	2.5	J	130	38	**FD 06S**	60	139	48	**FA 06S**	60	139	50
5.5	**BX 132SB 4**	1460	36	10.6	89.6	89.2	88.8	0.83	8.2	3.6	2.3	J	310	57	**FD 56**	75	320	70	**FA 06**	75	320	71
7.5	**BX 132MA 4**	1460	49	15.0	90.4	90.9	90.2	0.80	8.4	3.8	2.5	K	360	67	**FD 06**	100	370	80	**FA 07**	100	370	85
9.2	**BX 160MA 4**	1465	60	17.8	91.0	92.1	91.7	0.82	7.9	3.6	2.1	J	650	95	**FD 08**	170	725	125	**FA 08**	170	725	124
11	**BX 160MB 4**	1465	72	20.5	91.4	92.9	92.5	0.84	7.8	3.4	1.9	J	780	110	**FD 08**	170	855	140	**FA 08**	170	855	139
15	**BX 160L 4**	1465	98	28.1	92.1	93.2	92.6	0.82	9.0	4.1	2.3	K	890	121	**FD 08**	200	965	151	**FA 08**	200	965	150
18.5	**BX 180M 4**	1480	119	32.9	92.6	94.1	93.1	0.85	11.3	2.6	2.3	M	1560	155	**FD 09**	300	1760	195				
22	**BX 180L 4**	1475	142	38.2	93.0	93.6	92.8	0.88	10.2	2.5	2.0	L	1660	163	**FD 09**	300	1860	203				

Note: for more details on the available energy certifications look at the catalog's dedicated section.

4 P	1500 min^{-1} - S1	50 Hz - IE3

															d.c. brake				a.c. brake			
															FD				FA			
P_n kW		n min^{-1}	M_n Nm	In 400V A	η% 100%	η% 75%	η% 50%	cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	KVA code	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	J_m x 10^{-4} kgm^2	IM B5 Kg
30	**BX 200LA 4**	1483	193.2	54.8	93.6	93.9	93.4	0.84	7.5	2.7	3.2	N/A	3850	292	**FD20**	260	3910	317				
37	**BX 225SA 4**	1482	238.6	68.9	93.9	94.1	93.8	0.83	7.2	3.1	3.1	N/A	4270	322	**FD25**	400	4450	356				
45	**BX 225SB 4**	1482	290	82.3	94.2	94.4	94	0.84	8	3.2	3.5	N/A	5250	357	**FD25**	400	5430	391				
55	**BX 250MA 4**	1482	354.2	100	94.6	94.7	94	0.84	7.1	2.9	3.4	N/A	6940	406	**FD30**	1000	7540	452				
75	**BX 280SA 4**	1485	483	133	95	95.2	94.8	0.86	6.4	2.3	2.8	N/A	13800	645	**FD30**	1000	14400	691				
90	**BX 280SB 4**	1485	578	158	95.2	95.5	95.2	0.86	7.1	2.5	2.9	N/A	17300	700	**FD30**	1000	17900	746				
110	**BX 315SA 4**	1489	705	198	95.4	95.5	95	0.84	7	2.1	3	N/A	24300	930	**FD30**	1000	24900	976				
132	**BX 315SB 4**	1488	847	231	95.6	95.9	95.5	0.86	6.7	2.2	2.9	N/A	29000	1000	**FD160**	1600	30500	1121				
160	**BX 315SC 4**	1488	1026	282	95.8	96	95.8	0.85	6.9	2.2	3	N/A	32000	1065	**FD160**	1600	33500	1186				
200	**BX 315MA 4**	1487	1284	351	96	96.4	96.4	0.86	6.8	2.4	3	N/A	39000	1220	**FD250**	2500	41400	1390				
250	**BX 355MA 4**	1491	1601	435	96	96	95.6	0.86	6.4	2.1	2.9	N/A	59000	1610	**FD250**	2500	61400	1780				
315	**BX 355MB 4**	1491	2018	550	96	96.1	95.7	0.85	7.3	2.4	3.3	N/A	69000	1780	**FD400**	4000	73300	2000				
355	**BX 355MC 4**	1490	2273	616	96	96.2	95.8	0.86	6.3	2.3	2.8	N/A	72000	1820	**FD400**	4000	76300	2040				

Note: for more details on the available energy certifications look at the catalog's dedicated section.



4 P	1500 min^{-1} - S1	50 Hz - IE3



EECA

															d.c. brake				a.c. brake			
															FD				FA			
P_n kW		n min^{-1}	M_n Nm	In 400V A	η% 100%	η% 75%	η% 50%	cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	KVA code	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	J_m x 10^{-4} kgm^2	IM B5 Kg
30	**BX 200LAK 4**	1483	193	55.7	94.7	95.1	95	0.82	8.3	3	3.3	N/A	3660	319	**FD 8**	400	3940	337				
37	**BX 225SAK 4**	1482	238	65.9	95.1	95.5	95.4	0.85	7.7	2.8	3.1	N/A	5360	398	**FD 9**	600	5720	426				
45	**BX 225SBK 4**	1481	290	80.4	95.2	95.6	95.6	0.85	7.9	2.8	3.2	N/A	5360	398	**FD 9**	600	5720	426				
55	**BX 250MAK 4**	1485	354	98.9	95.6	95.8	95.5	0.84	7.9	3	3.3	N/A	9330	476	**FD 10**	800	10080	521				
75	**BX 280SAK 4**	1487	482	134	95.9	96.2	96.1	0.84	7.3	2.5	2.8	N/A	15000	665	**FD 1000**	1000	15360	771				
90	**BX 280SBK 4**	1487	578	161	96.2	96.4	96.1	0.84	7.9	2.9	3	N/A	18500	725	**FD 1000**	1000	18860	831				
110	**BX 315SAK 4**	1491	704	194	96.8	97	96.7	0.84	8.3	2.4	3.1	N/A	29000	1000	**FD 1000**	1000	29360	1106				
132	**BX 315SBK 4**	1490	846	234	96.9	97.1	96.8	0.84	8.1	2.6	3.2	N/A	32000	1065	**FD 1600**	1600	32500	1233				
160	**BX 315SCK 4**	1490	1025	279	96.7	96.9	96.6	0.86	8.2	2.7	3	N/A	39000	1220	**FD 1600**	1600	39500	1388				
200	**BX 355SAK 4**	1491	1281	345	96.6	96.7	96.4	0.87	7.3	2.1	2.7	N/A	59000	1610	**FD 2500**	2500	59500	1778				
250	**BX 355MAK 4**	1491	1601	435	96	96	95.6	0.86	6.4	2.1	2.9	N/A	69000	1780	**FD 2500**	2500	69500	1948				
315	**BX 355MBK 4**	1491	2017	550	96	96.1	95.7	0.85	7.3	2.4	3.3	N/A	72000	1820	**FD 2500**	2500	72500	1988				
355	**BX 355MCK 4**	1490	2275	616	96	96.2	95.8	0.86	6.3	2.3	2.8	N/A	84000	2140	**FD 2500**	2500	84500	2308				

Note: for more details on the available energy certifications look at the catalog's dedicated section.

4 P	1800 min^{-1} - S1	60 Hz - Nema Premium

ENERGY

															d.c. brake				a.c. brake			
															FD				FA			
P_n		n	M_n	In 460V	η%			cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	KVA code	J_m x 10^{-4}	IM B5	Mod	M_b	J_m x 10^{-4}	IM B5	Mod	M_b	J_m x 10^{-4}	IM B5
kW		min^{-1}	Nm	A	100%	75%	50%						kgm^2	Kg		Nm	kgm^2	Kg		Nm	kgm^2	Kg
0.75	**BX 90SR 4**	1755	4.1	1.48	85.5	86.4	83.9	0.73	8.0	3.7	2.5	L	27	16	**FD 14**	15	29	20.2	**FA 14**	15	29	20.1
1.1	**BX 90S 4**	1740	6.0	2.15	86.5	85.9	83.0	0.74	8.2	4.1	2.8	K	27	16	**FD 14**	15	29	20.2	**FA 14**	15	29	20.1
1.5	**BX 90LA 4**	1735	8.3	2.91	86.5	86.5	84.4	0.75	7.4	3.6	2.5	K	31	17	**FD 05**	26	35	23	**FA 05**	26	35	23.7
2.2	**BX 100LA 4**	1760	11.9	4.4	89.5	88.6	86.2	0.71	9.9	4.8	3.6	N	73	29	**FD 15**	40	77	36	**FA 15**	40	77	36
3	**BX 100LB 4**	1750	16.4	5.9	89.5	88.9	86.7	0.71	9.1	4.4	3.3	M	73	29	**FD 15**	40	77	36	**FA 15**	40	77	36
3.7	**BX 112M 4**	1760	20	6.7	89.5	89.5	89.1	0.77	10.4	4.7	3.4	M	130	38	**FD 06S**	60	139	48	**FA 06S**	60	139	50
5.5	**BX 132SB 4**	1770	30	9.9	91.7	92.0	90.2	0.76	10.7	5.1	4.6	N	410	77	**FD 56**	75	420	90	**FA 06**	75	420	91
7.5	**BX 132MA 4**	1770	41	13.4	91.7	91.3	89.7	0.76	11.0	4.9	4.4	N	410	77	**FD 06**	100	420	90	**FA 07**	100	420	95
9.2	**BX 160MA 4**	1770	50	15.6	92.4	92.5	91.6	0.8	9.1	4.1	2.6	L	650	95	**FD 08**	170	725	125	**FA 08**	170	725	124
11	**BX 160MB 4**	1770	59	18.2	92.4	92.9	92.0	0.82	9.3	4.0	2.4	L	780	110	**FD 08**	170	855	140	**FA 08**	170	855	139
15	**BX 160L 4**	1770	81	24.5	93.0	93.5	92.5	0.81	10.9	4.8	2.8	M	890	121	**FD 08**	200	965	151	**FA 08**	200	965	150
18.5	**BX 180M 4**	1780	99	28.6	93.6	94.5	93.2	0.85	13.0	2.9	2.7	N	1560	155	**FD 09**	300	1760	195				
22	**BX 180L 4**	1775	118	33.1	93.6	94.2	93.1	0.87	11.5	2.8	2.4	M	1660	163	**FD 09**	300	1860	203				

Note: for more details on the available energy certifications look at the catalog's dedicated section.



4 P	1800 min^{-1} - S1	60 Hz - Nema Premium



															d.c. brake				a.c. brake			
															FD				FA			
P_n kW		n min^{-1}	M_n Nm	In 460V A	η% 100%	η% 75%	η% 50%	cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	KVA code	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	J_m x 10^{-4} kgm^2	IM B5 Kg
30	**BX 200LAK 4**	1786	160	47.9	94.7	94.8	94.1	0.83	9.4	3.3	3.7	N/A	3660	319	**FD 8**	400	3940	337				
37	**BX 225SAK 4**	1784	198	57.3	95.3	95.5	94.9	0.85	8.8	2.9	3.4	N/A	5360	398	**FD 9**	600	5720	426				
45	**BX 225SBK 4**	1785	240	70.5	95.3	95.4	94.8	0.84	8.9	3	3.6	N/A	5360	398	**FD 9**	600	5720	426				
55	**BX 250MAK 4**	1787	293	85.8	95.7	95.8	95.2	0.84	9.1	3.3	3.7	N/A	9330	476	**FD 10**	800	10080	521				
75	**BX 280SAK 4**	1788	401	117	95.9	95.7	94.7	0.84	8.4	2.7	3.1	N/A	15000	665	**FD 1000**	1000	15360	771				
90	**BX 280SBK 4**	1788	481	140	96.1	95.9	95	0.84	9	3.1	3.3	N/A	18500	725	**FD 1000**	1000	18860	831				
110	**BX 315SAK 4**	1792	586	172	96.1	96	95.3	0.84	8.8	2.6	3.4	N/A	29000	1000	**FD 1000**	1000	29360	1106				
132	**BX 315SBK 4**	1791	704	206	96.4	96.3	95.6	0.84	9	2.8	3.6	N/A	32000	1065	**FD 1600**	1600	32500	1233				
160	**BX 315SCK 4**	1791	853	241	96.4	96.4	95.9	0.86	9	2.9	3.3	N/A	39000	1220	**FD 1600**	1600	39500	1388				
200	**BX 355SAK 4**	1792	1065	301	96.4	96.2	95.4	0.87	8.3	2.2	3	N/A	59000	1610	**FD 2500**	2500	59500	1778				
250	**BX 355MAK 4**	1792	1332	381	96.7	96.6	96	0.86	8.8	2.7	3.2	N/A	69000	1780	**FD 2500**	2500	69500	1948				
315	**BX 355MBK 4**	1791	1679	479	96.7	96.6	96.1	0.85	8.5	3.1	3.2	N/A	72000	1820	**FD 2500**	2500	72500	1988				
355	**BX 355MCK 4**	1792	1893	541	96.7	96.5	96.9	0.86	7.2	2.4	3.1	N/A	84000	2140	**FD 2500**	2500	84500	2308				

Note: for more details on the available energy certifications look at the catalog's dedicated section.

4 P	1500 min^{-1} - S1	50 Hz - IE3

															d.c. brake				a.c. brake			
															FD				FA			
P_n kW		n min^{-1}	M_n Nm	In 400V A	η% 100%	η% 75%	η% 50%	cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	KVA code	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	J_m x 10^{-4} kgm^2	IM B5 Kg
0.75	**MX 2SB 4**	1425	5.0	1.61	82.5	83.9	83.2	0.81	6.5	2.0	1.8	J	35	16	**FD 04**	15	37	19.9	**FA 04**	15	37	19.8
1.1	**MX 3SA 4**	1445	7.3	2.46	84.1	85.5	83.5	0.75	6.7	3.0	2.0	J	35	17	**FD 15**	15	26	24	**FA 15**	15	26	24
1.5	**MX 3SB 4**	1445	9.9	3.3	85.3	86.8	85.4	0.75	6.7	3.1	2.0	J	43	20	**FD 15**	26	47	27	**FA 15**	26	47	27
2.2	**MX 3LA 4**	1445	14.5	5.1	86.7	86.2	84.0	0.72	7.2	3.6	2.4	K	58	24	**FD 15**	40	62	31	**FA 15**	40	62	31
3	**MX 3LB 4**	1445	19.8	6.7	87.7	87.7	86.0	0.74	7.6	3.9	2.6	K	73	29	**FD 15**	40	77	36	**FA 15**	40	77	36
4	**MX 4SA 4**	1460	26	7.8	88.6	89.9	88.7	0.82	8.1	3.7	2.5	J	225	45	**FD 56**	75	235	58	**FA 06**	75	235	59
5.5	**MX 4SB 4**	1460	36	10.6	89.6	89.9	88.8	0.83	8.2	3.6	2.3	J	310	57	**FD 56**	75	320	70	**FA 06**	75	320	71
7.5	**MX 4LA 4**	1460	49	15.0	90.4	90.9	90.2	0.80	8.4	3.8	2.5	K	360	67	**FD 06**	100	370	80	**FA 07**	100	370	85
9.2	**MX 5SA 4**	1465	60	17.8	91.0	92.1	91.7	0.82	7.9	3.6	2.1	J	650	95	**FD 08**	170	725	125	**FA 08**	170	725	124
11	**MX 5SB 4**	1465	72	20.5	91.4	92.9	92.5	0.84	7.8	3.4	1.9	J	780	110	**FD 08**	170	855	140	**FA 08**	170	855	139
15	**MX 5LA 4**	1465	98	28.1	92.1	93.2	92.6	0.82	9.0	4.1	2.3	K	890	121	**FD 08**	200	965	151	**FA 08**	200	965	150



4 P	1800 min^{-1} - S1	60 Hz - IE3



															d.c. brake				a.c. brake			
															FD				FA			
P_n kW		n min^{-1}	M_n Nm	In 460V A	η% 100%	η% 75%	η% 50%	cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	KVA code	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	J_m x 10^{-4} kgm^2	IM B5 Kg
0.75	**MX 2SB 4**	1755	4.1	1.48	85.5	86.4	83.9	0.73	8.0	3.7	2.5	L	27	16	**FD 14**	15	29	20.2	**FA 14**	15	29	20.1
1.1	**MX 3SA 4**	1755	6.0	2.19	86.5	86.0	83.0	0.73	7.9	3.3	2.5	L	35	17	**FD 15**	15	26	24	**FA 15**	15	26	24
1.5	**MX 3SB 4**	1755	8.2	2.96	86.5	87.2	85.0	0.72	8.5	3.7	2.9	L	43	20	**FD 15**	26	47	27	**FA 15**	26	47	27
2.2	**MX 3LA 4**	1760	11.9	4.4	89.5	88.6	86.2	0.71	9.9	4.8	3.6	N	73	29	**FD 15**	40	77	36	**FA 15**	40	77	36
3	**MX 3LB 4**	1750	16.4	5.9	89.5	88.9	86.7	0.71	9.1	4.4	3.3	M	73	29	**FD 15**	40	77	36	**FA 15**	40	77	36
3.7	**MX 4SA 4**	1770	20.0	6.6	89.5	89.8	87.7	0.78	9.9	4.7	3.4	M	225	45	**FD 56**	75	235	58	**FA 06**	75	235	59
5.5	**MX 4SB 4**	1770	30	9.9	91.7	92.0	90.2	0.76	10.7	5.1	4.6	N	410	77	**FD 56**	75	420	90	**FA 06**	75	420	91
7.5	**MX 4LA 4**	1770	41	13.4	91.7	91.3	89.7	0.76	11.0	4.9	4.4	N	410	77	**FD 06**	100	420	90	**FA 07**	100	420	95
9.2	**MX 5SA 4**	1770	50	15.6	92.4	92.5	91.6	0.8	9.1	4.1	2.6	L	650	95	**FD 08**	170	725	125	**FA 08**	170	725	124
11	**MX 5SB 4**	1770	59	18.2	92.4	92.9	92.0	0.82	9.3	4.0	2.4	L	780	110	**FD 08**	170	855	140	**FA 08**	170	855	139
15	**MX 5LA 4**	1770	81	24.5	93.0	93.5	92.5	0.81	10.9	4.8	2.8	M	890	121	**FD 08**	200	965	151	**FA 08**	200	965	150

BX - IM B5 - CE/CCC



	Shaft					Flange						Motor							
	D DA	E EA	DB	GA GC	F FA	M	N	P	S	T	LA	AC	L	LB	LC	AD	AF	LL	V
BX 80 B	19 14(1)	40 30(1)	M6 M5(1)	21.5 16(1)	6 5(1)	165	130	200	11.5	3.5	11.5	156	320	280	351	119	74	80	38
BX 90 S	24 19(1)	50 40(1)	M8 M6(1)	27 21.5 (1)	8 6(1)							176	326	276	368	133	98	98	44
BX 90 LA																			
BX 100 LA	28 24(1)	60 50(1)	M10 M8(1)	31 27(1)	8 8(1)	215	180	250	14	4	14	195	410	350	462	142			50
BX 100 LB																			
BX 112 M											15	219	430	370	482	157			52
BX 132 SB	38 28(1)	80 60(1)	M12 M10(1)	41 31(1)	10 8(1)	265	230	300			20	258	493	413	556	193	118	118	58
BX 132 MA													528	448	591				
BX 160 MA	42 38(1)	110 80(1)	M16 M12(1)	45 41(1)	12 10(1)	300	250	350	18.5	5	15	310	596	486	680	245	187	187	51
BX 160 MB													640	530	724				
BX 160 L																			
BX 180 M	48 42(1)	110 110(1)	M16 M16(1)	51.5 45(1)	14 12(1)						18	348	708	598	823	261			52
BX 180 L																			
BX 200LA	55 45(1)	M20 M20(1)		59 48.5(1)	16 14(1)	350	300	400	19		20	423	821	711	934	328	300	311	55
BX 225SA	60 55(1)	140 110(1)		64 59(1)	18 16(1)	400	350	450				465	879	739	1001	348			48
BX 225SB																			
BX 250MA	65 55(1)			69 59(1)		500	450	550			24	514	884	744	1010	376			
BX 280SA	75 65(1)	140 140(1)		79.5 69(1)	20 18(1)				18		23	567	1088	948	1238	482	434	306	43
BX 280SB																			
BX 315SA	80 75(1)	170 140(1)		85 79.5(1)	22 20(1)	600	550	660	23	6	25	645	1204	1034	1352	537	473	347	42
BX 315SB																			
BX 315SC																			
BX 315MA	90 75(1)		M24 M20(1)	95 79.5(1)	25 20(1)								1315	1145	1463				
BX 355MA	100 75(1)	210 170(1)		106 79.5(1)	28 20(1)	740	680	800				740	1479	1269	1659	603	694	413	50
BX 355MB																			
BX 355MC																			

N.B.: 1) These values refer to the rear shaft end (PS).



BX - IM B5 - FD/FA - CE/CCC



	Shaft					Flange						Motor								R		ES (2)
	D DA	E EA	DB	GA GC	F FA	M	N	P	S	T	LA	AC	L	LB	LC	AD	AF	LL	V	FD	FA	
BX 80 B	19 14(1)	40 30(1)	M6 M5(1)	21.5 16(1)	6 5(1)	165	130	200	11.5	3.5	11.5	156	392	352	423	143	98	133	25	129	134	5
BX 90 S	24 19(1)	50 40(1)	M8 M6(1)	27 21.5 (1)	8 6(1)							176	410	360	452	146	110	165	32			6
BX 90 LA																				160	160	
BX 100 LA	28 24(1)	60 50(1)	M10 M8(1)	31 27(1)	8 8(1)	215	180	250	14	4	14	195	502	442	554	155			37			
BX 100 LB																						
BX 112 M											15	219	527	467	579	170			39	199	198	
BX 132 SB	38 28(1)	80 60(1)	M12 M10(1)	41 31(1)	10 8(1)	265	230	300			16	258	603	523	667	210	140	188	46	204	200	
BX 132 MA													627	547	690						226	
BX 160 MA	42 38(1)	110 80(1)	M16 M12(1)	45 41(1)	12 10(1)	300	250	350	18.5	5	15	310	736	626	820	245	187	187	51	266	247	—
BX 160 MB													780	670	864							
BX 160 L																						
BX 180 M	48 42(1)	110 110(1)	M16 M16(1)	51.5 45(1)	14 12(1)						18	348	866	756	981	261			52	305	—	
BX 180 L																						
BX 200LA	55 45(1)		M20 M20(1)	59 48.5(1)	16 14(1)	350	300	400	19	5	20	423	982	872	1095	328	300	311	55	275		
BX 225SA	60 55(1)	140 110(1)		64 59(1)	18 16(1)	400	350	450				465	1058	918	1180	348			48	308		
BX 225SB																						
BX 250MA	65 55(1)			69 59(1)		500	450	550			24	514	1099	959	1225	376				313		
BX 280SA	75 65(1)	140 140(1)		79.5 69(1)	20 18(1)				18		23	567	1340	1200	1490	482	434	306	43	500	—	
BX 280SB																						
BX 315SA	80 75(1)	170 140(1)		85 79.5(1)	22 20(1)	600	550	660	23	6	25	645	1452	1282	1600	537	473	347	42			
BX 315SB													1497	1327	1645							
BX 315SC																						
BX 315MA	90 75(1)		M24 M20(1)	95 79.5(1)	25 20(1)								1607	1437	1755							
BX 355MA	100 75(1)	210 170(1)		106 79.5(1)	28 20(1)	740	680	800				740	1790	1580	1970	603	694	413	50	—		
BX 355MB													1825	1615	2005							
BX 355MC																						

N.B.: 1) These values refer to the rear shaft end (PS). 2) “ES” hexagon is not present with PS option

BX - IM B5 - CUS/NBR/EECA



	Shaft					Flange						Motor							
	D DA	**E EA**	**DB**	**GA GC**	**F FA**	**M**	**N**	**P**	**S**	**T**	**LA**	**AC**	**L**	**LB**	**LC**	**AD**	**AF**	**LL**	**V**
BX 90 SR	19 19(1)	40 40(1)	M6 M6(1)	21.5 21.5(1)	6 6(1)	165	130	200	11.5	3.5	11.5	176	316	276	358	133	98	98	44
BX 90 S	24 19(1)	50 40(1)	M8 M6(1)	27 21.5(1)	8 6(1)								326		368				
BX 90 LA																			
BX 100 LA	28 24(1)	60 50(1)	M10 M8(1)	31 27(1)	8 8(1)	215	180	250	14	4	14	195	410	350	462	142			50
BX 100 LB																			
BX 112 M											15	219	430	370	482	157			52
BX 132 SB	38 28(1)	80 60(1)	M12 M10(1)	41 31(1)	10 8(1)	265	230	300			20	258	552	472	615	193	118	118	58
BX 132 MA																			
BX 160 MA	42 38(1)	110 80(1)	M16 M12(1)	45 41(1)	12 10(1)	300	250	350	18.5	5	15	310	596	486	680	245	187	187	51
BX 160 MB													640	530	724				
BX 160 L																			
BX 180 M	48 42(1)	110 110(1)	M16 M16(1)	51.5 45(1)	14 12(1)						18	348	708	598	823	261			52
BX 180 L																			
BX 200LAK	55 45(1)	110 110(1)	M20 M20(1)	59 48.5(1)	16 14(1)	350	300	400	19	5	20	423	821	711	934	328	300	311	55
BX 225SAK	60 55(1)	140 110(1)	M20 M20(1)	64 59(1)	18 16(1)	400	350	450	19	5	20	465	879	739	1001	348	300	311	48
BX 225SBK																			
BX 250MAK	65 55(1)	140 110(1)	M20 M20(1)	69 59(1)	18 16(1)	500	450	550	19	5	24	514	884	744	1010	376	300	311	
BX 280SAK	75 65(1)	140 140(1)	M20 M20(1)	79.5 69(1)	20 18(1)	500	450	550	18	5	23	567	1088	948	1238	482	434	306	43
BX 280SBK																			
BX 315SAK	80 75(1)	170 140(1)	M20 M20(1)	85 79.5(1)	22 20(1)	600	550	660	23	6	25	645	1204	1034	1352	537	473	347	42
BX 315SBK																			
BX 315SCK													1315	1145	1453				
BX 355SAK	100 75(1)	210 170(1)	M24 M20(1)	106 79.5(1)	28 20(1)	740	680	800	23	6	25	740	1479	1269	1659	603	694	413	50
BX 355MAK																			
BX 355MBK																			
BX 355MCK													1584	1374	1764				

N.B.: 1) These values refer to the rear shaft end (PS).



BX - IM B5 - FD/FA - CUS/NBR/EECA



	Shaft					Flange						Motor										
	D DA	E EA	DB	GA GC	F FA	M	N	P	S	T	LA	AC	L	LB	LC	AD	AF	LL	V	R FD	R FA	ES (2)
BX 90 SR	19 19(1)	40 40(1)	M6 M6(1)	21.5 21.5(1)	6 6(1)	165	130	200	11.5	3.5	11.5	176	400	360	442	146	110	165	32	129	134	6
BX 90 S	24 19(1)	50 40(1)	M8 M6(1)	27 21.5(1)	8 6(1)								410		452							
BX 90 LA																				160	160	
BX 100 LA	28 24(1)	60 50(1)	M10 M8(1)	31 27(1)	8 8(1)	215	180	250	14	4	14	195	502	442	554	155			37			
BX 100 LB																						
BX 112 M											15	219	527	467	579	170			39	199	198	
BX 132 SB	38 28(1)	80 60(1)	M12 M10(1)	41 31(1)	10 8(1)	265	230	300			16	258	661	581	724	210	140	188	46	204	200	
BX 132 MA																					226	
BX 160 MA	42 38(1)	110 80(1)	M16 M12(1)	45 41(1)	12 10(1)	300	250	350	18.5	5	15	310	736	626	820	245	187	187	51	266	247	—
BX 160 MB													780	670	864							
BX 160 L																						
BX 180 M	48 42(1)	110 110(1)	M16 M16(1)	51.5 45(1)	14 12(1)						18	348	866	756	981	261			52	305	—	
BX 180 L																						
BX 200LAK	55 45(1)		M20 M16(1)	59 48.5(1)	16 14(1)	350	300	400	19	5	20	417	967	857	1082	328	300	311	55	275		
BX 225SAK	60 55(1)	140 110(1)	M20 M20(1)	64 59(1)	18 16(1)	400	350	450				460	1065	925	1180	348			48	308		
BX 225SBK																						
BX 250MAK	65 55(1)			69 59(1)		500	450	550			24	510	1070	930	1240	376				313		
BX 280SAK	75 65(1)	140 140(1)		79.5 69(1)	20 18(1)				18		23	564	1284	1144	1379	482	434	306	43	500	—	
BX 280SBK																						
BX 315SAK	80 75(1)	170 140(1)		85 79.5(1)	22 20(1)	600	550	660	23	6	25	639	1493	1323	1643	537	473	347	42			
BX 315SBK													1530	1360	1680							
BX 315SCK													1604	1434	1791							
BX 355SAK	100 90(1)	210 170(1)	M24 M24(1)	106 95(1)	28 25(1)	740	680	800				725	1722	1512	1902	603	694	413	50	—		
BX 355MAK																						
BX 355MBK																						
BX 355MCK													1827	1617	2082							

N.B.: 1) These values refer to the rear shaft end (PS). 2) “ES” hexagon is not present with PS option

MX



	Rear shaft end					Motor						
	DA	**EA**	**DB**	**GC**	**FA**	**AC**	**LB**	**LC**	**AF**	**LL**	**J**	**AD**
MX 2SB	14	30	M5	16	5	156	246	278	74	80	44	119
MX 3SA	24	50	M8	27	8	195	265	317	98	98	53.5	142
MX 3SB												
MX 3LA							305	357				
MX 3LB												
MX 4SA	28	60	M10	31		258	361	424	118	118	64.5	193
MX 4SB												
MX 4LA							396	459				
MX 5SA	38	80	M12	41	10	310	418	502	187	187	77	245
MX 5SB							462	546				
MX 5LA												

MX_FD/FA



	Rear shaft end					Motor									
	DA	**EA**	**DB**	**GC**	**FA**	**AC**	**LB**	**LC**	**AF**	**LL**	**J**	**AD**	**R FD**	**R FA**	**ES** [1]
MX 2SB	14	30	M5	16	5	156	318	349	98	133	9	143	129	134	5
MX 3SA	24	50	M8	27	8	195	355	407	110	165	7	155	160	160	6
MX 3SB															
MX 3LA							397	450							
MX 3LB															
MX 4SA	28	60	M10	31		258	470	534	140	188		210	204	200	
MX 4SB															
MX 4LA							494	558						226	
MX 5SA	38	80	M12	41	10	310	558	644	187	187	17	245	266	247	—
MX 5SB							602	686							
MX 5LA															

N.B.:
1) “ES” hexagon is not present with PS option

MX CUS



	Rear shaft end					Motor						
	DA	**EA**	**DB**	**GC**	**FA**	**AC**	**LB**	**LC**	**AF**	**LL**	**J**	**AD**
MX 2SB	14	30	M5	16	5	176	262	293	98	98	79	133
MX 3SA	24	50	M8	27	8	195	265	317			53.5	142
MX 3SB												
MX 3LA							305	357				
MX 3LB												
MX 4SA	28	60	M10	31		258	361	424	118	118	64.5	193
MX 4SB							420	483				
MX 4LA												
MX 5SA	38	80	M12	41	10	310	418	502	187	187	77	245
MX 5SB							462	546				
MX 5LA												

MX_FD/FA CUS



	Rear shaft end					Motor									
	DA	**EA**	**DB**	**GC**	**FA**	**AC**	**LB**	**LC**	**AF**	**LL**	**J**	**AD**	**R FD**	**R FA**	**ES** [1]
MX 2SB	14	30	M5	16	5	176	347	379	110	165	-17	146	129	134	6
MX 3SA	24	50	M8	27	8	195	355	407			7	155	160	160	
MX 3SB															
MX 3LA							397	450							
MX 3LB															
MX 4SA	28	60	M10	31		258	470	534	140	188		210	204	200	
MX 4SB							528	592							
MX 4LA														226	
MX 5SA	38	80	M12	41	10	310	558	644	187	187	17	245	266	247	—
MX 5SB							602	686							
MX 5LA															

N.B.:
1) “ES” hexagon is not present with PS option

2 P	3000 min^{-1} - S1	50 Hz - IE2

A068744

														d.c. brake						a.c. brake				
														FD						FA				
P_n kW		n min^{-1}	M_n Nm	In 400V A	η% 100%	η% 75%	η% 50%	cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	Z_o 1/h NB	Z_o 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	Z_o 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.75	**BE 80A**	**2**	2860	2.5	1.65	80	79.6	76.4	0.83	6.8	3.8	3.5	9	9.5	**FD 04**	5	1700	3200	9.4	13.4	**FA 04**	5	3200	9.4	13.3
1.1	**BE 80B**	**2**	2845	3.7	2.35	81.5	82.2	79.9	0.83	6.9	3.8	3.1	11.4	11.3	**FD 04**	10	1500	3000	10.6	15.2	**FA 04**	10	3000	10.6	15.1
1.5	**BE 90SA**	**2**	2865	5	3.2	81.3	80.7	78.1	0.82	6.8	3.6	2.8	12.5	12.3	**FD 14**	15	900	2200	14.1	16.5	**FA 14**	15	2200	14.1	16.4
2.2	**BE 90L**	**2**	2870	7.3	4.7	83.2	83.1	80.8	0.82	6.9	3.1	2.9	16.7	14	**FD 05**	26	900	2200	21	20	**FA 05**	26	2200	21	20.7
3	**BE 100L**	**2**	2880	9.9	6.2	84.6	84.6	83.7	0.83	7.3	3.5	3.1	39	23	**FD 15**	26	700	1600	35	29	**FA 15**	26	1600	35	30
4	**BE 112M**	**2**	2920	13.1	8.2	85.8	85.5	84.3	0.82	7.9	3.5	3.1	57	28	**FD 06S**	40	—	950	66	39	**FA 06S**	40	950	66	40
5.5	**BE 132SA**	**2**	2925	18	10.6	87	85	81.7	0.86	8.5	3.6	3.3	145	42	**FD 06**	50	—	600	112	55	**FA 06**	50	600	112	56
7.5	**BE 132SB**	**2**	2935	24	14.3	88.1	87.4	84.7	0.86	8.8	3.9	3.6	178	53	**FD 06**	50	—	550	154	66	**FA 06**	50	550	154	67
9.2	**BE 132MB**	**2**	2920	30	16.4	88.8	86.5	84.2	0.91	8.4	3.7	3.3	210	65	**FD 56**	75	—	430	189	78	**FA 06**	75	430	189	79
11	**BE 160MA**	**2**	2940	36	20	89.4	89.5	88	0.89	8.1	3	2.9	340	84	—	—	—	—	—	—	—	—	—	—	—
15	**BE 160MB**	**2**	2950	49	27.2	90.5	90.5	89.5	0.88	8.5	3	2.8	420	97	—	—	—	—	—	—	—	—	—	—	—
18.5	**BE 160L**	**2**	2945	60	32	90.9	90.5	89.8	0.91	7.7	2.9	2.7	490	109	—	—	—	—	—	—	—	—	—	—	—

4 P	1500 min^{-1} - S1	50 Hz - IE2



A068744

															d.c. brake						a.c. brake				
															FD						FA				
P_n kW		n min^{-1}	M_n Nm	In 400V A	η% 100%	η% 75%	η% 50%	cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	Z_O 1/h NB	Z_O 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	Z_O 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.12	**BE 63A 4**	1360	0.84	0.45	59.1	59.6	53.5	0.65	3	2	2.2	2.3	3.5	**FD 02**	1.75	10000	13000	2.6	5.2	**FA 02**	1.75	13000	2.6	5
0.18	**BE 63B 4**	1370	1.25	0.64	64.7	65.1	59.8	0.62	3.5	2.3	2.5	3.3	5.1	**FD 02**	3.5	10000	13000	3	5.6	**FA 02**	3.5	13000	3	5.4
0.25	**BE 71A 4**	1380	1.73	0.68	68.5	68	62	0.78	4	2.3	2.5	5.8	5.1	**FD 03**	3.5	7700	11000	6.9	7.8	**FA 03**	3.5	11000	6.9	7.5
0.37	**BE 71B 4**	1385	2.55	1.05	72.7	69.3	64.2	0.75	4.0	2.3	2.2	6.9	5.9											
0.55	**BE 80A 4**	1430	3.7	1.38	77.1	73.4	68	0.77	6	2.2	1.9	15	8.2	**FD 04**	10	4100	8000	16.6	13.8	**FA 04**	10	8000	16.6	13.7
0.75	**BE 80B 4**	1430	5	1.76	79.6	78.5	75.1	0.78	6.1	3.2	3	28	12.2	**FD 04**	15	4100	7800	22	16.1	**FA 04**	15	7800	22	16
1.1	**BE 90S 4**	1430	7.4	2.53	81.4	82	79.5	0.76	6.3	2.9	2.8	28	13.6	**FD 14**	15	4800	8000	32	17.8	**FA 14**	15	8000	32	17.7
1.5	**BE 90LA 4**	1430	10	3.5	82.8	83	80	0.74	5.9	3.1	3	34	15.1	**FD 05**	26	3400	6000	34	21.1	**FA 05**	26	6000	34	21.8
2.2	**BE 100LA 4**	1430	14.7	4.9	84.3	85	84	0.76	5.8	3	2.8	54	22	**FD 15**	40	2600	4700	44	29	**FA 15**	40	4700	44	29
3	**BE 100LB 4**	1420	20	6.6	85.5	86	85.5	0.77	5.9	2.8	2.6	61	24	**FD 15**	40	2400	4400	58	31	**FA 15**	40	4400	58	31
4	**BE 112M 4**	1440	27	8.3	86.6	87	86	0.8	6.5	2.8	2.8	105	32	**FD 06S**	60	—	1400	107	42	**FA 06S**	60	2100	107	44
5.5	**BE 132S 4**	1460	36	11.1	88.5	88.5	87.5	0.81	7.3	2.9	2.9	270	53	**FD 56**	75	—	1050	223	66	**FA 06**	75	1200	223	67
7.5	**BE 132MA 4**	1460	49	14.8	89	89	88.5	0.82	6.9	2.9	2.8	319	59	**FD 06**	100	—	950	280	72	**FA 06**	100	1000	280	77
9.2	**BE 132MB 4**	1460	60	18.1	89.5	89.5	88.5	0.82	6.9	2.9	3	360	70	**FD 07**	150	—	900	342	86	**FA 07**	150	900	342	87
11	**BE 160M 4**	1465	72	21.5	91	91.3	90.5	0.81	6.5	2.8	2.6	650	99	**FD 08**	170	—	800	655	129	**FA 08**	170	800	655	128
15	**BE 160L 4**	1465	98	28.7	90.8	91	90.5	0.83	6.5	2.6	2.3	790	115	**FD 08**	200	—	750	725	129	**FA 08**	200	750	710	128
18.5	**BE 180M 4**	1465	121	35	91.6	92	91.3	0.83	6.5	2.6	2.5	1250	135	**FD 09**	300	—	400	1450	175	—	—	—	—	—
22	**BE 180L 4**	1465	143	41	91.6	91.8	91.4	0.84	6.8	2.7	2.6	1650	157	**FD 09**	300	—	300	1850	197	—	—	—	—	—

6 P	1000 min^{-1} - S1	50 Hz - IE2

A068744

														d.c. brake						a.c. brake				
														FD						FA				
P_n		n	M_n	In 400V	η%			cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	J_m x 10^{-4}	IM B5	Mod	M_b	Z_O 1/h		J_m x 10^{-4}	IM B5	Mod	M_b	Z_O 1/h	J_m x 10^{-4}	IM B5
kW		min^{-1}	Nm	A	100%	75%	50%					kgm^2	Kg		Nm	NB	SB	kgm^2	Kg		Nm		kgm^2	Kg
0.75	**BE 90S 6**	935	7.7	2.06	75.9	75.9	73	0.69	5.1	3.1	2.9	33	15	**FD 14**	15	3400	6500	28	19.2	**FA 14**	15	6500	28	19.1
1.1	**BE 100M 6 (*)**	945	11.1	2.75	78.1	76.2	73	0.74	4.9	2.2	1.9	82	22	**FD 15**	26	2500	4800	58	30	**FA 15**	26	4800	58	31
1.5	**BE 100LA 6**	945	15.2	3.9	79.8	77.5	74	0.72	5.6	2.5	2.3	95	24	**FD 15**	40	1900	4100	86	30	**FA 15**	40	4100	86	31
2.2	**BE 112M 6**	950	22	5.2	81.8	81.8	79.3	0.74	5.2	2.6	2.3	168	32	**FD 06S**	60	—	2100	177	42	**FA 06S**	60	2100	177	44
3	**BE 132S 6**	955	30	6.6	83.3	83.3	82.4	0.79	6.1	2.1	1.9	295	44	**FD 56**	75	—	1400	226	57	**FA 06**	75	1400	226	58
4	**BE 132MA 6**	965	40	8.7	84.6	85	83.1	0.79	6.9	2.2	2	383	56	**FD 06**	100	—	1200	305	69	**FA 07**	100	1200	318	74
5.5	**BE 160MA 6 (*)**	965	54	11.6	87	87	86.4	0.79	6.6	2.5	2.3	740	83	**FD 08**	170	—	1000	700	112	**FA 08**	170	1000	700	113
7.5	**BE 160MB 6 (*)**	965	74	15	88	88	87.2	0.82	6.6	2.3	2.1	970	103	**FD 08**	170	—	900	815	132	**FA 08**	170	900	815	133

(*) Power /size relation not standardized



2 P	3000 min^{-1} - S1	50 Hz - IE2



														d.c. brake						a.c. brake				
														FD						FA				
P_n kW		n min^{-1}	M_n Nm	In 400V A	η% 100%	η% 75%	η% 50%	cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	Z_O 1/h NB	Z_O 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	Z_O 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.75	**BE 80A 2**	2860	2.5	1.65	80	79.6	76.4	0.83	6.8	3.8	3.5	9	9.5	**FD 04**	5	1700	3200	9.4	12.5	**FA 04**	5	3200	9.4	12.4
1.1	**BE 80B 2**	2845	3.7	2.35	81.5	82.2	79.9	0.83	6.9	3.8	3.1	11.4	11.3	**FD 04**	10	1500	3000	10.6	13.4	**FA 04**	10	3000	10.6	13.3
1.5	**BE 90SA 2**	2865	5	3.2	81.3	80.7	78.1	0.82	6.8	3.6	2.8	12.5	12.3	**FD 14**	15	900	2200	14.1	16.5	**FA 14**	15	2200	14.1	16.4
2.2	**BE 90L 2**	2870	7.3	4.7	83.2	83.1	80.8	0.82	6.9	3.1	2.9	16.7	14	**FD 05**	26	900	2200	21	20	**FA 05**	26	2200	21	20.7
3.7	**BE 112M 2**	2930	12.1	7.8	85.5	83	81.2	0.79	7.9	3.5	3.1	57	28	**FD 06S**	40	—	950	66	39	**FA 06S**	40	950	66	40

4 P	1500 min^{-1} - S1	50 Hz - IE2

														d.c. brake						a.c. brake				
														FD						FA				
P_n kW		n min^{-1}	M_n Nm	In 400V A	η% 100%	η% 75%	η% 50%	cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	Z_O 1/h NB	Z_O 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	Z_O 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.37	**BE 71B 4**	1385	2.55	1.05	72.7	69.3	64.2	0.75	4.0	2.3	2.2	6.9	5.9	**FD 03**	5	6000	9400	8	8.6	**FA 03**	5	9400	8	8.3
0.55	**BE 80A 4**	1430	3.7	1.38	77.1	73.4	68	0.77	6	2.2	1.9	15	9.9	**FD 04**	10	4100	8000	16.6	13.8	**FA 04**	10	8000	16.6	13.7
0.75	**BE 80B 4**	1430	5	1.76	79.6	78.5	75.1	0.78	6.1	3.2	3	28	12.2	**FD 04**	15	4100	7800	22	16.1	**FA 04**	15	7800	22	16
1.1	**BE 90S 4**	1430	7.4	2.53	81.4	82	79.5	0.76	6.3	2.9	2.8	28	13.6	**FD 14**	15	4800	8000	32	17.8	**FA 14**	15	8000	32	17.7
1.5	**BE 90LA 4**	1430	10	3.5	82.8	83	80	0.74	5.9	3.1	3	34	15.1	**FD 05**	26	3400	6000	34	21.1	**FA 05**	26	6000	34	21.8
2.2	**BE 100LA 4**	1430	14.7	4.9	84.3	85	84	0.76	5.8	3	2.8	54	22	**FD 15**	40	2600	4700	44	29	**FA 15**	40	4700	44	29
3.7	**BE 112M 4**	1445	27	8.2	86.3	87	84.3	0.76	6.5	2.8	2.8	105	32	**FD 06S**	60	—	1400	107	42	**FA 06S**	60	2100	107	44



6 P	1000 min^{-1} - S1	50 Hz - IE2



														d.c. brake						a.c. brake				
														FD						FA				
P_n kW		n min^{-1}	M_n Nm	In 400V A	η% 100%	η% 75%	η% 50%	cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	Z_O 1/h NB	Z_O 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	Z_O 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.75	**BE 90S 6**	935	7.7	2.06	75.9	75.9	73	0.69	5.1	3.1	2.9	33	15	**FD 14**	15	3400	6500	28	16.8	**FA 14**	15	6500	28	16.7
1.1	**BE 100M 6 (*)**	945	11.1	2.75	78.1	76.2	73	0.74	4.9	2.2	1.9	82	22	**FD 15**	40	1900	4100	86	28	**FA 15**	40	4100	86	29
1.5	**BE 100LA 6**	945	15.2	3.9	79.8	77.5	74	0.72	5.6	2.5	2.3	95	24	**FD 15**	40	1700	3600	99	30	**FA 15**	40	3600	99	31
2.2	**BE 112M 6**	950	22	5.2	81.8	81.8	79.3	0.74	5.2	2.6	2.3	168	32	**FD 06S**	60	—	2100	177	42	**FA 06S**	60	2100	177	44
3.7	**BE 132MA 6**	970	36.1	8.3	84.3	83.6	81.3	0.76	6.9	2.2	2	383	56	**FD 06**	100	—	1200	305	58	**FA 07**	100	1200	318	63

(*) Power /size relation not standardized

4 P	1800 min^{-1} - S1	60 Hz - IE2

c UL us

P_n				n	M_n	In 400V	η%			cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	KVA Code	J_m x 10^{-4}	IM B5	d.c. brake FD						a.c. brake FA				
																	Mod	M_b	Z_O 1/h		J_m x 10^{-4}	IM B5	Mod	M_b	Z_O 1/h	J_m x 10^{-4}	IM B5
HP	kW			min^{-1}	Nm	A	100%	75%	50%						kgm^2	Kg		Nm	NB	SB	kgm^2	Kg		Nm		kgm^2	Kg
0.75	0.55	**BE 80A**	**4**	1740	3	1.23	75.5	73.1	66.8	0.74	8.7	3.8	3.0	N	19	9.9	**FD 04**	10	4100	8000	16.6	13.8	**FA 04**	10	8000	16.6	13.7
1	0.75	**BE 80B**	**4**	1745	4.1	1.46	82.5	81.1	77.6	0.78	7.6	3.5	3.2	K	28	12.2	**FD 04**	15	4100	7800	22	16.1	**FA 04**	15	7800	22	16
1.5	1.1	**BE 90S**	**4**	1740	6	2.25	84	82.7	79	0.73	7.7	3.5	3.2	L	28	13.6	**FD 14**	15	4800	8000	32	17.8	**FA 14**	15	8000	32	17.7
2	1.5	**BE 90LA**	**4**	1740	8.2	3.1	84.5	83.9	80.7	0.73	7.1	3.6	3.4	K	34	15.1	**FD 05**	26	3400	6000	34	21.1	**FA 05**	26	6000	34	21.8
3	2.2	**BE 100LA**	**4**	1745	12	4.2	87.5	85.5	83.2	0.76	7	3.3	2.9	J	54	22	**FD 15**	40	2600	4700	44	29	**FA 15**	40	4700	44	29
4	3	**BE 100LB**	**4**	1735	16.5	5.9	87.5	87.7	86.3	0.76	7	3.2	2.9	K	61	24	**FD 15**	40	2400	4400	58	31	**FA 15**	40	4400	58	31
5	3.7	**BE 112M**	**4**	1750	20	6.6	87.5	87.5	86.1	0.8	7.8	3.3	3.2	K	105	32	**FD 06S**	60	—	1400	107	42	**FA 06S**	60	2100	107	44
7.5	5.5	**BE 132S**	**4**	1760	30	9.3	89.5	89.5	87.7	0.83	8.7	3.5	3.5	K	270	53	**FD 56**	75	—	1050	223	66	**FA 06**	75	1200	223	67
10	7.5	**BE 132MA**	**4**	1760	43	12.7	89.5	89.5	87.9	0.83	8	3.4	3.3	K	319	59	**FD 06**	100	—	950	280	72	**FA 06**	100	1000	280	77
12.5	9.2	**BE 132MB**	**4**	1760	50	15.6	90	90	88.6	0.82	8.3	3.5	3.6	K	360	70	**FD 07**	150	—	900	342	86	**FA 07**	150	900	342	87
15	11	**BE 160M**	**4**	1765	60	18.7	91	91	90	0.81	7.7	2.9	2.8	J	650	99	**FD 08**	170	—	800	655	129	**FA 08**	170	800	655	128
20	15	**BE 160L**	**4**	1770	81	25.5	91	90.5	89.5	0.81	7.1	3.1	2.7	J	790	115	**FD 08**	200	—	750	725	129	**FA 08**	200	750	710	128
25	18.5	**BE 180M**	**4**	1765	100	30.3	92.4	91.9	90.5	0.83	7.3	2.7	2.5	H	1250	135	**FD 09**	300	—	400	1450	175	**—**	—	—	—	—
30	22	**BE 180L**	**4**	1770	119	36	92.4	92.5	92.2	0.83	8.1	3.3	3.2	J	1650	157	**FD 09**	300	—	300	1850	197	**—**	—	—	—	—



2 P	3000 min^{-1} - S1	50 Hz - IE2



A068744

															d.c. brake						a.c. brake				
															FD						FA				
P_n		n	M_n	In 400V	η%			cos φ	I_s/I_n	M_s/M_n	M_a/M_n	J_m x 10^{-4}	IM B5		Mod	M_b	Z_o 1/h		J_m x 10^{-4}	IM B5	Mod	M_b	Z_o 1/h	J_m x 10^{-4}	IM B5
kW		min^{-1}	Nm	A	100%	75%	50%					kgm^2	Kg			Nm	NB	SB	kgm^2	Kg		Nm		kgm^2	Kg
0.75	**ME 2SA 2**	2860	2.5	1.63	80	79.6	76.4	0.83	6.8	3.8	3.5	9	8.8		**FD 04**	5	1700	3200	9.4	12.7	**FA 04**	5	3200	9.4	12.6
1.1	**ME 2SB 2**	2845	3.7	2.35	81.5	82.2	79.9	0.83	6.9	3.8	3.1	11.4	10.6		**FD 04**	10	1500	3000	13	14.5	**FA 04**	10	3000	13	14.4
1.5	**ME 3SA 2**	2845	5.0	3.2	81.3	79	76	0.81	6.1	2.9	2.7	24	15.5		**FD 15**	13	1300	2600	22	22	**FA 15**	26	2600	22	23
2.2	**ME 3LA 2**	2895	7.3	4.7	83.2	83.1	80.8	0.82	6.9	2.7	2.5	31	18.7		**FD 15**	26	1100	2400	28	25.2	**FA 15**	26	2400	28	26.2
3	**ME 3LB 2**	2880	9.9	6.2	84.6	84.6	83.7	0.83	7.3	3.5	3.1	39	22		**FD 15**	26	700	1600	35	28.5	**FA 15**	26	1600	35	29.5
4	**ME 4SA 2**	2900	13.2	7.8	85.8	84.5	82.2	0.87	7.0	2.9	2.8	101	33		**FD 06**	50	—	1400	107	46	**FA 06**	50	2100	107	47
5.5	**ME 4SB 2**	2925	18.0	10.6	87.0	85.0	81.7	0.86	8.5	3.6	3.3	145	40		**FD 06**	50	—	600	112	48	**FA 06**	50	600	112	49
7.5	**ME 4LA 2**	2935	24	14.3	88.1	87.4	84.7	0.86	8.8	3.9	3.6	178	51		**FD 06**	50	—	550	154	55	**FA 06**	50	550	154	56
9.2	**ME 4LB 2**	2920	30	16.4	88.8	86.5	84.2	0.91	8.4	3.7	3.3	210	60		**FD 56**	75	—	430	189	66	**FA 06**	75	430	189	67
11	**ME 5SA 2**	2940	36	20.0	90.5	90.5	88.0	0.89	8.1	3.0	2.9	340	70												
15	**ME 5SB 2**	2950	49	27.2	90.9	90.5	89.5	0.88	8.5	3.0	2.8	420	83												
18.5	**ME 5LA 2**	2945	60	32	90.4	90.1	89.8	0.91	7.7	2.9	2.7	490	95												

4 P	1500 min^{-1} - S1	50 Hz - IE2

A068744

															d.c. brake						a.c. brake				
															FD						FA				
P_n		n	M_n	In 400V	η%			cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	J_m x 10^{-4}	IM B5	Mod	M_b	Z_O 1/h		J_m x 10^{-4}	IM B5	Mod	M_b	Z_O 1/h	J_m x 10^{-4}	IM B5
kW		min^{-1}	Nm	A	100%	75%	50%					kgm^2	Kg		Nm	NB	SB	kgm^2	Kg		Nm		kgm^2	Kg
0.12	ME 05A 4	1360	0.84	0.45	59.1	59.6	53.5	0.65	3	2	2.2	2.3	3.5	FD 02	1.75	10000	13000	2.6	5.2	FA 02	1.75	13000	2.6	5
0.18	ME 05B 4	1370	1.25	0.64	64.7	65.1	59.8	0.62	3.5	2.3	2.5	3.3	5.1	FD 02	3.5	10000	13000	3	5.6	FA 02	3.5	13000	3	5.4
0.25	ME 1SA 4	1380	1.73	0.68	68.5	68	62	0.78	4	2.3	2.5	5.8	5.1	FD 03	3.5	7700	11000	6.9	7.8	FA 03	3.5	11000	6.9	7.5
0.37	ME 1SB 4	1385	2.55	1.05	72.7	69.3	64.2	0.75	4.0	2.3	2.2	6.9	5.9	FD 03	5	6000	9400	8.0	8.6	FA 03	5	9400	8.0	8.3
0.55	ME 2SA 4	1430	3.7	1.38	77.1	73.4	68	0.77	6	2.2	1.9	15	9.9	FD 04	10	4100	8000	16.6	13.8	FA 04	10	8000	16.6	13.7
0.75	ME 2SB 4	1430	5	1.76	79.6	78.5	75.1	0.78	6.1	3.2	3.0	28	12.2	FD 04	15	4100	7800	22	16.1	FA 04	15	7800	22	16
1.1	ME 3SA 4	1430	7.4	2.53	82.5	82.0	79.5	0.76	6.3	2.9	2.8	28	15.5	FD 15	26	4800	8000	32	21.5	FA 15	26	8000	32	22.5
1.5	ME 3SB 4	1420	10	3.5	83.5	83.0	80.0	0.74	5.9	3.1	3.0	34	17	FD 15	26	3400	6000	34	23	FA 15	26	6000	34	24
2.2	ME 3LA 4	1430	14.7	4.9	84.3	85	84	0.76	5.8	3	2.8	54	21	FD 15	40	2600	4700	44	27	FA 15	40	4700	44	28
3	ME 3LB 4	1420	20	6.6	85.5	86.0	85.5	0.77	5.9	2.8	2.6	61	23	FD 15	40	2400	4400	58	29	FA 15	40	4400	58	30
4	ME 4SA 4	1440	27	8.3	87.0	87.0	86.0	0.80	6.5	2.8	2.8	105	42	FD 56	75	—	1400	107	55	FA 06	75	2100	107	56
5.5	ME 4SB 4	1460	36	11.1	88.5	88.5	87.5	0.81	7.3	2.9	2.9	270	51	FD 56	75	—	1050	223	64	FA 06	75	1200	223	65
7.5	ME 4LA 4	1460	49	14.8	89.0	89.0	88.5	0.82	6.9	2.9	2.8	319	57	FD 06	100	—	950	280	70	FA 07	100	1000	280	75
9.2	ME 4LB 4	1460	60	18.1	89.5	89.5	88.5	0.82	6.9	2.9	3.0	360	65	FD 07	150	—	900	342	81	FA 07	150	900	342	83
11	ME 5SA 4	1465	72	21.5	91.0	91.3	90.5	0.81	6.5	2.8	2.6	650	85	FD 08	170	—	800	655	115	FA 08	170	800	655	114
15	ME 5LA 4	1465	98	28.7	90.8	91.0	90.5	0.83	6.5	2.6	2.3	790	101	FD 08	200	—	750	725	131	FA 08	200	750	710	130



6 P	1000 min^{-1} - S1	50 Hz - IE2



A068744

															d.c. brake						a.c. brake				
															FD						FA				
P_n kW			n min^{-1}	M_n Nm	In 400V A	η% 100%	η% 75%	η% 50%	cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	Z_O 1/h NB	Z_O 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	Z_O 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.75	**ME 3SA**	**6**	940	7.6	1.98	75.9	75.0	70.7	0.72	4.7	2.2	2	33	17	**FD 15**	26	3400	6500	28	21	**FA 15**	26	6500	28	22
1.1	**ME 3LA**	**6 (*)**	945	11.1	2.75	78.1	76.2	73.0	0.74	4.9	2.2	1.9	82	21	**FD 15**	26	2700	5000	37	27	**FA 15**	26	5000	37	28
1.5	**ME 3LB**	**6**	945	15.2	3.8	79.8	77.5	74.0	0.72	5.6	2.5	2.3	95	23	**FD 15**	40	1900	4100	86	29	**FA 15**	40	4100	86	30
2.2	**ME 4SA**	**6**	955	22	4.9	81.8	81.8	80.0	0.80	5.7	1.9	1.7	216	34	**FD 06**	50	—	2100	177	47	**FA 06**	50	2100	177	48
3	**ME 4SB**	**6**	955	30	6.6	83.3	83.3	82.4	0.79	6.1	2.1	1.9	295	43	**FD 56**	75	—	1400	226	56	**FA 06**	75	1400	226	57
4	**ME 4LA**	**6**	965	40	8.6	84.6	85.0	83.1	0.79	6.9	2.2	2.0	383	54	**FD 06**	100	—	1200	305	70	**FA 07**	100	1200	305	72
5.5	**ME 5SA**	**6 (*)**	965	54	11.6	87.0	87.0	86.4	0.79	6.6	2.5	2.3	740	69	**FD 08**	170	—	1050	406	99	**FA 08**	170	1050	406	98
7.5	**ME 5SB**	**6 (*)**	965	74	15.0	88.0	88.0	87.2	0.82	6.6	2.3	2.1	970	89	**FD 08**	170	—	900	815	119	**FA 08**	170	900	815	118

2 P	3000 min^{-1} - S1	50 Hz - IE2

														d.c. brake						a.c. brake				
														FD						FA				
P_n kW		n min^{-1}	M_n Nm	In 400V A	η% 100%	η% 75%	η% 50%	cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	Z_O 1/h NB	Z_O 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	Z_O 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.75	**ME 2SA 2**	2860	2.5	1.63	80	79.6	76.4	0.83	6.8	3.8	3.5	9	8.8	**FD 04**	5	1700	3200	9.4	12.7	**FA 04**	5	3200	9.4	12.6
1.1	**ME 2SB 2**	2845	3.7	2.35	81.5	82.2	79.9	0.83	6.9	3.8	3.1	11.4	10.6	**FD 04**	10	1500	3000	10.6	14.5	**FA 04**	10	3000	10.6	14.4
1.5	**ME 3SA 2**	2845	5	3.2	81.3	79	76	0.81	6.1	2.9	2.7	24	15.5	**FD 15**	13	4800	8000	32	22.5	**FA 15**	26	8000	32	22.5
2.2	**ME 3LA 2**	2895	7.3	4.7	83.2	83.1	80.8	0.82	6.9	3.1	2.9	16.7	18.7	**FD 15**	26	3400	6000	34	25.7	**FA 15**	26	6000	34	25.7
3.7	**ME 4SA 2**	2930	12.1	7.8	84.7	83	81.2	0.79	7.9	3.5	3.1	57	33	**FD 56**	75	—	1400	107	46	**FA 06**	75	2100	107	47

4 P	1500 min^{-1} - S1	50 Hz - IE2



														d.c. brake						a.c. brake				
														FD						FA				
P_n kW		n min^{-1}	M_n Nm	In 400V A	η% 100%	η% 75%	η% 50%	cos φ	I_s/I_n	M_s/M_n	M_a/M_n	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	Z_O 1/h NB	Z_O 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	Z_O 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.37	**ME 1SB 4**	1385	2.55	1.05	72.7	69.3	64.2	0.75	4.0	2.3	2.2	6.9	5.9	**FD 03**	5	6000	9400	8	8.6	**FA 03**	5	9400	8	8.3
0.55	**ME 2SA 4**	1430	3.7	1.38	77.1	73.4	68	0.77	6	2.2	1.9	15	9.9	**FD 04**	10	4100	8000	16.6	13.8	**FA 04**	10	8000	16.6	13.7
0.75	**ME 2SB 4**	1430	5	1.76	79.6	78.5	75.1	0.78	6.1	3.2	3	28	12.2	**FD 04**	15	4100	7800	22	16.1	**FA 04**	15	7800	22	16
1.1	**ME 3SA 4**	1430	7.4	2.6	82.5	82	79	0.74	5.5	2.5	2.8	34	15.5	**FD 15**	26	4800	8000	32	22.5	**FA 15**	26	8000	32	22.5
1.5	**ME 3SB 4**	1420	10.1	3.48	84	84	83	0.74	6.2	2.9	2.9	40	17	**FD 15**	26	3400	6000	34	24	**FA 15**	26	6000	34	24
2.2	**ME 3LA 4**	1430	14.7	4.9	84.3	85	84	0.76	5.8	3	2.8	54	21	**FD 15**	40	2600	4700	44	28	**FA 15**	40	4700	44	28
3.7	**ME 4SA 4**	1440	27	8.25	87.5	86.8	84	0.80	7.1	3	3.1	213	42	**FD 56**	75	—	1400	107	55	**FA 06**	75	2100	107	56

6 P	1000 min^{-1} - S1	50 Hz - IE2

															d.c. brake						a.c. brake				
															FD						FA				
P_n kW			n min^{-1}	M_n Nm	In 400V A	η% 100%	η% 75%	η% 50%	cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	Z_O 1/h NB	Z_O 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	M_b Nm	Z_O 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.75	**ME 3SA**	**6**	940	7.6	1.98	75.9	75	70.7	0.72	4.7	2.2	2	33	17	**FD 15**	26	3400	6500	28	21	**FA 15**	26	6500	28	22
1.1	**ME 3LA**	**6 (*)**	945	11.1	2.75	78.1	76.2	73	0.74	4.9	2.2	1.9	82	21	**FD 15**	26	2700	5000	37	27	**FA 15**	26	5000	37	28
1.5	**ME 3LB**	**6**	945	15.2	3.8	79.8	77.5	74	0.72	5.6	2.5	2.3	95	23	**FD 15**	40	1900	4100	86	29	**FA 15**	40	4100	86	30
2.2	**ME 4SA**	**6**	955	22	4.9	81.8	81.8	80	0.8	5.7	1.9	1.7	216	34	**FD 56**	75	—	2100	177	47	**FA 06**	60	2100	177	48
3.7	**ME 4LA**	**6**	970	36.1	8.3	83.5	83.6	81.3	0.76	6.9	2.2	2	383	54	**FD 06**	100	—	1200	305	70	**FA 06**	100	1200	305	72



4 P	1800 min^{-1} - S1	60 Hz - IE2



c UL us

															d.c. brake						a.c. brake				
															FD						FA				
P_n			n	M_n	In 400V	η%			cos φ	$\frac{I_s}{I_n}$	$\frac{M_s}{M_n}$	$\frac{M_a}{M_n}$	KVA Code	J_m x 10^{-4}	IM B5	Mod	M_b	Z_o 1/h		J_m x 10^{-4}	IM B5	Mod	M_b	Z_o 1/h	J_m x 10^{-4}	IM B5
HP	kW		min^{-1}	Nm	A	100%	75%	50%						kgm^2	Kg		Nm	NB	SB	kgm^2	Kg		Nm		kgm^2	Kg
0.75	0.55	**ME 2SA 4**	1740	3	1.23	75.5	73.1	66.8	0.74	8.7	3.8	3.0	N	19	9.9	**FD 04**	10	4100	8000	16.6	13.8	**FA 04**	10	8000	16.6	13.7
1	0.75	**ME 2SB 4**	1745	4.1	1.46	82.5	81.1	77.6	0.78	7.6	3.5	3.2	K	28	12.2	**FD 04**	15	4100	7800	22	16.1	**FA 04**	15	7800	22	16
1.5	1.1	**ME 3SA 4**	1740	6	2.25	84	82.7	79	0.73	7.7	3.5	3.2	J	28	15.5	**FD 15**	26	4800	8000	32	21.5	**FA 15**	26	8000	32	22.5
2	1.5	**ME 3SB 4**	1740	8.2	3.1	84.5	83.9	80.7	0.73	7.1	3.6	3.4	K	34	17	**FD 15**	26	3400	6000	34	23	**FA 15**	26	6000	34	24
3	2.2	**ME 3LA 4**	1745	12	4.2	87.5	85.5	83.2	0.76	7	3.3	2.9	J	54	21	**FD 15**	40	2600	4700	44	27	**FA 15**	40	4700	44	28
4	3	**ME 3LB 4**	1735	16.5	5.9	87.5	87.7	86.3	0.76	7	3.2	2.9	K	61	23	**FD 15**	40	2400	4400	58	29	**FA 15**	40	4400	58	30
5	3.7	**ME 4SA 4**	1750	20	6.6	87.5	87.5	86.1	0.8	7.8	3.3	3.2	J	105	42	**FD 56**	75	—	1400	107	55	**FA 06**	75	2100	107	56
7.5	5.5	**ME 4SB 4**	1760	30	9.3	89.5	89.5	87.7	0.83	8.7	3.5	3.5	K	270	51	**FD 56**	75	—	1050	223	64	**FA 06**	75	1200	223	65
10	7.5	**ME 4LA 4**	1760	43	12.7	89.5	89.5	87.9	0.83	8	3.4	3.3	K	319	57	**FD 06**	100	—	950	280	70	**FA 07**	100	1000	280	75
12.5	9.2	**ME 4LB 4**	1760	50	15.6	90	90	88.6	0.82	8.3	3.5	3.6	K	360	65	**FD 07**	150	—	900	342	81	**FA 07**	150	900	342	83
15	11	**ME 5SA 4**	1765	60	18.7	91	91	90	0.81	7.7	2.9	2.8	J	650	85	**FD 08**	170	—	800	655	115	**FA 08**	170	800	655	114
20	15	**ME 5LA 4**	1770	81	25.5	91	90.5	89.5	0.81	7.1	3.1	2.7	J	790	101	**FD 08**	200	—	750	725	131	**FA 08**	200	750	710	130

BE - IM B5- CE/CUS/BIS/CCC



	Shaft					Flange						Motor							
	D DA	E EA	DB	GA GC	F FA	M	N	P	S	T	LA	AC	L	LB	LC	AD	AF	LL	V
BE 63	11	23	M4	12.5	4	115	95	140	9.5	3	10	121	207	184	232	95	74	80	26
BE 71	14	30	M5	16	5	130	110	160		3.5		138	249	219	281	108			37
BE 80	19	40	M6	21.5	6	165	130	200	11.5		11.5	156	274	234	315	119			38
BE 90 S	24	50	M8	27	8							176	326	276	378	133	98	98	44
BE 90 L																			
BE 100	28	60	M10	31		215	180	250	14	4	14	195	367	307	429	142			50
BE 112											15	219	385	325	448	157			52
BE 132 S	38	80	M12	41	10	265	230	300			20	258	493	413	576	193	118	118	58
BE 132 MA																			
BE 132 MB													528	448	611				
BE 160 M	42 38(1)	110 80(1)	M16 M12(1)	45 41(1)	12 10(1)	300	250	350	18.5	5	15	310	596	486	680	245	187	187	51
BE 160 L													640	530	724				
BE 180 M	48 42(1)	110 110(1)	M16 M16(1)	51.5 45(1)	14 12(1)						18	348	708	598	823	261			52
BE 180 L																			

N.B.:
1) These values refer to the rear shaft end.

BE - IM B5 - FD/FA - CE/CUS/BIS



	Shaft					Flange						Motor								R		ES (2)
	D DA	E EA	DB	GA GC	F FA	M	N	P	S	T	LA	AC	L	LB	LC	AD	AF	LL	V	FD	FA	
BE 63	11	23	M4	12.5	4	115	95	140	9.5	3	10	121	272	249	297	122	98	133	14	96	116	5
BE 71	14	30	M5	16	5	130	110	160		3.5		138	313	283	345	135			24	103	124	
BE 80	19	40	M6	21.5	6	165	130	200	11.5		11.5	156	348	308	390	143			25	129	134	
BE 90 S	24	50	M8	27	8							176	411	361	463	146	110	165	32			6
BE 90 L																				160	160	
BE 100	28	60	M10	31		215	180	250	14	4	14	195	458	398	521	155			37			
BE 112											15	219	484	424	547	170			39	199	198	
BE 132 S	38	80	M12	41	10	265	230	300			20	258	603	523	686	193	140	188	46	204	200	
BE 132 MA																						
BE 132 MB													628	548	711					226	217	—
BE 160 M	42 38(1)	110 80(1)	M16 M12(1)	45 41(1)	12 10(1)	300	250	350	18.5	5	15	310	736	626	820	245	187	187	51	266	247	
BE 160 L													780	670	864							
BE 180 M	48 42(1)	110 110(1)	M16 M16(1)	51.5 45(1)	14 12(1)						18	348	866	756	981	261			52	305	—	
BE 180 L																						

N.B.: 1) These values refer to the rear shaft end (PS). 2) “ES” hexagon is not present with PS option



ME - CE/CUS/BIS/CCC



	Rear shaft end					Motor						
	DA	**EA**	**DB**	**FA**	**GC**	**AC**	**LB**	**LC**	**AF**	**LL**	**J**	**AD**
ME 05	11	23	M4	12.5	4	121	165	191	74	80	48	95
ME 1S	14	30	M5	16	5	138	187	219			45	108
ME 2S	19	40	M6	21.5	6	156	202	245			44	119
ME 3S	28	60	M10	31	8	195	230	293	98	98	53.5	142
ME 3L							262	325				
ME 4S	38	80	M12	41	10	258	361	444	118	118	64.5	193
ME 4L												
ME 4LB							396	479				
ME 5S	38	80	M12	41	10	310	418	502	187	187	77	245
ME 5L							462	546				



ME_FD/FA - CE/CUS/BIS



	Rear shaft end					Motor									
	DA	**EA**	**DB**	**GC**	**FA**	**AC**	**LB**	**LC**	**AF**	**LL**	**J**	**AD**	**R FD**	**R FA**	**ES (1)**
ME 05	11	23	M4	12.5	4	121	231	256	98	133	-4.5	119	96	116	5
ME 1S	14	30	M5	16	5	138	248	280			-8	135	103	124	
ME 2S	19	40	M6	21.5	6	156	272	314			-17	143	129	134	
ME 3S	28	60	M10	31	8	195	326	389	110	165	7	155	160	160	6
ME 3L							353	416							
ME 4S	38	80	M12	41	10	258	470	553	140	188	7	210	204	200	
ME 4LA															
ME 4LB							495	578					226	217	
ME 5S	38	80	M12	41	10	310	558	642	187	187	17	245	266	247	---
ME 5L							602	686							

N.B.: 1) “ES” hexagon is not present with PS option

2P — 3000 min^{-1} - S1 — 50 Hz

															d.c. brake						a.c. brake				
															FD						FA				
P_n		n	M_n	IE1	η (100%)	η (75%)	η (50%)	cosφ	In 400V	Is / In	Ms / Mn	Ma / Mn	J_m x 10^{-4}	IM B5	Mod	Mb	Z_o 1/h		J_m x 10^{-4}	IM B5	Mod	Mb	Z_o 1/h	J_m x 10^{-4}	IM B5
kW		min^{-1}	Nm		%	%	%		A				kgm^2	Kg		Nm	NB	SB	kgm^2	Kg		Nm		kgm^2	Kg
0.18	BN 63A 2	2730	0.63	○	59.9	56.9	51.9	0.77	0.56	3.0	2.1	2.0	2.0	3.5	FD 02	1.75	3900	4800	2.6	5.2	FA 02	1.75	4800	2.6	5.0
0.25	BN 63B 2	2740	0.87	○	66.0	64.8	64.8	0.76	0.72	3.3	2.3	2.3	2.3	3.9	FD 02	1.75	3900	4800	3.0	5.6	FA 02	1.75	4800	3.0	5.4
0.37	BN 63C 2	2800	1.26	○	69.1	66.8	66.8	0.78	0.99	3.9	2.6	2.6	3.3	5.1	FD 02	3.5	3600	4500	3.9	6.8	FA 02	3.5	4500	3.9	6.6
0.37	BN 71A 2	2820	1.25	○	73.8	73.0	70.6	0.76	0.95	4.8	2.8	2.6	3.5	5.4	FD 03	3.5	3000	4100	4.6	8.1	FA 03	3.5	4200	4.6	7.8
0.55	BN 71B 2	2820	1.86	○	76.0	75.8	74.8	0.76	1.37	5.0	2.9	2.8	4.1	6.2	FD 03	5	2900	4200	5.3	8.9	FA 03	5	4200	5.3	8.6
0.75	BN 71C 2	2810	2.6	○	76.6	76.2	76.2	0.76	1.86	5.1	3.1	2.8	5.0	7.3	FD 03	5	1900	3300	6.1	10.0	FA 03	5	3600	6.1	9.7
0.75	BN 80A 2	2810	2.6	•	76.2	75.5	68.3	0.81	1.75	4.8	2.6	2.2	7.8	8.6	FD 04	5	1700	3200	9.4	12.5	FA 04	5	3200	9.4	12.4
1.1	BN 80B 2	2800	3.8	•	76.4	76.2	75.0	0.81	2.57	4.8	2.8	2.4	9.0	9.5	FD 04	10	1500	3000	10.6	13.4	FA 04	10	3000	10.6	13.3
1.5	BN 80C 2	2800	5.1	•	79.1	79.5	77.2	0.81	3.4	4.9	2.7	2.4	11.4	11.3	FD 04	15	1300	2600	13.0	15.2	FA 04	15	2600	13.0	15.1
1.5	BN 90SA 2	2870	5.0	•	82.0	81.5	78.1	0.80	3.4	5.9	2.7	2.6	12.5	12.3	FD 14	15	900	2200	14.1	16.5	FA 14	15	2200	14.1	16.4
1.85	BN 90SB 2	2880	6.1	•	82.5	82.0	75.4	0.80	4.0	6.2	2.9	2.6	16.7	14	FD 14	15	900	2200	18.3	18.2	FA 14	15	2200	18.3	18.1
2.2	BN 90L 2	2880	7.3	•	82.7	82.1	80.8	0.80	4.8	6.3	2.9	2.7	16.7	14	FD 05	26	900	2200	21	20	FA 05	26	2200	21	20.7
3	BN 100L 2	2860	10.0	•	81.5	81.3	77.4	0.79	6.7	5.6	2.6	2.2	31	20	FD 15	26	700	1600	35	26	FA 15	26	1600	35	27
4	BN 100LB 2	2870	13.3	•	83.1	83.0	77.8	0.80	8.7	5.8	2.7	2.5	39	23	FD 15	40	450	900	43	29	FA 15	40	1000	43	30
4	BN 112M 2	2900	13.2	•	85.5	84.5	83.0	0.82	8.2	6.9	3.0	2.9	57	28	FD 06S	40	—	950	66	39	FA 06S	40	950	66	40
5.5	BN 132SA 2	2890	18.2	•	84.7	84.5	81.2	0.84	11.2	5.9	2.6	2.2	101	35	FD 06	50	—	600	112	48	FA 06	50	600	112	49
7.5	BN 132SB 2	2900	25	•	86.5	86.3	84.4	0.85	14.7	6.4	2.6	2.2	145	42	FD 06	50	—	550	154	55	FA 06	50	550	154	56
9.2	BN 132M 2	2930	30	•	87.0	86.5	83.6	0.86	17.7	6.7	2.8	2.3	178	53	FD 56	75	—	430	189	66	FA 06	75	430	189	67
11	BN 160MR 2	2920	36	•	87.6	87.0	86.0	0.88	20.6	6.9	2.9	2.5	210	65											
15	BN 160MB 2	2930	49	•	89.6	89.4	88.0	0.86	28.1	7.1	2.6	2.3	340	84											
18.5	BN 160L 2	2930	60	•	90.4	90.1	89.0	0.86	34	7.6	2.7	2.3	420	97											
22	BN 180M 2	2930	72	•	89.9	89.7	89.5	0.88	40	7.8	2.6	2.4	490	109											
30	BN 200LA 2	2930	98	•	90.7	90.1	87.6	0.89	54	7.8	2.7	2.9	770	140											

○ = n.a. • = IE1

4P — 1500 min^{-1} - S1 — 50 Hz



															d.c. brake						a.c. brake				
															FD						FA				
P_n		n	M_n	IE1	η (100%)	η (75%)	η (50%)	cosφ	In 400V	Is / In	Ms / Mn	Ma / Mn	J_m x 10^{-4}	IM B5	Mod	Mb	Z_o 1/h		J_m x 10^{-4}	IM B5	Mod	Mb	Z_o 1/h	J_m x 10^{-4}	IM B5
kW		min^{-1}	Nm		%	%	%		A				kgm^2	Kg		Nm	NB	SB	kgm^2	Kg		Nm		kgm^2	Kg
0.06	**BN 56A** 4	1340	0.43	○	46.8	44.2	41.3	0.65	0.28	2.6	2.3	2.0	1.5	3.1											
0.09	**BN 56B** 4	1350	0.64	○	51.7	47.6	42.9	0.60	0.42	2.6	2.5	2.4	1.5	3.1											
0.12	**BN 63A** 4	1350	0.85	○	59.8	56.2	47.0	0.62	0.47	2.6	1.9	1.8	2.0	3.5	**FD 02**	1.75	10000	13000	2.6	5.2	**FA 02**	1.75	13000	2.6	5.0
0.18	**BN 63B** 4	1320	1.30	○	54.8	52.9	52.5	0.67	0.71	2.6	2.2	2.0	2.3	3.9	**FD 02**	3.5	10000	13000	3.0	5.6	**FA 02**	3.5	13000	3.0	5.4
0.25	**BN 63C** 4	1340	1.78	○	65.3	65.0	57.9	0.69	0.80	2.7	2.1	1.9	3.3	5.1	**FD 02**	3.5	7800	10000	3.9	6.8	**FA 02**	3.5	10000	3.9	6.6
0.25	**BN 71A** 4	1380	1.73	○	63.7	62.2	59.1	0.73	0.78	3.3	1.9	1.7	5.8	5.1	**FD 03**	3.5	7700	11000	6.9	7.8	**FA 03**	3.5	11000	6.9	7.5
0.37	**BN 71B** 4	1370	2.6	○	66.8	66.7	63.0	0.76	1.05	3.7	2.0	1.9	6.9	5.9	**FD 03**	5	6000	9400	8.0	8.6	**FA 03**	5.0	9400	8.0	8.3
0.55	**BN 71C** 4	1380	3.8	○	69.0	68.9	68.8	0.74	1.55	4.1	2.3	2.3	9.1	7.3	**FD 53**	7.5	4300	8700	10.2	10.0	**FA 03**	7.5	8700	10.2	9.7
0.55	**BN 80A** 4	1390	3.8	○	72.0	71.3	69.7	0.77	1.43	4.1	2.3	2.0	15	8.2	**FD 04**	10	4100	8000	16.6	12.1	**FA 04**	10	8000	16.6	12.0
0.75	**BN 80B** 4	1400	5.1	•	75.0	74.5	69.3	0.78	1.85	4.9	2.7	2.5	20	9.9	**FD 04**	15	4100	7800	22	13.8	**FA 04**	15	7800	22	13.7
1.1	**BN 80C** 4	1400	7.5	•	75.5	76.2	70.4	0.78	2.7	5.1	2.8	2.5	25	11.3	**FD 04**	15	2600	5300	27	15.2	**FA 04**	15	5300	27	15.1
1.1	**BN 90S** 4	1390	7.6	•	76.5	76.2	72.2	0.77	2.70	4.6	2.6	2.2	21	12.2	**FD 14**	15	4800	8000	23	16.4	**FA 14**	15	8000	23	16.3
1.5	**BN 90LA** 4	1410	10.2	•	78.7	78.5	74.9	0.77	3.6	5.3	2.8	2.4	28	13.6	**FD 05**	26	3400	6000	32	19.6	**FA 05**	26	6000	32	20.3
1.85	**BN 90LB** 4	1390	12.7	•	78.6	78.9	77.2	0.79	4.3	5.1	2.8	2.6	30	15.1	**FD 05**	26	3200	5900	34	21.1	**FA 05**	26	5900	34	21.8
2.2	**BN 100LA** 4	1410	14.9	•	81.1	81.4	79.9	0.75	5.2	4.5	2.2	2.0	40	18	**FD 15**	40	2600	4700	44	25	**FA 15**	40	4700	44	25
3	**BN 100LB** 4	1410	20	•	82.6	83.8	83.7	0.77	6.8	5.0	2.3	2.2	54	22	**FD 15**	40	2400	4400	58	28	**FA 15**	40	4400	58	29
4	**BN 112M** 4	1430	27	•	84.4	84.2	81.6	0.81	8.4	5.6	2.7	2.5	98	30	**FD 06S**	60	—	1400	107	40	**FA 06S**	60	2100	107	42
5.5	**BN 132S** 4	1440	36	•	84.7	84.8	82.5	0.81	11.6	5.5	2.3	2.2	213	44	**FD 56**	75	—	1050	223	57	**FA 06**	75	1200	223	58
7.5	**BN 132MA** 4	1440	50	•	86.0	86.3	85.3	0.81	15.5	5.7	2.5	2.4	270	53	**FD 06**	100	—	950	280	66	**FA 07**	100	1000	280	71
9.2	**BN 132MB** 4	1440	61	•	88.4	88.6	87.5	0.81	18.8	5.9	2.7	2.5	319	59	**FD 07**	150	—	900	342	75	**FA 07**	150	900	342	77
11	**BN 160MR** 4	1440	73	•	87.6	87.8	86.0	0.81	22.4	6.0	2.7	2.5	360	70	**FD 07**	150	—	850	382	86	**FA 07**	150	850	382	88
15	**BN 160L** 4	1460	98	•	88.7	88.5	88.4	0.81	30	6.0	2.3	2.1	650	99	**FD 08**	200	—	750	725	129	**FA 08**	200	750	710	128
18.5	**BN 180M** 4	1460	121	•	89.3	89.5	89.2	0.81	37	6.2	2.6	2.5	790	115	**FD 08**	250	—	700	865	145	**FA 08**	250	700	850	144
22	**BN 180L** 4	1460	144	•	89.9	90.0	90.0	0.80	44	6.4	2.5	2.5	1250	135	**FD 09**	300	—	400	1450	175					
30	**BN 200L** 4	1460	196	•	91.4	91.7	91.0	0.80	59	7.1	2.7	2.8	1650	157	**FD 09**	400	—	300	1850	197					

○ = n.a. • = IE1

6P — 1000 min^{-1} - S1 — 50 Hz

															d.c. brake						a.c. brake				
															FD						FA				
P_n kW		n min^{-1}	M_n Nm	IE1	η (100%) %	η (75%) %	η (50%) %	cosφ	In 400V A	Is / In	Ms / Mn	Ma / Mn	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h NB	Z_o 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.09	BN 63A 6	880	0.98	○	41.0	41.0	32.9	0.53	0.60	2.1	2.1	1.8	3.4	4.6	FD 02	3.5	9000	14000	4.0	6.3	FA 02	3.5	14000	4.0	6.1
0.12	BN 63B 6	870	1.32	○	45.0	44.0	41.8	0.60	0.64	2.1	1.9	1.7	3.7	4.9	FD 02	3.5	9000	14000	4.3	6.6	FA 02	3.5	14000	4.3	6.4
0.18	BN 71A 6	900	1.91	○	55.0	55.5	51.0	0.69	0.68	2.6	1.9	1.7	8.4	5.5	FD 03	5	8100	13500	9.5	8.2	FA 03	5.0	13500	9.5	7.9
0.25	BN 71B 6	900	2.70	○	62.0	58.5	51.4	0.71	0.82	2.6	1.9	1.7	10.9	6.7	FD 03	5	7800	13000	12	9.4	FA 03	5.0	13000	12	9.1
0.37	BN 71C 6	910	3.9	○	66.0	60.0	53.3	0.69	1.17	3.0	2.4	2.0	12.9	7.7	FD 53	7.5	5100	9500	14	10.4	FA 03	7.5	9500	14	10.1
0.37	BN 80A 6	910	3.9	○	68.0	67.4	63.3	0.68	1.15	3.2	2.2	2.0	21	9.9	FD 04	10	5200	8500	23	13.8	FA 04	10	8500	23	13.7
0.55	BN 80B 6	920	5.7	○	70.0	69.8	64.3	0.68	1.67	3.9	2.6	2.2	25	11.3	FD 04	15	4800	7200	27	15.2	FA 04	15	7200	27	15.1
0.75	BN 80C 6	920	7.8	•	70.0	70.0	64.4	0.65	2.38	3.8	2.5	2.2	28	12.2	FD 04	15	3400	6400	30	16.1	FA 04	15	6400	30	16.0
0.75	BN 90S 6	920	7.8	•	70.0	69.0	64.2	0.68	2.27	3.8	2.4	2.2	26	12.6	FD 14	15	3400	6500	28	16.8	FA 14	15	6500	28	16.7
1.1	BN 90L 6	920	11.4	•	72.9	72.6	69.1	0.69	3.2	3.9	2.3	2.0	33	15	FD 05	26	2700	5000	37	21	FA 05	26	5000	37	22
1.5	BN 100LA 6	940	15.2	•	75.2	74.2	70.3	0.72	4.0	4.1	2.1	2.0	82	22	FD 15	40	1900	4100	86	28	FA 15	40	4100	86	29
1.85	BN 100LB 6	930	19.0	•	76.6	72.8	62.6	0.73	4.8	4.6	2.1	2.0	95	24	FD 15	40	1700	3600	99	30	FA 15	40	3600	99	31
2.2	BN 112M 6	940	22	•	78.5	79.0	76.5	0.73	5.5	4.8	2.2	2.0	168	32	FD 06S	60	—	2100	177	42	FA 06S	60	2100	177	44
3	BN 132S 6	940	30	•	79.7	77.0	75.1	0.76	7.1	5.1	1.9	1.8	216	36	FD 56	75	—	1400	226	49	FA 06	75	1400	226	50
4	BN 132MA 6	950	40	•	81.4	81.5	79.5	0.77	9.2	5.5	2.0	1.8	295	45	FD 06	100	—	1200	305	58	FA 07	100	1200	318	63
5.5	BN 132MB 6	945	56	•	83.1	80.9	79.1	0.78	12.2	6.1	2.1	1.9	383	56	FD 07	150	—	1050	406	72	FA 07	150	1050	406	74
7.5	BN 160M 6	955	75	•	85.0	85.0	84.8	0.81	15.7	5.9	2.2	2.0	740	83	FD 08	170	—	900	815	112	FA 08	170	900	815	113
11	BN 160L 6	960	109	•	86.4	86.5	85.9	0.81	22.7	6.6	2.5	2.3	970	103	FD 08	200	—	800	1045	133	FA 08	200	800	1045	133
15	BN 180L 6	970	148	•	87.7	88.0	87.3	0.82	30	6.2	2.0	2.4	1550	130	FD 09	300	—	600	1750	170					
18.5	BN 200LA 6	960	184	•	88.6	88.0	87.3	0.81	37	5.9	2.0	2.3	1700	145	FD 09	400	—	450	1900	185					

○ = n.a. • = IE1



8P — 750 min^{-1} - S1 — 50 Hz



												d.c. brake						a.c. brake				
												FD						FA				
P_n kW			n min^{-1}	M_n Nm	η %	cosφ	In 400V A	Is/In	Ms/Mn	Ma/Mn	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h NB	Z_o 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.09	**BN 71A**	**8**	680	1.26	47	0.59	0.47	2.3	2.4	2.3	10.9	6.7	**FD 03**	3.5	9000	16000	12.0	9.4	**FA 03**	3.5	16000	12.0	9.1
0.12	**BN 71B**	**8**	680	1.69	51	0.59	0.58	2.1	2.3	2.2	12.9	7.7	**FD 03**	5.0	9000	16000	14.0	10.4	**FA 03**	5.0	16000	14.0	10.1
0.18	**BN 80A**	**8**	690	2.49	51	0.60	0.85	2.4	2.2	2.2	15	8.2	**FD 04**	5.0	6500	11000	16.6	12.1	**FA 04**	5.0	11000	16.6	12.0
0.25	**BN 80B**	**8**	680	3.51	54	0.63	1.06	2.4	2.0	1.9	20	9.9	**FD 04**	10.0	6000	10000	22	13.8	**FA 04**	10.0	10000	23	13.7
0.37	**BN 90S**	**8**	675	5.2	58	0.60	1.53	2.6	2.3	2.1	26	12.6	**FD 14**	15.0	4800	7500	28	16.8	**FA 14**	15.0	7500	28	16.7
0.55	**BN 90L**	**8**	670	7.8	62	0.60	2.13	2.6	2.2	2.0	33	15	**FD 05**	26	4000	6400	37	21	**FA 05**	26	6400	37	22
0.75	**BN 100LA**	**8**	700	10.2	68	0.63	2.53	3.4	1.9	1.7	82	22	**FD 15**	26	2800	4800	86	28	**FA 15**	26	4800	86	29
1.1	**BN 100LB**	**8**	700	15.0	68	0.64	3.65	3.2	1.7	1.7	95	24	**FD 15**	40	2500	4000	99	30	**FA 15**	40	4000	99	31
1.5	**BN 112M**	**8**	710	20.2	71	0.66	4.6	3.7	1.8	1.9	168	32	**FD 06S**	60	—	3000	177	42	**FA 06S**	60	3000	177	44
2.2	**BN 132S**	**8**	710	29.6	75	0.66	6.4	3.8	1.8	2.0	295	45	**FD 56**	75	—	2300	305	58	**FA 06**	75	2300	305	56
3	**BN 132MA**	**8**	710	40.4	76	0.69	8.3	3.9	1.6	1.8	370	53	**FD 06**	100	—	1900	394	69	**FA 07**	100	1900	406	74

2/4P — 3000/1500 min^{-1} - S1 — 50 Hz

													d.c. brake						a.c. brake				
													FD						FA				
P_n kW			n min^{-1}	M_n Nm	η %	cosφ	In 400V A	Is/In	Ms/Mn	Ma/Mn	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h NB	Z_o 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.20	**BN 63B**	**2**	2700	0.71	55	0.82	0.64	3.5	2.1	1.9	2.9	4.4	**FD 02**	3.5	2200	2600	3.5	6.1	**FA 02**	3.5	2600	3.5	5.9
0.15		**4**	1350	1.06	49	0.67	0.66	2.6	1.8	1.7					4000	5100					5100		
0.28	**BN 71A**	**2**	2700	0.99	56	0.82	0.88	2.9	1.9	1.7	4.7	4.4	**FD 03**	3.5	2100	2400	5.8	7.1	**FA 03**	3.5	2400	5.8	6.8
0.20		**4**	1370	1.39	59	0.72	0.68	3.1	1.8	1.7					3800	4800					4800		
0.37	**BN 71B**	**2**	2740	1.29	56	0.82	1.16	3.5	1.8	1.8	5.8	5.1	**FD 03**	5.0	1400	2100	6.9	7.8	**FA 03**	5.0	2100	6.9	7.5
0.25		**4**	1390	1.72	60	0.73	0.82	3.3	2.0	1.9					2900	4200					4200		
0.45	**BN 71C**	**2**	2780	1.55	63	0.85	1.21	3.8	1.8	1.8	6.9	5.9	**FD 03**	5.0	1400	2100	8.0	8.6	**FA 03**	5.0	2100	8.0	8.3
0.30		**4**	1400	2.0	63	0.73	0.94	3.6	2.0	1.9					2900	4200					4200		
0.55	**BN 80A**	**2**	2800	1.9	63	0.85	1.48	3.9	1.7	1.7	15	8.2	**FD 04**	5.0	1600	2300	17	12.1	**FA 04**	5.0	2300	16.6	12.0
0.37		**4**	1400	2.5	67	0.79	1.01	4.1	1.8	1.9					3000	4000					4000		
0.75	**BN 80B**	**2**	2780	2.6	65	0.85	1.96	3.8	1.9	1.8	20	9.9	**FD 04**	10	1400	1600	22	13.8	**FA 04**	10	1600	22	13.7
0.55		**4**	1400	3.8	68	0.81	1.44	3.9	1.7	1.7					2700	3600					3600		
1.1	**BN 90S**	**2**	2790	3.8	71	0.82	2.73	4.7	2.3	2.0	21	12.2	**FD 14**	10	1500	1600	23	16.4	**FA 14**	10	1600	23	16.3
0.75		**4**	1390	5.2	66	0.79	2.08	4.6	2.4	2.2					2300	2800					2800		
1.5	**BN 90L**	**2**	2780	5.2	70	0.85	3.64	4.5	2.4	2.1	28	14.0	**FD 05**	26	1050	1200	32	20	**FA 05**	26	1200	32	21
1.1		**4**	1390	7.6	73	0.81	2.69	4.7	2.5	2.2					1600	2000					2000		
2.2	**BN 100LA**	**2**	2800	7.5	72	0.85	5.2	4.5	2.0	1.9	40	18.3	**FD 15**	26	600	900	44	25	**FA 15**	26	900	44	25
1.5		**4**	1410	10.2	73	0.79	3.8	4.7	2.0	2.0					1300	2300					2300		
3.5	**BN 100LB**	**2**	2850	11.7	80	0.84	7.5	5.4	2.2	2.1	61	25	**FD 15**	40	500	900	65	31	**FA 15**	40	900	65	32
2.5		**4**	1420	16.8	82	0.80	5.5	5.2	2.2	2.2					1000	2100					2100		
4	**BN 112M**	**2**	2880	13.3	79	0.83	8.8	6.1	2.4	2.0	98	30	**FD 06S**	60	—	700	107	40	**FA 06S**	60	700	107	42
3.3		**4**	1420	22.2	80	0.80	7.4	5.1	2.1	2.0					—	1200					1200		
5.5	**BN 132S**	**2**	2890	18.2	80	0.87	11.4	5.9	2.4	2.0	213	44	**FD 56**	75	—	350	223	57	**FA 06**	75	350	223	58
4.4		**4**	1440	29	82	0.84	9.2	5.3	2.2	2.0					—	900					900		
7.5	**BN 132MA**	**2**	2900	25	82	0.87	15.2	6.5	2.4	2.0	270	53	**FD 06**	100	—	350	280	66	**FA 07**	100	350	293	71
6		**4**	1430	40	84	0.85	12.1	5.8	2.3	2.1					—	900					900		
9.2	**BN 132MB**	**2**	2920	30	83	0.86	18.6	6.0	2.6	2.2	319	59	**FD 07**	150	—	300	342	75	**FA 07**	150	300	342	77
7.3		**4**	1440	48	85	0.85	14.6	5.5	2.3	2.1					—	800					800		



2/6P — 3000/1000 min^{-1} - S3 60/40% — 50 Hz



												d.c. brake						a.c. brake				
												FD						FA				
P_n kW		n min^{-1}	M_n Nm	η %	cosφ	In 400V A	Is/In	Ms/Mn	Ma/Mn	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h NB	Z_o 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.25	**BN 71A**	**2**	2850	0.84	60	0.82	0.73	4.3	1.9	1.8	6.9	5.9	**FD 03**	1.75	1500	1700	8.0	8.6	**FA 03**	2.5	1700	8.0	8.3
0.08		**6**	910	0.84	43	0.70	0.38	2.1	1.4	1.5					10000	13000					13000		
0.37	**BN 71B**	**2**	2880	1.23	62	0.80	1.08	4.4	1.9	1.8	9.1	7.3	**FD 03**	3.5	1000	1300	10.2	10.0	**FA 03**	3.5	1300	10.2	9.7
0.12		**6**	900	1.27	44	0.73	0.54	2.4	1.4	1.5					9000	11000					11000		
0.55	**BN 80A**	**2**	2800	1.88	63	0.86	1.47	4.5	1.9	1.7	20	9.9	**FD 04**	5.0	1500	1800	22	13.8	**FA 04**	5.0	1800	22	13.7
0.18		**6**	930	1.85	52	0.65	0.77	3.3	2.0	1.9					4100	6300					6300		
0.75	**BN 80B**	**2**	2800	2.6	66	0.87	1.89	4.3	1.8	1.6	25	11.3	**FD 04**	5.0	1700	1900	27	15.2	**FA 04**	5.0	1900	27	15.1
0.25		**6**	930	2.6	54	0.67	1.00	3.2	1.7	1.8					3800	6000					6000		
1.10	**BN 90L**	**2**	2860	3.7	67	0.84	2.82	4.7	2.1	1.9	28	14.0	**FD 05**	13	1400	1600	32	20	**FA 05**	13	1600	32	21
0.37		**6**	920	3.8	59	0.71	1.27	3.3	1.6	1.6					3400	5200					5200		
1.5	**BN 100LA**	**2**	2880	5	73	0.84	3.53	5.1	1.9	2.0	40	18.3	**FD 15**	13	1000	1200	44	24	**FA 15**	13	1200	44	25
0.55		**6**	940	5.6	64	0.67	1.85	3.5	1.7	1.8					2900	4000					4000		
2.2	**BN 100LB**	**2**	2900	7.2	77	0.85	4.9	5.9	2.0	2.0	61	25	**FD 15**	26	700	900	65	31	**FA 15**	26	900	65	32
0.75		**6**	950	7.5	67	0.64	2.5	3.3	1.9	1.8					2100	3000					3000		
3	**BN 112M**	**2**	2900	9.9	78	0.87	6.4	6.3	2.0	2.1	98	30	**FD 06S**	40	—	1000	107	40	**FA 06S**	40	1000	107	32
1.1		**6**	950	11.1	72	0.64	3.4	3.9	1.8	1.8					—	2600					2600		
4.5	**BN 132S**	**2**	2910	14.8	78	0.84	9.9	5.8	1.9	1.8	213	44	**FD 56**	37	—	500	223	57	**FA 06**	37	500	223	58
1.5		**6**	960	14.9	74	0.67	4.4	4.2	1.9	2.0					—	2100					2100		
5.5	**BN 132M**	**2**	2920	18.0	78	0.87	11.7	6.2	2.1	1.9	270	53	**FD 56**	50	—	400	280	66	**FA 06**	50	400	280	67
2.2		**6**	960	22	77	0.71	5.8	4.3	2.1	2.0					—	1900					1900		

2/8P — 3000/750 min^{-1} - S3 60/40% — 50 Hz

													d.c. brake						a.c. brake				
													FD						FA				
P_n kW			n min^{-1}	M_n Nm	η %	cosφ	In 400V A	Is/In	Ms/Mn	Ma/Mn	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h NB	Z_o 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.25	**BN 71A**	**2**	2790	0.86	61	0.87	0.68	3.9	1.8	1.9	10.9	6.7	**FD 03**	1.75	1300	1400	12	9.4	**FA 03**	2.5	1400	12	9.1
0.06		**8**	680	0.84	31	0.61	0.46	2.0	1.8	1.9					10000	13000					13000		
0.37	**BN 71B**	**2**	2800	1.26	63	0.86	0.99	3.9	1.8	1.9	12.9	7.7	**FD 03**	3.5	1200	1300	14	10.4	**FA 03**	3.5	1300	14	10.1
0.09		**8**	670	1.28	34	0.75	0.51	1.8	1.4	1.5					9500	13000					13000		
0.55	**BN 80A**	**2**	2830	1.86	66	0.86	1.40	4.4	2.1	2.0	20	9.9	**FD 04**	5.0	1500	1800	22	13.8	**FA 04**	5.0	1800	22	13.7
0.13		**8**	690	1.80	41	0.64	0.72	2.3	1.6	1.7					5600	8000					8000		
0.75	**BN 80B**	**2**	2800	2.6	68	0.88	1.81	4.6	2.1	2.0	25	11.3	**FD 04**	10	1700	1900	27	15.2	**FA 04**	10	1900	27	15.1
0.18		**8**	690	2.5	43	0.66	0.92	2.3	1.6	1.7					4800	7300					7300		
1.10	**BN 90L**	**2**	2830	3.7	63	0.84	3.00	4.5	2.1	1.9	28	14.0	**FD 05**	13	1400	1600	32	20	**FA 05**	13	1600	32	21
0.28		**8**	690	3.9	48	0.63	1.34	2.4	1.8	1.9					3400	5100					5100		
1.5	**BN 100LA**	**2**	2880	5.0	69	0.85	3.69	4.7	1.9	1.8	40	18.3	**FD 15**	13	1000	1200	44	25	**FA 15**	13	1200	44	25
0.37		**8**	690	5.1	46	0.63	1.84	2.1	1.6	1.6					3300	5000					5000		
2.4	**BN 100LB**	**2**	2900	7.9	75	0.82	5.6	5.4	2.1	2.0	61	25	**FD 15**	26	550	700	65	31	**FA 15**	26	700	65	32
0.55		**8**	700	7.5	54	0.58	2.5	2.6	1.8	1.8					2000	3500					3500		
3	**BN 112M**	**2**	2900	9.9	76	0.87	6.5	6.3	2.1	1.9	98	30	**FD 06S**	40	—	900	107	40	**FA 06S**	40	900	107	42
0.75		**8**	690	10.4	60	0.65	2.8	2.5	1.6	1.6					—	2900					2900		
4	**BN 132S**	**2**	2870	13.3	73	0.84	9.4	5.6	2.3	2.4	213	44	**FD 56**	37	—	500	223	57	**FA 06**	37	500	223	58
1		**8**	690	13.8	66	0.62	3.5	2.9	1.9	1.8					—	3500					3500		
5.5	**BN 132M**	**2**	2870	18.3	75	0.84	12.6	6.1	2.4	2.5	270	53	**FD 06**	50	—	400	280	66	**FA 06**	50	400	280	67
1.5		**8**	690	21	68	0.63	5.1	2.9	1.9	1.9					—	2400					2400		



2/12P — 3000/500 min^{-1} - S3 60/40% — 50 Hz



													d.c. brake						a.c. brake				
													FD						FA				
P_n kW			n min^{-1}	M_n Nm	η %	cosφ	In 400V A	Is/In	Ms/Mn	Ma/Mn	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h NB	Z_o 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.55	**BN 80B**	**2**	2820	1.86	64	0.89	1.39	4.2	1.6	1.7	25	11.3	**FD 04**	5.0	1000	1300	27	15.2	**FA 04**	5.0	1300	27	15.1
0.09		**12**	430	2.0	30	0.63	0.69	1.8	1.9	1.8					8000	12000					12000		
0.75	**BN 90L**	**2**	2790	2.6	56	0.89	2.17	4.2	1.8	1.7	26	12.6	**FD 05**	13	1000	1150	30	18.6	**FA 05**	13	1150	30	19.3
0.12		**12**	430	2.7	26	0.63	1.06	1.7	1.4	1.6					4600	6300					6300		
1.10	**BN 100LA**	**2**	2850	3.7	65	0.85	2.87	4.5	1.6	1.8	40	18.3	**FD 15**	13	700	900	44	25	**FA 15**	13	900	44	25
0.18		**12**	430	4.0	26	0.54	1.85	1.5	1.3	1.5					4000	6000					6000		
1.5	**BN 100LB**	**2**	2900	4.9	67	0.86	3.76	5.6	1.9	1.9	54	22	**FD 15**	13	700	900	58	28	**FA 15**	13	900	58	29
0.25		**12**	440	5.4	36	0.46	2.18	1.8	1.7	1.8					3800	5000					5000		
2	**BN 112M**	**2**	2900	6.6	74	0.88	4.43	6.5	2.1	2.0	98	30	**FD 06S**	20	—	800	107	40	**FA 06S**	20	800	107	42
0.3		**12**	460	6.2	46	0.43	2.19	2.0	2.1	2.0					—	3400					3400		
3	**BN 132S**	**2**	2920	9.8	74	0.87	6.7	6.8	2.3	1.9	213	44	**FD 56**	37	—	450	223	57	**FA 06**	37	450	223	58
0.5		**12**	470	10.2	51	0.43	3.3	2.0	1.7	1.6					—	3000					3000		
4	**BN 132M**	**2**	2920	13.1	75	0.89	8.6	5.9	2.4	2.3	270	53	**FD 56**	37	—	400	280	66	**FA 06**	37	400	280	67
0.7		**12**	460	14.5	53	0.44	4.3	1.9	1.7	1.6					—	2800					2800		

4/6P — 1500/1000 min^{-1} - S1 — 50 Hz

													d.c. brake						a.c. brake				
													FD						FA				
P_n kW			n min^{-1}	M_n Nm	η %	cosφ	In 400V A	Is/In	Ms/Mn	Ma/Mn	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h NB	Z_o 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.22	**BN 71B**	**4**	1410	1.5	64	0.74	0.67	3.9	1.8	1.9	9.1	7.3	**FD 03**	3.5	2500	3500	10.2	10.0	**FA 03**	3.5	3500	10.2	9.7
0.13		**6**	920	1.4	43	0.67	0.65	2.3	1.6	1.7					5000	9000					9000		
0.30	**BN 80A**	**4**	1410	2.0	61	0.82	0.87	3.5	1.3	1.5	15	8.2	**FD 04**	5.0	2500	3100	16.6	12.1	**FA 04**	5.0	3100	16.6	12.0
0.20		**6**	930	2.1	54	0.66	0.81	3.2	1.9	2.0					4000	6000					6000		
0.40	**BN 80B**	**4**	1430	2.7	63	0.75	1.22	3.9	1.8	1.8	20	9.9	**FD 04**	10	1800	2300	22	13.8	**FA 04**	10	2300	22	13.7
0.26		**6**	930	2.7	55	0.70	0.97	2.7	1.5	1.6					3600	5500					5500		
0.55	**BN 90S**	**4**	1420	3.7	70	0.78	1.45	4.5	2.0	1.9	21	12.2	**FD 14**	10	1500	2100	23	16.1	**FA 14**	10	2100	23	16.3
0.33		**6**	930	3.4	62	0.70	1.10	3.7	2.3	2.0					2500	4100					4100		
0.75	**BN 90L**	**4**	1420	5.0	74	0.78	1.88	4.3	1.9	1.8	28	14	**FD 05**	13	1400	2000	32	20	**FA 05**	13	2000	32	21
0.45		**6**	920	4.7	66	0.71	1.39	3.3	2.0	1.9					2300	3600					3600		
1.1	**BN 100LA**	**4**	1450	7.2	74	0.79	2.72	5.0	1.7	1.9	82	22	**FD 15**	26	1400	2000	86	28	**FA 15**	26	2000	86	29
0.8		**6**	950	8.0	65	0.69	2.57	4.1	1.9	2.1					2100	3300					3300		
1.5	**BN 100LB**	**4**	1450	9.9	75	0.79	3.65	5.1	1.7	1.9	95	25	**FD 15**	26	1300	1800	99	31	**FA 15**	26	1800	99	32
1.1		**6**	950	11.1	72	0.68	3.24	4.3	2.0	2.1					2000	3000					3000		
2.3	**BN 112M**	**4**	1450	15.2	75	0.78	5.7	5.2	1.8	1.9	168	32	**FD 06S**	40	—	1600	177	42	**FA 06S**	40	1600	177	44
1.5		**6**	960	14.9	73	0.72	4.1	4.9	2.0	2.0					—	2400					2400		
3.1	**BN 132S**	**4**	1460	20	83	0.83	6.5	5.9	2.1	2.0	213	44	**FD 56**	37	—	1200	223	57	**FA 06**	37	1200	223	58
2		**6**	960	20	77	0.75	4.9	4.5	2.1	2.1					—	1900					1900		
4.2	**BN 132MA**	**4**	1460	27	84	0.82	8.8	5.9	2.1	2.2	270	53	**FD 06**	50	—	900	280	66	**FA 06**	50	900	280	67
2.6		**6**	960	26	79	0.72	6.6	4.3	2.0	2.0					—	1500					1500		



4/8P — **1500/750 min^{-1}** - S1 — **50 Hz**



													d.c. brake						a.c. brake				
													FD						FA				
P_n kW			n min^{-1}	M_n Nm	η %	cosφ	In 400V A	Is/In	Ms/Mn	Ma/Mn	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h NB	Z_o 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.37	**BN 80A**	**4**	1400	2.5	63	0.82	1.03	3.3	1.4	1.4	15	8.2	**FD 04**	10	2300	3500	16.6	12.1	**FA 04**	10	3500	16.6	12.0
0.18		**8**	690	2.5	44	0.60	0.98	2.2	1.5	1.6					4500	7000					7000		
0.55	**BN 80B**	**4**	1390	3.8	65	0.86	1.42	3.8	1.7	1.6	20	9.9	**FD 04**	10	2200	2900	22	13.8	**FA 04**	10	2900	22	13.7
0.30		**8**	670	4.3	49	0.65	1.36	2.3	1.7	1.8					4200	6500					6500		
0.65	**BN 90S**	**4**	1390	4.5	73	0.85	1.51	4.0	1.9	1.9	28	13.6	**FD 14**	15	2300	2800	30	17.8	**FA 14**	15	2800	30	17.7
0.35		**8**	690	4.8	49	0.57	1.81	2.5	2.1	2.2					3500	6000					6000		
0.9	**BN 90L**	**4**	1370	6.3	73	0.87	2.05	3.8	1.8	1.8	30	15.1	**FD 05**	26	1700	2100	34	21	**FA 05**	26	2100	34	22
0.5		**8**	670	7.1	57	0.62	2.04	2.4	2.1	2.0					2500	4200					4200		
1.30	**BN 100LA**	**4**	1420	8.7	72	0.83	3.14	4.3	1.7	1.8	82	22	**FD 15**	40	1300	1700	86	28	**FA 15**	40	1700	86	29
0.70		**8**	700	9.6	58	0.64	2.72	2.8	1.8	1.8					2000	3400					3400		
1.8	**BN 100LB**	**4**	1420	12.1	69	0.87	4.3	4.2	1.6	1.7	95	25	**FD 15**	40	1200	1700	99	31	**FA 15**	40	1700	99	32
0.9		**8**	700	12.3	62	0.63	3.3	3.2	1.7	1.8					1600	2600					2600		
2.2	**BN 112M**	**4**	1440	14.6	77	0.85	4.9	5.3	1.8	1.8	168	32	**FD 06S**	60	—	1200	177	42	**FA 06S**	60	1200	177	43
1.2		**8**	710	16.1	70	0.63	3.9	3.3	1.9	1.8					—	2000					2000		
3.6	**BN 132S**	**4**	1440	24	80	0.82	7.9	6.5	2.1	1.9	295	45	**FD 56**	75	—	1000	305	58	**FA 06**	75	1000	305	59
1.8		**8**	720	24	72	0.55	6.6	4.6	1.9	2.0					—	1400					1400		
4.6	**BN 132M**	**4**	1450	30	81	0.83	9.9	6.5	2.2	1.9	383	56	**FD 06**	100	—	1000	393	69	**FA 07**	100	1000	406	74
2.3		**8**	720	31	73	0.54	8.4	4.4	2.3	2.0					—	1300					1300		

2P — 3000 min^{-1} - S1 — 50 Hz

															d.c. brake						a.c. brake				
															FD						FA				
P_n kW		n min^{-1}	M_n Nm	IE1	η (100%) %	η (75%) %	η (50%) %	cosφ	In 400V A	Is/In	Ms/Mn	Ma/Mn	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h NB	Z_o 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.18	M 05A	2	2730	0.63	○	59.9	56.9	51.9	0.77	0.56	3.0	2.1	2.0	2.0	3.2	FD 02	1.75	3900	4800	2.6	4.9	FA 02	1.75	4800	2.6	4.7
0.25	M 05B	2	2740	0.87	○	66.0	64.8	64.8	0.76	0.72	3.3	2.3	2.3	2.3	3.6	FD 02	1.75	3900	4800	3.0	5.3	FA 02	1.75	4800	3.0	5.1
0.37	M 05C	2	2800	1.26	○	69.1	66.8	66.8	0.78	0.99	3.9	2.6	2.6	3.3	4.8	FD 02	3.5	3600	4500	3.9	6.5	FA 02	3.5	4500	3.9	6.3
0.55	M 1SD	2	2820	1.86	○	76.0	75.8	74.8	0.76	1.37	5.0	2.9	2.8	4.1	5.8	FD 03	5	2900	4200	5.3	8.5	FA 03	5	4200	5.3	8.2
0.75	M 1LA	2	2810	2.6	○	76.6	76.2	76.2	0.76	1.86	5.1	3.1	2.8	5.0	6.9	FD 03	5	1900	3300	6.1	9.6	FA 03	5	3300	6.1	9.3
1.1	M 2SA	2	2800	3.8	•	76.4	76.2	75.0	0.81	2.57	4.8	2.8	2.4	9.0	8.8	FD 04	10	1500	3000	10.6	11.9	FA 04	10	3000	10.6	12.6
1.5	M 2SB	2	2800	5.1	•	79.1	79.5	77.2	0.81	3.4	4.9	2.7	2.4	11.4	10.6	FD 04	15	1300	2600	13.0	9.9	FA 04	15	2600	13.0	14.4
2.2	M 3SA	2	2880	7.3	•	82.7	82.1	81.0	0.80	4.8	6.3	2.9	2.7	24	15.5	FD 15	26	1100	2400	28	22	FA 15	26	2400	28	23
3	M 3LA	2	2860	10.0	•	81.5	81.3	77.4	0.79	6.7	5.6	2.6	2.2	31	18.7	FD 15	26	700	1600	35	25	FA 15	26	1600	35	26
4	M 3LB	2	2870	13.3	•	83.1	83.0	77.8	0.80	8.7	5.8	2.7	2.5	39	22	FD 15	40	450	900	43	28	FA 15	40	900	43	29
5.5	M 4SA	2	2890	18.2	•	84.7	84.5	81.2	0.84	11.2	5.9	2.6	2.2	101	33	FD 06	50	—	600	112	46	FA 06	50	600	112	47
7.5	M 4SB	2	2900	25	•	86.5	86.3	84.4	0.85	14.7	6.4	2.6	2.2	145	40	FD 06	50	—	550	154	53	FA 06	50	550	154	54
9.2	M 4LA	2	2930	30	•	87.0	86.5	83.6	0.86	17.7	6.7	2.8	2.3	178	51	FD 56	75	—	430	189	64	FA 06	75	430	189	65
11	M 4LC	2	2920	36	•	87.6	87.0	86.0	0.88	20.6	6.9	2.9	2.5	210	60											
15	M 5SB	2	2930	49	•	89.6	89.4	88.0	0.86	28.1	7.1	2.6	2.3	340	70											
18.5	M 5SC	2	2930	60	•	90.4	90.1	89.0	0.86	34	7.6	2.7	2.3	420	83											
22	M 5LA	2	2930	72	•	89.9	89.7	89.5	0.88	40	7.8	2.6	2.4	490	95											

○ = n.a. • = IE1



4P — 1500 min^{-1} - S1 — 50 Hz



															d.c. brake						a.c. brake				
															FD						FA				
P_n kW		n min^{-1}	M_n Nm	IE1	η (100%) %	η (75%) %	η (50%) %	cosφ	In 400V A	Is / In	Ms / Mn	Ma / Mn	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h NB	Z_o 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.09	M 0B 4	1350	0.64	○	51.7	47.6	42.9	0.60	0.42	2.6	2.5	2.4	1.5	2.9											
0.12	M 05A 4	1350	0.85	○	59.8	56.2	47.0	0.62	0.47	2.6	1.9	1.8	2.0	3.2	FD 02	1.75	10000	13000	2.6	4.9	FA 02	1.75	13000	2.6	4.7
0.18	M 05B 4	1320	1.30	○	54.8	52.9	52.5	0.67	0.71	2.6	2.2	2.0	2.3	3.6	FD 02	3.5	10000	13000	3.0	5.3	FA 02	3.5	13000	3.0	5.1
0.25	M 05C 4	1340	1.78	○	65.3	65.0	57.9	0.69	0.80	2.7	2.1	1.9	3.3	4.8	FD 02	3.5	7800	10000	3.9	6.5	FA 02	3.5	10000	3.9	6.3
0.37	M 1SD 4	1370	2.6	○	66.8	66.7	63.0	0.76	1.05	3.7	2.0	1.9	6.9	5.5	FD 03	5	6000	9400	8.0	8.2	FA 03	5	9400	8.0	7.9
0.55	M 1LA 4	1380	3.8	○	69.0	68.9	68.8	0.74	1.55	4.1	2.3	2.3	9.1	6.9	FD 53	7.5	4300	8700	10.2	9.6	FA 03	7.5	8700	10.2	9.3
0.75	M 2SA 4	1400	5.1	•	75.0	74.5	69.3	0.78	1.85	4.9	2.7	2.5	20	9.2	FD 04	15	4100	7800	22	13.1	FA 04	15	7800	22	13.0
1.1	M 2SB 4	1400	7.5	•	76.4	76.2	70.4	0.78	2.66	5.1	2.8	2.5	25	10.6	FD 04	15	2600	5300	27	14.5	FA 04	15	5300	27	14.4
1.5	M 3SA 4	1410	10.2	•	79.6	80.5	79.3	0.77	3.5	4.6	2.1	2.1	34	15.5	FD 15	26	2800	4900	38	22	FA 15	26	4900	38	23
2.2	M 3LA 4	1410	14.9	•	81.1	81.4	79.9	0.75	5.2	4.5	2.2	2.0	40	17	FD 15	40	2600	4700	44	24	FA 15	40	4700	44	24
3	M 3LB 4	1410	20	•	82.6	83.8	83.7	0.77	6.8	5.0	2.3	2.2	54	21	FD 15	40	2400	4400	58	27	FA 15	40	4400	58	28
4	M 3LC 4	1400	27	○	82.7	83.1	80.5	0.78	9.0	4.7	2.3	2.2	61	23	FD 55	55	—	1300	65	29	FA 15	40	1300	65	30
5.5	M 4SA 4	1440	36	•	84.7	84.8	82.5	0.81	11.6	5.5	2.3	2.2	213	42	FD 56	75	—	1050	223	55	FA 06	75	1050	223	56
7.5	M 4LA 4	1440	50	•	86.0	86.3	85.3	0.81	15.5	5.7	2.5	2.4	270	51	FD 06	100	—	950	280	64	FA 07	100	950	280	65
9.2	M 4LB 4	1440	61	•	88.4	88.6	87.5	0.81	18.8	5.9	2.7	2.5	319	57	FD 07	150	—	900	342	73	FA 07	150	900	342	75
11	M 4LC 4	1440	73	•	87.6	87.8	86.0	0.81	22.4	6.0	2.7	2.5	360	65	FD 07	150	—	850	382	81	FA 07	150	850	382	83
15	M 5SB 4	1460	98	•	88.7	88.5	88.4	0.81	30.1	6.0	2.3	2.1	650	85	FD 08	200	—	750	725	115	FA 08	200	750	710	114
18.5	M 5LA 4	1460	121	•	89.3	89.5	89.2	0.81	37	6.2	2.6	2.5	790	101	FD 08	250	—	700	865	131	FA 08	250	700	850	130

○ = n.a. • = IE1

6P — 1000 min^{-1} - S1 — 50 Hz

																d.c. brake						a.c. brake				
																FD						FA				
P_n kW			n min^{-1}	M_n Nm	IE1	η (100%) %	η (75%) %	η (50%) %	cosφ	In 400V A	Is/In	Ms/Mn	Ma/Mn	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h NB	Z_o 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.09	M 05A	6	880	0.98	○	41.0	41.0	32.9	0.53	0.60	2.1	2.1	1.8	3.4	4.3	FD 02	3.5	9000	14000	4.0	6.0	FA 02	3.5	14000	4.0	5.8
0.12	M 05B	6	870	1.32	○	45.0	44.0	41.8	0.60	0.64	2.1	1.9	1.7	3.7	4.6	FD 02	3.5	9000	14000	4.3	6.3	FA 02	3.5	14000	4.3	6.1
0.18	M 1SC	6	900	1.91	○	55.0	55.5	51.0	0.69	0.68	2.6	1.9	1.7	8.4	5.1	FD 03	5	8100	13500	9.5	7.8	FA 03	5	13500	9.5	7.5
0.25	M 1SD	6	900	2.7	○	62.0	58.5	51.4	0.71	0.82	2.6	1.9	1.7	10.9	6.3	FD 03	5	7800	13000	12	9.0	FA 03	5	13000	12	8.7
0.37	M 1LA	6	910	3.9	○	66.0	60.0	53.3	0.69	1.17	3.0	2.4	2.0	12.9	7.3	FD 53	7.5	5100	9500	14	10.0	FA 03	7.5	9500	14	9.7
0.55	M 2SA	6	920	5.7	○	70.0	69.8	64.3	0.68	1.67	3.9	2.6	2.2	25	10.6	FD 04	15	4800	7200	27	14.5	FA 04	15	7200	27	14.4
0.75	M 2SB	6	920	7.8	•	70.0	70.0	64.4	0.65	2.38	3.8	2.5	2.2	28	11.5	FD 04	15	3400	6400	30	15.4	FA 04	15	6400	30	15.3
1.1	M 3SA	6	920	11.4	•	75.0	74.0	72.0	0.72	2.9	4.3	2.0	1.8	33	17	FD 15	26	2700	5000	37	23	FA 15	26	5000	37	24
1.5	M 3LA	6	940	15.2	•	75.2	74.2	70.3	0.72	4.0	4.1	2.1	2.0	82	21	FD 15	40	1900	4100	86	27	FA 15	40	4100	86	28
1.85	M 3LB	6	930	19.0	•	76.6	72.8	62.6	0.73	4.8	4.6	2.1	2.0	95	23	FD 15	40	1700	3600	99	29	FA 15	40	3600	99	30
2.2	M 3LC	6	930	23	•	77.7	76.8	72.4	0.71	5.8	4.7	2.3	2.1	95	23	FD 55	55	—	1900	99	29	FA 15	40	1900	99	30
3	M 4SA	6	940	30	•	79.7	77.0	75.1	0.76	7.1	5.1	1.9	1.8	216	34	FD 56	75	—	1400	226	47	FA 06	75	1400	226	48
4	M 4LA	6	950	40	•	81.4	81.5	79.5	0.77	9.2	5.5	2.0	1.8	295	43	FD 06	100	—	1200	305	56	FA 07	100	1200	305	57
5.5	M 4LB	6	945	56	•	83.1	80.9	79.1	0.78	12.2	6.1	2.1	1.9	383	54	FD 07	150	—	1050	406	70	FA 07	150	1050	406	72
7.5	M 5SA	6	955	75	•	85.0	85.0	84.8	0.81	15.7	5.9	2.2	2.0	740	69	FD 08	170	—	900	815	98	FA 08	170	900	800	98
11	M 5SB	6	960	109	•	86.4	86.5	85.9	0.81	22.7	6.6	2.5	2.3	970	89	FD 08	200	—	800	1045	119	FA 08	200	800	1030	118

○ = n.a. • = IE1



2/4P — 3000/1500 min^{-1} - S1 — 50 Hz



													d.c. brake						a.c. brake				
													FD						FA				
P_n kW			n min^{-1}	M_n Nm	η %	cosφ	In 400V A	Is/In	Ms/Mn	Ma/Mn	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h NB	Z_o 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.20	**M 05A**	**2**	2700	0.71	55	0.82	0.64	3.5	2.1	1.9	2.9	4.1	**FD 02**	3.5	2200	2600	3.5	5.8	**FA 02**	3.5	2600	3.5	5.6
0.15		**4**	1350	1.06	49	0.67	0.66	2.6	1.8	1.7					4000	5100					5100		
0.28	**M 1SB**	**2**	2700	0.99	56	0.82	0.88	2.9	1.9	1.7	4.7	4.0	**FD 03**	3.5	2100	2400	5.8	6.7	**FA 03**	3.5	2400	5.8	6.4
0.20		**4**	1370	1.39	59	0.68	1.02	3.1	1.8	1.7					3800	4800					4800		
0.37	**M 1SC**	**2**	2740	1.29	56	0.82	1.16	3.5	1.8	1.8	5.8	4.7	**FD 03**	5	1400	2100	6.9	7.4	**FA 03**	5	2100	6.9	7.1
0.25		**4**	1390	1.72	60	0.73	0.82	3.3	2.0	1.9					2900	4200					4200		
0.45	**M 1SD**	**2**	2780	1.55	63	0.85	1.21	3.8	1.8	1.8	6.9	5.5	**FD 03**	5	1400	2100	8.0	8.2	**FA 03**	5	2100	8.0	7.9
0.30		**4**	1400	2.0	63	0.74	0.93	3.8	2.1	1.9					2900	4200					4200		
0.55	**M 1LA**	**2**	2800	1.9	73	0.79	1.38	4.2	2.0	1.8	9.1	6.9	**FD 03**	5	1600	2200	10.2	9.6	**FA 03**	5	2200	10.2	9.3
0.37		**4**	1400	2.5	68	0.72	1.09	3.9	2.2	2.0					3300	4600					4600		
0.75	**M 2SA**	**2**	2780	2.6	65	0.85	1.96	3.8	1.9	1.8	20	9.2	**FD 04**	10	1400	1600	22	13.1	**FA 04**	10	1600	22	13.0
0.55		**4**	1400	3.8	68	0.81	1.44	3.9	1.7	1.7					2700	3600					3600		
1.1	**M 2SB**	**2**	2730	3.9	65	0.86	2.84	3.9	2.0	1.9	25	10.7	**FD 04**	10	1200	1500	27	14.5	**FA 04**	10	1500	27	14.5
0.75		**4**	1410	5.1	75	0.81	1.78	4.5	2.1	2.0					2300	3100					3100		
1.5	**M 3SA**	**2**	2830	5.1	74	0.83	3.5	4.7	2.1	2.0	34	15.5	**FD 15**	26	700	1000	38	22	**FA 15**	26	1000	38	23
1.1		**4**	1420	7.4	77	0.78	2.6	4.3	2.1	2.0					1600	2600					2600		
2.2	**M 3LA**	**2**	2800	7.5	72	0.85	5.2	4.5	2.0	1.9	40	17	**FD 15**	26	600	900	44	24	**FA 15**	26	900	44	24
1.5		**4**	1410	10.2	73	0.79	3.8	4.7	2.0	2.0					1300	2300					2300		
3.5	**M 3LB**	**2**	2850	11.7	80	0.84	7.5	5.4	2.2	2.1	61	23	**FD 15**	40	500	900	65	29	**FA 15**	40	900	65	30
2.5		**4**	1420	16.8	82	0.80	5.5	5.2	2.2	2.2					1000	2100					2100		
4.8	**M 4 SA**	**2**	2900	15.8	81	0.88	9.7	6.0	2.0	1.9	213	42	**FD 06**	50	—	400	233	55	**FA 06**	50	400	233	56
3.8		**4**	1430	25.4	81	0.84	8.1	5.2	2.1	2.1					—	950					950		
5.5	**M 4SB**	**2**	2890	18.2	80	0.87	11.4	5.9	2.4	2.0	213	42	**FD 56**	75	—	350	223	55	**FA 06**	75	350	223	56
4.4		**4**	1440	29	82	0.84	9.2	5.3	2.2	2.0					—	900					900		
7.5	**M 4LA**	**2**	2900	25	82	0.87	15.2	6.5	2.4	2.0	270	51	**FD 06**	100	—	350	280	64	**FA 07**	100	350	280	65
6		**4**	1430	40	84	0.85	12.1	5.8	2.3	2.1					—	950					950		
9.2	**M 4LB**	**2**	2920	30	83	0.86	18.6	6.0	2.6	2.2	319	57	**FD 07**	150	—	300	342	73	**FA 07**	150	300	342	75
7.3		**4**	1440	48	85	0.85	14.6	5.5	2.3	2.1					—	800					800		

2/6P — 3000/1000 min^{-1} - S3 60/40% — 50 Hz

													d.c. brake						a.c. brake				
													FD						FA				
P_n kW			n min^{-1}	M_n Nm	η %	cosφ	In 400V A	Is/In	Ms/Mn	Ma/Mn	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h NB	Z_o 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.25	M 1SA	2	2850	0.84	60	0.82	0.73	4.3	1.9	1.8	6.9	5.5	FD 03	1.75	1500	1700	8.0	8.2	FA 03	1.75	1700	8.0	7.9
0.08		6	910	0.84	43	0.70	0.38	2.1	1.4	1.5					10000	13000					13000		
0.37	M 1LA	2	2880	1.23	62	0.80	1.08	4.4	1.9	1.8	9.1	6.9	FD 03	3.5	1000	1300	10.2	9.6	FA 03	3.5	1300	10.2	9.3
0.12		6	900	1.27	44	0.73	0.54	2.4	1.4	1.5					9000	11000					11000		
0.55	M 2SA	2	2800	1.88	63	0.86	1.47	4.5	1.9	1.7	20	9.2	FD 04	5	1500	1800	22	13.1	FA 04	5	1800	22	13.0
0.18		6	930	1.85	52	0.65	0.77	3.3	2.0	1.9					4100	6300					6300		
0.75	M 2SB	2	2800	2.6	66	0.87	1.89	4.3	1.8	1.6	25	10.6	FD 04	5	1700	1900	27	14.5	FA 04	5	1900	27	14.4
0.25		6	930	2.6	54	0.67	1.00	3.2	1.7	1.8					3800	6000					6000		
1.1	M 3SA	2	2870	3.7	71	0.82	2.73	4.9	1.8	1.9	34	15.5	FD 15	13	1000	1300	38	22	FA 15	13	1300	38	23
0.37		6	930	3.8	63	0.70	1.21	3.1	1.5	1.8					3500	5000					5000		
1.5	M 3LA	2	2880	5.0	73	0.84	3.53	5.1	1.9	2.0	40	17	FD 15	13	1000	1200	44	24	FA 15	13	1200	44	24
0.55		6	940	5.6	64	0.67	1.85	3.5	1.7	1.8					2900	4000					4000		
2.2	M 3LB	2	2900	7.2	77	0.85	4.9	5.9	2.0	2.0	61	23	FD 15	26	700	900	65	29	FA 15	26	900	65	30
0.75		6	950	7.5	67	0.64	2.5	3.3	1.9	1.8					2100	3000					3000		
3	M 4SA	2	2910	9.9	74	0.88	6.6	5.6	2.0	2.1	170	36	FD 56	37	—	600	182	48	FA 06	37	600	182	50
1.1		6	960	10.9	73	0.68	3.2	4.5	2.2	2.0					—	2200					2200		
4.5	M 4SB	2	2910	14.8	78	0.84	9.9	5.8	1.9	1.8	213	42	FD 56	37	—	500	223	55	FA 06	37	500	223	56
1.5		6	960	14.9	74	0.67	4.4	4.2	1.9	2.0					—	2100					2100		
5.5	M 4LA	2	2920	18.0	78	0.87	11.7	6.2	2.1	1.9	270	51	FD 06	50	—	400	280	64	FA 06	50	400	280	65
2.2		6	960	22	77	0.71	5.8	4.3	2.1	2.0					—	1900					1900		



2/8P — 3000/750 min^{-1} - S3 60/40% — 50 Hz



													d.c. brake						a.c. brake				
													FD						FA				
P_n kW			n min^{-1}	M_n Nm	η %	cosφ	In 400V A	Is/In	Ms/Mn	Ma/Mn	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h NB	Z_o 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.37	**M 1LA**	**2**	2800	1.26	63	0.86	0.99	3.9	1.8	1.9	12.9	7.3	**FD 03**	3.5	1200	1300	14	10.0	**FA 03**	3.5	1300	14	9.7
0.09		**8**	670	1.28	34	0.75	0.51	1.8	1.4	1.5					9500	13000					13000		
0.55	**M 2SA**	**2**	2830	1.86	66	0.86	1.40	4.4	2.1	2.0	20	9.2	**FD 04**	5	1500	1800	22	13.1	**FA 04**	5	1800	22	13.0
0.13		**8**	690	1.80	41	0.64	0.72	2.3	1.6	1.7					5600	8000					8000		
0.75	**M 2SB**	**2**	2800	2.6	68	0.88	1.81	4.6	2.1	2.0	25	10.6	**FD 04**	10	1700	1900	27	14.5	**FA 04**	10	1900	27	14.4
0.18		**8**	690	2.5	43	0.66	0.92	2.3	1.6	1.7					4800	7300					7300		
1.1	**M 3SA**	**2**	2870	3.7	69	0.84	2.74	4.6	1.8	1.7	34	15.5	**FD 15**	13	1000	1300	38	22	**FA 15**	13	1300	38	23
0.28		**8**	690	3.9	44	0.56	1.64	2.3	1.4	1.7					3400	5000					5000		
1.5	**M 3LA**	**2**	2880	5.0	69	0.85	3.69	4.7	1.9	1.8	40	17	**FD 15**	13	1000	1200	44	24	**FA 15**	13	1200	44	24
0.37		**8**	690	5.1	46	0.63	1.84	2.1	1.6	1.6					3300	5000					5000		
2.4	**M 3LB**	**2**	2900	7.9	75	0.82	5.6	5.4	2.1	2.0	61	23	**FD 15**	26	550	700	65	29	**FA 15**	26	700	65	30
0.55		**8**	700	7.5	54	0.58	2.5	2.6	1.8	1.8					2000	3500					3500		
3	**M 4SA**	**2**	2920	9.8	72	0.85	7.1	5.6	2.0	1.8	162	36	**FD 56**	37	—	600	182	48	**FA 06**	37	600	182	50
0.75		**8**	710	10.1	61	0.64	2.8	3.0	1.7	1.8					—	3400					3400		
4	**M 4SB**	**2**	2870	13.3	73	0.84	9.4	5.6	2.3	2.4	213	42	**FD 56**	37	—	500	223	55	**FA 06**	37	500	223	56
1		**8**	690	13.8	66	0.62	3.5	2.9	1.9	1.8					—	3500					3500		
5.5	**M 4LA**	**2**	2870	18.3	75	0.84	12.6	6.1	2.4	2.5	270	51	**FD 06**	50	—	400	280	64	**FA 06**	50	400	280	65
1.5		**8**	690	21	68	0.63	5.1	2.9	1.9	1.9					—	2400					2400		

2/12P — 3000/500 min^{-1} - S3 60/40% — 50 Hz

													d.c. brake						a.c. brake				
													FD						FA				
P_n kW			n min^{-1}	M_n Nm	η %	cosφ	In 400V A	Is/In	Ms/Mn	Ma/Mn	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h NB	Z_o 1/h SB	J_m x 10^{-4} kgm^2	IM B5 Kg	Mod	Mb Nm	Z_o 1/h	J_m x 10^{-4} kgm^2	IM B5 Kg
0.55	**M 2SA**	**2**	2820	1.86	64	0.89	1.39	4.2	1.6	1.7	25	10.6	**FD 04**	5	1000	1300	27	14.5	**FA 04**	5	1300	27	14.4
0.09		**12**	430	2.0	30	0.63	0.69	1.8	1.9	1.8					8000	12000					12000		
0.75	**M 3SA**	**2**	2900	2.5	65	0.81	2.06	5.2	1.9	2.1	34	15.5	**FD 15**	13	700	900	38	22	**FA 15**	13	900	38	23
0.12		**12**	460	2.5	33	0.43	1.22	1.9	1.3	1.6					5000	7000					7000		
1.1	**M 3LA**	**2**	2850	3.7	65	0.85	2.87	4.5	1.6	1.8	40	17	**FD 15**	13	700	900	44	24	**FA 15**	13	900	44	24
0.18		**12**	430	4.0	26	0.54	1.85	1.5	1.3	1.5					4000	6000					6000		
1.5	**M 3LB**	**2**	2900	4.9	67	0.86	3.76	5.6	1.9	1.9	54	21	**FD 15**	13	700	900	58	27	**FA 15**	13	900	58	28
0.25		**12**	440	5.4	36	0.46	2.18	1.8	1.7	1.8					3800	5000					5000		
2	**M 3LC**	**2**	2850	6.7	70	0.84	4.9	4.9	1.8	1.7	61	23	**FD 55**	18	—	700	65	29	**FA 15**	18	700	65	30
0.3		**12**	450	6.4	38	0.47	2.4	1.7	1.6	1.7					—	3500					3500		
3	**M 4SA**	**2**	2920	9.8	74	0.87	6.7	6.8	2.3	1.9	213	42	**FD 56**	37	—	450	223	55	**FA 06**	37	450	223	56
0.5		**12**	470	10.2	51	0.43	3.3	2.0	1.7	1.6					—	3000					3000		
4	**M 4LA**	**2**	2920	13.1	75	0.89	8.6	5.9	2.4	2.3	270	51	**FD 56**	37	—	400	280	64	**FA 06**	37	400	280	65
0.7		**12**	460	14.5	53	0.44	4.3	1.9	1.7	1.6					—	2800					2800		



BN - IM B5



	Shaft					Flange						Motor							
	D DA	E EA	DB	GA GC	F FA	M	N	P	S	T	LA	AC	L	LB	LC	AD	AF	LL	V
BN 56	9	20	M3	10.2	3	100	80	120	7	3	8	110	185	165	207	91	74	80	34
BN 63	11	23	M4	12.5	4	115	95	140	9.5		10	121	207	184	232	95			26
BN 71	14	30	M5	16	5	130	110	160		3.5		138	249	219	281	108			37
BN 80	19	40	M6	21.5	6	165	130	200	11.5		11.5	156	274	234	315	119			38
BN 90	24	50	M8	27	8							176	326	276	378	133	98	98	44
BN 100	28	60	M10	31		215	180	250	14	4	14	195	367	307	429	142			50
BN 112											15	219	385	325	448	157			52
BN 132	38	80	M12	41	10	265	230	300			20	258	493	413	576	193	118	118	58
BN 160 MR	42 38(1)	110 80(1)	M16 M12(1)	45 41(1)	12 10(1)	300	250	350	18.5	5	15		562	452	645				218
BN 160 M												310	596	486	680	245	187	187	51
BN 160 L																			
BN 180 M	48 38(1)	110 110(1)		51.5 41(1)	14 10(1)							310	640	530	724				
BN 180 L	48 42(1)		M16 M16(1)	51.5 45(1)	14 12(1)						18	348	708	598	823	261			52
BN 200 L	55 42(1)		M20 M16(1)	59 45(1)	16 12(1)	350	300	400					722	612	837				66

NOTE:
1) These values refer to the rear shaft end.

BN_FD ; IM B5



	Shaft					Flange						Motor									
	D DA	E EA	DB	GA GC	F FA	M	N	P	S	T	LA	AC	L	LB	LC	AD	AF	LL	V	R	ES
BN 63	11	23	M4	12.5	4	115	95	140	9.5	3	10	121	272	249	297	122	98	133	14	96	5
BN 71	14	30	M5	16	5	130	110	160	9.5	3.5	11.5	138	310	280	342	135			25	103	
BN 80	19	40	M6	21.5	6	165	130	200	11.5			156	346	306	388	146			41	129	
BN 90 S	24	50	M8	27	8							176	409	359	461	149	110	165	39		6
BN 90 L																146				160	
BN 100	28	60	M10	31		215	180	250	14	4	14	195	458	398	521	158		165	62		
BN 112											15	219	484	424	547	173		165	73	199	
BN 132	38	80	M12	41	10	265	230	300			20	258	603	523	686	210	140	188	46	204(2)	
BN 160 MR	42 38(1)	110 80(1)	M16 M12(1)	45 41(1)	12 10(1)	300	250	350	18.5	5	15		672	562	755				161	226	
BN 160 M												310	736	626	820	245	187	187	51	266	—
BN 160 L	42 38(1)																				
BN 180 M	48 38(1)			51.5 41(1)	14 10(1)								780	670	864						
BN 180 L	48 42(1)	110 110(1)	M16 M16(1)	51.5 45(1)	14 12(1)						18	348	866	756	981	261			52	305	
BN 200 L	55 42(1)		M20 M16(1)	59 45(1)	16 12(1)	350	300	400	18.5				878	768	993				64		

NOTE:
1) These values refer to the rear shaft end.
2) For FD07 brake value R=226.

ES hexagon is not supplied with PS option.



BN_FA - IM B5



	Shaft					Flange						Motor									
	D DA	E EA	DB	GA GC	F FA	M	N	P	S	T	LA	AC	L	LB	LC	AD	AF	LL	V	R	ES
BN 63	11	23	M4	12.5	4	115	95	140	9.5	3	10	121	272	249	297	95	74	80	26	116	5
BN 71	14	30	M5	16	5	130	110	160		3.5		138	310	280	342	108			68	124	
BN 80	19	40	M6	21.5	6	165	130	200	11.5		11.5	156	346	306	388	119			83	134	
BN 90	24	50	M8	27	8							176	409	359	461	133	98	98	95	160	6
BN 100	28	60	M10	31		215	180	250	14	4	14	195	458	398	521	142			119		
BN 112											15	219	484	424	547	157			128	198	
BN 132	38	80	M12	41	10	265	230	300			20	258	603	523	686	210	140	188	46	200(2)	
BN 160 MR	42 38(1)	110 80(1)	M16 M12(1)	45 41(1)	12 10(1)	300	250	350	18.5	5	15		672	562	755	193	118	118	218	217	
BN 160 M												310	736	626	820	245	187	187	51	247	—
BN 160 L																					
BN 180 M	48 38(1)			51.5 41(1)	14 10(1)								780	670	864						

NOTE:
1) These values refer to the rear shaft end.
2) For FA07 brake value R=217.

Dimensions AD, AF, LL and V, relevant to terminal box of motors BN…FA featuring the separate brake supply (option SA), are coincident with corresponding dimensions of same-size BN…FD motors

ES hexagon is not supplied with PS option.



M



	Rear shaft end					Motor						
	DA	**EA**	**DB**	**FA**	**GC**	**AC**	**LB**	**LC**	**AF**	**LL**	**J**	**AD**
M 0	9	20	M3	3	10.2	110	133	155	74	80	42	91
M 05	11	23	M4	4	12.5	121	165	191			48	95
M 1	14	30	M5	5	16	138	187	219			45	108
M 2 S	19	40	M6	6	21.5	156	202	245			44	119
M 3 S	28	60	M10	8	31	195	230	293	98	98	53.5	142
M 3 L							262	325				
M 4	38	80	M12	10	41	258	361	444	118	118	64.5	193
M 4 LC							396	479				
M 5 S						310	418	502	187	187	77	245
M 5 L							462	546				



M_FD



	Rear shaft end					Motor								
	DA	**EA**	**DB**	**FA**	**GC**	**AC**	**LB**	**LC**	**AF**	**LL**	**J**	**AD**	**R**	**ES**
M 05	11	23	M4	4	12.5	121	231	256	98	133	48	122	96	5
M 1	14	30	M5	5	16	138	248	280			73	135	103	
M 2 S	19	40	M6	6	21.5	156	272	314			88	146	129	
M 3 S	28	60	M10	8	31	195	326	389	110	165	124.5	158	160	6
M 3 L							353	416						
M 4	38	80	M12	10	41	258	470	553	140	188	185.5	210	204 (1)	
M 4 LC							495	578			64.5		226	
M 5 S						310	558	642	187	187	77	245	266	—
M 5 L							602	686						

NOTE:
1) For FD07 brake value R=226.

ES hexagon is not supplied with PS option.

M_FA



	Rear shaft end					Motor								
	DA	**EA**	**DB**	**FA**	**GC**	**AC**	**LB**	**LC**	**AF**	**LL**	**J**	**AD**	**R**	**ES**
M 05	11	23	M4	4	12.5	121	231	256	74	80	48	95	116	5
M 1	14	30	M5	5	16	138	248	280			73	108	124	
M 2 S	19	40	M6	6	21.5	156	272	314			88	119	134	
M 3 S	28	60	M10	8	31	195	326	389	98	98	124.5	142	160	6
M 3 L							353	416						
M 4	38	80	M14	10	41	258	470	553	140	188	185.5	210	200 (1)	
M 4 LC							495	578			64.5		217	
M 5 S			M12			310	558	642	187	187	77	245	247	—
M 5 L							602	686						

NOTE:
1) For FA07 brake value R=217.

Dimensions AD, AF, LL and V, relevant to terminal box of motors M…FA featuring the separate brake supply (option SA), are coincident with corresponding dimensions of same-size M…FD motors

ES hexagon is not supplied with PS option.

INDEX OF REVISIONS

BR_CAT_300M_IE2-IE3_ENG_R04_1

	Description
34	Added lubrication table for Series 300M gear units supplied pre-filled with oil.
37	Added variants for gear units supplied complete with lubricant.
376	Added IEC provisions for gear units 311M L1 VK.
372... 469	Updated sizes for FZP output shafts (311M–325).
268, 278, ..., 465, 469	Removed note relating to screws and tightening torques for customer's shaft axial fixing in versions FDK and FZP
478, 479, ... 486	Added size 323 with related hydraulic provisions and overall dimensions in the table.
488, 490, ..., 495	Updated hydraulic motor section from H6 to H12.

2025 10 30

This publication supersedes and replaces any previous edition and revision. We reserve the right to implement modifications without notice. This catalogue cannot be reproduced, even partially, without prior consent.

Bonfiglioli

We have a relentless commitment to excellence, innovation & sustainability. Our team creates, distributes and services world-class power transmission & drive solutions to keep the world in motion.

HEADQUARTERS

Bonfiglioli S.p.A
Via Cav. Clementino Bonfiglioli, 1
40012 Calderara di Reno - Bologna (Italy)
Tel. +39 051 6473111